Ethical Imprints in LLMs:
From Corpus Ethics to ICL, SFT, and Their Interaction
on Deception Dilemmas

Abstract

Large language models make consistent moral judgments, but where these tendencies come from is not well understood. We ask whether the moral distribution of web text corresponds to model moral behavior, and test deception dilemmas across Chinese and English in a four-layer empirical study. We use DeepSeek-R1 for ICL probing, Llama-3.1-8B and Qwen2.5-7B for fine-tuning, and GPT-4o for cross-model replication. In both languages, roughly 60% of web text favors utilitarian reasoning (59.8% vs. 62.3%), inconsistent with a purely sociolinguistic explanation. In-context learning shifts model decisions sharply in low-resistance scenarios (Hostage Crisis, $V = 0.411$, $p = 0.001$). In a high-resistance scenario (Organ Allocation), Chinese shows near-zero ICL effects on DeepSeek-R1, while English shows significant effects. This damping disappears under GPT-4o, suggesting a model- and language-specific origin. Three findings stand out for multilingual alignment. First, fine-tuning on deontological data reverses direction in English (Llama-EN Deon $P(A)$ rises from $\sim$0% to 88%), showing that SFT value transfer is not language-neutral. Second, RLHF can override corpus-level tendencies entirely: Llama-3.1-8B English base $P(A)$ is near zero despite 62.3% utilitarian text in the web corpus. Third, moral damping in Organ Allocation is model-specific (DeepSeek-R1 only, $V=0.067$), not scenario-inherent (GPT-4o: $V=0.648$). These results show that corpus moral distributions correspond to model behavior in many conditions, but language, post-training, and model architecture each introduce points where this correspondence breaks.

1 Introduction

Large language models show consistent moral preferences across repeated runs, yet these preferences shift under different prompts. Prior work has mostly addressed this through architecture design, alignment techniques (RLHF, DPO), or prompting strategies such as few-shot learning (Brown et al., 2020) and chain-of-thought (Askell et al., 2021; Wei et al., 2023). Less work has asked what drives these preferences.

We ask whether a model's moral tendencies track its sociolinguistic context, or the statistical makeup of its pretraining data. We examine whether the distribution of ethical frameworks in web text of a given language corresponds to model moral preferences, beyond what language or culture alone would predict. Our experiments test for consistent distributional alignment across languages, models, and intervention types. We do not claim that specific corpora caused specific model behaviors. Three patterns stand out. Utilitarian shares in Chinese and English pretraining data are both near 60%, so language alone is unlikely to explain the corpus gap. Equal-sized English deontological SFT does not suppress utilitarian tendencies but reverses them, suggesting that deontological SFT outcomes depend on pretraining language. Neutral chain-of-thought suppresses utilitarian responses in Chinese (Neutral below Control in all 6 cells) but promotes them in English (5 of 6 cells show Neutral at or above Control), an asymmetry aligned with each corpus's pretraining language rather than with directional examples.

To test this systematically, we focus on deception, where utilitarianism and deontology disagree most sharply. We build a four-layer verification framework across Chinese and English, using Llama-3.1-8B and Qwen2.5-7B. Each layer tests a different aspect. The corpus layer measures utilitarian and deontological proportions in large-scale web corpora (CCI 4.0 and FineWeb) as representative samples of Chinese and English web text, not as replicas of any model's training set. The mechanism layer uses ICL to test whether models reflect the moral framework in their input. The model layer uses SFT to test whether these distributions

can be encoded into parameters. The interaction layer examines how parametric encoding and context interact. The English experiments serve as a cross-lingual check.

Contributions (1) We conduct a systematic four-layer empirical investigation (corpus, mechanism, model, interaction) replicated across Chinese/English and Llama/Qwen, linking language-level web-text moral distributions to model preferences.

(2) Cross-lingual corpus annotation shows utilitarian proportions near 60% in both languages, inconsistent with a language-only account.

(3) Deontological SFT produces a language-dependent asymmetry: it drives $P(A)$ to near zero in Chinese but *reverses direction* in English (Llama-EN Deon rises from $\sim$0% to 88%). Value transfer through SFT is not language-neutral.

(4) RLHF post-training can override corpus-level moral tendencies: Llama-3.1-8B English base $P(A)$ is near zero despite 62.3% utilitarian text in the English web corpus. Alignment interventions reshape corpus distributions, not merely amplify them.

(5) Moral damping in Organ Allocation is model-specific and language-specific, not universal: Chinese DeepSeek-R1 shows near-zero ICL effects (V=0.067), while GPT-4o shows strong effects in the same scenario (V=0.648). Resistance to context intervention depends on the model–language combination, not on the scenario alone.

2 Related Work

2.1 Measuring Moral Preferences in LLMs

Human moral preferences have long been studied through frameworks such as Moral Foundations Theory (Haidt and Graham, 2007; Graham et al., 2011). Recent work probes whether LLMs show similar preferences. Several benchmarks, including the ETHICS dataset (Hendrycks et al., 2021), Delphi (Jiang et al., 2021), the Moral Machine (Awad et al., 2018), and the Greatest Good Benchmark (Marraffini et al., 2024), find that models lean utilitarian in low-ambiguity cases (Scherrer et al., 2023). The strength of this lean varies across model families (Zheng et al., 2023) and is sensitive to context (Barabadi et al., 2026). Cross-lingual variation adds another dimension: Liu et al. (2024) reported that English- and Chinese-dominant models diverge along individualist–collectivist lines.

Schramowski et al. (2022) recovered a moral direction from pretrained embeddings without any explicit moral training, suggesting these tendencies come from the data itself. However, none of these studies trace preferences back to corpus-level distributions, which we address here.

2.2 Cross-Lingual Moral Reasoning

Jin et al. (2025) found significant cross-lingual differences in LLM moral judgments across more than 100 languages. Our work uses a controlled design to investigate what drives these differences.

2.3 ICL and SFT Effects on Values

Both ICL and SFT can redirect model behavior, but how the two interact is not well studied. On the ICL side, Wei et al. (2023) showed that large models rely more on pretrained knowledge than on example labels. Lin et al. (2024) showed that even a few well-formatted examples can activate latent aligned behaviors. Yet Chochlakis et al. (2024) found that chain-of-thought prompting (Wei et al., 2022) fails to shift subjective value judgments, pointing to hard limits on context-driven steering. On the SFT side, small high-quality datasets can change outputs (Solaiman and Dennison, 2021; Zhou et al., 2023), but this also creates risks: Qi et al. (2024) showed that just 10 adversarial examples suffice to break RLHF safety alignment. RLHF (Christiano et al., 2017; Ouyang et al., 2022) and Constitutional AI (Bai et al., 2022) set the broader training-time context. Yuan et al. (2026) found that post-RLHF reasoning chains improve honesty. This raises the question of whether reasoning-only prompts interact differently with moral preferences across languages, which we test in §5.2.

2.4 Pretraining Data Distribution and Moral Preferences

Feng et al. (2023) showed that political bias in pretraining data corresponds to measurable downstream effects in hate-speech detection and misinformation identification. This provides a methodological precedent for our multi-layer framework. Both Feng et al. (2023) and Schramowski et al. (2022) focused on political or safety dimensions and did not test how pretraining bias interacts with ICL or SFT. We extend this approach to moral-framework distributions with a four-layer design.

3 Methods

3.1 Scenario Selection: Why Deception?

Deception is a clear test case for comparing utilitarianism and deontology. Deontological theory treats lying as unconditionally wrong (Kant, 1785), while utilitarianism permits or requires it when the outcome justifies it (Bentham, 1789; Mill, 1863). Deception also appears frequently in varied pretraining text contexts. We standardize it into three scenarios with different levels of institutional resistance: Friend Referral (low), Hostage Crisis (medium-low), and Organ Allocation (high). These are inspired by the trolley problem tradition (Foot, 1967; Thomson, 1985) and represent low, medium, and high institutional constraint.

3.2 Corpus Collection and Annotation

Chinese text was drawn from CCI 4.0 (Common Crawl Chinese).[1] English text was drawn from FineWeb (Penedo et al., 2024),[2] specifically the base version (unfiltered general web text, not FineWeb-Edu), to avoid overestimating deontological proportions and to maintain comparability with CCI 4.0. We chose these two corpora because they are among the largest publicly available web-crawl datasets in their respective languages. CCI 4.0 overlaps substantially with the Chinese web text used to train Chinese-centric models; FineWeb is derived from Common Crawl, which forms the backbone of most English pretraining pipelines (Brown et al., 2020; Touvron et al., 2023). Neither corpus is the verified training set of any model tested here; we return to this limitation in §8.

After keyword filtering, 2,000 candidates per language were sampled. Annotation used DeepSeek-R1 (Volcengine ARK API) with semantically equivalent bilingual prompts verified by back-translation. Quality control included three rounds of independent annotation, confidence-threshold filtering (Relevance_Decision_Certainty ≥ 0.8, Framework_Mapping_Certainty ≥ 0.7), Fleiss' kappa computation, and removal of samples where all three rounds disagreed. Final counts: 321 Chinese (192 utilitarian, 129 deontological) and 199 English (124 utilitarian, 75 deontological). Fleiss' kappa: is_relevant κ=0.76 (substantial); moral_framework κ=0.52 (moderate). The lower framework kappa

---

[1]CCI 4.0: `https://huggingface.co/datasets/BAAI/CCI4-Data`

[2]FineWeb: `https://huggingface.co/datasets/HuggingFaceFW/fineweb`

reflects real ambiguity at the boundary between frameworks (Artstein and Poesio, 2008).

DeepSeek-R1 plays two roles: corpus annotator and ICL test model. Three points argue against circular reasoning. First, R1 matched human annotation most closely among three candidate models. Second, model-layer SFT used Llama-3.1-8B and Qwen2.5-7B, which are architecturally independent of R1, and both showed theoretically expected shifts on R1-labeled data. Third, the mechanism layer measures directional changes in $P(A)$ between Deon and Util contexts. Directional effects are much less sensitive to systematic annotator bias than absolute label accuracy.

3.3 Four-Layer Experimental Design

Corpus layer. We tabulate annotated utilitarian and deontological proportions and run a chi-square test comparing Chinese and English.

Mechanism layer. Using DeepSeek-R1, we run four-context ICL experiments (Deon, Util, Neutral, Control) on three standardized scenarios, 30 samples each, at T=0.2 and T=0.8, with $P(A)$ as the metric. Deon, Util, and Neutral contexts each provide few-shot chain-of-thought examples that differ only in moral direction. Neutral provides reasoning without a moral stance, to separate the reasoning process from moral content. Control has no examples. GPT-4o replicates the same protocol independently (§5.3).

Model layer. We build SFT training sets (Chinese: 192 utilitarian, 129 deontological; English: 124 utilitarian, 75 deontological) and use LoRA (Hu et al., 2022) to fine-tune Llama-3.1-8B (Meta AI, 2024) and Qwen2.5-7B (r=16, α=16, lr=2$\times 10^{-4}$, 5 epochs). Conditions: Base, Util_ZH, Deon_ZH, Util_EN, Deon_EN.

Interaction layer. We run four-context ICL experiments on the SFT-tuned models and analyze how parametric encoding and context interact.

4 Corpus Layer: Distributional Baseline

Chinese and English moral framework distributions are nearly identical (Table 1). A chi-square test shows no significant difference. The 2.5 pp utilitarian gap is too small to support a language-only story or a single-dataset artifact.

Figure 1 outlines the four-layer framework used in the mechanism, model, and interaction sections below.

Figure 1: Four-layer verification framework. Each layer tests a different aspect of the correspondence between corpus-level ethical distributions and model moral behavior: Corpus Layer (distributional baseline), Mechanism Layer (ICL context sensitivity), Model Layer (SFT parametric encoding), Interaction Layer (SFT x ICL dynamics).

5 Mechanism Layer: Context Sensitivity

5.1 Scene-Dependent Moral Damping

ICL effects on moral decisions depend strongly on the scenario, and this pattern holds across both languages. Hostage Crisis shows the strongest context modulation. In Chinese, Organ Allocation shows near-zero response to any intervention across all temperatures on DeepSeek-R1 (V =0.067, p =0.604 at T =0.2; V =0.070, p =0.588 at T =0.8), a pattern we call moral damping (near-zero ICL effect size). In English, however, Organ Allocation shows a significant ICL effect only at T =0.2 (V =0.339, p =0.009), while T =0.8 does not reach significance (V =0.118, p =0.360), indicating that moral damping in this scenario is partially language-specific on DeepSeek-R1. Under GPT-4o, damping disappears entirely in both languages (§5.3).

Tables 2 and 3 report selected $P(A)$ and Cramér's V; Figure 2 visualises effect sizes across all scenario–language–temperature cells.

	Total	Valid	Util	Deon
ZH (CCI)	2000	321	192 (59.8%)	129 (40.2%)
EN (FineWeb)	2000	199	124 (62.3%)	75 (37.7%)
χ^2=0.322, p=0.571			V=0.024 (n.s.)	

Table 1: Annotation statistics. Utilitarian gap 2.5 pp; χ^2=0.322, p=0.571, V=0.024 (n.s.).

Scenario	Lang	T	Deon	Util	V (p)
Hostage	ZH	0.2	30.0%	60.0%	0.268 (0.038) *
Hostage	ZH	0.8	16.7%	60.0%	0.411 (0.001) **
Friend	ZH	0.2	26.7%	56.7%	0.270 (0.036) *
Organ	ZH	0.2	40.0%	50.0%	0.067 (0.604) ×
Friend	EN	0.2	30.0%	90.0%	0.578 (<0.001) ★
Organ	EN	0.2	56.7%	90.0%	0.339 (0.009) **
Organ	EN	0.8	70.0%	83.3%	0.118 (0.360) ×

Table 2: Selected ICL results ($P(A)$ = proportion of utilitarian responses). ★ = strong effect (V >0.4, p<0.001); ** p<0.01; * p<0.05; × = not significant.

Scenario	T	ZH D	ZH U	ZH V	EN D	EN U	EN V
Friend	0.2	26.7	56.7	.270*	30.0	90.0	.578★
Friend	0.8	23.3	50.0	.242	60.0	80.0	.182
Hostage	0.2	30.0	60.0	.268*	53.3	80.0	.247
Hostage	0.8	16.7	60.0	.411**	50.0	80.0	.280*
Organ	0.2	40.0	50.0	.067	56.7	90.0	.339**
Organ	0.8	30.0	40.0	.070	70.0	83.3	.118

Table 3: Cramér's V across Chinese and English ICL (Deon vs. Util). ★ p<0.001; ** p<0.01; * p<0.05; unmarked = n.s. All $P(A)$ in %.

Figure 2: ICL moral reflection effect heatmap (Cramér's V, Deon ICL vs. Util ICL). Each cell = effect size of the four-context ICL on $P(A)$; darker = stronger intervention. ★ p<0.001; ** p<0.01; * p<0.05; n.s. = not significant.

5.2 Language Boundary Condition of Neutral CoT

Neutral chain-of-thought reasoning has opposite effects in DeepSeek-R1 depending on the language. In Chinese, neutral reasoning lowers $P(A)$ below Control in all conditions, suggesting the model's analytical process draws on deontological tendencies. In English, the direction reverses: $P(A)$ rises above Control in most conditions. What matters is not whether reasoning occurs, but what it draws

Figure 3: Full Chinese/English ICL context intervention results (DeepSeek-R1, 4 contexts × 3 scenarios × 2 temperatures). Left three columns: Chinese (ZH); right three: English (EN). Top row: T=0.2; bottom: T=0.8.

Figure 3(Supplement): GPT-4o ICL moral context experiments (Chinese/English, n=30/cell, 4 contexts x 3 scenarios x 2 temperatures). All scenarios significant (V=0.431 to 0.978); Organ Allocation damping absent in both languages, confirming that damping is specific to Chinese DeepSeek-R1, not a cross-model or cross-lingual universal.

on. The neutral context acts as a reasoning-only control. Its reversal across languages points to different moral tendencies in analytical pretraining text. GPT-4o did not show this pattern, so the effect may be specific to DeepSeek-R1's training.

Figure 3 reports full results across 24 cells (four contexts × three scenarios × two temperatures).

5.3 Cross-Model Validation: GPT-4o Replication

We ran the same four-context ICL experiment with GPT-4o (OpenAI, 2023) (checkpoint: gpt-4o-2024-11-20) on all three scenarios in both languages (n=30 per cell, T=0.2 and T=0.8). ICL polarity effects replicate fully: all six scenario groups are significant (V=0.431 to 0.978, all p<0.0001). Context sensitivity is not specific to one model or provider. Organ Allocation damping, however, is model-specific. GPT-4o shows no damping in either language (Chinese: V=0.648; English: V=0.788), unlike DeepSeek-R1's near-zero Chinese effect. Baseline tendencies also differ: GPT-4o Chinese Friend Referral Control $P(A)$ is 0%, compared to around 50% for DeepSeek-R1.

Figure 3(Supplement) summarizes the GPT-4o replication panel.

6 Model Layer: Parametric Encoding

6.1 Utilitarian SFT: Cross-Lingual and Cross-Architecture

Utilitarian SFT produces significant $P(A)$ gains in both languages and both architectures (Table 4, Figure 4). Differences in gain size are largely due to different starting points in the base models; both converge after fine-tuning. One exception: ZH-Qwen Organ Allocation at T=0.2 shows Util SFT

$P(A)$ slightly below Base, echoing the near-zero ICL effect seen in this scenario.

6.2 Deontological SFT: Language-Specific Asymmetry

Deontological SFT diverges sharply by language. Chinese runs reach near-zero $P(A)$; English runs reverse: Deon SFT raises $P(A)$ instead of lowering it (Table 4). This reversal holds across temperatures.

An equal-sample control (zh_deon_75: 75 Chinese deontological samples) also achieves $P(A)$ at or below 10%, ruling out sample size as the explanation (Table 5, Figure 5). We do not have a confirmed explanation for this reversal. Three post-hoc hypotheses fit the data but remain untested. First, English RLHF may suppress absolute-rule refusals, causing a rebound (Ouyang et al., 2022; Bai et al., 2022). Second, with 62.3% utilitarian pretraining data, gradient updates toward deontology may drift back toward the utilitarian majority (Zhou et al., 2023; Hu et al., 2022). Third, the SFT classification format may interfere with RLHF

Model	Base	Util SFT	Deon SFT
Llama-ZH	≈1.1%	88.9%↑	≈0%
Qwen-ZH	≈60%	≈79%↑	≈2%↓
Llama-EN	≈0%	≈92%↑	88%↑★
Qwen-EN	≈78%	≈99%↑	84%↑★
zh_deon_75	≈1.1%	–	≤10%

Table 4: SFT results ($P(A)$, @T=0.2, 3-scenario mean). English deontological SFT reversal: Llama-EN Deon rises from ∼0% to 88%; Qwen-EN similarly reverses. ★ marks direction reversal.

instruction-following pathways (Askell et al., 2021; Lin et al., 2024). Distinguishing these requires activation-level analysis, which we leave for future work.

7 Interaction Layer: Mechanistic Boundaries

7.1 Resolution Suppression

SFT has two separable effects. First, the gap in $P(A)$ between Deon and Util ICL contexts narrows (we call this resolution suppression). Second, $P(A)$ shifts toward the extreme matching the training framework (level anchoring). ZH-Qwen-Deon achieves both. EN-Qwen-Deon partially achieves the first but reverses the second (Table 6). Parametric encoding and behavioral locking are distinct mechanisms.

Figure 4: SFT parametric moral encoding results. $P(A)$ = Control-group utilitarian response rate (30 samples/scenario). Utilitarian SFT effective cross-linguistically and cross-architecturally; deontological SFT language-specific. Near-zero anchoring in Chinese, full directional reversal in English.

	Llama			Qwen		
Scenario T	ZH-129	ZH-75	EN-75	ZH-129	ZH-75	EN-75
Friend 0.2	0.0	0.0	86.7	0.0	10.0	80.0
Friend 0.8	0.0	3.3	90.0	6.7	0.0	66.7
Hostage 0.2	0.0	0.0	86.7	6.7	6.7	83.3
Hostage 0.8	3.3	0.0	100.0	3.3	6.7	76.7
Organ 0.2	0.0	3.3	90.0	0.0	10.0	90.0
Organ 0.8	0.0	3.3	83.3	10.0	0.0	73.3

Table 5: Equal-sample deontological SFT control (75 samples). Chinese Deon-75 achieves near-zero anchoring; English Deon-75 fully reverses. All values $P(A)$ in %.

Figure 5: Equal-sample Deon SFT control (75 samples, Control-group $P(A)$). Grey = Base; green = ZH Deon-75; purple = EN Deon-75. Chinese achieves near-zero anchoring; English fails to suppress utilitarian tendencies and reverses.

Model	Scenario	Base gap	Post-SFT gap
Qwen-ZH Util	Hostage	+90pp★	+23.3pp *
Qwen-ZH Util	Organ	+86.7pp★	+13.3pp n.s.
Llama-EN Util	Hostage	+63.3pp★	−6.7pp n.s.
Qwen-EN Util	Friend	+53.3pp★	0pp (ceiling)

Table 6: Resolution suppression. Deon vs. Util $P(A)$ gap (Base vs. SFT). All SFT gaps narrowed (*$p<0.05$); full data in Appendix D.

After SFT, the Deon/Util $P(A)$ gap narrows in most scenarios, but sensitivity to the four ICL contexts is preserved. Under Util SFT, the two architectures respond differently to the Neutral context. ZH-Qwen Neutral CoT shifts from suppressing utilitarian tendencies to amplifying them, suggesting deep internalization. ZH-Llama's high $P(A)$ drops under neutral reasoning, suggesting shallow internalization. Separating language mismatch from other factors requires further work.

Table 6 quantifies resolution suppression (Deon vs. Util $P(A)$ gap before and after SFT).

7.2 Defensive Contraction

When a Util SFT model receives Util ICL examples, $P(A)$ sometimes falls below the no-context Control baseline. We refer to this pattern as defensive contraction. The effect is strongest in ZH-Llama. At $T=0.8$, the Util SFT plus Util ICL condition falls below Control by 63.3 percentage points in Friend Referral, 40.0 pp in Hostage Crisis, and 50.0 pp in Organ Allocation. At $T=0.2$, Friend Referral and Hostage Crisis show contractions of 10.0 to 26.7 pp. ZH-Qwen shows the effect in Friend Re-

ferral (T=0.2: -23.3 pp; T=0.8: -13.3 pp). EN-Llama shows a mild version (-6.7 to 13.3 pp). EN-Qwen shows none.

This pattern is consistent with several recent findings. Redundant few-shot examples can degrade performance rather than help (Tang et al., 2025). Tan et al. (2024) found that 3–50% of samples are "anti-steerable": same-direction intervention produces a reversal instead of reinforcement. Braun et al. (2025) showed that excessive intervention strength degrades model capabilities by an amount equivalent to halving pretraining compute. Mishra et al. (2025) showed that SFT and ICL produce distinct internal activation patterns despite similar surface behavior, so co-directional stacking may cause interference rather than reinforcement. Our results fit this picture: parametric encoding and context prompting may operate at different depths, and aligning them in the same direction does not guarantee additive effects. The effect is stronger at T=0.8 than T=0.2 and stronger in Llama than Qwen. Distinguishing sampling dynamics from representational interference requires activation-level analysis beyond this study. The key point is that ICL and SFT effects do not simply add together. In some conditions, co-directional stacking produces the opposite of the expected outcome.

Figures 6a–6c plot SFT×ICL interaction patterns for all three scenarios.

8 Discussion and Conclusion

The moral distribution of web text corresponds to model behavior in many conditions. The more important finding is where this correspondence breaks. Three cases stand out.

Deontological SFT produces opposite results across languages. Chinese $P(A)$ falls near zero while English Llama $P(A)$ rises to 88 to 91 percent. This is not a weaker effect but a full directional flip. The same fine-tuning data encodes opposite moral tendencies depending on the pretraining language. Alignment pipelines that assume SFT transfers uniformly across languages risk producing the opposite of the intended effect (Gabriel, 2020).

Neutral chain-of-thought reasoning suppresses utilitarian tendencies in Chinese DeepSeek-R1 but promotes them in English. The analytical reasoning process appears to draw on implicit moral tendencies from the pretraining language, consistent with Jin et al. (2025). GPT-4o does not show this pattern, so cross-model generality remains open.

Figure 6a: SFT x ICL interaction, Friend Referral. Rows: language (ZH/EN) x temperature (T=0.2/T=0.8); columns: Llama-3.1-8B and Qwen2.5-7B. Bar colours: Base (grey), Util SFT (blue), Deon SFT (red). Down arrow marks defensive contraction (Util SFT + Util ICL $P(A)$ below Control).

Organ Allocation damping in Chinese DeepSeek-R1 does not hold in GPT-4o in either language. Even on DeepSeek-R1, the English Organ Allocation condition shows significant ICL effects. Damping is tied to a specific model-language pair, not a general rule.

At the interaction layer, SFT narrows the gap between Deon and Util ICL effects while preserving overall context sensitivity. Parametric moral preferences and context prompting appear to operate as separate mechanisms at different depths. In ZH-Llama, adding Util ICL to a Util SFT model drops $P(A)$ by up to 63.3 percentage points. Recent work offers a plausible account: SFT and ICL produce distinct internal activation patterns despite similar surface behavior (Mishra et al., 2025), so stacking them in the same direction can cause representational interference rather than reinforcement. This is consistent with findings that redundant same-direction intervention degrades rather than improves output (Tan et al., 2024; Braun et al., 2025). Confirming the exact mechanism in our setting requires activation-level analysis, which we leave for future work.

RLHF plays a clear role. Llama-3.1-8B English base $P(A)$ is near zero despite 62.3% utilitarian text in English web data. Post-training alignment

Figure 6b: SFT x ICL interaction, Hostage Crisis. Axes and legend as in Figure 6a.

Figure 6c: SFT x ICL interaction, Organ Allocation. Axes and legend as in Figure 6a.

can override corpus-level moral distributions entirely. Corpus distributions set a starting point, but downstream interventions can reshape or reverse them. No single factor (language, corpus distribution, or model family) accounts for the full pattern. The model's moral behavior reflects multiple interacting stages: pretraining corpus, RLHF post-training, and deployment-time prompting.

Limitations

CCI 4.0 and FineWeb characterize language-level web-text distributions, not verified model training sets. Isolating the causal path from training data to model behavior would require retraining with controlled data compositions.

Our framework is tested on deception as a deliberate case study (§3.1). Extending the analysis to other moral domains (e.g., fairness, harm) is a natural next step. Each ICL cell has $n=30$, limiting reliable detection to medium-to-large effects ($V \geq 0.3$ at $\alpha=0.05$). Weak but real context modulation may go undetected. Future work should increase sample sizes. GPT-4o replication supports cross-model polarity effects and model-specific Organ Allocation damping.

Ethics Statement

All test scenarios are fictional and involve no real individuals or private data. Models were accessed via public APIs or open-source channels. Pretraining corpora (CCI 4.0, FineWeb) are public datasets. Annotation was done with an automated LLM and required no human annotators or IRB review.

References

Ron Artstein and Massimo Poesio. 2008. Inter-coder agreement for computational linguistics. *Computational Linguistics*, 34(4):555–596. https://aclanthology.org/J08-4004.

Amanda Askell, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones, Nicholas Joseph, Ben Mann, Nova DasSarma, Nelson Elhage, Zac Hatfield-Dodds, Danny Hernandez, Jackson Kernion, Kamal Ndousse, Catherine Olsson, Dario Amodei, Tom Brown, Jack Clark, and 3 others. 2021. A general language assistant as a laboratory for alignment. *arXiv preprint arXiv:2112.00861*. https://arxiv.org/abs/2112.00861.

Edmond Awad, Sohan Dsouza, Richard Kim, Jonathan Schulz, Joseph Henrich, Azim Shariff, Jean-François Bonnefon, and Iyad Rahwan. 2018. The moral machine experiment. *Nature*, 563:59–64. https://doi.org/10.1038/s41586-018-0637-6.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, Carol Chen, Catherine Olsson, Christopher Olah, Danny Hernandez, Dawn Drain, Deep Ganguli, Dustin Li, Eli Tran-Johnson, Ethan Perez, and 32 others. 2022. Constitutional AI: Harmlessness from AI feedback. *arXiv preprint arXiv:2212.08073*. https://arxiv.org/abs/2212.08073.

Elyas Barabadi, Zahra Fotuhabadi, Amanollah Arghavan, and James R. Booth. 2026. Comparing AI and human moral reasoning: context-sensitive patterns beyond utilitarian bias. *Frontiers in Artificial Intelligence*. https://doi.org/10.3389/frai.2025.1710410.

Jeremy Bentham. 1789. *An Introduction to the Principles of Morals and Legislation*. T. Payne and Son. https://www.utilitarianism.com/jeremy-bentham/index.html.

Joschka Braun, Carsten Eickhoff, David Krueger, Seyed Ali Bahrainian, and Dmitrii Krasheninnikov. 2025. Understanding (Un)Reliability of steering vectors in language models. *arXiv preprint arXiv:2505.22637*. https://arxiv.org/abs/2505.22637.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, and 12 others. 2020. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. https://papers.nips.cc/paper/2020/hash/1457c0d6bfcb4967418bfb8ac142f64a-Abstract.html.

Georgios Chochlakis, Niyathi Maiya Pandiyan, Kristina Lerman, and Shrikanth Narayanan. 2024. Larger language models don't care how you think: Why chain-of-thought prompting fails in subjective tasks. *arXiv preprint arXiv:2409.06173*. https://arxiv.org/abs/2409.06173.

Paul Christiano, Jan Leike, Tom B Brown, Miljan Martic, Shane Legg, and Dario Amodei. 2017. Deep reinforcement learning from human preferences. In *Advances in Neural Information Processing Systems*, volume 30. https://papers.nips.cc/paper/7017-deep-reinforcement-learning-from-human-preferences.

Shangbin Feng, Chan Young Park, Yuhan Liu, and Yulia Tsvetkov. 2023. From pretraining data to language models to downstream tasks: Tracking the trails of political biases leading to unfair NLP models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics*. Best Paper Award. https://aclanthology.org/2023.acl-long.656/.

Philippa Foot. 1967. The problem of abortion and the doctrine of double effect. *Oxford Review*, 5:5–15. https://philpapers.org/rec/FOOTPO-2.

Iason Gabriel. 2020. Artificial intelligence, values, and alignment. *Minds and Machines*, 30:411–437. https://doi.org/10.1007/s11023-020-09539-2.

Jesse Graham, Brian A Nosek, Jonathan Haidt, Ravi Iyer, Spassena Koleva, and Peter H Ditto. 2011. Mapping the moral domain. *Journal of Personality and Social Psychology*, 101(2):366–385. https://doi.org/10.1037/a0021847.

Jonathan Haidt and Jesse Graham. 2007. When morality opposes justice: Conservatives have moral intuitions that liberals may not recognize. *Social Justice Research*, 20(1):98–116. https://doi.org/10.1007/s11211-007-0034-z.

Dan Hendrycks, Collin Burns, Steven Basart, Andrew Critch, Jerry Li, Dawn Song, and Jacob Steinhardt. 2021. Aligning AI with shared human values. In *International Conference on Learning Representations*. https://openreview.net/forum?id=dNy_RKzJacY.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*. https://openreview.net/forum?id=nZeVKeeFYf9.

Liwei Jiang, Jena D Hwang, Chandra Bhagavatula, Ronan Le Bras, Maxwell Forbes, Jon Borchardt, Jenny Liang, Oren Etzioni, Hannaneh Hajishirzi, and Yejin Choi. 2021. Can machines learn morality? the Delphi experiment. *arXiv preprint arXiv:2110.07574*. https://arxiv.org/abs/2110.07574.

Zhijing Jin, Max Kleiman-Weiner, Giorgio Georgiou, Katharina Reinecke, Rada Mihalcea, Joshua B. Tenenbaum, and Bernhard Schölkopf. 2025. Language model alignment in multilingual trolley problems. In *International Conference on Learning Representations*. https://openreview.net/forum?id=VEqPDZIDAh.

Immanuel Kant. 1785. *Groundwork of the Metaphysics of Morals*. Harper & Row. https://www.earlymoderntexts.com/assets/pdfs/kant1785.pdf.

Bill Yuchen Lin, Abhilasha Ravichander, Ximing Lu, Nouha Dziri, Melanie Sclar, Khyathi Chandu, Chandra Bhagavatula, and Yejin Choi. 2024. The unlocking spell on base LLMs. In *International Conference on Learning Representations*. https://openreview.net/forum?id=wxJ0eXwwda.

Xuelin Liu, Yanfei Zhu, Shucheng Zhu, Pengyuan Liu, Ying Liu, and Dong Yu. 2024. Evaluating moral beliefs across LLMs. In *Findings of the 2024 Conference on Empirical Methods in Natural Language Processing*. https://aclanthology.org/2024.findings-emnlp.272/.

Giovanni Franco Gabriel Marraffini, Andrés Cotton, Noe Fabian Hsueh, Axel Fridman, Juan Wisznia, and Luciano Del Corro. 2024. The greatest good benchmark: Measuring LLMs' alignment with utilitarian moral dilemmas. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language*

Processing, pages 21950–21959. https://aclanthology.org/2024.emnlp-main.1224/.

Meta AI. 2024. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*. https://arxiv.org/abs/2407.21783.

John Stuart Mill. 1863. *Utilitarianism*. Parker, Son, and Bourn. https://www.gutenberg.org/ebooks/11224.

Aayush Mishra, Daniel Khashabi, and Anqi Liu. 2025. IA2: Alignment with ICL activations improves supervised fine-tuning. *arXiv preprint arXiv:2509.22621*. https://arxiv.org/abs/2509.22621.

OpenAI. 2023. GPT-4 technical report. *arXiv preprint arXiv:2303.08774*. https://arxiv.org/abs/2303.08774.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744. https://proceedings.neurips.cc/paper_files/paper/2022/hash/b1efde53be364a73914f58805a001731-Abstract-Conference.html.

Guilherme Penedo, Hynek Kydlíček, Loubna Ben Allal, Anton Lozhkov, Margaret Mitchell, Colin Raffel, Leandro Von Werra, and Thomas Wolf. 2024. The FineWeb datasets: Decanting the web for the finest text data at scale. In *Advances in Neural Information Processing Systems*, volume 37. https://proceedings.neurips.cc/paper_files/paper/2024/hash/370df50ccfdf8bde18f8f9c2d9151bda-Abstract-Datasets_and_Benchmarks_Track.html.

Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. 2024. Fine-tuning aligned language models compromises safety, even when users do not intend to. In *International Conference on Learning Representations*. Oral. https://openreview.net/forum?id=hTEGyKf0dZ.

Nino Scherrer, Claudia Shi, Amir Feder, and David M. Blei. 2023. Evaluating the moral beliefs encoded in LLMs. In *Advances in Neural Information Processing Systems*. https://openreview.net/forum?id=O06z2G18me.

Patrick Schramowski, Cigdem Turan, Nico Andersen, Constantin A. Rothkopf, and Kristian Kersting. 2022. Large pre-trained language models contain human-like biases of what is right and wrong to do. *Nature Machine Intelligence*, 4:258–268. https://doi.org/10.1038/s42256-022-00458-8.

Irene Solaiman and Christy Dennison. 2021. PALMS: Process for adapting language models to society. In *Advances in Neural Information Processing Systems*. https://proceedings.neurips.cc/paper/2021/hash/2e855f9489df0712b4bd8ea9e2848c5a-Abstract.html.

Daniel Tan, David Chanin, Aengus Lynch, Brooks Paige, Dimitrios Kanoulas, Adrià Garriga-Alonso, and Robert Kirk. 2024. Analyzing the generalization and reliability of steering vectors. In *Advances in Neural Information Processing Systems*, volume 37. https://proceedings.neurips.cc/paper_files/paper/2024/hash/fb3ad59a84799bfb8d700e56d19c231b-Abstract-Conference.html.

Yongjian Tang, Doruk Tuncel, Christian Koerner, and Thomas Runkler. 2025. The few-shot dilemma: Overprompting large language models. *arXiv preprint arXiv:2509.13196*. https://arxiv.org/abs/2509.13196.

Judith Jarvis Thomson. 1985. The trolley problem. *Yale Law Journal*, 94(6):1395–1415. https://doi.org/10.2307/796133.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023. LLaMA: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*. https://arxiv.org/abs/2302.13971.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35. https://proceedings.neurips.cc/paper/2022/hash/9d5609613524ecf4f15af0f7b31abca4-Abstract-Conference.html.

Jerry Wei, Jason Wei, Yi Tay, Dustin Tran, Albert Webson, Yifeng Lu, Xinyun Chen, Hanxiao Liu, Da Huang, Denny Zhou, and Tengyu Ma. 2023. Larger language models do in-context learning differently. *arXiv preprint arXiv:2303.03846*. https://doi.org/10.48550/arXiv.2303.03846.

Ann Yuan, Asma Ghandeharioun, Carter Blum, Alicia Machado, Jessica Hoffmann, Daphne Ippolito, Martin Wattenberg, Lucas Dixon, and Katja Filippova. 2026. Think before you lie: How reasoning improves honesty. *arXiv preprint arXiv:2603.09957*. https://doi.org/10.48550/arXiv.2603.09957.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P Xing, Hao Zhang, Joseph E Gonzalez, and Ion Stoica. 2023. Judging

LLM-as-a-judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems*, volume 36. https://papers.nips.cc/paper_files/paper/2023/hash/91f18a1287b398d378ef22505bf41832-Abstract-Datasets_and_Benchmarks.html.

Chunting Zhou, Pengfei Liu, Puxin Xu, Srinivasan Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu, Lili Yu, Susan Zhang, Gargi Ghosh, Mike Lewis, Luke Zettlemoyer, and Omer Levy. 2023. LIMA: Less is more for alignment. In *Advances in Neural Information Processing Systems*. https://proceedings.neurips.cc/paper_files/paper/2023/hash/ac662d74829e4407ce1d126477f4a03a-Abstract-Conference.html.

A Annotation Quality Validation

A.1 Three-Round Fleiss' κ

Model	n (post-confidence filter)	is_relevant (κ)	moral_framework (κ)
DeepSeek	28	0.761	0.518
GPT-4o	27	0.801	0.847
Claude	26	0.887	0.846

Table A1: Fleiss' κ (Three-Round Annotation).

A.2 Human vs. LLM Annotation Cohen's κ

Model	n (shared sample)	is_relevant (κ)	moral_framework (κ)
DeepSeek	26	0.785	0.735
Claude	25	0.615	0.405
GPT-4o	27	0.443	0.172

Table A2: Human vs. LLM Annotation Cohen's κ.

B Full ICL Results

B.1 Chinese ICL Experiments (DeepSeek-R1)

Scenario	T	P(A) Deon	P(A) Util	P(A) Control	P(A) Neutral	Deon vs Util V	Deon vs Util p	D/U sig	Ctx V	Ctx p	Ctx sig
Friend Referral	0.2	26.67%	56.67%	46.67%	40.00%	0.2704	0.0362	*	0.2204	0.1201	n.s.
Friend Referral	0.8	23.33%	50.00%	60.00%	26.67%	0.2421	0.0608	n.s.	0.3155	0.0076	**
Hostage Crisis	0.2	30.00%	60.00%	60.00%	30.00%	0.268	0.038	*	0.3015	0.0122	*
Hostage Crisis	0.8	16.67%	60.00%	30.00%	26.67%	0.411	0.0014	**	0.3428	0.0028	**
Organ Allocation	0.2	40.00%	50.00%	53.33%	43.33%	0.067	0.604	n.s.	0.1056	0.7198	n.s.
Organ Allocation	0.8	30.00%	40.00%	53.33%	23.33%	0.070	0.588	n.s.	0.2346	0.0857	n.s.

Table B1: Full Chinese ICL Results (DeepSeek-R1).

B.2 English ICL Experiments (DeepSeek-R1)

Scenario	T	P(A) Deon	P(A) Util	P(A) Control	P(A) Neutral	Deon vs Util V	Deon vs Util p	D/U sig	Ctx V	Ctx p	Ctx sig
Friend Referral	0.2	30.00%	90.00%	80.00%	83.33%	0.5784	<0.001	★	0.5247	<0.001	★
Friend Referral	0.8	60.00%	80.00%	70.00%	70.00%	0.1818	0.1590	n.s.	0.1543	0.4142	n.s.
Hostage Crisis	0.2	53.33%	80.00%	66.67%	76.67%	0.2475	0.0552	n.s.	0.2247	0.1089	n.s.
Hostage Crisis	0.8	50.00%	80.00%	73.33%	63.33%	0.2795	0.0304	*	0.2398	0.0752	n.s.
Organ Allocation	0.2	56.67%	90.00%	53.33%	83.33%	0.3392	0.0086	**	0.3531	0.0018	**
Organ Allocation	0.8	70.00%	83.33%	83.33%	86.67%	0.1182	0.3598	n.s.	0.1626	0.3656	n.s.

Table B2: Full English ICL Results (DeepSeek-R1).

B.3 Chinese ICL Experiments (GPT-4o)

Scenario	T	P(A) Deon	P(A) Util	P(A) Control	P(A) Neutral	Deon vs Util V	Deon vs Util p	D/U sig	Ctx V	Ctx p	Ctx sig
Friend Referral	0.2	0.00%	23.33%	0.00%	0.00%	0.3115	0.0158	*	0.2489	<0.001	★
Friend Referral	0.8	0.00%	43.33%	0.00%	6.67%	0.4855	<0.001	★	0.3144	<0.001	★
Hostage Crisis	0.2	3.33%	100.00%	100.00%	100.00%	0.9339	<0.001	★	0.5645	<0.001	★
Hostage Crisis	0.8	26.67%	100.00%	93.33%	100.00%	0.7263	<0.001	★	0.4462	<0.001	★
Organ Allocation	0.2	6.67%	90.00%	26.67%	26.67%	0.8004	<0.001	★	0.3744	<0.001	★
Organ Allocation	0.8	33.33%	96.67%	63.33%	46.67%	0.6290	<0.001	★	0.2792	<0.001	★

Table B3: Full Chinese ICL Results (GPT-4o).

B.4 English ICL Experiments (GPT-4o)

Scenario	T	P(A) Deon	P(A) Util	P(A) Control	P(A) Neutral	Deon vs Util V	Deon vs Util p	D/U sig	Ctx V	Ctx p	Ctx sig
Friend Referral	0.2	0.00%	93.33%	3.33%	6.67%	0.9020	<0.001	★	0.5150	<0.001	★
Friend Referral	0.8	0.00%	93.33%	0.00%	0.00%	0.9020	<0.001	★	0.5517	<0.001	★
Hostage Crisis	0.2	0.00%	100.00%	90.00%	0.00%	0.9667	<0.001	★	0.5507	<0.001	★
Hostage Crisis	0.8	0.00%	100.00%	93.33%	0.00%	0.9667	<0.001	★	0.5591	<0.001	★
Organ Allocation	0.2	0.00%	100.00%	13.33%	50.00%	0.9667	<0.001	★	0.4552	<0.001	★
Organ Allocation	0.8	0.00%	100.00%	3.33%	36.67%	0.9667	<0.001	★	0.4863	<0.001	★

Table B4: Full English ICL Results (GPT-4o).

B.5 Cross-Lingual ICL Absolute Comparison (DeepSeek-R1)

English $P(A)$ exceeds Chinese in 23 of 24 cells. The largest gap is Neutral, Organ Allocation, T=0.8 (EN 86.7% vs. ZH 23.3%, Δ=63.4 pp). This systematic gap far exceeds the 2.5 pp corpus-layer utilitarian-proportion difference. It suggests that the absolute-value difference in Chinese/English ICL effects primarily reflects language-specific RLHF alignment in base models rather than differences in corpus-level moral distributions, which are near-identical across languages.

Scenario	T	Lang	P(A) Deon	P(A) Util	P(A) Control	P(A) Neutral	Deon vs Util V	Deon vs Util p	D/U sig	Ctx V	Ctx p	Ctx sig
Friend Referral	0.2	ZH	26.67%	56.67%	46.67%	40.00%	0.2704	0.0362	*	0.2204	0.1201	n.s.
Friend Referral	0.2	EN	30.00%	90.00%	80.00%	83.33%	0.5784	<0.001	★	0.5247	<0.001	★
Friend Referral	0.8	ZH	23.33%	50.00%	60.00%	26.67%	0.2421	0.0608	n.s.	0.3155	0.0076	**
Friend Referral	0.8	EN	60.00%	80.00%	70.00%	70.00%	0.1818	0.1590	n.s.	0.1543	0.4142	n.s.
Hostage Crisis	0.2	ZH	30.00%	60.00%	60.00%	30.00%	0.2680	0.0380	*	0.3015	0.0122	*
Hostage Crisis	0.2	EN	53.33%	80.00%	66.67%	76.67%	0.2475	0.0552	n.s.	0.2247	0.1089	n.s.
Hostage Crisis	0.8	ZH	16.67%	60.00%	30.00%	26.67%	0.4114	0.0014	**	0.3428	0.0028	**
Hostage Crisis	0.8	EN	50.00%	80.00%	73.33%	63.33%	0.2795	0.0304	*	0.2398	0.0752	n.s.
Organ Allocation	0.2	ZH	40.00%	50.00%	53.33%	43.33%	0.0670	0.6038	n.s.	0.1056	0.7198	n.s.
Organ Allocation	0.2	EN	56.67%	90.00%	53.33%	83.33%	0.3392	0.0086	**	0.3531	0.0018	**
Organ Allocation	0.8	ZH	30.00%	40.00%	53.33%	23.33%	0.0700	0.5883	n.s.	0.2346	0.0857	n.s.
Organ Allocation	0.8	EN	70.00%	83.33%	83.33%	86.67%	0.1182	0.3598	n.s.	0.1626	0.3656	n.s.

Table B5: Cross-lingual ICL absolute $P(A)$ comparison (DeepSeek-R1). EN exceeds ZH in 23 of 24 cells; the sole tie is Organ, Control, T=0.2 (both 53.3%). ★ p<0.001; ** p<0.01; * p<0.05.

C Full SFT Results

Model	T	Friend Referral	Hostage Crisis	Organ Allocation	Mean
Llama-Base	0.2	0.0%	0.0%	0.0%	0.0%
Llama-Base	0.8	0.0%	20.0%	30.0%	16.7%
Llama-Util	0.2	83.3%	93.3%	100.0%	92.2%
Llama-Util	0.8	96.7%	100.0%	96.7%	97.8%
Llama-Deon	0.2	86.7%	86.7%	90.0%	87.8%
Llama-Deon	0.8	90.0%	100.0%	83.3%	91.1%
Qwen-Base	0.2	73.3%	83.3%	80.0%	78.9%
Qwen-Base	0.8	83.3%	83.3%	90.0%	85.5%
Qwen-Util	0.2	100.0%	100.0%	96.7%	98.9%
Qwen-Util	0.8	100.0%	100.0%	100.0%	100.0%
Qwen-Deon	0.2	80.0%	83.3%	90.0%	84.4%
Qwen-Deon	0.8	66.7%	76.7%	73.3%	72.2%

Table C1: SFT Control-Group $P(A)$ Summary across T=0.2 and T=0.8.

D Full SFT+ICL Interaction Data

Column key: $P(A)$ deon/util/ctrl/neut = proportion choosing the utilitarian option under each ICL context. D/U V, D/U p = Cramér's V and p-value for the deontological vs. utilitarian context contrast. Ctx V, Ctx p = overall four-context effect size and p-value. Sig: ★ p<0.001, ** p<0.01, * p<0.05, N = n.s.

D.1 Chinese Llama-3.1-8B SFT+ICL

Scenario	Cond.	P(deon)	P(util)	P(ctrl)	P(neut)	D/U V	D/U p	D/U	Ctx V	Ctx p	Ctx
Friend Referral	Base	13.3%	3.3%	0.0%	0.0%	0.121	0.3502	N	0.273	0.02964	Y
	Deon_ZH	3.3%	33.3%	0.0%	0.0%	0.345	0.0076	Y	0.486	3.11e-06	Y
	Util_ZH	66.7%	73.3%	83.3%	23.3%	0.036	0.7782	N	0.471	6.97e-06	Y
Hostage Crisis	Base	3.3%	6.7%	0.0%	0.0%	0.000	1.0000	N	0.177	0.2885	N
	Deon_ZH	0.0%	40.0%	0.0%	3.3%	0.458	0.0004	Y	0.544	9.76e-08	Y
	Util_ZH	63.3%	73.3%	100.0%	26.7%	0.072	0.5789	N	0.554	4.92e-08	Y
Organ Allocation	Base	36.7%	13.3%	0.0%	6.7%	0.231	0.0736	N	0.396	2.94e-04	Y
	Deon_ZH	6.7%	43.3%	0.0%	0.0%	0.385	0.0029	Y	0.545	9.18e-08	Y
	Util_ZH	40.0%	83.3%	96.7%	36.7%	0.411	0.0014	Y	0.548	7.27e-08	Y

Table D1: ZH Llama SFT+ICL, T=0.2 (Base / Deon_ZH / Util_ZH $\times$ 3 scenarios).

Scenario	Cond.	P(deon)	P(util)	P(ctrl)	P(neut)	D/U V	D/U p	D/U	Ctx V	Ctx p	Ctx
Friend Referral	Base	10.0%	43.3%	20.0%	6.7%	0.339	0.0086	Y	0.358	0.001493	Y
	Deon_ZH	3.3%	30.0%	0.0%	3.3%	0.313	0.0153	Y	0.419	9.95e-05	Y
	Util_ZH	46.7%	33.3%	96.7%	20.0%	0.102	0.4292	N	0.580	8.86e-09	Y
Hostage Crisis	Base	6.7%	33.3%	6.7%	0.0%	0.292	0.0239	Y	0.399	2.63e-04	Y
	Deon_ZH	13.3%	26.7%	3.3%	6.7%	0.125	0.3329	N	0.270	0.03263	Y
	Util_ZH	50.0%	60.0%	100.0%	53.3%	0.067	0.6038	N	0.423	8.48e-05	Y
Organ Allocation	Base	16.7%	36.7%	16.7%	3.3%	0.188	0.1444	N	0.308	0.009956	Y
	Deon_ZH	13.3%	40.0%	0.0%	3.3%	0.264	0.0410	Y	0.450	2.13e-05	Y
	Util_ZH	33.3%	50.0%	100.0%	40.0%	0.135	0.2949	N	0.527	2.71e-07	Y

Table D2: ZH Llama SFT+ICL, T=0.8.

D.2 Chinese Qwen2.5-7B SFT+ICL

Scenario	Cond.	P(deon)	P(util)	P(ctrl)	P(neut)	D/U V	D/U p	D/U	Ctx V	Ctx p	Ctx
Friend Referral	Base	13.3%	100.0%	50.0%	40.0%	0.841	7.40e-11	Y	0.628	2.98E-10	Y
	Deon_ZH	0.0%	6.7%	0.0%	0.0%	0.093	0.4720	N	0.225	0.107	N
	Util_ZH	96.7%	76.7%	100.0%	100.0%	0.245	0.0576	N	0.390	3.97E-04	Y
Hostage Crisis	Base	10.0%	100.0%	73.3%	56.7%	0.871	1.50e-11	Y	0.668	1.36e-11	Y
	Deon_ZH	3.3%	3.3%	3.3%	0.0%	0.000	1.0000	N	0.092	0.795	N
	Util_ZH	76.7%	100.0%	96.7%	100.0%	0.312	0.0158	Y	0.390	3.97E-04	Y
Organ Allocation	Base	10.0%	96.7%	56.7%	30.0%	0.835	9.80e-11	Y	0.649	5.98E-11	Y
	Deon_ZH	0.0%	10.0%	6.7%	0.0%	0.153	0.2360	N	0.217	0.131	N
	Util_ZH	86.7%	100.0%	83.3%	100.0%	0.200	0.1210	N	0.288	0.0188	Y

Table D3: ZH Qwen SFT+ICL, T=0.2.

Scenario	Cond.	P(deon)	P(util)	P(ctrl)	P(neut)	D/U V	D/U p	D/U	Ctx V	Ctx p	Ctx
Friend Referral	Base	6.7%	70.0%	30.0%	40.0%	0.617	1.80e-06	Y	0.472	6.81E-06	Y
	Deon_ZH	0.0%	10.0%	10.0%	0.0%	0.153	0.2360	N	0.229	0.097	N
	Util_ZH	73.3%	70.0%	83.3%	93.3%	0.000	1.0000	N	0.228	0.1	N
Hostage Crisis	Base	16.7%	86.7%	40.0%	36.7%	0.667	2.40e-07	Y	0.516	5.44E-07	Y
	Deon_ZH	3.3%	6.7%	6.7%	3.3%	0.000	1.0000	N	0.076	0.873	N
	Util_ZH	70.0%	96.7%	83.3%	93.3%	0.313	0.0153	Y	0.298	0.014	Y
Organ Allocation	Base	16.7%	73.3%	33.3%	43.3%	0.536	3.30e-05	Y	0.418	1.06e-04	Y
	Deon_ZH	6.7%	6.7%	3.3%	6.7%	0.000	1.0000	N	0.062	0.929	N
	Util_ZH	83.3%	80.0%	73.3%	90.0%	0.000	1.0000	N	0.155	0.408	N

Table D4: ZH Qwen SFT+ICL, T=0.8.

D.3 English Llama-3.1-8B SFT+ICL

Scenario	Cond.	P(deon)	P(util)	P(ctrl)	P(neut)	D/U V	D/U p	D/U	Ctx V	Ctx p	Ctx
Friend Referral	Base	0.0%	6.7%	0.0%	0.0%	0.093	0.4720	N	0.225	0.1068	N
	Deon_EN	80.0%	90.0%	66.7%	93.3%	0.093	0.4696	N	0.273	0.0300	*
	Util_EN	66.7%	86.7%	93.3%	90.0%	0.197	0.1270	N	0.284	0.0214	*
Hostage Crisis	Base	20.0%	83.3%	0.0%	0.0%	0.600	3.30e-06	★	0.781	8.81E-16	★
	Deon_EN	76.7%	96.7%	83.3%	86.7%	0.245	0.0576	N	0.207	0.1618	N
	Util_EN	100.0%	93.3%	90.0%	90.0%	0.093	0.4720	N	0.164	0.3598	N
Organ Allocation	Base	53.3%	63.3%	0.0%	0.0%	0.068	0.6005	N	0.646	7.47E-11	★
	Deon_EN	73.3%	93.3%	93.3%	76.7%	0.224	0.0833	N	0.253	0.0528	N
	Util_EN	90.0%	96.7%	96.7%	93.3%	0.067	0.6048	N	0.118	0.6439	N

Table D5: EN Llama SFT+ICL, T=0.2.

Scenario	Cond.	P(deon)	P(util)	P(ctrl)	P(neut)	D/U V	D/U p	D/U	Ctx V	Ctx p	Ctx
Friend Referral	Base	6.7%	53.3%	3.3%	10.0%	0.473	0.0003	★	0.526	2.96e-07	★
	Deon_EN	83.3%	90.0%	96.7%	86.7%	0.049	0.7041	N	0.159	0.3886	N
	Util_EN	86.7%	90.0%	96.7%	86.7%	0.000	1.0000	N	0.136	0.5276	N
Hostage Crisis	Base	33.3%	83.3%	20.0%	30.0%	0.473	0.0003	★	0.498	1.55e-06	★
	Deon_EN	83.3%	90.0%	100.0%	93.3%	0.049	0.7041	N	0.217	0.1287	N
	Util_EN	93.3%	86.7%	96.7%	96.7%	0.056	0.6670	N	0.164	0.3598	N
Organ Allocation	Base	53.3%	73.3%	60.0%	23.3%	0.173	0.1804	N	0.367	0.0011	**
	Deon_EN	83.3%	93.3%	76.7%	86.7%	0.104	0.4212	N	0.168	0.3341	N
	Util_EN	90.0%	86.7%	100.0%	96.7%	0.000	1.0000	N	0.211	0.1474	N

Table D6: EN Llama SFT+ICL, T=0.8.

D.4   English Qwen2.5-7B SFT+ICL

Scenario	Cond.	P(deon)	P(util)	P(ctrl)	P(neut)	D/U V	D/U p	D/U	Ctx V	Ctx p	Ctx
Friend Referral	Base	43.3%	96.7%	76.7%	83.3%	0.546	2.40e-05	★	0.454	1.77e-05	★
	Deon_EN	70.0%	100.0%	66.7%	100.0%	0.373	0.0038	**	0.435	4.67E-05	★
	Util_EN	100.0%	100.0%	100.0%	100.0%	–	–	N	–	–	N
Hostage Crisis	Base	56.7%	100.0%	83.3%	96.7%	0.485	0.0002	★	0.467	8.66E-06	★
	Deon_EN	73.3%	100.0%	86.7%	86.7%	0.343	0.0079	**	0.277	0.0264	*
	Util_EN	100.0%	96.7%	100.0%	100.0%	0.000	1.0000	N	0.159	0.3878	N
Organ Allocation	Base	30.0%	96.7%	93.3%	90.0%	0.657	3.60e-07	★	0.659	2.80e-11	★
	Deon_EN	80.0%	83.3%	93.3%	93.3%	0.000	1.0000	N	0.180	0.2741	N
	Util_EN	96.7%	93.3%	96.7%	90.0%	0.000	1.0000	N	0.118	0.6439	N

Table D7: EN Qwen SFT+ICL, T=0.2.

Scenario	Cond.	P(deon)	P(util)	P(ctrl)	P(neut)	D/U V	D/U p	D/U	Ctx V	Ctx p	Ctx
Friend Referral	Base	53.3%	90.0%	56.7%	86.7%	0.370	0.0042	**	0.372	8.62e-04	★
	Deon_EN	73.3%	80.0%	83.3%	93.3%	0.039	0.7602	N	0.190	0.2281	N
	Util_EN	100.0%	100.0%	96.7%	100.0%	–	–	N	0.159	0.3878	N
Hostage Crisis	Base	56.7%	93.3%	86.7%	90.0%	0.385	0.0029	**	0.378	6.61e-04	★
	Deon_EN	83.3%	86.7%	86.7%	83.3%	0.000	1.0000	N	0.047	0.9671	N
	Util_EN	96.7%	96.7%	100.0%	100.0%	0.000	1.0000	N	0.130	0.5654	N
Organ Allocation	Base	76.7%	93.3%	80.0%	80.0%	0.187	0.1481	N	0.168	0.3332	N
	Deon_EN	80.0%	76.7%	90.0%	93.3%	0.000	1.0000	N	0.192	0.2173	N
	Util_EN	90.0%	100.0%	100.0%	96.7%	0.153	0.2361	N	0.227	0.1020	N

Table D8: EN Qwen SFT+ICL, T=0.8.