DEEP ENSEMBLE AS A GAUSSIAN PROCESS POSTERIOR

ABSTRACT

Deep Ensemble (DE) is a flexible, feasible, and effective alternative to Bayesian neural networks (BNNs) for uncertainty estimation in deep learning. However, DE is broadly criticized for lacking a proper Bayesian justification. Some attempts try to fix this issue, while they are typically coupled with a regression likelihood or rely on restrictive assumptions. In this work, we propose to define a Gaussian process (GP) approximate posterior with the ensemble members, based on which we perform variational inference directly in the function space. We further develop a function-space posterior regularization mechanism to properly incorporate prior knowledge. We demonstrate the algorithmic benefits of variational inference in the GP family, and provide strategies to make the training feasible. As a result, our method consumes only marginally added training cost than the standard Deep Ensemble. Empirically, our approach achieves better uncertainty estimation than the existing Deep Ensemble and its variants across diverse scenarios.

1 INTRODUCTION

Bayesian treatment of deep neural networks (DNNs) is promised to enjoy principled Bayesian uncertainty while unleashing the capacity of DNNs, with Bayesian neural networks (BNNs) as popular examples (MacKay, 1992; Hinton & Van Camp, 1993; Neal, 1995; Graves, 2011). Nevertheless, despite the surge of advance in BNNs (Louizos & Welling, 2016; Zhang et al., 2018), many of existing BNNs still face challenges in accurate and scalable inference (Sun et al., 2019), and exhibit limitations in uncertainty estimation and out-of-distribution robustness (Ovadia et al., 2019).

Alternatively, Deep Ensemble (DE) (Lakshminarayanan et al., 2017) independently trains multiple randomly-initialized DNNs (referred to as *basis functions* hereinafter) for ensemble, presenting higher flexibility, feasibility, and performance than standard Bayesian inference for DNNs. Despite the ability to explicitly explore the non-convex, multimodal loss landscape of DNNs (Fort et al., 2019; Wilson & Izmailov, 2020), DE lacks a rigorous Bayesian justification (He et al., 2020; Pearce et al., 2020). Some recent works like RMS (Lu & Van Roy, 2017; Osband et al., 2018; Pearce et al., 2020) and NTKGP (He et al., 2020) refine DE to be a "sample-then-optimize" approach which directly yields posterior samples after training (Matthews et al., 2017). However, such methods rely on a *regression likelihood* and often make strong assumptions like *linearised* and/or *infinite-width* models.

In this work, we endow DE with a principled learning criterion under the function-space Bayesian inference paradigm. In essence, the mixture of deltas (MoD) distribution over weights in DE induces a distribution over functions (i.e., a stochastic process). However, the singularity issue of MoD can yield an ill-defined objective for Bayesian learning (Hron et al., 2018). To remediate the issue, we instead specify a *Gaussian process* (GP) with DE's basis functions, analogous to deep kernel learning (Wilson et al., 2016), and expect it to approximate the true posterior. The imposition of a GP form on the approximate posterior is empowered by the *equivalence* between GPs and both finite- and infinite-width BNNs (Khan et al., 2019; Rudner et al., 2021; Neal, 1996; Lee et al., 2017; Garriga-Alonso et al., 2018; Matthews et al., 2018; Novak et al., 2018; He et al., 2020), as well as the associated computational advantages when adopting a GP prior without loss of generality.

Inspired by the Monte Carlo (MC) estimates for kernels (Rahimi et al., 2007), especially for neural network Gaussian process (NN-GP) kernels (Novak et al., 2018), we evaluate the empirical mean and covariance of the basis functions and use them to specify the GP approximate posterior. Namely, we define a parameteric and learnable GP kernel with finitely many and adaptive basis functions, in contrast to the typical kernels like radial basis function (RBF) and NN-GP kernels built with infinitely

Figure 1: Prediction on data from $y = x^3/4 + \epsilon, \epsilon \sim \mathcal{N}(0, 0.1)$. The two rows correspond to multilayer perceptrons (MLPs) with 2 hidden layers of 64 units and MLPs with 3 hidden layers of 512 units, respectively. The first four columns correspond to four methods. We plot the training data (red dots), mean predictions (dark blue curves), and uncertainty (shaded regions). For NN-GP, we performs analytic GP regression without training MLPs. The other methods train 50 MLPs, with the training speed depicted in the last column. As network size rises, DE-GP behaves consistently, while DE and RMS suffer from degeneracy. DE-GP is on par with the non-parameteric NN-GP in aspect of uncertainty quality, with only marginally added overheads upon DE.

many yet fixed basis functions. The flexibility of the GP is assured by the expressiveness of DNN basis functions – by learning the basis functions it is enabled to evolve over a rich variety of kernels.

Given these setups, we perform variational inference (VI) directly in function space. We maximize the functional evidence lower bound (fELBO) (Sun et al., 2019; Rudner et al., 2021) to push the *Deep Ensemble based Gaussian process* (DE-GP) towards the true posterior over functions. We further present a posterior regularization scheme in function space to conveniently incorporate structural priors, and present a concrete example on how to control function complexity. By VI, we are enabled to handle classification problems directly and exactly, without casting them into regression ones (He et al., 2020). In practice, DE-GP can be easily implemented on top of a standard DE, while only introducing minimally added cost.

Compared to DE and RMS, DE-GP overcomes the pathologies of posterior inference in the over-parameterized weight space containing many symmetries (Sun et al., 2019; Wang et al., 2019), hence offering better uncertainty estimates, especially when adopting *large* network (see Fig. 1). Further, we empirically demonstrate that DE-GP outperforms strong baselines on various regression datasets, and presents superior uncertainty estimates and out-of-distribution robustness in challenging classification tasks. DE-GP also shows promise in solving contextual bandit problems, where the uncertainty plays a vital role in guiding exploration.

2 BACKGROUND

2.1 BAYESIAN NEURAL NETWORKS AND DEEP ENSEMBLE

Consider learning on a dataset $\mathcal{D} = (\mathbf{X}, \mathbf{Y}) = \{(\boldsymbol{x}_i, \boldsymbol{y}_i)\}_{i=1}^n$, with $\boldsymbol{x}_i \in \mathcal{X}$ as data and $\boldsymbol{y}_i$ as C-dimensional targets. Let $g(\cdot, \boldsymbol{w}) : \mathcal{X} \rightarrow \mathbb{R}^C$ denote the function represented by a DNN with weights $\boldsymbol{w}$. Bayesian neural networks (BNNs) treat $\boldsymbol{w}$ as random variables and chase the posterior $p(\boldsymbol{w}|\mathcal{D})$ by imposing a prior $p(\boldsymbol{w})$. Among the family, variational BNNs (VBNNs) are particularly appealing as they cast posterior inference as an optimization problem (Graves, 2011; Blundell et al., 2015; Louizos & Welling, 2016), where a variational distribution $q(\boldsymbol{w})$ is introduced to approximate the true posterior by maximizing the evidence lower bound (ELBO):

$$\mathbb{E}_{q(\boldsymbol{w})}[\log p(\mathcal{D}|\boldsymbol{w})] - D_{\mathrm{KL}}[q(\boldsymbol{w})\|p(\boldsymbol{w})]. \tag{1}$$

Other popular BNN methods include Laplace approximation (Mackay, 1992), MC dropout (Gal & Ghahramani, 2016), Markov chain Monte Carlo (MCMC) (Neal, 1995; Welling & Teh, 2011), etc.

BNNs marginalize over the posteriors to obtain the *posterior predictive* for new data $\boldsymbol{x}^*$:

$$p(y|\boldsymbol{x}^*, \mathcal{D}) = \mathbb{E}_{p(\boldsymbol{w}|\mathcal{D})}p(y|\boldsymbol{x}^*, \boldsymbol{w}) \approx \mathbb{E}_{q(\boldsymbol{w})}p(y|\boldsymbol{x}^*, \boldsymbol{w}) \approx \sum_{s=1}^{S} p(y|\boldsymbol{x}^*, \boldsymbol{w}_s), \tag{2}$$

where $\boldsymbol{w}_s \sim q(\boldsymbol{w}), s = 1, ..., S$. As expected, such a procedure propagates the embedded model uncertainty into the prediction. However in practice, most of the existing BNN approaches face obstacles in precise posterior inference due to non-trivial and convoluted posterior dependencies (Louizos

& Welling, 2016; Zhang et al., 2018; Shi et al., 2018; Sun et al., 2019), and deliver unsatisfactory uncertainty estimation and out-of-distribution (OOD) robustness (Ovadia et al., 2019).

As a workaround of BNNs, Deep Ensemble (DE) (Lakshminarayanan et al., 2017) deploys a set of M DNNs (referred to as *basis functions*) with weights $\{\boldsymbol{w}_i\}_{i=1}^M$ for ensemble. $\{\boldsymbol{w}_i\}_{i=1}^M$ are independently trained to interpret the data from different angles, under maximum likelihood estimation (MLE) principle in standard DE, or maximum a posteriori (MAP) principle in regularized DE (rDE):

$$\max_{\boldsymbol{w}_1,...,\boldsymbol{w}_M} \mathcal{L}_{\text{DE}} = \frac{1}{M}\sum_{i=1}^M \log p(\mathcal{D}|\boldsymbol{w}_i), \quad \max_{\boldsymbol{w}_1,...,\boldsymbol{w}_M} \mathcal{L}_{\text{rDE}} = \frac{1}{M}\sum_{i=1}^M [\log p(\mathcal{D}|\boldsymbol{w}_i) + \log p(\boldsymbol{w}_i)]. \quad (3)$$

Due to the randomness in network initialization and stochastic gradient descent (SGD), DE can effectively explore the complex, non-convex loss landscape of DNNs (Fort et al., 2019; Wilson & Izmailov, 2020), thus shows appealing potential in various uncertainty estimation scenarios (Lakshminarayanan et al., 2017; Ovadia et al., 2019). However, DE lacks a rigorous Bayesian justification. To this end, a suite of works based on the notion of "sample-then-optimize" (Matthews et al., 2017) are developed. For example, RMS (Lu & Van Roy, 2017; Osband et al., 2018; Pearce et al., 2020) regularizes $\{\boldsymbol{w}_i\}_{i=1}^M$ towards randomised priors to obtain posterior samples after training, while it typically assumes *linear* data likelihood which is impractical for deep models and classification tasks. He et al. (2020) proposed to add a randomised function to each basis function to realise a function-space Bayesian interpretation, while the method is asymptotically exact in the *infinite width* limit and is limited to regressions. So, a proper Bayesian exposition for DE is still a paramount need.

2.2 Relation of Bayesian Neural Networks to Gaussian Processes

It is early shown that shallow BNNs converge to GPs in the infinite width limit (Neal, 1996). Recently, there is ongoing effort to extend the result to multiple layers (Lee et al., 2017; Matthews et al., 2018), convolutional architectures (Garriga-Alonso et al., 2018; Novak et al., 2018), and beyond (Yang, 2019). Briefly, an infinitely wide BNN amount to the NN-GP:

$$\mathcal{GP}(0, k(\boldsymbol{x}, \boldsymbol{x}')), \text{with } k(\boldsymbol{x}, \boldsymbol{x}') := \mathbb{E}_{\boldsymbol{w}\sim p(\boldsymbol{w})}[g(\boldsymbol{x}, \boldsymbol{w})g(\boldsymbol{x}', \boldsymbol{w})^\top], \quad (4)$$

where $p(\boldsymbol{w})$ is a layerwise isotropic Gaussian and the DNN specifying g has infinite width. Notably, k is a matrix-valued kernel, with values in the space of $C \times C$ matrices. Due to the i.i.d. weights, the kernel evaluation $k(\boldsymbol{x}^*, \boldsymbol{x}^*)$ of some data $\boldsymbol{x}^*$ is a scaled identity matrix. The hierarchical nature of DNNs makes k a compositional kernel, which can be analytically estimated in some cases (Novak et al., 2018; 2019). Yet, the current implementations routinely suffer from scalability issues and struggle to handle modern network configurations. Thus, Novak et al. (2018) developed an MC estimate of k using *finitely wide* NNs, in a similar spirit to the classic random feature approaches (Rahimi et al., 2007). Formally, supposing that g comprises a feature projector $h(\cdot, \boldsymbol{w}) : \mathcal{X} \to \mathbb{R}^{\hat{C}}$ and a linear readout layer with weight variance σ_w^2 and bias variance σ_b^2, the MC NN-GP kernel takes the form of

$$k(\boldsymbol{x}, \boldsymbol{x}') \approx (\sigma_w^2 \hat{k}(\boldsymbol{x}, \boldsymbol{x}') + \sigma_b^2)\mathbf{I}_C, \text{with } \hat{k}(\boldsymbol{x}, \boldsymbol{x}') = \frac{1}{S\hat{C}}\sum_{s=1}^S h(\boldsymbol{x}, \boldsymbol{w}_s)^\top h(\boldsymbol{x}', \boldsymbol{w}_s), \quad (5)$$

where $\mathbf{I}_C$ refers to the indentity matrix of size $C \times C$ and $\boldsymbol{w}_s \sim p(\boldsymbol{w}), s = 1, ..., S$.

Based on the canonical results of GP regression, we know the posteriors of infinitely wide BNNs are still GPs, corresponding to the Bayesian training of the *last* readout layer (Arora et al., 2019; Lee et al., 2019). Despite a golden standard for small regression problems, analytical posterior inference for NN-GP faces challenges when handling contemporary DNN architectures (Novak et al., 2018), large data (Shi et al., 2019) and classification problems. Instead, we use DE to define a parametric, adaptive kernel in a similar vein to above MC kernels, and perform variational inference in function space, which is more flexible and can unleash the potential of practically sized SGD-trained DNNs.

It is also noteworthy that finitely wide BNNs with Gaussian posteriors on weights can be connected to Neural Tangent Kernel (NTK) (Jacot et al., 2018) based GPs (Khan et al., 2019; Rudner et al., 2021), providing supports for dictating a GP approximate posterior in this work. Yet, these methods make strong assumptions like local linearization, while our method bypasses this.

3 Methodology

3.1 Deep Ensemble as a Gaussian Process Posterior

Let g_i denote $g(\cdot, \boldsymbol{w}_i)$. DE actually defines a distribution $q(f; \boldsymbol{w}_i, ..., \boldsymbol{w}_M) = \frac{1}{M}\sum_i \delta(f - g_i)$ over functions $f : \mathcal{X} \to \mathbb{R}^C$. To make DE a Bayesian method, a natural idea is to push q towards the true

posterior over functions. However, the mixture of delta (MoD) distribution can yield ill-defined objectives for approximate inference (Hron et al., 2018). To address this, we instead utilize the basis functions to define a kernel as well as a GP variational, in a similar spirit to NN-GP, as follows:

$$q(f; \boldsymbol{w}_1, ..., \boldsymbol{w}_M) := \mathcal{GP}(f|m_q(\boldsymbol{x}), k_q(\boldsymbol{x}, \boldsymbol{x}')),$$
$$m_q(\boldsymbol{x}) := \frac{1}{M} \sum_{i=1}^{M} g_i(\boldsymbol{x}), \tag{6}$$
$$k_q(\boldsymbol{x}, \boldsymbol{x}') := \frac{1}{M} \sum_{i=1}^{M} \left(g_i(\boldsymbol{x}) - m_q(\boldsymbol{x}) \right) \left(g_i(\boldsymbol{x}') - m_q(\boldsymbol{x}') \right)^{\top} + \lambda \mathbf{I}_C.$$

As shown, the empirical mean and central covariance of finitely many, adaptive basis functions are leveraged to specify the DE-GP. $k_q(\boldsymbol{x}, \boldsymbol{x}')$ is a *linear*, *matrix-valued* kernel with a small scaled identity matrix $\lambda \mathbf{I}_C$ appended to avoid singularity. The variations in $k_q(\boldsymbol{x}, \boldsymbol{x}')$ are confined to having up to $M - 1$ rank, which is likely to be reasonable given the previous investigations showing that low-rank approximate posteriors for DNNs conjoin effectiveness and *efficiency* (Maddox et al., 2019; Izmailov et al., 2020; Dusenberry et al., 2020). Note that the popular Nyström method (Williams & Seeger, 2001) also uses a low-rank matrix to approximate the original kernel matrix.

Akin to the kernels in (Wilson et al., 2016), the DE-GP kernels are highly flexible, and may automatically discover the underlying structures of high-dimensional data without manual participation.

3.2 VARIATIONAL INFERENCE IN FUNCTION SPACE

Given these setups, we perform variational inference directly in function space. We specify the functional prior as the aforementioned NN-GPs $p(f) = \mathcal{GP}(f|0, k(\boldsymbol{x}, \boldsymbol{x}'))$ to enjoy the inductive bias carried by specific NN architectures.[1] As will be shown later, the variational inference in the GP family is much simpler than that using general stochastic processes.

Formally, DE-GP evolves by maximizing the functional ELBO (fELBO) (Sun et al., 2019):

$$\max_{q(f)} \mathbb{E}_{q(f)}[\log p(\mathcal{D}|f)] - D_{\mathrm{KL}}[q(f)\|p(f)]. \tag{7}$$

fELBO involves the KL divergence between two GPs, which, on its own, is challenging to cope with, yet can be replaced by the KL divergence between the marginal distributions of function evaluations.

As proved by (Sun et al., 2019), with a measurement set $\tilde{\mathbf{X}}$ including all training inputs $\mathbf{X}$, we have

$$\mathcal{L} = \sum_{(\boldsymbol{x}_i, \boldsymbol{y}_i) \in \mathcal{D}} \mathbb{E}_{q(f)}[\log p(\boldsymbol{y}_i|f(\boldsymbol{x}_i))] - D_{\mathrm{KL}}[q(\mathbf{f}^{\tilde{\mathbf{X}}})\|p(\mathbf{f}^{\tilde{\mathbf{X}}})]$$
$$= \log p(\mathcal{D}) - D_{\mathrm{KL}}[q(\mathbf{f}^{\tilde{\mathbf{X}}})\|p(\mathbf{f}^{\tilde{\mathbf{X}}}|\mathcal{D})] \leq \log p(\mathcal{D}), \tag{8}$$

where $\mathbf{f}^{\tilde{\mathbf{X}}}$ is the concatenation of the vectorized outputs of f for $\tilde{\mathbf{X}}$, i.e., $\mathbf{f}^{\tilde{\mathbf{X}}} \in \mathbb{R}^{|\tilde{\mathbf{X}}|C}$.

In this way, we can obtain a tractable lower bound $\mathcal{L}$ for the log marginal likelihood.

3.3 POSTERIOR REGULARIZATION IN FUNCTION SPACE

Though Bayesian learning in function space enables a direct imposition of prior knowledge on function properties like smoothness and periodicity (Sun et al., 2019), sometimes the prior knowledge cannot be trivially designed as a prior distribution over functions. For example, the functions are periodical only over a limited input range, or the functions are Lipschitz continuous. In these cases, posterior regularization (Ganchev et al., 2010; Zhu et al., 2014) provides a principled workaround to impose structural constraints.

Briefly, we apply posterior regularization to functional variational inference by solving:

$$\max_{q(f)} \mathcal{L} \text{ s.t.: } q(f) \in Q. \tag{9}$$

$Q = \{q(f)|\mathbb{E}_{q(f)}\Omega(f) \leq 0\}$ is a valid set defined in terms of a functional Ω which delivers some statistic of interest of a function.[2] For tractable optimization, we slack the constraint as a penalty:

$$\max_{q(f)} \mathcal{L}' = \mathcal{L} - \beta \max\{\mathbb{E}_{q(f)}\Omega(f), 0\}. \tag{10}$$

---

[1]Note that the NN-GP prior and the DE-GP variational posterior can be defined with various architectures. We actually use the MC estimate of the NN-GP prior during training.

[2]Here we assume one-dimensional outputs for Ω for notation compactness.

β is a trade-off coefficient. We next present an example on how to induce prior knowledge on function (hypothesis) complexity.

For the sake of brevity, we assume a binary classification scenario in the following discussion where $y \in \{-1, 1\}$ and $f, g_i : \mathcal{X} \rightarrow \mathbb{R}$. We use 0-1 loss $\ell(f(\boldsymbol{x}), y) = \mathbf{1}_{y \neq \text{sign}(f(\boldsymbol{x}))}$ to measure the classification error on one datum. We assume an underlying distribution $\mu = \mu(\boldsymbol{x}, y)$ supported on $\mathcal{X} \times \{-1, 1\}$ for generating the training data $\mathcal{D}$, based on which we can define the *true* risk of a function (hypothesis) f: $R(f) := \mathbb{E}_{(\boldsymbol{x}, y) \sim \mu} \ell(f(\boldsymbol{x}), y)$. We set $\mathbb{E}_{q(f)} \Omega(f) := \mathbb{E}_{q(f)} R(f)$ in the seek of a posterior over functions that can generalize well.

It is easy to see that a hypothesis sample $f \sim q(f) = \mathcal{GP}(m_q(\boldsymbol{x}), k_q(\boldsymbol{x}, \boldsymbol{x}'))$ can be decomposed as $f(\boldsymbol{x}) = \frac{1}{M} \sum_{i=1}^{M} g_i(\boldsymbol{x}) + \zeta(\boldsymbol{x})$ with $\zeta(\boldsymbol{x}) \sim \mathcal{GP}(0, k_q(\boldsymbol{x}, \boldsymbol{x}'))$. Then, given the fact that a voting is incorrect when at least one of the individuals makes a mistake, we have

$$\ell(f(\boldsymbol{x}), y) \leq \sum_{i=1}^{M} [\ell(g_i(\boldsymbol{x}), y)] + \ell(\zeta(\boldsymbol{x}), y). \tag{11}$$

Note that $\zeta(\boldsymbol{x})$ can be re-parameterized as $\zeta(\boldsymbol{x}) = \frac{1}{\sqrt{M}} \sum_{i=1}^{M} \epsilon_i (g_i(\boldsymbol{x}) - m_q(\boldsymbol{x})) + \sqrt{\lambda} \epsilon_0, \epsilon_i \sim \mathcal{N}(0, 1), i = 0, ..., M$, which is essentially a real-valued random function symmetric around 0. Thus, for any $(\boldsymbol{x}, y) \sim \mu$, we have $\mathbb{E}_{q(f)} \ell(\zeta(\boldsymbol{x}), y) = \mathbb{E}_{\epsilon_0, ..., \epsilon_M} \ell(\zeta(\boldsymbol{x}), y) = 1/2$. As a result,

$$\mathbb{E}_{q(f)} R(f) \leq \mathbb{E}_{q(f)} \mathbb{E}_{(\boldsymbol{x}, y) \sim \mu} \sum_{i=1}^{M} [\ell(g_i(\boldsymbol{x}), y)] + \mathbb{E}_{(\boldsymbol{x}, y) \sim \mu} [1/2] = \sum_{i=1}^{M} [R(g_i)] + 1/2. \tag{12}$$

Namely, the expected generalization error of the approximately posteriori functions can be bounded from above by those of the DNN basis functions.[3] Recalling the theoretical and empirical results showing that DNNs' generalization error $R(g_i)$ can be penalized by controlling model capacity in terms of norm-based regularization $\min_{\boldsymbol{w}_i} ||\boldsymbol{w}_i||_2^2$ (Neyshabur et al., 2015; 2017; Bartlett et al., 2017; Jiang et al., 2019), we opt to maximize the following refined fELBO for learning DE-GP:

$$\max_{\boldsymbol{w}_1, ..., \boldsymbol{w}_M} \mathcal{L}_{\text{DE-GP}} = \sum_{(\boldsymbol{x}_i, \boldsymbol{y}_i) \in \mathcal{D}} \mathbb{E}_{q(f)} [\log p(\boldsymbol{y}_i | f(\boldsymbol{x}_i))] - D_{\text{KL}} [q(\mathbf{f}^{\tilde{\mathbf{X}}}) \| p(\mathbf{f}^{\tilde{\mathbf{X}}})] - \beta \sum_{i} ||\boldsymbol{w}_i||_2^2. \tag{13}$$

Intuitively, the weight space of an over-parameterized DNN contains many redundant interpretations for the data, thus pushing the weights towards zero would not hurt data fitting but boost generalization. In practice, when processing with shallow architectures, β can be set as 0 to remove the constraint on model capacity; while when using deep architectures (e.g., ResNet (He et al., 2016)), we can set β according to commonly used weight decay coefficient for better generalization. Comparisons in Fig. 2 and Table 1 support this.

Figure 2: Comparison on the L_2 norm of weights. We traine models on CIFAR-10 with ResNet-20. DE-GP ($\beta = 0$) finds solutions with high complexity and poor test accuracy (see Table 1), yet DE-GP ($\beta = 0.1$) settles this.

3.4 THE ALGORITHM

We outline the training procedure of DE-GP in Algorithm 1, and elaborate some details below.

3.4.1 MINI-BATCH TRAINING

In deep learning scenarios, DE-GP should proceed by mini-batch training. At each step, we manufacture a stochastic measurement set with a mini-batch $\mathcal{D}_s = (\mathbf{X}_s, \mathbf{Y}_s)$ from the training data $\mathcal{D}$ and random samples $\mathbf{X}_\nu$ from a continuous distribution ν (e.g., a uniform distribution) supported on $\mathcal{X}$. Then, we adapt the objective defined in Eq. (13) to the following form:

$$\mathcal{L}_{\text{DE-GP}} = \sum_{(\boldsymbol{x}_i, \boldsymbol{y}_i) \in \mathcal{D}_s} \mathbb{E}_{q(f)} [\log p(\boldsymbol{y}_i | f(\boldsymbol{x}_i))] - \alpha D_{\text{KL}} [q(\mathbf{f}^{\tilde{\mathbf{X}}_s}) \| p(\mathbf{f}^{\tilde{\mathbf{X}}_s})] - \beta \sum_{i} ||\boldsymbol{w}_i||_2^2, \tag{14}$$

where $\tilde{\mathbf{X}}_s$ indicates the union of $\mathbf{X}_s$ and $\mathbf{X}_\nu$. When $\alpha = 1$ and $\beta = 0$, $\mathcal{L}_{\text{DE-GP}}$ is a lower bound of $\log p(\mathcal{D}_s)$ according to (Sun et al., 2019). Yet, given that we do not perform intensive hyper-parameter tuning for the NN-GP prior, it is reasonable to make α a tunable hyper-parameter to better trade off between the data fitting and the priori inductive bias.

---

[3] A similar conclusion can be drawn in multi-class classification scenario (see Appendix A).

Algorithm 1: Deep Ensemble as a Gaussian process posterior (DE-GP).

1: **Input:** $\mathcal{D}$: Dataset; $\{g_i\}_{i=1}^M$: an ensemble of DNNs; k: kernel of GP prior; α, β: trade-off coefficients; ν: sampling distribution for extra measurement points.

2: **while** not converged **do**

3:    $\mathcal{D}_s = (\mathbf{X}_s, \mathbf{Y}_s) \subset \mathcal{D}, \mathbf{X}_\nu \sim \nu, \tilde{\mathbf{X}}_s = \{\mathbf{X}_s, \mathbf{X}_\nu\}$

4:    $\mathbf{g}_i = g_i(\tilde{\mathbf{X}}_s) \in \mathbb{R}^{|\tilde{\mathbf{X}}_s|C}, i = 1, ..., M$

5:    $\mathbf{m}_q^{\tilde{\mathbf{X}}_s} = \frac{1}{M}\sum_i \mathbf{g}_i, \mathbf{k}_q^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s} = \frac{1}{M}\sum_{i=1}^M (\mathbf{g}_i - \mathbf{m}_q^{\tilde{\mathbf{X}}_s})(\mathbf{g}_i - \mathbf{m}_q^{\tilde{\mathbf{X}}_s})^\top + \lambda \mathbf{I}_{|\tilde{\mathbf{X}}_s|C}$

6:    $\mathbf{k}^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s} = k(\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s) \in \mathbb{R}^{|\mathbf{X}_s|C \times |\mathbf{X}_s|C}$

7:    $\mathcal{L}_1 = \frac{1}{U}\sum_{i=1}^U \sum_{(\boldsymbol{x}, \boldsymbol{y}) \in \mathcal{D}_s} \log p(\boldsymbol{y}|\mathbf{f}_i(\boldsymbol{x})), \mathbf{f}_i \sim \mathcal{N}(\mathbf{m}_q^{\tilde{\mathbf{X}}_s}, \mathbf{k}_q^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s})$

8:    $\mathcal{L}_2 = D_{\mathrm{KL}}[\mathcal{N}(\mathbf{m}_q^{\tilde{\mathbf{X}}_s}, \mathbf{k}_q^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s})\|\mathcal{N}(\mathbf{0}, \mathbf{k}^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s})], \mathcal{L}_3 = \sum_i \|\boldsymbol{w}_i\|_2^2$

9:    $\boldsymbol{w}_i = \boldsymbol{w}_i + \eta \nabla_{\boldsymbol{w}_i}(\mathcal{L}_1 - \alpha\mathcal{L}_2 - \beta\mathcal{L}_3), i = 1, ..., M$

3.4.2 AN EXACT AND EFFICIENT ESTIMATION OF THE MARGINAL KL DIVERGENCE

The marginal distributions of function evaluations are multivariate Gaussian by the definition of GP:

$$q(\mathbf{f}^{\tilde{\mathbf{X}}_s}) = \mathcal{N}(\mathbf{f}^{\tilde{\mathbf{X}}_s}|\mathbf{m}_q^{\tilde{\mathbf{X}}_s}, \mathbf{k}_q^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s}), \ p(\mathbf{f}^{\tilde{\mathbf{X}}_s}) = \mathcal{N}(\mathbf{f}^{\tilde{\mathbf{X}}_s}|\mathbf{0}, \mathbf{k}^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s}), \tag{15}$$

with the kernel matrices $\mathbf{k}_q^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s}, \mathbf{k}^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s} \in \mathbb{R}^{|\tilde{\mathbf{X}}_s|C \times |\tilde{\mathbf{X}}_s|C}$ as the joints of pair-wise outcomes.

Therefore, the marginal KL divergence and its gradients can be estimated exactly without resorting to some approximations (Rudner et al., 2021). What's more, as discussed in Section 2.2, there is a simple structure in the prior kernel matrices, so we can write them in the form of Kronecker product:

$$\mathbf{k}^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s} \approx (\sigma_w^2 \hat{\mathbf{k}}^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s} + \sigma_b^2) \otimes \mathbf{I}_C, \tag{16}$$

where $\hat{\mathbf{k}}^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s} \in \mathbb{R}^{|\tilde{\mathbf{X}}_s| \times |\tilde{\mathbf{X}}_s|}$ corresponds to the evaluation of kernel $\hat{k}$. Hence we can exploit the property of Kronecker product to inverse $\mathbf{k}^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s}$ in $\mathcal{O}(|\tilde{\mathbf{X}}_s|^3)$ complexity.

Besides, as $\mathbf{k}_q^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s}$ is low-rank, we can leverage the Woodbury matrix identity (Woodbury, 1950) and matrix determinant lemma (Harville, 1998) to efficiently compute the inverse and determinant of $\mathbf{k}_q^{\tilde{\mathbf{X}}_s, \tilde{\mathbf{X}}_s}$ in $\mathcal{O}(|\tilde{\mathbf{X}}_s|CM^2)$ time complexity given that usually $M \ll |\tilde{\mathbf{X}}_s|C$ (e.g., $10 \ll 256C$).

3.5 DISCUSSION

Diversity. The diversity among the ensemble members in function space is explicitly encouraged by the KL divergence between variational and the prior in fELBO. Arguably, the diversity on the points far away from the training data is further fostered, giving rise to calibrated uncertainty (see Fig. 1 and Fig. 9 in Appendix B.2). However, the diversity in DE does not have a clear theoretical support.

Efficiency. Compared to the overhead introduced by DNNs, the effort of estimating the KL divergence between Gaussians is negligible. The added cost of DE-GP primarily arises from the extra measurement points and the evaluation of the prior kernels. In practice, we use a small batch size for the extra measurement points. We build the prior NN-GP kernels with cheap architectures and perform MC estimation in parallel. Eventually, DE-GP is only marginally slower than DE in training.

Weight sharing. DE-GP does not care about how the basis functions are parameterized, so we can perform weight sharing among the basis functions, for example, using a shared feature extractor and M independent MLP classifiers to construct M basis functions (Deng et al., 2021). With shared weights, DE-GP is still likely to be reliable because our learning principle induces diversity in function space regardless of the weights. Experiments in Section 5.3 validate this.

Limitations. Despite being Bayesian in principle, DE-GP is likely to be less flexible than DE and other variants because all the involved basis functions need to be updated simultaneously. So, the ML practitioners need to make a trade-off between theoretical soundness and flexibility in practical usage.

4 RELATED WORK

Bayesian neural networks (BNNs). Bayesian treatment of DNNs is an emerging topic in deep learning yet with a long history (Mackay, 1992; Hinton & Van Camp, 1993; Neal, 1995; Graves, 2011). BNNs can be learned by virtue of variational inference (Blundell et al., 2015; Hernández-Lobato & Adams, 2015; Louizos & Welling, 2016; Zhang et al., 2018; Khan et al., 2018; Deng

Figure 3: Comparison on average test NLL and RMSE on UCI regression problems. The lower the better.

et al., 2020), Laplace approximation (Mackay, 1992; Ritter et al., 2018), Markov chain Monte Carlo (Welling & Teh, 2011; Chen et al., 2014; Zhang et al., 2019), particle-optimization based variational inference (Liu & Wang, 2016), Monte Carlo dropout (Gal & Ghahramani, 2016), and other methods (Maddox et al., 2019; Izmailov et al., 2020). To avoid the difficulties of posterior inference in weight space, some recent works advocate performing Bayesian reasoning in function space (Sun et al., 2019; Rudner et al., 2021; Wang et al., 2019). In function space, BNNs of infinite or even finitely width equal to Gaussian processes (GPs) (Neal, 1996; Lee et al., 2017; Novak et al., 2018; He et al., 2020; Khan et al., 2019), which provides valuable insights for this work.

Deep Ensemble (DE) (Lakshminarayanan et al., 2017) is a qualified alternative to BNNs for uncertainty estimation (Ovadia et al., 2019), yet lacks a proper Bayesian interpretation. Some works regard DE as a "sample-then-optimize" (Matthews et al., 2017) method, but usually rely on restrictive assumptions (Lu & Van Roy, 2017; Osband et al., 2018; Pearce et al., 2020; He et al., 2020). Having identified that DE specifies a GP, we offer a more proper Bayesian exposition for DE.

5 EXPERIMENTS

We evaluate DE-GP in multiple scenarios to prove that DE-GP yields better uncertainty estimates than competing baselines, while preserving non-degraded predictive performance. The baselines include DE, rDE, NN-GP, RMS, etc. In *all* experiments, we estimate the prior kernel with 10 MC samples and set the sampling distribution for extra measurement points ν as the uniform distribution over the data region. Code is provided in the supplementary material.

5.1 ILLUSTRATIVE REGRESSION

We build two regression problems with data from $y = x^3/4 + \epsilon, \epsilon \sim \mathcal{N}(0, 0.1)$ and $y = x \sin 5x + \epsilon, \epsilon \sim \mathcal{N}(0, 0.2)$, respectively. We consider two architectures: MLPs with 2 hidden layers of 64 units and MLPs with 3 hidden layers of 512 units, where ReLU activation is used. For NN-GP, we analytically estimate the GP kernel and perform GP regression without training MLPs. For DE-GP, DE, rDE, and RMS, we train 50 MLPs. For MC dropout, we train a MLP with the commonly used 0.2 dropout rate. We use the default values for α and β, i.e., $\alpha = 1$ and $\beta = 0$.

Fig. 1 and Appendix B.2 show the results on the two problems. We also provide the comparison on training speed in Fig. 1. As shown, DE-GP delivers calibrated uncertainty estimates across settings, on par with the non-parametric Bayesian baseline NN-GP. Yet, the baselines like DE, rDE, and RMS suffer from degeneracy issue as the dimension of weights increases. Though NN-GP outperforms other methods, the involved analytical GP regression may have scalability and effectiveness issues when facing modern architectures (Novak et al., 2018), while DE-GP does not suffer from them.

5.2 UCI REGRESSION

Suggested by existing works (Hernández-Lobato & Adams, 2015; Pearce et al., 2020), we then assess DE-GP on 5 UCI real-valued regression problems. The used architecture is a MLP with 2 hidden layers of 256 units and ReLU activation. 10 networks are trained for DE, DE-GP and other variants. For DE-GP, we set $\beta = 0$ (stated in Section 3.3) and tune α according to validation sets.

We perform cross validation with 5 splits. Fig. 3 shows the results. DE-GP surpasses or approaches the baselines across scenarios in aspects of both test negative log-likelihood (NLL) and test root mean square error (RMSE). Notably, DE-GP's merits are prominent on the large-scale *Protein* dataset.

5.3 IMAGE CLASSIFICATION ON FASHION-MNIST AND CIFAR-10

In the classification experiments, we augment the data log-likelihood (i.e., the first term in Eq. (14)) with a *trainable temperature* to tackle oversmoothing and avoid underconfidence. [4]

---

[4] We can make the temperature a Bayesian variable, but it is unnecessary as our model is already Bayesian.

Figure 4: (Left): Test error varies w.r.t. ensemble size on Fashion-MNIST. (Middle): Test NLL varies w.r.t. ensemble size on Fashion-MNIST. (Right): Test error versus uncertainty plots for methods trained on Fashion-MNIST and tested on both Fashion-MNIST and MNIST. Ensemble size is fixed as 10.

Table 1: Test accuracy comparison on CIFAR-10. Results are summarized over 3 trials.

Architecture	DE-GP ($\beta = 0.1$)	DE-GP ($\beta = 0$)	DE	rDE	RMS
ResNet-20	**94.61**±0.10%	93.80±0.09%	93.47±0.21%	94.53±0.04%	93.56±0.07%
ResNet-56	95.50±0.03%	94.32±0.06%	94.02±0.11%	**95.60**±0.02%	94.43±0.02%

Fashion-MNIST. We use a widened LeNet5 architecture with batch normalizations (BNs) (Ioffe & Szegedy, 2015) for the Fashion-MNIST dataset (Xiao et al., 2017). Considering the inefficiency of NN-GP, we mainly compare DE-GP to DE, rDE, and RMS. We set α as well as the regularization coefficients for rDE and RMS all as 0.1 according to validation accuracy. For DE-GP, we use $\beta = 0$ given the limited capacity of the architecture. The in-distribution performance is averaged over 3 runs. Fig. 4-(Left) and Fig. 4-(Middle) display how ensemble size impacts the test results. Notably, the test error of DE-GP is consistently superior to the baselines with statistical evidence.

Besides, to compare the quality of uncertainty estimates, we use the trained models to make prediction and quantify *epistemic uncertainty* for both the in-distribution test set and the out-of-distribution (OOD) MNIST test set. All predictions on OOD data are regarded as wrong. The *epistemic uncertainty* is estimated by the mutual information between the prediction and the variable function:

$$\mathcal{I}(f, y|\boldsymbol{x}, \mathcal{D}) \approx H\left(\frac{1}{S}\sum_{s=1}^{S} p(y|f_s(\boldsymbol{x}))\right) - \frac{1}{S}\sum_{s=1}^{S} H\left(p(y|f_s(\boldsymbol{x}))\right), s = 1, ..., S, \tag{17}$$

where H indicates Shannon entropy, with $f_s = g(\cdot, \boldsymbol{w}_s)$ for DE, rDE, and RMS, and $f_s \sim q(f; \boldsymbol{w}_1, ..., \boldsymbol{w}_M)$ for DE-GP. We normalize the uncertainty estimates into $[0, 1]$. For each threshold $\tau \in [0, 1]$, we plot the average test error for data with $\leq \tau$ uncertainty in Fig. 4-(Right). It is prominent that under various uncertainty thresholds, DE-GP makes fewer mistakes than the baselines, implying that DE-GP succeeds to assign relatively higher uncertainty for the OOD data.

CIFAR-10. Next, we apply DE-GP to the real-world image classification task CIFAR-10 (Krizhevsky et al., 2009). We consider the popular ResNet architectures (He et al., 2016) including ResNet-20 and ResNet-56. The ensemble size is fixed as 10. We split the data as training set, validation set, and test set of size 45000, 5000, 10000, respectively. We set $\beta = 0.1$, equivalent with the regularization coefficient on weight in rDE. We select α from $\{0.1, 0.05, 0.01, 0.005\}$ according to validation performance. We use a lite ResNet-20 architecture without BNs and residual connections to set up the prior NN-GP kernel for both the ResNet-20 and ResNet-56 based variational posteriors.

We present the in-distribution test accuracy in Table 1 and the error versus uncertainty plots on the combination of CIFAR-10 and SVHN test sets in Fig. 5. It is noteworthy that DE-GP is better than or on par with the practically-used, competing rDE in aspect of test accuracy. DE-GP ($\beta = 0$) shows unsatisfactory test accuracy, verifying the necessity of performing posterior regularization to penalize function complexity when using ultra-deep networks. The error versus uncertainty plots are similar to those for Fashion-MNIST, substantiating the universality of DE-GP.

We further test the trained methods on CIFAR-10 corruptions (Hendrycks & Dietterich, 2019), a challenging OOD generalization/robustness benchmark for deep models. As shown in Fig. 6 and Appendix B.3, DE-GP reveals smaller Expected Calibration Error (ECE) (Guo et al., 2017) and lower NLL at various levels of skew, reflecting its ability to make conservative predictions under corruptions and good OOD robustness.

More results for the deeper ResNet-110 architecture are provided in Fig. 12 in Appendix B.3.

Figure 5: Test error versus uncertainty plots for methods trained on CIFAR-10 and tested on both CIFAR-10 and SVHN with ResNet-20 (Left) or ResNet-56 (Right) architecture.

Figure 6: Expected Calibration Error on CIFAR-10 corruptions for models trained with ResNet-20 (Left) or ResNet-56 (Right) architecture. We summarize the results across 19 types of skew in each box.

Weight Sharing. We build a ResNet-20 with 10 classification heads and a shared feature extraction module to evaluate the methods under weight sharing. We set a larger value for α for DE-GP to induce higher magnitudes of functional diversity. The test accuracy and error versus uncertainty plots on CIFAR-10 are illustrated in Fig. 7. We exclude RMS from the comparison as it assumes i.i.d. basis functions which may be incompatible with weight sharing. DE-GP benefits from the diversity in function space, hence performs better than DE and rDE, which purely hinge on the diversity in weight space.

Figure 7: In-distribution test accuracy (Left) and error versus uncertainty plots on the combination CIFAR-10 and SVHN (Right) under weight sharing. (ResNet-20)

5.4 CONTEXTUAL BANDIT

Finally, we apply DE-GP to contextual bandit, an important decision-making task where the uncertainty helps to guide exploration. Following (Wang et al., 2019), we plug DE-GP into the BNNs based Thompson sampling algorithm. We reuse most of the settings for UCI regression. We leverage the GenRL library to build two contextual bandit problems Covertype and Mushroom (Riquelme et al., 2018). The cumulative reward is depicted in Fig. 8. As desired, DE-GP offers better uncertainty estimates and hence beats the baselines by clear margins. The potential of DE-GP in more reinforcement learning and Bayesian optimization scenarios deserves future investigation.

Figure 8: Cumulative reward varies w.r.t. round on Covertype (Left) and Mushroom (Right). Random corresponds to the Uniform algorithm. Summarized over 5 trails.

6 CONCLUSION

In this work, we attempt to establish a proper Bayesian justification for Deep Ensemble by drawing inspiration from the connection between BNNs and GPs. We propose to leverage the ensemble members to specify an adaptive GP approximate posterior, and perform variational inference directly in function space. We inherit some theoretical results from existing works on functional variational inference, and further develop a posterior regularization scheme to conveniently induce prior knowledge on function properties. We demonstrate how to penalize the function complexity based on this scheme and empirically show the necessity of doing so. The whole algorithm can be implemented easily and efficiently. Extensive experiments validate the effectiveness of our method. We hope this work may shed light on the development of more useful and more graceful BNNs.

ETHICS STATEMENT

This work proposes a Bayesian refinement of Deep Ensemble. Its potential positive impacts in the society are evident: its ability to enable better uncertainty estimation while maintaining predictive performance is crucial in industry, e.g., automatic driving, disease analysis, and financial applications. In this scenarios, the uncertainty estimates could be used to reject uncertain predictions, and raise the requirement of inviting humans into the decision process. As a fundamental research in machine learning, the negative consequences are not obvious. Though in theory any technique can be misused, it is not likely to happen at the current stage.

REPRODUCIBILITY STATEMENT

It is easy to reproduce the experiments given the code in the supplementary material.

REFERENCES

Sanjeev Arora, Simon S Du, Wei Hu, Zhiyuan Li, Ruslan Salakhutdinov, and Ruosong Wang. On exact computation with an infinitely wide neural net. *arXiv preprint arXiv:1904.11955*, 2019.

Peter Bartlett, Dylan J Foster, and Matus Telgarsky. Spectrally-normalized margin bounds for neural networks. *arXiv preprint arXiv:1706.08498*, 2017.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural network. In *International Conference on Machine Learning*, pp. 1613–1622, 2015.

Tianqi Chen, Emily Fox, and Carlos Guestrin. Stochastic gradient hamiltonian monte carlo. In *International conference on machine learning*, pp. 1683–1691. PMLR, 2014.

Zhijie Deng, Hao Zhang, Xiao Yang, Yinpeng Dong, and Jun Zhu. Bayesadapter: Being bayesian, inexpensively and reliably, via bayesian fine-tuning. *arXiv preprint arXiv:2010.01979*, 2020.

Zhijie Deng, Xiao Yang, Shizhen Xu, Hang Su, and Jun Zhu. Libre: A practical bayesian approach to adversarial detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 972–982, June 2021.

Michael Dusenberry, Ghassen Jerfel, Yeming Wen, Yian Ma, Jasper Snoek, Katherine Heller, Balaji Lakshminarayanan, and Dustin Tran. Efficient and scalable bayesian neural nets with rank-1 factors. In *International conference on machine learning*, pp. 2782–2792. PMLR, 2020.

Stanislav Fort, Huiyi Hu, and Balaji Lakshminarayanan. Deep ensembles: A loss landscape perspective. *arXiv preprint arXiv:1912.02757*, 2019.

Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning*, pp. 1050–1059, 2016.

Kuzman Ganchev, Joao Graça, Jennifer Gillenwater, and Ben Taskar. Posterior regularization for structured latent variable models. *The Journal of Machine Learning Research*, 11:2001–2049, 2010.

Adrià Garriga-Alonso, Carl Edward Rasmussen, and Laurence Aitchison. Deep convolutional networks as shallow gaussian processes. *arXiv preprint arXiv:1808.05587*, 2018.

Alex Graves. Practical variational inference for neural networks. In *Advances in Neural Information Processing Systems*, pp. 2348–2356, 2011.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. *arXiv preprint arXiv:1706.04599*, 2017.

David A Harville. Matrix algebra from a statistician's perspective, 1998.

Bobby He, Balaji Lakshminarayanan, and Yee Whye Teh. Bayesian deep ensembles via the neural tangent kernel. *arXiv preprint arXiv:2007.05864*, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pp. 1026–1034, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

José Miguel Hernández-Lobato and Ryan Adams. Probabilistic backpropagation for scalable learning of Bayesian neural networks. In *International Conference on Machine Learning*, pp. 1861–1869, 2015.

Geoffrey Hinton and Drew Van Camp. Keeping neural networks simple by minimizing the description length of the weights. In *ACM Conference on Computational Learning Theory*, 1993.

Jiri Hron, Alex Matthews, and Zoubin Ghahramani. Variational bayesian dropout: pitfalls and fixes. In *International Conference on Machine Learning*, pp. 2019–2028. PMLR, 2018.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pp. 448–456. PMLR, 2015.

Pavel Izmailov, Wesley J Maddox, Polina Kirichenko, Timur Garipov, Dmitry Vetrov, and Andrew Gordon Wilson. Subspace inference for bayesian deep learning. In *Uncertainty in Artificial Intelligence*, pp. 1169–1179. PMLR, 2020.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *arXiv preprint arXiv:1806.07572*, 2018.

Yiding Jiang, Behnam Neyshabur, Hossein Mobahi, Dilip Krishnan, and Samy Bengio. Fantastic generalization measures and where to find them. *arXiv preprint arXiv:1912.02178*, 2019.

Mohammad Emtiyaz Khan, Didrik Nielsen, Voot Tangkaratt, Wu Lin, Yarin Gal, and Akash Srivastava. Fast and scalable Bayesian deep learning by weight-perturbation in adam. In *International Conference on Machine Learning*, pp. 2616–2625, 2018.

Mohammad Emtiyaz Khan, Alexander Immer, Ehsan Abedi, and Maciej Korzepa. Approximate inference turns deep networks into gaussian processes. *arXiv preprint arXiv:1906.01930*, 2019.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems*, pp. 6402–6413, 2017.

Jaehoon Lee, Yasaman Bahri, Roman Novak, Samuel S Schoenholz, Jeffrey Pennington, and Jascha Sohl-Dickstein. Deep neural networks as gaussian processes. *arXiv preprint arXiv:1711.00165*, 2017.

Jaehoon Lee, Lechao Xiao, Samuel S Schoenholz, Yasaman Bahri, Roman Novak, Jascha Sohl-Dickstein, and Jeffrey Pennington. Wide neural networks of any depth evolve as linear models under gradient descent. *arXiv preprint arXiv:1902.06720*, 2019.

Qiang Liu and Dilin Wang. Stein variational gradient descent: A general purpose Bayesian inference algorithm. In *Advances in Neural Information Processing Systems*, pp. 2378–2386, 2016.

Christos Louizos and Max Welling. Structured and efficient variational deep learning with matrix gaussian posteriors. In *International Conference on Machine Learning*, pp. 1708–1716, 2016.

Xiuyuan Lu and Benjamin Van Roy. Ensemble sampling. *arXiv preprint arXiv:1705.07347*, 2017.

David JC MacKay. A practical Bayesian framework for backpropagation networks. *Neural Computation*, 4(3): 448–472, 1992.

David John Cameron Mackay. *Bayesian methods for adaptive models*. PhD thesis, California Institute of Technology, 1992.

Wesley J Maddox, Pavel Izmailov, Timur Garipov, Dmitry P Vetrov, and Andrew Gordon Wilson. A simple baseline for bayesian uncertainty in deep learning. In *Advances in Neural Information Processing Systems*, pp. 13153–13164, 2019.

Alexander G de G Matthews, Jiri Hron, Richard E Turner, and Zoubin Ghahramani. Sample-then-optimize posterior sampling for bayesian linear models. In *NeurIPS Workshop on Advances in Approximate Bayesian Inference*, 2017.

Alexander G de G Matthews, Mark Rowland, Jiri Hron, Richard E Turner, and Zoubin Ghahramani. Gaussian process behaviour in wide deep neural networks. *arXiv preprint arXiv:1804.11271*, 2018.

Radford M Neal. *Bayesian Learning for Neural Networks*. PhD thesis, University of Toronto, 1995.

Radford M Neal. Priors for infinite networks. In *Bayesian Learning for Neural Networks*, pp. 29–53. Springer, 1996.

Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. Norm-based capacity control in neural networks. In *Conference on Learning Theory*, pp. 1376–1401. PMLR, 2015.

Behnam Neyshabur, Srinadh Bhojanapalli, David McAllester, and Nathan Srebro. Exploring generalization in deep learning. *arXiv preprint arXiv:1706.08947*, 2017.

Roman Novak, Lechao Xiao, Jaehoon Lee, Yasaman Bahri, Greg Yang, Jiri Hron, Daniel A Abolafia, Jeffrey Pennington, and Jascha Sohl-Dickstein. Bayesian deep convolutional networks with many channels are gaussian processes. *arXiv preprint arXiv:1810.05148*, 2018.

Roman Novak, Lechao Xiao, Jiri Hron, Jaehoon Lee, Alexander A Alemi, Jascha Sohl-Dickstein, and Samuel S Schoenholz. Neural tangents: Fast and easy infinite neural networks in python. *arXiv preprint arXiv:1912.02803*, 2019.

Ian Osband, John Aslanides, and Albin Cassirer. Randomized prior functions for deep reinforcement learning. *arXiv preprint arXiv:1806.03335*, 2018.

Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua V Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. *arXiv preprint arXiv:1906.02530*, 2019.

Tim Pearce, Felix Leibfried, and Alexandra Brintrup. Uncertainty in neural networks: Approximately bayesian ensembling. In *International conference on artificial intelligence and statistics*, pp. 234–244. PMLR, 2020.

Ali Rahimi, Benjamin Recht, et al. Random features for large-scale kernel machines. In *NIPS*, volume 3, pp. 5. Citeseer, 2007.

Carlos Riquelme, George Tucker, and Jasper Snoek. Deep bayesian bandits showdown: An empirical comparison of bayesian deep networks for thompson sampling. *arXiv preprint arXiv:1802.09127*, 2018.

Hippolyt Ritter, Aleksandar Botev, and David Barber. A scalable laplace approximation for neural networks. In *6th International Conference on Learning Representations, ICLR 2018-Conference Track Proceedings*, volume 6. International Conference on Representation Learning, 2018.

Tim G. J. Rudner, Zonghao Chen, and Yarin Gal. Rethinking function-space variational inference in bayesian neural networks. In *Third Symposium on Advances in Approximate Bayesian Inference*, 2021. URL https://openreview.net/forum?id=KtY5qphxnCv.

Jiaxin Shi, Shengyang Sun, and Jun Zhu. Kernel implicit variational inference. In *International Conference on Learning Representations*, 2018.

Jiaxin Shi, Mohammad Emtiyaz Khan, and Jun Zhu. Scalable training of inference networks for gaussian-process models. In *International Conference on Machine Learning*, pp. 5758–5768. PMLR, 2019.

Shengyang Sun, Guodong Zhang, Jiaxin Shi, and Roger Grosse. Functional variational Bayesian neural networks. In *International Conference on Learning Representations*, 2019.

Ziyu Wang, Tongzheng Ren, Jun Zhu, and Bo Zhang. Function space particle optimization for Bayesian neural networks. In *International Conference on Learning Representations*, 2019.

Max Welling and Yee W Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pp. 681–688, 2011.

Christopher Williams and Matthias Seeger. Using the nyström method to speed up kernel machines. In *Proceedings of the 14th annual conference on neural information processing systems*, number CONF, pp. 682–688, 2001.

Andrew Gordon Wilson and Pavel Izmailov. Bayesian deep learning and a probabilistic perspective of generalization. *arXiv preprint arXiv:2002.08791*, 2020.

Andrew Gordon Wilson, Zhiting Hu, Ruslan Salakhutdinov, and Eric P Xing. Deep kernel learning. In *Artificial intelligence and statistics*, pp. 370–378. PMLR, 2016.

Max A Woodbury. *Inverting modified matrices*. Statistical Research Group, 1950.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

Greg Yang. Scaling limits of wide neural networks with weight sharing: Gaussian process behavior, gradient independence, and neural tangent kernel derivation. *arXiv preprint arXiv:1902.04760*, 2019.

Guodong Zhang, Shengyang Sun, David Duvenaud, and Roger Grosse. Noisy natural gradient as variational inference. In *International Conference on Machine Learning*, pp. 5847–5856, 2018.

Ruqi Zhang, Chunyuan Li, Jianyi Zhang, Changyou Chen, and Andrew Gordon Wilson. Cyclical stochastic gradient mcmc for bayesian deep learning. *arXiv preprint arXiv:1902.03932*, 2019.

Jun Zhu, Ning Chen, and Eric P Xing. Bayesian inference with posterior regularization and applications to infinite latent svms. *The Journal of Machine Learning Research*, 15(1):1799–1847, 2014.

A PENALIZE FUNCTION COMPLEXITY IN MULTI-CLASS CLASSIFICATION

In the multi-class classification scenario where $y \in \{1, 2, ..., C\}$ and $f, g_i : \mathcal{X} \to \mathbb{R}^C$, we use the loss $\ell(f(\boldsymbol{x}), y) = \mathbf{1}_{f(\boldsymbol{x})[y] < \max_{y' \neq y} f(\boldsymbol{x})[y']}$ to measure prediction error where $f(\boldsymbol{x})[j]$ denotes j-th coordinate of $f(\boldsymbol{x})$. The distinct difference between this scenario and the binary classification scenario is that in this setting, $\zeta(\boldsymbol{x})$ is a vector-valued function:

$$\zeta(\boldsymbol{x}) = \frac{1}{\sqrt{M}} \sum_{i=1}^{M} \epsilon_i(g_i(\boldsymbol{x}) - m_q(\boldsymbol{x})) + \sqrt{\lambda}\boldsymbol{\epsilon}_0, \tag{18}$$

where $\boldsymbol{\epsilon}_0 \sim \mathcal{N}(\mathbf{0}, \mathbf{I}_C)$ and $\epsilon_i \sim \mathcal{N}(0, 1), i = 1, ..., M$. We then make a mild assumption to simplify the analysis.

Assumption 1. *For any $(\boldsymbol{x}, y) \in \mu$, the elements on the diagonal of $k_q(\boldsymbol{x}, \boldsymbol{x})$ have the same value.*

This assumption implies that for any $j, j' \in \{1, ..., C\}$,

$$\frac{1}{M} \sum_{i=1}^{M} (g_i(\boldsymbol{x})[j] - m_q(\boldsymbol{x})[j])^2 + \lambda = \frac{1}{M} \sum_{i=1}^{M} (g_i(\boldsymbol{x})[j'] - m_q(\boldsymbol{x})[j'])^2 + \lambda. \tag{19}$$

I.e.,

$$\sum_{i=1}^{M} (g_i(\boldsymbol{x})[j] - m_q(\boldsymbol{x})[j])^2 = \sum_{i=1}^{M} (g_i(\boldsymbol{x})[j'] - m_q(\boldsymbol{x})[j'])^2. \tag{20}$$

Therefore, $\zeta(\boldsymbol{x})$ possesses the same variance across its output coordinates and becomes a random guess classifier. Based on this, we have $\mathbb{E}_{q(f)}\ell(\zeta(\boldsymbol{x}), y) = \mathbb{E}_{\epsilon_0,...,\epsilon_M}\ell(\zeta(\boldsymbol{x}), y) = (C-1)/C$. We can then derive a similar conclusion to that in Section 3.3.

The validity of Assumption 1. When the data dimension $|\mathcal{X}|$ is high and the number of training data n is finitely large, with zero probability the sampled data $(\boldsymbol{x}, y) \sim \mu$ resides in the training set. Therefore, only the KL divergence term of the fELBO explicitly affects the predictive uncertainty at $\boldsymbol{x}$. Because the NN-GP prior possesses a diagonal structure, it is hence reasonable to make the above assumption.

B MORE OF EXPERIMENTS

We provide more experimental details and results in this section. In all experiments, the number of MC samples for estimating the expected log-likelihood (i.e., U in Line 7 of Algorithm 1) is set as 256. Unless otherwise stated, we set the regularization constant λ as 0.05 times of the average eigenvalue of the central covariance matrices, and set the weight and bias variance for defining the NN-GP prior kernel at each layer as $2/fan\_in$ and 0.01, where fan_in is the number of input features, as suggested by He initialization (He et al., 2015).

B.1 DETAILED SETTINGS

Illustrative regression. For the problem on $y = x^3/4 + \epsilon, \epsilon \sim \mathcal{N}(0, 0.1)$, we randomly sample 20 data points from $[-1.5, -0.6] \cup [0.6, 1.5]$. For the problem on $y = x\sin 5x + \epsilon, \epsilon \sim \mathcal{N}(0, 0.2)$, we use 6 data points $\{-0.8, -0.1, 0.02, 0.2, 0.6, 0.8\}$ following (Pearce et al., 2020). For optimizing the DNN basis functions, we use an Adam (Kingma & Ba, 2014) optimizer with 0.003 learning rate. The optimization takes 300 iterations. We set hidden size as 64 for the architecture of the prior NN-GP kernel for speedup. The regularization constant λ is set as $1e-4$ times of the average eigenvalue of the central covariance matrices.

UCI regression. We pre-process the UCI data by standard normalization. We set the variance for data noise and the weight variance for the prior kernel following (Pearce et al., 2020). The batch size for stochastic training is 256. We use an Adam optimizer to optimize for 1000 epochs. The learning rate is initialized as 0.01 and decays by 0.99 every 5 epochs.

Fashion-MNIST classification. The used architecture is Conv(32, 3, 1)-BN-ReLU-MaxPool(2)-Conv(64, 3, 0)-BN-ReLU-MaxPool(2)-Linear(256)-ReLU-Linear(10), where Conv(x, y, z) represents

NN-GP   DE-GP (our)   DE   rDE   RMS   MC dropout

Figure 9: Prediction on toy data from $y = x \sin 5x + \epsilon, \epsilon \sim \mathcal{N}(0, 0.2)$. The two rows correspond to MLPs with 2 hidden layers of 64 units and MLPs with 3 hidden layers of 512 units, respectively. DE-GP provides calibrated uncertainty estimates and is consistently behaved as mode complexity increases.

Figure 10: Negative log-likelihood on CIFAR-10 corruptions for models trained with ResNet-20 (Left) or ResNet-56 (Right) architecture. We summarize the results across 19 types of skew in each box.

a 2D convolution with x output channels, kernel size y, and padding z. The batch size for training data is 64. The batch size for extra measurement points is 0. We use an SGD optimizer to optimize for 24 epochs. The learning rate is initialized as 0.1 and follows a cosine decay schedule. We use an Adam optimizer with $1e-3$ learning rate to optimize the temperature. We use 1000 MC samples to estimate the posterior predictive and the epistemic uncertainty, because the involved computation is only the cheap softmax transformation on the sampled function values.

CIFAR-10 classification. We perform data augmentation including random horizontal flip and random crop. The batch size for training data is 128. The batch size for extra measurement points is 0. We use a SGD optimizer with 0.9 momentum to optimize for 200 epochs. The learning rate is initialized as 0.1 and decays by 0.1 at 100-th and 150-th epochs. We use an Adam optimizer with $1e-3$ learning rate to optimize the temperature. We use 1000 MC samples to estimate the posterior predictive and the epistemic uncertainty.

Contextual bandit. We use MLPs with 2 hidden layers of 256 units. The batch size for training data is 512. The batch size for extra measurement points is 0. We update the model (i.e., the agent) for 100 epochs with an Adam optimizer every 50 rounds. We set $\alpha = 1$ and $\beta = 0$ without tuning.

B.2 MORE RESULTS ON ILLUSTRATIVE REGRESSION

We depict the results on $y = x \sin 5x + \epsilon, \epsilon \sim \mathcal{N}(0, 0.2)$ problem in Fig. 9, which are consistently with those in Fig. 1.

B.3 MORE RESULTS ON CIFAR-10 CLASSIFICATION

We plot the negative log-likelihood and test accuracy on CIFAR-10 corruptions for models trained with ResNet-20 and ResNet-56 in Fig. 10 and Fig. 11. As shown, DE-GP outperforms the baselines in aspect of negative log-likelihood, but yields similar test accuracy to the baselines. Recapping the results in Fig. 6, DE-GP indeed has improved OOD robustness, but may still face problems in OOD generalization.

We then conduct experiments with the deeper ResNet-110 architecture. Due to resource constraint, we use 5 ensemble members. The other settings are roughly the same as those for ResNet-56. The results are offered in Fig. 12, which validate the effectiveness of DE-GP for large networks.

Figure 11: Test accuracy on CIFAR-10 corruptions for models trained with ResNet-20 (Left) or ResNet-56 (Right) architecture. We summarize the results across 19 types of skew in each box.

Figure 12: (Left): Expected Calibration Error on CIFAR-10 corruptions for models trained with ResNet-110 architecture. We summarize the results across 19 types of skew in each box. (Right): Test error versus uncertainty plots for methods trained on CIFAR-10 and tested on both CIFAR-10 and SVHN with ResNet-110 architecture. Ensemble size is fixed as 5 for these experiments.

B.4 ABLATION STUDY ON THE ARCHITECTURE OF PRIOR KERNEL

We perform an ablation study on the architecture for defining the prior NN-GP kernel, with the results listed in Table 2. Surprisingly, using a prior kernel with the cheap ResNet-20 architecture results in DE-GP with better test accuracy. We deduce this is because a deeper prior architecture induces more complex, black-box correlation for the function, which may lead to over-regularization.

Table 2: Ablation study on the architecture of the prior NN-GP kernel for training DE-GP.

Prior kernel architecture / DE-GP architecture	ResNet-20	ResNet-56	ResNet-110
ResNet-56 (10 ensemble member)	95.50%	95.28%	-
ResNet-110 (5 ensemble member)	95.54%	-	94.87%