Patch Vestiges in the Adversarial Examples Against Vision Transformer Can Be Leveraged for Adversarial Detection

blind review

blind review

Abstract

Vision Transformer (ViT), a Transformer-based architecture that divides images into patches, can catch up with or surpass convolution-based networks in multiple Computer Vision tasks. However, ViT is also vulnerable in the face of adversarial examples (AEs). Thus the topic around the attack and defense of ViT becomes very rewarding. Recent studies have found that the AEs against ViT seem to have grid-like textures that coincide with the patches. We confirm such sensation is true. In this paper, we show that these grid-like textures are the remained vestiges due to the patch division of ViT. We name them Patch Vestiges. We propose statistics to measure the sizes of Patch Vestiges in the images or AEs quantitatively. We also build a linear-regression classifier to detect the AEs against ViT practically via the proposed statistics. The experiments show that the performance of the simple classifier can even match some recent adversarial detection methods, suggesting that when trying to attack ViT or detect the AEs against ViT, Patch Vestiges are worth considering about as a critical factor.

Transformer (Vaswani et al. 2017) is almost based on self-attention mechanisms and fully connected layers. It creatively subverts the architecture of RNNs and realizes the state-of-the-art performances on almost all Natural Language Processing tasks. It is naturally hoped that Transformer can be applied to the field of Computer Vision. However, Transformer requires a sequential input that has a quite different shape from an image. Vision Transformer (ViT) (Dosovitskiy et al. 2020) overcomes the difficulty by dividing an image into small patches and linking them into a sequence. With the help of Transformer, ViT achieves excellent performances in many Computer Vision tasks.

Although ViT is effective, it has similar weakness with CNNs in front of the adversarial examples. Adversarial Examples (AEs) (Szegedy et al. 2013) are images with artificial perturbations that are small enough to fool the human eyes but can make deep neural networks output wrong results. Some preliminary studies (Bhojanapalli et al. 2021; Shao et al. 2021; Mahmood, Mahmood, and van Dijk 2021) show that ViT is vulnerable to all common AEs, and even weaker than CNNs under some attacks. The good news is that it is difficult for the AEs against CNNs to transfer to ViT

directly (Shao et al. 2021; Naseer et al. 2021; Aldahdooh, Hamidouche, and Déforges 2021). Thus it is meaningful to study the unique natures of the AEs against ViT.

To the human eye, the magnified adversarial perturbations of the AEs against ViT seem to have grid-like textures and exhibit some periodicity and repetition (Bhojanapalli et al. 2021), as shown in Figure 1. This is the initial inspiration of this paper. A very intuitive conjecture is that the AEs against ViT may also be divided into patches. In this paper, we confirm this conjecture is true and bring up the concept Patch Vestiges. We define Patch Vestiges as the abnormalities of the AEs against ViT that are caused by the patch division.

We also find a method to measure Patch Vestiges quantitatively. We propose *Leaps* to measure the step changes between two adjacent pixels in different patches. We assume the step changes are the key points of Patch Vestiges. Additionally, we propose statistics PV, IPC and NCC based on *Leaps* and build a binary linear-regression classifier with them. The experiments show that our approximations of *Leaps* is successful and that by our proposed statistics PV, IPC and NCC the linear-regression classifier can detect the AEs against ViT effectively.

We sum up the key contributions of this paper as follows:

- We substantiate the human instinct that the patches used in Vision Transformer remain vestiges in the adversarial examples.

- We bring up the concept Patch Vestiges and find a quantitative measurement for them.

- We prove that Patch Vestiges can be the critical weakness for the adversarial examples against ViT.

Related Work

Vision Transformers Vision Transformer (ViT) (Dosovitskiy et al. 2020) is the first to successfully leverage Transformer (Vaswani et al. 2017) in Computer Vision tasks by dividing images into patches. DeiT (Touvron et al. 2021) uses a similar model structure but adds a new distillation token . T2T-ViT (Yuan et al. 2021) recursively integrates adjacent tokens to better extract the low-level image features.Swin Transformer (Liu et al. 2021) shows the superiority of Transformer and defeats CNN-based models in many tasks by bringing in the shifted window scheme.

| (a) ResNet / ViT "plane" | (b) ResNet AE "dog" | (c) ResNet AE perturb. | (d) ViT AE "dog" | (e) ViT AE perturb. |

Figure 1: A clean image and its AEs and according adversarial perturbations. The image "plane" is chosen from the ILSVRC2012 (ImageNet) dataset (Russakovsky et al. 2015). ResNet and ViT both give the correct classification when the input is clean. The AEs generated by PGD $\ell_\infty = 8$ make ResNet and ViT both output the wrong category "dog". The adversarial perturbations are effect images magnified from the real values to make them explicit.

Adversarial Detection Bayesian uncertainty (BU) and kernel density (KD) are previously proposed to detect the out-of-manifold points (Feinman et al. 2017). RCE (Pang et al. 2018) uses a new Reverse Cross-Entropy based on KD to better distance the clean images from the AEs. LID (Ma et al. 2018) detects the AEs by the local sparseness. A Mahalanobis distance based score is afterwards proposed (Lee et al. 2018). Under the assumption that AEs are out of the manifold of the natural scenes, natural scene statistics (NSS) are used in the detector (Kherchouche et al. 2020). More recently, LiBRe (Deng et al. 2021) leverages Bayesian neural networks with refined training procedures for adversarial detection.

Methodology

Despite the recent excellent improvements of ViT, we focus on the vanilla ViT model (Dosovitskiy et al. 2020) because the fixed division makes the research stable. The vanilla ViT divides an image into $n \times n$ patches in a grid shape, making several horizontal and vertical dividing lines. Intuitively, the adversarial perturbations of the adjacent pixels astride the dividing lines should have step changes. We measure the step changes by *Leaps*. To calculate *Leaps*, we approximately assume the pixel values of the clean image and the adversarial perturbations inside the patches vary mildly, and only the adversarial perturbations across the patches are violent, as shown in Figure 2(a).

| (a) *Leaps* | (b) PV, IPC and NCC |

Figure 2: (a) The illustrative diagrams of *Leaps*. (b) The example positions of the proposed statistics PV, IPC and NCC.

We calculate *Leaps* as follows. We denote the change of the pixel values between the adjacent pixels i and j as $G(i, j)$. For both clean images and inside-patch adversarial perturbations, a center G should be equal to the average of its bilateral Gs. But for adversarial perturbations astride the dividing lines, the equality does not hold. Thus we define

$$Leap(i, \vdash)$$
$$= \left| G(i, i\oplus1) - \frac{(G(i, i\ominus1) + G(i\oplus1, i\oplus2))}{2} \right|, \quad (1)$$

where $\vdash$ means the alternative direction that is either horizontal or vertical and $i\oplus n, i\ominus n$ means moving n pixels forward or backward along the direction $\vdash$. $Leap(i, \vdash)$ shows the non-smoothness of the local changes G around the pixel i. If $Leap(i, \vdash)$ is higher and i and $i\oplus1$ stride over a dividing line, there will be a higher possibility that the given image is an AE against ViT.

Based on *Leap*, we propose PV, IPC and NCC, standing for Patch Vestiges, Inside-Patch Contrast and Natural Change Contrast respectively. PV consists of *Leaps* astride the dividing lines, IPC consists of *Leaps* fully inside the patches, and NCC consists of all the adjacent changes (see Figure 2(b)). More precise definitions are:

$$PV(X) = Ave_{\vdash \in \{-, |\}, i \in PB(X, \vdash)}(Leap(i, \vdash)),$$
$$IPC(X) = Ave_{\vdash \in \{-, |\}, i \in PI(X)}(Leap(i, \vdash)), \quad (2)$$
$$NCC(X) = Ave_{\vdash \in \{-, |\}, i \in X}(|G(i, i\oplus1)|),$$

where Ave means the average, $PB(X, \vdash)$ means the pixel set that i and $i\oplus1$ stride over a dividing line, and $PI(X)$ means the pixel set that $i, i\oplus1, i\oplus2, i\ominus1$ are in the same patch. Under this definition, PV will be much higher than IPC only for the images with strong Patch Vestiges. NCC measures the natural pixel fluctuations of clean images and is a baseline for PV and IPC.

We also leverage linear regression and build a simple binary classifier $y = a_1PV + a_2IPC + a_3NCC + a_4$. If PV is very different from IPC in the AEs against ViT, the binary classifier will have high capacity to distinguish those AEs from clean images. And since PV, IPC and NCC are all statistics, if the the simple linear classifier works well, DNNs should be more capable to dig out the artifacts in Patch Vestiges.

(a) Clean images   (b) PGD AEs against ResNet   (c) PGD AEs against ViT

Figure 3: The distributions of the statistics PV, IPC and NCC of the images or AEs on the CIFAR-10 training set. The AEs are generated by the PGD $\ell_\infty = 8$ attack. The victim models are ResNet and ViT respectively. The solid lines in the figures represent the frequencies of the statistics accumulated by 100 groups. The dashed lines are the averages of the according statistics.

Experimental Setups

Datasets We use the CIFAR-10 (Krizhevsky 2009) dataset for our experiments. The CIFAR-10 dataset has 50,000 training images, 10,000 test images and 10 categories. The size of each image is 3×32×32.

Attacks We use the white-box adversarial attack methods FGSM (Goodfellow, Shlens, and Szegedy 2015), BIM (Kurakin, Goodfellow, and Bengio 2017a), PGD (Kurakin, Goodfellow, and Bengio 2017b) and DeepFool (DF) (Moosavi-Dezfooli, Fawzi, and Frossard 2016). We restrict all the AEs with $\ell_\infty = 8$. Notice that DF originally generates AEs with $\ell_\infty \leq 8$. We rescale the perturbations and use DF* to denote the modification. We run all PGD attacks for 20 iterations. We use the AEs of PGD to train the linear-regression classifier and directly test it on the AEs of all the attack methods.

Victim Models The major victim model is vanilla Vision Transformer (ViT) (Dosovitskiy et al. 2020). We also use ResNet (He et al. 2016) as a contrast model. ViT used in the experiments has a 4×4 patch size, 6 layers and 16 heads for Multi-Head Attentions. The ResNet model in the experiments has 56 layers.

Compared Methods We use LID (Ma et al. 2018) and NSS (Kherchouche et al. 2020) for comparison. Notice that the settings of the methods and not in accord with ours strictly. For example, our classifier only requires the input image, the ViT logits and the patch size. The comparison is more of a reference.

Environments We build our project on the open-source toolbox ARES (Dong et al. 2020) and make references to the codes of TRADES (Zhang et al. 2019). We run the experiments on GeForce RTX 2080 Ti.

Results

We first compare the distributions and the averages of PV, IPC and NCC over the clean images, the AEs using the PGD attack against ResNet and those against ViT. All the images and AEs are from the training set of CIFAR-10. The results are shown in Figure 3. We observe that for the clean images and the AEs against ResNet, the distributions of PV and IPC are approximate. But PV in the AEs against ViT is much larger than IPC. We use the T'-test and confirm PV is significantly larger than IPC and NCC (p<5e-4) in Figure 3(c). We can also observe in Figure 3(c) that there are large area where the distribution of PV is not overlapped with IPC and NCC. The results prove that the assumptions and approximations about $Leaps$ is effective, and illustrate that Patch Vestiges are unique and significant characteristics of the AEs against ViT.

Model	KR	DR			
		FGSM	BIM	PGD	DF*
LID	**96.17**	57.36	85.17	**94.51**	**78.64**
NSS	93.29	87.10	66.26	62.09	61.55
Ours	86.90	**94.60**	**87.74**	88.11	74.62

Table 1: The KR (%) of the clean images and the DR (%) of the different AEs of the compared models. DF* is the DF modification introduced in the experimental setup section. All the AEs have perturbations with $\ell_\infty = 8$.

We also train a linear classifier using the PGD attack and compare the keeping rates (KR, the ratio of classifying clean images correctly) and the detection rates (DR, the ratio of classifying AEs correctly) under different attacks. Table 1 shows the results. We observe that the simple linear-regression classifier, although not state-of-the-art, is comparable enough with the mature adversarial detection methods. This again suggests that Patch Vestiges are significant. The results also show that Patch Vestiges are the intrinsic attributes of the AEs against ViT and are easily transferred from one attack method to another.

Conclusion

In this paper, we confirm the human intuition that the division of the patches by ViT remains large vestiges in the adversarial examples. We bring up the concept Patch Vestiges to measure to what extend the patches leaves over the

its trace. We also quantitatively show that Patch Vestiges can be leveraged to detect whether an image is an adversarial example against ViT or a clean one.

Besides the practical significance, our work can also promote people's thinking. Is a more complicated structure more vulnerable or safe? In many area, the answer is "vulnerable". But in this paper, the artifacts of ViT on the contrary improve its robustness. Perhaps it can not be easily answered in the AE area.

References

Aldahdooh, A.; Hamidouche, W.; and Déforges, O. 2021. Reveal of Vision Transformers Robustness against Adversarial Attacks. arXiv:2106.03734.

Bhojanapalli, S.; Chakrabarti, A.; Glasner, D.; Li, D.; Unterthiner, T.; and Veit, A. 2021. Understanding Robustness of Transformers for Image Classification. arXiv:2103.14586.

Deng, Z.; Yang, X.; Xu, S.; Su, H.; and Zhu, J. 2021. LiBRe: A Practical Bayesian Approach to Adversarial Detection. In *Proceedings of the 2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 972–982.

Dong, Y.; Fu, Q.-A.; Yang, X.; Pang, T.; Su, H.; Xiao, Z.; and Zhu, J. 2020. Benchmarking Adversarial Robustness on Image Classification. In *Proceedings of the 2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Dosovitskiy, A.; Beyer, L.; Kolesnikov, A.; Weissenborn, D.; Zhai, X.; Unterthiner, T.; Dehghani, M.; Minderer, M.; Heigold, G.; Gelly, S.; Uszkoreit, J.; and Houlsby, N. 2020. An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale. arXiv:2010.11929.

Feinman, R.; Curtin, R. R.; Shintre, S.; and Gardner, A. B. 2017. Detecting Adversarial Samples from Artifacts. arXiv:1703.00410.

Goodfellow, I. J.; Shlens, J.; and Szegedy, C. 2015. Explaining and Harnessing Adversarial Examples. In *Proceedings of the International Conference on Learning Representations (ICLR)*.

He, K.; Zhang, X.; Ren, S.; and Sun, J. 2016. Deep Residual Learning for Image Recognition. In *Proceedings of the 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 770–778.

Kherchouche, A.; Fezza, S. A.; Hamidouche, W.; and Déforges, O. 2020. Detection of Adversarial Examples in Deep Neural Networks with Natural Scene Statistics. In *Proceedings of the 2020 International Joint Conference on Neural Networks (IJCNN)*, 1–7.

Krizhevsky, A. 2009. Learning Multiple Layers of Features from Tiny Images.

Kurakin, A.; Goodfellow, I. J.; and Bengio, S. 2017a. Adversarial Examples in the Physical World. In *Workshop of the International Conference on Learning Representations (ICLR)*.

Kurakin, A.; Goodfellow, I. J.; and Bengio, S. 2017b. Adversarial Machine Learning at Scale. In *Proceedings of the International Conference on Learning Representations (ICLR)*.

Lee, K.; Lee, K.; Lee, H.; and Shin, J. 2018. A Simple Unified Framework for Detecting Out-of-Distribution Samples and Adversarial Attacks. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Liu, Z.; Lin, Y.; Cao, Y.; Hu, H.; Wei, Y.; Zhang, Z.; Lin, S. C.-F.; and Guo, B. 2021. Swin Transformer: Hierarchical Vision Transformer using Shifted Windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*.

Ma, X.; Li, B.; Wang, Y.; Erfani, S. M.; Wijewickrema, S. N. R.; Houle, M. E.; Schoenebeck, G. R.; Song, D. X.; and Bailey, J. 2018. Characterizing Adversarial Subspaces Using Local Intrinsic Dimensionality. In *Proceedings of the International Conference on Learning Representations (ICLR)*.

Mahmood, K.; Mahmood, R.; and van Dijk, M. 2021. On the Robustness of Vision Transformers to Adversarial Examples. arXiv:2104.02610.

Moosavi-Dezfooli, S.-M.; Fawzi, A.; and Frossard, P. 2016. DeepFool: A Simple and Accurate Method to Fool Deep Neural Networks. In *Proceedings of the 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2574–2582.

Naseer, M.; Ranasinghe, K.; Khan, S. H.; Khan, F. S.; and Porikli, F. M. 2021. On Improving Adversarial Transferability of Vision Transformers. arXiv:2106.04169.

Pang, T.; Du, C.; Dong, Y.; and Zhu, J. 2018. Towards Robust Detection of Adversarial Examples. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Russakovsky, O.; Deng, J.; Su, H.; Krause, J.; Satheesh, S.; Ma, S.; Huang, Z.; Karpathy, A.; Khosla, A.; Bernstein, M. S.; Berg, A. C.; and Fei-Fei, L. 2015. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision*, 115: 211–252.

Shao, R.; Shi, Z.; Yi, J.; Chen, P.-Y.; and Hsieh, C.-J. 2021. On the Adversarial Robustness of Visual Transformers. arXiv:2103.15670.

Szegedy, C.; Zaremba, W.; Sutskever, I.; Bruna, J.; Erhan, D.; Goodfellow, I. J.; and Fergus, R. 2013. Intriguing Properties of Neural Networks. *Computer Science*.

Touvron, H.; Cord, M.; Douze, M.; Massa, F.; Sablayrolles, A.; and J'egou, H. 2021. Training Data-Efficient Image Transformers & Distillation through Attention. In *ICML*.

Vaswani, A.; Shazeer, N. M.; Parmar, N.; Uszkoreit, J.; Jones, L.; Gomez, A. N.; Kaiser, L.; and Polosukhin, I. 2017. Attention is All you Need. arXiv:1706.03762.

Yuan, L.; Chen, Y.; Wang, T.; Yu, W.; Shi, Y.; Jiang, Z.-H.; Tay, F. E. H.; Feng, J.; and Yan, S. 2021. Tokens-to-Token ViT: Training Vision Transformers From Scratch on ImageNet. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 558–567.

Zhang, H. R.; Yu, Y.; Jiao, J.; Xing, E. P.; Ghaoui, L. E.; and Jordan, M. I. 2019. Theoretically Principled Trade-off between Robustness and Accuracy. In *Proceedings of the International Conference on Machine Learning (ICML)*.