RAAR: Retrieval Augmented Agentic Reasoning for Cross-Domain Misinformation Detection

Abstract

Cross-domain misinformation detection is challenging, as misinformation arises across domains with substantial differences in knowledge and discourse. Existing methods often rely on single-perspective cues and struggle to generalize to challenging or underrepresented domains, while reasoning large language models (LLMs) though effective on complex tasks, are limited to same-distribution data. To address these gaps, we introduce RAAR, the first retrieval-augmented agentic reasoning framework for cross-domain misinformation detection. To enable cross-domain transfer beyond same-distribution assumptions, RAAR retrieves multi-perspective source-domain evidence aligned with each target sample's semantics, sentiment, and writing style. To overcome single-perspective modeling and missing systematic reasoning, RAAR constructs verifiable multi-step reasoning paths through specialized multi-agent collaboration, where perspective-specific agents produce complementary analyses and a summary agent integrates them under verifier guidance. RAAR further applies supervised fine-tuning and reinforcement learning to train a single multi-task verifier to enhance verification and reasoning capabilities. Based on RAAR, we trained the RAAR-8b and RAAR-14b models. Evaluation on three cross-domain misinformation detection tasks shows that RAAR substantially enhances the capabilities of the base models and outperforms other cross-domain methods, advanced LLMs, and LLM-based adaptation approaches. The project is open-sourced here.

1 Introduction

Misinformation poses a growing threat across diverse domains such as public health, politics, and finance, where false claims frequently emerge in new contexts (Gradoń et al., 2021). In realistic scenarios, cross-domain misinformation detection involves training on known domains and predicting misinformation in unseen domains (Silva et al., 2021). Unlike general tasks, this setting requires not only effective feature learning and representation, but also an understanding of systematic cross-domain differences in knowledge structures and discourse characteristics (Doumas et al., 2022). These differences induce substantial distribution shifts that render surface-level cues unreliable, making cross-domain misinformation detection a particularly challenging problem that demands reasoning over ambiguous and implicit evidence. Recent advances in reasoning capabilities have led to significant breakthroughs in a range of complex tasks (Sun et al., 2025), suggesting strong potential for improving cross-domain generalization.

With the rise of large language models (LLMs), techniques such as few-shot learning (Singal et al., 2024), instruction tuning (Liu et al., 2024a, 2025c), and retrieval-augmented generation (RAG) (Niu et al., 2024) have been applied to misinformation detection, including adaptations of RAG and multi-agent approaches for cross-domain settings (Liu et al., 2025b; Li et al., 2025). However, existing approaches have several limitations. First, ML and DL methods require separate fine-tuning or task-specific prompts for each misinformation task, meaning a single model can only handle one task and cannot generalize across tasks. Second, most methods analyze data from a single perspective, failing to integrate multiple dimensions such as sentiment, writing style, and semantics, which reduces effectiveness in complex or challenging domains. Third, systematic reasoning over ambiguous or implicit evidence is largely absent, further hindering performance in underrepresented domains. These limitations underscore the need for methods that can perform systematic, cross-domain reasoning over multidimensional and ambiguous evidence.

Moreover, reasoning LLMs such as GPT-o1 and DeepSeek-R1 (Guo et al., 2025) have been widely applied in domains such as finance (Qian

et al., 2025), mental health (Dai et al., 2025), and medicine (Chen et al., 2025). However, these models primarily perform direct inference on data from the same distribution, focusing on information within a single domain. This makes it difficult to handle the substantial differences in knowledge structures and discourse encountered in cross-domain misinformation detection. Moreover, relying on a single model to construct reasoning paths limits their ability to exploit multidimensional, domain-specific information for complex tasks, constraining performance in unseen domains.

To address the research gaps, we propose RAAR, the first retrieval-augmented agentic reasoning framework for cross-domain misinformation detection, leveraging retrieval-augmented agentic reasoning with supervised fine-tuning (SFT) and reinforcement learning (RL), allowing cross-domain knowledge transfer, multidimensional reasoning, and multi-task optimization. RAAR incorporates three key stages to address the limitations of existing methods. (1) Retrieval augmented data building: to overcome the reliance on same-distribution assumptions and provide rich cross-domain evidence, we retrieve source-domain data similar in semantics, sentiment, and style for each target-domain sample, enabling multi-perspective reference for subsequent analysis. (2) Multi-Agent collaborated reasoning path building: to perform systematic, multidimensional reasoning over complex and ambiguous evidence, specialized sub-agents analyze semantic, sentiment, and stylistic aspects, while a summary agent integrates their outputs and conducts additional reasoning under verifier guidance. (3) Model optimization: to improve prediction accuracy and cross-domain reasoning, we apply SFT and RL, enabling a single model to handle multiple misinformation tasks (fake news, rumors, conspiracy theories) and overcoming the single-task limitation of traditional models.

Based on the RAAR framework, we trained RAAR-8b and RAAR-14b based on Qwen3-8b and Qwen3-14b, respectively. Both models achieve substantial improvements over the original base models and outperform other cross-domain methods, advanced LLMs, and LLM-adapted models. RAAR-14b surpasses the latest DeepSeek-V3.2-Reasoner in average F1 performance.

Our main contributions are as follows:
- We propose RAAR, the first reasoning framework for cross-domain misinformation detection, leveraging retrieval-augmented agentic reasoning with SFT and RL for cross-domain knowledge transfer and multi-step reasoning.
- We employ multi-agent collaboration to integrate multiple perspectives into coherent reasoning paths, significantly enhancing cross-domain reasoning capabilities.
- Experiments show that RAAR significantly boosts cross-domain misinformation detection, surpassing existing methods and advanced LLMs, and validating retrieval augmentation and multi-agent reasoning.

2 Method

This section presents the RAAR framework, with its overall structure shown in Figure 1. Starting with task formulation, we then describe its three key stages in detail.

2.1 Task Formulation

Cross-domain misinformation detection aims to use labeled data from source domains to verify information in an unseen target domain. Specifically, given multiple source-domain datasets D_s and a target-domain misinformation dataset D_t. The goal is to leverage source-domain knowledge to improve detection performance in a more challenging target domain. Formally, we define $\{D_s, D_t\} \subseteq D = \{(x, y^*)\}$, where x denotes a text content and y^* is the corresponding label. Here, D_t denotes the more challenging domains selected. The whole process includes three main stages.

Stage 1. Retrieval Augmented Data Building: retrieve source-domain data similar in semantics $\{(x_{sem}^s, y_{sem}^s)\}$, sentiment $\{(x_{sen}^s, y_{sen}^s)\}$, and style $\{(x_{sty}^s, y_{sty}^s)\}$ for each target-domain sample $\{(x^t, y^*)\}$:

$$D_{ra} = Retrieval(D) = \{(x_{ra}, y^*)\}, \quad (1)$$

where $x_{ra} = \{x_t, \{(x_{sen}^s, y_{sen}^s)\}, \{(x_{sem}^s, y_{sem}^s)\}, \{(x_{sty}^s, y_{sty}^s)\}\}$. The x_{ra} template can be found at Appendix C.5.1. D_{ra} is split into two equal parts, D_{search} and D_{RL}, which are used for reasoning path search in stage 2 and RL in stage 3, respectively.

Stage 2. Multi-agent Collaborated Reasoning Path Building:

$$D_{SFT} = MultiAgents(D_{search}) = \{(x_{ra}, \hat{CoT}, \hat{y})\}, \quad (2)$$

where $\hat{CoT}$ is the multi-perspective reasoning path, $\hat{y}$ is the final answer based on $\hat{CoT}$.

Figure 1: The architecture of RAAR. ① Retrieval Augmented Data Building: Retrieve source-domain samples similar to target-domain data in semantics, sentiment, and style for multi-perspective analysis. ② Multi-agent Collaborated Reasoning Path Building: Use multi-agent collaboration and a verifier to construct coherent, multi-perspective reasoning paths. ③ Model Optimization: Fine-tune the model with SFT and RL to enhance cross-domain verification and reasoning.

Stage 3: Two-step model optimization:

$$\pi_\theta^{sft} = SFT_{(\pi_\theta)}(\hat{CoT}, \hat{y}|x_{ra}) \quad (3)$$

$$\hat{CoT}_{RL}, \hat{y}_{RL} = \pi_\theta^{sft}(D_{RL}) \quad (4)$$

$$\pi_\theta^{RAAR} = RL_{(\pi_\theta^{sft})}(D_{RL}, \hat{CoT}_{RL}, \hat{y}_{RL}, Reward) \quad (5)$$

where π_θ is an initial LLM models. The $reward$ includes accuracy and format. π_θ^{sft} acquires reasoning ability through SFT, then is fed D_{RL} data to generate initial reasoning, which is further improved via RL.

After all stages, we obtain an optimized RAAR LLM π_θ^{RAAR}, with the ultimate goal of improving π_θ to provide multi-perspective reasoning and a more accurate final answer $\hat{y}$. The whole process of the framework can be found at Algorithm 1.

2.2 Stage 1: Retrieval Augmented Data Building

This section focuses on retrieving multi-perspective reference samples from source-domain data for target-domain instances, serving as the foundation for subsequent reasoning construction. Previous studies have shown that sentiment, semantics, and writing style are important features for misinformation detection (Liu et al., 2025b; Bharadwaj and Shao, 2019; YANG et al., 2024). We further conduct sentiment analysis, semantic analysis, and writing style analysis in the Appendix B.2. Results show that examples retrieved from the source domain based on these features are likely to share the same labels as those in the target domain, making them more useful for the subsequent reasoning

process to analyze commonalities across domains. Meanwhile, we conducted statistical analyses to compare the performance of different models and ultimately selected Emollama (Liu et al., 2024b), RoBERTa (Liu et al., 2019), and StyleEmb (Wegmann et al., 2022) as our embedder. We encode the input using the above three embedders, and extract the last hidden state as embeddings for sentiment (E_{sen}^t, E_{sen}^s), semantic (E_{sem}^t, E_{sem}^s), and writing style (E_{sty}^t, E_{sty}^s), respectively. We next introduce the sentiment-based retrieval process.

$$E_{sen}^t = EmoLlama(D_t) = (e_{sen}^{t_1}, e_{sen}^{t_2}, ..., e_{sen}^{t_M}) \quad (6)$$

$$E_{sen}^s = EmoLlama(D_s) = (e_{sen}^{s_1}, e_{sen}^{s_2}, ..., e_{sen}^{s_N}) \quad (7)$$

where M is the number of target domain items, N is the number of source domain items. Next, we traverse the sentiment embeddings of the target domain (e_{sen}^t) within E_{sen}^t and compute their cosine similarity with each sentiment embedding e_{sen}^s from the source domain E_{sen}^s. For each target-domain instance, we then select the top-k most similar source-domain examples ($\{(x_{sen}^s, y_{sen}^s)\}$) based on these similarity scores to construct D_{ra}, which serves as the few-shot examples for the subsections[1]. The retrieval procedure for semantic and style embeddings follows the same methodology as for sentiment. Finally, we obtain the complete $D_{ra} = \{(x_{ra}, y^*)\}$. $x_{ra} = \{x_t, \{(x_{sen}^s, y_{sen}^s)\}, \{(x_{sem}^s, y_{sem}^s)\}, \{(x_{sty}^s, y_{sty}^s)\}\}$

---

[1] All retrieval is restricted to training-only data: during training, retrieval is conducted within the training set, and during testing, each test instance retrieves exclusively from the training splits of source domains, never from other test samples.

denotes the retrieval augmented items and y^* denotes the ground-truth answer.

We divide D_{ra} equally into D_{search} and D_{RL}, where D_{search} is used for reasoning path search as detailed in Section 2.3, and D_{RL} is used for the reinforcement learning component described in Section 2.4.2.

2.3 Stage 2: Multi-agent Collaborated Reasoning Path Building

After obtaining D_{search}, we introduce a multi-agent framework to enable systematic, multidimensional reasoning over complex and ambiguous evidence. Three specialized SubAgents, namely the Sentiment Agent (A_{sen}), Semantic Agent (A_{sem}), and Style Agent (A_{sty}), analyze D_{search} from their respective perspectives and generate dimension-specific responses with supporting reasons. A Summary Agent (A_{sum}) then integrates these outputs to construct coherent reasoning paths.

$$CoT^{sub}, y^{sub} = SubAgents(D_{search}) =$$
$$\{A_{sen}(x_t, \{(x^s_{sen}, y^s_{sen})\}), A_{sem}(x_t, \{(x^s_{sem}, y^s_{sem})\}),$$
$$A_{sty}(x_t, \{(x^s_{sty}, y^s_{sty})\})\} \quad (8)$$

where $CoT^{sub} = \{CoT_{sen}, CoT_{sem}, CoT_{sty}\}$ and $y^{sub} = \{y_{sen}, y_{sem}, y_{sty}\}$. Subsequently, the Summary Agent (A_{sum}) integrates these perspectives and performs additional reasoning to produce the initial reasoning chain (CoT_0) and prediction (y_0).

$$CoT_0, y_0 = A_{sum}(CoT^{sub}, y^{sub}) \quad (9)$$

$$Verifier(y_0, y^*) \in \{True, False\} \quad (10)$$

An LLM-based verifier is employed to determine whether y_0 is correct. If not, the three sub-agents and the summarizing agent will each adopt multiple strategies collaboratively to identify the correct reasoning path.

Strategy for SubAgents: **(1) Double-Check (DC)**: This strategy informs the agent that the summarizing agent's answer is incorrect. The agent needs to self-verify, correcting errors or offering further justification if it keeps its original stance. **(2) Communication**: Under this strategy, each agent is informed of the other agents' answers and reasoning. Similarly, if any issues are identified, the agent should make corrections; if it maintains its position, it should offer further justification. Based on existing studies (Chen et al., 2025; Qian et al., 2025), we improved and adapted the

following strategies for Summary Agent: **(1) Cross-agent consolidation**: Aggregate sub-agent outputs to produce a unified answer. **(2) Cross-agent re-consideration**: Re-evaluate the current reasoning by cross-checking sub-agent rationales. **(3) Cross-agent diversification**: Leverage sub-agent signals to explore an alternative reasoning path. **(4) Cross-agent verification**: Assess the consistency of the current reasoning across sub-agent perspectives. **(5) Cross-agent rectification**: Identify and correct potential flaws in the current reasoning using sub-agent contents.

The above strategies ensure not only efficiency in identifying the correct reasoning path but also sufficient diversity in the reasoning process. Due to cost and time considerations, we set the total number of search rounds to $N = 3$. During the exploration process, updates are first made from the summary agent. If the answer is still incorrect, update then backtrack to the subagents[2]. If the correct reasoning path is not found after more than N iterations, we provide appropriate hints to force each agent to revisit previous steps, refine its hypotheses based on the verifier's feedback, and adjust its reasoning process to arrive at the correct reasoning path. After obtaining the complete and correct reasoning paths, we use LLMs to organize all the reasoning steps and generate a more human-like, intuitive thinking process ($\hat{CoT}$).

$$\hat{CoT} = LLMrephrase(CoT_0, CoT_1, ...CoT_N, x_{ra}) \quad (11)$$

Based on this natural reasoning, generate a rich and high-quality final response ($\hat{y}$), where $\hat{y}$ consists of a clear answer in the first paragraph, followed by a summarized explanation in the second paragraph.

$$\hat{y} = LLMrefine(\hat{CoT}, x_{ra}) \quad (12)$$

All LLMs involved in this section use DeepSeek-v3.2-chat due to its cost advantage. The prompts for all agents, as well as those for all steps involving LLMs, can be found in the Appendix E.

2.4 Stage 3: Model Optimization

2.4.1 Retrieval Augmented SFT

After collecting the human-like $\hat{CoT}$s and the final answers $\hat{y}$, we use the template in Appendix C.5.2 to construct the dataset (D_{SFT}) for SFT. The input

---

[2]It is worth noting that to avoid getting stuck in a loop, when all three agents provide the same incorrect answer, we first update the subagents to generate as diverse answers as possible for the summary agent to reference.

is the retrieval augmented data x_{ra}. Given an initial LLM model π_θ. We can get the π_θ^{sft} through SFT.

$$L_{SFT}(\theta) \leftarrow -log\pi_\theta(\hat{CoT}, \hat{y} \mid x_{ra})$$
$$\theta \leftarrow \theta - \eta\nabla(\theta)L_{SFT}(\theta) \quad (13)$$

The SFT stage guides the model to systematically construct its reasoning process before producing the final answer. Training is performed on retrieval-augmented data that encourages multi-step, multi-perspective reasoning, with target outputs consisting of a final answer accompanied by a summarizing explanation. This approach fosters a coherent analytical process, enhancing both interpretability and accuracy in cross-domain misinformation detection.

2.4.2 RL

In the RL stage, we adopt the Group Relative Policy Optimization (GRPO) algorithm (Shao et al., 2024) to further enhance reasoning ability of π_θ^{sft}. Each sample in the training dataset D_{RL} consists of two components (x_{ra}, y^*), where x_{ra} represents the question and y^* denotes the model's output containing only the final answer without the reasoning process. Similar to previous studies (Zhu et al., 2025), two reward mechanisms are employed: an accuracy reward, which encourages the model to produce correct answers, and a format reward, which ensures that the generated outputs adhere to the expected format.

(1) Format reward: We introduce a format reward to ensure that the model's output follows the structure: "<think>\n*[reasoning]*\n</think>\n\n\n<answer> \n*[firstsentence]*\n\n*[response]*</answer>". *[firstsentence]* contains the explicit predicted label. If the output conforms to this format, the model receives a reward of 1; otherwise, the reward is 0. **(2) Accuracy reward:** The reward is 1 for a correct answer, 0.1 for incorrect, and 0 for None. Unlike LLM-based evaluation, we compute it directly using hard-coded rules, requiring the model to give the answer in the first sentence.

3 Experiments

3.1 Datasets

We conduct experiments on AMTCele (Pérez-Rosas et al., 2018), PHEME (Kochkina et al., 2018), and COCO (Langguth et al., 2023). AMTCele, a cross-domain fake news dataset, includes FakeNewsAMT and Celebrity with both legit and fake labels. PHEME is a Twitter dataset containing rumours and non-rumours across nine breaking news events. COCO is a conspiracy-oriented Twitter dataset covering 12 conspiracy categories, with tweets labeled as Unrelated, Conspiracy, or Related.

We evaluate the difficulty of each domain in AMTCele and PHEME using GPT-4.1 and DeepSeek-Chat, in order to select relatively challenging domains (lower performance) (Luan and Dong, 2018). The detailed results are reported in Table 3. Based on the performance of the two models, for AMTCele we use the *celebrity* domain as the test set, which originates from popular culture media and exhibits weaker structure and higher semantic noise. For PHEME, we select four challenging domains, *prince*, *putinmissing*, *gurlitt*, and *ebola* as test set, where each test event contains a single core rumor, while the training set consists of five major crisis events involving discussions of both true and false information. For COCO, as each instance may involve multiple domains, domain-wise splitting is more complex. Therefore, building upon the RAEmoLLM work, we additionally include data from the Unrelated category to better align with the original task setting of the dataset. The statistics of each dataset and more analysis can be found in Appendix B.1.

3.2 Baselines

1) LLMs: We select mainstream LLMs as our baseline models for comparison, including reasoning-oriented models such as GPT-5-mini (OpenAI, 2025), DeepSeek-v3.2-Reasoner (Liu et al., 2025a), and Qwen3 (8B, 14B, and 32B) (Yang et al., 2025). In addition, we include advanced LLMs, including LLama3.1-8b-instruct (Llama-8b) (Dubey et al., 2024), GPT-4.1 (OpenAI, 2025), DeepSeek-v3.2-Chat (Liu et al., 2025a), as strong baselines. In this paper, we consider two experimental settings: zero-shot evaluation and few-shot evaluation enhanced by RAAR retrieval of in-context examples.

2) Cross-domain methods: MOSE (Qin et al., 2020): mixture-of-experts (MoE). EDDFN (Silva et al., 2021): multimodal features. MDFEND (Nan et al., 2021) Domain Gate mechanism based on MoE framework. CANMD (Yue et al., 2022): contrastive learning. MetaAdapt (Yue et al., 2023): meta-learning paradigm.

3) LLM-based Adaptation methods: Instruction Tuning: We fine-tune two variants of the model based on Qwen3-8b, including a zero-shot

Models	AMTCele				PHEME				COCO				Ave. F1	Ave. Rank
	ACC	Pre	Recall	F1	ACC	Pre	Recall	F1	ACC	Pre	Recall	F1		
cross-domain methods														
MDFEND	0.642	0.663	0.642	0.630	0.433	0.622	0.575	0.420	0.720	0.722	0.640	0.662	0.570	19.7
EDDFN	0.680	0.686	0.680	0.678	0.331	0.536	0.507	0.278	0.715	0.681	0.680	0.680	0.545	19.7
MOSE	0.492	0.248	0.492	0.330	0.555	0.546	0.554	0.534	0.466	0.355	0.343	0.348	0.404	20.3
CANMD	0.504	0.751	0.504	0.342	0.482	0.570	0.569	0.481	0.628	0.595	0.583	0.579	0.468	20.7
MetaAdapt	0.608	0.576	0.820	0.677	**0.692**	**0.625**	0.508	0.433	0.511	0.492	0.504	0.487	0.532	21.7
ZS														
GPT-5-mini-R	0.780	0.780	0.780	0.780	0.586	0.549	0.554	0.547	0.765	0.798	0.686	0.691	0.673	9.3
Deepseek-R	0.832	0.833	0.832	0.832	0.512	0.515	0.518	0.495	0.776	0.810	0.705	0.708	0.679	10.0
Qwen-8b-R	0.776	0.779	0.776	0.775	0.571	0.361	0.361	0.358	0.641	0.666	0.529	0.516	0.550	21.0
Qwen-14b-R	0.742	0.765	0.742	0.736	0.567	0.375	0.380	0.365	0.706	0.726	0.604	0.610	0.570	19.3
Qwen-32b-R	0.742	0.757	0.742	0.738	0.560	0.548	0.556	0.537	0.687	0.729	0.575	0.566	0.614	14.0
GPT-4.1	0.856	0.862	0.856	0.855	0.579	0.524	0.525	0.524	0.781	0.596	0.537	0.537	0.639	11.3
Deepseek-C	0.846	0.856	0.846	0.845	0.496	0.503	0.504	0.481	0.712	0.747	0.609	0.612	0.646	12.7
Llama-8b	0.666	0.554	0.444	0.489	0.462	0.344	0.315	0.309	0.471	0.463	0.340	0.358	0.385	25.7
RA														
GPT-5-mini-R	0.790	0.792	0.790	0.790	0.584	0.553	0.560	0.550	0.786	0.807	0.714	0.725	0.688	7.0
Deepseek-R	**0.868**	**0.871**	**0.868**	**0.868**	0.531	0.522	0.526	0.509	0.793	0.818	0.726	0.739	0.705	6.7
Qwen-8b-R	0.786	0.799	0.786	0.784	0.526	0.356	0.359	0.341	0.716	0.712	0.626	0.634	0.586	17.3
Qwen-14b-R	0.782	0.785	0.782	0.781	0.535	0.540	0.547	0.520	0.750	0.753	0.666	0.677	0.659	12.3
Qwen-32b-R	0.804	0.804	0.804	0.804	0.535	0.531	0.536	0.515	0.735	0.750	0.652	0.666	0.662	11.7
GPT-4.1	0.820	0.847	0.820	0.816	0.570	0.517	0.518	0.516	0.812	0.817	0.759	0.755	0.696	7.3
Deepseek-C	0.862	0.864	0.862	0.862	0.518	0.518	0.521	0.500	0.763	0.797	0.684	0.689	0.684	9.0
Llama-8b	0.820	0.549	0.547	0.548	0.448	0.339	0.339	0.298	0.598	0.592	0.586	0.568	0.472	23.3
Adaptation														
IT_zs	0.784	0.794	0.784	0.782	0.461	0.568	0.561	0.459	**0.819**	0.801	**0.785**	**0.792**	0.678	10.7
IT_ra	0.750	0.509	0.500	0.503	0.578	0.578	**0.591**	**0.562**	0.660	0.552	0.572	0.530	0.532	16.3
RAEmoLLM	0.808	0.843	0.808	0.803	0.570	0.527	0.530	0.525	0.812	**0.822**	0.761	0.758	0.696	7.0
MARO	0.688	-	-	0.680	0.608	0.538	0.538	0.538	-	-	-	-	-	-
ARG	0.667	0.695	0.668	0.655	0.432	0.523	0.521	0.431	0.765	0.744	0.746	0.741	0.609	15.7
RAAR-8b	0.812	0.813	0.812	0.812	0.536	0.558	0.567	0.528	0.776	0.779	0.707	0.727	0.689	7.3
RAAR-14b	0.842	0.842	0.842	0.842	0.541	0.572	0.582	0.535	0.799	0.792	0.748	0.759	**0.712**	**4.0**

Table 1: Main results on three datasets. "ZS" denotes the zero-shot setting. "RA" denotes few-shot setting based retrieval augmented data. "R" denotes a reasoning model. The results of MARO in AMTCele are refer to (Li et al., 2025) .

fine-tuned version (IT_zs) (like conspemollm (Liu et al., 2024a)) and a retrieval-augmented fine-tuned version with few-shot examples (IT_ra). ARG (Hu et al., 2024): multi-perspective. **RAEmoLLM** (Liu et al., 2025b): RAG. **MARO** (Li et al., 2025): Multi agents.

Details of the above baselines can be found in the Appendix C.4. The templates for zero-shot, few-shot based on RA data, and instruction-tuning methods can be found at Appendix C.5.2.

3.3 Settings and Evaluation

We develop RAAR-8B and RAAR-14B under the RAAR framework, built on the reasoning versions of Qwen3-8B and Qwen3-14B. In Stage 1, we select top two examples for each dimension, details are provided in Section 3.5. Details of training settings can be found in Appendix C.3.

We evaluate model performance using multiple metrics, including accuracy, precision, recall, and F1 score, all in their macro variants. Due to class imbalance in the PHEME and COCO datasets, our analysis focuses on F1 score. We further use average F1 and rank to assess overall model performance across the three tasks.

3.4 Main results

Table 1 shows the performance of baselines and our methods. Overall, RAAR-14B achieves the highest average F1 and rank across the three datasets. RAAR also substantially improves the base models (from Qwen3-8B to RAAR-8B and from Qwen3-14B to RAAR-14B) and outperforms other cross-domain methods, advanced LLMs, and LLM-based adaptation approaches, demonstrating its effectiveness for complex cross-domain misinformation detection. We next provide a detailed analysis.

RAAR outperforms existing LLM-based adaptation methods: The final part of the table compares LLM-based adaptation methods. **(1) Dataset-specific adaptation:** Instruction-tuning approaches tend to overfit their training datasets. While IT_zs performs best on COCO and IT_ra on PHEME, both achieve only moderate results on other datasets, especially the small-scale AMTCele, indicating limited cross-domain generalization without reasoning. **(2) RAG-based adaptation:** RAEmoLLM improves over GPT-4.1 in the zero-shot setting but still falls behind RAAR-14B, suggesting that sentiment-augmented retrieval alone is insufficient for complex cross-domain misinformation detection. Without systematic multi-step

reasoning or integration of complementary perspectives, it struggles to capture ambiguous or implicit evidence, limiting its cross-domain generalization. **(3) MultiAgent-based adaptation:** Despite employing multiple agents, MARO relies on simple analysis and lacks systematic multi-perspective reasoning, while its rule-based constraints limit applicability to the COCO propagation intent detection task. Consequently, it performs poorly on challenging or underrepresented long-context domains where ambiguity and implicit cues require integrated sentiment, stylistic, and semantic analysis. **(4) Multi-perspective adaptation:** Although ARG enhances models through multi-perspective reasoning, its performance on cross-domain tasks is not ideal, indicating the importance of retrieval augmentation and reinforcement learning.

Comparison with LLMs: (1) Larger models perform better: Large-scale models (GPT and DeepSeek) consistently outperform smaller models (Qwen and Llama-8B) in cross-domain misinformation detection, highlighting their superior representation capacity and world knowledge for more robust reasoning under distribution shifts. **(2) Few-shot learning yields clear gains:** Few-shot results consistently outperform zero-shot performance, indicating that retrieval-augmented in-context examples provide effective cross-domain cues and enable more reliable reasoning. **(3) RAAR outperforms advanced LLMs:** The RAAR framework significantly enhances base models, with RAAR-14B surpassing advanced proprietary models like GPT-4.1 and DeepSeek in average F1 and rank scores, demonstrating strong cross-domain effectiveness. **(4) Reasoning models excel on complex tasks.** DeepSeek's reasoning version outperforms its chat version in most cases, highlighting the importance of explicit reasoning for complex cross-domain tasks. **(5) Special case:** DeepSeek-series models and GPT-4.1 excel on the AMTCele dataset, likely due to effective knowledge distillation and robust generalization to social media language, which also benefits long-text tasks.

RAAR outperforms existing cross-domain methods: The RAAR series consistently outperforms cross-domain methods on complex tasks across all three benchmarks, showcasing the benefits of LLMs and the proposed training strategy. In contrast, existing cross-domain methods are highly unstable: MDFEND, EDDFN, and MetaAdapt excel on AMTCele and COCO but struggle on PHEME, likely due to limited short-text under-

Models	AMTCele		PHEME		COCO		Ave. F1
	ACC	F1	ACC	F1	ACC	F1	
RAAR-8b	0.812	0.812	0.536	0.528	0.776	0.727	0.689
Reason_zs	0.786	0.785	**0.554**	**0.545**	0.763	0.535	0.622
w/o RA	0.748	0.743	0.525	0.520	0.756	0.710	0.658
1shot RA	0.778	0.777	0.544	0.539	0.773	0.725	0.680
4shot RA	0.804	0.803	0.512	0.510	**0.790**	**0.746**	0.686
w/o agents	0.778	0.777	0.518	0.514	0.783	0.739	0.677
w/o semantic	0.790	0.790	0.531	0.526	0.784	0.740	0.685
w/o sentiment	0.786	0.786	0.538	0.531	0.775	0.727	0.681
w/o style	0.810	0.810	0.507	0.335	0.775	0.723	0.623
w/o RL	0.810	0.810	0.525	0.515	0.764	0.712	0.679
SFT+Full	0.782	0.782	0.535	0.522	0.761	0.718	0.674
SFT+PPO	0.786	0.784	0.506	0.498	0.774	0.727	0.670
RAAR-Llama	**0.834**	**0.834**	0.506	0.504	0.773	0.726	0.688
RAAR-14b	0.842	0.842	0.541	0.535	0.799	0.759	0.712
RAAR-14b w/o RL	0.818	0.818	0.501	0.495	0.782	0.738	0.684
RAAR-14b w/o agents	0.810	0.810	0.535	0.527	0.795	0.749	0.695

Table 2: Ablation Analysis. "w/o" denotes without. Bold indicates best performance and underlining denotes the second-best performance among the first three parts (RAAR-8b ablation).

standing, while MOSE and CANMD underperform on AMTCele, reflecting difficulty with unstructured long-text data.

The PHEME dataset is relatively large, and COCO's train and test sets share similar distributions, which fine-tuned models tend to favor. However, in multi-task training, most current methods effectively handle only one dataset (e.g., IT_zs, IT_ra), highlighting RAAR's advantage in integrating multiple tasks during training.

We also compare the resource and time costs of RAAR with baseline methods to further evaluate its effectiveness at Appendix C.6.

3.5 Ablation study

To assess the contribution of each RAAR module, we create variant models and perform ablation experiments by systematically removing individual components. **(1) For Retrieval Data Building: Reason_zs:** Without retrieval-augmented examples, reasoning is performed solely based on the target text. **w/o RA:** Without using retrieval augmentation, few-shot examples are randomly sampled. **1/4shot RA:** Retrieval-augmented with one/four example(s) for each dimension. **(2) For Complex Reasoning Building: w/o agents:** Without using any agents, reasoning is performed directly based on the retrieval-augmented data. **w/o semantic:** Without semantic agent. **w/o sentiment:** Without sentiment agent. **w/o style:** Without writing style agent. **(3) For Training: w/o RL:** Without the RL step, SFT is performed only using D_{SFT}. **SFT+Full:** Conduct SFT using the complex path built from full training datasets. **SFT+PPO:** The RL phase is trained using PPO. **RAAR-Llama:** Apply RAAR to train Llama-8b.

Table 2 presents the ablation results. All variants exhibit some degree of performance decline in average F1 score. For the *Reason_zs* variant, like the previously mentioned instruction-tuning, it excels on only a single dataset and tends to overfit specific data types. The *w/o RA* results show that using randomly selected few-shot examples causes a substantial performance drop, highlighting the importance of retrieval augmentation for obtaining effective examples. Comparing the **1shot** and **4shot** settings, more examples generally improve performance, but the number of examples should be balanced, as too many can hinder the model's understanding.

In the Complex Reasoning Building section, all w/o agent variants have little impact on the COCO dataset and in some cases perform slightly better. This may be because COCO consists entirely of COVID19–related content; although topics are subdivided, the sentiment, semantics, and writing style across topics are likely very similar, making it difficult for agents to distinguish during analysis. For datasets with more distinct topics, such as AMTCele and PHEME, the results show that each agent contributes significantly. Notably, the *w/o sentiment* variant on AMTCele drops by 0.26, highlighting the importance of sentiment analysis for long-text news[3].

For training, the *w/o RL* results show that the RL step provides overall improvements across all datasets. The *SFT+Full* results indicate that simply increasing SFT training data does not effectively enhance the model and may even cause overfitting. In contrast, *SFT+PPO* results show that GRPO offers advantages over standard PPO, providing memory savings and more effective group-level optimization. The average F1 score of *RAAR-Llama* is comparable to RAAR-8B, demonstrating the generality of the RAAR framework.

Ablation experiments with the 14B model show that RAAR increases average F1 by +1.7% over the model without agents, while RL adds +2.8%, confirming the effectiveness of both components. Overall, the 14B model outperforms Qwen-8B, and the larger drops in the w/o RL and w/o agents ablations further underscore the value of these modules.

---

[3]The *w/o style* variant performs poorly on PHEME, likely because during testing the model generates repeated and irrelevant words across multiple samples, preventing correct answers.

4 Error Analysis

Appendix D presents detailed confusion metrics, case studies, and reasoning comparisons across *Reason_zs*, RAAR-8B, and RAAR-14B. The analysis shows that RAAR-14B relies heavily on lexical, stylistic, and sentiment cues. In AMTCele, sensational celebrity reports are often flagged as fake, while conventionally styled news is sometimes accepted as legit. In PHEME, confident or excited unverified claims are frequently classified as non-rumors, whereas humorous or sarcastic posts are misinterpreted as rumors. In COCO, explicit conspiratorial terminology biases the model toward the *Conspiracy* label, while neutral or technical framings are occasionally under-labeled. Overall, even when the summary agent is prompted for more perspective analysis in addition to the analysis from subagents, RAAR may focus on specific analytical angles in certain cases, potentially reinforcing human-like biases and misinterpreting formally neutral or emotionally restrained content.

The reasoning comparison cases across models show that model scale and inference design critically determine sensitivity to implicit intent and discourse structure, with smaller models relying on surface heuristics and larger models exhibiting deeper, more robust reasoning. More detailed analysis can be found at Appendix D.

5 Conclusion

In this paper, we propose the RAAR framework, the first retrieval-augmented agentic reasoning approach for cross-domain misinformation detection. RAAR integrates a retrieval-augmented agentic reasoning mechanism with SFT and RL to enable cross-domain knowledge transfer and multi-step reasoning. We evaluated our trained models RAAR-8B and RAAR-14B, and competitive baselines on challenging domains selected from three datasets. The results demonstrate that RAAR outperforms other cross-domain and LLM-based methods, validating the effectiveness of the framework. Additionally, we conducted ablation studies to analyze the contributions of different components and performed error analyses, providing a foundation for future improvements.

In the future, we aim to enhance the RAAR framework by incorporating more perspectives (e.g., topic and stance) and adapting the framework to multilingual and multimodal settings.

6 Limitation

Due to limited computational resources and cost, we only trained the 8B and 14B open-source LLMs and the ablation for the 14B model was performed only on two main parts. Therefore, we did not explore the potential impact of using larger models or different architectures on the performance of cross-domain misinformation detection when applying the RAAR framework.

Although our analysis considers multiple perspectives, including sentiment, semantics, and writing style, there remain many potentially useful features—such as stance, argumentation structure, and topical information—that were not analyzed. Exploring these features will be a focus of our future work.

Since the framework is designed to focus on sentiment, semantics, and writing style, even though the Summary Agent is instructed to consider other aspects in addition to these three, some cases show that the final reasoning primarily concentrates on sentiment, semantics, and style, resulting in reasoning that is not fully comprehensive.

The COCO dataset contains instances that may belong to multiple topics, making it unrealistic to balance the data and leading to data imbalance. This can also result in the retrieval process occasionally selecting irrelevant or noisy samples.

Limitations of the cross-domain setting: **AMTCele**: The fake news in the six training domains is manually generated via AMT, whereas the test set (Celebrity domain) consists of longer, more informal articles from online entertainment and celebrity magazines. This stylistic discrepancy increases distributional shift. At the same time, since the test content is published on open websites, it may have appeared in LLM pretraining data, introducing potential contamination concerns. **PHEME**: All data comes from social media platforms and shares similar writing styles. However, the dataset is split by events. The semantic and sentiment gaps between test events and training events can be substantial. Retrieved cases may contain noisy or weakly relevant examples, and some may not effectively support multi-perspective reasoning. **COCO**: This dataset is also collected from social media, with most discussions centered on COVID-19. Although subtopics differ, they remain within a single overarching theme. Consequently, retrieval across subtopics may lead to confusion among closely related discussions, making it harder to identify the most informative evidence.

References

Pranav Bharadwaj and Zongru Shao. 2019. Fake news detection with semantic features and text mining. *International Journal on Natural Language Computing (IJNLC) Vol*, 8.

Junying Chen, Zhenyang Cai, Ke Ji, Xidong Wang, Wanlong Liu, Rongsheng Wang, and Benyou Wang. 2025. Towards medical complex reasoning with llms through medical verifiable problems. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 14552–14573.

Carmela Comito, Francesco Sergio Pisani, Erica Coppolillo, Angelica Liguori, Massimo Guarascio, and Giuseppe Manco. 2023. Towards self-supervised cross-domain fake news detection. In *ITASEC*.

Chongyuan Dai, Jinpeng Hu, Hongchang Shi, Zhuo Li, Xun Yang, and Meng Wang. 2025. Psyche-r1: Towards reliable psychological llms through unified empathy, expertise, and reasoning. *arXiv preprint arXiv:2508.10848*.

Leonidas AA Doumas, Guillermo Puebla, Andrea E Martin, and John E Hummel. 2022. A theory of relation learning and cross-domain generalization. *Psychological Review*, 129(5):999.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Kacper T Gradoń, Janusz A Hołyst, Wesley R Moy, Julian Sienkiewicz, and Krzysztof Suchecki. 2021. Countering misinformation: A multidisciplinary approach. *Big Data & Society*, 8(1):20539517211013848.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Beizhe Hu, Qiang Sheng, Juan Cao, Yuhui Shi, Yang Li, Danding Wang, and Peng Qi. 2024. Bad Actor, Good Advisor: Exploring the Role of Large Language Models in Fake News Detection. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 22105–22113.

Elena Kochkina, Maria Liakata, and Arkaitz Zubiaga. 2018. All-in-one: Multi-task learning for rumour verification. In *Proceedings of the 27th International Conference on Computational Linguistics*, pages 3402–3413.

Johannes Langguth, Daniel Thilo Schroeder, Petra Filkuková, Stefan Brenner, Jesper Phillips, and Konstantin Pogorelov. 2023. Coco: an annotated twitter dataset of covid-19 conspiracy theories. *Journal of Computational Social Science*, pages 1–42.

Hui Li, Ante Wang, Kunquan Li, Zhihao Wang, Liang Zhang, Delai Qiu, Qingsong Liu, and Jinsong Su. 2025. A multi-agent framework with automated decision rule optimization for cross-domain misinformation detection. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 5720–5736.

Aixin Liu, Aoxue Mei, Bangcai Lin, Bing Xue, Bingxuan Wang, Bingzheng Xu, Bochao Wu, Bowei Zhang, Chaofan Lin, Chen Dong, and 1 others. 2025a. Deepseek-v3. 2: Pushing the frontier of open large language models. *arXiv preprint arXiv:2512.02556*.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

Zhiwei Liu, Boyang Liu, Paul Thompson, Kailai Yang, and Sophia Ananiadou. 2024a. Conspemollm: Conspiracy theory detection using an emotion-based large language model. In *ECAI 2024*, pages 4649–4656. IOS Press.

Zhiwei Liu, Kailai Yang, Qianqian Xie, Christine De Kock, Sophia Ananiadou, and Eduard Hovy. 2025b. Raemollm: Retrieval augmented llms for cross-domain misinformation detection using in-context learning based on emotional information. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 16508–16523.

Zhiwei Liu, Kailai Yang, Qianqian Xie, Tianlin Zhang, and Sophia Ananiadou. 2024b. Emollms: A series of emotional large language models and annotation tools for comprehensive affective analysis. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 5487–5496.

Zhiwei Liu, Xin Zhang, Kailai Yang, Qianqian Xie, Jimin Huang, and Sophia Ananiadou. 2025c. Fmdllama: Financial misinformation detection based on large language models. In *Companion Proceedings of the ACM on Web Conference 2025*, pages 1153–1157.

Cuiju Luan and Guozhu Dong. 2018. Experimental identification of hard data sets for classification and feature selection methods with insights on method selection. *Data & Knowledge Engineering*, 118:41–51.

Qiong Nan, Juan Cao, Yongchun Zhu, Yanyan Wang, and Jintao Li. 2021. Mdfend: Multi-domain fake news detection. In *Proceedings of the 30th ACM International Conference on Information & Knowledge Management*, pages 3343–3347.

Cheng Niu, Yang Guan, Yuanhao Wu, Juno Zhu, Juntong Song, Randy Zhong, Kaihua Zhu, Siliang Xu, Shizhe Diao, and Tong Zhang. 2024. Veract scan: Retrieval-augmented fake news detection with justifiable reasoning. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*, pages 266–277.

OpenAI. 2025. Gpt-5 system card. Official OpenAI announcement for the GPT-5 model family.

OpenAI. 2025. Introducing gpt-4.1. Official OpenAI announcement for the GPT-4.1.

Ajay Patel, Jiacheng Zhu, Justin Qiu, Zachary Horvitz, Marianna Apidianaki, Kathleen McKeown, and Chris Callison-Burch. 2025. Styledistance: Stronger content-independent style embeddings with synthetic parallel examples. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 8662–8685.

Verónica Pérez-Rosas, Bennett Kleinberg, Alexandra Lefevre, and Rada Mihalcea. 2018. Automatic detection of fake news. In *Proceedings of the 27th International Conference on Computational Linguistics*, pages 3391–3401.

Lingfei Qian, Weipeng Zhou, Yan Wang, Xueqing Peng, Jimin Huang, and Qianqian Xie. 2025. Fino1: On the transferability of reasoning enhanced llms to finance. *arXiv e-prints*, pages arXiv–2502.

Zhen Qin, Yicheng Cheng, Zhe Zhao, Zhe Chen, Donald Metzler, and Jingzheng Qin. 2020. Multitask mixture of sequential experts for user activity streams. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 3083–3091.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junmei Song, Mingchuan Zhang, Y. K. Li, Yu Wu, and Daya Guo. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *ArXiv*, abs/2402.03300.

Jiao Shi, Xin Zhao, Nan Zhang, Yu Lei, and Lingtong Min. 2024. Rough-fuzzy graph learning domain adaptation for fake news detection. *IEEE Transactions on Computational Social Systems*, 11(4):5275–5286.

Amila Silva, Ling Luo, Shanika Karunasekera, and Christopher Leckie. 2021. Embracing domain differences in fake news: Cross-domain fake news detection using multi-modal data. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pages 557–565.

Ronit Singal, Pransh Patwa, Parth Patwa, Aman Chadha, and Amitava Das. 2024. Evidence-backed fact checking using rag and few-shot in-context learning with llms. In *Proceedings of the Seventh Fact Extraction and VERification Workshop (FEVER)*, pages 91–98.

Kaitao Song, Xu Tan, Tao Qin, Jianfeng Lu, and Tie-Yan Liu. 2020. Mpnet: Masked and permuted pre-training for language understanding. *Advances in neural information processing systems*, 33:16857–16867.

Jiankai Sun, Chuanyang Zheng, Enze Xie, Zhengying Liu, Ruihang Chu, Jianing Qiu, Jiaqi Xu, Mingyu Ding, Hongyang Li, Mengzhe Geng, and 1 others. 2025. A survey of reasoning with foundation models: Concepts, methodologies, and outlook. *ACM Computing Surveys*, 57(11):1–43.

Wei Tang, Zuyao Ma, Haifeng Sun, and Jingyu Wang. 2023. Learning sparse alignments via optimal transport for cross-domain fake news detection. In *ICASSP 2023 - 2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 1–5.

Yu Tong, Weihai Lu, Zhe Zhao, Song Lai, and Tong Shi. 2024. Mmdfnd: Multi-modal multi-domain fake news detection. In *Proceedings of the 32nd ACM International Conference on Multimedia*, pages 1178–1186.

Anna Wegmann, Marijn Schraagen, and Dong Nguyen. 2022. Same author or just same topic? towards content-independent style representations. In *Proceedings of the 7th Workshop on Representation Learning for NLP*, pages 249–268.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

HUI-KUO YANG, WEN-CHIH PENG, and 1 others. 2024. Explore the style for fake news detection. *Journal of Information Science & Engineering*, 40(6).

Da Yin, Tao Meng, and Kai-Wei Chang. 2020. Sentibert: A transferable transformer-based architecture for compositional sentiment semantics. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 3695–3706.

Zhenrui Yue, Huimin Zeng, Ziyi Kou, Lanyu Shang, and Dong Wang. 2022. Contrastive domain adaptation for early misinformation detection: A case study on covid-19. In *Proceedings of the 31st ACM International Conference on Information & Knowledge Management*, pages 2423–2433.

Zhenrui Yue, Huimin Zeng, Yang Zhang, Lanyu Shang, and Dong Wang. 2023. Metaadapt: Domain adaptive few-shot misinformation detection via meta learning. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5223–5239.

Fanrui Zhang, Dian Li, Qiang Zhang, Junxiong Lin, Jiahong Yan, Jiawei Liu, Zheng-Jun Zha, and 1 others. 2025a. Fact-r1: Towards explainable video misinformation detection with deep reasoning. *arXiv preprint arXiv:2505.16836*.

Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, Fei Huang, and Jingren Zhou. 2025b. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*.

Jie Zhu, Qian Chen, Huaixia Dou, Junhui Li, Lifan Guo, Feng Chen, and Chi Zhang. 2025. Dianjin-r1: Evaluating and enhancing financial reasoning in large language models. *arXiv preprint arXiv:2504.15716*.

A Related Work

A.1 Cross-domain misinformation detection

Cross-domain misinformation detection leverages information or data from different domains to identify misinformation in the target domain, making it more consistent with real-world conditions. (Comito et al., 2023) proposed a deep learning–based architecture that can handle cross-domain fake news by generating high-level features across domains. (Tang et al., 2023) learns cross-domain transferable features by aligning source news and target news using optimal transport (OT) techniques. (Shi et al., 2024) develops a rough-fuzzy graph learning domain adaptation method for fake news detection that models cross-domain uncertainty, refines target region analysis, and preserves sparse structures to capture shared features. (Tong et al., 2024) design MMDFND, a multi-modal, multi-domain fake news detection model that leverages domain-aware extraction and cross-modal/domain integration to achieve state-of-the-art results on two real-world datasets. (Yue et al., 2023) proposes MetaAdapt, a meta-learning approach for domain-adaptive few-shot misinformation detection that uses limited target examples to guide adaptive knowledge transfer by weighting source tasks based on their similarity to the meta task. (Liu et al., 2025b) develops a retrieval-augmented LLM framework for cross-domain misinformation detection that uses affective embeddings to retrieve relevant examples as few-shot demonstrations for in-context learning. (Li et al., 2025) proposes a multi-agent framework that uses expert agents, a question-reflection mechanism, and decision rule optimization to improve analysis quality and cross-domain performance. However, existing approaches often rely on task-specific fine-tuning or prompts, consider data from a single perspective without integrating semantics, sentiment, or style, and lack systematic reasoning over ambiguous or implicit evidence. These limitations

hinder cross-task and cross-domain generalization, motivating methods that combine robust, interpretable representations with cross-domain reasoning.

A.2 Application of complex reasoning

Complex reasoning, represented by GPT-o1 and DeepSeek-R1 (Guo et al., 2025), has further enhanced LLMs and has been applied across multiple fields. Huotuo-o1 (Chen et al., 2025) guides LLMs to construct complex reasoning paths using multi-step strategies and further enhances the model's reasoning ability through supervised fine-tuning and reinforcement learning. (Qian et al., 2025) introduced FinCoT, the first high-fidelity open CoT corpus for the financial domain, built from seven QA datasets with domain supervision, iterative LLM refinement, and difficulty-aware filtering. Based on FinCoT, they developed the first open financial reasoning model trained with SFT and GRPO. (Dai et al., 2025) propose Psyche-R1, the first Chinese psychological LLM integrating empathy, expertise, and reasoning, trained on a large corpus of CoT-based questions and empathetic dialogues using a hybrid strategy of GRPO for reasoning and supervised fine-tuning for empathy and domain knowledge. (Zhang et al., 2025a) applied a similar process for video misinformation detection. However, these methods primarily rely on direct inference from data within the same distribution, operate with a single model, and lack the capacity to analyze tasks from multiple perspectives, rendering them clearly insufficient for addressing complex cross-domain misinformation.

B Data analysis

B.1 Data process and statistics

We conduct experiments on the AMTCele (Pérez-Rosas et al., 2018), PHEME (Kochkina et al., 2018), COCO (Langguth et al., 2023). AMTCele was constructed by (Liu et al., 2025b), including FakeNewsAMT and Celebrity. It is a cross-domain fake news dataset covering multiple topical domains. Legitimate news is collected from mainstream media outlets, while fake news is generated via Amazon Mechanical Turk crowdsourcing; the Celebrity subset focuses on news from online entertainment and celebrity magazines. PHEME is a Twitter-based dataset consisting of rumours and non-rumours associated with nine breaking news events, widely used to study misinformation detection in social media contexts. COCO is a conspiracy-oriented Twitter dataset covering 12 conspiracy theory categories. Tweets are labeled by overall intention as Unrelated (unrelated to Conspiracy), Related (related to conspiracy but does not propagate), or Conspiracy (related to conspiracy and aims to spread). The data statistic can be found in Table 4.

We evaluate the difficulty of each domain in AMTCele and PHEME using GPT-4.1 and DeepSeek-Chat, in order to select relatively challenging domains (lower performance) (Luan and Dong, 2018). The detailed results are reported in Table 3. For AMTCele, the fake news in the six training domains is manually generated via AMT, whereas the test set (Celebrity domain) consists of longer, more informal articles from online entertainment and celebrity magazines. This stylistic difference increases the distributional shift. As a result, LLMs exhibit comparatively poorer performance on this domain, and we therefore select it for our experiments. For PHEME, based on the performance of the two models and the data volume, we select four more challenging domains: *prince, putinmissing, gurlitt* and *ebola*, where each test event contains only a single core rumor, while the training set (five events) involves major crisis events in which users discussed multiple aspects of both true and false information. Therefore, our current splits are consistent with the original dataset characteristics. Since some of the remaining domains are highly imbalanced (e.g. in charliehebdo domain, 1621 non-rumour and 458 rumour), we apply data balancing for each selected domain, ensuring that the two classes within each domain have approximately equal sample sizes. For COCO, as each instance may involve multiple domains, domain-wise splitting is more complex. Therefore, building upon the RAEmoLLM work, we additionally include data from the Unrelated category to better align with the original task setting of the dataset.

B.2 Sentiment, semantic, and style analysis

We take AMTCele as an example for analysis, since the number of legit and fake data points is equal in each domain, making the analysis results more reasonable and reliable. Table 5 presents the statistics of similarities for different embeddings (semantic (Liu et al., 2019), sentiment (Liu et al., 2024b), and writing style (Wegmann et al., 2022)). We conducted t-tests on the top K cosine similarities

Algorithm 1 Retrieval Augmented Agentic Reasoning Training

Require: Source data: D_s. Target data: D_t. $\{D_s, D_t\} \in D = \{(x, y^*)\}$, SubAgents: $A_{sen}, A_{sem}, A_{sty}$, Summary Agent: A_{sum}, max steps: N, Embeddings: $E_{sen}, E_{sem}, E_{sty}$, Initial model π_θ, SubAgents update strategies: double-check S_{dc}^{sub}, communication S_{com}^{sub}, S_{random}^{sub} denotes randomly select S_{dc}^{sub} or S_{com}^{sub}. Summary agent random strategies $S_{random}^{sum} \in \{Refine, Backtracking, NewPath, Validation, Correction\}$, LLM (DeepSeek-V3.2) for searching reasoning paths and a Verifier.

    // Stage 1: Retrieval Augmented Data Building
1: **for** $e_{sen}^t, e_{sem}^t, e_{sty}^t$ in $E_{sen}(D_t), E_{sem}(D_t), E_{sty}(D_t)$ **do**
2:     **for** $e_{sen}^s, e_{sem}^s, e_{sty}^s$ in $E_{sen}(D_s), E_{sem}(D_s), E_{sty}(D_s)$ **do**
3:         $Sco \leftarrow score_{sen}, score_{sem}, score_{sty} = cosine(e_{sen}^t, e_{sen}^s), cosine(e_{sem}^t, e_{sem}^s), cosine(e_{sty}^t, e_{sty}^s)$
4:     **end for**
5: **end for**
6: $D_{ra} = \{(x_{ra}, y^*)\} \leftarrow$ select top k examples for each dimensions according to Sco
7: $D_{search}, D_{RL} \leftarrow split(D_{ra})$
8: $D_{SFT} \leftarrow \emptyset$
    // Stage 2: Multi-agent Collaborated Reasoning Path Building
9: $CoT^{sub}, y^{sub} = SubAgents(D_{search})$
10: $CoT_0, y_0 = A_{sum}(CoT^{sub}, y^{sub})$
11: **for** i to N **do**
12:     **if** $not\ Verifier(y_0, y^*)$ **then**
13:         **if** $same(y_{sub}) = y_0$ **then**
14:             $CoT^{sub}, y^{sub} = SubAgents(CoT^{sub}, y^{sub}, S_{dc}^{sub})$
15:             **if** $same(y_{sub})$ and $y_{sub} \neq y_*$ **then**
16:                 $CoT_i, y_i = A_{sum}(CoT^{sub}, y^{sub}, S_{random}^{sum})$
17:             **else**
18:                 $CoT_i, y_i = A_{sum}(CoT^{sub}, y^{sub})$
19:             **end if**
20:         **else**
21:             $CoT_i, y_i = A_{sum}(CoT^{sub}, y^{sub}, S_{random}^{sum})$
22:             **if** $not\ Verifier(y_i, y^*)$ **then**
23:                 $CoT^{sub}, y^{sub} = SubAgents(CoT^{sub}, y^{sub}, S_{random}^{sub})$
24:                 $CoT_i, y_i = A_{sum}(CoT^{sub}, y^{sub}, S_{random}^{sum})$
25:             **end if**
26:         **end if**
27:     **end if**
28:     **if** $Verifier(y_0, y^*)$ **then**
29:         $\hat{CoT} \leftarrow LLMrephrase(CoT_0, CoT_1, ...CoT_N, x_{ra})$
30:         $\hat{y} \leftarrow LLMrefine(\hat{CoT}, x_{ra})$
31:         $D_{SFT} \leftarrow (x_{ra}, \hat{CoT}, \hat{y})$
32:     **end if**
33: **end for**
    // Step 3.1: SFT
34: **for** $(x_{ra}, \hat{CoT}, \hat{y})$ in D_{SFT} **do**
35:     $L_{SFT}(\theta) \leftarrow -log\pi_\theta(\hat{CoT}, \hat{y} \mid x_{ra})$
36:     $\theta \leftarrow \theta - \eta\nabla(\theta)L_{SFT}(\theta)$
37: **end for**
    // Step 3.2: RL
38: **for** (x_{ra}, y^*) in D_{RL} **do**
39:     $\hat{CoT}, \hat{y} = \pi_\theta(x_{ra})$
40:     $Reward \leftarrow Rule(\hat{y}, y^*) + Format(\hat{CoT}, \hat{y})$
41:     $\theta \leftarrow update(L_{GRPO}(x_{ra}, y^*, \hat{CoT}, \hat{y}, Reward, \pi_\theta)$
42: **end for**
43: Return π_θ

AMTCele	biz	edu	entmt	polit	sports	tech	celebrity		
DeepSeek-C	0.887	0.925	0.925	0.937	0.937	0.962	0.845		
GPT-4.1	0.937	0.925	0.899	0.937	0.975	0.975	0.855		
Ave.	0.912	0.925	0.912	0.937	0.956	0.969	0.85		
PHEME	sydneysiege	ottawashooting	charliehebdo	ferguson	germanwings	prince	putinmissing	gurlitt	ebola
DeepSeek-C	0.600	0.519	0.648	0.552	0.572	0.076	0.609	0.393	0.176
GPT-4.1	0.652	0.563	0.626	0.602	0.593	0.394	0.385	0.343	0.300
Ave.	0.626	0.541	0.637	0.577	0.583	0.235	0.497	0.368	0.238

Table 3: F1 score of GPT-4.1 and DeepSeek-C in each domain of AMTCele and PHEME.

				Train					Test
AMTCele	Domains	Technology	Education	Business	Sports	Politics	Entertainment	Total	Celebrities
	Legit	40	40	40	40	40	40	240	250
	Fake	40	40	40	40	40	40	240	250
PHEME	Events	Charlie Hebdo	Sydney siege	Ferguson	Ottawa shooting	Germanwings-crash		Total	4 events
	Rumours	458	522	284	470	238	-	1972	430
	Non-rumours	500	699	300	420	231	-	2150	193
				Other domains and part of Unrelated				Total	Test
COCO	Unrelated			604				604	302
	Related			540				540	248
	Conspiracy			1181				1181	612

Table 4: Statistics of datasets. AMTCele includes 7 domains. PHEME contains 9 domains (events). COCO has 12 domains (topics) and Unrelated category. For AMTCele, we apply Celebrity as the test set, and for PHEME, we apply four difficult domains as the test set. For COCO, we select Fake Virus, Harmful Radiation, Depopulation, and part of Unrelated data as the test set.

AMTCele	Semantic (Roberta)				Sentiment (EmoLlama)				Writing style (styleembedding)			
	top1	top2	top4	top8	top1	top2	top4	top8	top1	top2	top4	top8
fake→fake	0.99	0.99	0.99	0.99	0.86	0.85	0.84	0.82	0.74	0.73	0.73	0.72
fake→legit	0.99	0.99	0.99	0.99	0.81	0.80	0.77	0.75	0.73	0.72	0.71	0.70
t	3.96	5.03	6.37	8.77	4.91	7.42	11.44	17.97	5.45	8.01	11.46	16.59
p	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
legit→legit	0.99	0.99	0.99	0.99	0.89	0.88	0.87	0.85	0.73	0.73	0.72	0.71
legit→fake	0.99	0.99	0.99	0.99	0.87	0.86	0.84	0.83	0.73	0.72	0.71	0.70
t	2.78	4.64	7.59	11.31	2.30	3.49	5.42	9.18	3.14	3.94	4.97	6.12
p	0.01	0.00	0.00	0.00	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Table 5: Statistics values of cosine similarity between embeddings of different dimensions on AMTCele dataset. Top K denotes retrieval top K examples. "A→B" represents the calculation of cosine similarity between each data point in A category in one domain and each data point in B in other domains. Each element (i, j) in the resulting calculation represents the cosine similarity between the i-th vector in the A group embeddings and the j-th vector in the B group embeddings. The top 4 refers to selecting the four highest values from each row. The t-value and p-value represent the t-test results for the "A-B" results of the two lines above.

AMTCele	all-mpnet-base-v2				Qwen3-Embedding-8B				StyleDistance				Sentibert			
	top1	top2	top4	top8	top1	top2	top4	top8	top1	top2	top4	top8	top1	top2	top4	top8
fake→fake	0.41	0.38	0.36	0.33	0.44	0.42	0.40	0.38	0.93	0.93	0.93	0.92	0.85	0.84	0.83	0.82
fake→legit	0.40	0.38	0.35	0.32	0.42	0.41	0.39	0.37	0.92	0.92	0.91	0.91	0.85	0.84	0.83	0.82
t	0.79	1.39	2.41	3.98	4.51	6.61	9.85	14.31	3.90	6.05	9.15	14.45	2.15	2.33	2.28	2.08
p	0.43	0.17	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.02	0.02	0.04
legit→legit	0.41	0.38	0.35	0.32	0.42	0.40	0.38	0.36	0.95	0.95	0.94	0.94	0.85	0.84	0.84	0.82
legit→fake	0.40	0.38	0.35	0.32	0.42	0.41	0.39	0.37	0.93	0.92	0.92	0.91	0.84	0.84	0.83	0.82
t	1.36	1.31	1.36	0.92	-0.25	-1.25	-3.18	-5.85	9.21	13.35	19.37	27.75	3.16	4.47	5.67	6.84
p	0.17	0.19	0.17	0.36	0.81	0.21	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Table 6: Statistics values of cosine similarity from other embedding models. Top K denotes retrieval top K examples. "A→B" represents the calculation of cosine similarity between each data point in A category in one domain and each data point in B in other domains. Each element (i, j) in the resulting calculation represents the cosine similarity between the i-th vector in the A group embeddings and the j-th vector in the B group embeddings. The top 4 refers to selecting the four highest values from each row. The t-value and p-value represent the t-test results for the "A-B" results of the two lines above.

both within and between categories. For example, "fake-legit" refers to the cosine similarity computed between each data point in the "fake" category and each data point in the "legit" category. In this computation, the "fake" data points come from one domain, while the "legit" data points come from other domains. The results shown are the averages across all domains. We then selected the top K similarity values and performed t-tests on them. The results indicate that the t-values for the top K (1, 2, 4, 8) similarity values, both within and between categories, are all positive, with p-values less than 0.05. This suggests that the top K data points retrieved based on cosine similarity within the "fake" category are highly likely to mostly belong to the same "fake" category. From the results in Table 5, it can be seen that all embeddings lead to the same conclusion for the top 1, 2, 4, and 8 cases. Considering the ablation study presented in the main text, including the 1-shot and 4-shot settings, we ultimately adopt the 2-shot approach used in this paper, retrieving 2 examples for the experiments. Additionally, we also conduct similar analysis based on other kinds of semantic embeddings (all-mpnet-base-v2 (Song et al., 2020), and Qwen3-Embedding-8B (Zhang et al., 2025b)), sentiment embeddings (sentibert (Yin et al., 2020)), and style embeddings (StyleDistance (Patel et al., 2025)). Table 6 presents their statistical results. Since their p-values are higher than those of the aforementioned models and may result in greater bias, we adopt the three models described above.

C Experiment details and analysis

C.1 Retrieval process

Test data usage: All test sets are treated strictly as target domains. For each target-domain instance, retrieval is performed exclusively from the training split of the remaining source domains.

Training-phase retrieval: During training, retrieval is conducted only within the training data. The retrieval index is built strictly from training-only data and does not include any test samples.

Test-phase retrieval isolation: Test instances do not retrieve from other test instances. Each test sample retrieves only from the pre-defined training-domain index.

Therefore, no training procedure ever accesses test data, and no retrieval index contains any test samples. This design ensures strict separation between training and testing, eliminating the possibility of data leakage through retrieval.

C.2 Clarification on gold label usage in the multi-agent reasoning system

During the reasoning process, gold label hints are provided only if the number of search rounds exceeds 3 and the system still cannot find an answer. This occurs very rarely (AMTCele: 4/240 instances; PHEME: 110/2060 instances; COCO: 226/1162 instances). The slightly higher number in COCO is due to its three-class classification setting, which leads to more complex reasoning paths compared to the binary tasks. When the number of search rounds is fewer than 3 and the answer is incorrect, we only notify the subagent that the summary agent's conclusion is incorrect and ask whether they would like to revise or keep their answer. For the summary agent, across the four strategies used to optimize reasoning paths, we only indicate that the reasoning may be incomplete and do not provide the gold label.

C.3 Experiment settings

We develop two LLMs based on the RAAR framework, namely RAAR-8B and RAAR-14B, which are built upon the reasoning versions of Qwen3-8B and Qwen3-14B, respectively. In stage 1, we select the top two examples for each dimension, details are provided in Section 3.5. Both models are trained in two stages, consisting of SFT followed by RL optimization. During SFT, we set the learning rate to 1e-5 with a warmup ratio of 0.1. Training is conducted for 3 epochs with a batch size of 128. In the RL stage, we perform 8 rollouts per sample with a training batch size of 1024. The model is trained for 5 epochs using a learning rate of 1e-6 and a sampling temperature of 1. We adopt DeepSpeed ZeRO-3 optimization and offload parameters to the CPU to further save GPU memory. For both stages, the maximum input sequence length is 24k tokens, and the maximum output length is 8k tokens. Full-parameter training is carried out on four NVIDIA A100 GPUs (80 GB) in both stages.

C.4 Baseline details

Cross-domain methods: MOSE (Qin et al., 2020) adopts a multi-domain mixture-of-experts (MoE) architecture with a dedicated prediction head for each domain. EDDFN (Silva et al., 2021) is designed to jointly capture domain-specific features and domain-invariant representations. MD-

FEND (Nan et al., 2021) introduces a Domain Gate mechanism to dynamically select the most relevant experts within an MoE framework. CANMD (Yue et al., 2022) addresses label distribution shift through label shift correction and leverages contrastive learning to enhance domain generalization. MetaAdapt (Yue et al., 2023) employs a meta-learning paradigm to enable domain-adaptive few-shot misinformation detection.

LLM-based Adaptation methods: Instruction Tuning: We fine-tune two variants of the model based on Qwen3-8b, including a zero-shot fine-tuned version (IT_zs) (like conspemollm (Liu et al., 2024a)) and a retrieval-augmented fine-tuned version with few-shot examples (IT_ra). **ARG** (Hu et al., 2024) improves smaller models through multi-perspective explanatory reasoning generated by LLMs. **RAEmoLLM** (Liu et al., 2025b) is a misinformation detection framework that enhances in-context demonstration retrieval with emotional information; in our implementation, GPT-4.1 is adopted as the base model, and examples are retrieved based on sentiment intensity. **MARO** (Li et al., 2025) is a multi-agent framework that improves cross-domain misinformation detection by integrating expert agents, question-driven reflection, and cross-domain decision rule optimization.

C.5 Prompt templates

C.5.1 Prompt template for x_{ra}

> **Template for x_{ra}**
> **Task:** *[task description]*
> **Target text:** *[target text]*
>
> Here are a few examples retrieved through sentiment intensity:
> **Text1**: *[text1]*
> **Text2**: *[text2]*
>
> Here are a few examples retrieved through semantic information:
> **Text1**: *[text1]*
> **Text2**: *[text2]*
>
> Here are a few examples retrieved through writing style information:
> **Text1**: *[text1]*
> **Text2**: *[text2]*

C.5.2 Prompt templates for evaluating LLMs

The following are the templates for zero-shot inference and few-shot inference based on RA data. *[task description]* for AMTCele: *"Determine whether the target text is fake or legit."*. *[task description]* for PHEME: *"Classify the target text as rumour or non-rumour."*. *[task description]* for

COCO: *"Determine whether the target text is Unrelated, Related, or Conspiracy. Unrelated means the text contains conspiracy-related keywords but uses them in an unrelated or different context. Related means the text is conspiracy-related but does not propagate conspiracy misinformation. Conspiracy means the text is conspiracy-related and actively propagates or supports the misinformation."*. *[target text]* and is the original text from each dataset. The zero-shot and few-shot instruction-tuning methods are also based on these two templates.

> **Template for constructing SFT dataset**
> **Input:** x_{ra}
> **Output:**
> <think>
> *[CôT]*
> </think>
>
> <answer>
> *[ŷ]*
> </answer>

> **Template for Zero-shot setting**
> **Task:** *[task description]*
> **Target text:** *[target text]*

> **Template for few-shot setting (same with x_{ra})**
> **Task:** *[task description]*
> **Target text:** *[target text]*
>
> Here are a few examples retrieved through sentiment intensity:
> **Text1**: *[text1]*
> **Text2**: *[text2]*
>
> Here are a few examples retrieved through semantic information:
> **Text1**: *[text1]*
> **Text2**: *[text2]*
>
> Here are a few examples retrieved through writing style information:
> **Text1**: *[text1]*
> **Text2**: *[text2]*

C.6 Comparison with training-based methods and cost analysis

	Resources	Train time	Inference (s/item)
IT_ra (8b)	4*A100	1.14h	0.131
RAEmoLLM	1*A100	None	1.592
ARG	1*A100 + API	0.766h	0.185
MARO	OpenAI API	51.9h	1.29
RAAR-8b	4*A100	Reasoning Paths (14h) + SFT (0.57h) + RL (23h)	0.131
RAAR-14b	4*A100	Reasoning Paths (14h) SFT (1h)+ RL (35h)	0.199

Table 7: Computational cost of each method

This section compares the resource and time costs of RAAR with baseline methods. RAAR

Figure 2: Confusion Metrics of zero-shot reasoning models (Reason_zs ablation).

Figure 3: Confusion Metrics of RAAR-8b.

Figure 4: Confusion Metrics of RAAR-14b.

is built upon SFT combined with GRPO, and to ensure a fair comparison we include recent training-based approaches such as ConspemoLLM (IT_ra), RAEmoLLM, MARO, and ARG. Regarding computational cost, we report detailed statistics for both training and inference time, where the training time in the table refers to the total training time across the three datasets. Although RAAR requires longer training time due to the reasoning path construction, SFT and GRPO optimization stages, its average inference time remains competitive and shows certain efficiency advantages. Considering its strong reasoning capability and consistent performance across tasks, RAAR achieves a favorable trade-off between effectiveness and efficiency. In future work, deploying the model on servers as an API service could further improve practical efficiency.

D Error Analysis Details

D.1 Confusion Metrics

D.2 Case Study for RAAR-14b

In this section, we present a case study of RAAR-14b by closely examining its predictions, as it achieves the strongest performance across all evaluation settings. To save space, we have not shown retrieval examples for all instances.

Case Study 1 Dataset: AMTCele

Target Text:

Jennifer Aniston Finally Pregnant At 48 Years Old? | Celeb Dirty Laundry

Jennifer Aniston and Justin Theroux have been married more than a year, so the inevitable pregnancy rumors will begin. According to the latest cover issue of Star Magazine, Jennifer Aniston is "finally" pregnant at 48 years old. Now, we've heard in the past that Jennifer Aniston has struggled to get pregnant, even back when she was married to Brad Pitt.

Error Type: Legit → Fake

Analysis: This article was labeled as fake primarily due to its sensational headline and tabloid style framing. Although the content reports on a celebrity rumor circulating in mainstream entertainment media, the model appears to associate speculative language and celebrity topics with falsity. The presence of a question mark in the headline and emotionally charged phrasing likely triggered a fake prediction, despite the text functioning as standard entertainment reporting rather than fabricated misinformation. This case illustrates how stylistic sensationalism is treated as a proxy for falsity in the model's decision process.

Case Study 2   Dataset: AMTCele
Target Text:

> Brad Pitt Is "Still in Contact" With Ex Jennifer Aniston Following Angelina Jolie Divorce (REPORT)
>
> According to a new report by E! Online, Brad Pitt is still in communication with his ex-wife, Jennifer Aniston. A source tells the outlet that the pair have a "friendly, but limited relationship." The confirmation comes shortly after Us Weekly reported that Pitt had been texting Aniston amid his divorce from Angelina Jolie.

Error Type: Fake → Legit

Analysis: This fabricated gossip article was misclassified as legitimate because it closely follows conventional news-reporting conventions. It cites recognizable media outlets, attributes claims to unnamed sources, and adopts a neutral narrative tone. These surface signals resemble professional journalism, leading the model to accept the content as legitimate. The error shows that the model relies on reporting format and stylistic realism rather than assessing whether the claims are independently verifiable or speculative in nature.

Case Study 3   Dataset: PHEME
Target Text:

> TORONTO: Quick reminder that Prince is seemingly playing @masseyhall tonight. No more details at the minute.
>
> Here are a few examples retrieved through sentiment intensity: Text: Ottawa, be safe, be smart.. The Hill is under attack. The label of this text: non-rumour. Text: We are in full lock down until further notice from Ottawa Police.. The label of this text: rumour.
>
> Here are a few examples retrieved through semantic information: Text: The #sydneysiege is over! Confirmed by Sydney Police on twitter! Thank god! I hope everyone are and stays safe!. The label of this text: non-rumour. Text: Ottawa police are confirming a shooting at the War Memorial.

Minutes ago. No other info. #cbcOTT #OTTnews. The label of this text: non-rumour.

> Here are a few examples retrieved through writing style information: Text: BREAKING: Gunman in #SydneySiege has told police he has "devices all over the city" & demands to speak with Prime Minister, acc. to reports.. The label of this text: rumour. Text: The door is solid, you can't knock it down… it's bulletproof-JimTilmon on NYTimes rpt #Germanwings pilot locked out. The label of this text: rumour.

Error Type: Rumour → Non-rumour

Analysis: This post conveys unverified information about a possible surprise performance, indicated by vague phrasing such as "seemingly" and the absence of official confirmation. However, the model classified it as non-rumour, likely because the message is presented confidently and resembles an announcement rather than speculation. The lack of explicit uncertainty markers, such as "might" or "possibly," led the model to treat the statement as factual. Compared to few-shot examples, the model often relies on overt cues: posts labeled as rumours frequently contain urgent language, emotional intensity, or dramatic stylistic features (e.g., "BREAKING," "all over the city"), whereas this post's neutral, matter-of-fact style aligns more closely with non-rumour examples that report confirmed events. This demonstrates that the model struggles to recognize implicit uncertainty in short social media posts and tends to be misled when unverified information is framed confidently or in a formal announcement style.

Case Study 4   Dataset: PHEME
Target Text:

> #putindead I heard it from a good source that Vladimir Putin was riding a weasel on the back of a woodpecker and he fell off and died.

Error Type: Non-rumour → Rumour

Analysis: This tweet is clearly satirical, using absurd imagery to mock death rumors. Despite this, the model labeled it as a rumour, likely due to literal interpretation of phrases such as "heard it from a good source" and the mention of a public figure's death. The model fails to detect humor and exaggeration, treating the post as a serious information claim rather than parody. This reflects an over-reliance on lexical cues without pragmatic interpretation.

Case Study 5   Dataset: COCO
Target Text:

Good luck & Good luck; remember until Trump gets COVID it's just a Democrat-Deep State-Pedophile Hoax to undermine Trump. BTW Jared me; a Nigerian prince have come up with a vaccine based on experiments by China on Uigher prisoners. Plz invest in our company Total Fraud Inc.

Here are a few examples retrieved through sentiment intensity: Text: That's why they're called the Lying Fake News and they can cover for the Deep State Democrats and their Chinese friends we were not supposed to find out about Flynn Trump or the Wuhan Virus origin so they could monopolize the drug and vaccine market and America gets the short end. The label of this text: Conspiracy (related and supporting). Text: Love how the Q people are willing to believe Soros pays protesters; Hillary eats babies but can't accept that Trump got COVID from hosting super-spreader events; rallies; making fun of people with masks on...they think it was a Deep State Op or something. The label of this text: Related (but not supporting).

Here are a few examples retrieved through semantic information: Text: We'd better isolate the Trump cult so only they can be hurt by their ignorance; indifference to science. I'm worried they'll stop Soc Dist; spread Covid-19. I hear them saying it's a "deep state lib conspiracy" to hurt Trump. The label of this text: Related (but not supporting). Text: Pfizer invested and two Muslim scientists Dr. Şahin and Türeci invented the vaccine for COVID-19 and Trump did what? Shamelessly invented a lie. Maybe his Muslim ban was his input. Trumptards wonder if vaccine is a deep state hoax that they can trust. Ignorance is bliss until.... The label of this text: Related (but not supporting).

Here are a few examples retrieved through writing style information: Text: Even Trump said in a recent presser "we're doing this [insert Deep State/Drain the Swamp with COVID19 shutdown] for them...the children. Present and future generations. I'm a Healthcare care worker forced to take PTO (layoff) because of fear.. The label of this text: Related (but not supporting). Text: Local school gets closed for a week due to a Covid outbreak: Cue local moms screaming that immuno-compromised people should stay home; referring to this as a "Plandemic". This is why case numbers are going up Folks. Selfishness and the death of compassion and common sense.. The label of this text: Unrelated.

Error Type: Conspiracy → Unrelated

Analysis: This post explicitly advances a conspiratorial framing by labeling COVID as a hoax and attributing it to a coordinated plot involving Democrats, the Deep State, and pedophiles. Despite these strong conspiracy indicators, the model predicted Unrelated, suggesting it failed to recognize the conspiratorial claim as the main communicative function. A likely reason is that the sentence is short, colloquial, and the conspiratorial content is compressed into a single compound phrase. Compared with few-shot examples retrieved through sentiment and semantic information, such as texts explicitly linking Trump, the Deep State, or vaccine hoaxes and labeled Conspiracy (related and supporting), this post presents similar thematic content but in a denser, slogan-like format. If the model relies on a narrow set of keyword triggers or expects more elaborated narrative structures, it may mis-handle compressed conspiracy jargon and dismiss it as off-topic rhetoric. This case highlights the model's under-sensitivity to conspiracy cues when they appear as condensed, informal expressions rather than extended argumentative text.

D.3 Case Study for Model Performance Comparison

Across model variants, performance differences are primarily driven by model scale and inference configuration. Smaller zero-shot models rely heavily on shallow heuristics, over-weighting surface cues such as negation, hedging, and source mentions, which results in systematic errors in cases requiring discourse-level integration, including rumor initiation through questioning, denial-as-rumor dynamics, and implicit conspiracy endorsement. Prompting improves task alignment for smaller models, but their predictions remain dominated by explicit lexical patterns rather than integrated reasoning. In contrast, larger models demonstrate stronger holistic reasoning, jointly integrating sentiment, semantics, and pragmatic context. This enables more robust handling of mixed stances, rhetorical camouflage, and implicit presuppositions, leading to more accurate distinctions between discussion and propagation, skepticism and endorsement, and factual reporting and rumor circulation. Overall, increased model scale enhances sensitivity to implicit intent and discourse structure, whereas smaller models remain prone to reasoning fragmentation when surface cues conflict with communicative function.

E Prompt templates for constructing complex reasoning paths

To save space, we have not shown retrieval examples for all instances.

Model Reasoning Performance Comparison Case Study 1 - Fake News

Dataset Name. AMTCele

Instance Content (Original Text).

Jennifer Aniston dashes 'Friends' reunion hopes

Jennifer Aniston has once again broken hearts by shooting down the possibility of a "Friends" reunion. In an interview with ITV, the actress talked about looking back with fondness on working on the beloved, hit NBC series. "Not only was it a gift for us, but it's something people have been able to carry with them," Aniston said. "It's comfort food and it makes them feel better when they are feeling down, when they want to distract themselves." And to answer the question that always seems to come up – will there be a reunion? – Aniston said don't count on it. "I don't know what we would do," she said. "I think that period of time was sort of nostalgic, you know?" "There's something about a time where our faces weren't shoved into cell phones and we weren't, like, checking Facebooks and Instagrams, and we were in a room together – or at a coffee shop together – and we were talking," she added. "And we've lost that." But they can still "be there for you" in syndication, so hold tight to that. You can, however, see Aniston on the big screen when her latest film Office Christmas Party opens December 9.

Gold Label. Legit

8B Zero-shot Prediction. Fake

8B Zero-shot Reasoning. Okay, let's look at this text about Jennifer Aniston and a 'Friends' reunion. Hmm, it's written like a typical celebrity news article—has a headline, quotes her directly, and even mentions a specific interview source, ITV. That feels pretty legit at first glance.

Wait, but I remember that 'Friends' reunion rumors have been all over the place for years. I think there was a big one a few years back where they actually did a special episode or something. So if Aniston said there wouldn't be a reunion, that might be a bit surprising or even contradictory to what happened before.

Let me think... Oh right, there was a Friends: The Reunion special on Netflix in 2021. That was a huge deal. So if this article is saying she shot down the idea, but then a reunion actually happened, that's a problem. The text says she said 'don't count on it' and that the period was 'nostalgic' and 'we've lost that.' But then the Netflix special was a full reunion with all the cast. That seems like a direct contradiction.

Also, the article mentions her new movie Office Christmas Party opening December 9. I think that movie came out in 2017. So the timing here feels off. If this were a real article from when the movie was coming out, it would have been around late 2017. But the Netflix reunion special was in early 2021. So if this article was published in late 2017, it would be predicting something that hadn't happened yet. But if it was published after the reunion, it would be wrong because the reunion did happen.

Let me check the quotes again. She says, 'I think that period of time was sort of nostalgic' and 'we've lost that.' That sounds like she's talking about the past, not ruling out a future event. Saying 'don't count on it' is vague—it could mean she doesn't know, or she doesn't want to speculate. But the Netflix reunion was a real event, so her statement here seems to be wrong.

Oh, and the article is presented as a news report, but it's not from a major outlet like The New York Times or Entertainment Weekly. It's just 'ITV' as the source. That's a bit suspicious—real news outlets usually attribute quotes to specific journalists or have more context. This feels like it could be a fabricated article, maybe from a fake news site, that's using a real quote from a real interview but then making up the whole story about a 'Friends' reunion being shot down, when in fact the opposite happened.

So putting it all together: the core claim—that Aniston said there wouldn't be a 'Friends' reunion—is false because a real reunion happened. The article uses real quotes and a real interview source to make it seem credible, but the main point is fabricated. That's classic fake news: take a few real details to make a false story believable. I think this is fake.

RAAR-8B Prediction. Legit

8B Reasoning. Okay, let me start by reading this target text carefully. It's about Jennifer Aniston supposedly killing 'Friends' reunion hopes. Hmm, the headline is pretty dramatic - 'dashes hopes' and 'broken hearts' - that feels like clickbait language right away.

Wait, but let me check the sentiment examples they provided. The legit 'Walking Dead' example has emotional language too - 'heartbreaking,' 'bittersweet' - but it's presented as genuine interview content. The fake Scarlett Johansson example feels different though, with that awkward 'Easter Eggs' line that doesn't sound like real conversation. Comparing this to the target text, the Aniston quotes do sound natural and emotional, not forced. She's talking about comfort food and nostalgia, which feels authentic.

Now looking at the semantic content - does this make sense? Friends reunion rumors are totally real, and Aniston has been pretty clear about not doing one. The details about how the cast used to interact before social media... that actually rings true based on what I know about the show's history. And the mention of her new movie Office Christmas Party - I think that was real, released around December 2017. This all fits together logically.

Oh, and the writing style - it reads like proper journalism. It's structured like a real news article with attribution, quotes, and background context. The fake examples tend to have more sensational language or awkward phrasing, but this feels professional. The transition from the emotional interview to the business update about her film seems smooth too.

Let me double-check - is there anything that feels off? The quotes sound like something Aniston would actually say. The interview with ITV seems plausible. The timeline checks out. Nothing jumps out as obviously fabricated like that awkward 'Easter Eggs' line in the fake example.

Actually, thinking about it more - this reminds me of how real entertainment news often works. Celebrities do express nostalgia about old shows, and the social media comparison feels like genuine commentary. The article even acknowledges the irony of being on phones now versus being together in person.

I'm leaning toward this being legit. The emotional tone matches real interview content, the facts check out, and the writing style is professional. It doesn't have the red flags I saw in the fake examples. The sentiment feels authentic rather than manufactured for clicks.

RAAR-14B Prediction. Legit

14B Reasoning. Okay, let me start by reading this target text carefully. It's about Jennifer Aniston saying there won't be a Friends reunion. Hmm, the tone feels right - she's nostalgic but realistic, not overly emotional or sensational. That reminds me of the legit examples where actors talk about their work in a measured way.

Wait, let me check the sentiment examples they provided. The fake Scarlett Johansson one felt different - it had this weird mix of reluctance and excitement that didn't quite match. But this Aniston piece? She's genuinely reflective about the past, talking about how the show provided comfort, and then clearly states there's no reunion. The emotional flow feels natural, not manufactured.

Now looking at the semantic details - oh, this is important. The text mentions specific things: ITV interview, December 9 release date for her movie, the exact quote structure with 'I think that period of time was sort of nostalgic.' These aren't vague claims - they're concrete details that would be hard to fake convincingly. Legit news usually includes these verifiable elements.

Also, the writing style feels professional. It's structured like real journalism - headline, attribution, direct quotes, background context. Reminds me of the Columbia acceptance error story they labeled as legit. The language is formal but accessible, with proper punctuation and balanced sentences.

Let me double-check against the fake patterns. The fake examples often have inconsistencies or emotional whiplash. But here, everything hangs together logically. She talks about the show's legacy, acknowledges the reunion question, gives her answer, and then naturally transitions to her current project. No red flags in the narrative flow.

Hmm, all three angles - sentiment, semantics, and style - seem to point in the same direction. The sentiment is authentic nostalgia, the details are specific and verifiable, and the writing matches professional standards. There's no internal contradiction that would make me suspicious.

Oh, and thinking about it independently - I remember hearing about Jennifer Aniston discussing Friends reunions in interviews. The content aligns with what I'd expect from a real celebrity interview. Nothing feels exaggerated or implausible.

So putting it all together: the emotional tone feels genuine, the specific details check out, the writing is professional, and it matches real-world knowledge. Everything consistently suggests this is legitimate reporting rather than fabricated content.

Analysis: This case highlights clear differences in reasoning reliability across model scales and inference paradigms. The 8B zero-shot model misclassifies the instance by over-relying on external world knowledge and post-hoc factual verification (e.g., later real-world reunion events), introducing temporal leakage that is inappropriate for the task setting. In contrast, both the 8B and 14B models correctly predict the label by grounding their decisions in intrinsic textual cues, including narrative coherence, quotation structure, and stylistic consistency, rather than speculative external validation.
Comparing the two non-zero-shot models, the 14B model demonstrates more stable and concise reasoning, integrating sentiment, semantics, and writing style into a unified judgment without overfitting to individual cues. The 8B model reaches the correct conclusion but relies on more surface-level heuristics and explicit pattern matching. Overall, this example illustrates that larger models exhibit stronger capacity for holistic reasoning and internal evidence integration, while smaller zero-shot models are more prone to reasoning drift when unsupported by task-aligned inductive biases.

Model Reasoning Performance Comparison Case Study 2 - Rumour

Dataset Name. PHEME

Instance Content (Original Text).

Security at Massey Hall tells CP24 there is NO Prince show #Toronto #prince'd #purple'd

Here are a few examples retrieved through sentiment intensity: Text: "Contrary to earlier reports no incident occurred near the Rideau Centre," Ottawa police say. #cbcOTT OTTnews. The label of this text: rumour. Text: #Ottawa City Hall is currently in lock-down. Please avoid the area.. The label of this text: non-rumour.

Here are a few examples retrieved through semantic information: Text: Rideau Centre general manager tell globeandmail there was no shooting inside the mall. But people can't leave or enter. #OttawaShooting. The label of this text: rumour. Text: #CNN frustrated by Canadians' lack of panic. #OttawaShooting #cdnpoli. The label of this text: non-rumour.

Here are a few examples retrieved through writing style information: Text: All my prayers are going to the hostages in Sydney.. And all not Muslims are terrorists..It's a religion of peace.. The label of this text: non-rumour. Text: Harper to make statement today after gunman shot dead in #Parliament. PM safe, not on Parliament Hill, being briefed by security officials.. The label of this text: rumour.

Gold Label. Rumour

8B Zero-shot Prediction. Non-rumour

8B Zero-shot Reasoning. Okay, let's look at this text. It says security at Massey Hall told CP24 there's no Prince show. Hmm, first impression—this sounds like a direct statement from an official source, not some random guess. Wait, but the task is to figure out if it's a rumour or not. What makes something a rumour? Usually, it's unverified information that's spreading, right? Like when people share something without knowing if it's true, and it gets passed around.
Let me think about this specific claim. Prince was a huge artist, and Massey Hall is a big venue in Toronto. I remember there was a lot of buzz about a Prince show there a few years back. So this isn't some obscure event—it's a real, high-profile thing that people were talking about.
Now, the text says security specifically told CP24, which is a local news station. That's a credible source. If security at the venue is saying there's no show, that's pretty definitive. It's not like they're saying 'maybe' or 'I heard something.' It's a flat 'NO.'
Also, the hashtags #Toronto and #prince'd #purple'd give context—it's about a Prince concert in Toronto, and those hashtags were really popular back then. So this is likely from that time period. Hold on, though. Just because it sounds official doesn't automatically make it non-rumour. Sometimes rumours dress up as official statements to seem more believable. But here, the claim is so specific and negative—it's denying a show that was widely expected. If there really was no show, then this is just a factual correction, not a rumour.
Let me consider the opposite: what if this was a rumour? Then it would be unverified, maybe false, and spreading uncertainty. But the text presents it as a direct quote from security to a news outlet. That's verification right there. News outlets usually check with sources before reporting. Oh, and the tone is matter-of-fact, not speculative. No 'I heard that...' or 'People are saying...' It's stated as a fact from a source. That leans toward non-rumour.
Wait, but could it be a rumour if the source itself was unreliable? Like, what if the security person wasn't official or the news report was wrong? But the text doesn't cast doubt—it just reports what security said. In rumour classification, we usually go by the text's own presentation. If it's presented as a verified report, it's non-rumour.
Yeah, I think this is non-rumour. It's a straightforward denial from an official source about a public event. No speculation, no uncertainty, just a clear statement. The hashtags and context make it even more concrete—it's about a real event that was in the news.
Final check: If I saw this tweet, would I think it's spreading unverified info? Probably not—I'd think it's a news update. So, non-rumour it is.

RAAR-8B Prediction. Rumour

8B Reasoning. Okay, let me start by reading the target text carefully. It says 'Security at Massey Hall tells CP24 there is NO Prince show' with hashtags about Toronto and Prince. Hmm, the word 'NO' in all caps really stands out—it feels like it's trying to emphasize they're denying something strongly.
Now, looking at the sentiment examples: The first one about Ottawa police denying an incident is labeled rumour, even though it's a denial. That makes me think maybe denials can still spread uncertainty. The second one about City Hall lockdown is straightforward and non-rumour. So, sentiment-wise, this target text seems similar to the rumour example because it's a strong denial, but I'm not sure if that automatically makes it a rumour.
Moving to the semantic examples: The one where the mall manager denies a shooting but people can't leave is labeled rumour. That's interesting—it's a denial but still feels like it's part of a rumour cycle. The CNN example is just an opinion and is non-rumour. So, semantically, this target text is denying a Prince show, but it's citing a specific source (Massey Hall security), which might make it seem more credible. But wait, the mall manager example also cites a source and is still rumour, so maybe the act of denying something in a crisis is what matters, not just the source.
Then, the writing style examples: The prayer message is personal and non-rumour, while the one about Harper making a statement is rumour because it's speculative. The target text has hashtags and a declarative tone, which feels more like the rumour example—it's presenting information authoritatively but in a way that could be misinterpreted.
Putting it all together: I'm leaning toward rumour because the text is denying a Prince show, and in the examples, denials during events like the Ottawa shooting were often rumours. Even though it cites a source, the style and context suggest it's part of a rumour mill—like when people share unverified info to settle debates. So, yeah, I think this is rumour.

RAAR-14B Prediction. Rumour

14B Reasoning. Okay, let me start by reading the target text carefully. It says security at Massey Hall told CP24 there's NO Prince show happening in Toronto, with hashtags like #prince'd and #purple'd. Hmm, the tone feels definitive with that 'NO' in caps, but I need to figure out if this is spreading a rumour or just stating facts.
Looking at the sentiment examples, the rumour one says 'Contrary to earlier reports no incident occurred' – that's correcting something that was already circulating. The non-rumour is just a straightforward lockdown notice. This target text feels more like the non-rumour because it's not correcting previous misinformation, it's just stating what security said directly.
Wait, let me check the semantic examples. The rumour one mentions 'no shooting inside the mall' but then says people can't leave or enter – that creates uncertainty. The non-rumour is just about CNN being frustrated. The target text seems closer to the non-rumour here because it's a simple denial without adding any ambiguous details about the situation.
Now for the writing style examples – the non-rumour is personal prayers, while the rumour has that formal 'PM safe, not on Parliament Hill' structure. The target text has that authoritative 'Security at Massey Hall tells CP24' phrasing, which feels more like the rumour style with its official sources and specific details.
Hmm, I'm getting conflicting signals here. The sentiment and semantic analysis point toward non-rumour, but the writing style suggests rumour. Let me think about this differently – what makes something a rumour versus just factual reporting?
Oh, I see the key difference now. Rumours often involve correcting or denying claims that are already circulating in public discourse. This text is specifically denying a Prince show, which implies there were rumours or expectations about such a show happening. The hashtags #prince'd and #purple'd are clearly referencing Prince fandom, so this is directly engaging with a potential rumour about a concert.
Also, the structure 'Security at Massey Hall tells CP24' is similar to how rumours often get attributed to official sources to lend credibility. Even though it's a denial, it's still participating in the rumour ecosystem by addressing something that people were likely talking about. Let me double-check – if there were no circulating rumours about a Prince show, this would just be routine information. But since it's specifically denying it, that means the denial is responding to some unverified claims. That pushes it into rumour territory for me.
Yeah, I think the writing style expert had the right insight here. The authoritative framing and specific source attribution, combined with the fact that it's denying something that was apparently being discussed, makes this a rumour. It's not just neutral reporting – it's engaging with and trying to correct potential misinformation.

Analysis: This case further illustrates how model scale affects sensitivity to conversational context and rumor dynamics. The 8B zero-shot model misclassifies the instance by equating explicit source attribution and declarative tone with factual verification, treating the denial as authoritative news rather than as part of an ongoing rumor discourse. Its reasoning remains confined to surface-level indicators of credibility, such as named sources and definitive language, without modeling the broader communicative context in which such denials typically arise.
The prompted 8B model improves upon this by recognizing that denials themselves can function as rumor-carrying acts, particularly when responding to widely circulated expectations. However, its reasoning still relies heavily on analogical pattern matching to prior examples (e.g., crisis denials), leading to a less stable integration of semantic and pragmatic cues. In contrast, the 14B model correctly captures the discourse-level function of the text, identifying that explicit negation ("NO Prince show") presupposes an existing rumor and actively participates in its circulation. Larger models exhibit stronger capacity for pragmatic reasoning, enabling them to infer implicit presuppositions and communicative intent beyond literal content. Overall, this case demonstrates that increased model scale primarily enhances the ability to reason over implicit social context, which is critical for accurate rumor classification.

Model Reasoning Performance Comparison Case Study 3 - Conspiracy

Dataset Name. COCO

Instance Content (Original Text).

Conspiracy/not... This virus so massively attack people at wuhan some army barricade in-out gate to wuhan when i watch this video i feel china govt. Do depopulation but i hope people in wuhan can recover and back to normal again.

Gold Label. Conspiracy

8B Zero-shot Prediction. Related

8B Zero-shot Reasoning. Okay, let me read this carefully. The text starts with 'Conspiracy/not...'—that's interesting, like someone is setting up a contrast right away. Hmm, it's talking about the virus attacking people in Wuhan, and mentions an army barricade at the gate. That immediately brings to mind the early pandemic lockdowns and the initial speculation about the virus's origin.

Wait, the person says they watched a video and felt the Chinese government was doing depopulation. That's a really strong claim—depopulation is a huge conspiracy theory about governments intentionally reducing population. But then they immediately add 'but I hope people in Wuhan can recover and back to normal again.' So there's a personal hope mixed in with that fear.

Let me think about the definitions. 'Unrelated' would be if they used words like 'depopulation' in a totally different context, like talking about a movie plot or a demographic study. But here, it's directly about the pandemic and Wuhan, so it's definitely related to conspiracy themes.

Now, is it 'Conspiracy'—meaning it actively propagates the misinformation? The text states the feeling as a personal reaction ('I feel'), not as a stated fact. It's more like an emotional interpretation of what they saw. They're not saying 'The Chinese government is secretly depopulating Wuhan' as a flat claim; they're expressing a suspicion. That feels more like 'Related'—it's engaging with the conspiracy idea but not pushing it as truth.

Also, the hopeful ending shows they're not fully endorsing the conspiracy; they're still wishing for recovery. That balance makes it seem like they're discussing the theory rather than spreading it. If it were 'Conspiracy,' it might be more direct, like 'The Chinese government is using the virus for depopulation.' This is subtler.

So, putting it all together: the text is clearly about a conspiracy theory (depopulation during the pandemic), but it's framed as a personal feeling mixed with hope. That fits 'Related'—it's conspiracy-related but doesn't actively propagate the misinformation as fact. Yeah, that makes sense.

RAAR-8B Prediction. Conspiracy

8B Reasoning. Okay, let me start by reading this target text carefully. It begins with 'Conspiracy/not...' which immediately makes me pause - that feels like someone trying to decide whether to classify something as conspiracy or not. Hmm, but then they immediately jump into talking about the virus attacking Wuhan and army barricades, and then they say 'I feel China govt. Do depopulation.' That's pretty strong language right there.

Wait, depopulation is a really heavy accusation - that's not just questioning something, that's making a serious claim about intentional mass reduction. And they're connecting it to specific events in Wuhan with army barricades, which reminds me of those early COVID conspiracy theories about China covering things up.

Let me compare this to the examples they gave. The first conspiracy example talks about vaccines being used to chip people and says 'the conspiracy people were right' - that's clearly supporting conspiracy theories. The second one about global control and population control is also clearly pushing conspiracy thinking. My text feels similar in tone - it's not just mentioning conspiracy topics, it's actively drawing conclusions about intentional depopulation.

Oh, and looking at the unrelated examples - like the spiritual healing one or the Modi accountability text - those use conspiracy-related terms but in completely different contexts. My text is directly about COVID and government actions, so it's definitely not unrelated.

The related example about chemtrails is interesting - that person is just discussing the topic without really endorsing it, saying 'I know about chemtrails' but then questioning visibility. My text goes much further - it's making definitive claims about depopulation based on observations.

Also, the emotional language stands out - 'massively attack people,' 'I feel China govt. Do depopulation,' and hoping people recover. This isn't neutral discussion - there's strong personal conviction and emotional investment in this narrative.

Let me double-check - is there any way this could be just related without supporting? No, because they're not questioning or discussing possibilities - they're stating their belief as fact. The 'I feel' makes it personal endorsement, not just information sharing.

And it's definitely not conspiracy in the sense of just mentioning terms - they're actively propagating the idea that the government is intentionally depopulating people through COVID measures. That's serious misinformation.

So putting it all together - this text is conspiracy-related, it's actively supporting and spreading that conspiracy theory rather than just discussing it, and it's making definitive claims about intentional harm. That fits the 'Conspiracy' classification perfectly.

RAAR-14B Prediction. Conspiracy

14B Reasoning. Okay, let me start by reading this target text carefully. It says: 'Conspiracy/not... This virus so massively attack people at wuhan some army barricade in-out gate to wuhan when i watch this video i feel china govt. Do depopulation but i hope people in wuhan can recover and back to normal again.'

Hmm, right away I notice the word 'Conspiracy' right at the beginning, which immediately signals this is conspiracy-related content. But the rest of the text is a bit messy and emotional.

Let me think about the sentiment here. The person says they 'feel china govt. Do depopulation' - that's pretty strong language. They're not just mentioning the idea, they're expressing a personal feeling that this is happening. And then they follow it with 'but i hope people in wuhan can recover' - so there's some genuine concern mixed in. This feels similar to those conspiracy examples where people express fear and suspicion while still having some empathy.

Now looking at the actual content - they're claiming the virus is 'massively attack[ing]' people in Wuhan, that there were army barricades, and that this feels like depopulation. These are specific claims about what's happening, not just general speculation. It's not like the unrelated example where someone mentions conspiracy terms but in a completely different context.

Wait, let me compare this to the examples. The 'Unrelated' examples use conspiracy terms but in totally different ways - like the spiritualist talking about machines or someone using 'dalali' in a different context. This text is clearly about the conspiracy theory itself.

And it's definitely not like the 'Related' example where someone mentions chemtrails but is open to discussion and not really pushing the theory. Here, the person is actively stating their feelings about depopulation happening.

The writing style is interesting too - it's fragmented and emotional, with 'Conspiracy/not' at the beginning like they're trying to figure something out. It reminds me of the 'Conspiracy' examples that have that urgent, emotional tone.

So putting it all together: this text is definitely conspiracy-related because it's talking about depopulation theories. And it's not just mentioning them - it's actively propagating the idea by saying 'i feel china govt. Do depopulation' based on what they saw in a video. Even though there's that hopeful ending, the core message is pushing the conspiracy narrative.

Yeah, this has to be 'Conspiracy' - it's related to conspiracy theories and it's actively supporting and spreading that misinformation, just like the other conspiracy examples.

Analysis. This case highlights a critical distinction in how models attribute belief and intent in conspiracy-related content. The 8B zero-shot model misclassifies the instance as *Related* by treating explicit hedging cues (e.g., "I feel" and expressions of hope) as sufficient evidence of non-endorsement. Its reasoning relies on a narrow interpretation of conspiracy propagation, assuming that misinformation must be asserted as an objective fact rather than as a personally endorsed belief grounded in affective interpretation.
In contrast, both the prompted 8B and 14B models correctly identify the instance as *Conspiracy* by recognizing that first-person belief statements ("I feel China govt. do depopulation") constitute active propagation under COCO's definition, even when framed emotionally or accompanied by empathetic language. The prompted 8B model demonstrates improved boundary awareness by distinguishing discussion from endorsement, but it still depends on explicit lexical cues and emotional intensity to justify its decision. The 14B model further exhibits greater reasoning stability, integrating belief attribution, causal implication, and discourse framing into a unified judgment without over-weighting surface hedging. Increasing model scale enhances sensitivity to implicit endorsement and belief commitment, which is essential for reliable conspiracy detection.

Model Reasoning Performance Comparison Case Study 4 - Conspiracy

Dataset Name. COCO

Instance Content (Original Text).

It's a pretty big leap from "5G frequencies can impact cells" to "5G is a trigger that will activate a Coronavirus plague!" tho isn't it? Coronaviris is a bioweapon combining a cold bug with HIV. Wtf does that have to do with 5G? Plenty of legitimate weirdness w/o making it up.

Gold Label. Conspiracy

8B Zero-shot Prediction. Related

8B Zero-shot Reasoning. Okay, let me read this carefully. The text is talking about 5G and COVID-19, which immediately makes me think of that conspiracy theory that 5G towers caused or spread the virus. Hmm, but the author isn't just stating that theory—they're actually questioning it.
Wait, they start by saying it's a 'pretty big leap' from one idea to another. That sounds like they're pointing out a logical jump, not agreeing with it. Then they ask, 'Wtf does that have to do with 5G?' which is clearly expressing confusion or disbelief about the connection.
Oh, and they mention the virus being a 'bioweapon combining a cold bug with HIV.' That's another common conspiracy claim, but again, the tone here feels critical. The author seems to be mocking or challenging these ideas, not endorsing them.
Let me check the definitions. 'Unrelated' would be if they used these keywords in a totally different context, like talking about 5G internet speeds or a movie plot. But here, they're directly addressing the conspiracy theories, so it's definitely related.
Now, is it 'Conspiracy'? That would mean they're actively spreading or supporting the misinformation. But the text does the opposite—it questions the leap, asks why it matters, and even says there's 'plenty of legitimate weirdness' without making things up. They're not pushing the narrative; they're poking holes in it.
So, it's conspiracy-related because it's about those theories, but it doesn't propagate them. That fits 'Related' perfectly. The author is engaging with the topic to debunk or critique it, not to promote it. Yeah, that makes sense.

RAAR-8B Prediction. Related

8B Reasoning. Okay, let me start by reading this target text carefully. The person is talking about 5G and coronavirus, but they're clearly questioning the connection. They say it's a 'pretty big leap' from one idea to another, which already sounds skeptical. Hmm, looking at the sentiment examples - the first one where someone says coronavirus theories are crazy but acknowledges a lab leak possibility was labeled Unrelated. That feels similar to what's happening here - the speaker isn't fully endorsing the conspiracy.
Wait, but then there's the second sentiment example where someone definitively says 'It is a bioweapon' and that's labeled Conspiracy. That's different - they're stating it as fact rather than questioning it.
Now looking at the semantic examples - the first one where someone says 'could also be an unfinished bioweapon' but then says 'of all the conspiracy theories are crazy' was Unrelated. The second one where someone describes what others are saying about vaccines being poison and microchips, but clearly doesn't endorse it, was Related.
Oh, and the writing style examples show that questioning conspiracy theories or being critical of them gets labeled Related, while supporting them gets Conspiracy.
Let me think about this target text again. The speaker says 'Coronaviris is a bioweapon combining a cold bug with HIV' - that sounds like they're stating a conspiracy theory as fact. But then they immediately question how that connects to 5G, saying 'Wtf does that have to do with 5G?' and talking about 'plenty of legitimate weirdness w/o making it up.'
Wait, that's interesting - they're presenting the bioweapon theory but then immediately undermining it by questioning the connection. This feels more like they're using the conspiracy theory as an example to make a point about how people jump to conclusions, rather than actually promoting the theory itself.
Comparing to the examples - when someone says 'It is a bioweapon' definitively, that's Conspiracy. When someone says 'could also be' while dismissing other theories, that's Unrelated. But here, they're stating the bioweapon theory as fact while simultaneously casting doubt on its relevance to 5G.
Hmm, but the main thrust seems to be about the logical leap between 5G and coronavirus, not really about whether coronavirus is a bioweapon. The bioweapon claim seems to be serving as an example of what people are connecting to 5G, rather than being the main point.
Also, the tone feels more like someone making a rhetorical point about conspiracy thinking patterns rather than trying to convince others of the bioweapon theory. The 'Wtf does that have to do with 5G?' and 'plenty of legitimate weirdness' suggests they're being critical of the whole approach. Looking back at the definitions - Unrelated would be if they used conspiracy keywords in a completely different context. Related means conspiracy-related but not propagating. Conspiracy means actively supporting.
This feels like it's conspiracy-related because it's directly discussing 5G and coronavirus conspiracy theories, but it's not actively propagating them - in fact, it's questioning the logic behind them. The speaker seems to be using these theories as examples of flawed reasoning rather than endorsing them.
Yeah, I think this fits better as Related. It's engaging with conspiracy content but doing so critically rather than supportively. The primary focus is on the logical connection between unrelated concepts, not on promoting the conspiracy theories themselves.

RAAR-14B Prediction. Conspiracy

14B Reasoning. Okay, let me start by reading the target text carefully. It says: 'It's a pretty big leap from "5G frequencies can impact cells" to "5G is a trigger that will activate a Coronavirus plague!" tho isn't it? Coronaviris is a bioweapon combining a cold bug with HIV. Wtf does that have to do with 5G? Plenty of legitimate weirdness w/o making it up.'
Hmm, the tone feels skeptical right away—phrases like 'pretty big leap' and 'wtf does that have to do with 5G?' suggest the author is questioning the logic of connecting 5G to coronavirus. But then there's that line: 'Coronaviris is a bioweapon combining a cold bug with HIV.' Wait, that's a strong conspiracy claim about COVID-19 being a bioweapon, which is a common misinformation theory.
Let me check the task definitions again. 'Unrelated' means conspiracy keywords are used in a different context, 'Related' means the text is about conspiracies but doesn't spread them, and 'Conspiracy' means it actively propagates or supports the misinformation.
Looking at the sentiment examples, one text mentions coronavirus as a bioweapon but is labeled 'Unrelated' because it's discussing it in a different context. Another is labeled 'Conspiracy' for stating it as fact. Here, the target text seems to be pushing the bioweapon idea as if it's true, not just discussing it neutrally.
Now, the semantic examples: one is 'Unrelated' when it's just mentioning a conspiracy theory without endorsing it, and another is 'Related' when it's talking about vaccine conspiracies but not supporting them. In the target text, the bioweapon claim is presented as a fact ('Coronaviris is a bioweapon'), which feels like it's propagating the misinformation, not just referencing it.
Also, the style examples show that texts questioning conspiracies or discussing them without support are 'Related.' But here, the author isn't just questioning—they're stating the bioweapon theory as a given, even while rhetorically dismissing the 5G link. That subtle shift makes it seem like they're endorsing the bioweapon part.
Wait, let me double-check: the 'wtf' part is clearly skeptical about 5G, but the bioweapon statement is straightforward. It's like they're saying, 'Oh, and by the way, coronavirus is a bioweapon too.' That feels like they're adding another layer of misinformation, not just critiquing one. Comparing to the 'Conspiracy' example where someone says 'It is a bioweapon' directly, this text does the same—it's not framed as a theory or speculation but as a fact. So, it's actively spreading that false claim.
I think the key is that the text goes beyond just being related to conspiracies; it's putting out there that coronavirus is a bioweapon, which is a known piece of misinformation. Even with the skepticism about 5G, the bioweapon part is presented as truth, making it propagate the conspiracy. So, overall, this fits 'Conspiracy' because it's not just talking about the theories—it's supporting and spreading them.

Analysis: This case exposes a subtle but important distinction in how models resolve internally mixed stances within conspiracy-related discourse. Both the 8B zero-shot and prompted 8B models misclassify the instance as *Related* by prioritizing explicit skeptical markers (e.g., rhetorical questions and dismissive phrasing toward the 5G claim) and treating them as evidence of non-endorsement. Their reasoning fragments the text into locally skeptical segments, failing to reconcile these with the unqualified assertion that "Coronavirus is a bioweapon," which constitutes active propagation under RAAR's definition.
In contrast, the 14B model correctly classifies the instance as *Conspiracy* by integrating contradictory cues into a coherent belief-level interpretation. Rather than evaluating skepticism and endorsement in isolation, it recognizes that explicitly stated conspiracy claims remain propagative even when embedded within partial critique or irony. Larger models exhibit stronger capacity for holistic reasoning, enabling them to attribute implicit belief commitment and weigh conflicting discourse signals appropriately. Overall, this case demonstrates that increased model scale improves robustness against rhetorical camouflage, allowing larger models to avoid under-classifying conspiratorial content that mixes critique with assertion.

Sentiment Agent
1. Initial prompt for Sentiment Agent:

"""<question>
{}
</question>

You are an expert in sentiment analysis. You need to collaborate with a semantic analysis expert and a writing style analysis expert to address the above problem. Your primary responsibility is the sentiment analysis component. Respond to the question from the perspective of sentiment analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.
The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
]
}}
```"""

2. Double-check prompt for Sentiment Agent:

"""<question>
{}
</question>

<previous response>
{}
</previous response>

<response requirements>

You are an expert in sentiment analysis. You need to collaborate with a semantic analysis expert and a writing style analysis expert to address the above problem. Your primary responsibility is the sentiment analysis component. Respond to the question from the perspective of sentiment analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

</response requirements>

<question> represents the question to be answered, and <previous response> contains your prior answer. An overseeing expert has integrated the opinions of your three experts, but the final answer is incorrect. Please double-check your answer. If you still stand by your judgment, provide additional evidence. If you find an issue, provide a revised judgment along with your reasoning.

Output Format
The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
]
}}
```"""

3. Communication prompt for Sentiment Agent:

"""<question>
{}
</question>

<previous response>
{}
</previous response>

<semantic agent>
{}
</semantic agent>

<style agent>
{}
</style agent>

<response requirements>

You are an expert in sentiment analysis. You need to collaborate with a semantic analysis expert and a writing style analysis expert to address the above problem. Your primary responsibility is the sentiment analysis component. Respond to the question from the perspective of sentiment analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

</response requirements>

<question> represents the question to be answered, and <previous response> contains your prior answer. <semantic agent> and <style agent> are the corresponding examples and analysis from a semantic analysis expert and a writing style analysis expert. In the last round, an overseeing expert has integrated the opinions of your three experts, but the final answer is incorrect. At this communication stage, please double-check your answer and consider the feedback from the other experts. If you still stand by your judgment, provide additional evidence. If you find an issue, provide a revised judgment along with your reasoning.
Output Format
The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
]
}}
```"""

4. Hint prompt for Sentiment Agent:

"""<question>
{}
</question>

<previous response>
{}
</previous response>

<response requirements>

You are an expert in sentiment analysis. You need to collaborate with a semantic analysis expert and a writing style analysis expert to address the above problem. Your primary responsibility is the sentiment analysis component. Respond to the question from the perspective of sentiment analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

</response requirements>

<question> represents the question to be answered, and <previous response> contains your prior answer. An overseeing expert has integrated the opinions of your three experts, but the final answer is incorrect. Now, I'll secretly tell you that the labeled answer is "{}", but you must pretend not to know. Please refine your answer accordingly to ensure the final answer aligns with the correct one.

Output Format
The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
]
}}
```"""

Semantic Agent

1. Initial prompt for Semantic Agent

"""<question>
{}
</question>

You are an expert in semantic analysis. You need to collaborate with a sentiment analysis expert and a writing style analysis expert to address the above problem. Your primary responsibility is the semantic analysis component. Respond to the question from the perspective of semantic analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
] }}
```"""

2. Double-check prompt for Semantic Agent:

"""<question>
{}
</question>

<previous response>
{}
</previous response>

<response requirements>

You are an expert in semantic analysis. You need to collaborate with a sentiment analysis expert and a writing style analysis expert to address the above problem. Your primary responsibility is the semantic analysis component. Respond to the question from the perspective of semantic analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

</response requirements>

<question> represents the question to be answered, and <previous response> contains your prior answer. An overseeing expert has integrated the opinions of your three experts, but the final answer is incorrect. Please double-check your answer. If you still stand by your judgment, provide additional evidence. If you find an issue, provide a revised judgment along with your reasoning.

Output Format
The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
]
}}
```"""

3. Communication for Semantic Agent:

"""<question>
{}
</question>

<previous response>
{}
</previous response>

<sentiment agent>
{}
</sentiment agent>

<style agent>
{}
</style agent>

<response requirements>

You are an expert in semantic analysis. You need to collaborate with a sentiment analysis expert and a writing style analysis expert to address the above problem. Your primary responsibility is the semantic analysis component. Respond to the question from the perspective of semantic analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

</response requirements>

<question> represents the question to be answered, and <previous response> contains your prior answer. <sentiment agent> and <style agent> are the corresponding examples and analysis from a sentiment analysis expert and a writing style analysis expert. In the last round, an overseeing expert has integrated the opinions of your three experts, but the final answer is incorrect. At this communication stage, please double-check your answer and consider the feedback from the other experts. If you still stand by your judgment, provide additional evidence. If you find an issue, provide a revised judgment along with your reasoning.

Output Format
The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
]
}}
```"""

4. Hint prompt for Semantic Agent:

"""<question>
{}
</question>

<previous response>
{}
</previous response>

<response requirements>

You are an expert in semantic analysis. You need to collaborate with a sentiment analysis expert and a writing style analysis expert to address the above problem. Your primary responsibility is the semantic analysis component. Respond to the question from the perspective of semantic analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

</response requirements>

<question> represents the question to be answered, and <previous response> contains your prior answer. An overseeing expert has integrated the opinions of your three experts, but the final answer is incorrect. Now, I'll secretly tell you that the labeled answer is "{}", but you must pretend not to know. Please refine your answer accordingly to ensure the final answer aligns with the correct one.

Output Format
The output format must strictly follow the JSON structure below:
```json
{{
"response": [
{{"judgment": "...", "reason": "..."}},
]
}}
```"""

Style agent
1. Initial prompt for Style Agent:

"""<question>
{}
</question>

You are an expert in writing style analysis. You need to collaborate with a sentiment analysis expert and a semantic analysis expert to address the above problem. Your primary responsibility is the writing style analysis component. Respond to the question from the perspective of writing style analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
]
}}
```"""

2. Double-check prompt for Style Agent

"""<question>
{}
</question>

<previous response>
{}
</previous response>

<response requirements>

You are an expert in writing style analysis. You need to collaborate with a sentiment analysis expert and a semantic analysis expert to address the above problem. Your primary responsibility is the writing style analysis component. Respond to the question from the perspective of writing style analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

</response requirements>

<question> represents the question to be answered, and <previous response> contains your prior answer. An overseeing expert has integrated the opinions of your three experts, but the final answer is incorrect. Please double-check your answer. If you still stand by your judgment, provide additional evidence. If you find an issue, provide a revised judgment along with your reasoning.

Output Format
The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
]
}}
```"""

3. Communication prompt for Style Agent:

"""<question>
{}
</question>

<previous response>
{}
</previous response>

<sentiment agent>
{}
</sentiment agent>

<semantic agent>
{}
</semantic agent>

<response requirements>

You are an expert in writing style analysis. You need to collaborate with a sentiment analysis expert and a semantic analysis expert to address the above problem. Your primary responsibility is the writing style analysis component. Respond to the question from the perspective of writing style analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

</response requirements>

<question> represents the question to be answered, and <previous response> contains your prior answer. <sentiment agent> and <semantic agent> are the corresponding examples and analysis from a sentiment analysis expert and a semantic analysis expert. In the last round, an overseeing expert has integrated the opinions of your three experts, but the final answer is incorrect. At this communication stage, please double-check your answer and consider the feedback from the other experts. If you still stand by your judgment, provide additional evidence. If you find an issue, provide a revised judgment along with your reasoning.

Output Format
The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
]
}}
```"""

4. Hint prompt for Style Agent:

"""<question>
{}
</question>

<previous response>
{}
</previous response>

<response requirements>

You are an expert in writing style analysis. You need to collaborate with a sentiment analysis expert and a semantic analysis expert to address the above problem. Your primary responsibility is the writing style analysis component. Respond to the question from the perspective of writing style analysis, incorporating retrieved examples. Provide your judgment along with well-reasoned evidence or explanations.

</response requirements>

<question> represents the question to be answered, and <previous response> contains your prior answer. An overseeing expert has integrated the opinions of your three experts, but the final answer is incorrect. Now, I'll secretly tell you that the labeled answer is "{}", but you must pretend not to know. Please refine your answer accordingly to ensure the final answer aligns with the correct one.

Output Format
The output format must strictly follow the JSON structure below:
```json
{{
"response": [
"judgment": "...", "reason": "...",
]
}}
```"""

Summary Agent

1. query_Summary_prompt_init:

"""\<question>
{}
</question>

<sentiment>
{}
</sentiment>

<semantic>
{}
</semantic>

<style>
{}
</style>

Please respond to the above question <question> using the Chain of Thought (CoT) reasoning method. During the reasoning process, please consider information from the three expert agents. <sentiment> denotes analysis based on sentiment and examples retrieved by sentiment intensity. <semantic> denotes analysis based on semantics and examples retrieved by semantic information. <style> denotes analysis based on writing style and examples retrieved by writing style. And you may also incorporate your own independent reasoning.
Your response should consist of multiple steps, each of which includes three types of actions: **"Inner Thinking"**, **"Final Conclusion"**, and **"Verification"**:

- **'Inner Thinking'**: This is the step where thinking is done. Note that multiple 'Inner Thinking' steps are required to describe thorough reasoning. Each step should first generate a brief title.
- **'Final Conclusion'**: At this stage, you summarize the correct reasoning from previous 'Inner Thinking' steps and provide the final answer. No title is required here.
- **'Verification'**: At this stage, you verify the conclusion from the "Final Conclusion" step. If the conclusion holds, end the process. If not, return to "Inner Thinking" for further reasoning. No title is required here.

The output format must strictly follow the JSON structure below:
```json
{{
"CoT": [
"action": "Inner Thinking", "title": "...", "content": "...",
...,
"action": "Final Conclusion", "content": "...",
"action": "Verification", "content": "..."
]
}}
```"""

2. Cross-Agent Consolidation:
"""<question>
{}
</question>

<sentiment>
{}
</sentiment>

<semantic>
{}
</semantic>

<style>
{}
</style>

<previous reasoning>
{}
</previous reasoning>

<response requirements>
Your response must include the following steps, each composed of three types of actions: **"Inner Thinking"**, **"Final Conclusion"**, and **"Verification"**:

1. **Inner Thinking**: Break down the reasoning process into multiple concise steps. Each step should start with a brief title to clarify its purpose.
2. **Final Conclusion**: Summarize the correct reasoning from all previous 'Inner Thinking' steps and provide the final answer. No title is needed for this section.
3. **Verification**: Verify the accuracy of the "Final Conclusion". If it holds, conclude the process. Otherwise, return to "Inner Thinking" for further refinement.

</response requirements>

<question> represents the question to be answered, <sentiment>, <semantic>, and <style> are derived from the latest analyses of three experts, each from a different perspective, and <previous reasoning> contains your prior reasoning. Your task is to continue from the current 'Verification' step. Upon review, your previous reasoning and Final Conclusion appear incomplete or insufficiently justified or false. Proceed to refine the reasoning based on the three experts' latest analysis in <sentiment>, <semantic>, and <style> and construct a new Final Conclusion. And you may also incorporate your own independent reasoning.

Output Format
Strictly follow the JSON structure below. You do not need to repeat your previous reasoning. Begin directly from the next 'Verification' stage.
```json
{{
"CoT": [
"action": "Inner Thinking", "title": "...", "content": "...",
...,
"action": "Final Conclusion", "content": "...",
"action": "Verification", "content": "..."
]
}}
"""

**3. Cross-Agent Reconsideration:**

"""<question>
{}
</question>

<sentiment>
{}
</sentiment>

<semantic>
{}
</semantic>

<style>
{}
</style>

<previous reasoning>
{}
</previous reasoning>

<response requirements>
Your response must include the following steps, each composed of three types of actions: **"Inner Thinking"**, **"Final Conclusion"**, and **"Verification"**:

1. **Inner Thinking**: Break down the reasoning process into multiple concise steps. Each step should start with a brief title to clarify its purpose.
2. **Final Conclusion**: Summarize the correct reasoning from all previous 'Inner Thinking' steps and provide the final answer. No title is needed for this section.
3. **Verification**: Verify the accuracy of the "Final Conclusion". If it holds, conclude the process. Otherwise, return to "Inner Thinking" for further refinement.

</response requirements>

<question> represents the question to be answered, <sentiment>, <semantic>, and <style> are derived from the latest analyses of three experts, each from a different perspective, and <previous reasoning> contains your prior reasoning. Your task is to continue from the current 'Verification' step. Upon review, your previous reasoning and Final Conclusion appear incomplete or insufficiently justified or false. Proceed to refine the reasoning using **backtracking** to revisit earlier points of reasoning and construct a new Final Conclusion.

### Output Format
Strictly follow the JSON structure below. You do not need to repeat your previous reasoning. Begin directly from the next 'Verification' stage.

```json
{{
"CoT": [
"action": "Verification", "content": "...",
"action": "Inner Thinking", "title": "...", "content": "...",
...,
"action": "Final Conclusion", "content": "...",
"action": "Verification", "content": "..."
]
}}
```"""

4. Cross-Agent Diversification:

"""<question>
{}
</question>

<sentiment>
{}
</sentiment>

<semantic>
{}
</semantic>

<style>
{}
</style>

<previous reasoning>
{}
</previous reasoning>

<response requirements>
Your response must include the following steps, each composed of three types of actions: **"Inner Thinking"**, **"Final Conclusion"**, and **"Verification"**:

1. **Inner Thinking**: Break down the reasoning process into multiple concise steps. Each step should start with a brief title to clarify its purpose.
2. **Final Conclusion**: Summarize the correct reasoning from all previous 'Inner Thinking' steps and provide the final answer. No title is needed for this section.
3. **Verification**: Verify the accuracy of the "Final Conclusion". If it holds, conclude the process. Otherwise, return to "Inner Thinking" for further refinement.

</response requirements>

<question> represents the question to be answered, <sentiment>, <semantic>, and <style> are derived from the latest analyses of three experts, each from a different perspective, and <previous reasoning> contains your prior reasoning. Your task is to continue from the current 'Verification' step. Upon review, your previous reasoning and Final Conclusion appear incomplete or insufficiently justified or false. Proceed to refine the reasoning by exploring new approaches to solving this problem and construct a new Final Conclusion.

Output Format
Strictly follow the JSON structure below. You do not need to repeat your previous reasoning. Begin directly from the next 'Verification' stage.

```json
{{
"CoT": [
"action": "Verification", "content": "...",
"action": "Inner Thinking", "title": "...", "content": "...",
...,
"action": "Final Conclusion", "content": "...",
"action": "Verification", "content": "..."
]
}}
```"""

5. Cross-Agent Verification

"""<question>
{}
</question>

<sentiment>
{}
</sentiment>

<semantic>
{}
</semantic>

<style>
{}
</style>

<previous reasoning>
{}
</previous reasoning>

<response requirements>
Your response must include the following steps, each composed of three types of actions: **"Inner Thinking"**, **"Final Conclusion"**, and **"Verification"**:

1. **Inner Thinking**: Break down the reasoning process into multiple concise steps. Each step should start with a brief title to clarify its purpose.
2. **Final Conclusion**: Summarize the correct reasoning from all previous 'Inner Thinking' steps and provide the final answer. No title is needed for this section.
3. **Verification**: Verify the accuracy of the "Final Conclusion". If it holds, conclude the process. Otherwise, return to "Inner Thinking" for further refinement.

</response requirements>

<question> represents the question to be answered, <sentiment>, <semantic>, and <style> are derived from the latest analyses of three experts, each from a different perspective, and <previous reasoning> contains your prior reasoning. Your task is to continue from the current 'Verification' step. Upon review, your previous reasoning and Final Conclusion appear incomplete or insufficiently justified or false. Proceed to refine the reasoning by conducting a thorough **validation** process to ensure validity and construct a new Final Conclusion.

Output Format
Strictly follow the JSON structure below. You do not need to repeat your previous reasoning. Begin directly from the next 'Verification' stage.

```json
{{
"CoT": [
"action": "Verification", "content": "...",
"action": "Inner Thinking", "title": "...", "content": "...",
...,
"action": "Final Conclusion", "content": "...",
"action": "Verification", "content": "..."
]
}}
```"""

6. Cross-Agent Rectification:

"""\<question\>
{}
\</question\>

\<sentiment\>
{}
\</sentiment\>

\<semantic\>
{}
\</semantic\>

\<style\>
{}
\</style\>

\<previous reasoning\>
{}
\</previous reasoning\>

\<response requirements\>
Your response must include the following steps, each composed of three types of actions: **"Inner Thinking"**, **"Final Conclusion"**, and **"Verification"**:

1. **Inner Thinking**: Break down the reasoning process into multiple concise steps. Each step should start with a brief title to clarify its purpose.
2. **Final Conclusion**: Summarize the correct reasoning from all previous 'Inner Thinking' steps and provide the final answer. No title is needed for this section.
3. **Verification**: Verify the accuracy of the "Final Conclusion". If it holds, conclude the process. Otherwise, return to "Inner Thinking" for further refinement.

\</response requirements\>

\<question\> represents the question to be answered, \<sentiment\>, \<semantic\>, and \<style\> are derived from the latest analyses of three experts, each from a different perspective, and \<previous reasoning\> contains your prior reasoning. Your task is to continue from the current 'Verification' step. Upon review, your previous reasoning and Final Conclusion appear incomplete or insufficiently justified or false. Proceed to refine the reasoning by making precise **corrections** to address prior flaws and construct a new Final Conclusion.

Output Format
Strictly follow the JSON structure below. You do not need to repeat your previous reasoning. Begin directly from the next 'Verification' stage.

```json
{{
"CoT": [
"action": "Verification", "content": "...",
"action": "Inner Thinking", "title": "...", "content": "...",
...,
"action": "Final Conclusion", "content": "...",
"action": "Verification", "content": "..."
]
}}
```"""

7. Hint prompt for Summary Agent:

"""<question>
{}
</question>

<sentiment>
{}
</sentiment>

<semantic>
{}
</semantic>

<style>
{}
</style>

<previous reasoning>
{}
</previous reasoning>

<response requirements>
Your response must include the following steps, each composed of three types of actions: **"Inner Thinking"**, **"Final Conclusion"**, and **"Verification"**:

1. **Inner Thinking**: Break down the reasoning process into multiple concise steps. Each step should start with a brief title to clarify its purpose.
2. **Final Conclusion**: Summarize the correct reasoning from all previous 'Inner Thinking' steps and provide the final answer. No title is needed for this section.
3. **Verification**: Verify the accuracy of the "Final Conclusion". If it holds, conclude the process. Otherwise, return to "Inner Thinking" for further refinement.

</response requirements>

<question> represents the question to be answered, <sentiment>, <semantic>, and <style> are derived from the latest analyses of three experts, each from a different perspective, and <previous reasoning> contains your prior reasoning. Your task is to continue from the current 'Verification' step. Now, I'll secretly tell you that the labeled answer is "{}", but you must pretend not to know. Your 'Verification' requires careful consideration, and if incorrect, you need to provide new Inner Thinking steps and a new Final Conclusion to ensure the final answer aligns with the correct one.

Output Format
Strictly follow the JSON structure below. You do not need to repeat your previous reasoning. Begin directly from the next 'Verification' stage.

```json
{{
"CoT": [
"action": "Verification", "content": "...",
"action": "Inner Thinking", "title": "...", "content": "...",
...,
"action": "Final Conclusion", "content": "...",
"action": "Verification", "content": "..."
]
}}
```"""

Other function:

1. Verify prompt:

"""<Model Response>
{}
</Model Response>

<Reference Answer>
{}
</Reference Answer>

You are provided with a model-generated response (<Model Response>) and a reference answer (<Reference Answer>). Compare the model response with the reference answer and determine its correctness. Your task is to simply output "True" if the response is correct, and "False" otherwise."""

2. Reformat complex reasoning:

"""<Thought Process>
{}
</Thought Process>

<Question>
{}
</Question>

The <Thought Process> above reflects the model's reasoning based on the <Question>. Your task is to rewrite the <Thought Process> to resemble a more human-like, intuitive natural thinking process. The new version should:

1. Be presented as step-by-step reasoning, with each thought on a new line separated by a line break.
2. Avoid structured titles or formatting, or phrasing it as something an agent said, focusing on natural transitions. Use casual and natural language for transitions or validations, such as "hmm," "oh," "also," or "wait."
3. Expand the content, making the reasoning richer, more detailed, and logically clear while still being conversational and intuitive.

Return directly the revised natural thinking in JSON format as follows:
```json
{{
"NaturalReasoning": "..."
}}
```"""

3. Prompt for obtaining the final answer:

"""<Internal Thinking>
{}
</Internal Thinking>

<Question>
{}
</Question>

The <Internal Thinking> represents your internal thoughts about the <Question>. Based on this, generate a rich and high-quality final response to the user. If there is a clear answer, provide it first. Ensure your final response closely follows the <Question>. The response style should resemble GPT-4's style as much as possible. Output only your final response, without any additional content."""