Robustness as an Emergent Property of Task Performance

Abstract

Robustness is widely viewed as a key challenge for real-world applications. However, because current research focuses only on difficult tasks, it partially captures real-world readiness. In this paper, we argue and verify that robustness – consistency across semantically equivalent inputs – closely follows task difficulty: once models master a task, robustness emerges naturally. Through an empirical analysis of multiple models across diverse datasets and configurations (e.g., paraphrases, temperature changes), we observe a strong positive correlation between task performance and robustness. Furthermore, our findings indicate that robustness is driven primarily by task-specific competence rather than inherent model attributes, challenging the common view of robustness as an independent capability. This perspective implies that as tasks mature and model performance saturates, robustness on those tasks will similarly emerge. For researchers, this suggests that explicit efforts to measure robustness may deserve reduced emphasis, as robustness is likely to improve alongside performance. For practitioners, it signals that while many existing benchmarks are still unstable, models are already reliable on earlier tasks and suitable for deployment.

1 Introduction

One man's trash is another man's treasure

Robustness – the ability of models to produce consistent outputs across semantically equivalent inputs – becomes increasingly critical as AI scales into high-stakes applications (Kumar and Mishra, 2025; Guo et al., 2023). Even State-of-the-art models often exhibit unpredictable behavior under minor input changes, undermining confidence in their reliability and hence practicality, especially in scenarios where stability is critical (Yang et al., 2024; Wang and Zhao, 2024; Ashury-Tahan et al., 2025).

Figure 1: Linear regression of robustness on performance. Robustness increases slightly faster than performance, with a slope of 1.05. Performance explains 92.4% of robustness variance, indicating a strong predictive relationship. Colors denote models, and shapes represent datasets. Dashed gray line: random baseline, i.e., the probability of answering consistently across all example configurations, assuming per-configuration success probability equals the model's performance.

Most robustness works focus on challenging tasks and not on saturated tasks (Voronov et al., 2024; Pezeshkpour and Hruschka, 2023; Sclar et al., 2024; Alzahrani et al., 2024; Ashury-Tahan et al., 2025; Mizrahi et al., 2024; Kumar and Mishra, 2025). Thus, they are not able to capture a full picture of real-world readiness, where model behavior on saturated tasks is relevant for deployment decisions. Moreover, these works evaluate robustness as a distinct signal, separate from performance, assuming it to be an inherent property of the model. We challenge this view by proposing that robustness depends on task difficulty, rather than model skill alone; a lack of robustness in one setting does not indicate global brittleness. Missing evaluations on saturated tasks obscure this link and leave a key aspect of robustness hidden.

In this work, we examine robustness across different levels of task difficulty, considering it

not as a standalone property but in relation to model performance. We focus on a key dimension of real-world robustness: stability under *meaning-preserving input variations*. We argue and verify that **performance serves as a meaningful signal of model robustness**. When models demonstrate high success and questions are unquestionably easy for them, they are easy regardless of how they are presented. To explore this hypothesis, we analyze multiple models across diverse datasets and configurations, spanning a range of difficulties.

Our findings reveal a strong positive correlation between benchmark performance and model robustness, demonstrating that as model performance approaches the upper limits of a task, so does its resilience to inference variations. As evident from the random-baseline robustness in Figure 1, this phenomenon goes well beyond the "trivial robustness" expected from high success rates, and remains consistent across diverse model architectures.

Importantly, our results reveal that robustness is not predominantly an intrinsic property of the model, as often assumed in prior work. Instead, we find that *task-specific competence is the main driver of robust behavior*: models exhibit high robustness primarily on tasks they have mastered, regardless of architecture or scale.

Our findings have implications for both practitioners and researches. For real-world deployment, the results suggest that extremely strong task performance is a reliable indicator of a model's consistency on that task, supporting its readiness for safe use. For researchers, the results indicate that robustness may warrant less focus, as robustness appears to be a concomitant effect that increases as a benchmark approaches saturation. Thus, as model saturation extends to new tasks over time, robustness on those tasks is likely to arise naturally.

2 Preliminaries

Let D denote a dataset, with examples $\{x_i \mid i \in \{1, \ldots, |D|\}\}$. Each example can be inferred using one of the configurations $v \in V$, denoted as x_i^v.

Let $m(x_i^v)$ represent the model prediction for x_i^v, and let $\text{score}(m(x_i^v))$ denote the benchmark evaluation score assigned to the prediction.

In what follows, we define the key terms used throughout our analysis.

Inference Configuration Configurations are chosen to reflect naive user inputs in real-world settings of diverse types, for which the model is expected to produce identical outputs. This includes surface form variations (paraphrasing), in-context modifications (modifying demonstrations and their quantity), generation parameter changes (varying temperature), and prompt noise (such as random string addition). Formally, given an example x_i, we define a set of configurations $\{x_i^v \mid v \in V\}$, which share the same semantic meaning but differ in how they are presented to the model. The detailed configuration can be found in App. §A.

In our main results, all configurations are equally valid references and considered original. Otherwise, we denote x_i^o the original reference configuration. We calculate metric scores against each original reference and then average the results.

Model Capability The performance score (e.g., accuracy, F1) obtained by a model on the original version. We define the overall capability of a model m on dataset D as the average score across all examples:

$$\text{Capability}(m, D) = \frac{1}{|D|} \sum_{i=1}^{|D|} \text{score}(m(x_i^o))$$

Model Robustness (Output Consistency) Following previous work, we define robustness at the example level (Nalbandyan et al., 2025; Ackerman et al., 2024; Zhu et al., 2024; Habba et al., 2025; Ashury-Tahan et al., 2025) as strict agreement of model predictions across configurations.

Given the set of configurations V, a model m is considered *robust* on example x_i if all configuration outputs are equivalent:

$$c_i = \mathbf{1}\Big[m(x_i^{v_1}) \equiv m(x_i^{v_2}) \ \forall v_1, v_2 \in V\Big]$$

Dataset-level robustness is the fraction of examples that are robust:

$$\text{OutputConsistency}(m, D) = \frac{1}{|D|} \sum_{i=1}^{|D|} c_i$$

3 Experimental Setup

Our experiments span 9 models and 6 diverse datasets, covering difficulty levels from sentiment analysis (IMDB) and reading comprehension (BoolQ) to advanced reasoning (MMLU, MMLU-Pro), reward-model evaluation (RewardBench), and graduate-level problem solving (GPQA). From each dataset, we sample 100 examples and generate predictions under 24 different

Figure 2: Robustness rate per dataset, computed using the output consistency metric, in relation to overall performance (represented by dashed lines). Robustness rises as benchmarks saturate. Camel bars represent the random baseline consistency probability with similar success rates, which is approximately 0 when performance is below ~80%. Additional robustness metrics analysis can be found in App. §C.

configurations, resulting in roughly $130k$ total inferences. We then evaluate, for each model–dataset pair, performance[1] and robustness across these configurations. More details are provided in App. §A.

Robustness Primary Metric To keep robustness and performance measurements as independent as possible, we use *OutputConsistency* as our main robustness metric. Unlike performance, robustness is computed solely from model outputs and aggregated across example configurations.

Additional Robustness Metrics To further support our findings, we evaluate two additional score-based metrics: (i) the standard deviation of scores across example configurations, and (ii) the performance drop rate across configurations. Formal definitions are provided in App. §B.

Random Baseline We also compare our results to a random baseline, computed as the probability of consistent answers across all configurations, assuming that the success probability of each configuration equals the model's overall performance.

Contamination While contamination is a potential concern in evaluation studies, we mitigate it by using *diverse* datasets and configurations, reducing the likelihood of exact overlap with pretraining corpora. Moreover, our analysis emphasizes consistency in all 24 varied configurations, making it unlikely that contamination alone explains the observed robustness patterns. As shown in App. §C.2, models do not favor any specific configuration; instead, consistency values follow a long-tail distribution across datasets and models.

[1] We validate against existing benchmarks (see App §A.2).

4 Results

This section reports our main finding: performance strongly correlates with output consistency, measured via *OutputConsistency* (§2). Additional results and statistical analyses appear in App. C.

Higher performance is associated with a greater proportion of consistent answers This suggests that the ability to solve a dataset also reflects an ability to generalize across configurations. For example, all models on IMDB achieve performance between 95% and 97%, and their robustness is comparatively high, ranging from 81% to 94%. This is not trivial, as illustrated in Figure 2, and becomes evident when comparing consistency to a random baseline with a similar overall success rate, which in the case of IMDB case achieves only between 33% and 54%.

Models outperform random baselines across benchmark regimes Models substantially exceed the random baseline on all benchmarks, underscoring robustness that is not explained by chance. For the four datasets on the right of Figure 2, the random baseline achieves zero robustness (as performance is lower than 80%). Even in cases of very high success probability (IMDB, BoolQ), the gap remains significant, 43.4% and 62.9% on average, respectively. An extreme case is `llama-4-Scout-17B-Instruct` on BoolQ, which outperforms the random baseline by 70.4%.

Model-specific factors are comparatively weaker Our analysis shows that although architecture and design matter, their effect on consistency is modest relative to the strong perfor-

mance–robustness trend in Figure 1. Nevertheless, models can differ in inherent robustness; for example, `gpt-oss-120b` is far more robust than `gpt-oss-20b` on datasets where their performance is similar (e.g., on BoolQ, a 1-point performance difference results in 120B achieving 78% robustness compared to 56% for 20B; similarly, on MMLU, a 6-point performance gap corresponds to a 40% robustness difference).

Perturbations as arbitrary noise Significance testing using ANOVA shows that our findings are not driven by particular experimental choices, with configuration parameters (e.g., replacing prompt space chars with TAB chars) exerting only a minor effect on performance (see Appendix §C.3). This suggests that perturbations of different types are largely equivalent, and may reflect different ways of injecting noise into the generation task.

Our results show few outliers, indicating little contamination, otherwise, the original would often be high when its paraphrases are not.

5 Related Work

Robustness LLM robustness has been widely studied, with work highlighting brittleness across tasks (Alzahrani et al., 2024), domains (Ashury-Tahan et al., 2025), input perturbation types (Mizrahi et al., 2024), or robustness as a phenomenon and how to address it (Kumar and Mishra, 2025). However, these works have treated robustness as an isolated phenomenon. Lunardi et al. show that while model rankings remain stable under paraphrasing, absolute effectiveness often drops. Ding et al. (2018) further link adversarial robustness to input distribution.

Saturation Progress Evaluation benchmarks for LLMs has become increasingly saturated (Bengio et al., 2025; Reuel et al., 2024; HAI, 2023; Ott et al., 2022; Bengio et al., 2025). Studies show rapid early gains followed by plateaus as models near perfect scores, often accelerated by data overlap (Sainz et al., 2023), underscoring the pace and capabilities of current systems. Recent work addresses saturation by introducing harder benchmarks, weighted metrics, or progressively challenging evaluations (Ivanov and Volkov, 2025; Mirzadeh et al., 2024; Etzine et al., 2025; Bradley, 2024). While these works highlight challenges such as evaluation limits or propose solutions, other perspectives on what saturation implies for models remain underexplored.

Generalization and Learning Order Prior work in both NLP and vision shows that LLMs tend to acquire and generalize tasks in a consistent order across architectures and training regimes; that is, some tasks are systematically easier to learn than others (Hacohen et al., 2020; Pliushch et al., 2022; Baldock et al., 2021; Choshen et al., 2022; Edamadaka et al., 2025). Recent studies also reveal striking similarities in learned parameters (Kaushik et al., 2025). Whereas previous studies primarily examine generalization to unseen examples after the task has been learned, we demonstrate that the same structured behavior applies to meaning-preserving variations of those inputs, capturing an additional dimension of task competence.

6 Discussion

While model robustness is often studied in isolation, here we take a broader perspective. We find that robustness to semantically equivalent inputs is mainly tied to overall task performance, where high performance corresponds to robust and consistent model behavior. Interestingly, intrinsic signals from the model itself are relatively weak.

At a higher level, our work relates to the dynamics of saturation, where tasks become progressively easier for models over time. Together with the observed link between performance and robustness, it suggests that, without explicitly addressing it, *as models advance, robustness may increasingly cease to be a primary bottleneck.*

These patterns matter for applications where robustness is as critical as accuracy (e.g., healthcare, safety). They suggest that high model performance may function as an empirical indicator of the model's readiness for reliable deployment. While this means that top current benchmarks likely do not measure tasks that can be used in sensitive domains, it also means that older tasks that were abandoned by the research community and never shown to be robust, are likely a possibility.

Our findings indicate that perceived model robustness often reflects task-specific competence rather than inherent model properties, calling for a reduced focus on measuring and improving robustness in isolation.

Given the strong signals observed, a natural future direction is to explore other robustness types (e.g., adversarial robustness) to see whether similar patterns arise.

7 Limitations

Scope of Tasks   Our experiments are focused on the classification task to ensure comparability of results; however, this comes at the cost of reduced generalizability, as the findings may only partially apply to other tasks.

Model Behavior   Our analysis and conclusions are based on a diverse set of models. While the observed behaviors are consistent across this set, they may not generalize under substantial shifts in model architectures or training paradigms.

Evaluated Models   Due to cost constraints, we did not include closed-source models in our evaluation. Consequently, caution should be exercised when generalizing these results to all model types.

Robustness Types   Our evaluation focuses only on lightweight, semantic-preserving prompt perturbations. Thus, our conclusions may not extend to other robustness settings, such as strong adversarial attacks, non–semantic-preserving shifts, or tool-use scenarios.

References

Samuel Ackerman, Ella Rabinovich, Eitan Farchi, and Ateret Anaby Tavor. 2024. A novel metric for measuring the robustness of large language models in non-adversarial scenarios. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 2794–2802, Miami, Florida, USA. Association for Computational Linguistics.

Norah Alzahrani, Hisham Abdullah Alyahya, Yazeed Alnumay, Sultan Alrashed, Shaykhah Alsubaie, Yusef Almushaykeh, Faisal Mirza, Nouf Alotaibi, Nora Altwairesh, Areeb Alowisheq, M Saiful Bari, and Haidar Khan. 2024. When benchmarks are targets: Revealing the sensitivity of large language model leaderboards. *Preprint*, arXiv:2402.01781.

Shir Ashury-Tahan, Yifan Mai, Rajmohan C, Ariel Gera, Yotam Perlitz, Asaf Yehudai, Elron Bandel, Leshem Choshen, Eyal Shnarch, Percy Liang, and Michal Shmueli-Scheuer. 2025. The mighty torr: A benchmark for table reasoning and robustness. *Preprint*, arXiv:2502.19412.

Robert J. N. Baldock, Hartmut Maennel, and Behnam Neyshabur. 2021. Deep learning through the lens of example difficulty. *Preprint*, arXiv:2106.09647.

Yoshua Bengio, Sören Mindermann, Daniel Privitera, Tamay Besiroglu, Rishi Bommasani, Stephen Casper, Yejin Choi, Philip Fox, Ben Garfinkel, Danielle Goldfarb, Hoda Heidari, Anson Ho, Sayash Kapoor, Leila Khalatbari, Shayne Longpre, Sam Manning, Vasilios Mavroudis, Mantas Mazeika, Julian Michael, and 77 others. 2025. International ai safety report. *Preprint*, arXiv:2501.17805.

William F. Bradley. 2024. Enhancing llm evaluations: The garbling trick. *ArXiv*, abs/2411.01533.

Leshem Choshen, Guy Hacohen, Daphna Weinshall, and Omri Abend. 2022. The grammar-learning trajectories of neural language models. *Preprint*, arXiv:2109.06096.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. 2019. Boolq: Exploring the surprising difficulty of natural yes/no questions. *Preprint*, arXiv:1905.10044.

Gavin Weiguang Ding, Kry Yik-Chau Lui, Xiaomeng Jin, Luyu Wang, and Ruitong Huang. 2018. On the sensitivity of adversarial robustness to input data distributions. In *International Conference on Learning Representations*.

Sathya Edamadaka, Soojung Yang, Ju Li, and Rafael Gómez-Bombarelli. 2025. Universally converging representations of matter across scientific foundation models. *Preprint*, arXiv:2512.03750.

Bryan Etzine, Masoud Hashemi, Nishanth Madhusudhan, Sagar Davasam, Roshnee Sharma, Sathwik Tejaswi Madhusudhan, and Vikas Yadav. 2025. Revitalizing saturated benchmarks: A weighted metric approach for differentiating large language model performance. In *Proceedings of the 5th Workshop on Trustworthy NLP (TrustNLP 2025)*, pages 511–523, Albuquerque, New Mexico. Association for Computational Linguistics.

Zishan Guo, Renren Jin, Chuang Liu, Yufei Huang, Dan Shi, Supryadi, Linhao Yu, Yan Liu, Jiaxuan Li, Bojian Xiong, and Deyi Xiong. 2023. Evaluating large language models: A comprehensive survey. *Preprint*, arXiv:2310.19736.

Eliya Habba, Ofir Arviv, Itay Itzhak, Yotam Perlitz, Elron Bandel, Leshem Choshen, Michal Shmueli-Scheuer, and Gabriel Stanovsky. 2025. Dove: A large-scale multi-dimensional predictions dataset towards meaningful llm evaluation. *Preprint*, arXiv:2503.01622.

Guy Hacohen, Leshem Choshen, and Daphna Weinshall. 2020. Let's agree to agree: Neural networks share classification order on real datasets. *Preprint*, arXiv:1905.10854.

Stanford HAI. 2023. Ai benchmarks hit saturation. https://hai.stanford.edu/news/ai-benchmarks-hit-saturation. Accessed: July 22, 2025.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring massive multitask language understanding. *Preprint*, arXiv:2009.03300.

Igor Ivanov and Dmitrii Volkov. 2025. Resurrecting saturated llm benchmarks with adversarial encoding. *Preprint*, arXiv:2502.06738.

Prakhar Kaushik, Shravan Chaudhari, Ankit Vaidya, Rama Chellappa, and Alan Yuille. 2025. The universal weight subspace hypothesis. *Preprint*, arXiv:2512.05117.

Pankaj Kumar and Subhankar Mishra. 2025. Robustness in large language models: A survey of mitigation strategies and evaluation metrics. *Preprint*, arXiv:2505.18658.

Nathan Lambert, Valentina Pyatkin, Jacob Morrison, LJ Miranda, Bill Yuchen Lin, Khyathi Chandu, Nouha Dziri, Sachin Kumar, Tom Zick, Yejin Choi, Noah A. Smith, and Hannaneh Hajishirzi. 2024. Rewardbench: Evaluating reward models for language modeling. *Preprint*, arXiv:2403.13787.

Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, Benjamin Newman, Binhang Yuan, Bobby Yan, Ce Zhang, Christian Cosgrove, Christopher D. Manning, Christopher Ré, Diana Acosta-Navas, Drew A. Hudson, and 31 others. 2023. Holistic evaluation of language models. *Preprint*, arXiv:2211.09110.

Riccardo Lunardi, Vincenzo Della Mea, Stefano Mizzaro, and Kevin Roitero. 2025. On robustness and reliability of benchmark-based evaluation of llms. *Preprint*, arXiv:2509.04013.

Andrew L. Maas, Raymond E. Daly, Peter T. Pham, Dan Huang, Andrew Y. Ng, and Christopher Potts. 2011. Learning word vectors for sentiment analysis. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pages 142–150, Portland, Oregon, USA. Association for Computational Linguistics.

Iman Mirzadeh, Keivan Alizadeh-Vahid, Hooman Shahrokhi, Oncel Tuzel, Samy Bengio, and Mehrdad Farajtabar. 2024. Gsm-symbolic: Understanding the limitations of mathematical reasoning in large language models. *ArXiv*, abs/2410.05229.

Moran Mizrahi, Guy Kaplan, Dan Malkin, Rotem Dror, Dafna Shahaf, and Gabriel Stanovsky. 2024. State of what art? a call for multi-prompt llm evaluation. *Preprint*, arXiv:2401.00595.

Grigor Nalbandyan, Rima Shahbazyan, and Evelina Bakhturina. 2025. Score: Systematic consistency and robustness evaluation for large language models. In *North American Chapter of the Association for Computational Linguistics*.

Simon Ott, Adriano Barbosa-Silva, Kathrin Blagec, Janina Brauner, and Matthias Samwald. 2022. Mapping global dynamics of benchmark creation and saturation in artificial intelligence. *Nature Communications*, 13.

Pouya Pezeshkpour and Estevam Hruschka. 2023. Large language models sensitivity to the order of options in multiple-choice questions. *Preprint*, arXiv:2308.11483.

Iuliia Pliushch, Martin Mundt, Nicolas Lupp, and Visvanathan Ramesh. 2022. When deep classifiers agree: Analyzing correlations between learning order and image statistics. *Preprint*, arXiv:2105.08997.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. 2023. Gpqa: A graduate-level google-proof q&a benchmark. *Preprint*, arXiv:2311.12022.

Anka Reuel, Amelia F. Hardy, Chandler Smith, Max Lamparth, Malcolm Hardy, and Mykel J. Kochenderfer. 2024. Betterbench: Assessing ai benchmarks, uncovering issues, and establishing best practices. *ArXiv*, abs/2411.12990.

Oscar Sainz, Jon Ander Campos, Iker García-Ferrero, Julen Etxaniz, Oier López de Lacalle, and Eneko Agirre. 2023. Nlp evaluation in trouble: On the need to measure llm data contamination for each benchmark. In *Conference on Empirical Methods in Natural Language Processing*.

Melanie Sclar, Yejin Choi, Yulia Tsvetkov, and Alane Suhr. 2024. Quantifying language models' sensitivity to spurious features in prompt design or: How i learned to start worrying about prompt formatting. *Preprint*, arXiv:2310.11324.

Anton Voronov, Lena Wolf, and Max Ryabinin. 2024. Mind your format: Towards consistent evaluation of in-context learning improvements. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 6287–6310, Bangkok, Thailand. Association for Computational Linguistics.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, Tianle Li, Max Ku, Kai Wang, Alex Zhuang, Rongqi Fan, Xiang Yue, and Wenhu Chen. 2024. Mmlu-pro: A more robust and challenging multi-task language understanding benchmark. *Preprint*, arXiv:2406.01574.

Yuqing Wang and Yun Zhao. 2024. Rupbench: Benchmarking reasoning under perturbations for robustness evaluation in large language models. *ArXiv*, abs/2406.11020.

Zeyu Yang, Zhao Meng, Xiaochen Zheng, and Roger Wattenhofer. 2024. Assessing adversarial robustness of large language models: An empirical study. *ArXiv*, abs/2405.02764.

Kaijie Zhu, Jindong Wang, Jiaheng Zhou, Zichen Wang, Hao Chen, Yidong Wang, Linyi Yang, Wei Ye, Yue Zhang, Neil Zhenqiang Gong, and Xing Xie. 2024. Promptrobust: Towards evaluating the robustness of large language models on adversarial prompts. *Preprint*, arXiv:2306.04528.

A Experimental Setup

A.1 Experimental Design

Building on the definitions above, we conduct experiments on both saturated and less saturated benchmarks, incorporating different configurations.

The Data We conducted our experiments using the following benchmarks: IMDB (Maas et al., 2011), BoolQ (Clark et al., 2019), MMLU (Hendrycks et al., 2021), MMLU-Pro (Wang et al., 2024), GPQA (Rein et al., 2023), and RewardBench (Lambert et al., 2024). The datasets were chosen to share a similar classification task and use the same exact-match accuracy metric, ensuring comparability.

The Models For each dataset, we evaluated the capability and robustness of 9 open-weight models and 6 model families, all listed in Table A.2. These models were selected as open-weight representatives from different model families, allowing us to analyze how performance on a benchmark relates to robustness behavior. Each model was evaluated using all perturbation types described below.

Configurations Following previous work (Habba et al., 2025; Mizrahi et al., 2024; Alzahrani et al., 2024), we implement our experiments using the following variations with exact parameter values provided in Table A.1:

1. **Paraphrases**: An LLM judge paraphrased the original prompt, and the resulting text was used as an alternative template.

2. **Number of Demonstrations**: We varied the number of in-context examples provided.

3. **Random Noise**: Random patterns were added as prefixes, suffixes, or space replacements of varying lengths to introduce noise.

4. **Model Temperature**: Inference was performed under different temperature settings.

In total, we apply 24 configurations, each representing a unique combination of these variations to assess the robustness of model performance. The use of multiple configurations helps mitigate contamination concerns that could affect our results.

Evaluation Since our experiments focused on classification tasks, we evaluated results using exact match between the gold answer and the model output. We instructed the model to output the final answer only. Prior to output comparison, both strings were normalized (i.e., lowercasing, and stripping whitespace).

Required Computation We sampled 100 examples from each dataset and evaluated each model on all samples across 24 configurations. This yields 14,400 inferences per model and 129,600 total inferences across nine models.

A.2 Performance Verification with External Benchmarks

To sanity-check our results, we compared the performance scores we have got and presented in Table A.2 against published scores from external sources. A practical challenge is coverage: our model list includes several newer models, whereas some benchmarks (e.g., IMDB, BoolQ) are *older* and are not consistently reported for recent models. Accordingly, we focus our cross-check on widely reported tasks such as MMLU, MMLU-Pro and GPQA. The results presented below indicate a positive correlation between the scores and only minor differences, despite variations in evaluation runs between our setup and theirs.

Llama models. We compared our measurements with the scores reported on the official model cards and community evaluations (e.g., the Llama 4 Maverick model card on Hugging Face[2]). Overall, the numbers are closely aligned (Table A.3).

HELM Capabilities We used the HELM (Liang et al., 2023) capabilities leaderboard, which reports results for MMLU-Pro and GPQA on some of our reported models. The results are similar to ours (see Table A.4). One difference that may explain their slightly better scores is that they ran the evaluation with chain-of-thought (CoT) prompting, whereas we requested a final answer only.

---

[2]https://huggingface.co/meta-llama/
Llama-4-Maverick-17B-128E-Instruct

Configuration Parameter	Number of variations	Values
Paraphrases	2	(a paraphrase created with an LLM for each dataset)
Number of demonstrations	2	2, 4
Random noise	3	no noise; replace prompt spaces with another character (e.g., TAB); add a random string at the beginning and end (70 chars)
Model temperature	2	0.2, 0.6

Table A.1: Configuration parameters used in the experimental setup. We ran all experiments using the 24 unique configurations listed in the table.

Model	IMDB	BoolQ	MMLU	RewardBench	MMLU-Pro	GPQA
gpt-oss-120b	.97	.94	.82	.78	.80	.66
gpt-oss-20b	.97	.94	.76	.69	.68	.68
Mistral-Large-3-675B-Instruct	.97	.91	.84	.75	.66	.44
llama-4-maverick-17b-instruct	.96	.91	.80	.74	.62	.42
llama-3-3-70b-instruct	.95	.93	.75	.76	.57	.46
Llama-4-Scout-17B-Instruct	.97	.88	.75	.71	.56	.34
Qwen2.5-72B-Instruct	.97	.94	.74	.76	.57	.35
DeepSeek-V2.5	.97	.93	.72	.75	.52	.36
phi-4	.96	.88	.70	.67	.50	.38
Average	.97	.92	.76	.73	.61	.45

Table A.2: Benchmark performance summary.

Model	MMLU	MMLU-Pro
Llama 4 Maverick 17B	80 (85)	62 (62)
Llama 4 Scout	75 (79)	56 (58)
Llama 3.1 70B	75 (79)	57 (53)

Table A.3: Our measured scores (outside parentheses) versus published scores (in parentheses). Minor differences are expected due to evaluation details (e.g., prompt templates, decoding settings).

Model	MMLU-Pro	GPQA
Llama 4 Scout	75 (74)	56 (50)
Llama 4 Maverick 17B	80 (81)	62 (65)
Qwen2.5-72B-Instruct	57 (63)	35 (42)
gpt-oss-120b	80 (79)	66 (68)
gpt-oss-20b	68 (74)	68 (59)

Table A.4: Our measured scores (outside parentheses) versus published scores (in parentheses). Minor differences are expected due to evaluation details (e.g., running with CoT).

B Robustness Metrics

B.1 Robustness Main Metric

While it is common practice to measure robustness using scores, we find it somewhat less ideal to reflect both performance and robustness using the exact same numbers. Instead, we rely primarily on the model's outputs in the paper, which offer a more direct reflection of its ability to maintain consistent predictions under meaning-preserving variations.

It is important to note that this choice *does not affect the validity* of our results: all robustness metrics we examined yielded similar trends.

B.2 Other Robustness Metrics

We used the following robustness metrics to complement our main output-based measure and provide a broader perspective on model behavior under different configurations:

Standard Deviation (STD) We compute the standard deviation of the model's scores across the original and perturbed versions of each input. Formally, for a given input x_i and its variants $\{x_i^v \mid v \in V\}$, we calculate:

$$\sigma_{x_i} = \text{STD}\bigg(\{\text{score}(m(x_i^v)) \mid v \in V\} \bigg)$$

A value of 0 indicates perfectly consistent behavior across perturbations, while higher values reflect increased variability in the model's responses.

Performance Drop Rate (PDR) We follow ([Zhu et al., 2024](#)) and calculate the relative drop in performance when the model is evaluated on perturbed inputs compared to the original test set. We define:

$$\rho_{x_i} \, (\%) = \frac{1}{|V|} \sum_{v \in V} [1 - \frac{\text{score}(m(x_i^o))}{\text{score}(m(x_i^v))}]$$

$$PDR\,(m, D) = \frac{1}{|D|} \sum_{x_i \in D} \rho_{x_i}$$

Here, performance is measured using the primary evaluation metric. A higher percentage indicates a greater sensitivity to perturbations.

C Results

We provide the results of 2 additional robustness metrics described in App. §B, and show they correlate well with our main results in the paper. While the primary metric used in the paper in output consistency which is string-based, these metrics provide another aspects that are score based.

C.1 PDR Trends

Calculating the PDR at the example level and averaging across models reveals a pattern similar to our main result as can be seen in Figure B.1. Here, the bars illustrate how far performance can vary per instance, essentially indicating where score consistency is lacking, which complements what we examined in Figure 2, where the bars reflected output consistency. In this figure, they represent performance variability rather than stability. We observe the same dataset ordering as before, but reversed from left to right: GPQA remains the least robust and IMDB the most robust. The relationship with overall performance is also evident when comparing the bar trend to the dashed trend.

Figure B.1: Average PDR reveals a similar trend: lower values indicate smaller performance drops across perturbations, signaling higher robustness and more consistent model behavior. The dashed lines indicates the performance.

C.2 Model-Dataset Full STD Distributions

To provide a more granular perspective on our results, we extended the STD metric by calculating the full distribution of per-example STD across models. These distributions reveal detailed patterns of model consistency.

While an STD of 0 indicates a consistent score, it is important to distinguish between success consistency and failure consistency. In our setup, success consistency means producing the same correct answer across all configurations, whereas consistent failure can occur due to different incorrect answers, which does not necessarily indicate robust behavior. Therefore, in the figures, we not only reflect the STD score but also differentiate whether an STD of 0 corresponds to all failures or all successes.

Considering only successful cases, the results closely mirror what we presented in Figure 2. While that figure reflected output consistency, here we focus on score consistency. It is also evident that as robustness decreases, the STD distribution becomes flatter, whereas higher performance leads to an long-tail distribution.

It offers additional evidence that inherent model robustness is limited, as the STD distribution is similar across models within the same benchmark, i.e., their graph trends follow a comparable pattern.

Figure C.1: Per-example STD distribution for each model on the IMDb dataset.

Figure C.2: Per-example STD distribution for each model on the BoolQ dataset.

Figure C.3: Per-example STD distribution for each model on the MMLU dataset.

Figure C.4: Per-example STD distribution for each model on the MMLU-Pro dataset.

Figure C.5: Per-example STD distribution for each model on the RewardBench dataset.

Figure C.6: Per-example STD distribution for each model on the GPQA dataset.

C.3 Statistical Testing

We analyzed the influence of four experimental factors (number of demos, prompt variation, template, and temperature) on performance across the datasets using both Type II and Type III ANOVA. Type II ANOVA evaluates each factor after accounting for all other factors, assuming no interaction terms, while Type III ANOVA additionally considers the presence of interactions and tests each factor after adjusting for all other factors and interactions. These tests assess whether different choices for each parameter significantly affect the results.

Overall, the findings indicate that parameter choices have only a minor impact on performance. As shown in Table C.1 and Table C.2, the majority of p-values (approximately 70%) are not significant. While prompt variation and number of demos exhibit statistically significant differences in some datasets (e.g., RewardBench, MMLU and MMLU-Pro), their effect sizes remain very small (<0.005), suggesting limited practical impact.

dataset	factor	F	p-value	eta_sq	partial_eta_sq	sum_sq
BoolQ	C(num_demos)	0.245	0.620	1.135e-05	1.137e-05	0.018
BoolQ	C(prompt_variation)	12.338	4.412e-06	0.001	0.001	1.848
BoolQ	C(template_used)	2.289	0.130	1.059e-04	1.060e-04	0.171
BoolQ	C(temprature)	0.022	0.881	1.030e-06	1.032e-06	0.002
GPQA	C(num_demos)	0.061	0.805	2.924e-06	2.924e-06	0.015
GPQA	C(prompt_variation)	1.279	0.278	1.224e-04	1.224e-04	0.633
GPQA	C(template_used)	0.003	0.954	1.579e-07	1.579e-07	8.164e-04
GPQA	C(temprature)	0.583	0.445	2.785e-05	2.786e-05	0.144
IMDB	C(num_demos)	0.123	0.726	6.015e-06	6.016e-06	0.004
IMDB	C(prompt_variation)	0.892	0.410	8.747e-05	8.748e-05	0.058
IMDB	C(template_used)	0.128	0.721	6.275e-06	6.276e-06	0.004
IMDB	C(temprature)	0.947	0.331	4.641e-05	4.642e-05	0.031
MMLU	C(num_demos)	4.836	0.028	2.236e-04	2.239e-04	0.869
MMLU	C(prompt_variation)	15.438	1.996e-07	0.001	0.001	5.547
MMLU	C(template_used)	3.175	0.075	1.468e-04	1.470e-04	0.570
MMLU	C(temprature)	0.724	0.395	3.346e-05	3.352e-05	0.130
MMLU-Pro	C(num_demos)	5.030	0.025	2.328e-04	2.329e-04	1.197
MMLU-Pro	C(prompt_variation)	6.235	0.002	5.771e-04	5.773e-04	2.968
MMLU-Pro	C(template_used)	1.124	0.289	5.202e-05	5.206e-05	0.268
MMLU-Pro	C(temprature)	0.063	0.802	2.914e-06	2.916e-06	0.015
RewardBench	C(num_demos)	10.468	0.001	4.799e-04	4.824e-04	2.037
RewardBench	C(prompt_variation)	35.940	3.686e-23	0.005	0.005	20.980
RewardBench	C(template_used)	2.003	0.157	9.184e-05	9.235e-05	0.390
RewardBench	C(temprature)	1.439	0.230	6.595e-05	6.632e-05	0.280

Table C.1: Summary across datasets — Type II ANOVA.

dataset	factor	F	p-value	eta_sq	partial_eta_sq	sum_sq
BoolQ	C(num_demos, Sum)	0.245	0.620	9.265e-07	1.137e-05	0.018
BoolQ	C(prompt_variation, Sum)	12.338	4.412e-06	9.319e-05	0.001	1.848
BoolQ	C(template_used, Sum)	2.289	0.130	8.645e-06	1.060e-04	0.171
BoolQ	C(temprature, Sum)	0.022	0.881	8.410e-08	1.032e-06	0.002
BoolQ	Intercept	243192.586	0.000	0.918	0.918	18209.710
GPQA	C(num_demos, Sum)	0.061	0.805	1.615e-06	2.924e-06	0.015
GPQA	C(prompt_variation, Sum)	1.279	0.278	6.761e-05	1.224e-04	0.633
GPQA	C(template_used, Sum)	0.003	0.954	8.723e-08	1.579e-07	8.164e-04
GPQA	C(temprature, Sum)	0.583	0.445	1.539e-05	2.786e-05	0.144
GPQA	Intercept	16936.111	0.000	0.447	0.447	4187.914
IMDB	C(num_demos, Sum)	0.123	0.726	2.021e-07	6.016e-06	0.004
IMDB	C(prompt_variation, Sum)	0.892	0.410	2.939e-06	8.748e-05	0.058
IMDB	C(template_used, Sum)	0.128	0.721	2.108e-07	6.276e-06	0.004
IMDB	C(temprature, Sum)	0.947	0.331	1.559e-06	4.642e-05	0.031
IMDB	Intercept	586755.026	0.000	0.966	0.966	18989.883
MMLU	C(num_demos, Sum)	4.836	0.028	5.261e-05	2.239e-04	0.869
MMLU	C(prompt_variation, Sum)	15.438	1.996e-07	3.359e-04	0.001	5.547
MMLU	C(template_used, Sum)	3.175	0.075	3.454e-05	1.470e-04	0.570
MMLU	C(temprature, Sum)	0.724	0.395	7.873e-06	3.352e-05	0.130
MMLU	Intercept	70297.530	0.000	0.765	0.765	12630.152
MMLU-Pro	C(num_demos, Sum)	5.030	0.025	9.103e-05	2.329e-04	1.197
MMLU-Pro	C(prompt_variation, Sum)	6.235	0.002	2.257e-04	5.773e-04	2.968
MMLU-Pro	C(template_used, Sum)	1.124	0.289	2.034e-05	5.206e-05	0.268
MMLU-Pro	C(temprature, Sum)	0.063	0.802	1.140e-06	2.916e-06	0.015
MMLU-Pro	Intercept	33643.358	0.000	0.609	0.609	8007.085
RewardBench	C(num_demos, Sum)	10.468	0.001	4.018e-04	4.824e-04	2.037
RewardBench	C(prompt_variation, Sum)	35.940	3.686e-23	0.004	0.005	20.980
RewardBench	C(template_used, Sum)	2.003	0.157	7.689e-05	9.235e-05	0.390
RewardBench	C(temprature, Sum)	1.439	0.230	5.522e-05	6.632e-05	0.280
RewardBench	Intercept	4240.655	0.000	0.163	0.164	825.159

Table C.2: Summary across datasets — Type III ANOVA.

D Saturation Progress

Saturation in LLM evaluation is a well-known challenge, with numerous papers highlighting, analyzing, or accounting for it in their studies. Here, we provide evidence from existing research showing that saturation is becoming increasingly prevalent. This strengthens our findings: as models improve in capabilities and benchmarks lose relevance, their ability to generalize also becomes more critical.

A figure published as part of the International AI Safety Report ([Bengio et al., 2025](#)) demonstrating the rapid advance of AI model performance from 1998 to 2024. In recent benchmarks, models progressed quickly from poor performance to surpassing human experts.

Table 1: Descriptive statistics of reported results over time for specific benchmarks and AI tasks. A single task can be represented through several benchmarks.

	NLP	Computer vision	Total
Benchmarks with ≥ 1 reported result	1318	2447	3765
Benchmarks with ≥ 3 results at different time points (% of above)	661 (50%)	1274 (52%)	1935 (51%)
AI tasks with ≥ 1 reported result	346	601	947
AI tasks with ≥ 3 results at different time points (% of above)	197 (57%)	386 (64%)	583 (62%)

Figure D.1: A table taken from (Ott et al., 2022) that demonstrates how, over time, the number of benchmarks relevant for repeated reporting drops significantly. For example, only 50% of NLP benchmarks have results at three or more time points.

Figure D.2: A figure published as part of the International AI Safety Report (Bengio et al., 2025) demonstrating that AI models improved from near-random (33%) to expert-level (70%) accuracy on PhD-level science questions within 15 months,

E AI Assistance Usage

We used AI for paraphrasing and improving clarity of writing only.