BERTology Meets Biology: Interpreting Attention in Protein Language Models

Abstract

Transformer architectures have proven to learn useful representations for protein classification and generation tasks. However, these representations present challenges in interpretability. In this work, we demonstrate a set of methods for analyzing protein transformer models through the lens of attention. We show that attention: (1) captures the folding structure of proteins, connecting amino acids that are far apart in the underlying sequence, but spatially close in the three-dimensional structure, (2) targets binding sites, a key functional component of proteins, and (3) focuses on progressively more complex biophysical properties with increasing layer depth. We find this behavior to be consistent across three Transformer architectures (BERT, ALBERT, XLNet) and two distinct protein datasets. We also present a three-dimensional visualization of the interaction between attention and protein structure. Code for visualization and analysis is available at `[supplementary-material]`.

1 Introduction

The study of proteins, the fundamental macromolecules governing biology and life itself, has led to remarkable advances in understanding human health and the development of disease therapies. The decreasing cost of sequencing technology has enabled vast databases of naturally occurring proteins (El-Gebali et al., 2019a), which are rich in information for developing powerful machine learning models of protein sequences. For example, sequence models leveraging principles of co-evolution, whether modeling pairwise or higher-order interactions, have enabled prediction of structure or function (Rollins et al., 2019).

Proteins, as a sequence of amino acids, can be viewed precisely as a language and therefore modeled using neural architectures developed for natural language. In particular, the Transformer (Vaswani et al., 2017), which has revolutionized unsupervised learning for text, shows promise for similar impact on protein sequence modeling. However, the strong performance of the Transformer comes at the cost of interpretability, and this lack of transparency can hide underlying problems such as model bias and spurious correlations (Niven & Kao, 2019; Tan & Celis, 2019; Kurita et al., 2019). In response, much NLP research now focuses on interpreting the Transformer, e.g., the subspecialty of "BERTology" (Rogers et al., 2020), which specifically studies the BERT model (Devlin et al., 2019).

In this work, we adapt and extend this line of interpretability research to protein sequences. We analyze Transformer protein models through the lens of attention, and present a set of interpretability methods that capture the unique functional and structural characteristics of proteins. We also introduce two analysis methods that apply to Transformer models more broadly: a novel calibration analysis of attention as a measure of probability, and a joint, cross-layer probing analysis of attention weights and embeddings, showing that layers of the model in which knowledge is accrued in embeddings may be far removed from layers in which this information is leveraged in the attention mechanism. Finally, we present a visualization of attention contextualized within three-dimensional protein structure.

Our analysis reveals that attention captures high-level structural properties of proteins, connecting amino acids that are spatially close in three-dimensional structure, but apart in the underlying sequence (Figure 1a). We also find that attention targets binding sites, a key functional component of proteins (Figure 1b). Further, we show that attention captures substitution properties of amino acids, and constructs progressively higher-level representations of structure and function with increasing

(a) Attention in head 12-4, which targets amino acid pairs that are close in physical space (see inset subsequence 117D-157I) but lie apart in the sequence. Example is a *de novo* designed TIM-barrel (5BVL) with characteristic symmetry.

(b) Attention in head 7-1, which targets binding sites, a key functional component of proteins. Example is HIV-1 protease (7HVP). The primary location receiving attention is 27G, a binding site for protease inhibitor small-molecule drugs.

Figure 1: Examples of how specialized attention heads in a Transformer recover protein structure and function, based solely on language model pre-training. Orange lines depict attention between amino acids (line width proportional to attention weight; values below 0.1 hidden). Heads were selected based on alignment with ground-truth annotations of contact maps and binding sites. Visualizations based on the NGL Viewer (Rose et al., 2018; Rose & Hildebrand, 2015; Nguyen et al., 2017).

layer depth. In contrast to NLP, which aims to automate a capability that humans already have—understanding natural language—protein modeling also seeks to shed light on biological processes that are not fully understood. Thus we also discuss how interpretability can aid scientific discovery.

2 BACKGROUND: PROTEINS

In this section we provide background on the biological concepts discussed in later sections.

Amino acids. Just as language is composed of words from a shared lexicon, every protein sequence is formed from a vocabulary of 20 standard amino acids. While word synonyms are encoded in a thesaurus, proteins that are similar in structure or function are captured in a *substitution matrix*, which scores pairs of amino acids on how readily they may be substituted for one another while maintaining protein viability. One common substitution matrix is BLOSUM (Henikoff & Henikoff, 1992), which is derived from co-occurrence statistics of amino acids in aligned protein sequences.

Protein structure. Though a protein may be abstracted as a sequence of amino acids, it represents a physical entity with a well-defined three-dimensional structure (Figure 1). *Secondary structure* describes the local segments of proteins, and may be divided into three broad categories: *Helix*, *Strand*, and *Turn/Fold*, as well as an *Other* category for local structure that falls outside these categories. *Tertiary structure* encompasses the large-scale formations that determine the overall shape and function of the protein. One way to characterize tertiary structure is by a *contact map*, which describes the pairs of amino acids that are in contact (within 8 angstroms of one another) in the folded protein structure but lie apart (by at least 6 positions) in the underlying sequence (Rao et al., 2019).

Binding sites. Proteins may also be characterized by their functional properties. *Binding sites* are protein regions that bind with other molecules to carry out a specific function. For example, the HIV-1 protease is an enzyme responsible for a critical process in replication of HIV (Brik & Wong, 2003). It has a binding site, shown in Figure 1b, that is a target for drug development to ensure inhibition.

Post-translational modifications. After a protein is translated from RNA, it may undergo additional modifications, e.g. phosphorylation, which play a key role in protein structure and function.

3 METHODOLOGY

Model. We demonstrate our interpretability methods on five Transformer models that were pretrained through language modeling of amino acid sequences. We primarily focus on the BERT-Base model

from TAPE (Rao et al., 2019), which was pretrained on Pfam, a dataset of 31M protein sequences (El-Gebali et al., 2019b). We refer to this model as *TapeBert*. We also analyze 4 pre-trained Transformer models from ProtTrans (Elnaggar et al., 2020): *ProtBert* and *ProtBert-BFD*, which are 30-layer, 16-head BERT models; *ProtAlbert*, a 12-layer, 64-head ALBERT (Lan et al., 2019) model, and *ProtXLNet*, a 30-layer, 16-head XLNet (Yang et al., 2019) model. *ProtBert-BFD* was pretrained on BFD (Steinegger & Söding, 2018), a dataset of 2.1B protein sequences, while the other ProtTrans models were pretrained on UniRef100 (Suzek et al., 2014), which includes 216M protein sequences.

Here we present an overview of BERT, with additional details on all models in Appendix A.1. BERT inputs a sequence of amino acids $\boldsymbol{x} = (x_1, \ldots, x_n)$ and applies a series of encoders. Each encoder layer ℓ outputs a sequence of continuous embeddings $(\mathbf{h}_1^{(\ell)}, \ldots, \mathbf{h}_n^{(\ell)})$ using a multi-headed attention mechanism. Each attention head in a layer produces a set of attention weights α for an input, where $\alpha_{i,j} > 0$ is the attention from token i to token j, such that $\sum_j \alpha_{i,j} = 1$. Intuitively, attention weights define the influence of every token on the next layer's representation for the current token. We denote a particular head by *<layer>-<head_index>*, e.g. head *3-7* for the 3rd layer's 7th head.

Attention analysis. We analyze how attention aligns with various protein properties. For properties of token pairs, e.g. contact maps, we define an indicator function $f(i, j)$ that returns 1 if the property is present in token pair (i, j) (e.g., if amino acids i and j are in contact), and 0 otherwise. We then compute the proportion of high-attention token pairs $(\alpha_{i,j} > \theta)$ where the property is present, aggregated over a dataset $\boldsymbol{X}$:

$$p_\alpha(f) = \sum_{\mathbf{x} \in \mathbf{X}} \sum_{i=1}^{|\mathbf{x}|} \sum_{j=1}^{|\mathbf{x}|} f(i,j) \cdot \mathbb{1}_{\alpha_{i,j} > \theta} \Big/ \sum_{\mathbf{x} \in \mathbf{X}} \sum_{i=1}^{|\mathbf{x}|} \sum_{j=1}^{|\mathbf{x}|} \mathbb{1}_{\alpha_{i,j} > \theta} \qquad (1)$$

where θ is a threshold to select for high-confidence attention weights. For properties of individual tokens, e.g. binding sites, we substitute $f(j)$ for $f(i, j)$ in Eq. 1, where $f(j)$ returns 1 if the property is present in token j (e.g. if j is a binding site). In this case, $p_\alpha(f)$ equals the proportion of attention that is directed *to* property f. We present an alternative, continuous version of this metric in Appendix B.1.

Probing tasks. We also perform *probing tasks* on the model, which test the knowledge contained in model representations by using the them as inputs to a classifier that predicts a property of interest (Veldhoen et al., 2016; Conneau et al., 2018; Adi et al., 2016). The performance of the probing classifier serves as a measure of the knowledge of the property that is encoded in the representation. We run both *embedding probes*, which assess the knowledge encoded in the output embeddings of each layer, and *attention probes* (Coenen et al., 2019; Clark et al., 2019), which measure the knowledge contained in the attention weights for pairwise features. Details are provided in Appendix B.2.

Datasets. For our analyses of amino acids and contact maps, we use a curated dataset from TAPE based on ProteinNet (AlQuraishi, 2019; Fox et al., 2013; Berman et al., 2000; Moult et al., 2018), which contains amino acid sequences annotated with spatial coordinates (used for the contact map analysis). For the analysis of secondary structure and binding sites we use the Secondary Structure dataset (Rao et al., 2019; Berman et al., 2000; Moult et al., 2018; Klausen et al., 2019) from TAPE. We obtained token-level binding site and protein modification labels from the Protein Data Bank (Berman et al., 2000). For analyzing attention, we used a random subset of 5000 sequences from the training split of the respective datasets (note that none of the aforementioned annotations were used in model training). For the diagnostic classifier, we used the respective training splits for training and the validation splits for evaluation. See Appendix B.3 for additional details.

Experimental details We exclude attention to the `[SEP]` delimiter token, as it has been shown to be a "no-op" attention token (Clark et al., 2019), as well as attention to the `[CLS]` token, which is not explicitly used in language modeling. We set the attention threshold θ to 0.3 to select for high-confidence attention while retaining sufficient data for analysis. We truncate all protein sequences to a length of 512 to reduce memory requirements.[1]

We note that all of the above analyses are purely associative and do not attempt to establish a causal link between attention and model behavior (Vig et al., 2020; Grimsley et al., 2020), nor to *explain* model predictions (Jain & Wallace, 2019; Wiegreffe & Pinter, 2019).

---

[1] 94% of sequences had length less than 512. Experiments performed on single 16GB Tesla V-100 GPU.

Figure 2: Alignment between attention and contact maps across five pretrained Transformer models from TAPE (a) and ProtTrans (b–e). The heatmaps show the proportion of high-confidence attention ($\alpha_{i,j} > \theta$) from each head that connects pairs of amino acids that are in contact with one another. In TapeBert (a), for example, we can see that 45% of attention in head 12-4 (the 12th layer's 4th head) is aligned with contacts. The probability of a randomly chosen pair of amino acids being in contact is 1.3%. The bar plots show the maximum value from each layer. Note that the vertical striping in ProtAlbert (b) is likely due to cross-layer parameter sharing (see Appendix A.2).

4 WHAT DOES ATTENTION UNDERSTAND ABOUT PROTEINS?

4.1 PROTEIN STRUCTURE

Here we explore the relationship between attention and tertiary structure, as characterized by contact maps (see Section 2). Secondary structure results are included in Appendix C.1.

Attention aligns strongly with contact maps in the deepest layers. Figure 2 shows the alignment (Eq. 1) between attention and contact maps across five models[2]. For all models, alignment is strongest in a small number of heads in the deepest layers (see statistical significance tests in Appendix C.2). Figure 1a shows an example protein and the induced attention from one such head. Considering the model was trained on a masked language modeling task without any spatial information, the presence of these structurally-aware attention heads is intriguing. One possible reason for this emergent behavior is that contacts are more likely to biochemically interact with one another, creating statistical dependencies between the amino acids in contact. By focusing attention on the contacts of a masked position, the language model may acquire valuable context for token prediction.

While there seems to be a strong correlation between the attention head output and classically-defined contacts, there are also differences. The model may have learned a differing contextualized or nuanced formulation that describes amino acid interactions. These learned interactions could then be used for further discovery and investigation or repurposed for prediction tasks similar to how principles of coevolution enabled a powerful representation for structure prediction.

Attention is a well-calibrated predictor of contact maps in some cases. It has been implied that attention weights represent a model's confidence in detecting implicit features (Voita et al., 2019; Correia et al., 2019). To quantify and test this intuition, we propose *attention calibration*, a measure of the correspondence between attention weight and feature probability. We base this metric on Expected Calibration Error (Naeini et al., 2015)—or ECE—which estimates the expected difference between a classifier's confidence and the true class probability through Bayesian binning. We demonstrate this approach by measuring attention calibration with the contact map property $f(i, j)$, a pairwise feature indicating whether the amino acids at positions i and j are in contact.

---

[2]Heads with fewer than 100 high-confidence attention weights across the dataset are grayed out.

Figure 3: Probability two amino acids are in contact [95% confidence intervals], as a function of attention between the amino acids in Head 12-4, showing attention approximates a perfectly-calibrated estimator (green line).

Figure 4: Percentage of high-confidence attention focused on binding sites in TapeBert. Especially in the deeper layers, binding sites are targeted at a much higher frequency than would occur by chance (4.8%).

Following the ECE method, we first partition all samples (amino-acid pairs (i, j)) from the dataset into 10 equal-sized bins based on confidence (attention weight $\alpha_{i,j}$), as shown in the calibration plot in Figure 3 (x-axis). We then compute the empirical probability of the positive class within each bin, i.e., the proportion of amino acid pairs that are in contact (y-axis). The ECE is defined as the average absolute difference between empirical probability and confidence (attention) across bins. Traditionally a weighted average is used; however, due to the sparsity of attention, the first bucket ($\alpha < 0.1$) would dominate this calculation. The first bin in Figure 3, for example, contains 99.96% of all examples. Since both attention and empirical probability is low in this bin, a weighted average would produce an artificially low calibration error. Therefore we instead use an unweighted average.

This approach yields a calibration error of 0.09 for the most aligned head from TapeBert (Figure 3) suggesting a moderate level of calibration. The results were mixed for the ProtTrans models on their respective most-aligned heads: ProtBert (0.13), ProtBert-BFD (0.15), ProtAlbert (0.13), ProtXLNet (0.12). (See Appendix C.2.) However, calibration methods such as isotonic regression (Zadrozny & Elkan, 2002) may be applied as a post-processing step to improve the calibration of attention weights and thereby provide a more precise understanding of attention as a measure of confidence.

4.2 BINDING SITES AND POST-TRANSLATIONAL MODIFICATIONS

We also analyze how attention interacts with binding sites and post-translational modifications (PTMs), which both play a key role in protein function.

Attention targets binding sites, especially in the deeper layers. As Figure 4 shows, binding sites are attended to most strongly in the final six layers of TapeBert, which include 5 heads that focus at least 40% of attention on binding sites.[3] The ProtBert, ProtBert-BFD, and ProtAlbert models showed similar behavior, each having heads that directed up to 51%, 46%, and 57% to binding sites, respectively (see App. C.3). We also find that binding sites are attended to from far away in the sequence. In Head 7-1 (Fig. 1b) for example, attention to binding sites spans 124 tokens on average.

Why does attention target binding sites? In contrast to contact maps, which reveal relationships *within* proteins, binding sites describe how a protein interacts with other molecules. These external interactions ultimately define the high-level function of the protein, and thus binding sites remain conserved even when the sequence as a whole evolves (Kinjo & Nakamura, 2009). Further, structural motifs in binding sites are mainly restricted to specific families or superfamilies of proteins (Kinjo & Nakamura, 2009), and binding sites can reveal evolutionary relationships among proteins (Lee et al., 2017). Thus binding sites may provide the model with a high-level characterization of the protein that is robust to individual sequence variation.

Attention targets PTMs in a small number of heads. A small number of heads in each model concentrate their attention very strongly on post-translational modifications (PTMs). For example, Head 11-6 in TapeBert focused 64% of attention on PTMs, though PTMs occur at only 0.8% of

---

[3]The background frequency of binding sites in the dataset is 4.8%.

Figure 5: Each plot shows the fraction of attention focused on a given property averaged over all heads within each layer. The plots, sorted by center of gravity (dashed line), show that heads in deeper layers focus relatively more attention on binding sites and contacts, whereas attention toward specific secondary structures is more even across layers.

Figure 6: Performance of probing classifiers by layer, sorted by task order in Figure 5. The embedding probes (orange) show the knowledge encoded in each layer's output embeddings. The attention probe (blue), show the information encoded in attention weights for the (pairwise) contact feature. Additional details are provided in Appendix B.2.

sequence positions in the dataset.[4] Similar to our discussion on binding sites, PTMs are critical to protein function (Rubin & Rosen, 1975) and thereby are likely to exhibit behavior that is conserved across the sequence space. See Appendix C.4 for full results.

4.3 CROSS-LAYER ANALYSIS

We analyze how attention captures properties of varying complexity across different layers of the model, and compare to a probing analysis of embeddings and attention weights (see Section 3).

Attention targets higher-level properties in deeper layers. As shown in Figure 5, deeper layers focus relatively more attention on binding sites and contacts (high-level concept), whereas secondary structure (low- to mid-level concept) is targeted more evenly across layers. The probing analysis of attention (Figure 6, blue) similarly shows that knowledge of contact maps (a pairwise feature) is encoded in attention weights primarily in the last 1-2 layers. These results are consistent with prior work in NLP that suggests deeper layers in text-based Transformers attend to more complex properties (Vig & Belinkov, 2019) and encode higher-level representations (Raganato & Tiedemann, 2018; Peters et al., 2018; Tenney et al., 2019; Jawahar et al., 2019).

The *embedding* probes (Figure 6, orange) also show that the model first builds representations of local secondary structure in lower layers before fully encoding binding sites and contact maps in deeper layers. However, this analysis also reveals stark differences in how knowledge of contact maps is accrued in embeddings, which accumulate this knowledge gradually over many layers, compared to attention weights, which acquire this knowledge only in the final layers in this case. This example points out limitations of common layerwise probing approaches that only consider embeddings, which, intuitively, represent what the model *knows* but not necessarily how it operationalizes that knowledge.

---

[4]This head also targets binding sites (Fig. 4) but at a percentage of 49%.

Figure 7: Percentage of each head's attention focused on amino acids *Pro* (left) and *Phe* (right).

Figure 8: Pairwise attention similarity (left) vs. substitution matrix (right) (codes in App. C.5)

4.4 AMINO ACIDS AND THE SUBSTITUTION MATRIX

In addition to high-level structural and functional properties, we also performed a fine-grained analysis of the interaction between attention and particular amino acids.

Attention heads specialize in particular amino acids. We computed the proportion of TapeBert's attention to each of the 20 standard amino acids, as shown in Figure 7 for two example amino acids. For 16 of the amino acids, there exists an attention head that focuses over 25% of attention on that amino acid, significantly greater than the background frequencies of the corresponding amino acids, which range from 1.3% to 9.4% (see App. C.5 for detailed results). Similar behavior was observed for ProtBert, ProtBert-BFD, ProtAlbert, and ProtXLNet models, with 17, 15, 16, and 18 amino acids, respectively, receiving greater than 25% of the attention from at least one attention head.

Attention is consistent with substitution relationships. A natural follow-up question is whether each head has "memorized" specific amino acids to target, or whether it has actually learned meaningful properties that correlate with particular amino acids. To test the latter hypothesis, we analyze whether amino acids with similar structural and functional properties are attended to similarly across heads. Specifically, we compute the Pearson correlation between the distribution of attention across heads between all pairs of distinct amino acids, as shown in Figure 8 (left). For example, the entry for *Pro* (P) and *Phe* (F) is the correlation between the two heatmaps in Figure 7. We compare these scores to the BLOSUM62 substitution scores (Sec. 2) in Figure 8 (right), and find a Pearson correlation of 0.73, suggesting that attention is moderately consistent with substitution relationships. Similar correlations are observed for ProtBert (0.68), ProtBert-BFD (0.75), ProtXLNet (0.71), and ProtAlbert (0.60).

5 RELATED WORK

5.1 PROTEIN LANGUAGE MODELS

Deep neural networks for protein language modeling have received broad interest. Early work applied the Skip-gram model (Mikolov et al., 2013) to construct continuous embeddings from protein sequences (Asgari & Mofrad, 2015). Sequence-only language models have since been trained through autoregressive or autoencoding self-supervision objectives for discriminative and generative tasks, for example, using LSTMs or Transformer-based architectures (Alley et al., 2019; Bepler & Berger, 2019; Rao et al., 2019; Rives et al., 2019). TAPE created a benchmark of five tasks to assess protein sequence models, and ProtTrans also released several large-scale pretrained protein Transformer

models (Elnaggar et al., 2020). Riesselman et al. (2019); Madani et al. (2020) trained autoregressive generative models to predict the functional effect of mutations and generate natural-like proteins.

From an interpretability perspective, Rives et al. (2019) showed that the output embeddings from a pretrained Transformer can recapitulate structural and functional properties of proteins through learned linear transformations. In our work, we take an interpretability-first perspective to focus on the internal model representations, specifically attention and intermediate hidden states, across multiple protein language models. We also explore novel biological properties including binding sites and post-translational modifications.

5.2 INTERPRETING MODELS IN NLP

The rise of deep neural networks in ML has also led to much work on interpreting these so-called black-box models. This section reviews the NLP interpretability literature on the Transformer model, which is directly comparable to our work on interpreting Transformer models of protein sequences.

Interpreting Transformers. The Transformer is a neural architecture that uses attention to accelerate learning (Vaswani et al., 2017). In NLP, transformers are the backbone of state-of-the-art pre-trained language models such as BERT (Devlin et al., 2019). *BERTology* focuses on interpreting what the BERT model learns about language using a suite of probes and interventions (Rogers et al., 2020). So-called *diagnostic classifiers* are used to interpret the outputs from BERT's layers (Veldhoen et al., 2016). At a high level, mechanisms for interpreting BERT can be placed into three main categories: interpreting the learned embeddings (Ethayarajh, 2019; Wiedemann et al., 2019; Mickus et al., 2019; Adi et al., 2016; Conneau et al., 2018), BERT's learned knowledge of syntax (Lin et al., 2019; Liu et al., 2019; Tenney et al., 2019; Htut et al., 2019; Hewitt & Manning, 2019; Goldberg, 2019), and BERT's learned knowledge of semantics (Tenney et al., 2019; Ettinger, 2020).

Interpreting attention specifically. Interpreting attention on textual sequences is a well-established area of research (Wiegreffe & Pinter, 2019; Zhong et al., 2019; Brunner et al., 2020; Hewitt & Manning, 2019). Past work has been shown that attention correlates with syntactic and semantic relationships in natural language in some cases (Clark et al., 2019; Vig & Belinkov, 2019; Htut et al., 2019). Depending on the task and model architecture, attention may have less or more explanatory power for model predictions (Jain & Wallace, 2019; Serrano & Smith, 2019; Pruthi et al., 2020; Moradi et al., 2019; Vashishth et al., 2019). Visualization techniques have been used to convey the structure and properties of attention in Transformers (Vaswani et al., 2017; Kovaleva et al., 2019; Hoover et al., 2019; Vig, 2019). Recent work has begun to analyze attention in Transformer models outside of the domain of natural language (Schwaller et al., 2020; Payne et al., 2020).

Our work extends these methods to protein sequence models, but also introduces methods for interpreting Transformers that, to our knowledge, have not previously been applied in NLP or other domains. First, we introduce the notion of *attention calibration*, the degree to which attention weights correspond to the actual probability of particular features. Second, we present cross-layer probing analyses of both attention weights and layer embeddings. While past work has analyzed attention and embeddings across layers, we believe we are the first to do so using a single, unified metric, which enables us to directly compare the relative information content of the two representations.

6 CONCLUSIONS AND FUTURE WORK

This paper builds on the synergy between NLP and computational biology by adapting and extending NLP interpretability methods to protein sequence modeling. We show how a Transformer language model recovers structural and functional properties of proteins and integrates this knowledge directly into its attention mechanism. In some cases, attention also provides a well-calibrated measure of confidence in the model's predictions of these properties.

While this paper focuses on reconciling attention with known properties of proteins, one might also leverage attention to uncover novel relationships or more nuanced forms of existing measures such as contacts maps, as discussed in Section 4.1. In this way, language models have the potential to serve as tools for scientific discovery. But in order for learned representations to be accessible to domain experts, they must be presented in an appropriate context to facilitate discovery. Visualizing attention in the context of protein structure (Figure 1) is one attempt to do so. We believe there is the potential to develop such contextual visualizations of learned representations in a range of scientific domains.

REFERENCES

Yossi Adi, Einat Kermany, Yonatan Belinkov, Ofer Lavi, and Yoav Goldberg. Fine-grained analysis of sentence embeddings using auxiliary prediction tasks. arXiv:1608.04207 [cs.CL]., 2016.

Ethan C Alley, Grigory Khimulya, Surojit Biswas, Mohammed AlQuraishi, and George M Church. Unified rational protein engineering with sequence-only deep representation learning. *bioRxiv*, pp. 589333, 2019.

Mohammed AlQuraishi. ProteinNet: a standardized data set for machine learning of protein structure. *arXiv preprint arXiv:1902.00249*, 2019.

Ehsaneddin Asgari and Mohammad RK Mofrad. Continuous distributed representation of biological sequences for deep proteomics and genomics. *PloS one*, 10(11), 2015.

Tristan Bepler and Bonnie Berger. Learning protein sequence embeddings using information from structure. *arXiv preprint arXiv:1902.08661*, 2019.

Helen M Berman, John Westbrook, Zukang Feng, Gary Gilliland, Talapady N Bhat, Helge Weissig, Ilya N Shindyalov, and Philip E Bourne. The protein data bank. *Nucleic acids research*, 28(1): 235–242, 2000.

Ashraf Brik and Chi-Huey Wong. HIV-1 protease: mechanism and drug discovery. *Organic & Biomolecular Chemistry*, 1(1):5–14, 2003.

Gino Brunner, Yang Liu, Damian Pascual, Oliver Richter, Massimiliano Ciaramita, and Roger Wattenhofer. On identifiability in transformers. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=BJg1f6EFDB.

Kevin Clark, Urvashi Khandelwal, Omer Levy, and Christopher D. Manning. What does BERT look at? an analysis of BERT's attention. *arXiv preprint arXiv:1906.04341*, 2019.

Andy Coenen, Emily Reif, Ann Yuan, Been Kim, Adam Pearce, Fernanda Viégas, and Martin Wattenberg. Visualizing and measuring the geometry of bert. *arXiv preprint arXiv:1906.02715*, 2019.

Alexis Conneau, German Kruszewski, Guillaume Lample, Loïc Barrault, and Marco Baroni. What you can cram into a single vector: Probing sentence embeddings for linguistic properties, 2018.

Gonçalo M. Correia, Vlad Niculae, and André F. T. Martins. Adaptively sparse transformers. *arXiv preprint arXiv:1909.00015*, 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://www.aclweb.org/anthology/N19-1423.

Sara El-Gebali, Jaina Mistry, Alex Bateman, Sean R. Eddy, Aurélien Luciani, Simon C. Potter, Matloob Qureshi, Lorna J. Richardson, Gustavo A. Salazar, Alfredo Smart, Erik L. L. Sonnhammer, Layla Hirsh, Lisanna Paladin, Damiano Piovesan, Silvio C. E. Tosatto, and Robert D. Finn. The Pfam protein families database in 2019. *Nucleic Acids Research*, 47(D1):D427–D432, January 2019a. doi: 10.1093/nar/gky995.

Sara El-Gebali, Jaina Mistry, Alex Bateman, Sean R Eddy, Aurélien Luciani, Simon C Potter, Matloob Qureshi, Lorna J Richardson, Gustavo A Salazar, Alfredo Smart, Erik L L Sonnhammer, Layla Hirsh, Lisanna Paladin, Damiano Piovesan, Silvio C E Tosatto, and Robert D Finn. The Pfam protein families database in 2019. *Nucleic Acids Research*, 47(D1):D427–D432, 2019b. ISSN 0305-1048. doi: 10.1093/nar/gky995. URL https://academic.oup.com/nar/article/47/D1/D427/5144153.

Ahmed Elnaggar, Michael Heinzinger, Christian Dallago, Ghalia Rihawi, Yu Wang, Llion Jones, Tom Gibbs, Tamas Feher, Christoph Angerer, Martin Steinegger, Debsindhu Bhowmik, and Burkhard Rost. Prottrans: Towards cracking the language of life's code through self-supervised deep learning and high performance computing, 2020.

Kawin Ethayarajh. How contextual are contextualized word representations? comparing the geometry of BERT, ELMo, and GPT-2 embeddings. *arXiv preprint arXiv:1909.00512*, 2019.

Allyson Ettinger. What BERT is not: Lessons from a new suite of psycholinguistic diagnostics for language models. *Transactions of the Association for Computational Linguistics*, 8:34–48, 2020.

Naomi K Fox, Steven E Brenner, and John-Marc Chandonia. Scope: Structural classification of proteins—extended, integrating scop and astral data and classification of new structures. *Nucleic acids research*, 42(D1):D304–D309, 2013.

Yoav Goldberg. Assessing BERT's syntactic abilities. *arXiv preprint arXiv:1901.05287*, 2019.

Christopher Grimsley, Elijah Mayfield, and Julia R.S. Bursten. Why attention is not explanation: Surgical intervention and causal reasoning about neural models. In *Proceedings of The 12th Language Resources and Evaluation Conference*, pp. 1780–1790, Marseille, France, May 2020. European Language Resources Association. ISBN 979-10-95546-34-4. URL `https://www.aclweb.org/anthology/2020.lrec-1.220`.

S Henikoff and J G Henikoff. Amino acid substitution matrices from protein blocks. *Proceedings of the National Academy of Sciences*, 89(22):10915–10919, 1992. ISSN 0027-8424. doi: 10.1073/pnas.89.22.10915. URL `https://www.pnas.org/content/89/22/10915`.

John Hewitt and Christopher D Manning. A structural probe for finding syntax in word representations. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4129–4138, 2019.

Benjamin Hoover, Hendrik Strobelt, and Sebastian Gehrmann. exBERT: A visual analysis tool to explore learned representations in transformers models. *arXiv preprint arXiv:1910.05276*, 2019.

Phu Mon Htut, Jason Phang, Shikha Bordia, and Samuel R Bowman. Do attention heads in BERT track syntactic dependencies? *arXiv preprint arXiv:1911.12246*, 2019.

Sarthak Jain and Byron C. Wallace. Attention is not Explanation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 3543–3556, June 2019.

Ganesh Jawahar, Benoît Sagot, and Djamé Seddah. What does BERT learn about the structure of language? In *ACL 2019 - 57th Annual Meeting of the Association for Computational Linguistics*, Florence, Italy, July 2019. URL `https://hal.inria.fr/hal-02131630`.

Akira Kinjo and Haruki Nakamura. Comprehensive structural classification of ligand-binding motifs in proteins. *Structure*, 17(2), 2009.

Michael Schantz Klausen, Martin Closter Jespersen, Henrik Nielsen, Kamilla Kjaergaard Jensen, Vanessa Isabell Jurtz, Casper Kae Soenderby, Morten Otto Alexander Sommer, Ole Winther, Morten Nielsen, Bent Petersen, et al. Netsurfp-2.0: Improved prediction of protein structural features by integrated deep learning. *Proteins: Structure, Function, and Bioinformatics*, 2019.

Olga Kovaleva, Alexey Romanov, Anna Rogers, and Anna Rumshisky. Revealing the dark secrets of BERT. *arXiv preprint arXiv:1908.08593*, 2019.

Keita Kurita, Nidhi Vyas, Ayush Pareek, Alan W Black, and Yulia Tsvetkov. Measuring bias in contextualized word representations, 2019.

Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations, 2019.

Juyong Lee, Janez Konc, Dusanka Janezic, and Bernard Brooks. Global organization of a binding site network gives insight into evolution and structure-function relationships of proteins. *Sci Rep*, 7 (11652), 2017.

Yongjie Lin, Yi Chern Tan, and Robert Frank. Open sesame: Getting inside BERT's linguistic knowledge. *arXiv preprint arXiv:1906.01698*, 2019.

Nelson F Liu, Matt Gardner, Yonatan Belinkov, Matthew Peters, and Noah A Smith. Linguistic knowledge and transferability of contextual representations. *arXiv preprint arXiv:1903.08855*, 2019.

Ali Madani, Bryan McCann, Nikhil Naik, Nitish Shirish Keskar, Namrata Anand, Raphael R Eguchi, Po-Ssu Huang, and Richard Socher. Progen: Language modeling for protein generation. *bioRxiv*, 2020.

Timothee Mickus, Denis Paperno, Mathieu Constant, and Kees van Deemeter. What do you mean, BERT? assessing BERT as a distributional semantics model. *arXiv preprint arXiv:1911.05758*, 2019.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 26*, pp. 3111–3119. Curran Associates, Inc., 2013.

Pooya Moradi, Nishant Kambhatla, and Anoop Sarkar. Interrogating the explanatory power of attention in neural machine translation. In *Proceedings of the 3rd Workshop on Neural Generation and Translation*, pp. 221–230, Hong Kong, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-5624. URL https://www.aclweb.org/anthology/D19-5624.

John Moult, Krzysztof Fidelis, Andriy Kryshtafovych, Torsten Schwede, and Anna Tramontano. Critical assessment of methods of protein structure prediction (CASP)-Round XII. *Proteins: Structure, Function, and Bioinformatics*, 86:7–15, 2018. ISSN 08873585. doi: 10.1002/prot.25415. URL http://doi.wiley.com/10.1002/prot.25415.

Mahdi Pakdaman Naeini, Gregory F. Cooper, and Milos Hauskrecht. Obtaining well calibrated probabilities using bayesian binning. In *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence*, AAAI'15, pp. 2901–2907. AAAI Press, 2015. ISBN 0262511290.

Hai Nguyen, David A Case, and Alexander S Rose. NGLview–interactive molecular graphics for Jupyter notebooks. *Bioinformatics*, 34(7):1241–1242, 12 2017. ISSN 1367-4803. doi: 10.1093/bioinformatics/btx789. URL https://doi.org/10.1093/bioinformatics/btx789.

Timothy Niven and Hung-Yu Kao. Probing neural network comprehension of natural language arguments, 2019.

Josh Payne, Mario Srouji, Dian Ang Yap, and Vineet Kosaraju. Bert learns (and teaches) chemistry, 2020.

Matthew Peters, Mark Neumann, Luke Zettlemoyer, and Wen-tau Yih. Dissecting contextual word embeddings: Architecture and representation. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 1499–1509, Brussels, Belgium, October-November 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1179. URL https://www.aclweb.org/anthology/D18-1179.

Danish Pruthi, Mansi Gupta, Bhuwan Dhingra, Graham Neubig, and Zachary C. Lipton. Learning to deceive with attention-based explanations. In *Annual Conference of the Association for Computational Linguistics (ACL)*, July 2020. URL https://arxiv.org/abs/1909.07913.

Alessandro Raganato and Jörg Tiedemann. An analysis of encoder representations in transformer-based machine translation. In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pp. 287–297, Brussels, Belgium, November 2018. Association for Computational Linguistics. doi: 10.18653/v1/W18-5431. URL https://www.aclweb.org/anthology/W18-5431.

Roshan Rao, Nicholas Bhattacharya, Neil Thomas, Yan Duan, Xi Chen, John Canny, Pieter Abbeel, and Yun S Song. Evaluating protein transfer learning with tape. In *Advances in Neural Information Processing Systems*, 2019.

Adam J Riesselman, Jung-Eun Shin, Aaron W Kollasch, Conor McMahon, Elana Simon, Chris Sander, Aashish Manglik, Andrew C Kruse, and Debora S Marks. Accelerating protein design using autoregressive generative models. *bioRxiv*, pp. 757252, 2019.

Alexander Rives, Siddharth Goyal, Joshua Meier, Demi Guo, Myle Ott, C Lawrence Zitnick, Jerry Ma, and Rob Fergus. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *bioRxiv*, pp. 622803, 2019.

Anna Rogers, Olga Kovaleva, and Anna Rumshisky. A primer in bertology: What we know about how bert works, 2020.

Nathan J Rollins, Kelly P Brock, Frank J Poelwijk, Michael A Stiffler, Nicholas P Gauthier, Chris Sander, and Debora S Marks. Inferring protein 3d structure from deep mutation scans. *Nature genetics*, 51(7):1170, 2019.

Alexander S. Rose and Peter W. Hildebrand. NGL Viewer: a web application for molecular visualization. *Nucleic Acids Research*, 43(W1):W576–W579, 04 2015. ISSN 0305-1048. doi: 10.1093/nar/gkv402. URL https://doi.org/10.1093/nar/gkv402.

Alexander S Rose, Anthony R Bradley, Yana Valasatava, Jose M Duarte, Andreas Prlić, and Peter W Rose. NGL viewer: web-based molecular graphics for large complexes. *Bioinformatics*, 34(21): 3755–3758, 05 2018. ISSN 1367-4803. doi: 10.1093/bioinformatics/bty419. URL https://doi.org/10.1093/bioinformatics/bty419.

Charles Rubin and Ora Rosen. Protein phosphorylation. *Annual Review of Biochemistry*, 44:831–887, 1975. URL https://doi.org/10.1146/annurev.bi.44.070175.004151.

Philippe Schwaller, Benjamin Hoover, Jean-Louis Reymond, Hendrik Strobelt, and Teodoro Laino. Unsupervised Attention-Guided Atom-Mapping. *ChemRxiv*, 5 2020. doi: 10.26434/chemrxiv.12298559.v1. URL https://chemrxiv.org/articles/Unsupervised_Attention-Guided_Atom-Mapping/12298559.

Sofia Serrano and Noah A. Smith. Is attention interpretable? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2931–2951, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1282. URL https://www.aclweb.org/anthology/P19-1282.

Martin Steinegger and Johannes Söding. Clustering huge protein sequence sets in linear time. *Nature Communications*, 9(2542), 2018. doi: 10.1038/s41467-018-04964-5.

Baris E. Suzek, Yuqi Wang, Hongzhan Huang, Peter B. McGarvey, Cathy H. Wu, and the UniProt Consortium. UniRef clusters: a comprehensive and scalable alternative for improving sequence similarity searches. *Bioinformatics*, 31(6):926–932, 11 2014. ISSN 1367-4803. doi: 10.1093/bioinformatics/btu739. URL https://doi.org/10.1093/bioinformatics/btu739.

Yi Chern Tan and L. Elisa Celis. Assessing social and intersectional biases in contextualized word representations. In *Advances in Neural Information Processing Systems 32*, pp. 13230–13241. Curran Associates, Inc., 2019.

Ian Tenney, Dipanjan Das, and Ellie Pavlick. BERT rediscovers the classical NLP pipeline. *arXiv preprint arXiv:1905.05950*, 2019.

Shikhar Vashishth, Shyam Upadhyay, Gaurav Singh Tomar, and Manaal Faruqui. Attention interpretability across NLP tasks. *arXiv preprint arXiv:1909.11218*, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Sara Veldhoen, Dieuwke Hupkes, and Willem H. Zuidema. Diagnostic classifiers revealing how neural networks process hierarchical structure. In *CoCo@NIPS*, 2016.

Jesse Vig. A multiscale visualization of attention in the transformer model. *arXiv preprint arXiv:1906.05714*, 2019.

Jesse Vig and Yonatan Belinkov. Analyzing the structure of attention in a transformer language model. arXiv:1906.04284 [cs.CL]., 2019.

Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Yaron Singer, and Stuart Shieber. Causal mediation analysis for interpreting neural nlp: The case of gender bias, 2020.

Elena Voita, David Talbot, Fedor Moiseev, Rico Sennrich, and Ivan Titov. Analyzing multi-head self-attention: Specialized heads do the heavy lifting, the rest can be pruned, 2019.

Gregor Wiedemann, Steffen Remus, Avi Chawla, and Chris Biemann. Does BERT make any sense? interpretable word sense disambiguation with contextualized embeddings. *arXiv preprint arXiv:1909.10430*, 2019.

Sarah Wiegreffe and Yuval Pinter. Attention is not not explanation. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 11–20, November 2019.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Ruslan Salakhutdinov, and Quoc V. Le. Xlnet: Generalized autoregressive pretraining for language understanding, 2019.

Bianca Zadrozny and Charles Elkan. Transforming classifier scores into accurate multiclass probability estimates. In *Proceedings of the Eighth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '02, pp. 694–699, New York, NY, USA, 2002. Association for Computing Machinery. ISBN 158113567X. doi: 10.1145/775047.775151. URL https://doi.org/10.1145/775047.775151.

Ruiqi Zhong, Steven Shao, and Kathleen McKeown. Fine-grained sentiment analysis with faithful attention. *arXiv preprint arXiv:1908.06870*, 2019.

A   Model Overview

A.1   BERT Transformer Architecture

Stacked Encoder: BERT uses a stacked-encoder architecture, which inputs a sequence of tokens $x = (x_1, ..., x_n)$ and applies position and token embeddings followed by a series of encoder layers. Each layer applies multi-head self-attention (see below) in combination with a feedforward network, layer normalization, and residual connections. The output of each layer ℓ is a sequence of contextualized embeddings $(\mathbf{h}_1^{(\ell)}, \ldots, \mathbf{h}_n^{(\ell)})$.

Self-Attention: Given an input $x = (x_1, \ldots, x_n)$, the self-attention mechanism assigns to each token pair i, j an attention weight $\alpha_{i,j} > 0$ where $\sum_j \alpha_{i,j} = 1$. Attention in BERT is bidirectional. In the multi-layer, multi-head setting, α is specific to a layer and head. The BERT-Base model has 12 layers and 12 heads. Each attention head learns a distinct set of weights, resulting in 12 x 12 = 144 distinct attention mechanisms in this case.

The attention weights $\alpha_{i,j}$ are computed from the scaled dot-product of the *query vector* of i and the *key vector* of j, followed by a softmax operation. The attention weights are then used to produce a weighted sum of value vectors:

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right) V \tag{2}$$

using query matrix Q, key matrix K, and value matrix V, where d_k is the dimension of K. In a multi-head setting, the queries, keys, and values are linearly projected h times, and the attention operation is performed in parallel for each representation, with the results concatenated.

A.2   Other Transformer Variants

ALBERT: The architecture of ALBERT differs from BERT in two ways: (1) It shares parameters across layers, unlike BERT which learns distinct parameters for every layer and (2) It uses factorized embeddings, which allows the input token embeddings to be of a different (smaller) size than the hidden states. The original version of ALBERT designed for text also employed a sentence-order prediction pretraining task, but this was not used on the models studied in this paper.

XLNet: Instead of the masked-language modeling pretraining objective use for BERT, XLNet uses a bidirectional auto-regressive pretraining method that considers all possible orderings of the input factorization. The architecture also adds a segment recurrence mechanism to process long sequences, as well as a relative rather than absolute encoding scheme.

B   Additional Experimental Details

B.1   Alternative attention alignment metric

Here we present an alternative formulation to Eq. 1 based on an attention-weighted average. We define an indicator function $f(i, j)$ for property f that returns 1 if the property is present in token pair (i, j) (i.e., if amino acids i and j are in contact), and zero otherwise. We then compute the proportion of attention that aligns with f over a dataset X as follows:

$$p_\alpha(f) = \sum_{x \in X} \sum_{i=1}^{|x|} \sum_{j=1}^{|x|} f(i,j)\alpha_{i,j}(x) \bigg/ \sum_{x \in X} \sum_{i=1}^{|x|} \sum_{j=1}^{|x|} \alpha_{i,j}(x) \tag{3}$$

where $\alpha_{i,j}(x)$ denotes the attention from i to j for input sequence x.

B.2   Probing methodology

Embedding probe. We probe the embedding vectors output from each layer using a linear probing classifier. For token-level probing tasks (binding sites, secondary structure) we feed each token's

output vector directly to the classifier. For token-pair probing tasks (contact map) we construct a pairwise feature vector by concatenating the elementwise differences and products of the two tokens' output vectors, following the TAPE[5] implementation.

We use task-specific evaluation metrics for the probing classifier: for secondary structure prediction, we measure F1 score; for contact prediction, we measure precision@$L/5$, where L is the length of the protein sequence, following standard practice (Moult et al., 2018); for binding site prediction, we measure precision@$L/20$, since approximately one in twenty amino acids in each sequence is a binding site (4.8% in the dataset).

Attention probe. Just as the attention weight $\alpha_{i,j}$ is defined for a pair of amino acids (i, j), so is the contact property $f(i, j)$, which returns true if amino acids i and j are in contact. Treating the attention weight as a feature of a token-pair (i, j), we can train a probing classifier that predicts the contact property based on this feature, thereby quantifying the attention mechanism's knowledge of that property. In our multi-head setting, we treat the attention weights across all heads in a given layer as a feature vector, and use a probing classifier to assess the knowledge of a given property in the attention weights across the entire layer. As with the embedding probe, we measure performance of the probing classifier using precision@$L/5$, where L is the length of the protein sequence, following standard practice for contact prediction.

B.3 DATASETS

We used two protein sequence datasets from the TAPE repository for the analysis: the ProteinNet dataset (AlQuraishi, 2019; Fox et al., 2013; Berman et al., 2000; Moult et al., 2018) and the Secondary Structure dataset (Rao et al., 2019; Berman et al., 2000; Moult et al., 2018; Klausen et al., 2019). The former was used for analysis of amino acids and contact maps, and the latter was used for analysis of secondary structure. We additionally created a third dataset for binding site and post-translational modification (PTM) analysis from the Secondary Structure dataset, which was augmented with binding site and PTM annotations obtained from the Protein Data Bank's Web API.[6] We excluded any sequences for which annotations were not available. The resulting dataset sizes are shown in Table 1. For the analysis of attention, a random subset of 5000 sequences from the training split of each dataset was used, as the analysis was purely evaluative. For training and evaluating the diagnostic classifier, the full training and validation splits were used.

Table 1: Datasets used in analysis

Dataset	Train size	Validation size
ProteinNet	25299	224
Secondary Structure	8678	2170
Binding Sites / PTM	5734	1418

---

[5] https://github.com/songlab-cal/tape
[6] http://www.rcsb.org/pdb/software/rest.do

C ADDITIONAL RESULTS OF ATTENTION ANALYSIS

C.1 SECONDARY STRUCTURE

Figure 9: Percentage of each head's attention that is focused on *Helix* secondary structure, averaged over a dataset. Results are shown for all five model variants. Note that the ordering of heads within a layer is not comparable across models.

(a) TapeBert Model

(b) ProtBert Model

(c) ProtBert-BFD Model

(d) ProtXLNet Model

(e) ProtAlbert Model

Figure 10: Percentage of each head's attention that is focused on *Strand* secondary structure, averaged over a dataset. Results are shown for all five model variants. Note that the ordering of heads within a layer is not comparable across models.

(a) TapeBert Model

(b) ProtBert Model

(c) ProtBert-BFD Model

(d) ProtXLNet Model

(e) ProtAlbert Model

Figure 11: Percentage of each head's attention that is focused on *Turn/Bend* secondary structure, averaged over a dataset. Results are shown for all five model variants. Note that the ordering of heads within a layer is not comparable across models.

C.2 CONTACT MAPS

(a) TapeBert Model

(b) ProtBert Model

(c) ProtBert-BFD Model

(d) ProtXLNet Model

(e) ProtAlbert Model

Figure 12: Top-10 heads aligned with contact maps for each model, with 95% confidence intervals shown. The orange dotted lines represents the background frequency of contact pairs in the dataset amongst all possible position pairings.

Figure 13: Calibration analysis for contact maps in most-aligned head within each model.

C.3 BINDING SITES

(a) TapeBert Model

(b) ProtBert Model

(c) ProtBert-BFD Model

(d) ProtXLNet Model

(e) ProtAlbert Model

Figure 14: Percentage of each head's attention that is focused on binding sites, averaged over a dataset. Results are shown for all five model variants. Note that the ordering of heads within a layer is not comparable across models.

(a) TapeBert Model

(b) ProtBert Model

(c) ProtBert-BFD Model

(d) ProtXLNet Model

(e) ProtAlbert Model

Figure 15: Results for top-10 heads from previous figure, with 95% confidence intervals. The orange dotted line represents the background frequency of binding sites in the database.

C.4 POST-TRANSLATIONAL MODIFICATIONS

Figure 16: Percentage of each head's attention that is focused on post-translational modifications, averaged over a dataset.

(a) TapeBert Model

(b) ProtBert Model

(c) ProtBert-BFD Model

(d) ProtXLNet Model

(e) ProtAlbert Model

Figure 17: Results for top-10 heads from previous figure, with 95% confidence intervals. The orange dotted line represents the background frequency of post-translational modifications in the database.

C.5 AMINO ACIDS

Figure 18: Percentage of each head's attention that is focused on the given amino acid, averaged over a dataset.

Figure 19: Percentage of each head's attention that is focused on the given amino acid, averaged over a dataset (cont.)

Table 2: Amino acids and the corresponding maximally attentive heads. The differences between the attention percentages and the background frequencies of each amino acid are all statistically significant. ($p < 0.00001$).

Abbrev	Code	Name	Top Head	Attn %	Background %
Ala	A	Alanine	12-11	25.5	7.9
Arg	R	Arginine	12-8	63.2	5.2
Asn	N	Asparagine	8-2	44.8	4.3
Asp	D	Aspartic acid	12-6	79.9	5.8
Cys	C	Cysteine	11-6	83.2	1.3
Gln	Q	Glutamine	11-7	7.1	3.8
Glu	E	Glutamic acid	11-7	16.2	6.9
Gly	G	Glycine	2-11	98.1	7.1
His	H	Histidine	9-10	56.7	2.7
Ile	I	Isoleucine	11-10	27.0	5.6
Leu	L	Leucine	2-12	44.1	9.4
Lys	K	Lysine	12-8	29.4	6.0
Met	M	Methionine	3-10	73.5	2.3
Phe	F	Phenylalanine	12-3	22.7	3.9
Pro	P	Proline	1-11	98.3	4.6
Ser	S	Serine	12-7	36.1	6.4
Thr	T	Threonine	12-7	19.0	5.4
Trp	W	Tryptophan	11-4	68.1	1.3
Tyr	Y	Tyrosine	12-3	51.6	3.4
Val	V	Valine	12-11	34.0	6.8