A Survey on *Entropy Mechanism* in Large Reasoning Models

Abstract

Entropy mechanism emerges as a key organizing principle for understanding and improving Large Reasoning Models (LRMs). This survey examines how entropy shapes both their training and inference behavior. On the training side, we take a mathematical perspective: casting existing RL-based reasoning algorithms into a unified objective and using this formulation to derive an entropy-centric decomposition of methods, clarifying how different approaches adjust exploration–exploitation "knobs". On the inference side, based on the characteristic of LRM that trading increased inference tokens yields better performance, we summarize methods that leverage entropy to enhance inference performance or reduce uncertainty. Finally, we discuss open challenges and future directions of entropy-driven research for LRMs. Our repository is available on https://anonymous.4open.science/r/Awesome_LRM_with_Entropy-0503.

1 Introduction

Large Reasoning Models (LRMs) (*e.g.*, OpenAI o1 (OpenAI, 2024) and DeepSeek-R1 (Guo et al., 2025)) are designed for slow thinking—deliberate, token-intensive reasoning that markedly improves systematic reasoning and complex problem-solving (Pan et al., 2026; Li et al., 2025d). Their reasoning capabilities are supported by two key components: (i) Reinforcement Learning (RL)–based training, which explicitly encourages and shapes reasoning behavior (Zeng et al., 2025a; Kimi Team, 2025; MiniMax-AI, 2025), and (ii) Test-Time Scaling (TTS) (Muennighoff et al., 2025; Chen et al., 2024b), which allocates substantially more inference-time compute to extend and refine the reasoning trace.

Entropy measures the model's uncertainty over the next-token distribution. A high entropy indicates many possible continuations, whereas a low

Figure 1: The left panel shows reward and entropy during GRPO training on GSM8K with Qwen3-8B, and the right panel shows entropy at inference after training, where the high entropy parts are shown.

entropy suggests the model is more certain or conservative. According to existing studies, entropy plays a central role in both the RL training and TTS inference stages of LRMs. During RL, entropy and task reward naturally lie at opposite ends of the exploration–exploitation trade-off (Xue et al., 2025; Zhang et al., 2025c; Audibert et al., 2009; Yue et al., 2025), as illustrated in Fig. 1(left). In settings with sparse rewards, PPO/GRPO-style ratio clipping and batch- or group-mean baselines (Schulman et al., 2017; Shao et al., 2024) induce systematic bias in estimated advantages, driving the policy to concentrate probability mass on a narrow set of high-reward trajectories (Jin et al., 2025; Liu et al., 2025b). This behavior accelerates entropy collapse and premature convergence, sharply reducing exploration and solution-space coverage and ultimately trapping the model in suboptimal policy regions (Cui et al., 2025; Huang et al., 2025b; Hao et al., 2025). During inference, LRMs generate far longer reasoning than conventional Large Language Models (LLMs). The high-entropy segments are typically regarded as an important internal signal and turning points in the reasoning, where it initiates reflection, introduces assumptions, and triggers other key reasoning patterns (Wang et al., 2025f; Shorinwa et al., 2025) as Fig. 1(right). By understanding, controlling, and exploiting the transitions between high- and low-entropy phases

Figure 2: Timeline of papers on entropy mechanisms in LRM within sixteen months after the emergence of GRPO.

during reasoning, researchers can raise the think quality of LRMs (Kayal et al., 2025; Farquhar et al., 2024). Fig. 2 shows the rapid growth of LRM+entropy research, led by top institutes, highlighting entropy's importance in LRMs.

This survey examines entropy mechanisms in LRM training and inference, as shown in Fig. 3, which highlights the relevant work and classifications. On the training side, we introduce a new unifying perspective: we embed existing approaches into a single RL objective and interpret their effects as regularizing specific parameters within that objective. Distinct from prior surveys organized around benchmarks and problem types (Xu et al., 2025a; Liu et al., 2025c), we categorize training methods according to their modified parameters in PPO/GRPO's original optimization objective, explicitly identifying the specific 'knob' that is modified for each. On the inference side, we revisit several recurring criticisms of LRMs (e.g., excessive inference time (Zhang et al., 2025c; Alomrani et al., 2025)) and analyze how entropy-aware TTS techniques leverage intrinsic signals to mitigate these issues in practice. Building on these insights, we highlight key open challenges and outline several promising directions for future research.

2 Entropy Mechanism in LRM Training

LRMs are typically trained with policy-gradient methods, such as PPO and GRPO, to strengthen their inference capabilities (Schulman et al., 2017; Shao et al., 2024; Zhang et al., 2025c). The corresponding training loss is shown in Fig. 4. $\{o_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot \mid q)$ denotes a group of G trajectories generated by the behavior policy $\pi_{\theta_{\text{old}}}$. Each trajectory o_i has a token sequence of length $|o_i|$, and the inner sum runs over token positions $t = 1, \ldots, |o_i|$. $r_{i,t}(\theta)$ is the importance ratio.

Existing training approaches largely operate by adjusting five control knobs: **(i) The sampling term** $q \sim P(Q)$ & $\{o_i\}$ determines which queries are exposed to the learner and thus which parts of the loss landscape are emphasized during training. **(ii) The advantages of tokens** $\hat{A}_{i,t}$ determine which pattern is encouraged/punished. **(iii) The clip ratio** $\text{clip}(\cdot)$, which controls the magnitude of policy updates by capping the importance ratio $r_{i,t}$. And **(iv) The KL loss** $\beta D_{\text{KL}}(\pi_\theta \| \pi_{\text{ref}})$ regularizes deviation from a reference policy controlled by β. Additionally, some methods directly change **(v) The learning objective itself** $\mathcal{J}_{\text{PPO/GRPO}}(\theta)$, for example by adding or reweighting loss terms. We organize all methods by the parameters they modify

Figure 3: An entropy-centric overview of LRM mechanisms in training and inference.

$$\mathcal{J}_{\text{PPO/GRPO}}(\theta) = \mathbb{E}_{\substack{q \sim P(Q), \\ \{o_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot|q)}} \left[-\frac{1}{G} \sum_{i=1}^{G} \frac{1}{|o_i|} \sum_{t=1}^{|o_i|} \min \left(r_{i,t}(\theta)\, \hat{A}_{i,t}, \text{clip}\left(r_{i,t}(\theta), 1-\varepsilon,\, 1+\varepsilon \right) \hat{A}_{i,t} \right) + \beta\, D_{\text{KL}}\big(\pi_{\theta} \,\|\, \pi_{\text{ref}}\big) \right]$$

Figure 4: The PPO/GRPO optimization objective, where different colors mark different parts.

to form an entropy-control guideline; methods that affect multiple parameters are presented separately. With this organization, future researchers who wish to examine a specific parameter can directly anchor it to its corresponding entropy-control role and related method family. Although the optimization relationship between entropy and model performance in LRMs remains difficult to characterize precisely, we nevertheless attempt in the Appendix. A.8 to provide a unified formulation of these key "knobs" through an optimization objective, illustrating how they can directly influence final performance.

2.1 Sampling – $q \sim P(Q)$ & $\{o_i\}$

Policy learning algorithms learn from self-generated samples, making sampling schemes crucial for training. In GRPO-based methods, within-group sample diversity is essential for effective learning signals. Based on rollout trajectories, sampling approaches can be categorized as: **(1) Single-Turn Sampling**, the standard single-round inference commonly used in tasks like math reasoning;

(2) Agentic Sampling, involving multi-turn rollouts with tool interactions

2.1.1 Single-Turn Sample

AEPO-Wang (Wang et al., 2025b) adopts a dynamic sampling strategy: when the overall entropy is low, it increases the sampling temperature, and when the entropy is high, it decreases the temperature, thereby controlling the diversity of samples. Some methods treat high-entropy tokens in the sampling process as critical turning points and use them as signals to branch the sampling trajectories. TreeRL (Hou et al., 2025) is a representative example: it uses such high-entropy tokens to construct tree-structured sampling results. FR3E (Zheng et al., 2025b), ADR (Zhang et al., 2025f), ROSE (Zhao et al., 2026) and ETTRL (Liu et al., 2025a) adopt similar strategies. In contrast, CURE (Li et al., 2025b) emphasizes that the rollout should already be in a high-entropy regime at the very beginning to enhance the diversity of early decisions and concatenates the low-entropy

segments of the rollout into the prompt and then re-rolls for new samples. Cao *et al.* (Cao et al., 2025a) directly use entropy as a measure of problem difficulty, constructing a curriculum learning trajectory that progresses from low to high-entropy—that is, from easy to hard. POPE (Qu et al., 2026) and HIVE (Wu et al., 2026) use entropy as a measure of problem difficulty, enabling models to progressively learn from more challenging problems and thereby achieve more stable optimization.

2.1.2 Agentic Sample

For agentic sampling, the presence of tool-related information that is not directly generated by the model leads to irregular entropy fluctuations. ARPO (Dong et al., 2025b) observes this phenomenon and, analogous to single-turn samples, shares the preceding prefix at high-entropy tool-call turns and then samples new branches from that point. AEPO-Dong (Dong et al., 2025a), as a follow-up, found that multiple consecutive high-entropy rounds would concentrate limited branching resources on a few tracks, causing sampling to "freeze" on a high-entropy chain (high-entropy rollout collapse). Therefore, AEPO-Dong added entropy pre-monitoring and branch penalties to the ARPO framework: on the one hand, adaptively allocating the number of global vs. branch rollouts based on problem entropy/tool entropy; on the other hand, suppressing consecutive high-entropy branches on the same path, distributing exploration more evenly across different tracks.

2.2 Advantage – $\hat{A}_{i,t}$

In RL, advantage fundamentally influences the direction of optimization, while original GRPO's advantage setting is also considered to be one of the causes of entropy collapse. Some studies directly control entropy changes during the reinforcement process by modifying different advantage calculation methods. They can be categorized from two perspectives: (1) **Entropy as Advantage Bonus**, where entropy or entropy-derived metrics are directly incorporated into the advantage calculation. (2) **Entropy as Coefficient**, where entropy is used to weight the advantage, thereby amplifying or suppressing tokens within specific entropy ranges.

2.2.1 Entropy as Advantage Bonus

Entropy-as-bonus methods can be understood as balancing two competing objectives: encouraging exploration and reducing uncertainty. On the exploration side, Cheng et al. (2025) show that adding an entropy term to the advantage encourages longer and deeper reasoning traces, improving Pass@K coverage. RL-ZVP (Le et al., 2025) constructs fine-grained entropy-based advantages for zero-variance samples, promoting diverse correct solutions while reducing penalties on high-entropy tokens in fully incorrect samples. PRL (Yao et al., 2026a) further introduces entropy-derived process rewards to provide intermediate supervision, thereby broadening the model's reasoning boundary. Motivated by the U-shaped pattern of token entropy (Deng et al., 2025), PEAR (Huang et al., 2025a) uses the entropy gap between thinking and answer contents as an additional advantage, encouraging exploration during reasoning while normalizing the final answer.

On the uncertainty-reduction side, several methods suppress excessive entropy to improve stability and efficiency. EM-INF (Agarwal et al., 2025) shows that entropy minimization can stabilize model outputs, while EMPG (Wang et al., 2025e) penalizes future entropy to steer the policy away from ambiguous tokens. ETR (Xiong et al., 2026) introduces an entropy-trend reward that encourages a downward entropy trajectory across reasoning steps, reducing prolonged uncertainty and overthinking while preserving local exploration. ENTRA (Cai et al., 2026) uses entropy to identify and discourage redundant low-importance reasoning tokens, reducing unnecessary repetition while preserving essential reasoning steps. Similarly, EMPO (Zhang et al., 2025b) treats entropy as an advantage signal for suppressing unreliable generations. Overall, entropy-aware advantages balance exploration with uncertainty control.

2.2.2 Entropy as Advantage Coefficient

Another line of work uses entropy to reweight advantages, modulating the contribution of tokens, segments, or samples during policy updates. At the token level, EDGE-GRPO (Zhang et al., 2025e) uses inverse entropy to emphasize low-entropy tokens, while GTPO/GRPO-S (Tan et al., 2025) redistributes rewards with dynamic entropy weighting at the token or sequence level. ERPO (Yu et al., 2026), ACPO (Yin et al., 2025), and EAPO (He et al., 2026) further adjust token-level learning signals according to entropy-related uncertainty, informativeness, or reward polarity, helping the model focus on critical reasoning steps.

At the sample or group level, entropy guides

which responses should be amplified or suppressed. UCAS (Xie et al., 2025) and AsymGRPO (Gu et al., 2026) apply asymmetric advantage modulation to encourage confident correct responses while preserving informative exploration in incorrect or uncertain ones. ProGRPO (Li et al., 2026b) reweights advantages using generative probability signals to reduce over-confident updates, and LESS (Chen et al., 2025c) weights recurring low-entropy segments according to their correctness. Beyond direct weighting, CANON (Chen et al., 2025a), QAE (Wu et al., 2025b), and AdaThink-Med (Rui et al., 2025) use entropy for response regrouping, entropy-change control, or difficulty-aware advantage estimation. These methods selectively strengthen reliable reasoning signals while controlling uncertain updates with advantage reweight.

2.3 Clip Mechanism – clip(·)

The clipping mechanism constrains update magnitude based on $r_{i,t}(\theta)$, creating an approximate trust region that prevents destabilizing large updates on individual tokens. The lower and upper bounds respectively restrict updates that decrease or increase token probabilities, selectively damping gradients and influencing policy entropy. Building on this idea, existing methods can be broadly categorized by control granularity and objectives into two types: **(1) Range-level clip modulation**: directly adjusting the global clipping interval to globally relax or tighten the update range. **(2) Token-level clip modulation**: performing fine-grained control at the token level, assigning different effective clipping behaviors to different types of tokens, or restoring/recalibrating the gradients of tokens.

2.3.1 Range-level Clip Modulation

Range-level methods directly adjust the clipping interval to globally relax or tighten policy updates, thereby influencing exploration and entropy dynamics. DAPO (Yu et al., 2025) observes that positive samples with low old probabilities often correspond to new reasoning branches or reflections, but are easily clipped by the upper bound, which may suppress exploration and accelerate entropy collapse. It therefore raises the clip upper bound by a constant. Similarly, DLER (Liu et al., 2025e) shows that tokens clipped by the upper bound are often high-entropy tokens worth learning, and thus adopts a larger upper clipping threshold. EAG-RL (Fang et al., 2025) further makes this adjustment entropy-adaptive, assigning larger

upper bounds to high-entropy trajectories.

Other methods redesign the clipping range from the perspective of stability. Park *et al.* (Park et al., 2025) remove the upper bound and raise the lower bound to make error correction less aggressive. BAPO (Xi et al., 2025) considers the effect of off-policy training and dynamically widens the clipping interval by increasing the upper bound and decreasing the lower bound, reducing excessive clipping as training proceeds. DISPO (Karaman et al., 2026) decouples up- and down-clipping for correct and incorrect responses, yielding multiple controllable update regimes to balance exploration and distillation. FEC (Chen et al., 2026) analyzes how different importance-ratio regions contribute to entropy increase or decrease, and dynamically adjusts clipping thresholds to achieve flexible entropy control.

2.3.2 Token-level Clip Modulation

Token-level methods redesign clipping behavior for individual tokens or token groups, preserving useful entropy while avoiding unstable probability shifts. Archer (Wang et al., 2025d) assigns wider clipping bounds to high-entropy reasoning tokens and tighter bounds to low-entropy knowledge tokens, while DCPO (Yang et al., 2025b) adapts the clipping range according to each token's old probability, giving low-probability tokens wider upper bounds. BandPO (Li et al., 2026c) similarly introduces probability-aware bounds that bridge trust-region constraints and ratio clipping, allowing more flexible updates for low-probability actions. ASPO (Wang et al., 2025c) further flips the importance ratio for positive-advantage tokens and pairs it with reversed clipping, favoring correct but currently low-probability tokens. ESPO (Sheng et al., 2025) recomputes ratios over subsequences and assigns wider clipping ranges to high-entropy segments, redistributing updates toward exploratory parts of the trajectory. SSPO (Jiao et al., 2026) replaces hard clipping with soft sequence-level gating, smoothing the effect of clipped ratios instead of abruptly truncating gradients. ERC (Su et al., 2025b) introduces an additional entropy ratio as a soft clipping constraint to prevent excessive entropy shifts, and Clip-Cov (Cui et al., 2025) clips gradients only for high-covariance tokens where large advantages align with high probabilities.

Another line of methods focuses on restoring or recalibrating gradients for clipped tokens, since completely discarding them may accumu-

late bias and accelerate entropy reduction. CE-GPPO (Su et al., 2025a) reactivates clipped tokens with reduced learning weights, whereas AEPO-Dong (Dong et al., 2025a) restores gradients only for tokens exceeding the upper clipping bound. M2PO (Zheng et al., 2025a) controls extreme high-entropy outliers under off-policy training, preserving informative high-entropy tokens while bounding the second moment of importance weights.

2.4 KL Penalty – $\beta D_{\mathrm{KL}}(\pi_\theta \| \pi_{\mathbf{ref}})$

The KL penalty constrains the learned policy π_θ from drifting too far from a reference policy π_{ref}, with its strength controlled by β. As a reference-based trust region, it stabilizes policy updates and preserves prior capabilities, but may also restrict exploration and indirectly affect policy entropy. Recent studies therefore revisit this knob by removing KL regularization, adapting its strength, or reshaping the region where exploration is encouraged.

A common strategy is to remove the KL term by setting $\beta = 0$, motivated by the concern that fixed KL constraints may over-restrict policy divergence and accelerate entropy collapse, especially in long-chain reasoning or multi-turn tasks. Representative examples include Open-Reasoner-Zero (Hu et al., 2025) and DAPO (Yu et al., 2025) for single-turn reasoning, as well as AceReason-Nemetron (Chen et al., 2025d) and MT-GRPO (Zeng et al., 2025b) for multi-round settings. KL-Cov (Cui et al., 2025) takes a selective approach by applying KL penalties to high-covariance tokens, suppressing over-amplified confident tokens while preserving useful updates elsewhere.

Other methods retain KL regularization but adapt its strength. Archer (Wang et al., 2025d) and Cao *et al.* (Cao et al., 2025a) weaken KL on high-entropy tokens to encourage exploration and strengthen it on low-entropy tokens to preserve core capabilities. APO (Hong et al., 2025) modulates KL by sample difficulty, relaxing constraints for hard problems while tightening them for easy ones. ProRL (Liu et al., 2025d) periodically updates the reference policy with recent online snapshots, recalibrating the KL constraint during long-term RL. Beyond coefficient adjustment, TRE (Huang et al., 2026) encourages exploration within a local trust region of plausible tokens, maximizing entropy only over top-K or nucleus-filtered candidates to avoid probability leakage into long-tail tokens.

2.5 Optimization Objective – $\mathcal{J}_{\mathrm{PPO/GRPO}}(\theta)$

The optimization objective fundamentally determines the update direction of RL. In LRMs, it governs how the output-token distribution evolves, steering the model toward behaviors aligned with the specified objective. Recent work revisits the PPO/GRPO objective through entropy-aware designs, which can be broadly grouped into two families: **(1) Entropy-Based Optimization Objective**, which allows the model to directly learn an additional entropy-based objective besides the original optimization objective. **(2) Entropy-Guided Loss Reweighting**, which recalculates or reweights the optimization objective to control the update directions applied to different tokens.

2.5.1 Entropy-Based Optimization Objective

A straightforward way to extend the PPO/GRPO objective is to introduce entropy-related terms directly into the optimization objective, so that the model learns from both task rewards and explicit entropy signals. EVOL-RL (Zhou et al., 2025) follows this idea by adding a negative policy-entropy term, helping maintain response diversity under label-free, majority-vote reward settings and preventing rapid entropy collapse. Subsequent studies refine this strategy by assigning heterogeneous entropy weights across samples, tokens, or reasoning stages. For instance, AER (Zhang et al., 2025d) introduces a sample-level entropy-coefficient loss, allocating larger entropy weights to hard samples while reducing unnecessary entropy pressure on easy samples.

At a finer granularity, AEnt (Shen, 2025) controls token-level truncated entropy over a high-probability token set, avoiding distortions from enforcing high entropy over implausible long-tail tokens. Its adaptive coefficient maintains diversity only within plausible candidate tokens. AEPO-He (He et al., 2025a) applies adaptive entropy control across reasoning stages, enforcing higher entropy during the Reflection phase to mitigate repetitive or mechanical reasoning patterns. EPO (Xu et al., 2025c) takes a round-level perspective in agentic RL, anchoring each round's entropy to a historical running average to prevent late-stage policy collapse and excessive entropy fluctuations.

Recent methods also revisit the objective from broader distributional or multi-mode perspectives. Distribution-Centric Policy Optimization (DCPO) (Li et al., 2026d) formulates policy optimization around distribution-level control, aiming

to better balance exploration and exploitation. Policy Split (Yao et al., 2026b) introduces dual-mode entropy regularization, separating exploitation-oriented updates from exploration-oriented high-entropy updates to preserve stable reasoning while maintaining exploratory capacity.

Some approaches depart more radically from standard PPO/GRPO by rewriting the objective in terms of entropy or reward-induced distributions. One-shot Entropy Minimization (Gao et al., 2025) improves reasoning by minimizing conditional entropy on a small set of samples, while FlowRL (Zhu et al., 2025) adopts a GFlowNet-style MSE objective to match the reward-induced distribution, encouraging both high reward and high policy entropy. Overall, these methods treat entropy as an explicit optimization target for shaping exploration, stability, and reasoning diversity.

2.5.2 Entropy-Guided Loss Reweighting

Entropy-guided loss reweighting controls entropy dynamics by changing which tokens, steps, or trajectories dominate policy-gradient updates, without explicitly modifying the PPO/GRPO objective. One line of work introduces entropy-based masking or selective gradient allocation to focus learning on critical positions. Wang *et al.* (Wang et al., 2025f) split tokens by local entropy and retain only high-entropy forking tokens for GRPO updates. DART-GUI (Li et al., 2025a) extends this idea to multi-round agentic settings by aggregating token entropy into step-level entropy and optimizing only high-entropy decision steps. D^3S (Wang et al., 2025a) scores tokens by the product of advantage and entropy, selecting top-K tokens across samples for gradient computation. UloRL (Du et al., 2025) incorporates global entropy trends by activating masking for high-confidence tokens in correctly solved samples when the policy entropy falls below a preset threshold. EG-SPO (Hu et al., 2026) further generalizes selective updating through entropy-gated gradient allocation, applying stronger PPO updates to high-entropy tokens while attenuating updates on low-entropy ones.

Other methods preserve most tokens but softly reweight their learning signals to regulate the entropy trajectory. Prog-Adv-Reweight (Jin et al., 2025) observes that positive-advantage updates tend to concentrate probability mass and accelerate entropy decay, and therefore temporarily downweights such updates before gradually restoring their influence. SimKO (Peng et al., 2025)

first selects high-entropy tokens and then applies top-K smoothing to distribute positive-advantage signals across plausible candidates; for incorrect samples, it additionally penalizes the most confident wrong token to avoid consolidating erroneous modes. Clip-Cov (Cui et al., 2025) and STEER (Hao et al., 2025) both estimate each token's contribution to entropy change, suppressing updates that may cause excessive entropy shifts. EntroPIC (Yang et al., 2025a) formulates entropy stabilization as a feedback-control problem, dynamically adjusting loss coefficients for positive- and negative-advantage terms. Beyond token-level reweighting, UEC-RL (Wang et al., 2026) performs targeted exploration through selective trajectory retention and replay, while Entrocraft (Li et al., 2026a) reshapes the effective advantage distribution via rejection sampling to follow a desired entropy curve.

3 Entropy Mechanisms in LRM Inference

An increasing number of studies (Nikitin et al., 2024; Agrawal et al., 2024; Jiang et al., 2025) have identified pronounced overthinking phenomena in LLM generation. Recently, entropy has been introduced into inference mechanisms to both evaluate (Xu and Lu, 2025; Liu et al., 2025f; Nikitin et al., 2024) and regulate (Sharma and Chopra, 2025b; Li et al., 2025c) inference behavior. These explorations reveal a clear trend: **Entropy is evolving from a passive representation of uncertainty into an active control signal for inference**.

Compared with general LLMs, LRMs exhibit stronger dependencies along reasoning chains and denser branching in path selection, which amplifies computational overhead and error accumulation when inference is not properly controlled. Accordingly, this section focuses on LRM inference and organizes existing work into two core directions: (i) **Entropy-guided inference**, which monitors entropy dynamics to decide when to continue, pause, branch, or trigger correction, thereby reducing redundant computation and improving efficiency; (ii) **Self-consistency enhancement**, which uses entropy to evaluate candidate answers or reasoning paths and select more reliable outputs.

3.1 Entropy-Guided Inference

Entropy-guided inference monitors entropy changes in real time to determine how inference should proceed, with branching control being a

key factor for inference performance. DTS (Xu et al., 2025e) models token generation as a tree and uses next-token entropy to decide when to expand branches. EAGER (Scalena et al., 2025) monitors top-K entropy at each step to trigger branching adaptively. ARTS (Hong et al., 2026) further decouples proposal and decision in reasoning tree search, using verifier-guided decisions to navigate sparse, high-entropy search spaces and preserve rare but valid reasoning paths. Meanwhile, entropy is also used as a criterion for early stopping or regeneration. EAT (Wang et al., 2025g) monitors token-level entropy changes to determine when to stop. SEAT (Xu et al., 2025d) defines semantic entropy over clustered parallel responses and uses it to decide whether another inference round is needed. EGL (Correa and de Matos, 2025) computes entropy after the draft pass and generates an uncertainty report to guide adaptive refinement when entropy exceeds a threshold.

3.2 Self-Consistency Enhancement

Self-consistency enhancement uses entropy to assess the credibility of candidate answers or reasoning paths, obtaining more robust outputs through entropy-aware filtering or weighting. SCRL (Yan et al., 2026) questions the reliability of consensus itself and introduces entropy-gated negative pseudo-labeling to filter unreliable trajectories when majority consensus is weak or misleading. DualResearch (Shi et al., 2025) treats two inference graphs as posterior answer distributions and uses their Shannon entropy as weighting factors for answer aggregation. IEW (Sharma and Chopra, 2025a) extends this idea to the full inference chain by aggregating multiple paths with inverse-entropy weighting, assigning higher weights to more stable, lower-entropy paths. STaR (Zhang et al., 2025a) quantifies uncertainty along the inference chain based on token-level entropy, enabling the selection of the most reliable reasoning path.

4 Challenge and Future Directions

This survey reviews entropy-related methods for RL training and TTS inference in the LRM era, discussing current limitations and future directions. Notably, all surveyed methods emerged within sixteen months after GRPO, reflecting the rapid advancement of LLMs into the reasoning era. As entropy remains a fundamental challenge, it will continue to drive the research of LRMs. Additionally,

Appendix A.8 provides a comprehensive overview of method settings and performance, while Appendix A.9 briefly covers entropy-related issues in earlier pretraining and SFT methods.

Challenge: Entropy to Performance. It is important to emphasize that entropy control is a means, not an end. The goal is to preserve diversity while improving the accuracy of exploration. Although many methods show empirical gains by adjusting entropy, results vary across settings, indicating that the relationship is not a simple trade-off. A central challenge is to deepen our understanding of this link and make entropy-driven improvements more consistently transfer to performance.

Challenge: Intrinsic Relations Between Parameters. Most existing methods focus on adjusting one algorithmic parameter or a small set of parameters, but lack coordination across approaches. There is still a shortage of methods that adopt a global, fine-grained perspective for tuning LRM training and inference. Developing such frameworks would enable a more systematic analysis of how entropy influences learning dynamics and performance.

Future: Entropy in Agentic Models. The deep integration of agentic multi-turn tool calls and reasoning capabilities has greatly enhanced the model's ability to tackle complex problems. This approach is seen as a crucial breakthrough in moving beyond single-turn problem-solving. In the context of agentic tasks, new entropy-related issues arise, particularly in multi-turn tool calls, reasoning, and environmental interaction. Research on dynamically monitoring and controlling policy entropy in such tasks is crucial to avoid instability in training or inference caused by continuous high-entropy decisions or excessive branching. Solving these issues will enable agentic RL to not only "effectively explore" but also "robustly exploit and consolidate".

Future: Entropy in Parallel Thinking. Parallel thinking refers to having the model generate multiple reasoning paths in parallel and then aggregate or synthesize them into a final answer. This offers a simple and efficient way to convert pass@k potential into pass@1 performance. However, it may also amplify current LLM weaknesses in reasoning robustness and stability. By leveraging entropy to monitor the credibility and diversity of these parallel paths, we can filter for high-quality candidates and provide more reliable signals for path fusion. This could help reduce risks such as hallucinations, logical conflicts, and inconsistencies, thereby further improving overall performance.

Limitations

This survey is limited to the LRM era and primarily focuses on entropy-related methods in RL training and inference. Entropy issues in earlier stages of the broader LLM pipeline, such as pretraining and SFT, are only briefly covered in the appendix. Our taxonomy and narrative synthesis necessarily involve subjective choices, which are significant but largely unavoidable in a fast-evolving research landscape. In addition, due to heterogeneous experimental settings across studies (*e.g.*, base models, training data, and hyperparameters), we avoid direct head-to-head comparisons. As a result, some of our observations should be interpreted as descriptive trends rather than definitive conclusions. Finally, given the rapid progress of this field, the coverage and conclusions of this survey may need to be updated as new results emerge, while we try to continue updating new papers on our repository.

References

Shivam Agarwal, Zimin Zhang, Lifan Yuan, Jiawei Han, and Hao Peng. 2025. The unreasonable effectiveness of entropy minimization in llm reasoning. *arXiv preprint arXiv:2505.15134*.

Sudhanshu Agrawal, Wonseok Jeon, and Mingu Lee. 2024. Adaedl: Early draft stopping for speculative decoding of large language models via an entropy-based lower bound on token acceptance probability. In *NeurIPS Efficient Natural Language and Speech Processing Workshop*, pages 355–369. PMLR.

Mohammad Ali Alomrani, Yingxue Zhang, Derek Li, Qianyi Sun, Soumyasundar Pal, Zhanguang Zhang, Yaochen Hu, Rohan Deepak Ajwani, Antonios Valkanas, Raika Karimi, and 1 others. 2025. Reasoning on a budget: A survey of adaptive and controllable test-time compute in llms. *arXiv preprint arXiv:2507.02076*.

Jean-Yves Audibert, Rémi Munos, and Csaba Szepesvári. 2009. Exploration–exploitation tradeoff using variance estimates in multi-armed bandits. *Theoretical Computer Science*, 410(19):1876–1902.

Ruichu Cai, Haopeng Du, Qingwen Lin, Yutong Chen, Zijian Li, and Boyan Xu. 2026. Entra: Entropy-based redundancy avoidance in large language model reasoning. *arXiv preprint arXiv:2601.07123*.

Hongye Cao, Zhixin Bai, Ziyue Peng, Boyan Wang, Tianpei Yang, Jing Huo, Yuyao Zhang, and Yang Gao. 2025a. Efficient reinforcement learning with semantic and token entropy for llm reasoning. *arXiv preprint arXiv:2512.04359*.

Yilin Cao, Ruike Zhang, Penghui Wei, Qingchao Kong, and Wenji Mao. 2025b. Perspective-driven preference optimization with entropy maximization for diverse argument generation. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 22479–22496.

Haw-Shiuan Chang, Nanyun Peng, Mohit Bansal, Anil Ramakrishna, and Tagyoung Chung. 2024. Real sampling: Boosting factuality and diversity of open-ended generation via asymptotic entropy. *arXiv preprint arXiv:2406.07735*.

Guanxu Chen, Yafu Li, Yuxian Jiang, Chen Qian, Qihan Ren, Jingyi Yang, Yu Cheng, Dongrui Liu, and Jing Shao. 2025a. Conditional advantage estimation for reinforcement learning in large reasoning models. *arXiv preprint arXiv:2509.23962*.

Kun Chen, Peng Shi, Fanfan Liu, Haibo Qiu, Zhixiong Zeng, Siqi Yang, and Wenji Mao. 2026. Flexible entropy control in rlvr with gradient-preserving perspective. *arXiv preprint arXiv:2602.09782*.

Minghan Chen, Guikun Chen, Wenguan Wang, and Yi Yang. 2025b. Seed-grpo: Semantic entropy enhanced grpo for uncertainty-aware policy optimization. *arXiv preprint arXiv:2505.12346*.

Shiqi Chen, Miao Xiong, Junteng Liu, Zhengxuan Wu, Teng Xiao, Siyang Gao, and Junxian He. 2024a. In-context sharpness as alerts: An inner representation perspective for hallucination mitigation. In *International Conference on Machine Learning*, pages 7553–7567. PMLR.

Xinzhu Chen, Xuesheng Li, Zhongxiang Sun, and Weijie Yu. 2025c. Beyond high-entropy exploration: Correctness-aware low-entropy segment-based advantage shaping for reasoning llms. *arXiv preprint arXiv:2512.00908*.

Yang Chen, Zhuolin Yang, Zihan Liu, Chankyu Lee, Peng Xu, Mohammad Shoeybi, Bryan Catanzaro, and Wei Ping. 2025d. Acereason-nemotron: Advancing math and code reasoning through reinforcement learning. *arXiv preprint arXiv:2505.16400*.

Zhe Chen, Weiyun Wang, Yue Cao, Yangzhou Liu, Zhangwei Gao, Erfei Cui, Jinguo Zhu, Shenglong Ye, Hao Tian, Zhaoyang Liu, and 1 others. 2024b. Expanding performance boundaries of open-source multimodal models with model, data, and test-time scaling. *arXiv preprint arXiv:2412.05271*.

Daixuan Cheng, Shaohan Huang, Xuekai Zhu, Bo Dai, Wayne Xin Zhao, Zhenliang Zhang, and Furu Wei. 2025. Reasoning with exploration: An entropy perspective. *arXiv preprint arXiv:2506.14758*.

Yunseon Choi, Sangmin Bae, Seonghyun Ban, Minchan Jeong, Chuheng Zhang, Lei Song, Li Zhao, Jiang Bian, and Kee-Eung Kim. 2024. Hard prompts made interpretable: Sparse entropy regularization for prompt tuning with rl. In *62nd Annual Meeting of the Association for Computational Linguistics, ACL*

2024, pages 8252–8271. Association for Computational Linguistics (ACL).

Andrew GA Correa and Ana CH de Matos. 2025. Entropy-guided loop: Achieving reasoning through uncertainty-aware generation. *arXiv preprint arXiv:2509.00079*.

Ganqu Cui, Yuchen Zhang, Jiacheng Chen, Lifan Yuan, Zhi Wang, and 1 others. 2025. The entropy mechanism of reinforcement learning for reasoning language models. *arXiv preprint arXiv:2505.22617*.

Jia Deng, Jie Chen, Zhipeng Chen, Wayne Xin Zhao, and Ji-Rong Wen. 2025. Decomposing the entropy-performance exchange: The missing keys to unlocking effective reinforcement learning. *arXiv preprint arXiv:2508.02260*.

Guanting Dong, Licheng Bao, Zhongyuan Wang, Kangzhi Zhao, Xiaoxi Li, Jiajie Jin, Jinghan Yang, Hangyu Mao, Fuzheng Zhang, Kun Gai, and 1 others. 2025a. Agentic entropy-balanced policy optimization. *arXiv preprint arXiv:2510.14545*.

Guanting Dong, Hangyu Mao, Kai Ma, Licheng Bao, Yifei Chen, Zhongyuan Wang, Zhongxia Chen, Jiazhen Du, Huiyang Wang, Fuzheng Zhang, and 1 others. 2025b. Agentic reinforced policy optimization. *arXiv preprint arXiv:2507.19849*.

Dong Du, Shulin Liu, Tao Yang, Shaohua Chen, and Yang Li. 2025. Ulorl: An ultra-long output reinforcement learning approach for advancing large language models' reasoning abilities. *arXiv preprint arXiv:2507.19766*.

Yue Fang, Yuxin Guo, Jiaran Gao, Hongxin Ding, Xinke Jiang, Weibin Liao, Yongxin Xu, Yinghao Zhu, Zhibang Yang, Liantao Ma, and 1 others. 2025. Toward better ehr reasoning in llms: Reinforcement learning with expert attention guidance. *arXiv preprint arXiv:2508.13579*.

Sebastian Farquhar, Jannik Kossen, Lorenz Kuhn, and Yarin Gal. 2024. Detecting hallucinations in large language models using semantic entropy. *Nature*, 630(8017):625–630.

Zitian Gao, Lynx Chen, Haoming Luo, Joey Zhou, and Bryan Dai. 2025. One-shot entropy minimization. *arXiv preprint arXiv:2505.20282*.

Andrey Goncharov, Daniil Vyazhev, Petr Sychev, Edvard Khalafyan, and Alexey Zaytsev. 2025. Complexity-aware fine-tuning. *arXiv preprint arXiv:2506.21220*.

Hengrui Gu, Xiaotian Han, Yujing Bian, Feiyi Wang, and Kaixiong Zhou. 2026. Asymmetric advantage modulation calibrates entropy dynamics in rlvr. *arXiv preprint arXiv:2604.04894*.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025.

Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Zhezheng Hao, Hong Wang, Haoyang Liu, Jian Luo, Jiarui Yu, and 1 others. 2025. Rethinking entropy interventions in rlvr: An entropy change perspective. *arXiv preprint arXiv:2510.10150*.

Chen He, Xun Jiang, Lei Wang, Hao Yang, Chong Peng, Peng Yan, Fumin Shen, and Xing Xu. 2025a. What makes reasoning invalid: Echo reflection mitigation for large language models. *arXiv preprint arXiv:2511.06380*.

Yongquan He, Wenyuan Zhang, Xuancheng Huang, Peng Zhang, Lingxun Meng, Xiang Zhou, Ke Zeng, and Xunliang Cai. 2025b. Don't half-listen: Capturing key-part information in continual instruction tuning. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 23649–23668, Vienna, Austria. Association for Computational Linguistics.

Yuhang He, Haodong Wu, Siyi Liu, Hongyu Ge, Hange Zhou, Keyi Wu, Zhuo Zheng, Qihong Lin, Zixin Zhong, and Yongqi Zhang. 2026. Rethinking token-level credit assignment in rlvr: A polarity-entropy analysis. *arXiv preprint arXiv:2604.11056*.

Minjie Hong, Zirun Guo, Yan Xia, Zehan Wang, Ziang Zhang, Tao Jin, and Zhou Zhao. 2025. Apo: Enhancing reasoning ability of mllms via asymmetric policy optimization. *arXiv preprint arXiv:2506.21655*.

Zesheng Hong, Jiadong Yu, and Hui Pan. 2026. Amortized reasoning tree search: Decoupling proposal and decision in large language models. *arXiv preprint arXiv:2602.12846*.

Zhenyu Hou, Ziniu Hu, Yujiang Li, Rui Lu, Jie Tang, and Yuxiao Dong. 2025. Treerl: Llm reinforcement learning with on-policy tree search. *arXiv preprint arXiv:2506.11902*.

Jingcheng Hu, Yinmin Zhang, Qi Han, Daxin Jiang, Xiangyu Zhang, and Heung-Yeung Shum. 2025. Openreasoner-zero: An open source approach to scaling up reinforcement learning on the base model. *arXiv preprint arXiv:2503.24290*.

Yuelin Hu, Zhengxue Cheng, Wei Liu, and Li Song. 2026. Entropy-gated selective policy optimization: Token-level gradient allocation for hybrid training of large language models. *arXiv preprint arXiv:2602.03309*.

Chao Huang, Yujing Lu, Quangang Li, Shenghe Wang, Yan Wang, Yueyang Zhang, Long Xia, Jiashu Zhao, Zhiyuan Sun, Daiting Shi, and Tingwen Liu. 2026. Tre: Encouraging exploration in the trust region. *arXiv preprint arXiv:2602.03635*.

Chen Huang, Wei Lu, and Wenxuan Zhang. 2025a. Pear: Phase entropy aware reward for efficient reasoning. *arXiv preprint arXiv:2510.08026*.

Guanhua Huang, Tingqiang Xu, Mingze Wang, Qi Yi, Xue Gong, and 1 others. 2025b. Low-probability tokens sustain exploration in reinforcement learning with verifiable reward. *arXiv preprint arXiv:2510.03222*.

Jerry Huang, Peng Lu, and Qiuhao Zeng. 2025c. Calibrated language models and how to find them with label smoothing. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 25593–25612. PMLR.

Shuyang Jiang, Yusheng Liao, Ya Zhang, Yanfeng Wang, and Yu Wang. 2025. Overthinking reduction with decoupled rewards and curriculum data scheduling. *arXiv preprint arXiv:2509.25827*.

Zhengbo Jiao, Shaobo Wang, Zifan Zhang, Wei Wang, Bing Zhao, Hu Wei, and Linfeng Zhang. 2026. Credit where it is due: Cross-modality connectivity drives precise reinforcement learning for mllm reasoning. *arXiv preprint arXiv:2602.11455*.

Renren Jin, Pengzhi Gao, Yuqi Ren, Zhuowen Han, Tongxuan Zhang, and 1 others. 2025. Revisiting entropy in reinforcement learning for large reasoning models. *arXiv preprint arXiv:2511.05993*.

Batuhan K. Karaman, Aditya Rawal, Suhaila Shakiah, Mohammad Ghavamzadeh, Mingyi Hong, Arijit Biswas, and Ruida Zhou. 2026. Dispo: Enhancing training efficiency and stability in reinforcement learning for large language model mathematical reasoning. *arXiv preprint arXiv:2602.00983*.

Gautam Siddharth Kashyap, Mark Dras, and Usman Naseem. 2025. Too helpful, too harmless, too honest or just right? In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 29711–29722.

Aya Kayal, Eduardo Pignatelli, and Laura Toni. 2025. The impact of intrinsic rewards on exploration in reinforcement learning. *Neural Computing and Applications*, pages 1–35.

Jiyeon Kim, Hyunji Lee, Hyowon Cho, Joel Jang, Hyeonbin Hwang, Seungpil Won, Youbin Ahn, Dohaeng Lee, and Minjoon Seo. 2024. Knowledge entropy decay during language model pretraining hinders new knowledge acquisition. *ArXiv*, abs/2410.01380.

Kimi Team. 2025. Kimi k2: Open agentic intelligence. *Preprint*, arXiv:2507.20534.

Thanh-Long V. Le, Myeongho Jeon, Kim Vu, Viet Lai, and Eunho Yang. 2025. No prompt left behind: Exploiting zero-variance prompts in llm reinforcement learning via entropy-guided advantage shaping. *arXiv preprint arXiv:2509.21880*.

Bolian Li, Yifan Wang, Yi Ding, Anamika Lochab, Ananth Grama, and Ruqi Zhang. 2026a. Addressing performance saturation for llm rl via precise entropy curve control. *arXiv preprint arXiv:2604.26326*.

Pengxiang Li, Zechen Hu, Zirui Shang, Jingrong Wu, Yang Liu, Hui Liu, Zhi Gao, Chenrui Shi, Bofei Zhang, Zihao Zhang, Xiaochuan Shi, Zedong Yu, Yuwei Wu, Xinxiao Wu, Yunde Jia, Liuyu Xiang, Zhaofeng He, and Qing Li. 2025a. Efficient multi-turn rl for gui agents via decoupled training and adaptive data curation. *arXiv preprint arXiv:2509.23866*.

Pengyi Li, Elizaveta Goncharova, Andrey Kuznetsov, and Ivan Oseledets. 2026b. Back to basics: Revisiting exploration in reinforcement learning for llm reasoning via generative probabilities. *arXiv preprint arXiv:2602.05281*.

Qingbin Li, Rongkun Xue, Jie Wang, Ming Zhou, Zhi Li, Xiaofeng Ji, Yongqi Wang, Miao Liu, Zheming Yang, Minghui Qiu, and 1 others. 2025b. Cure: Critical-token-guided re-concatenation for entropy-collapse prevention. *arXiv preprint arXiv:2508.11016*.

Xianzhi Li, Ethan Callanan, Abdellah Ghassel, and Xiaodan Zhu. 2025c. Entropy-gated branching for efficient test-time reasoning. *Preprint*, arXiv:2503.21961.

Yuan Li, Bo Wang, Yufei Gao, Yuqian Yao, Xinyuan Wang, Zhangyue Yin, and Xipeng Qiu. 2026c. Bandpo: Bridging trust regions and ratio clipping via probability-aware bounds for llm reinforcement learning. *arXiv preprint arXiv:2603.04918*.

Zhaochun Li, Chen Wang, Jionghao Bai, Shisheng Cui, Ge Lan, Zhou Zhao, and Yue Wang. 2026d. Distribution-centric policy optimization dominates exploration-exploitation trade-off. *arXiv preprint arXiv:2601.12730*.

Zhong-Zhi Li, Duzhen Zhang, Ming-Liang Zhang, Jiaxin Zhang, Zengyan Liu, Yuxuan Yao, Haotian Xu, Junhao Zheng, Pei-Jie Wang, Xiuyi Chen, Yingying Zhang, Fei Yin, Jiahua Dong, Zhiwei Li, Bao-long Bi, Ling-rui Mei, Jun-Feng Fang, Xiao Liang, Zhijiang Guo, and 2 others. 2025d. From system 1 to system 2: A survey of reasoning large language models. *arXiv preprint arXiv:2502.17419*.

Ziniu Li, Congliang Chen, Tian Xu, Zeyu Qin, Jiancong Xiao, Zhi-Quan Luo, and Ruoyu Sun. 2025e. Preserving diversity in supervised fine-tuning of large language models. In *ICLR*.

Chonghan Liu, Yimin Du, Qi An, Xin He, Cunqi Zhai, Fei Tan, Weijia Lin, Xiaochun Gong, Yongchao Deng, Shousheng Jia, and Xiangzheng Zhang. 2026. Vepo: Variable entropy policy optimization for low-resource language foundation models. *arXiv preprint arXiv:2603.19152*.

Jia Liu, ChangYi He, YingQiao Lin, MingMin Yang, FeiYang Shen, and ShaoGuo Liu. 2025a. Ettrl: Balancing exploration and exploitation in llm test-time reinforcement learning via entropy mechanism. *arXiv preprint arXiv:2508.11356*.

Keliang Liu, Dingkang Yang, Ziyun Qian, Weijie Yin, Yuchi Wang, Hongsheng Li, Jun Liu, Peng Zhai, Yang Liu, and Lihua Zhang. 2025b. Reinforcement learning meets large language models: A survey of advancements and applications across the llm lifecycle. *arXiv preprint arXiv:2509.16679*.

Keliang Liu, Dingkang Yang, Ziyun Qian, Weijie Yin, Yuchi Wang, Hongsheng Li, Jun Liu, Peng Zhai, Yang Liu, and Lihua Zhang. 2025c. Reinforcement learning meets large language models: A survey of advancements and applications across the llm lifecycle. *arXiv preprint arXiv:2509.16679*.

Mingjie Liu, Shizhe Diao, Ximing Lu, Jian Hu, Xin Dong, Yejin Choi, Jan Kautz, and Yi Dong. 2025d. Prorl: Prolonged reinforcement learning expands reasoning boundaries in large language models. *arXiv preprint arXiv:2505.24864*.

Shih-Yang Liu, Xin Dong, Ximing Lu, Shizhe Diao, Mingjie Liu, Min-Hung Chen, Hongxu Yin, Yu-Chiang Frank Wang, Kwang-Ting Cheng, Yejin Choi, Jan Kautz, and Pavlo Molchanov. 2025e. Dler: Doing length penalty right–incentivizing more intelligence per token via reinforcement learning. *arXiv preprint arXiv:2510.15110*.

Xiaoou Liu, Tiejin Chen, Longchao Da, Chacha Chen, Zhen Lin, and Hua Wei. 2025f. Uncertainty quantification and confidence calibration in large language models: A survey. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 2*, pages 6107–6117.

Lu Ma, Hao Liang, Meiyi Qiang, Lexiang Tang, Xiaochen Ma, Zhen Hao Wong, Junbo Niu, Chengyu Shen, Runming He, Yanhao Li, and 1 others. 2025. Learning what reinforcement learning can't: Interleaved online fine-tuning for hardest questions. *arXiv preprint arXiv:2506.07527*.

Yuchun Miao, Sen Zhang, Liang Ding, Yuqi Zhang, Lefei Zhang, and Dacheng Tao. 2025. The energy loss phenomenon in rlhf: A new perspective on mitigating reward hacking. *arXiv preprint arXiv:2501.19358*.

MiniMax-AI. 2025. Minimax-m2. GitHub repository. Accessed: 2025-12-03.

Jisoo Mok, Jaeyoung Do, Sungjin Lee, Tara Taghavi, Seunghak Yu, and Sungroh Yoon. 2023. Large-scale lifelong learning of in-context instructions and how to tackle it. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12573–12589, Toronto, Canada. Association for Computational Linguistics.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori B Hashimoto. 2025. s1: Simple test-time scaling. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 20286–20332.

Basil Mustafa, Carlos Riquelme, Joan Puigcerver, Rodolphe Jenatton, and Neil Houlsby. 2022. Multimodal contrastive learning with limoe: the language-image mixture of experts. *Advances in Neural Information Processing Systems*, 35:9564–9576.

Dang Nguyen, Ali Payani, and Baharan Mirzasoleiman. 2025. Beyond semantic entropy: Boosting llm uncertainty quantification with pairwise semantic similarity. *arXiv preprint arXiv:2506.00245*.

Alexander Nikitin, Jannik Kossen, Yarin Gal, and Pekka Marttinen. 2024. Kernel language entropy: Fine-grained uncertainty quantification for llms from semantic similarities. *Advances in Neural Information Processing Systems*, 37:8901–8929.

OpenAI. 2024. Openai o1 system card. *Preprint*, arXiv:2412.16720.

Qianjun Pan, Wenkai Ji, Yuyang Ding, Junsong Li, Shilian Chen, Junyi Wang, Jie Zhou, Qin Chen, Min Zhang, Yulan Wu, and 1 others. 2026. A survey of slow thinking-based reasoning llms using reinforcement learning and test-time scaling law. *Information Processing & Management*, 63(2):104394.

Jaesung R Park, Junsu Kim, Gyeongman Kim, Jinyoung Jo, Sean Choi, Jaewoong Cho, and Ernest K Ryu. 2025. Clip-low increases entropy and clip-high decreases entropy in reinforcement learning of large language models. *arXiv preprint arXiv:2509.26114*.

Ruotian Peng, Yi Ren, Zhouliang Yu, Weiyang Liu, and Yandong Wen. 2025. Simko: Simple pass@k policy optimization. *arXiv preprint arXiv:2510.14807*.

Yulei Qin, Xiaoyu Tan, Zhengbao He, Gang Li, Haojia Lin, Zongyi Li, Zihan Xu, Yuchen Shi, Siqi Cai, Renting Rui, Shaofei Cai, Yuzheng Cai, Xuan Zhang, Sheng Ye, Ke Li, and Xing Sun. 2025. Learn the ropes, then trust the wins: self-imitation with progressive exploration for agentic reinforcement learning. *arXiv preprint arXiv:2509.22601*.

Yuxiao Qu, Amrith Setlur, Virginia Smith, Ruslan Salakhutdinov, and Aviral Kumar. 2026. Pope: Learning to reason on hard problems via privileged on-policy exploration. *arXiv preprint arXiv:2601.18779*.

Shaohao Rui, Kaitao Chen, Weijie Ma, and Xiaosong Wang. 2025. Adathink-med: Medical adaptive thinking with uncertainty-guided length calibration. *arXiv preprint arXiv:2509.24560*.

Daniel Scalena, Leonidas Zotos, Elisabetta Fersini, Malvina Nissim, and Ahmet Üstün. 2025. Eager: Entropy-aware generation for adaptive inference-time scaling. *arXiv preprint arXiv:2510.11170*.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Aman Sharma and Paras Chopra. 2025a. The sequential edge: Inverse-entropy voting beats parallel self-consistency at matched compute. *arXiv preprint arXiv:2511.02309*.

Aman Sharma and Paras Chopra. 2025b. Think just enough: Sequence-level entropy as a confidence signal for llm reasoning. *arXiv preprint arXiv:2510.08146*.

Han Shen. 2025. On entropy control in llm-rl algorithms. *arXiv preprint arXiv:2509.03493*.

Yuepeng Sheng, Yuwei Huang, Shuman Liu, Haibo Zhang, and Anxiang Zeng. 2025. Espo: Entropy importance sampling policy optimization. *arXiv preprint arXiv:2512.00499*.

Jinxin Shi, Zongsheng Cao, Runmin Ma, Yusong Hu, Jie Zhou, Xin Li, Lei Bai, Liang He, and Bo Zhang. 2025. Dualresearch: Entropy-gated dual-graph retrieval for answer reconstruction. *arXiv preprint arXiv:2510.08959*.

Ola Shorinwa, Zhiting Mei, Justin Lidard, Allen Z Ren, and Anirudha Majumdar. 2025. A survey on uncertainty quantification of large language models: Taxonomy, open research challenges, and future directions. *ACM Computing Surveys*.

Felix Stahlberg and Shankar Kumar. 2025. The role of outgoing connection heterogeneity in feedforward layers of large language models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 22487–22495, Suzhou, China. Association for Computational Linguistics.

Alessandro Stolfo, Wes Gurnee, Ben Wu, Yonatan Belinkov, Xingyi Song, Mrinmaya Sachan, and Neel Nanda. 2024. Confidence regulation neurons in language models. In *Proceedings of the 38th International Conference on Neural Information Processing Systems*, pages 125019–125049.

Zhenpeng Su, Leiyu Pan, Minxuan Lv, Yuntao Li, Wenping Hu, Fuzheng Zhang, Kun Gai, and Guorui Zhou. 2025a. Ce-gppo: Controlling entropy via gradient-preserving clipping policy optimization in reinforcement learning.

Zhenpeng Su, Leiyu Pan, Minxuan Lv, Tiehua Mei, Zijia Lin, Yuntao Li, Wenping Hu, Ruiming Tang, Kun Gai, and Guorui Zhou. 2025b. Entropy ratio clipping as a soft global constraint for stable reinforcement learning. *arXiv preprint arXiv:2512.05591*.

Heejae Suh, Yejin Jeon, Deokhyung Kang, Taehee Park, Yejin Min, and Gary Lee. 2025. Enstom: Enhancing dialogue systems with entropy-scaled steering vectors for topic maintenance. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 24615–24631.

Hongze Tan, Jianfei Pan, Jinghao Lin, Tao Chen, Zhihang Zheng, Zhihao Tang, and Haihua Yang. 2025. Gtpo and grpo-s: Token and sequence-level reward shaping with policy entropy. *arXiv preprint arXiv:2508.04349*.

Benedict Aaron Tjandra, Muhammed Razzak, Jannik Kossen, Kunal Handa, and Yarin Gal. 2024. Fine-tuning large language models to appropriately abstain with semantic entropy. In *Neurips Safe Generative AI Workshop 2024*.

Zhongwei Wan, Hui Shen, Xin Wang, Che Liu, Zheda Mai, and Mi Zhang. 2025a. Meda: Dynamic kv cache allocation for efficient multimodal long-context inference. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 2485–2497.

Zifu Wan, Ce Zhang, Silong Yong, Martin Q Ma, Simon Stepputtis, Louis-Philippe Morency, Deva Ramanan, Katia Sycara, and Yaqi Xie. 2025b. Only: One-layer intervention sufficiently mitigates hallucinations in large vision-language models. *arXiv preprint arXiv:2507.00898*.

Chao Wang, Tao Yang, Hongtao Tian, Yunsheng Shi, Qiyao Ma, Xiaotao Liu, Ting Yao, and Wenbo Ding. 2025a. Learning more with less: A dynamic dual-level down-sampling framework for efficient policy optimization. *arXiv preprint arXiv:2509.22115*.

Chen Wang, Zhaochun Li, Jionghao Bai, Yuzhi Zhang, Shisheng Cui, Zhou Zhao, and Yue Wang. 2025b. Arbitrary entropy policy optimization: Entropy is controllable in reinforcement finetuning. *arXiv preprint arXiv:2510.08141*.

Chen Wang, Lai Wei, Yanzhi Zhang, Chenyang Shao, Zedong Dan, Weiran Huang, Ge Lan, and Yue Wang. 2026. Targeted exploration via unified entropy control for reinforcement learning. *arXiv preprint arXiv:2604.14646*.

Jiakang Wang, Runze Liu, Lei Lin, Wenping Hu, Xiu Li, Fuzheng Zhang, Guorui Zhou, and Kun Gai. 2025c. Aspo: Asymmetric importance sampling policy optimization. *arXiv preprint arXiv:2510.06062*.

Jiakang Wang, Runze Liu, Fuzheng Zhang, Xiu Li, and Guorui Zhou. 2025d. Stabilizing knowledge, promoting reasoning: Dual-token constraints for rlvr. *arXiv preprint arXiv:2507.15778*.

Jiawei Wang, Jiacai Liu, Yuqian Fu, Yingru Li, Xintao Wang, Yuan Lin, Yu Yue, Lin Zhang, Yang Wang, and Ke Wang. 2025e. Harnessing uncertainty:

Entropy-modulated policy gradients for long-horizon llm agents. *arXiv preprint arXiv:2509.09265*.

Shenzhi Wang, Le Yu, Chang Gao, Chujie Zheng, Shixuan Liu, Rui Lu, Kai Dang, Xionghui Chen, Jianxin Yang, Zhenru Zhang, and 1 others. 2025f. Beyond the 80/20 rule: High-entropy minority tokens drive effective reinforcement learning for llm reasoning. *arXiv preprint arXiv:2506.01939*.

Xi Wang, James McInerney, Lequn Wang, and Nathan Kallus. 2025g. Entropy after ⟨/Think⟩ for reasoning model early exiting. *Preprint*, arXiv:2509.26522.

Yizhou Wang, Lingzhi Zhang, Yue Bai, Mang Tik Chiu, Zhengmian Hu, Mingyuan Zhang, Qihua Dong, Yu Yin, Sohrab Amirghodsi, and Yun Fu. 2025h. Cautious next token prediction. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 25685–25697.

Canshi Wei. 2024. Enhancing fine-grained image classifications via cascaded vision language models. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 1857–1871.

Xin-Cheng Wen, Binbin Chen, Haoxuan Lan, Hang Yu, Peng Di, and Cuiyun Gao. 2026. Swe-fuse: Empowering software agents via issue-free trajectory learning and entropy-aware rlvr training. *arXiv preprint arXiv:2603.07927*.

Jiahao Wu, Ning Lu, Shengcai Liu, Kun Wang, Yanting Yang, Li Qing, and Ke Tang. 2026. Train at moving edge: Online-verified prompt selection for efficient rl training of large reasoning model. *arXiv preprint arXiv:2603.25184*.

Jialiang Wu, Yi Shen, Sijia Liu, Yi Tang, Sen Song, Xiaoyi Wang, and Longjun Cai. 2025a. Improve decoding factuality by token-wise cross layer entropy of large language models. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 3912–3921.

Junkang Wu, Kexin Huang, Jiancan Wu, An Zhang, Xiang Wang, and Xiangnan He. 2025b. Quantile advantage estimation for entropy-safe reasoning. *arXiv preprint arXiv:2509.22611*.

Zhiheng Xi, Xin Guo, Yang Nan, Enyu Zhou, Junrui Shen, Wenxiang Chen, Jiaqi Liu, Jixuan Huang, Zhihao Zhang, Honglin Guo, and 1 others. 2025. Bapo: Stabilizing off-policy reinforcement learning for llms via balanced policy optimization with adaptive clipping. *arXiv preprint arXiv:2510.18927*.

Can Xie, Ruotong Pan, Xiangyu Wu, Yunfei Zhang, Jiayi Fu, Tingting Gao, and Guorui Zhou. 2025. Unlocking exploration in rlvr: Uncertainty-aware advantage shaping for deeper reasoning. *arXiv preprint arXiv:2510.10649*.

Xuan Xiong, Huan Liu, Li Gu, Zhixiang Chi, Yue Qiu, Yuanhao Yu, and Yang Wang. 2026. Etr: Entropy trend reward for efficient chain-of-thought reasoning. *arXiv preprint arXiv:2604.05355*.

Beining Xu and Yongming Lu. 2025. Tecp: Token-entropy conformal prediction for llms. *Mathematics*, 13(20):3351.

Fengli Xu, Qianyue Hao, Zefang Zong, Jingwei Wang, Yunke Zhang, Jingyi Wang, Xiaochong Lan, Jiahui Gong, Tianjian Ouyang, Fanjin Meng, and 1 others. 2025a. Towards large reasoning models: A survey of reinforced reasoning with large language models. *arXiv preprint arXiv:2501.09686*.

Guowei Xu, Wenxin Xu, Jiawang Zhao, and Kaisheng Ma. 2025b. Weft: Weighted entropy-driven fine-tuning for dllms. *arXiv preprint arXiv:2509.20863*.

Wujiang Xu, Wentian Zhao, Zhenting Wang, Yu-Jhe Li, Can Jin, Mingyu Jin, Kai Mei, Kun Wan, and Dimitris N. Metaxas. 2025c. Epo: Entropy-regularized policy optimization for llm agents reinforcement learning. *arXiv preprint arXiv:2509.22576*.

Zenan Xu, Zexuan Qiu, Guanhua Huang, Kun Li, Siheng Li, Chenchen Zhang, Kejiao Li, Qi Yi, Yuhao Jiang, Bo Zhou, and 1 others. 2025d. Adaptive termination for multi-round parallel reasoning: An universal semantic entropy-guided framework. *arXiv preprint arXiv:2507.06829*.

Zicheng Xu, Guanchu Wang, Yu-Neng Chuang, Guangyao Zheng, Alexander S Szalay, Zirui Liu, and Vladimir Braverman. 2025e. Dts: Enhancing large reasoning models via decoding tree sketching. *arXiv preprint arXiv:2511.00640*.

Boyang Xue, Fei Mi, Qi Zhu, Hongru Wang, Rui Wang, Sheng Wang, Erxin Yu, Xuming Hu, and Kam-Fai Wong. 2025. Ualign: Leveraging uncertainty estimations for factuality alignment on large language models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6002–6024.

Dong Yan, Jian Liang, Yanbo Wang, Shuo Lu, Ran He, and Tieniu Tan. 2026. What if consensus lies? selective-complementary reinforcement learning at test time. *arXiv preprint arXiv:2603.19880*.

Kai Yang, Xin Xu, Yangkun Chen, Weijie Liu, Jiafei Lyu, Zichuan Lin, Deheng Ye, and Saiyong Yang. 2025a. Entropic: Towards stable long-term training of llms via entropy stabilization with proportional-integral control. *arXiv preprint arXiv:2511.15248*.

Shihui Yang, Chengfeng Dou, Peidong Guo, Kai Lu, Qiang Ju, Fei Deng, and Rihui Xin. 2025b. Dcpo: Dynamic clipping policy optimization. *arXiv preprint arXiv:2509.02333*.

Jiarui Yao, Ruida Wang, and Tong Zhang. 2026a. Prl: Process reward learning improves llms' reasoning ability and broadens the reasoning boundary. *arXiv preprint arXiv:2601.10201*.

Jiashu Yao, Heyan Huang, Chuwei Luo, Daiqing Wu, Zeming Liu, Yuhang Guo, and Yangyang Kang.

2026b. Policy split: Incentivizing dual-mode exploration in llm reinforcement with dual-mode entropy regularization. *arXiv preprint arXiv:2604.11510*.

Yao Yao, Zuchao Li, and Hai Zhao. 2024. Sirllm: Streaming infinite retentive llm. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2611–2624.

Junxi Yin, Haisen Luo, Zhenyu Li, Yihua Liu, Dan Liu, Zequn Li, and Xiaohang Xu. 2025. Pinpointing crucial steps: Attribution-based credit assignment for verifiable reinforcement learning. *arXiv preprint arXiv:2510.08899*.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, and 1 others. 2025. Dapo: An open-source llm reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*.

Song Yu, Li Li, Wenwen Zhao, and Zhisheng Yang. 2026. Erpo: Token-level entropy-regulated policy optimization for large reasoning models. *arXiv preprint arXiv:2603.28204*.

Xiaojian Yuan, Tianyu Pang, Chao Du, Kejiang Chen, Weiming Zhang, and Min Lin. 2024a. A closer look at machine unlearning for large language models. *arXiv preprint arXiv:2410.08109*.

Xiaowei Yuan, Zhao Yang, Yequan Wang, Shengping Liu, Jun Zhao, and Kang Liu. 2024b. Discerning and resolving knowledge conflicts through adaptive decoding with contextual information-entropy constraint. In *Findings of the Association for Computational Linguistics ACL 2024*, pages 3903–3922.

Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai Wang, Shiji Song, and Gao Huang. 2025. Does reinforcement learning really incentivize reasoning capacity in llms beyond the base model? *arXiv preprint arXiv:2504.13837*.

Aohan Zeng, Xin Lv, Qinkai Zheng, Zhenyu Hou, Bin Chen, Chengxing Xie, Cunxiang Wang, Da Yin, Hao Zeng, Jiajie Zhang, and 1 others. 2025a. Glm-4.5: Agentic, reasoning, and coding (arc) foundation models. *arXiv preprint arXiv:2508.06471*.

Siliang Zeng, Quan Wei, William Brown, Oana Frunza, Yuriy Nevmyvaka, Yang Katie Zhao, and Mingyi Hong. 2025b. Reinforcing multi-turn reasoning in llm agents via turn-level credit assignment. In *ICML 2025 Workshop on Computer Use Agents*.

Huajian Zhang, Mingyue Cheng, Yucong Luo, and Xiaoyu Tao. 2025a. Star: Towards cognitive table reasoning via slow-thinking large language models. *arXiv preprint arXiv:2511.11233*.

Qingyang Zhang, Haitao Wu, Changqing Zhang, Peilin Zhao, and Yatao Bian. 2025b. Right question is already half the answer: Fully unsupervised llm reasoning incentivization. *arXiv preprint arXiv:2504.05812*.

Qiyuan Zhang, Fuyuan Lyu, Zexu Sun, Lei Wang, Weixu Zhang, Wenyue Hua, Haolun Wu, Zhihan Guo, Yufei Wang, Niklas Muennighoff, and 1 others. 2025c. A survey on test-time scaling in large language models: What, how, where, and how well? *arXiv preprint arXiv:2503.24235*.

Xiaoyun Zhang, Xiaojian Yuan, Di Huang, You Wang, Hu Chen, Jingqing Ruan, Kejiang Chen, and Xing Hu. 2025d. Rediscovering entropy regularization: Adaptive coefficient unlocks its potential for llm reinforcement learning. *arXiv preprint arXiv:2510.10959*.

Xingjian Zhang, Siwei Wen, Wenjun Wu, and Lei Huang. 2025e. Edge-grpo: Entropy-driven grpo with guided error correction for advantage diversity. *arXiv preprint arXiv:2507.21848*.

Yujian Zhang, Keyu Chen, Zhifeng Shen, Ruizhi Qiao, and Xing Sun. 2025f. Adaptive dual reasoner: Large reasoning models can think efficiently by hybrid reasoning. *arXiv preprint arXiv:2510.10207*.

Zhaohan Zhang, Ziquan Liu, and Ioannis Patras. 2025g. Get confused cautiously: Textual sequence memorization erasure with selective entropy maximization. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 10924–10939.

Ziqi Zhao, Zhaochun Ren, Jiahong Zou, Liu Yang, Zhiwei Xu, Xuri Ge, Zhumin Chen, Xinyu Ma, Daiting Shi, Shuaiqiang Wang, and 1 others. 2026. Reinforced efficient reasoning via semantically diverse exploration. *arXiv preprint arXiv:2601.05053*.

Haizhong Zheng, Jiawei Zhao, and Beidi Chen. 2025a. Prosperity before collapse: How far can off-policy rl reach with stale data on llms? *arXiv preprint arXiv:2510.01161*.

Tianyu Zheng, Tianshun Xing, Qingshui Gu, Taoran Liang, Xingwei Qu, Xin Zhou, Yizhi Li, Zhoufutu Wen, Chenghua Lin, Wenhao Huang, and 1 others. 2025b. First return, entropy-eliciting explore. *arXiv preprint arXiv:2507.07017*.

Yujun Zhou, Zhenwen Liang, Haolin Liu, Wenhao Yu, Kishan Panaganti, Linfeng Song, Dian Yu, Xiangliang Zhang, Haitao Mi, and Dong Yu. 2025. Evolving language models without labels: majority drives selection, novelty promotes variation. *arXiv preprint arXiv:2509.15194*.

Wenhong Zhu, Hongkun Hao, Zhiwei He, Yiming Ai, and Rui Wang. 2024. Improving open-ended text generation via adaptive decoding. In *Proceedings of the 41st International Conference on Machine Learning*, pages 62386–62404.

Xuekai Zhu, Daixuan Cheng, Dinghuai Zhang, Hengli Li, Kaiyan Zhang, Che Jiang, Youbang Sun, Ermo Hua, Yuxin Zuo, Xingtai Lv, Qizheng Zhang, Lin Chen, Fanghao Shao, Bo Xue, Yunchong Song, Zhenjie Yang, Ganqu Cui, Ning Ding, Jianfeng Gao, and 4 others. 2025. Flowrl: Matching reward distributions for llm reasoning. *arXiv preprint arXiv:2509.15207*.

A   Appendix

A.1   Overall formulation

appendix:formula Before analyzing each training knob separately, we first introduce a unified quantity that measures the entropy of the current policy over the training distribution. Since the training objective is defined over sampled queries $q \sim P(Q)$ and group rollouts $\{o_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot \mid q)$, the most natural entropy quantity is the average token-level entropy evaluated under the same training measure. This definition allows us to quantify how each component in training changes the entropy of the current policy in a consistent way.

$$\mathcal{H}_{\text{train}}(\theta) := \mathbb{E}_{q \sim P(Q)} \mathbb{E}_{\{o_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot|q)}$$
$$\left[\frac{1}{G} \sum_{i=1}^{G} \frac{1}{|o_i|} \sum_{t=1}^{|o_i|} \mathcal{H}_{i,t}(\theta) \right] \quad (1)$$

where

$$\mathcal{H}_{i,t}(\theta) = -\sum_{y \in \mathcal{V}} \pi_\theta(y \mid q, o_{i,<t})$$
$$\log \pi_\theta(y \mid q, o_{i,<t}) \quad (2)$$

Let one optimization step be written as

$$\theta^+ = \theta + \Delta\theta \quad (3)$$

To attribute the entropy change to different training knobs, we decompose the update as

$$\Delta\theta = \Delta\theta_q + \Delta\theta_A + \Delta\theta_{\text{clip}}$$
$$+ \Delta\theta_{\text{KL}} + \Delta\theta_J \quad (4)$$

where the five terms correspond to the sampling term $q \sim P(Q)$, the token advantage $\hat{A}_{i,t}$, the clip ratio $\text{clip}(r_{i,t}(\theta), 1 - \epsilon, 1 + \epsilon)$, the KL penalty $\beta D_{\text{KL}}(\pi_\theta \| \pi_{\text{ref}})$, and the learning objective $J_{\text{PPO/GRPO}}(\theta)$, respectively.

The one-step entropy change is then defined as

$$\Delta\mathcal{H}_{\text{train}} := \mathcal{H}_{\text{train}}(\theta^+) - \mathcal{H}_{\text{train}}(\theta). \quad (5)$$

Using a second-order expansion around θ, we obtain

$$\Delta\mathcal{H}_{\text{train}} \approx \sum_{m \in \{q,A,\text{clip},\text{KL},J\}} C_m$$
$$+ \frac{1}{2} \sum_{m,n \in \{q,A,\text{clip},\text{KL},J\}} I_{m,n} \quad (6)$$

where

$$C_m := \nabla_\theta \mathcal{H}_{\text{train}}(\theta)^\top \Delta\theta_m$$
$$I_{m,n} := \Delta\theta_m^\top \nabla_\theta^2 \mathcal{H}_{\text{train}}(\theta) \Delta\theta_n \quad (7)$$

Here, C_m measures the first-order marginal contribution of the m-th training knob to the entropy change, while $I_{m,n}$ captures the second-order interaction between different knobs.

To compare the relative importance of different knobs, we further define the normalized first-order attribution as

$$\rho_m = \frac{|C_m|}{|C_q| + |C_A| + |C_{\text{clip}}| + |C_{\text{KL}}| + |C_J|} \quad (8)$$

A.2   Contribution of sampling
$q \sim P(Q) \ \& \ \{o_i\}$

The sampling term affects entropy indirectly by changing which queries are emphasized during training. Even if the policy update rule remains unchanged, modifying the query distribution $P(Q)$ changes the gradient composition across training samples, and therefore changes the direction in which the policy entropy evolves. In this sense, sampling does not act on entropy explicitly, but rather reweights the optimization trajectory that determines entropy dynamics.

To make this dependence explicit, we introduce an auxiliary sampling parameter ξ_q and write the query distribution as $P_{\xi_q}(Q)$. Let the gradient of the training objective under this sampling distribution be

$$g(\theta, \xi_q) := \nabla_\theta J_{\text{PPO/GRPO}}(\theta; \xi_q) =$$
$$\mathbb{E}_{q \sim P_{\xi_q}(Q)} [u(q; \theta)] \quad (9)$$

where $u(q; \theta)$ denotes the query-level gradient contribution after taking expectations over rollouts and tokens.

Its derivative with respect to ξ_q is

$$\frac{\partial g(\theta, \xi_q)}{\partial \xi_q} = \mathbb{E}_{q \sim P_{\xi_q}(Q)} \left[u(q; \theta) \frac{\partial \log P_{\xi_q}(q)}{\partial \xi_q} \right] \quad (10)$$

For a small perturbation $\Delta\xi_q$, the corresponding sampling-induced parameter update can be approximated as

$$\Delta\theta_q \approx -\eta \frac{\partial g(\theta, \xi_q)}{\partial \xi_q} \Delta\xi_q. \quad (11)$$

Therefore, the first-order entropy contribution of sampling is

$$C_q = \nabla_\theta \mathcal{H}_{\text{train}}(\theta)^\top \Delta\theta_q$$
$$\approx -\eta \nabla_\theta \mathcal{H}_{\text{train}}(\theta)^\top \frac{\partial g(\theta, \xi_q)}{\partial \xi_q} \Delta\xi_q, \qquad (12)$$

or equivalently,

$$C_q \approx -\eta \nabla_\theta \mathcal{H}_{\text{train}}(\theta)^\top \mathbb{E}_{q \sim P_{\xi_q}(Q)}$$
$$\left[u(q;\theta) \frac{\partial \log P_{\xi_q}(q)}{\partial \xi_q} \right] \Delta\xi_q. \qquad (13)$$

The corresponding entropy sensitivity is

$$S_{\xi_q} := \frac{\partial \mathcal{H}_{\text{train}}(\theta^+)}{\partial \xi_q} \approx$$
$$-\eta \nabla_\theta \mathcal{H}_{\text{train}}(\theta)^\top \frac{\partial g(\theta, \xi_q)}{\partial \xi_q}. \qquad (14)$$

This expression shows that the effect of sampling on entropy is determined by how the reweighted query gradient aligns with the entropy gradient.

A.3 Contribution of token advantage $\hat{A}_{i,t}$

The token advantage $\hat{A}_{i,t}$ directly controls how strongly each token contributes to the policy update. Therefore, any entropy-aware modification to the advantage term changes entropy by reweighting token-level policy gradients. This covers both types of methods discussed in the main text, including entropy as an advantage bonus and entropy as a coefficient.

To keep the notation consistent with the main text, we write the advantage as $\hat{A}_{i,t}^{(\xi_A)}$, where ξ_A is an auxiliary parameter that represents the strength of the entropy-aware adjustment. In the PPO/GRPO surrogate, the effective ratio term is

$$\omega_{i,t}(\theta) = \begin{cases} r_{i,t}(\theta), & \text{unclipped,} \\ \text{clip}(r_{i,t}(\cdot), & \text{clipped.} \end{cases} \qquad (15)$$

For a perturbation $\Delta\xi_A$, the resulting parameter update is approximated by

$$\Delta\theta_A \approx -\eta \mathbb{E}_{q \sim P(Q)} \mathbb{E}_{\{o_i\} \sim \pi_{\theta_{\text{old}}}(\cdot|q)}$$
$$\left[\frac{1}{G} \sum_{i=1}^{G} \frac{1}{|o_i|} \sum_{t=1}^{|o_i|} \omega_{i,t}(\theta) \frac{\partial \hat{A}_{i,t}^{(\xi_A)}}{\partial \xi_A} \qquad (16) \right.$$
$$\left. \nabla_\theta \log \pi_\theta(o_{i,t} \mid q, o_{i,<t}) \right] \Delta\xi_A$$

Thus, the first-order entropy contribution of the advantage term is

$$C_A = \nabla_\theta \mathcal{H}_{\text{train}}(\theta)^\top \Delta\theta_A, \qquad (17)$$

namely,

$$C_A \approx -\eta \nabla_\theta \mathcal{H}_{\text{train}}(\theta)^\top \mathbb{E}$$
$$\left[\frac{1}{G} \sum_{i=1}^{G} \frac{1}{|o_i|} \sum_{t=1}^{|o_i|} \omega_{i,t}(\theta) \frac{\partial \hat{A}_{i,t}^{(\xi_A)}}{\partial \xi_A} \qquad (18) \right.$$
$$\left. \nabla_\theta \log \pi_\theta(o_{i,t} \mid q, o_{i,<t}) \right] \Delta\xi_A.$$

The corresponding entropy sensitivity is

$$S_{\xi_A} := \frac{\partial \mathcal{H}_{\text{train}}(\theta^+)}{\partial \xi_A} \approx -\eta \nabla_\theta \mathcal{H}_{\text{train}}(\theta)^\top \mathbb{E}$$
$$\left[\frac{1}{G} \sum_{i=1}^{G} \frac{1}{|o_i|} \sum_{t=1}^{|o_i|} \omega_{i,t}(\theta) \right.$$
$$\left. \frac{\partial \hat{A}_{i,t}^{(\xi_A)}}{\partial \xi_A} \nabla_\theta \log \pi_\theta(o_{i,t} \mid q, o_{i,<t}) \right]$$
$$(19)$$

This formulation makes clear that the advantage term influences entropy through token-wise gradient reweighting rather than by directly redefining entropy itself.

A.4 Contribution of the clip ratio $\text{clip}(r_{i,t}(\theta), 1 - \epsilon, 1 + \epsilon)$

The clipping operation affects entropy by changing which token updates are saturated and which are still allowed to contribute linearly to the surrogate objective. As a result, adjusting the clipping range changes the subset of tokens that effectively shape the policy update, thereby altering the entropy trajectory. This mechanism is especially important because clipping regulates the exploration-exploitation trade-off in a highly local and token-dependent manner.

Using the symmetric clipping notation from the main text, define

$$r_{i,t}^{\text{clip}}(\theta; \epsilon) = \text{clip}(r_{i,t}(\theta), 1 - \epsilon, 1 + \epsilon) \qquad (20)$$

Its derivative with respect to ϵ can be written piecewise as

$$\frac{\partial r_{i,t}^{\text{clip}}(\theta; \epsilon)}{\partial \epsilon} = \qquad (21)$$
$$\mathbf{1}\{r_{i,t}(\theta) > 1 + \epsilon\} - \mathbf{1}\{r_{i,t}(\theta) < 1 - \epsilon\}$$

For a perturbation $\Delta\epsilon$, the clip-induced update is approximately

$$\Delta\theta_{\text{clip}} \approx -\eta\mathbb{E}_{q\sim P(Q)}\mathbb{E}_{\{o_i\}\sim\pi_{\theta_{\text{old}}}(\cdot|q)}$$

$$\left[\frac{1}{G}\sum_{i=1}^{G}\frac{1}{|o_i|}\sum_{t=1}^{|o_i|}\frac{\partial r_{i,t}^{\text{clip}}(\theta;\epsilon)}{\partial\epsilon}\right. \tag{22}$$

$$\left.\hat{A}_{i,t}\nabla_\theta\log\pi_\theta(o_{i,t}\mid q,o_{i,<t})\right]\Delta\epsilon.$$

Therefore, the first-order entropy contribution of clipping is

$$C_{\text{clip}} = \nabla_\theta\mathcal{H}_{\text{train}}(\theta)^\top\Delta\theta_{\text{clip}} \tag{23}$$

that is,

$$C_{\text{clip}} \approx -\eta\nabla_\theta\mathcal{H}_{\text{train}}(\theta)^\top\mathbb{E}$$

$$\left[\frac{1}{G}\sum_{i=1}^{G}\frac{1}{|o_i|}\sum_{t=1}^{|o_i|}\frac{\partial r_{i,t}^{\text{clip}}(\theta;\epsilon)}{\partial\epsilon}\right. \tag{24}$$

$$\left.\hat{A}_{i,t}\nabla_\theta\log\pi_\theta(o_{i,t}\mid q,o_{i,<t})\right]\Delta\epsilon$$

The corresponding sensitivity is

$$S_\epsilon := \frac{\partial\mathcal{H}_{\text{train}}(\theta^+)}{\partial\epsilon} \approx -\eta\nabla_\theta\mathcal{H}_{\text{train}}(\theta)^\top$$

$$\mathbb{E}\left[\frac{1}{G}\sum_{i=1}^{G}\frac{1}{|o_i|}\sum_{t=1}^{|o_i|}\frac{\partial r_{i,t}^{\text{clip}}(\theta;\epsilon)}{\partial\epsilon}\right. \tag{25}$$

$$\left.\hat{A}_{i,t}\nabla_\theta\log\pi_\theta(o_{i,t}\mid q,o_{i,<t})\right]$$

This shows that clipping influences entropy by controlling whether saturated ratio regions continue to transmit policy gradients.

A.5 Contribution of the KL penalty $\beta D_{\text{KL}}(\pi_\theta\|\pi_{\text{ref}})$

The KL term constrains the current policy toward the reference policy and thus affects entropy by regularizing the direction and magnitude of policy drift. Unlike the advantage or clipping terms, the KL penalty does not act through token reweighting. Instead, it contributes a direct regularization gradient whose alignment with the entropy gradient determines whether it increases or decreases overall entropy.

Under the notation of the main text, the KL-induced update is

$$\Delta\theta_{\text{KL}} = -\eta\beta\nabla_\theta\mathbb{E}_{q\sim P(Q)}\mathbb{E}_{\{o_i\}\sim\pi_{\theta_{\text{old}}}(\cdot|q)}$$

$$\left[\frac{1}{G}\sum_{i=1}^{G}\frac{1}{|o_i|}\sum_{t=1}^{|o_i|}D_{\text{KL}}\right. \tag{26}$$

$$\left.\left(\pi_\theta(\cdot\mid q,o_{i,<t})\|\pi_{\text{ref}}(\cdot\mid q,o_{i,<t})\right)\right]$$

Accordingly, the first-order entropy contribution of the KL term is

$$C_{\text{KL}} = \nabla_\theta\mathcal{H}_{\text{train}}(\theta)^\top\Delta\theta_{\text{KL}}, \tag{27}$$

namely,

$$C_{\text{KL}} = -\eta\beta\nabla_\theta\mathcal{H}_{\text{train}}(\theta)^\top$$

$$\nabla_\theta\mathbb{E}\left[\frac{1}{G}\sum_{i=1}^{G}\frac{1}{|o_i|}\sum_{t=1}^{|o_i|}D_{\text{KL}}\right. \tag{28}$$

$$\left.\left(\pi_\theta(\cdot\mid q,o_{i,<t})\|\pi_{\text{ref}}(\cdot\mid q,o_{i,<t})\right)\right].$$

The corresponding entropy sensitivity is

$$S_\beta := \frac{\partial\mathcal{H}_{\text{train}}(\theta^+)}{\partial\beta} \approx -\eta\nabla_\theta\mathcal{H}_{\text{train}}(\theta)^\top$$

$$\nabla_\theta\mathbb{E}\left[\frac{1}{G}\sum_{i=1}^{G}\frac{1}{|o_i|}\sum_{t=1}^{|o_i|}D_{\text{KL}}\right. \tag{29}$$

$$\left.\left(\pi_\theta(\cdot\mid q,o_{i,<t})\|\pi_{\text{ref}}(\cdot\mid q,o_{i,<t})\right)\right].$$

Therefore, the effect of the KL coefficient β on entropy is governed by the alignment between the KL regularization gradient and the entropy gradient.

A.6 Contribution of Optimization Objective $\mathbf{J}_{\text{PPO/GRPO}}(\theta)$

Many entropy-related training methods can be understood as modifying the original PPO/GRPO objective by adding auxiliary regularizers, reweighting terms, or entropy-aware losses. This makes the objective-level analysis especially general: once an additional term is written explicitly in the training objective, its entropy effect can be quantified through its induced parameter update and its alignment with the entropy gradient.

Suppose the training objective is augmented as

$$J(\theta) = J_{\text{PPO/GRPO}}(\theta) + \sum_{k=1}^{K}\lambda_k\Omega_k(\theta), \tag{30}$$

where each $\Omega_k(\theta)$ denotes an additional objective term and λ_k is its weight.

Then the update induced by the k-th objective term is

$$\Delta\theta_{J,k} = -\eta\lambda_k\nabla_\theta\Omega_k(\theta). \quad (31)$$

Its first-order contribution to the training entropy is

$$
\begin{aligned}
C_{J,k} &= \nabla_\theta\mathcal{H}_{\text{train}}(\theta)^\top\Delta\theta_{J,k} \\
&= -\eta\lambda_k\nabla_\theta\mathcal{H}_{\text{train}}(\theta)^\top\nabla_\theta\Omega_k(\theta).
\end{aligned} \quad (32)
$$

Summing over all additional objective terms gives

$$
\begin{aligned}
\Delta\theta_J &= \sum_{k=1}^{K}\Delta\theta_{J,k}, \\
C_J &= \sum_{k=1}^{K}C_{J,k}.
\end{aligned} \quad (33)
$$

The entropy sensitivity with respect to λ_k is

$$
\begin{aligned}
S_{\lambda_k} &:= \frac{\partial\mathcal{H}_{\text{train}}(\theta^+)}{\partial\lambda_k} \approx \\
&\quad -\eta\nabla_\theta\mathcal{H}_{\text{train}}(\theta)^\top\nabla_\theta\Omega_k(\theta).
\end{aligned} \quad (34)
$$

This formulation is highly general and can be directly applied to any additional loss term introduced in entropy-aware training.

A.7 Cumulative contribution over the training trajectory

The one-step decomposition above characterizes the local mechanism of entropy change. However, the observed entropy evolution during training is the result of many successive updates. To connect the local analysis with the global training dynamics, we further define the cumulative contribution of each knob along the optimization trajectory.

For $m \in \{q, A, \text{clip}, \text{KL}, J\}$, define

$$\mathcal{C}_m^{(0\to T)} = \sum_{k=0}^{T-1}\nabla_\theta\mathcal{H}_{\text{train}}(\theta_k)^\top\Delta\theta_{m,k}. \quad (35)$$

This quantity measures the cumulative first-order contribution of the m-th knob to the entropy evolution from step 0 to step T.

We also define the normalized cumulative attribution as

$$\bar{\rho}_m^{(0\to T)} = \frac{\left|\mathcal{C}_m^{(0\to T)}\right|}{\sum_{u\in\{q,A,\text{clip},\text{KL},J\}}\left|\mathcal{C}_u^{(0\to T)}\right|}. \quad (36)$$

This cumulative view is useful for identifying which training knob dominates entropy collapse or entropy preservation at different stages of training.

A.8 Settings & Results Of Entropy-related Methods

We observe that existing methods are rarely compared head-to-head in a systematic manner, and the community's widely accepted and commonly used baselines are typically GRPO or DAPO. Meanwhile, differences in base models, training data, and hyperparameter choices can substantially affect RL training outcomes. With many contemporaneous studies emerging in parallel, these factors further complicate fair evaluations of the effectiveness of different approaches. To mitigate this confounding issue, this survey organizes methods by base model and annotates the detailed training setups reported for most works in Tabs. 1–5 and Tabs. 6–10. Our goal is to provide researchers with a comprehensive visual overview rather than an authoritative comparison or ranking of methods. All configuration details are sourced from the original papers and linked repositories.

Meanwhile, this paper compiles and summarizes the acquisition addresses of mainstream base models employed in the experiments, covering models such as DeepSeek-R1-Distill-Qwen https://huggingface.co/deepseek-ai, LLaMA https://huggingface.co/meta-LLaMA and Qwen https://huggingface.co/Qwen.

To facilitate a clear evaluation of the improvements in model reasoning capabilities achieved by different methods, the following clarifications are provided. Methods that were not evaluated on mathematical benchmarks are excluded from our analysis, such as EMPG (Wang et al., 2025e), EPO (Xu et al., 2025c), and EPPO (Miao et al., 2025). Furthermore, given the discrepancies in the benchmarks adopted by different methods, we only select the metrics from mathematical benchmarks, namely AIME24, AIME25, MATH500, Olympiad, Minerva, MATH, and AMC23, for statistical analysis, in accordance with the frequency of benchmark utilization. Benchmarks with low evaluation frequency (e.g., AMC, GSM8K, AMC24) as

well as non-mathematical benchmarks (e.g., Live-CodeBench, CoQA, WebWalker) are eliminated from the statistics. Correspondingly, to ensure that all methods are included in the statistical scope, a small number of base models (e.g., BP-Math-32B, GLM-9B) are also excluded. Regarding the challenge of standardizing evaluation metrics across models, two types of tables are constructed in this study: Tabs. 1–5 only include methods evaluated by the pass@1 and accuracy (acc) metrics; Tabs. 6–10 cover all types of evaluation metrics, with specific metric names labeled prior to the corresponding values. For the statistics of experimental parameters, this study focuses on the parameter configurations in the training phase. For methods involving multi-stage training, parameter variations across stages are denoted in the format of "8k/16k". The training datasets are restricted to mathematical domains. Additionally, "MATH (3–5)" denotes the subset of the MATH dataset with difficulty levels ranging from 3 to 5.

Specifically, we systematically extract and document the following key training hyperparameters from each paper. We record the "Global Size" (total batch size across all devices for one parameter update) and "Mini Batch" (per-device batch size), which determine the gradient computation granularity and memory requirements during training. The "Learn. Rate" (learning rate) controls the step size of parameter updates and is critical for training stability and convergence speed. "Data Col." (data columns) refers to the number of data fields used in training. "Train. Steps" indicates the total number of parameter update iterations, representing the complete training trajectory from initialization to convergence. "Rollout Num." specifies the number of candidate response sequences generated per prompt during policy optimization, which directly impacts sample efficiency and exploration diversity. "Samp. Temp." (sampling temperature) modulates the randomness of generated outputs, with higher values increasing diversity. "Max Len." (maximum response length) defines the upper bound of generated sequence lengths.

A.9 Entropy in the Broader LLM Training and Inference Pipeline

Although our survey focuses on entropy mechanisms specifically for LRMs, entropy-driven techniques have also been explored throughout the broader LLM pipeline, including pretraining, supervised finetuning, and decoding. To maintain

conceptual completeness while preserving narrative focus in the main text, we provide in this appendix a concise overview of such methods. These works are not explicitly designed for LRMs, yet they are conceptually aligned with the entropy-centric framework developed in this survey. As shown in Fig. 5, we categorize the related methods into three groups along the LLM pipeline: pretraining, supervised fine-tuning (SFT), and decoding, and we list representative works for each stage.

A.9.1 Entropy in Pretraining

During the pretraining stage, entropy mechanisms are leveraged to regulate knowledge organization and expert utilization within large models. LIMoE (Mustafa et al., 2022) imposes dual entropy constraints on the routing distribution: the minimum-entropy loss encourages each token to confidently select a single expert, improving determinism and computational efficiency, while the maximum-entropy loss promotes broader expert activation at the sample level, preserving representation diversity. Researchers also introduce the concept of knowledge entropy (Kim et al., 2024), demonstrating that knowledge entropy gradually decreases as pretraining progresses, making it increasingly difficult for the model to acquire new knowledge and exacerbating catastrophic forgetting.

A.9.2 Entropy in Supervised Fine-Tuning

During the SFT stage, entropy mechanisms play an important role in the training process in multiple ways. Entropy is widely used to improve reasoning ability after SFT. GEM (Li et al., 2025e) introduces maximum-entropy regularization during fine-tuning, encouraging the model to maintain higher entropy and avoiding concentrating high probability on a single token, thereby improving reasoning performance. WeFT (Xu et al., 2025b) increases the training weight of high-entropy regions in diffusion models, so that more model capacity is allocated to reasoning-critical steps. EM-FT (Agarwal et al., 2025) minimizes token-level distribution entropy during fine-tuning, making the model more inclined to select more reliable steps when generating chains of reasoning. POEM (Cao et al., 2025b) encourages viewpoint diversity in generated semantic representations via entropy maximization. Another work proposes a new fine-tuning loss (Stahlberg and Kumar, 2025) that improves fine-tuning by reducing the outgoing connection entropy of FFN layers. In addition, sparse Tsal-

Figure 5: An entropy-centric overview of LMMs.

lis entropy regularization (Choi et al., 2024) filters low-probability tokens, enabling fine-tuning to learn more interpretable hard prompts.

Entropy plays an important role in reducing hallucinations after SFT. The study (Yuan et al., 2024a) incorporates a maximum-entropy mechanism into SFT, increasing predictive entropy on the forget set and thereby reducing hallucinations. Another study (Tjandra et al., 2024) uses semantic entropy as an unlabeled, data-driven signal to fine-tune large language models, so that they proactively refuse when uncertain and reduce hallucination risk. Label smoothing (Huang et al., 2025c) is also introduced into LLM fine-tuning and is explained by its equivalent KL regularization toward the uniform distribution, thereby reducing hallucinations.

Entropy also stabilizes the SFT training process and prevents collapse. TrinityX (Kashyap et al., 2025) adds an entropy regularizer in router training, encouraging more diverse expert selection while avoiding excessive collapse to a small number of experts. ReLIFT (Ma et al., 2025) incorporates an entropy regularization term into the online SFT objective to stabilize training and mitigate distribution collapse. Another work uses entropy as an objective by maximizing next-token distribution entropy on the forgetting set, mitigating privacy risks without significantly harming general capabilities (Zhang et al., 2025g).

Entropy is also used for SFT data processing. A study uses the model's single-token answer entropy to measure question difficulty, partitions data into different difficulty levels, and applies different training strategies for different levels (Goncharov et al., 2025). Other works use entropy for sample filtering and data replay during fine-tuning to improve training efficiency or preserve key capabilities (He et al., 2025b; Mok et al., 2023).

Overall, entropy is not only a metric for characterizing LLMs' uncertainty, but also an efficient signal that directly guides SFT optimization, affecting key components such as training objective design, weight allocation, and sample selection; therefore, it plays an important role in SFT.

A.9.3 Entropy in Decoding

In the decoding of LLMs, entropy serves as a key control signal for decoding, effectively improving the stability and consistency of generation. The study (Stolfo et al., 2024) finds that neurons inside the model influence generative behavior by regulating their distribution entropy. Therefore, the study (Zhu et al., 2024) continuously monitors changes in entropy before and after token generation to promptly correct the generation direction when unstable fluctuations occur. Meanwhile, entropy is also injected as a penalty term into probability adjustment (Chen et al., 2024a), making the model more inclined to select low-entropy, high-confidence tokens. Furthermore, END (Wu et al., 2025a) incorporates cross-layer entropy to enable more consistent risk estimation across different feature levels. REAL (Chang et al., 2024) computes residual entropy that helps the model adaptively shrink or expand the sampling space during decoding. In long-text scenarios, SNNE (Nguyen et al., 2025) introduces continuous semantic similarity to unify and extend the semantic entropy framework, improving hallucination detection.

Entropy is further employed as a mechanism for scheduling and regulating the inference process. COIECD (Yuan et al., 2024b) determines whether a knowledge conflict has occurred by assessing the information-entropy constraint of the token, triggering a more cautious sampling strategy. CascadeVLM (Wei, 2024) uses entropy to measure the uncertainty of the sample and routes

different samples accordingly. CNTP (Wang et al., 2025h) relies on the predictive entropy of the current token to determine whether multiple sampling should be performed, improving inference quality and reliability. At the attention level, entropy can also serve as a trigger signal. ONLY (Wan et al., 2025b) calculates the Text-to-Visual Entropy Ratio for each layer to identify target layers for attention intervention. EnSToM (Suh et al., 2025) utilizes the internal entropy of the LLM as an uncertainty signal to dynamically control activation steering, thereby improving the service capabilities of the dialogue system.

Furthermore, in long dialogues or multimodal tasks, entropy begins to guide the dynamic management of context and resources. SirLLM (Yao et al., 2024) leverages token entropy and memory decay mechanisms to dynamically filter and retain the most important KV cache, enhancing the model's ability to handle long dialogues. MEDA (Wan et al., 2025a) uses cross-modal attention entropy to determine the size of the KV cache for each layer, thereby achieving efficient multimodal inference.

Table 1: Performance of Different Entropy-Based Methods on Mathematical Benchmarks – DeepSeek-R1-Distill-Qwen Models (pass@1 & acc)

Base Model	Method	AIME24	AIME25	MATH500	Olympiad	Minerva	MATH	AMC23	open-source	Train Data	Global Size	Mini Batch	Learn. Rate	Data Col.	Train. Steps	Rollout Num.	Samp. Temp.	Max Len.
DeepSeek-R1-Distill-Qwen-1.5B	PEAR (Huang et al., 2025a)	23.33	–	77.20	–	–	–	70.00	✓	GSM8K	128	-	1E-6	7473	-	8	0.6	16K
	DA-DLER-R1-1.5B (Liu et al., 2025e)	34.37	–	–	48.70	44.89	86.70	–	✓	DeepScaleR-Preview	512	64	1E-6	40K	600	16	1.0	4000
	DLER-R1-1.5B (Liu et al., 2025e)	34.38	–	–	48.31	43.59	86.95	–	✓	DeepScaleR-Preview	512	64	1E-6	40K	450	16	1.0	4000
	ProRL (Liu et al., 2025d)	48.13	33.33	–	60.22	47.98	91.89	–	✓	DeepScaleR	256	64	2E-6	40k	-	16	1.2	8k
	ADR (Zhang et al., 2025f)	36.5	23.3	81.0	–	–	–	–	✗	OpenMathReasoning, DeepScaleR-Preview	-	-	-	-	-	-	-	8k/16k
	HIVE (Wu et al., 2026)	37.5	–	87.2	53.2	35.1	–	–	✗	DAPO, MATH, OPEN-R1	128	512	1E-6	–	1000	8	1.0	–
DeepSeek-R1-Distill-Qwen-7B	TreeRL (Hou et al., 2025)	60.8	–	94.4	57.1	–	–	–	✓	MATH-train, NuminaMath	480	-	1.5E-6	-	-	30	1.2	8K
	DA-DLER-R1-7B (Liu et al., 2025e)	53.9	–	–	61.16	53.60	94.17	–	✓	DeepScaleR-Preview	512	64	1.0E-6	40K	600	16	1.0	4000
	DA-DLER-R1-7B (Liu et al., 2025e)	55.62	–	–	60.48	53.88	94.21	–	✓	DeepScaleR-Preview	512	64	1.0E-6	40K	450	16	1.0	4000
	ETR (Xiong et al., 2026)	56.7	–	90.6	–	–	–	87.5	✓	DeepMath(5-10)	32	16	1E-5	7000	207	5	1.0	16K

Table 2: Performance of Different Entropy-Based Methods on Mathematical Benchmarks – LLaMA Models (All Metrics)

Base Model	Method	AIME24	AIME25	MATH500	Olympiad	Minerva	MATH	AMC23	open-source	Train Data	Global Size	Mini Batch	Learn. Rate	Data Col.	Train. Steps	Rollout Num.	Samp. Temp.	Max Len.
LLaMA-3.1-8B	TTRL (Liu et al., 2025a)	10	-	63.7	-	-	-	-	✗	-	-	-	-	-	-	-	0.6	3K
	ETMR (Liu et al., 2025a)	16.9	-	59.5	-	-	-	-	✗	AIME24, AMC, MATH-500	-	-	-	-	-	32	0.6	3K
LLaMA-3.1-8B-Instruct	AEPO-Dong (Dong et al., 2025a)	26.7	16.7	65.8	-	-	80.6	-	✓	-	128	16	-	-	-	16	0.6	20K
	ARPO (Dong et al., 2025b)	23.3	16.7	64.6	-	-	80.2	-	✓	Tool-Star, STILL	128	16	-	-	-	-	-	4K
	EM_INF (Agarwal et al., 2025)	3.3	-	43.0	16.4	22.8	-	-	✓	-	-	-	-	-	-	-	0.1	-
	GRPO + D³S (Wang et al., 2025a)	5.3	0.1	-	3.3	22.5	35.9	20.3	✗	DeepScaleR	-	-	5E-7	-	-	32	0.6	-
	UEC-RL (Wang et al., 2026)	9.27	2.08	–	–	28.3	56.6	–	✓	DAPO-17K	-	-	-	-	-	5	1.0	8K
LLaMA-3.2-3B-Instruct	SimKO (Peng et al., 2025)	13.8	1.0	54.6	21.0	18.5	-	35.2	✓	GSM8K, MATH	1K	256	1E-6	-	-	8	1.0	-
	HIVE (Wu et al., 2026)	17.5	–	53.8	20.0	20.5	–	–	✗	DAPO, MATH, OPEN-R1	256	512	1E-6	–	1000	8	1.0	–

Table 3: Performance of Different Entropy-Based Methods on Mathematical Benchmarks – Qwen-2.5 Models (pass@1 & acc)

Base Model	Method	AIME24	AIME25	MATH500	Olympiad	Minerva	MATH	AMC23	open-source	Train Data	Global Size	Mini Batch	Learn. Rate	Data Col.	Train. Steps	Rollout Num.	Samp. Temp.	Max Len.
Qwen-2.5-1.5B	ERPO (Yu et al., 2026)	3.75	2.08	–	–	4.22	27.19	–	✗	MATH(3–5)	16	–	5E-6	8441	–	8	1.0	2K
Qwen-2.5-3B	TTRL (Liu et al., 2025a)	7.9	-	72.2	-	-	-	40.7	✗	AIME24, AMC, MATH-500	-	-	-	-	-	-	0.6	3K
	ETMR (Liu et al., 2025a)	9.2	-	71.7	-	-	-	-	✗	AIME24, AMC, MATH-500	-	-	-	-	-	-	-	-
	SCRL (Yan et al., 2026)	–	8.4	68.2	–	29.5	–	–	✓	AIME25, AMC, MATH-500, Minerva, GPQA	8	–	5E-7	–	–	16	0.6	3K
	ERPO (Yu et al., 2026)	7.08	2.92	–	–	8.91	37.50	–	✗	MATH(3–5)	16	–	5E-6	8441	–	8	1.0	2K
Qwen-2.5-7B	SimKO (Peng et al., 2025)	16.3	9.4	76.7	38.7	35.2	-	-	✓	MATH	1K	256	1E-6	-	-	8	1.0	-
	FR3E (Zheng et al., 2025b)	25.2	-	79.0	42.1	39.0	-	-	✓	DeepScaler, SimpleRL (3-5)	512	128	1E-6	-	-	16	-	16k
	ERPO (Yu et al., 2026)	12.92	7.08	–	–	13.28	49.53	–	✗	MATH(3–5)	16	–	5E-6	8441	–	8	1.0	2K
Qwen-2.5-7B-Instruct	AEPO-Dong (Dong et al., 2025a)	33.3	33.0	80.4	-	-	90.0	-	✓	-	128	16	-	1K	-	16	0.6	20K
	ARPO (Dong et al., 2025b)	30	30.0	78.8	-	-	88.8	-	✓	Tool-Star, STILL	128	-	-	-	-	-	-	4K
	EM_INF (Agarwal et al., 2025)	11.1	-	73.8	38.2	41.2	-	45.8	✓	-	-	-	-	-	-	-	0.1	-
	TRE-P (Huang et al., 2026)	74.27	–	–	–	–	–	–	✗	MATH	512	64	1E-6	7500	300	8	1.0	8K
Qwen-2.5-14B	TreeRL (Hou et al., 2025)	20.8	-	81.7	44.6	-	-	55.9	✓	MATH-train, NuminaMath	480	-	1.5E-6	-	-	30	1.2	8K
	DCPO (Li et al., 2026d)	20	85.0	84.6	-	-	-	-	✓	MATH-DAPO-17k, MATH (3-5)	512	32	-	25k	400	-	1.0	3K
Qwen-2.5-32B	FR3E (Zheng et al., 2025b)	40.2	-	87.4	51.7	45.6	-	-	✓	DeepScaler, SimpleRL (3-5)	512	128	1E-6	-	-	16	-	16k

Table 4: Performance of Different Entropy-Based Methods on Mathematical Benchmarks – Qwen-2.5-Math Models (pass@1 & acc)

Base Model	Method	AIME24	AIME25	MATH500	Olympiad	Minerva	MATH	AMC23	open-source	Train Data	Global Size	Mini Batch	Learn. Rate	Data Col.	Train. Steps	Rollout Num.	Samp. Temp.	Max Len.
Qwen-2.5-Math-1.5B	GRPO + D³S (Wang et al., 2025a)	11.2	6.9	-	10.6	23.5	53.7	48.6	✗	DeepScaleR	-	-	5E-7	-	-	32	1.0	-
	GSPO + D³S (Wang et al., 2025a)	11.4	8.2	-	10.5	22.9	54.0	48.4	✗	DeepScaleR	-	-	5E-7	-	-	32	1.0	-
	TTRL (Liu et al., 2025a)	15.8	-	73.0	-	–	–	–	✗	AIME24, AMC, MATH-500	-	-	-	-	-	-	0.6	3K
	EDGE-GRPO (Zhang et al., 2025e)	10	-	73.20	37.33	29.04	–	–	✓	DeepScaleR-Random-1K, DeepScaleR-Hard-1K	-	-	1E-6	2k	1000	-	-	1K
	EMPO (Zhang et al., 2025b)	13.3	-	-	36.6	32.4	73.0	55.0	✓	-	-	-	-	-	-	-	-	-
	UCAS (Xie et al., 2025)	23.3	-	80.6	42.1	31.6	–	–	✓	MATH (3-5)	512	-	1E-6	-	-	16	1.0	3K
	AEnt (Shen, 2025)	21.7	-	75.0	37.7	33.0	–	–	✓	MATH	512	-	2E-6	7.5K	-	16	-	3K
	HIVE (Wu et al., 2026)	16.7	–	77.9	40.3	31.5	–	–	✗	DAPO, MATH, OPEN-R1	256	512	1E-6	–	1000	8	1.0	–
Qwen-2.5-Math-7B	FR3E (Zheng et al., 2025b)	39.1	-	82.2	46.5	40.8	–	67.5	✗	DeepScaler, SimpleRL (3-5)	512	128	1E-6	-	-	16	-	16k
	DCPO (Li et al., 2026d)	46.7	82.6	82.5	-	–	–	16.7	✗	MATH-DAPO-17k, MATH (3-5)	512	32	-	25k	400	-	1.0	3K
	Entropy Adv (Cheng et al., 2025)	33.7	17.6	83.1	-	-	–	69.8	✗	DAPO-Math-17K	512	32	1E-06	-	-	16	1.0	8K
	GRPO + D³S (Wang et al., 2025a)	20.3	7.9	-	10.7	25.0	52.2	54.4	✗	DeepScaleR	-	-	5E-07	-	-	32	1.0	-
	GSPO + D³S (Wang et al., 2025a)	18.3	8.3	-	11.5	28.4	54.9	53.2	✗	DeepScaleR	-	-	5E-07	-	-	32	1.0	-
	AEPO-Wang (Wang et al., 2025b)	50.0	-	-	42.4	37.5	82.0	–	✓	DAPO-17K	128	-	10-6	-	-	-	-	2K
	SimKO (Peng et al., 2025)	32.8	12.9	77.6	39.8	35.0	–	62.4	✓	MATH	1K	256	10-6	-	-	8	1.0	-
	EDGE-GRPO (Zhang et al., 2025e)	16.67	-	79.00	42.67	36.03	–	–	✓	DeepScaleR-Random-1K, DeepScaleR-Hard-1K	-	-	1E-6	2k	1000	-	-	1K
	EMPO (Zhang et al., 2025b)	20.0	-	-	37.3	40.4	78.0	65.0	✓	-	-	-	-	-	-	-	-	-
	UCAS (Xie et al., 2025)	43.3	-	85.6	48.0	37.6	–	–	✗	MATH (3-5)	512	-	1E-6	-	-	16	1.0	3K
	SCRL (Yan et al., 2026)	–	26.9	85.6	–	41.6	–	–	✓	AIME25, AMC, MATH-500, Minerva, GPQA	–	–	5E-7	-	-	16	1.0	3K
	HIVE (Wu et al., 2026)	36.7	–	93.0	43.8	34.8	–	–	✗	DAPO, MATH, OPEN-R1	256	512	1E-6	–	1000	8	1.0	–
	UEC-RL (Wang et al., 2026)	28.5	10.7	–	–	35.7	80.4	–	✓	DAPO-Math-17k	–	–	–	–	–	5	1.0	8K
Qwen-2.5-Math-7B-Instruct	EM_INF (Agarwal et al., 2025)	14.4	-	80.2	40.8	42.3	–	–	✗	-	-	-	-	-	-	-	0.1	-

Table 5: Performance of Different Entropy-Based Methods on Mathematical Benchmarks – Qwen-3 Models (pass@1 & acc)

Base Model	Method	AIME24	AIME25	MATH500	Olympiad	Minerva	MATH	AMC23	open-source	Train Data	Global Size	Mini Batch	Learn. Rate	Data Col.	Train. Steps	Rollout Num.	Samp. Temp.	Max Len.
Qwen-3-4B	PEAR (Huang et al., 2025a)	56.66	–	84.00	–	–	–	87.50	✓	GSM8K	128	-	1E-6	7,473	-	8	0.6	16K
	AER (Zhang et al., 2025d)	25.2	22.1	86.7	–	–	–	70.2	✗	open-source DeepscaleR	128	32	1E-6	-	-	-	-	8k
	ENTRA (Cai et al., 2026)	–	–	93.20	–	–	–	–	✗	MATH, Weekly12K	–	–	–	2000	200	–	0.6	38K
	ETR (Xiong et al., 2026)	73.3	–	91.4	–	–	–	90.0	✓	DeepMath-103K	32	16	1E-5	7000	207	5	1.0	16K
	Policy Split (Yao et al., 2026b)	–	–	–	–	–	94.12	–	✗	DeepMath-103K	256	–	3E-6	20K	-	8	–	12K
Qwen-3-8B	PEAR (Huang et al., 2025a)	60	–	85.40	–	–	–	92.50	✓	GSM8K	128	-	1E-6	7,473	-	8	0.6	16K
	AER (Zhang et al., 2025d)	31.4	25.1	89.4	–	–	–	75.6	✗	open-source DeepscaleR	128	32	1E-6	-	-	-	-	8k
	QAE+CLIP-Cov (Wu et al., 2025b)	46.04	37.40	–	–	–	–	90.23	✓	DAPO-Math-17K	512	32	1E-6	-	-	32	0.7	20K
	QAE+Clip-Higher (Wu et al., 2025b)	48.23	34.90	–	–	–	–	92.97	✓	DAPO-Math-17K	512	32	1E-6	-	-	32	0.7	20K
	QAE+KL-Cov (Wu et al., 2025b)	44.69	33.44	–	–	–	–	87.97	✓	DAPO-Math-17K	512	32	1E-6	-	-	32	0.7	20K
	ENTRA (Cai et al., 2026)	–	–	94.80	–	–	–	–	✗	MATH, Weekly12K	–	–	–	2000	200	–	0.6	38K
	ETR (Xiong et al., 2026)	73.3	–	93.6	–	–	–	92.5	✓	DeepMath-103K	32	16	1E-5	7000	207	5	1.0	16K
	Policy Split (Yao et al., 2026b)	–	–	–	–	–	94.40	–	✗	DeepMath-103K	256	–	3E-6	20K	-	8	–	12K

Table 6: Performance of Various Entropy-Based Methods on Mathematical Benchmarks – DeepSeek-R1-Distill-Qwen Models (All Metrics)

Base Model	Method	AIME24	AIME25	MATH500	Olympiad	Minerva	MATH	AMC23	open-source	Train Data	Global Size	Mini Batch	Learn. Rate	Data Col.	Train. Steps	Rollout Num.	Samp. Temp.	Max Len.
DeepSeek-R1-Distill-Qwen-1.5B	PEAR (Huang et al., 2025a)	acc@1: 23.33	-	acc@1: 77.20	-	-	-	acc@1: 70.00	✓	GSM8K	128	-	1E-06	7,473	-	8	0.6	16K
	CE-GPPO (Su et al., 2025a)	avg@32: 42.0	avg@32: 33.9	-	-	-	-	avg@32: 85.9	✓	KlearReasoner-MathSub-30K	-	-	1E-06	30k	-	8	-	16k
	AEnt (Shen, 2025)	avg@4: 39.2	-	avg@4: 88.2	avg@4: 59.1	avg@4: 35.9	-	-	✓	OpenR1-math	256	-	1E-06	40k	-	8	-	7K
	ASPO-Math-1.5B (Wang et al., 2025c)	avg@64: 49.0
pass@64: 80.0	avg@64: 35.1
pass@64: 70.0	avg@64: 90.5
pass@64: 94.4	avg@64: 58.8
pass@64: 66.9	avg@64: 35.1
pass@64: 50.4	-	avg@64: 87.2
pass@64: 95.0	✓	-	-	-	-	-	-	-	-	-
	Archer-1.5B (Wang et al., 2025d)	avg@64: 48.7
pass@64: 83.3	avg@64: 33.8
pass@64: 70.0	avg@64: 90.8
pass@64: 94.4	avg@4: 59.3
pass@4: 67.1	avg@8: 35.7
pass@8: 51.1	-	avg@64: 86.0
pass@64: 97.5	✓	DeepScaleR, SkyworkOR1, DAPO-Math-17K	64	32	1E-06	51,800	520	16	1.0	32K
	DA-DLER-R1-1.5B (Liu et al., 2025e)	avg@64: 34.37	-	-	pass@1: 48.70	pass@1: 44.89	pass@1: 86.70	-	✓	DeepScaleR-Preview-Dataset	512	64	1E-06	40K	600	16	1.0	4000
	DLER-R1-1.5B (Liu et al., 2025e)	pass@1: 34.38	-	-	pass@1: 48.31	pass@1: 43.59	pass@1: 86.95	-	✓	DeepScaleR-Preview-Dataset	512	64	1E-06	40K	450	16	1.0	4000
	ProRL (Liu et al., 2025d)	pass@1: 48.13	pass@1: 33.33	-	pass@1: 60.22	pass@1: 47.98	pass@1: 91.89	-	✗	DeepScaleR Dataset	256	64	2E-06	40k	-	16	1.2	8k
	ADR (Zhang et al., 2025f)	pass@1: 36.5	-	pass@1: 23.3	pass@1: 81.0	-	-	-	✓	OpenMathReasoning DeepScaleR-Preview	-	-	-	-	-	-	-	8k/16k
	ProGRPO (Li et al., 2026b)	pass@1: 46.0
pass@32: 76.7	pass@1: 33.6
pass@32: 60.0	pass@1: 87.0
pass@32: 98.2	pass@1: 62.0
pass@32: 81.8	pass@1: 34.8
pass@32: 58.1	-	pass@1: 86.3	✗	DAPO-Math-17k	512	32	1×10^{-6}	-	-	8	1	32K
	BandPO (Li et al., 2026c)	mean@32: 20.00
pass@32: 51.80	mean@32: 23.85
pass@32: 40.65	-	-	-	-	mean@32: 77.34
pass@32: 94.98	✗	DAPO , MATH(3–5)	256	64	1×10^{-6}	-	800	-	1	-
	HIVE (Wu et al., 2026)	acc: 37.5	-	acc: 87.2	acc: 53.2	acc: 35.1	-	-	✗	DAPO,MATH, OPEN-R1	128	512	1×10^{-6}	–	1000	8	1	-
DeepSeek-R1-Distill-Qwen-7B	TreeRL (Hou et al., 2025)	acc@1: 60.8	-	acc@1: 94.4	acc@1: 57.1	-	-	-	✓	MATH-train, NuminaMath	480	-	1.5E-06	-	-	30	1.2	8K
	CE-GPPO (Su et al., 2025a)	avg@32: 66.0	avg@32: 51.4	avg@4: 95.6	-	-	-	avg@32: 93.8	✓	KlearReasoner-MathSub-30K	-	-	1E-06	30k	-	8	-	16k
	DA-DLER-R1-7B (Liu et al., 2025e)	pass@1: 53.90	-	-	pass@1: 61.16	pass@1: 53.60	pass@1: 94.17	-	✓	DeepScaleR-Preview-Dataset	512	64	1E-06	40K	600	16	1.0	4000
	DLER-R1-7B (Liu et al., 2025e)	pass@1: 55.62	-	-	pass@1: 60.48	pass@1: 53.88	pass@1: 94.21	-	✓	DeepScaleR-Preview-Dataset	512	64	1E-06	40K	450	16	1.0	4000
	BandPO (Li et al., 2026c)	mean@32: 29.90
pass@32: 49.14	mean@32: 34.58
pass@32: 57.21	-	-	-	-	mean@32: 89.84
pass@32: 95.00	✓	DAPO , MATH(3–5)	256	64	1×10^{-6}	-	500	-	1	-
	ETR (Xiong et al., 2026)	pass@1: 56.7	-	pass@1: 90.6	-	-	-	pass@1: 87.5	✓	DeepMath(5-10)	32	16	1×10^{-5}	7,000	207	5	1	16384

Table 7: Performance of Various Entropy-Based Methods on Mathematical Benchmarks – LLaMA Models (All Metrics)

Base Model	Method	AIME24	AIME25	MATH500	Olympiad	Minerva	MATH	AMC23	open-source	Train Data	Global Batch Size	Mini Batch	Learn. Rate	Data Col.	Train. Steps	Rollout Num.	Samp. Temp.	Max Len.
LLaMA-3.1-8B	MENTOR (Qin et al., 2025)	avg@32: 1.2	avg@32: 0.6	-	pass@1: 8.9	pass@1: 16.2	pass@1: 30.2	-	✓	OpenR1-MATH	128	64	1E-06	220K	120	8	1.0	8k
	TTRL (Liu et al., 2025a)	pass@1: 10.0	-	pass@1: 63.7	-	-	-	-	✗	AIME24, AMC, MATH-500	-	-	-	-	-	32	0.6	3K
	ETMR (Liu et al., 2025a)	pass@1: 16.9	-	pass@1: 59.5	-	-	-	-	✗	AIME24, AMC, MATH-500	-	-	-	-	-	32	0.6	3K
LLaMA-3.1-8B-Instruct	AEPO-Dong (Dong et al., 2025a)	pass@1: 26.7	pass@1: 16.7	pass@1: 65.8	-	-	pass@1: 80.6	-	✓	-	128	16	-	-	-	16	0.6	20K
	ARPO (Dong et al., 2025b)	pass@1: 23.3	pass@1: 16.7	pass@1: 64.6	-	-	pass@1: 80.2	-	✓	Tool-Star, Tool-Star	128	16	-	-	-	16	-	4K
	EM_INF (Agarwal et al., 2025)	pass@1: 3.3	-	pass@1: 43.0	pass@1: 16.4	pass@1: 22.8	-	-	✓	-	-	-	-	-	-	-	0.1	-
	GRPO + D³S (Wang et al., 2025a)	pass@1: 5.3	pass@1: 0.1	-	pass@1: 3.3	pass@1: 22.5	pass@1: 35.9	pass@1: 20.3	✓	DeepScaleR	-	-	5E-07	-	-	32	1.0	-
	UEC-RL (Wang et al., 2026)	pass@1: 9.27	pass@1: 2.08	-	-	pass@1: 28.3	pass@1: 56.6	-	✓	DAPO-17K	-	-	-	-	-	5	1	8192
LLaMA-3.2-3B-Instruct	SimKO (Peng et al., 2025)	pass@1: 13.8	pass@1: 1.0	pass@1: 54.6	pass@1: 21.0	pass@1: 18.5	-	pass@1: 35.2	✓	GSM8K, MATH	1K	256	1E-06	-	-	8	1.0	-
	M2PO (Zheng et al., 2025a)	avg@16: 10.4	avg@16: 4.4	avg@4: 52.0	avg@4: 18.1	avg@4: 21.2	-	avg@4: 33.8	✓	DeepScaleR Math	256	512	1E-06	-	1000	8	1.0	16K
	ROSE (Zhao et al., 2026)	pass@8: 20.00	pass@8: 6.67	pass@8: 55.00	-	-	-	pass@8: 45.00	✓	MATH	512	-	1×10^{-6}	7500	-	8	-	-
	PRL (Yao et al., 2026a)	pass@8: 16.67	-	pass@8: 74.00	pass@8: 41.33	pass@8: 36.40	-	pass@8: 67.50	✗	NuminaMath	128	256	1×10^{-6}	150k	-	-	-	3072
	HIVE (Wu et al., 2026)	acc: 17.5	-	acc: 53.8	acc: 20.0	acc: 20.5	-	-	✗	DAPO,MATH, OPEN-R1	256	512	1×10^{-6}	-	1000	8	1	-

Table 8: Performance of Various Entropy-Based Methods on Mathematical Benchmarks – Qwen-2 Models (All Metrics)

Base Model	Method	AIME24	AIME25	MATH500	Olympiad	Minerva	MATH	AMC23	open-source	Train Data	Global Batch Size	Mini Batch	Learn. Rate	Data Col.	Train. Steps	Rollout Num.	Samp. Temp.	Max Len.
Qwen-2.5-3B	TTRL (Liu et al., 2025a)	pass@1: 7.9	-	pass@1: 72.2	-	-	-	-	✗	AIME24, AMC, MATH-500	-	-	-	-	-	64/32	0.6	3K
	MENTOR (Qin et al., 2025)	avg@32: 8.3	avg@32: 3.8	-	pass@1: 35.2	pass@1: 26.5	pass@1: 69.8	-	✓	MATH (3-5)	128	64	1E-06	-	120	8	1.0	8k
	SCRL (Yan et al., 2026)	-	pass@1: 8.4	pass@1: 68.2	-	pass@1: 29.5	-	-	✓	AIME25 AMC MATH-500 Minerva GPQA	8	-	5×10^{-7}	-	-	16	0.6	3072
	ERPO (Yu et al., 2026)	acc: 7.08	acc: 2.92	-	-	acc: 8.91	-	acc: 37.50	✗	MATH(3-5)	16	-	5×10^{-6}	8,441	-	8	1	2048
	DCPO (Li et al., 2026d)	avg@1: 33	-	avg@1: 62.5	avg@1: 71.2	-	-	avg@1: 10	✓	DAPO-Math-17k, MATH (3-5)	512	32	-	25k	400	-	1.0	3K
	ETMR (Liu et al., 2025a)	pass@1: 9.2	-	pass@1: 71.7	-	-	-	-	✗	AIME24, AMC, MATH-500	-	-	-	-	-	-	-	-
Qwen-2.5-7B	GRPO+POSITION (Deng et al., 2025)	pass@4: 29.75	pass@4: 25.36	pass@4: 90	-	-	-	pass@4: 80	✗	STILL-3	512	32	1E-06	90K	-	-	1.0	8K
	GRPO+PPL (Deng et al., 2025)	pass@4: 35.48	pass@4: 24.35	pass@4: 92.4	-	-	-	pass@4: 85	✗	STILL-3	512	32	1E-06	90K	-	-	1.0	8K
	SimKO (Peng et al., 2025)	pass@1: 16.3	pass@1: 9.4	pass@1: 76.7	pass@1: 38.7	pass@1: 35.2	-	pass@1: 57.3	✓	MATH	1K	256	1E-06	-	-	8	1.0	-
	MENTOR (Qin et al., 2025)	avg@32: 18.3	avg@32: 16.5	-	pass@1: 45.2	pass@1: 34.9	pass@1: 81.4	-	✓	MATH (3-5)	128	64	1E-06	-	120	8	1.0	8k
	Clip-Cov (Cui et al., 2025)	avg@32: 22.1	avg@32: 15.8	avg@32: 80.4	avg@32: 44.1	avg@32: 41.1	-	-	✓	Eurus-2-RL-Math	256	128	5E-07	-	-	8	1.0	8K
	KL-Cov (Cui et al., 2025)	avg@32: 22.6	avg@32: 12.9	avg@32: 80.8	avg@32: 42.6	avg@32: 38.2	-	-	✓	Eurus-2-RL-Math	256	128	5E-07	-	-	8	1.0	8K
	FlowRL (Zhu et al., 2025)	avg@16: 15.41	avg@16: 10.83	avg@16: 66.96	avg@16: 34.61	avg@16: 31.41	-	-	✓	DAPO-Math-17K	512	-	1E-06	-	-	8	-	8K
	EM 1-shot (Gao et al., 2025)	-	-	avg@8: 67.4	avg@8: 33.6	avg@8: 22.1	-	avg@8: 45.6	✓	NuminaMath	64	2	2E-05	1.0	10	-	0.5	-
	FR3E (Zheng et al., 2025b)	acc: 25.2	-	acc: 79	acc: 42.1	acc: 39	-	acc: 67.5	✓	DeepScaler, SimpleRL (3-5)	512	128	1E-06	-	-	16	-	16k
	DCPO (Li et al., 2026d)	pass@32:18.8	acc:15.3	-	acc:42.20	acc:38.20	acc:79.2	-	✗	DAPO-Math-17k	512	128	1×10^{-6}	-	-	8	1	8192
	ProGRPO (Li et al., 2026b)	pass@1: 21.3 pass@32: 53.3	pass@1: 15.9 pass@32: 50.0	pass@1: 80.5 pass@32: 94.2	pass@1: 42.7 pass@32: 67.5	pass@1: 32.0 pass@32: 53.3	-	pass@1: 67.2 pass@32: 92.5	✗	DAPO-Math-17k	512	32	1×10^{-6}	-	-	8	1	8K
	ID (Chen et al., 2026)	pass32: 17.0	pass32: 9.3	-	pass4: 42.6	-	-	-	✗	DAPO-Math-17k	512	-	1×10^{-6}	-	400	8	-	8192
	DID (Chen et al., 2026)	pass32: 16.9	pass32: 12.1	-	pass4: 42.4	-	-	-	✗	DAPO-Math-17k	512	-	1×10^{-6}	-	400	8	-	8192
	OD (Chen et al., 2026)	pass32: 16.9	pass32: 11.7	-	pass4: 44.0	-	-	-	✗	DAPO-Math-17k	512	-	1×10^{-6}	-	400	8	-	8192
	ERPO (Yu et al., 2026)	acc: 12.92	acc: 7.08	-	-	acc: 13.28	-	acc: 49.53	✗	MATH(3-5)	16	-	5×10^{-6}	8,441	-	8	1	2048
	AsymGRPO (Gu et al., 2026)	Avg@10: 16.00	Avg@10: 11.03	Avg@5: 75.25	Avg@5: 37.33	-	-	Avg@10: 54.50	✗	MATH	-	-	2×10^{-6}	-	-	8	-	-
	ARTS (Hong et al., 2026)	-	-	BoN@16: 74.6	-	-	-	-	✗	MATH	-	-	-	-	-	16	0.6	-
Qwen-2.5-7B-Instruct	AEPO-Dong (Dong et al., 2025a)	pass@1: 33.3	pass@1: 33	pass@1: 80.4	-	-	pass@1: 90	-	✓	-	128	16	-	1K	-	16	0.6	20K
	ARPO (Dong et al., 2025b)	pass@1: 30	pass@1: 30	pass@1: 78.8	-	-	pass@1: 88.8	-	✓	STILL, Tool-Star	128	-	-	-	-	16	-	4K
	EM_INF (Agarwal et al., 2025)	pass@1: 11.1	-	pass@1: 73.8	pass@1: 38.2	pass@1: 41.2	-	-	✓	-	-	-	-	-	-	-	0.1	-
	EGSPO (Hu et al., 2026)	majority@32: 22.0	majority@32: 21.0	-	-	-	-	-	✗	-	240	32	5×10^{-6}	12,500	-	8	1	10,240
	TRE-P (Huang et al., 2026)	pass@1: 74.27	-	-	-	-	-	-	✗	MATH	512	64	1×10^{-6}	7,500	300	8	1	8,192
Qwen-2.5-14B	TreeRL (Hou et al., 2025)	acc: 20.8	-	acc: 81.7	acc: 44.6	-	-	-	✓	MATH-train, NuminaMath	480	-	1.5E-06	-	-	30	1.2	8K
	DCPO (Li et al., 2026d)	avg@1: 20	avg@1: 85	avg@1: 84.6	-	-	-	avg@1: 23.3	✓	DAPO-Math-17k, MATH (3-5)	512	32	-	25k	400	-	1.0	3K
	STEER (Hao et al., 2025)	avg@32: 19.3	avg@32: 14.0	avg@1: 81.6	avg@1: 46.3	avg@1: 39.1	-	avg@32: 70.3	✓	DAPO-Math-17k	512	32	1E-06	-	150	8	1.0	3K
Qwen-2.5-32B	DAPO (Yu et al., 2025)	avg@32: 50	-	-	-	-	-	-	✓	DAPO-Math-17K	-	512	1E-06	17K	-	16	-	20K
	M2PO (Zheng et al., 2025a)	avg@16: 24.8	avg@16: 19.4	avg@4: 85.7	avg@4: 51.7	avg@4: 41.5	-	avg@4: 76.3	✓	DeepScaleR Math	256	512	1E-06	-	1000	8	1.0	16K
	Clip-Cov (Cui et al., 2025)	avg@32: 32.3	avg@32: 22.7	avg@32: 87	avg@32: 57.2	avg@32: 46	-	-	✓	Eurus-2-RL-Math	256	128	5E-07	-	-	8	1.0	8K
	KL-Cov (Cui et al., 2025)	avg@32: 36.8	avg@32: 30.8	avg@32: 84.6	avg@32: 49	avg@32: 46.3	-	-	✓	Eurus-2-RL-Math	256	128	5E-07	-	-	8	1.0	8K
	FlowRL (Zhu et al., 2025)	avg@16: 23.95	avg@16: 21.87	avg@16: 80.75	avg@16: 51.83	avg@16: 38.21	-	-	✓	DAPO	512	-	1E-06	-	-	8	-	8K
	FR3E (Zheng et al., 2025b)	acc: 40.2	-	acc: 87.4	acc: 51.7	acc: 45.6	-	acc: 80	✓	DeepScaler, SimpleRL (3-5)	512	128	1E-06	-	-	16	-	16k

Table 9: Performance of Various Entropy-Based Methods on Mathematical Benchmarks – Qwen-2-Math Models (All Metrics)

Base Model	Method	AIME24	AIME25	MATH500	Olympiad	Minerva	MATH	AMC23	open-source	Train Data	Global Size	Mini Batch	Learn. Rate	Data Col.	Train. Steps	Rollout Num.	Samp. Temp.	Max Len.
Qwen-2.5-Math-1.5B	GRPO + D³S (Wang et al., 2025a)	pass@1: 11.2	pass@1: 6.9	-	pass@1: 10.6	pass@1: 23.5	pass@1: 53.7	pass@1: 48.6	✗	DeepScaleR	-	-	5E-07	-	-	32	1.0	-
	GSPO + D³S (Wang et al., 2025a)	pass@1: 11.4	pass@1: 8.2	-	pass@1: 10.5	pass@1: 22.9	pass@1: 54.0	pass@1: 48.4	✗	DeepScaleR	-	-	5E-07	-	-	32	1.0	-
	TTRL (Liu et al., 2025a)	pass@1: 15.8	-	pass@1: 73.0	-	-	-	-	✗	AIME24, AMC, MATH-500	-	-	5E-07	-	-	64/32	0.6	3K
	EDGE-GRPO (Zhang et al., 2025e)	pass@1: 10.0	-	pass@1: 73.20	pass@1: 37.33	pass@1: 29.04	-	-	✓	DeepScaleR-Random-1K, DeepScaleR-Hard-1K	-	-	1E-06	2k	1000	-	-	1K
	ETMR (Liu et al., 2025a)	pass@1: 21.0	-	-	pass@1: 76.9	-	-	-	✗	AIME24, AMC, MATH-500	-	-	-	-	-	-	-	-
	EMPO (Zhang et al., 2025b)	pass@1: 13.3	-	-	pass@1: 36.6	pass@1: 32.4	pass@1: 73.0	pass@1: 55.0	✓	-	-	-	-	-	-	-	-	-
	STEER (Hao et al., 2025)	avg@32: 17.2	avg@32: 9.7	avg@1: 75.4	avg@1: 36.9	avg@1: 28.0	-	avg@32: 61.3	✓	DAPO-Math-17k	512	32	1E-06	-	150	8	1.0	3K
	UCAS (Xie et al., 2025)	pass@1: 23.3	-	pass@1: 80.6	pass@1: 42.1	pass@1: 31.6	-	-	✓	MATH (3-5)	512	-	1E-06	-	-	16	1.0	3K
	AEnt (Shen, 2025)	acc: 21.7	-	acc: 75.0	acc: 37.7	acc: 33.0	-	-	✓	MATH	512	-	2E-06	7.5K	-	16	-	3K
	PRL (Yao et al., 2026a)	pass@8: 30.00	-	pass@8: 89.40	pass@8: 58.07	pass@8: 45.59	-	pass@8: 85.00	✗	NuminaMath	128	256	1×10^{-6}	150k	-	-	-	3072
	HIVE (Wu et al., 2026)	acc: 16.7	-	acc: 77.9	acc: 40.3	acc: 31.5	-	-	✗	DAPO, MATH, OPEN-R1	256	512	1×10^{-6}	-	1000	8	1	-
	AsymGRPO (Gu et al., 2026)	Avg@10: 18.67	Avg@10: 13.79	Avg@5: 74.45	Avg@5: 36.38	-	-	Avg@10: 55.25	✗	MATH (train)	512	128	2×10^{-6}	-	-	8	-	2560
Qwen-2.5-Math-7B	FR3E (Zheng et al., 2025b)	acc: 39.1	-	acc: 82.2	acc: 46.5	acc: 40.8	-	acc: 67.5	✓	DeepScaler, SimpleRL (3-5)	512	128	1E-06	-	-	16	-	16k
	ACPO (Yin et al., 2025)	acc@8: 34.2	acc@8: 16.25	acc@8: 83.4	-	-	-	acc@8: 71.9	✗	DAPO-17k	192	-	1E-06	-	-	-	1.0	-
	DCPO (Li et al., 2026d)	avg@1: 46.7	avg@1: 82.6	avg@1: 82.5	-	-	-	avg@1: 16.7	✓	Math-DAPO-17k, MATH (3-5)	512	32	-	25k	400	-	1.0	3K
	CANON-Inter (Chen et al., 2025a)	avg@10: 32.7	avg@10: 18.7	pass@1: 87.0	pass@1: 51.7	-	-	-	✓	OpenR1-Math-220k (45k subset)	-	-	1E-06	45k	-	16	-	8K
	Entropy Adv (Cheng et al., 2025)	pass@1: 33.7	pass@1: 17.6	pass@1: 83.1	-	-	-	pass@1: 69.8	✓	DAPO-Math-17K	512	32	1E-06	-	-	16	1.0	8K
	GRPO + D³S (Wang et al., 2025a)	pass@1: 20.3	pass@1: 7.9	-	pass@1: 10.7	pass@1: 25.0	pass@1: 52.2	pass@1: 54.4	✗	DeepScaleR	-	-	5E-07	-	-	32	1.0	-
	GSPO + D³S (Wang et al., 2025a)	pass@1: 18.3	pass@1: 8.3	-	pass@1: 11.5	pass@1: 28.4	pass@1: 54.9	pass@1: 53.2	✓	DeepScaleR	-	-	5E-07	-	-	32	1.0	-
	AEPO-Wang (Wang et al., 2025b)	pass@1: 50.0	-	pass@1: 42.4	pass@1: 47.4	pass@1: 43.3	pass@1: 82.0	-	✓	DAPO-17K	128	-	1E-06	-	-	-	-	2K
	SimKO (Peng et al., 2025)	pass@1: 32.8	pass@1: 12.9	pass@1: 77.6	pass@1: 39.8	pass@1: 35.0	-	pass@1: 62.4	✓	MATH	1K	256	1E-06	-	-	8	1.0	-
	EDGE-GRPO (Zhang et al., 2025e)	pass@1: 16.67	-	pass@1: 79.00	pass@1: 42.67	pass@1: 36.03	-	-	✓	DeepScaleR-Random-1K, DeepScaleR-Hard-1K	-	-	1E-06	2k	1000	-	-	1K
	EMPO (Zhang et al., 2025b)	pass@1: 20.0	-	-	pass@1: 37.3	pass@1: 40.4	pass@1: 78.0	pass@1: 65.0	✓	-	-	-	-	-	-	-	-	-
	GRPO+POSITION (Deng et al., 2025)	pass@4: 55.33	pass@4: 30.85	pass@4: 93.20	-	-	-	pass@4: 85.00	✓	STILL-3	512	32	1E-06	90K	-	-	1.0	8K
	GRPO+PPL (Deng et al., 2025)	pass@4: 56.89	pass@4: 33.18	pass@4: 94.40	-	-	-	pass@4: 87.50	✓	STILL-3	512	32	1E-06	90K	-	-	1.0	8K
	M2PO (Zheng et al., 2025a)	avg@16: 33.3	avg@16: 17.5	avg@4: 84.0	avg@4: 47.1	avg@4: 38.1	-	avg@4: 63.8	✓	DeepScaleR	256	512	1E-06	-	1000	8	1.0	16K
	CURE (Li et al., 2025b)	avg@32: 35.5 avg@1: 18.5	avg@16: 16.2	avg@32: 83.4 avg@1: 50.5	avg@1: 48.2	-	avg@1: 41.7	avg@32: 89.7	✓	DAPO-Math-17K	512	32	1E-06	17K	110	-	1.0	2596
	STEER (Hao et al., 2025)	avg@32: 36.9	avg@32: 16.2	avg@1: 82.4	avg@1: 43.3	avg@1: 41.7	-	avg@32: 72.2	✓	DAPO-Math-17k	512	32	1E-06	-	150	8	1.0	3K
	EM-1 shot (Gao et al., 2025)	-	-	avg@8: 78.8	avg@8: 39.7	avg@8: 35.3	-	avg@8: 70.3	✓	NuminaMath	64	2	2E-05	1.0	10	-	0.5	-
	UCAS (Xie et al., 2025)	pass@1: 43.3	-	pass@1: 85.6	pass@1: 48.0	pass@1: 37.6	-	-	✓	MATH (3-5)	512	-	1E-06	-	-	16	1.0	3K
	PRL (Yao et al., 2026a)	pass@8: 43.33	-	pass@8: 93.60	pass@8: 65.19	pass@8: 52.57	-	pass@8: 85.00	✓	NuminaMath	128	256	1×10^{-6}	150k	-	-	-	3072
	DCPO (Li et al., 2026d)	pass@32:35.2	acc:17.8	-	acc:43.70	acc:43.40	acc:82.0	-	✓	DAPO-Math-17k	512	128	1×10^{-6}	-	-	8	1	8192
	ID (Chen et al., 2026)	pass32: 33.1	pass32: 18.1	-	pass4: 48.3	-	-	-	✗	DAPO-Math-17k	512	-	1×10^{-6}	-	400	8	-	4096
	DID (Chen et al., 2026)	pass32: 31.5	pass32: 15.2	-	pass4: 47.8	-	-	-	✗	DAPO-Math-17k	512	-	1×10^{-6}	-	400	8	-	4096
	OD (Chen et al., 2026)	pass32: 31.1	pass32: 18.3	-	pass4: 47.5	-	-	-	✗	DAPO-Math-17k	512	-	1×10^{-6}	-	400	8	-	4096
	SCRL (Yan et al., 2026)	-	pass@1: 26.9	pass@1: 85.6	-	pass@1: 41.6	-	-	✓	AIME25 AMC MATH-500 Minerva GPQA	-	-	5×10^{-7}	-	-	16	1	3072
	HIVE (Wu et al., 2026)	acc: 36.7	-	acc: 93.0	acc: 43.8	acc: 34.8	-	-	✗	DAPO,MATH, OPEN-R1	256	512	1×10^{-6}	-	1000	8	1	-
	EAPO (He et al., 2026)	Avg@32:39.8 Pass@32: 68.9	Avg@32:17.2 Pass@32: 37.6	-	Avg@4:45.1 Pass@4:57.3	Avg@4:43.9 Pass@4:57.3	Avg@4:83.7 Pass@4:88.7	-	✗	DeepScaleR	512	32	1×10^{-6}	40,315	220	8	1	3072
	UEC-RL (Wang et al., 2026)	pass@1: 28.5	pass@1: 10.7	-	-	pass@1: 35.7	pass@1: 80.4	-	✓	DAPO-Math-17k	-	-	-	-	-	5	1	8192

Table 10: Performance of Various Entropy-Based Methods on Mathematical Benchmarks – Qwen-3 Models (All Metrics)

Base Model	Method	AIME24	AIME25	MATH500	Olympiad	Minerva	MATH	AMC23	open-source	Train Data	Global Size	Mini Batch	Learn. Rate	Data Col.	Train. Steps	Rollout Num.	Samp. Temp.	Max Len.
Qwen-3-1.7B	RL-ZVP (Le et al., 2025)	acc@8: 12.50 pass@8: 23.99	acc@8: 6.25 pass@8: 13.23	acc@8: 70.98 pass@8: 87.35	acc@8: 35.11 pass@8: 54.84	acc@8: 29.96 pass@8: 44.76	-	acc@8: 48.75 pass@8: 77.19	✗	MATH, NuminaMath-CoT	512	32	3E-06	27.5k	672	8	1.0	4K
	M2PO (Zheng et al., 2025a)	avg@16: 14.0	avg@16: 6.5	avg@16: 87.5	avg@4: 35.6	avg@4: 29.4	-	avg@4: 48.1	✓	DeepScaleR Math	256	512	1E-06	-	1000	8	1.0	4K
Qwen-3-4B	PEAR (Huang et al., 2025a)	acc@1: 56.66	-	acc@1: 84.00	-	-	-	acc@1: 87.50	✓	GSM8K	128	-	1E-06	7,473	-	8	0.6	16K
	AER (Zhang et al., 2025d)	pass@1: 25.2	pass@1: 22.1	pass@1: 86.7	-	-	-	pass@1: 70.2	✗	DeepscaleR	128	32	1E-06	-	-	-	-	8k
	M2PO (Zheng et al., 2025a)	avg@16: 26.7	avg@16: 21.0	avg@4: 85.8	avg@4: 52.3	avg@4: 40.5	-	avg@4: 64.4	✓	DeepScaleR Math	256	512	1E-06	-	1000	8	1.0	16K
	ROSE (Zhao et al., 2026)	pass@8: 23.33	pass@8: 23.33	pass@8: 80.80	-	-	-	pass@8: 77.50	✓	MATH	512	-	1×10^{-6}	7500	-	8	-	-
	ENTRA (Cai et al., 2026)	-	-	acc: 93.20	-	-	-	-	✓	MATH, Weekly12K	-	-	-	2000	200	-	0.6	38912
	DCPO (Li et al., 2026d)	pass@32:56.6	acc:42.7	-	acc:61.40	acc:48.20	-	-	✓	DAPO-17K	512	128	1×10^{-6}	-	-	8	1	8192
	AsymGRPO (Gu et al., 2026)	Avg@10: 39.33	Avg@10: 28.67	Avg@5: 89.33	Avg@5: 58.48	-	-	Avg@10: 81.00	✗	MATH	128	64	2×10^{-6}	-	-	8	-	4096
	ETR (Xiong et al., 2026)	pass@1: 73.3	-	pass@1: 91.4	-	-	-	pass@1: 90.0	✓	DeepMath-103K	32	16	1×10^{-5}	7,000	207	5	1	16384
	Policy Split (Yao et al., 2026b)	-	-	-	-	-	acc: 94.12	-	✗	DeepMath-103K	256	-	3×10^{-6}	20K	-	8	-	12,288
	Entrocraft (Li et al., 2026a)	-	mean@32: 15.1 pass@32: 46.7	mean@32: 79.0 pass@32: 93.0	-	-	-	mean@32: 65.0 pass@32: 95.0	✓	Numina-Math	1024	-	1×10^{-6}	100K	-	8	-	4096
Qwen-3-8B	PEAR (Huang et al., 2025a)	acc@1: 60.00	-	acc@1: 85.40	-	-	-	acc@1: 92.50	✓	GSM8K	128	-	1E-06	7,473	-	8	0.6	16K
	AER (Zhang et al., 2025d)	pass@1: 31.4	pass@1: 25.1	pass@1: 89.4	-	-	-	pass@1: 75.6	✓	DeepscaleR	128	32	1E-06	-	-	-	-	8k
	QAE+CLIP-Cov (Wu et al., 2025b)	pass@1: 46.04	pass@1: 37.40	-	-	-	-	pass@1: 90.23	✓	DAPO-Math-17K	512	32	1E-06	-	-	32	0.7	20K
	QAE+Clip-Higher (Wu et al., 2025b)	pass@1: 48.23	pass@1: 34.90	-	-	-	-	pass@1: 92.97	✓	DAPO-Math-17K	512	32	1E-06	-	-	32	0.7	20K
	QAE+KL-Cov (Wu et al., 2025b)	pass@1: 44.69	pass@1: 33.44	-	-	-	-	pass@1: 87.97	✓	DAPO-Math-17K	512	32	1E-06	-	-	32	0.7	20K
	RL-ZVP (Le et al., 2025)	acc@8: 33.33 pass@8: 54.66	acc@8: 24.58 pass@8: 39.36	acc@8: 89.73 pass@8: 96.13	acc@8: 58.20 pass@8: 72.28	acc@8: 45.96 pass@8: 58.83	-	acc@8: 78.75 pass@8: 94.18	✗	DAPO-Math-17k, NuminaMath-CoT	512	32	3E-06	37k	1056	16	1.0	8K
	M2PO (Zheng et al., 2025a)	avg@16: 30.2	avg@16: 23.1	avg@8: 83.00	avg@4: 54.8	avg@4: 42.6	-	avg@4: 71.3	✓	DeepScaleR Math	256	512	1E-06	-	1000	8	1.0	16K
	ROSE (Zhao et al., 2026)	pass@8: 33.33	pass@8: 30.00	pass@8: 83.00	-	-	-	pass@8: 80.00	✓	MATH	512	-	1×10^{-6}	7500	-	8	-	-
	ENTRA (Cai et al., 2026)	-	-	acc: 94.80	-	-	-	-	✗	MATH, Weekly12K	-	-	-	2000	200	-	0.6	38912
	DISPO (Karaman et al., 2026)	avg@16: 45.00	avg@16: 31.46	avg@16: 92.34	-	avg@16: 44.60	-	avg@16: 87.66	✓	GSM8K Math Mathematics	-	32	1×10^{-6}	-	-	16	1	20,480
	ETR (Xiong et al., 2026)	pass@1: 73.3	-	pass@1: 93.6	-	-	-	pass@1: 92.5	✓	DeepMath-103K	32	16	1×10^{-5}	7,000	207	5	1	16384
	Policy Split (Yao et al., 2026b)	-	-	-	-	-	acc: 94.40	-	✗	DeepMath-103K	256	-	3×10^{-6}	20K	-	8	-	12,288