Unveiling Source of Performance Variance on Searching-based Compiler Optimization

MLArchSys 2022 Submission **#10** – Confidential Draft – Do NOT Distribute!!

Abstract—In order to squeeze out the performance in the post-Moore era, compiler auto-tuning approach has been widely studied and productized. Despite its superior efficiency in compiler optimization problems, performance variance in final tuning output has long been an issue for searching-based auto-tuning methods. It poses a challenge to research reproducibility and production stability. In general, the causes of such performance variance come from many aspects across different system layers. In addition to generic causes, we observe that auto-tuners add unique sources of variance, including the use of different search methods and cost models.

In this work, we specifically focus on the performance variance originating from the nature of auto-tuning. Based on our observation, we set three major hypotheses on search method, cost model, and hardware characteristics. Then, we validated our hypotheses through experiments with a production auto-tuner and a representative set of machine learning workloads. Our result suggests impactful factors to consider in the future auto-tuner design.

I. INTRODUCTION

As the performance from hardware innovations is stagnating due to the end of Moore's Law [10], leveraging latent opportunities in compiler optimization space is becoming more critical. However, the ever-increasing complexity in hardware and software stacks makes even the most advanced compilers fail to deliver the best optimization settings for individual workloads from time to time. It strongly motivates the recent efforts in auto-tuning approach in both industry and academia [1], [6], [8], [9], [11], [12], [14]–[16].

Most auto-tuning techniques are essentially an iterative feedback-directed search in the optimization space - promising candidates are generated, evaluated, and reflected upon to generate even more promising candidates for future tuning trials. Evaluation is usually conducted by the actual compilation and run-time measurement for the sake of high accuracy. However, due to its expensive cost, recent studies introduce various cost models that can select superior candidates without the actual measurement [2], [5], [13]. One popular approach is to train a learning-based cost model on-the-fly by using the run-time samples collected during the tuning process. And then, auto-tuning methods can use this cost model to filter out non-promising candidates cheaply and evaluate only the promising ones with the actual measurement. In addition, to effectively explore the extremely huge and complicated optimization search space, these auto-tuning methods adopt intelligent search methods to make the best use of the feedback from the evaluation. Evolutionary search [16], multi-armed bandit [14], ensemble search [1] and reinforcement learning [6], [9] are representative examples.

Overall, the auto-tuning approach has successfully demonstrated its strong performance and is widely deployed in the industry [6], [11], [12], [15], [16]. However, performance variance in the final tuning outcome has been problematic and one of the major challenges to reproducibility and production stability of auto-tuning methods. The source of variance can be diverse and laid across the multiple system layers ranging from hardware to software stacks (e.g., non-deterministic behavior of hardware, interrupt from the operating system, etc.). Also, auto-tuners add another source of variance. For example, since most search methods are randomization-based, the search pattern may differ across tuning runs.

To address this problem, we investigate the representative root causes for the performance variance. Specifically, this work focuses on the unique sources of variance that originated from the nature of the auto-tuning approach. Based on our experience with production auto-tuners, we set three hypotheses on search method, cost model, and hardware property. Then, we conduct experiments to verify each of the hypotheses. Given the importance of the problem, we believe this is a meaningful step forward to attack a long-standing concern in auto-tuners.

The contributions of this paper are as follows:

- We discuss the unique source of performance variance in the popular auto-tuning approach and set three hypotheses to assess their influence.
- We analyze our hypotheses with the production auto-tuner and the representative machine learning workloads on AWS Cloud instances.
- Future works outline our next steps to address this enormous challenge in the auto-tuning approach.

II. POTENTIAL SOURCES OF PERFORMANCE VARIANCE IN AUTO-TUNERS

Figure 1 illustrates the overarching workflow of the popular auto-tuning approach with a learning-based cost model [2], [5], [16]. Once users provide the tuning budget (e.g., number of candidate trials), auto-tuners repeatedly perform four steps using its three major components: search method, cost model, and measurer. First off, search method, such as evolutionary search [7], generates a set of promising candidates and queries the cost model to predict the competency between candidates and filter out non-promising ones. Then, the measurer takes the filtered candidates and evaluates them on the actual hardware. It accompanies the actual compilation that applies the optimization setting in each candidate and the run-time measurement of the compiled executable. Once the run-time

Fig. 1: Representative auto-tuning workflow with three major components: search method, cost model and measurer. Within the predefined tuning budget (e.g., number of candidate trials, wall-clock time), these components in the auto-tuner repeat the four steps by working together closely.

performance is collected, it will be provided as feedback to both search method and cost model. Search method will use the run-time performance as the feedback to generate more promising candidates in the next iteration (e.g., mutation and cross-over in the evolutionary search [7]). On the other hand, the cost model will use the run-time performance for its training process. Furthermore, recent work [17] has shown that past performance tuning datasets could be leveraged to pretrain the cost model.

Because every component interacts very closely with each other, a slight difference in the behavior of one component may lead to quite different outcomes across tuning runs. For example, popular search methods [1], [6], [7] leverage random search to certain extent, especially at the beginning of the tuning process. Unfortunately, some source of non-determinism is inevitable - it is impossible to completely eliminate run-time noise during the measurement. Also, search methods require some randomness for their statistical efficiency. Therefore, in this work, we examine three aspects that we may be able to improve in the future auto-tuner design.

A. Hypothesis 1: search method may generate imbalanced training data for the cost model.

We observe the potential dilemma between search method and the cost model. In order to find out the best candidates, search method exploits the previous feedback to effectively cut down the search space and focus on the narrowed promising space. Ironically, this may imply the generation of biased training data for the cost model.

B. Hypothesis 2: instability of cost model accuracy may affect final performance variance.

Since the cost model is constructed online, it is not clear if training data collected during the tuning process is enough to make the cost model's accuracy mature and stable enough. Also, *Hypothesis 1* adds another source of variance in its accuracy across tuning runs.

C. Hypothesis 3: certain hardware and its target-specific optimization may inherently have higher run-time variance than others.

Non-determinism in hardware behavior incurs some run-time noise in the measurer and results in noisy feedback that may guide the search in a biased direction. If certain hardware is intrinsically noisier, the auto-tuner may consider this factor in its strategy of utilizing feedback.

III. EVALUATION

A. Experiment Setup

1) Auto-tuner: For experiments, we investigate the new auto-tuning technology based on TVM [4] called MetaSchedule. MetaSchedule is a tuning framework that follows the auto-tuning framework in Figure 1.

The search space of any tensor program is defined as different ways to lower and execute the model without impacting its results, for example, how to tile the loops and whether to vectorize the innermost loop in workloads. The tuner will generate potential tuning search space for a given workload. All the candidates are selected from a certain search space. We defined the search space using the default optimization rules for CPU and GPU defined in TVM MetaSchedule, including multilevel tiling, loop unrolling and vectorization, etc.

The search space grows exponentially as the number of loops increases, so a search strategy is defined and applied to generate measurement candidates in the search space. For example, the random search strategy can explore the search space via randomization. In contrast, the evolutionary search strategy can generate new measurement candidates based on the results from previous rounds of auto-tuning.

In order to maximize auto-tuning efficiency, we utilize the cost model to extract features, predict the candidates' performance, and select candidates with the most potential for measurement. Selected candidates are then compiled and measured by the evaluator. The measurement results are used for later end-to-end compilation, cost model update, and search strategy update.

2) Workloads: We select 5 representative tensor programs to conduct all the experiments, covering most compute-intensive subgraphs in end-to-end model tuning. The workloads are as follows:

- *C2D:* 2-D Convolution, NHWC layout;
- *C3D:* 3-D Convolution, NHWC layout;
- *GMM:* Batch Matrix Multiplication;
- *T2D:* Transposed 2-D Convolution, NHWC layout;
- *TBG:* Transposed Batch Matrix Multiplication

3) Hardware: Our experiments are all based on AWS EC2 machines. CPU experiments are conducted on `c5.9xlarge` machine with 36 Intel(R) Platinum 8223CL CPU @ 3.00GHz vCPUs. GPU experiments are conducted on `p3.2xlarge` machine with an NVIDIA V100 GPU.

In order to separate autotuning from measurement, we used another AWS Cloud machine (`c5.12xlarge`) to do tuning and conduct measurement via TVM's RPC module. TVM's

(a) Examine *Hypothesis 1* on CPU: Comparison of evolutionary search (default search method in MetaSchedule, denoted in *EvoSearch*) and random search. Random search shows more stable results across tuning runs despite its lower performance.

(b) Examine *Hypothesis 2* on CPU: Comparison of evolutionary search with XGBoost [3] (default cost model in MetaSchedule) and evolutionary search without cost model (no filtering step in Figure 1). Variance seems lower when cost model is disabled. Interestingly, final performance is pretty close on *GMM* and *TBG*. On *C3D*, the search without any cost model even outperforms the one with the cost model.

(c) Examine *Hypothesis 3*: Comparison of the variance between CPU and GPU experiments. In every workload, CPU showed more stable performance despite its lower performance.

Fig. 2: Experiments to validate our hypotheses. We plotted their tuning progress by targeting five representative deep learning workloads and collecting the best performance in GFLOPS, together with latency at each trial. AWS instances of `c5.9xlarge` (36 Intel Xeon Platinum 8223CL vCPUs) and `p3.2xlarge` (NVIDIA V100 GPU) are used for CPU and GPU experiments correspondingly. Each experiment included five tuning runs, each consuming 2,000 trials. The shaded area shows the performance variance at each trial. In general, we observe that the performance variance alleviates as tuning proceeds.

TimeEvaluator module is explicitly used for workload running time measurements.

B. Result

Figure 2 presents our experimental results. Overall, tuning jobs experience high variance during early phases and stabilize their performance as the tuning proceeds. However, in some tuning workloads, such as *T2D*, the variance gets larger. Our future study will examine this further (e.g., assign more trials).

- *Hypothesis 1: search method may generate imbalanced training data for cost model.*

  To validate this hypothesis, we compare the tuning progress between evolutionary search (*EvoSearch*) and random search. Since random search explores search space without any feedback, it would generate the most balanced training data that can be collected during the tuning process. Figure 2a presents the experimental result. Since random search does not use any intelligence during candidate generation, it generally shows worse performance than evolutionary search. However, it consistently demonstrates stability by exhibiting less performance variance across workloads. Especially, random search showcases significantly better stability in *C3D*, *T2D* and *TBG*.

- *Hypothesis 2: instability of cost model accuracy may affect final performance variance.*

  In order to compare, we conduct tuning runs with a cost model (XGBoost) and without it. Without any cost model,

all promising candidates generated by evolutionary search will be evaluated with measurer (See Figure 1). Note that these two experiments had an equal number of measurements during each tuning instance (i.e., 1 trial = 1 measurement), so the overall tuning time stays similar as overhead in the measurer usually dominates the overall tuning time. Figure 2b presents the result.

Overall, we could stabilize the performance variance by disabling the cost model. With the cost model, the variance on most workloads (i.e., All but *GMM*) does not improve and gets worse often. We suspect this might be attributed to the unstable cost model accuracy with the online training approach. Future work may assign more trials to see if the variance improves with more training samples for the cost model.

- *Hypothesis 3: certain hardware and its target-specific optimization may inherently have higher run-time variance than others.*

Figure 2c exhibits default MetaSchedule tuning (i.e., evolutionary search with cost model) on two separate hardware architectures – CPU (Intel Xeon Platinum 8223CL) and GPU (NVIDIA V100) machines. Although GPU shows higher performance throughput in every workload, it generally presents worse variance. Especially, variance in *T2D* is significant.

Such difference in hardware performance variance could be attributed to the difference during search space construction - some optimization rules could be hardware-specific, especially layout-related rules. Also, the use of the cost model further enhanced such difference. On the other hand, the different memory architectures in CPU and GPU resulted in distinct performance sensitivity on tensor program compilation. Minor changes in GPU memory access patterns may bring an enormous performance leap compared to CPU. Future work can set up the same optimization search space to different hardware and further explore their characteristics.

IV. FUTURE DIRECTION AND CONCLUSION

This work investigates the performance variance problem in the popular compiler auto-tuning approach. By focusing on the causes of such variance that originates from the nature of auto-tuning, we suggest three factors to consider to alleviate the performance variance in the future design of auto-tuners: Firstly, search method may consider both the search process itself and the balance of training data for the cost model. Future studies may examine the ratio of randomly generated candidates and see its impact on the balance of training data. Secondly, we may need to take a deeper look at the training progress of the cost model. If a standard tuning budget is insufficient to reach stable accuracy, we may consider offline tuning or transfer learning. Last but not least, we show that certain hardware can be inherently noisier than others. Our future investigation may examine a statistical approach to cope with this issue gracefully.

REFERENCES

[1] J. Ansel, S. Kamil, K. Veeramachaneni, J. Ragan-Kelley, J. Bosboom, U.-M. O'Reilly, and S. Amarasinghe, "Opentuner: An extensible framework for program autotuning," in *Proceedings of the 23rd international conference on Parallel architectures and compilation*, 2014, pp. 303–316.

[2] R. Baghdadi, M. Merouani, M.-H. Leghettas, K. Abdous, T. Arbaoui, K. Benatchba *et al.*, "A deep learning based cost model for automatic code optimization," *Proceedings of Machine Learning and Systems*, vol. 3, pp. 181–193, 2021.

[3] T. Chen, T. He, M. Benesty, V. Khotilovich, Y. Tang, H. Cho, K. Chen *et al.*, "Xgboost: extreme gradient boosting," *R package version 0.4-2*, vol. 1, no. 4, pp. 1–4, 2015.

[4] T. Chen, T. Moreau, Z. Jiang, L. Zheng, E. Yan, H. Shen, M. Cowan, L. Wang, Y. Hu, L. Ceze, C. Guestrin, and A. Krishnamurthy, "TVM: An automated End-to-End optimizing compiler for deep learning," in *13th USENIX Symposium on Operating Systems Design and Implementation (OSDI 18)*. Carlsbad, CA: USENIX Association, Oct. 2018, pp. 578–594. [Online]. Available: https://www.usenix.org/conference/osdi18/presentation/chen

[5] T. Chen, L. Zheng, E. Yan, Z. Jiang, T. Moreau, L. Ceze, C. Guestrin, and A. Krishnamurthy, "Learning to optimize tensor programs," *Advances in Neural Information Processing Systems*, vol. 31, 2018.

[6] C. Cummins, B. Wasti, J. Guo, B. Cui, J. Ansel, S. Gomez, S. Jain, J. Liu, O. Teytaud, B. Steiner *et al.*, "Compilergym: Robust, performant compiler optimization environments for ai research," in *2022 IEEE/ACM International Symposium on Code Generation and Optimization (CGO)*. IEEE, 2022, pp. 92–105.

[7] F.-A. Fortin, F.-M. De Rainville, M.-A. G. Gardner, M. Parizeau, and C. Gagné, "Deap: Evolutionary algorithms made easy," *The Journal of Machine Learning Research*, vol. 13, no. 1, pp. 2171–2175, 2012.

[8] G. Fursin, Y. Kashnikov, A. W. Memon, Z. Chamski, O. Temam, M. Namolaru, E. Yom-Tov, B. Mendelson, A. Zaks, E. Courtois *et al.*, "Milepost gcc: Machine learning enabled self-tuning compiler," *International journal of parallel programming*, vol. 39, no. 3, pp. 296–327, 2011.

[9] A. Haj-Ali, N. K. Ahmed, T. Willke, Y. S. Shao, K. Asanovic, and I. Stoica, "Neurovectorizer: End-to-end vectorization with deep reinforcement learning," in *Proceedings of the 18th ACM/IEEE International Symposium on Code Generation and Optimization*, 2020, pp. 242–255.

[10] J. Hennessy and D. Patterson, "A new golden age for computer architecture: Domain-specific hardware/software co-design, enhanced."

[11] B. Jeon, S. Park, P. Liao, S. Xu, T. Chen, and Z. Jia, "Collage: Automated integration of deep learning backends," *arXiv preprint arXiv:2111.00655*, 2021.

[12] Z. Jia, O. Padon, J. Thomas, T. Warszawski, M. Zaharia, and A. Aiken, "Taso: optimizing deep learning computation with automatic generation of graph substitutions," in *Proceedings of the 27th ACM Symposium on Operating Systems Principles*, 2019, pp. 47–62.

[13] S. Kaufman, P. Phothilimthana, Y. Zhou, C. Mendis, S. Roy, A. Sabne, and M. Burrows, "A learned performance model for tensor processing units," *Proceedings of Machine Learning and Systems*, vol. 3, pp. 387–400, 2021.

[14] S. Park, S. Latifi, Y. Park, A. Behroozi, B. Jeon, and S. Mahlke, "Srtuner: Effective compiler optimization customization by exposing synergistic relations," in *2022 IEEE/ACM International Symposium on Code Generation and Optimization (CGO)*. IEEE, 2022, pp. 118–130.

[15] P. M. Phothilimthana, A. Sabne, N. Sarda, K. S. Murthy, Y. Zhou, C. Angermueller, M. Burrows, S. Roy, K. Mandke, R. Farahani *et al.*, "A flexible approach to autotuning multi-pass machine learning compilers," in *2021 30th International Conference on Parallel Architectures and Compilation Techniques (PACT)*. IEEE, 2021, pp. 1–16.

[16] L. Zheng, C. Jia, M. Sun, Z. Wu, C. H. Yu, A. Haj-Ali, Y. Wang, J. Yang, D. Zhuo, K. Sen *et al.*, "Ansor: Generating {High-Performance} tensor programs for deep learning," in *14th USENIX Symposium on Operating Systems Design and Implementation (OSDI 20)*, 2020, pp. 863–879.

[17] L. Zheng, R. Liu, J. Shao, T. Chen, J. E. Gonzalez, I. Stoica, and A. H. Ali, "Tenset: A large-scale program performance dataset for learned tensor compilers," in *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 1)*, 2021.