Dynamic Fair Division with Partial Information

Abstract

We consider the fundamental problem of fairly and efficiently allocating T indivisible items among n agents with additive preferences. The items become available over a sequence of rounds, and every item must be allocated immediately and irrevocably before the next one arrives. Previous work shows that when the agents' valuations for the items are drawn from known distributions, it is possible (under mild technical assumptions) to find allocations that are envy-free with high probability and Pareto efficient ex-post.

We study a *partial-information* setting, where it is possible to elicit ordinal but not cardinal information. When a new item arrives, the algorithm can query each agent for the relative rank of this item with respect to a subset of the past items. When values are drawn from i.i.d. distributions, we give an algorithm that is envy-free and $(1-\epsilon)$-welfare-maximizing with high probability. We provide similar guarantees (envy-freeness and a constant approximation to welfare with high probability) even with minimally expressive queries that ask for a comparison to a single previous item. For independent but non-identical agents, we obtain envy-freeness and a constant approximation to Pareto efficiency with high probability. We prove that all our results are asymptotically tight.

1 Introduction

We consider the following fundamental problem in fair division. A set of T indivisible items, arriving one at a time, must be allocated among a set of n agents with additive preferences. The value $v_{i,t}$ that agent i has for the item in round t is realized once the item arrives. Each item must be allocated immediately and irrevocably upon arrival, and we ask that the overall allocation is *fair* and *efficient*.

Previous work on this problem shows that, despite the uncertainty about future valuations, one can achieve simultaneous fairness and efficiency when agents' values are stochastic. Specifically, when each $v_{i,t}$ is drawn i.i.d. from a distribution D, the simple algorithm that maximizes welfare — each item is allocated to the agent with the highest value — is envy-free with high probability and (obviously) ex-post Pareto efficient [DGK$^+$14, KPW16]. The same guarantee holds for independent and non-identical agents ($v_{i,t}$ is drawn from an agent-specific distribution D_i) for the algorithm that maximizes weighted welfare [BG22]. Even when agents' valuations for an item are correlated (but items are independent), Pareto efficiency ex-post is compatible with strong fairness guarantees ("envy-freeness with high probability or envy-freeness up-to-one item ex-post") [ZP20].

Despite the computational simplicity of (most of) the aforementioned algorithms, an unappealing aspect, especially from a practical perspective, is the requirement that agents report an exact numerical value for each item. Eliciting expressive additive valuations can be impractical, e.g., due to agents' cognitive limitations. Motivated by such considerations, a growing body of work in AI studies what can be achieved by algorithms that only elicit *ordinal* information. This idea originates from [PR06], who defined the notion of distortion to measure the worst-case de-

terioration of an aggregate cardinal objective (e.g., utilitarian social welfare) due to only having access to preferences of limited expressiveness, particularly ordinal rankings. Recent works prove bounds on the distortion in the context of many problems in social choice, e.g., voting [CNPS17, GKM17, MSW20, MW19, Kem20a, Kem20b, GHS20], matching [FRFZ14], and participatory budgeting [BNPS21]; see [AFRSV21] for a recent survey.

In this paper, we study the power and limits of eliciting ordinal information in dynamic fair division. The value $v_{i,t}$ of agent i for item t is drawn from an *unknown* distribution upon arrival, and the algorithm is provided, from each agent, partial ordinal information about this item, e.g., its rank relative to the past items allocated to this agent, or even just a single past item allocated to this agent. Under what distributional assumptions and elicitation constraints, can we simultaneously achieve qualitative fairness and efficiency? We answer these questions.

Our contribution. We start by establishing a separation between the cardinal setting and our ordinal one. Pareto efficiency alone is trivial (allocate all goods to the same agent) and, in the cardinal setting, it is known that Pareto efficiency ex-post is compatible with envy-freeness with high probability (as long as agents are independent). We prove (Theorem 4) that in our setting, even for the case of two i.i.d. agents and any *known* distribution, envy-freeness with high probability is incompatible with even a very mild notion of (exact) Pareto efficiency, one-swap-Pareto efficiency, which requires that there is no beneficial one-to-one trade of items between agents (but allows for improvements via many-to-many trades of items).

We proceed to give an essentially matching positive result. For any number of i.i.d. agents and an unknown distribution D, there exists an algorithm (Algorithm 1) that is envy-free with high probability and guarantees a $(1 - \varepsilon)$-approximation to the optimal utilitarian social welfare (the sum of utilities), for all $\varepsilon > 0$, with high probability (Theorem 5). When an item arrives, the algorithm learns for each agent i its relative rank compared to a subset of prior items allocated to agent i (but otherwise knows nothing about the underlying numerical valuation). Our algorithm works in epochs. Each epoch has an exploration/sampling phase, where each agent gets a pre-determined number of items, followed by an exploitation/ranking phase, where each fresh item is given to an agent whose empirical quantile is largest. The goal is to make a sublinear number of errors compared to the "ideal" algorithm that allocates each item to the agent with the highest true quantile. The algorithm has to balance the need for sampling, which leads to more accurate empirical quantiles, against the number of inefficient allocations made while sampling. A significant technical barrier is that we cannot fix a target accuracy because the underlying distribution is unknown. That is, for every fixed accuracy for the empirical quantiles, there exists a distribution for which this accuracy is not good enough for even a constant approximation to the optimal welfare. Instead, we need to make our epochs progressively longer, thereby guaranteeing progressively better bounds.

Given this strong positive result, we explore the limits of what we can achieve when further restricting the amount of information available. What if each agent can remember only a *single* item previously allocated to them, and the fresh item is compared to just this one item?[1] Surprisingly, the aforementioned positive result can almost be recovered even in this very restrictive setting. We prove that there exists an algorithm (Algorithm 2) that is envy-free with high probability and guarantees a $(1 - 1/e)^2 - \varepsilon$ approximation to the optimal welfare with high probability, for all $\varepsilon > 0$ (Theorem 9). Our algorithm again proceeds in epochs with gradually increasing exploration and exploitation phases; this time the goal is a sublinear number of differences compared to allocating each item to a uniformly random agent with quantile at least $1 - 1/n$, which we prove is envy-free and approximately efficient (Lemmas 2 and 1). When exploring, the algorithm puts a new item in memory, estimates its quantile, and rejects it if not sufficiently close to $1 - 1/n$. We need to sample enough to ensure high confidence in the estimated quantile, but also account for the additional sampling since an item's quantile value might be far from $1 - 1/n$ to begin with; several technical details need to be accounted for. We give a near-matching lower bound: no algorithm with a memory of one item can achieve a $0.999-$approximation to the social welfare with high probability; therefore a constant approximation (which Algorithm 2 provides) is all we can hope for.

Finally, we relax the i.i.d. condition and study agents that are independent but not identical; each agent i's values are drawn from an unknown distribution D_i. Even with unbounded memory, we show that it is impossible to get a $18/19$ approximation to Pareto efficiency with probability more

---

[1]So, the algorithm only learns if the new item is better or worse than the item in memory and may, at that time, choose to replace the item in memory.

than 2/3, even for two agents (Theorem 12). At the same time, we prove that Algorithms 1 and 2 are envy-free and $1/e$ approximately Pareto efficient with high probability! Note that, though both algorithms give the same formal guarantees and Algorithm 2 elicits strictly less information, one might still prefer to use Algorithm 1 since it has significantly shorter exploration phases.

We leave the study of correlated agents as an interesting open problem. Finally, we note that beyond stochastic valuations, [BKPP18] show that it is possible to achieve sublinear envy by randomly allocating every item when agents' valuations are adversarially generated (and this is optimal); however, sublinear envy is incompatible with non-trivial efficiency even in the cardinal setting [ZP20].

Related Work. A number of works study fair division under ordinal preferences, e.g., [AGMW15, BEL10, BBL+17, NNR17], but often these models do not assume an underlying cardinal model and work directly on the ordinal preferences. [ABM16] assume underlying cardinal information and, among other results, bound the approximation ratio of truthful mechanisms that elicit rankings. Closer to our work, [HS21] study rules that have access to the ranking of the top-k items of each agent and bound the ratio of the social welfare of the allocation returned by a rule in the worst case. They also characterize the value of k needed to achieve prominent notions of fairness, namely envy-freeness up to one item (EF1) and approximate maximin share guarantee (MMS), as well as bound the loss in efficiency incurred due to fairness constraints in this setting.

Our work contributes to the growing literature in dynamic fair division [KPS14, AAGW15, FPV15, FPV17, BKPP18, HPPZ19, ZP20, GPT21, BKM22, GBI21, VPF21] (and we note that the welfare-maximizing algorithms of [DGK+14, KPW16, BG22] work in the dynamic setting, even though the their settings are not explicitly dynamic). To the best of our knowledge, we are the first to study imperfect expressivity in a dynamic setting in fair division.

2 Preliminaries

A set of T indivisible items/goods, labeled by $\mathcal{G} = \{1, 2, \cdots, T\}$, needs to be allocated to a set of n agents, labeled by $\mathcal{N} = \{1, \ldots, n\}$. Agent $i \in \mathcal{N}$ assigns a value $v_{i,t} \in [0, 1]$ to item $t \in \mathcal{G}$. We assume agents have *additive* valuation functions, so $v_i(S) = \sum_{t \in S} v_{i,t}$ for $S \subseteq \mathcal{G}$. An allocation A is a partition of the items into bundles $A_1, \ldots, A_n$, where A_i is the set of items assigned to agent $i \in \mathcal{N}$. Each allocation has an associated utility profile $v(A) = (v_1(A_1), \ldots, v_n(A_n))$.

Items arrive online, one per round. The agents' valuations for the item in round t (the t-th item) are realized when the item arrives. Every item is allocated immediately and irrevocably before moving on to the next round. We write $\mathcal{G}^t = \{1, 2, \cdots, t\}$ for the set of items that arrived in the first t rounds, and A_i^t for the allocation of agent i after the t-th item was allocated. We consider two different models which specify how values are generated. In the **i.i.d. model**, the value of agent i for item t is independently drawn from an *unknown* distribution D with CDF F, i.e., $v_{i,t} \sim D$ for all $i \in \mathcal{N}$ and $t \in \mathcal{G}$. In the **non-i.i.d. model**, the value of item t for agent i is independently drawn from an *unknown*, agent-dependent distribution D_i with CDF F_i, i.e., $v_{i,t} \sim D_i$ for all $i \in \mathcal{N}$ and $t \in \mathcal{G}$. We write X_i for the random variable for i's valuation, and $X_{i,t}$ for the random variable for i's valuation for item t. It is often convenient to work directly with the quantile of an agent's value rather than the value itself; let $Q_i = F_i(X_i)$ and $Q_{i,t} = F_i(X_{i,t})$ respectively be the random variable denoting the quantile of agent i the associated item. Note that all Q_i and $Q_{i,t}$ are i.i.d. and follow a $\text{Unif}[0, 1]$ distribution. Unless explicitly stated otherwise, we assume all distributions are continuous and bounded.

Ordinal information. We assume the realizations $v_{i,t}$ are not available. Instead, our algorithms have access to *ordinal* information. Specifically, given current item t, the algorithm can access each agent's *ranking* for $S = \{t\} \cup M$, $M \subseteq \mathcal{G}^{t-1}$. The size of M, which we will informally refer to as the *memory size*, determines the complexity of eliciting information from each agent. In one extreme, agent i compares a new item t to a single item they had previously received, i.e., $M \subseteq A_i^{t-1}, |M| \leq 1$. In the other extreme, t is compared to all previous items she received, so $M = A_i^{t-1}$. We write $\sigma_i(S)$ for the ranking of agent i for a subset S of the items, and $\sigma_i^{-1}(S, t)$ for the position of item $t \in S$ with respect to a subset S according to agent i. The highest value item is in position 1 and the lowest in position $|S|$. For example, if $S = \{1, 4\}$, $v_{i,1} = 1$ and $v_{i,4} = 0.1$, $\sigma_i(S) = (1 \succ 4)$, $\sigma_i^{-1}(S, 1) = 1$ and $\sigma_i^{-1}(S, 4) = 2$.

Algorithms. An algorithm $\mathcal{A}$, in each step t, queries each agent for ordinal information with respect to some subset M and then makes a (possibly randomized) allocation decision based on this ordinal information and the history so far. An instance of our problem is parameterized by the number of agents n and the (unknown) value distributions $D_1, \ldots, D_n$. Let $\mathcal{E}_P(t)$ be the event that some algorithm satisfies property P (e.g., envy-freeness or PO or ε-welfare) at time t. We are interested in the probability that an algorithm satisfies certain properties in the limit, as the number of rounds tends to infinity, where the randomness is over the random choices of the algorithm as well as the randomness in the valuations.

Definition 1. An algorithm satisfies P with high probability if $\lim_{t \to \infty} \Pr[\mathcal{E}_P(t)] = 1$.

Note that this definition of high probability allows for dependency on n and the underlying distributions (i.e., they are treated as constants).

Efficiency notions. An allocation A Pareto dominates an allocation A', denoted $A \succ A'$, when $v_i(A_i) \geq v_i(A_i')$ for all $i \in \mathcal{N}$ and there exists $j \in \mathcal{N}$ with $v_j(A_j) > v_j(A_j')$. An allocation A is *Pareto efficient* or *Pareto optimal* (PO) if there is no feasible (integral) allocation that Pareto dominates it. An allocation A' is in the (one) swap-neighborhood of A when it can be created from A with a single exchange of items between one pair of agents. Formally, there exist $i, j \in \mathcal{N}$ and items $z_j \in A_j$ and $z_i \in A_i$ so that $A_i' = (A_i \setminus \{z_i\}) \cup \{z_j\}$, $A_j' = (A_j \setminus \{z_j\}) \cup \{z_i\}$, and $A_k' = A_k$ for all other agents $k \neq i, j$. An allocation A is *one-swap Pareto optimal* (SPO) if it is undominated by any allocation in its swap-neighborhood. We use a notion of approximate efficiency defined by [RF90] according to which an allocation A is α-*Pareto efficient* when $v(A)/\alpha$ is undominated.

The social welfare of an allocation A is $\mathsf{sw}(A) = \sum_{i \in \mathcal{N}} v_i(A_i)$. Let allocation A^* denote a (social) welfare optimal allocation for which $\mathsf{sw}(A^*) \geq \mathsf{sw}(A)$ for all feasible allocations A. An allocation provides an α-approximation to welfare if $\mathsf{sw}(A) \geq \alpha \cdot \mathsf{sw}(A^*)$.

Fairness notions. We focus on a prominent notion of fairness called *envy-freeness*. An allocation $A^T = (A_1^T, \ldots, A_n^T)$ of T items is *envy-free* (EF) when $v_i(A_i^T) \geq v_i(A_j^T)$ for all $i, j \in \mathcal{N}$, and c-strongly-envy-free (c-strong-EF) when $v_i(A_i) \geq v_i(V_j) + cT$.

3 Ideal Quantile-based Algorithms.

For our analysis, it will be useful to compare our algorithms with ideal algorithms that know *exact* quantile values for every item (and, in fact, several of our lower bounds apply to these stronger algorithms too). Two ideal algorithms of interest are (1) quantile maximization, which allocates each item to the agent with the highest quantile value for it, and (2) "q−threshold," which allocates each item uniformly at random among agents whose quantile is at least q (and uniformly at random over all agents, if all quantile values are less than q).

In the i.i.d. model, quantile maximization is the same as value maximization, and thus envy-free with high probability and ex-post welfare optimal. The property we will use is c-strong envy-freeness, for some distribution-dependent constant c, which we state as Lemma 1. This was essentially proved by [DGK+14]; we provide an alternate proof that also works, essentially unchanged, for the $\frac{n-1}{n}$-threshold algorithm.

Lemma 1. *[Essentially [DGK+14].] In the i.i.d. and non-i.i.d. models, the quantile maximization algorithm and the $\frac{n-1}{n}$-threshold algorithm are c-strongly envy-free, with high probability, where the constant $c = \min_{i \in \mathcal{N}} (\mathbb{E}[X_i \mid Q_i \geq 1/2] - \mathbb{E}[X_i])/(4n)$.*

Note that c is strictly positive since our distributions are continuous. In the i.i.d. model, we show that the $\frac{n-1}{n}$-threshold algorithm gives a $\left(1 - \frac{1}{e}\right)^2 - \varepsilon$ approximation to welfare (Lemma 2) with high probability. Proofs omitted from this section appear in Appendix A.

Lemma 2. *In the i.i.d. model, the $\frac{n-1}{n}$-threshold algorithm guarantees a $\left(\left(1 - \frac{1}{e}\right)^2 - \varepsilon\right)$-approximation to welfare, with high probability, for all $\varepsilon > 0$.*

Proof. Let F be the CDF of an arbitrary continuous distribution. The expected contribution of an item to the welfare of the threshold algorithm is at least

$$\mathop{\mathbb{E}}_{Q \sim \mathrm{Unif}[0,1]} \left[F^{-1}(Q) \mid Q \geq \frac{n-1}{n} \right] \cdot \Pr_{\vec{Q} \sim \mathrm{Unif}[0,1]^n} \left[\max_{i \in \mathcal{N}} Q_i \geq \frac{n-1}{n} \right].$$

For the first term we have

$$
\mathop{\mathbb{E}}_{Q\sim\text{Unif}[0,1]}\left[F^{-1}(Q)\mid Q\geq\frac{n-1}{n}\right] = \mathop{\mathbb{E}}_{Q\sim\text{Unif}[\frac{n-1}{n},1]}\left[F^{-1}(Q)\right]
$$

$$
= \left(\int_{\frac{n-1}{n}}^{1}F^{-1}(q)\cdot f_{\text{Unif}[\frac{n-1}{n},1]}(q)\,\mathrm{d}q\right)
$$

$$
= \left(\int_{\frac{n-1}{n}}^{1}F^{-1}(q)\cdot n\,\mathrm{d}q\right)
$$

$$
\geq^{(f_{\text{Beta}[n,1]}(x)=nx^{n-1})}\left(\int_{\frac{n-1}{n}}^{1}F^{-1}(q)\cdot f_{\text{Beta}[n,1]}(q)\,\mathrm{d}q\right)
$$

$$
= \mathop{\mathbb{E}}_{Q\sim\text{Beta}[n,1]}\left[F^{-1}(Q)\mid Q\geq\frac{n-1}{n}\right]\cdot\mathop{\text{Pr}}_{Q\sim\text{Beta}[n,1]}\left[Q\geq\frac{n-1}{n}\right]
$$

$$
\geq \mathop{\mathbb{E}}_{Q\sim\text{Beta}[n,1]}\left[F^{-1}(Q)\right]\cdot\mathop{\text{Pr}}_{Q\sim\text{Beta}[n,1]}\left[Q\geq\frac{n-1}{n}\right]
$$

$$
= \mathop{\mathbb{E}}_{\vec{Q}\sim\text{Unif}[0,1]^n}\left[F^{-1}(\max_{i\in\mathcal{N}}Q_i)\right]\cdot\mathop{\text{Pr}}_{\vec{Q}\sim\text{Unif}[0,1]^n}\left[\max_{i\in\mathcal{N}}Q_i\geq\frac{n-1}{n}\right],
$$

where we used the fact that the maximum of n draws from $U[0,1]$ follows a $\text{Beta}(n,1)$. The expected contribution to the welfare is thus at least $\mathbb{E}_{\vec{Q}\sim\text{Unif}[0,1]^n}\left[F^{-1}(\max_{i\in\mathcal{N}}Q_i)\right]\left(1-\left(1-\frac{1}{n}\right)^n\right)^2\geq$ $\left(1-\frac{1}{e}\right)^2\mathbb{E}_{\vec{Q}\sim\text{Unif}[0,1]^n}\left[F^{-1}(\max_{i\in\mathcal{N}}Q_i)\right]$.

Finally, for any fixed $\varepsilon>0$, standard Chernoff bounds tell us that with high probability, the optimal welfare of T items is at most $T\cdot(1+\varepsilon/2)\,\mathbb{E}_{\vec{Q}\sim\text{Unif}[0,1]^n}\left[F^{-1}(\max_{i\in\mathcal{N}}Q_i)\right]$ while the welfare of the threshold algorithm is at least $T\cdot(1-\varepsilon/2)\left(1-\frac{1}{e}\right)^2\left[\mathbb{E}_{\vec{Q}\sim\text{Unif}[0,1]^n}\left[F^{-1}(\max_{i\in\mathcal{N}}Q_i)\right]\right.$; see Appendix A for these straightforward arguments. Thus, the algorithm is a $\left(1-\frac{1}{e}\right)^2\cdot(1-\varepsilon/2)/(1+\varepsilon/2)\geq\left(1-\frac{1}{e}\right)^2(1-\varepsilon)\geq\left(1-\frac{1}{e}\right)^2-\varepsilon$ approximation to welfare, with high probability. $\qquad\square$

Finally, we prove that both ideal algorithms are approximately efficient. Let $\mathcal{P}^*$ be the following property of an allocation: all items such that exactly one agent has quantile values at least $1-1/n$ are in the bundle of this agent. Both ideal algorithms (quantile maximization and $1-1/n$-threshold) satisfy $\mathcal{P}^*$. We prove that, in the non-i.i.d. model, $\mathcal{P}^*$ implies a $1/e$ approximation to efficiency.

Lemma 3. *In the non-i.i.d. model, every algorithm whose allocations satisfy $\mathcal{P}^*$ is $(1/e-\varepsilon)$-Pareto optimal, with high probability, for all $\varepsilon>0$.*

Our proof uses the fact that there is a (roughly) $1/e$ probability that exactly one agent has the high quantile, so the value of an agent's bundle in an algorithm that satisfies $\mathcal{P}^*$ is, with high probability, a $1/e$ approximation to their value for their T/n most valuable items. Therefore, when considering an alternate allocation A', the agent in A' that gets at most T/n items cannot be improved upon by more than a $1/e$ factor.

4 Unbounded memory in the i.i.d. model

We explore some fundamental limits of our setting. Efficiency by itself is easy: allocate all items to the same agent. In contrast to the cardinal setting, we find one-swap-Pareto efficiency is incompatible with envy-freeness with high probability, even for two i.i.d. agents, and even when the underlying distribution is *known*. Proofs missing from this section can be found in Appendix B.

Theorem 4. *In the i.i.d. model, even for $n=2$ agents, there does not exist an algorithm $\mathcal{A}$ which is one-swap-Pareto efficient and envy-free with high probability, even when values are sampled according to D, for any continuous, bounded and known value distribution D.*

As the agents are a priori identical, we can assume without loss of generality that $\mathcal{A}$ gives the first item to agent 1. The proof of Theorem 4 shows that, with positive probability, this decision becomes

222 an irrevocable "mistake," in the sense that agent 2 really liked the item and agent 1 did not. This
223 mistake will make envy-freeness and one-swap-Pareto efficiency incompatible.

224 Theorem 4 implies that when we have access to only ordinal information, we need to settle for
225 *some* approximation to envy-freeness and efficiency. Our main positive result for this section is an
226 algorithm that essentially matches the aforementioned lower bound.

227 **Theorem 5.** *In the i.i.d. model, Algorithm 1 achieves envy-freeness and a $(1 - \varepsilon)$ approximation to*
228 *welfare, with high probability, for all $\varepsilon > 0$.*

229 Algorithm 1 works in epochs: each epoch k has an exploration/sampling phase, where each agent i
230 receives a pre-determined set of items, denoted G_i^k, irrespective of their valuation. This is followed
231 by an exploitation/ranking phase, where each item is given to the agent with the highest empirical
    quantile (with respect to items received in the preceding exploration phase, i.e. G_i^k).

Algorithm 1: EF + $(1 - \varepsilon)$-Welfare

---

for *epoch $k = 1 \ldots$* **do**
  Sampling Phase: ($n \cdot k^4$ items)
  Give the j-th item in this phase to agent $j \pmod n$.
  Ranking Phase: (k^8 items)
  for *each item g in this phase* **do**
    Elicit $\sigma_i^{-1}(G_i^k \cup \{g\}, g)$ for all $i \in \mathcal{N}$.
    Allocate g to an agent $j \in \arg\min_{i \in \mathcal{N}} \sigma_i^{-1}(G_i^k \cup \{g\}, g)$.

232

233 We start with a technical lemma, which gives us a bound on the length of the exploration period we
234 need in each epoch. The following definition will be useful.

235 **Definition 2.** A sample of $n \cdot m$ items (where each agent is allocated exactly m items) is ε-accurate
236 if, with probability at least $1 - \varepsilon$, the relative rank of a fresh item (with respect to the sample) is
237 highest for the agent with highest quantile value.

238 **Lemma 6.** *If $\varepsilon, \delta \in (0, 1)$, and $m \in \mathbb{Z}^+$ are such that $\varepsilon > 2n\sqrt{\frac{\ln(2n/\delta)}{2m}}$, then giving m samples to*
239 *each agent is ε-accurate with probability at least $1 - \delta$.*

240 *Proof.* We will use the Dvoretzky–Kiefer–Wolfowitz (DKW) inequality [DKW56, Mas90] to show
241 the empirical CDF of sampled quantiles is reasonably close to a uniform distribution with probability
242 $1 - \delta$. We then show this is sufficient to guarantee ε-accuracy for the chosen ε. Let $\hat{F}_i$ be the
243 empirical CDF of the sampled *quantiles* for agent i, i.e., $\hat{F}_i(q)$ for $q \in [0, 1]$ is a random variable
244 that describes the proportion of sampled items with quantile at most q. Note that $\hat{F}_i$ exactly captures
245 agent i's ranking for a new item: if a fresh item has quantile q_i for agent i and q_j for agent j, then i
246 ranks it higher than j exactly when $\hat{F}_i(q_i) > \hat{F}_j(q_j)$.

247 Noting that the CDF for the actual quantile distribution (i.e., the uniform distribution) is the identity
248 on $[0, 1]$, the DKW inequality states that for all $\gamma > 0$, $\Pr\left[\sup_{q \in [0,1]} |\hat{F}_i(q) - q| > \gamma\right] \leq 2e^{-2m\gamma^2}$.
249 We want this condition to hold for all n agents, simultaneously, with probability at least $1 - \delta$, so
250 we pick γ such that $2e^{-2m\gamma^2} \leq \delta/n$ and apply a union bound; it suffices to choose $\gamma = \sqrt{\frac{\ln(2n/\delta)}{2m}}$.

251 We now show that the DKW condition ($\sup_{q \in [0,1]} |\hat{F}_i(q) - q| \leq \gamma$) being satisfied for all agents
252 i is sufficient to guarantee ε-accuracy. Consider sampling quantiles $Q_1, \ldots, Q_n$ for a fresh item.
253 Let $i^{\max} \in \arg\max_{i \in \mathcal{N}} Q_i$ be a quantile-maximizing agent (technically a random variable). Our
254 goal is to show that with probability at least $1 - \varepsilon$ (with respect to the samples of $Q_1, \ldots, Q_n$)
255 $\hat{F}_{i^{\max}}(Q_{i^{max}}) > \hat{F}_j(Q_j)$ for all $j \neq i^{\max}$. This ensures that $i^{\max}$ has the highest empirical rank,
256 and hence receives the item. Let $Q_{(1)}, \ldots, Q_{(n)}$ be the respective order statistics. A key observation
257 is that $Q_{(n)} - Q_{(n-1)} \sim \text{Beta}[1, n]$ [Gen19]. The PDF of a $\text{Beta}[1, n]$ distribution is $f(x) = nx^{n-1}$
258 for $x \in [0, 1]$. Since $f(x) \leq n$, $\Pr\left[Q_{(n)} - Q_{(n-1)} < \rho\right] < n\rho$ for all $\rho > 0$. Plugging in $\rho = 2\gamma$,
259 we have $\Pr\left[Q_{(n)} - Q_{(n-1)} \leq 2\gamma\right] < 2n\gamma$. We will show that as long as $\varepsilon > 2n\gamma$, ε-accuracy holds.
260 First, we have $\Pr\left[Q_{(n)} - Q_{(n-1)} > 2\gamma\right] > 1 - \varepsilon$. Conditioned on $Q_{(n)} - Q_{(n-1)} > 2\gamma$, the item is

261 given to $i^{\max}$. To see why, observe $Q_{i^{\max}} = Q_{(n)}$ and $Q_j \leq Q_{(n-1)}$ for all $j \neq i^{\max}$, by definition.

262 Using the DKW inequality condition, it follows that $\hat{F}_{i^{\max}}(Q_{i^{\max}}) \geq Q_{i^{\max}} - \gamma > Q_j + \gamma \geq \hat{F}_j(Q_j)$.

263 We conclude that for $\varepsilon > 2n\sqrt{\frac{\ln(2n/\delta)}{2m}}$, ε-accuracy is satisfied with probability at least $1 - \delta$. $\square$

264 Using Lemma 6, we can get, for each epoch, a bound on the number of decisions where Algorithm 1
265 differs from the quantile maximization algorithm.

266 **Lemma 7.** *The allocation of Algorithm 1 differs from that of the quantile maximization algorithm*
267 *after T steps by at most $f(T)$ items with high probability, where $f(T) \in O(\text{poly}(n) \cdot T^{15/16})$.*

268 *Proof.* We start by bounding the accuracy of Algorithm 1 in each epoch k. In epoch k, each agent
269 receives k^4 items during the sampling phase. We claim that the sample in epoch k for $k \geq 3n$ is
270 ε_k-accurate for $\varepsilon_k := 3n/k^{3/2}$ with probability at least $1 - \delta_k$, for $\delta_k := 2n/e^{2k}$. Indeed, first note
271 that by the choice of k, we have that $\varepsilon_k, \delta_k \in (0,1)$. Hence, we just need to show that these values
272 satisfy the inequality of Lemma 6. We have that

$$\varepsilon_k = \frac{3n}{k^{3/2}} > \frac{2n}{k^{3/2}} = 2n\sqrt{\frac{1}{k^3}} = 2n\sqrt{\frac{\ln(e^{2k})}{2k^4}} = 2n\sqrt{\frac{\ln(2n/\delta_k)}{2k^4}}.$$

273 Next, fix a time T. Slightly abusing notation, let $k(t) = \min\{K \in \mathbb{N} | \sum_{k=1}^{K} nk^4 + k^8 \geq t\}$ be the
274 function that given an item t returns the epoch item t is in. Notice that $T \geq \sum_{k=1}^{k(T)-1} nk^4 + k^8 \geq$
275 $(k(T) - 1)^8$, and therefore $k(T) \leq 2T^{1/8}$. In any run of the algorithm, we can classify every item
276 $t \leq T$ into one of four categories.

277 1. Item t was allocated in one of the first $3n - 1$ epochs, that is, $k(t) < 3n$.

278 2. Item t was allocated in the sampling phase of epoch $k(t) \geq 3n$.

279 3. Item t was allocated in the ranking phase of epoch $k(t) \geq 3n$; the epoch was $\varepsilon_{k(t)}$-accurate.

280 4. Item t was allocated in the ranking phase of epoch $k(t) \geq 3n$; the epoch was not $\varepsilon_{k(t)}$-accurate.

281 We say an item t was a mistake if it was given to an agent with a non-maximum quantile for it. We
282 show that the number of mistakes in each category are bounded by $3^{10}n^9, 2nT^{5/8}, 9nT^{15/16}$, and
283 $158n\ln(T)$ respectively, with high probability. This implies that the total number of mistakes is at
284 most the sum of these quantities, which is $O(\text{poly}(n) \cdot T^{15/16})$, with high probability, via a union
285 bound. The bounds for categories 1 and 2 are postponed to Appendix B.

286 Each item t in the third category has probability $\varepsilon_{k(t)}$ of being a mistake. The expected number
287 of mistakes is therefore at most $\sum_{k=3n}^{k(T)} \varepsilon_{k(t)} k^8 = \sum_{k=3n}^{k(T)} 3nk^{13/2} \leq 3nk(T)^{15/2} \leq 8nT^{15/16}$.
288 Using Hoeffding's inequality we get that with high probability the number of mistakes is at most
289 $9nT^{15/16}$, since a deviation of $nT^{15/16}$ occurs with probability at most $\exp(-2n^2T^{15/8}/T) =$
290 $\exp(-2n^2T^{7/8})$. For the fourth category, the expected number of items is at most $\sum_{k=3n}^{k(T)} \delta_k k^8 =$
291 $2n\sum_{k=3n}^{k(T)} \frac{k^8}{e^{2k}} \leq 2n\sum_{k=1}^{\infty} \frac{k^8}{e^{2k}} \leq 158n$. Using Markov's inequality we have that the number of
292 mistakes is at most $158n\ln(T)$ with probability at least $1 - \ln(T)$, i.e., with high probability. $\square$

293 The proof of Theorem 5 is a relatively straightforward consequence of Lemma 7 since the ideal
294 quantile maximization algorithm satisfies nice properties (e.g., Lemma 1).

5 Bounded memory in the i.i.d. model

296 In this section, we are interested in the more ambitious problem of designing dynamic algorithms
297 with even more limited partial information: each agent is allowed to "remember" only a single item.
298 We first show that, in this case, we need to settle for constant approximations of welfare. Proofs
299 missing from this section can be found in Appendix C.

300 **Theorem 8.** *In the i.i.d. model, given a memory of one item per agent, there is no algorithm $\mathcal{A}$ that*
301 *is .999-welfare maximizing with high probability for all continuous and bounded value distributions.*

302 Our positive result matches this lower bound up to a constant.

303 **Theorem 9.** *In the i.i.d. model, given a memory of one item per agent, Algorithm 2 achieves envy-*
304 *freeness and a $(1 - 1/e)^2 - \varepsilon$ approximation to welfare, with high probability, for all $\varepsilon > 0$.*

305 Algorithm 2 works in epochs, similar to Algorithm 1. In each epoch's exploration/sampling phase, it
306 tries to find an item whose quantile is close to the $\frac{n-1}{n}$-threshold algorithm. Epoch k makes k^3 such
307 attempts, and each candidate item is tested against k^6 fresh items to get an estimated quantile. If
308 everything is within the error we can tolerate, the algorithm remembers this item for this epoch; oth-
309 erwise, the agent has an arbitrary item in memory during this epoch. During the exploitation/ranking
310 phase, Algorithm 2 tries to mimic the $\frac{n-1}{n}$-threshold algorithm (instead of the quantile maximization
311 algorithm as Algorithm 1 did), and, in fact, inherits its approximation factor (Lemma 2) exactly.

Algorithm 2: Bounded Memory

---

for *Epoch $k = 1 \ldots$* **do**
    Sampling Phase: (k^9 items)
    NOTWITHINERROR $\leftarrow \mathcal{N}$
    for *trial $= 1, \ldots, k^3$* **do**
        for $i \in$ NOTWITHINERROR **do**
            Allocate the next item to agent i, and update her memory
        Test $k^6 - |$NOTWITHINERROR$|$ number of items (for each agent)
        for $i \in$ NOTWITHINERROR **do**
            if *Proportion of test items for agent i is within $\pm 1/k^2$ of $(n-1)/n$* **then**
                NOTWITHINERROR $\leftarrow$ NOTWITHINERROR $\setminus \{i\}$
    Ranking Phase: (k^{18} items)
    for *each item g in this phase* **do**
        if *Some agent i has high signal* **then**
            Give g to a (uniformly) random such agent
        else
            Give g to an agent uniformly at random

---

312 Our first technical lemma, Lemma 10, gives necessary bounds on the various variables of Algo-
313 rithm 2 for a sample to be ε-accurate with respect to the ideal threshold algorithm; see Definition 3.

314 **Definition 3.** *A set of n items in memory, one for each agent, is ε-accurate with respect to q^* if with*
315 *probability at least $1 - \varepsilon$, when a fresh item is sampled, the agents with true quantile above q^* are*
316 *exactly those that value the fresh item more than their item in memory.*

317 **Lemma 10.** *For all $\varepsilon, \delta \in (0, 1)$, if (1) at least τ trials are done with $\tau \geq \frac{\ln(2n/\delta)}{\varepsilon/(3n)}$, and (2) at least*
318 *ℓ test items are used per trial for $\ell \geq \frac{18n^2}{\varepsilon^2} \ln\left(\frac{4\tau n}{\delta}\right)$, and (3) the tolerance for accepting an item*
319 *is $\varepsilon/(3n)$, then the items in memory are ε-accurate (for all agents, simultaneously) with respect to*
320 *$q^* = \frac{n-1}{n}$, with probability at least $1 - \delta$.*

321 Though Lemmas 6 and 10 resemble each other (and are used in analogous ways), the proofs require
322 different techniques, as the sampling processes are very different. Next, we prove an analogue to
323 Lemma 7: the number of disagreements between Algorithm 2 and the ideal threshold algorithm
324 is sublinear.[2] The proofs of Lemmas 7 and 11 are similar, precisely because Lemma 6 matches
325 Lemma 10. Theorem 9 follows from Lemma 11 as in the i.i.d. case.

326 **Lemma 11.** *The allocation of Algorithm 2 differs from that of the $\frac{n-1}{n}$-threshold algorithm after T*
327 *steps by at most $f(T)$ items with high probability, where $f(T) \in O\left(poly(n) \cdot T^{17/18}\right)$.*

6 The non-i.i.d. model

329 In this section, we study the non-i.i.d. model. Proofs missing from this section can be found in
330 Appendix D. We first establish a strong lower bound for the non-i.i.d. model. The following negative
331 result holds even for algorithms that know the associated quantile for every fresh item.

---

[2]Note these are randomized algorithms, so by "differ on a item" here we mean that the distributions over agents receiving the item differ.

Theorem 12. *Even for 2 non-identical agents, there is no algorithm that is EF and c-PO with probability p, for $c > 18/19$ and $p > 2/3$, for all continuous and bounded value distributions.*

Proof. Suppose for contradiction that there is an algorithm $\mathcal{A}$ so that for all bounded continuous distributions (X_1, X_2) there exists a $T^* = T^*(X_1, X_2)$ where for all $t \geq T^*$, $\mathcal{A}$ is envy-free and c-PO with probability at least $2/3 + \varepsilon$ for some constant $c > 18/19$ and some fixed $\varepsilon > 0$.

Consider two distributions D_F and D_S; we describe these later in the proof. Consider the three instances $I_0 = (D_F, D_F)$, $I_1 = (D_S, D_F)$ and $I_2 = (D_F, D_S)$. Let $\mathcal{E}_j^{\mathcal{A}}$ be the event that $\mathcal{A}$ is envy-free and $c-$PO on instance I_j after time T_j for $j \in \{0, 1, 2\}$. By construction, $\Pr[\mathcal{E}_j^{\mathcal{A}}] \geq 2/3 + \varepsilon$ for all $j \in \{0, 1, 2\}$. Let z be a parameter we will fix later in the proof, and let $Z_i^t = \mathbb{I}\{Q_{i,t} \geq 1 - z\}$ for $i = \{1, 2\}$. Observe that $Z_1^t \cdot Z_2^t$ is 1 with probability z^2 and 0 otherwise.

The following events characterize a specific notion of a "nice" sample, in which the number of items with high quantiles for both agents is near its expectation: $\mathcal{E}_1^T = \mathbb{I}\{\frac{1}{T}\sum_{t=1}^{T} Z_1^t \cdot Z_2^t > z^2 - \delta\}$, $\mathcal{E}_2^T = \mathbb{I}\{\frac{1}{T}\sum_{t=1}^{T} Z_1^t \cdot Z_2^t < z^2 + \delta\}$, $\mathcal{E}_3^T = \mathbb{I}\{\frac{1}{T}\sum_{t=1}^{T} Z_1^t < z + \delta\}$ and $\mathcal{E}_4^T = \mathbb{I}\{\frac{1}{T}\sum_{t=1}^{T} Z_2^t < z + \delta\}$ for some $\delta > 0$. By Hoeffding's inequality, $\Pr[\bar{\mathcal{E}}_1^T] = \Pr[\frac{1}{T}\sum_{t=1}^{T} Z_1^t \cdot Z_2^t - z^2 \leq -\delta] \leq 2\exp(-2T\delta^2)$. It follows that for $T \geq \log(2/\varepsilon')/(2\delta^2)$, $\Pr[\bar{\mathcal{E}}_1^T] \leq \varepsilon'$. Similarly, for $T \geq \log(2/\varepsilon')/(2\delta^2)$ it holds that $\Pr[\bar{\mathcal{E}}_2^T] \leq \varepsilon'$, $\Pr[\bar{\mathcal{E}}_3^T] \leq \varepsilon'$, and $\Pr[\bar{\mathcal{E}}_4^T] \leq \varepsilon'$. Consider an arbitrary $T > T_{\max} = \max\{T_0, T_1, T_2, \log(2/\varepsilon')/(2\delta^2)\}$, and set $\varepsilon' = \varepsilon/2$. Applying a union bound

$$\Pr[\bar{\mathcal{E}}_0^{\mathcal{A}} \cup \bar{\mathcal{E}}_1^{\mathcal{A}} \cup \bar{\mathcal{E}}_2^{\mathcal{A}} \cup \bar{\mathcal{E}}_1^T \cup \bar{\mathcal{E}}_2^T \cup \bar{\mathcal{E}}_3^T \cup \bar{\mathcal{E}}_4^T] \leq \sum_{i=0}^{2} \Pr[\bar{\mathcal{E}}_i^{\mathcal{A}}] + \sum_{i=1}^{4} \Pr[\bar{\mathcal{E}}_i^T] \leq 3 \cdot (\frac{1}{3} - \varepsilon) + 4 \cdot \frac{\varepsilon}{2} < 1.$$

It follows that $\Pr[\mathcal{E}_0^{\mathcal{A}} \cap \mathcal{E}_1^{\mathcal{A}} \cap \mathcal{E}_2^{\mathcal{A}} \cap \mathcal{E}_1^T \cap \mathcal{E}_2^T \cap \mathcal{E}_3^T \cap \mathcal{E}_4^T] > 0$. Therefore, there must exist a sequence of T items whose quantiles satisfy all of $\mathcal{E}_1^T$, $\mathcal{E}_2^T$, $\mathcal{E}_3^T$ and $\mathcal{E}_4^T$, and, since $\mathcal{A}$ does not have access to the items' values, there must exist an allocation A^T for these T items (in the support of $\mathcal{A}$) that is EF and $c-$PO, no matter which of I_0, I_1 or I_2 the values were taken from. Let $q^T = \{(q_1(t), q_2(t))\}_{t=1}^{T}$ be these items' quantiles. Let $H_B = \{t \in [T] : q_1(t) \geq 1 - z \text{ and } q_2(t) \geq 1 - z\}$ be the items for which $Z_1^t \cdot Z_2^t = 1$, and $H_1 = \{t \in [T] : q_1(t) \geq 1 - z\}$ the items for which $Z_1^t = 1$.

For ease of exposition, we pick D_F and D_S to be non-continuous; see Appendix D for the adjusted proof. Set distributions $D_F = \text{Unif}\{1\}$ and D_S, under which each item is valued at 0 with probability z and at value 1 with probability $1 - z$.

By $\mathcal{E}_0^{\mathcal{A}}$, A^T is envy-free on I_0. It follows that $|A_1^T| = |A_2^T| = \frac{T}{2}$. Some agent receives at most half the items in H_B; without loss of generality this is agent 2, i.e. $|A_2^T \cap H_B| \geq |H_B|/2$. We show that there exists a feasible Pareto-improvement on I_1.

Let $\hat{A}^T$ be the allocation that is identical to A^T except that the agents swap the sets $A_1^T \setminus H_1$ and $A_2^T \cap H_B$. For the utilities in I_1 we have $u_1(\hat{A}_1^T) \geq u_1(A_1^T) + \frac{|H_B|}{2} \geq^{(\mathcal{E}_1^T)} u_1(A_1^T)\left(1 + \frac{z^2}{2} - \frac{\delta}{2}\right)$ and

$$u_2(\hat{A}_2^T) \geq u_2(A_2^T) - |H_B| + |A_1^T| - |H_1| \geq^{(\mathcal{E}_2^T \text{ and } \mathcal{E}_3^T)} u_2(A_2^T)\left(\frac{3}{2} - z^2 - z - 2\delta\right).$$

Letting $\delta \to 0$ and picking $z = 1/3$, both agents improve their utility by a factor of $19/18$. We conclude that A^T is at most $18/19$-Pareto optimal on instance I_1, which contradicts $\mathcal{E}_1^{\mathcal{A}}$. $\square$

Algorithms 1 and 2 are envy-free with high probability, even in the non-i.i.d. model, since envy-freeness is not an "inter-agent" property. Our last result shows that they also give a constant approximation to Pareto efficiency, by combining Lemma 3 with Lemmas 7 and 11.

Theorem 13. *In the non-i.i.d. model, both Algorithm 1 (unbounded memory) and Algorithm 2 (one-item memory) are envy-free and $(1/e - \varepsilon)$-Pareto optimal, with high probability, for all $\varepsilon > 0$.*

Interestingly, the guarantees for Algorithm 2 in the non-i.i.d. model are only marginally worse compared to the i.i.d. model; the approximation ratio decreases from $(1 - 1/e)^2 \approx 0.4$ to $1/e \approx 0.37$. Finally, we note that, even though the formal guarantees in Theorem 13 are the same for the two algorithms, and even though Algorithm 2 uses memory size of one, Algorithm 1 has the benefit of much shorter epoch lengths (in addition to better guarantees under the i.i.d. model).

References

[AAGW15] Martin Damyanov Aleksandrov, Haris Aziz, Serge Gaspers, and Toby Walsh. Online fair division: Analysing a food bank problem. In *Proceedings of the 24th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 2540–2546, 2015.

[ABM16] Georgios Amanatidis, Georgios Birmpas, and Evangelos Markakis. On truthful mechanisms for maximin share allocations. In *Proceedings of the 25th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 31–37, 2016.

[AFRSV21] Elliot Anshelevich, Aris Filos-Ratsikas, Nisarg Shah, and Alexandros A Voudouris. Distortion in social choice problems: the first 15 years and beyond. In *Proceedings of the 30th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 4294–4301, 2021.

[AGMW15] Haris Aziz, Serge Gaspers, Simon Mackenzie, and Toby Walsh. Fair assignment of indivisible objects under ordinal preferences. *Artificial Intelligence*, 227:71–92, 2015.

[BBL+17] Dorothea Baumeister, Sylvain Bouveret, Jérôme Lang, Nhan-Tam Nguyen, Trung Thanh Nguyen, Jörg Rothe, and Abdallah Saffidine. Positional scoring-based allocation of indivisible goods. *Autonomous Agents and Multi-Agent Systems*, 31(3):628–655, 2017.

[BEL10] Sylvain Bouveret, Ulle Endriss, and Jérôme Lang. Fair division under ordinal preferences: Computing envy-free allocations of indivisible goods. In *Proceedings of the 19th European Conference on Artificial Intelligence (ECAI)*, pages 387–392, 2010.

[BG22] Yushi Bai and Paul Gölz. Envy-free and pareto-optimal allocations for agents with asymmetric random valuations. In *Proceedings of the 32nd International Joint Conference on Artificial Intelligence (IJCAI)*, 2022. Forthcoming.

[BKM22] Siddharth Barman, Arindam Khan, and Arnab Maiti. Universal and tight online algorithms for generalized-mean welfare. In *Proceedings of the 36th AAAI Conference on Artificial Intelligence (AAAI)*, 2022. forthcoming.

[BKPP18] Gerdus Benade, Aleksandr M Kazachkov, Ariel D Procaccia, and Christos-Alexandros Psomas. How to make envy vanish over time. In *Proceedings of the 10th ACM Conference on Economics and Computation (EC)*, pages 593–610, 2018.

[BNPS21] Gerdus Benade, Swaprava Nath, Ariel D Procaccia, and Nisarg Shah. Preference elicitation for participatory budgeting. *Management Science*, 67(5):2813–2827, 2021.

[CNPS17] Ioannis Caragiannis, Swaprava Nath, Ariel D Procaccia, and Nisarg Shah. Subset selection via implicit utilitarian voting. *Journal of Artificial Intelligence Research*, 58:123–152, 2017.

[DGK+14] John P. Dickerson, Jonathan Goldman, Jeremy Karp, Ariel D Procaccia, and Tuomas Sandholm. The computational rise and fall of fairness. In *Proceedings of the 28th AAAI Conference on Artificial Intelligence (AAAI)*, pages 1405–1411, 2014.

[DKW56] Aryeh Dvoretzky, Jack Kiefer, and Jacob Wolfowitz. Asymptotic minimax character of the sample distribution function and of the classical multinomial estimator. *The Annals of Mathematical Statistics*, pages 642–669, 1956.

[FPV15] Eric Friedman, Christos-Alexandros Psomas, and Shai Vardi. Dynamic fair division with minimal disruptions. In *Proceedings of the 16th ACM Conference on Economics and Computation (EC)*, pages 697–713, 2015.

[FPV17] Eric Friedman, Christos-Alexandros Psomas, and Shai Vardi. Controlled dynamic fair division. In *Proceedings of the 18th ACM Conference on Economics and Computation (EC)*, pages 461–478, 2017.

[FRFZ14] Aris Filos-Ratsikas, Søren Kristoffer Stiil Frederiksen, and Jie Zhang. Social welfare in one-sided matchings: Random priority and beyond. In *Proceedings of the 7th International Symposium on Algorithmic Game Theory (SAGT)*, pages 1–12, 2014.

[GBI21] Artur Gorokh, Siddhartha Banerjee, and Krishnamurthy Iyer. From monetary to non-monetary mechanism design via artificial currencies. *Mathematics of Operations Research*, 2021.

[Gen19] James E Gentle. *Computational statistics*. Springer, 2019.

[GHS20] Vasilis Gkatzelis, Daniel Halpern, and Nisarg Shah. Resolving the optimal metric distortion conjecture. In *Proceedings of the 61st Symposium on Foundations of Computer Science (FOCS)*, pages 1427–1438, 2020.

[GKM17] Ashish Goel, Anilesh K Krishnaswamy, and Kamesh Munagala. Metric distortion of social choice rules: Lower bounds and fairness properties. In *Proceedings of the 18th ACM Conference on Economics and Computation (EC)*, pages 287–304, 2017.

[GPT21] Vasilis Gkatzelis, Alexandros Psomas, and Xizhi Tan. Fair and efficient online allocations with normalized valuations. In *Proceedings of the 35th AAAI Conference on Artificial Intelligence (AAAI)*, pages 5440–5447, 2021.

[HPPZ19] Jiafan He, Ariel D Procaccia, Alexandros Psomas, and David Zeng. Achieving a fairer future by changing the past. *Proceedings of the 28th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 343–349, 2019.

[HS21] Daniel Halpern and Nisarg Shah. Fair and efficient resource allocation with partial information. In *Proceedings of the 30th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 5456–5463, 2021.

[Kem20a] David Kempe. An analysis framework for metric voting based on lp duality. In *Proceedings of the 34th AAAI Conference on Artificial Intelligence (AAAI)*, pages 2079–2086, 2020.

[Kem20b] David Kempe. Communication, distortion, and randomness in metric voting. In *Proceedings of the 34th AAAI Conference on Artificial Intelligence (AAAI)*, pages 2087–2094, 2020.

[KPS14] Ian Kash, Ariel D Procaccia, and Nisarg Shah. No agent left behind: Dynamic fair division of multiple resources. *Journal of Artificial Intelligence Research*, 51:579–603, 2014.

[KPW16] David Kurokawa, Ariel D Procaccia, and Junxing Wang. When can the maximin share guarantee be guaranteed? In *Proceedings of the 30th AAAI Conference on Artificial Intelligence (AAAI)*, pages 523–529, 2016.

[Mas90] Pascal Massart. The tight constant in the Dvoretzky-Kiefer-Wolfowitz inequality. *The annals of Probability*, pages 1269–1283, 1990.

[MSW20] Debmalya Mandal, Nisarg Shah, and David P Woodruff. Optimal communication-distortion tradeoff in voting. In *Proceedings of the 21st ACM Conference on Economics and Computation (EC)*, pages 795–813, 2020.

[MW19] Kamesh Munagala and Kangning Wang. Improved metric distortion for deterministic social choice rules. In *Proceedings of the 20th ACM Conference on Economics and Computation (EC)*, pages 245–262, 2019.

[NNR17] Nhan-Tam Nguyen, Trung Thanh Nguyen, and Jörg Rothe. Approximate solutions to max-min fair and proportionally fair allocations of indivisible goods. In *Proceedings of the 16th International Conference on Autonomous Agents and Multi-Agent Systems (AAMAS)*, pages 262–271, 2017.

[PR06] Ariel D. Procaccia and Jeffrey S. Rosenschein. The distortion of cardinal preferences in voting. In *Proceedings of the 10th International Workshop on Cooperative Information Agents (CIA)*, pages 317–331, 2006.

[RF90] Günther Ruhe and Bernd Fruhwirth. ε-optimality for bicriteria programs and its application to minimum cost flows. *Computing*, 44(1):21–34, 1990.

[VPF21] Shai Vardi, Alexandros Psomas, and Eric Friedman. Dynamic fair resource division. *Mathematics of Operations Research*, 2021.

[ZP20] David Zeng and Alexandros Psomas. Fairness-efficiency tradeoffs in dynamic fair division. In *Proceedings of the 21st ACM Conference on Economics and Computation (EC)*, pages 911–912, 2020.