WHAT THEY DO WHEN IN DOUBT: A STUDY OF INDUCTIVE BIASES IN SEQ2SEQ LEARNERS

ABSTRACT

Sequence-to-sequence (seq2seq) learners are widely used, but we still have only limited knowledge about what inductive biases shape the way they generalize. We address that by investigating how popular seq2seq learners generalize in tasks that have high ambiguity in the training data. We use four new tasks to study learners' preferences for memorization, arithmetic, hierarchical, and compositional reasoning. Further, we connect to Solomonoff's theory of induction and propose to use description length as a principled and sensitive measure of inductive biases.

In our experimental study, we find that LSTM-based learners can learn to perform counting, addition, and multiplication by a constant from a *single training example*. Furthermore, Transformer and LSTM-based learners show a bias toward the hierarchical induction over the linear one, while CNN-based learners prefer the opposite. The latter also show a bias toward a compositional generalization over memorization. Finally, across all our experiments, description length proved to be a sensitive measure of inductive biases.

1 INTRODUCTION

Sequence-to-sequence (seq2seq) learners (Sutskever et al., 2014) demonstrated remarkable performance in machine translation, story generation, and open-domain dialog (Sutskever et al., 2014; Fan et al., 2018; Adiwardana et al., 2020). Yet, these models have been criticized for requiring a tremendous amount of data and being unable to generalize systematically (Dupoux, 2018; Loula et al., 2018; Lake and Baroni, 2017; Bastings et al., 2018). In contrast, humans rely on their inductive biases to generalize from a limited amount of data (Chomsky, 1965; Lake et al., 2019). Due to the centrality of humans' biases in language learning, several works have studied inductive biases of seq2seq models and connected their poor generalization to the lack of the "right" biases (Lake and Baroni, 2017; Lake et al., 2019).

In this work, we focus on studying inductive biases of seq2seq models. We start from an observation that, generally, multiple explanations can be consistent with a limited training set, each leading to different predictions on unseen data. A learner might prefer one type of explanations over another in a systematic way, as a result of its *inductive biases* (Ritter et al., 2017; Feinman and Lake, 2018).

To illustrate the setup we work in, consider a quiz-like question: if $f(3)$ maps to 6, what does $f(4)$ map to? The "training" example is consistent with the following answers: 6 ($f(x) \equiv 6$); 7 ($f(x) = x + 3$); 8 ($f(x) = 2 \cdot x$); any number z, since we always can construct a function such that $f(3) = 6$ and $f(4) = z$. By analyzing the learner's output on this new input, we can infer its biases.

This example demonstrates how biases of learners are studied through the lenses of the poverty of the stimulus principle (Chomsky, 1965; 1980): if nothing in the training data indicates that a learner should generalize in a certain way, but it does nonetheless, then this is due to the biases of the learner. Inspired by the work of Zhang et al. (2019) in the image domain, we take this principle to the extreme and study biases of seq2seq learners in the regime of very few training examples, often as little as one. Under this setup, we propose four new synthetic tasks that probe seq2seq learners' preferences to memorization-, arithmetic-, hierarchical- and compositional-based "reasoning".

Next, we connect to the ideas of Solomonoff's theory of induction (Solomonoff, 1964) and Minimal Description Length (Rissanen, 1978; Grunwald, 2004) and propose to use description length, under a learner, as a principled measure of its inductive biases.

Our experimental study[1] shows that the standard seq2seq learners have strikingly different inductive biases. We find that LSTM-based learners can learn non-trivial counting-, multiplication-, and addition-based rules from as little as one example. CNN-based seq2seq learners would prefer linear over hierarchical generalizations, while LSTM-based ones and Transformers would do just the opposite. When investigating the compositional reasoning, description length proved to be a sensitive measure. Equipped with it, we found that CNN-, and, to a lesser degree, LSTM-based learners prefer compositional generalization over memorization when provided with enough composite examples. In turn, Transformers show a strong bias toward memorization.

2 SEARCHING FOR INDUCTIVE BIASES

To formalize the way we look for inductive biases of a learner $\mathcal{M}$, we consider a training dataset of input/output pairs, $T = \{x_i, y_i\}_{i=1}^n$, and a hold-out set of inputs, $H = \{x_i\}_{i=n+1}^k$. W.l.o.g, we assume that there are two candidate "rules" that explain the training data, but do not coincide on the hold-out data: $\mathcal{C}_1(x_i) = \mathcal{C}_2(x_i) = y_i, \ 1 \le i \le n$ and $\exists i : \mathcal{C}_1(x_i) \ne \mathcal{C}_2(x_i), n + 1 \le i \le k$.

To compare preferences of a learner $\mathcal{M}$ toward those two rules, we fit the learner on the training data T and then compare its predictions on the hold-out data H to the outputs of the rules. We refer to this approach as "intuitive". Usually, the measures of similarity between the outputs are task-specific: McCoy et al. (2020) used accuracy of the first term, Zhang et al. (2019) used correlation and MSE, and Lake and Baroni (2017) used accuracy calculated on the entire output sequence.

We too start with an accuracy-based measure. We define the fraction of perfect agreement (FPA) between a learner $\mathcal{M}$ and a candidate generalization rule $\mathcal{C}$ as the fraction of seeds that generalize *perfectly* in agreement with that rule on the hold-out set H. Larger FPA of $\mathcal{M}$ is w.r.t. $\mathcal{C}$, more biased $\mathcal{M}$ is toward $\mathcal{C}$. However, FPA does not account for imperfect generalization nor allows direct comparison between two candidate rules when both are dominated by a third candidate rule. Hence, below we propose a principled approach based on the description length.

Description Length and Inductive Biases At the core of the theory of induction (Solomonoff, 1964) is the question of continuation of a finite string that is very similar to our setup. Indeed, we can easily re-formulate our motivating example as a string continuation problem: "$3 \to 6; 4 \to$". The solution proposed by Solomonoff (1964) is to select the continuation that admits "the simplest explanation" of the entire string, i.e. that is produced by programs of the shortest length (description length).

Our intuition is that when a continuation is "simple" for a learner, then this learner is biased toward it. We consider a learner $\mathcal{M}$ to be biased toward $\mathcal{C}_1$ over $\mathcal{C}_2$ if the training set and its extension according to $\mathcal{C}_1$ has a shorter description length (for $\mathcal{M}$) compared to that of $\mathcal{C}_2$. Denoting description length of a dataset D under the learner $\mathcal{M}$ as $L_{\mathcal{M}}(D)$, we hypothesise that if $L_{\mathcal{M}}(\{\mathcal{C}_1(x_i)\}_{i=1}^k) < L_{\mathcal{M}}(\{\mathcal{C}_2(x_i)\}_{i=1}^k)$, then $\mathcal{M}$ is biased toward $\mathcal{C}_1$.

Calculating Description Length To find the description length of data under a fixed learner, we use the online (prequential) code (Rissanen, 1978; Grunwald, 2004; Blier and Ollivier, 2018).

The problem of calculating $L_{\mathcal{M}}(D)$, $D = \{x_i, y_i\}_{i=1}^k$ is considered as a problem of transferring outputs y_i one-by-one, in a compressed form, between two parties, Alice (sender) and Bob (receiver). Alice has the entire dataset $\{x_i, y_i\}$, while Bob only has inputs $\{x_i\}$. Before the transmission starts, both parties agreed on the initialization of the model $\mathcal{M}$, order of the inputs $\{x\}$, random seeds, and the details of the learning procedure. Outputs $\{y_i\}$ are sequences of tokens from a vocabulary V. W.l.o.g. we fix some order over $\{x\}$. We assume that, given x, the learner $\mathcal{M}$ produces a probability distribution over the space of the outputs y, $p_{\mathcal{M}}(y|x)$.

The very first output y_1 can be sent by using not more than $c = |y_1| \cdot \log |V|$ nats, using a naïve encoding.[2] After that, both Alice and Bob update their learners using the example (x_1, y_1), available to both of them, and get identical instances of $\mathcal{M}_1$.

Further transfer is done iteratively under the invariant that both Alice and Bob start every step t with exactly the same learners $\mathcal{M}_{t-1}$ and finish with identical $\mathcal{M}_t$. At step t Alice would use $\mathcal{M}_{t-1}$ to

---

[1]Code will be provided upon acceptance.

[2]As we are interested in comparing candidate generalization rules, the value of the additive constant c is not important, as it is learner- and candidate-independent. In experiments, we subtract it from all measurements.

Figure 1: Illustration of the tasks. After training on the train examples (green blocks), learners are tested on held-out examples (red blocks). In pink blocks are generalizations according to the candidate rules.

encode the next output y_t. This can be done using $\left(-\log p_{\mathcal{M}_{t-1}}(y_t|x_t)\right)$ nats (MacKay, 2003). Since Bob has exactly the same model, he can decode the message to obtain y_t and use the new pair (x_t, y_t) to update his model and get M_t. Alice also updates her model, and proceeds to sending the next y_{t+1} (if any), encoding it with the help of $\mathcal{M}_t$. The cumulative number of nats transmitted is:

$$L_{\mathcal{M}}(D) = -\sum_{t=2}^{k} \log p_{\mathcal{M}_{t-1}}(y_t|x_t) + c. \tag{1}$$

The obtained code length of Eq. 1 depends on the order in which y are transmitted and the procedure we use to update $\mathcal{M}$. To account for that, we average out the data order by training with multiple random seeds. Further, for larger datasets, full re-training after adding a new example is impractical and, in such cases, examples can be transmitted in blocks.

If we measure the description length of the training data T shuffled with the hold-out data H, both datasets would have symmetric roles. However, there is a certain asymmetry in the extrapolation problem: we are looking for an extrapolation from T, not vice-versa. To break this symmetry, we always transmit outputs for the entire training data as the first block.

While $L_{\mathcal{M}}(D)$ is seemingly different from the "intuitive" measures introduced before, we can illustrate their connection as follows. Consider a case where we first transmit the training outputs as the first block and *all* of the hold-out data outputs under $\mathcal{C}$, $\mathcal{C}(H)$, as the second block. Then the description length is equal to cross-entropy of the trained learner on the hold-out data, recovering a process akin to the "intuitive" measuring of inductive biases. With smaller blocks, the description length also catches whether a learner is capable of finding regularity in the data fast, with few data points; hence it also encodes the speed-of-learning ideas for measuring inductive biases (Chaabouni et al., 2019).

Finally, the description length has three more attractive properties when measuring inductive biases: (a) it is domain-independent, i.e. can be applied for instance in the image domain, (b) it allows comparisons across models that account for model complexity, and (c) it enables direct comparison between two candidate rules (as we will show in the Section 5).

3 TASKS

We describe four tasks that we use to study inductive biases of seq2seq learners. We select those tasks to cover different aspects of learners' behavior. Each task has a highly ambiguous training set which is consistent with infinite number of generalizations. We pre-select several candidate rules highlighting biases that are useful for language processing and known to exist in humans, or

are otherwise reasonable. Our experiments show that these rules cover many cases of the learners' behavior.

The first two tasks study biases in arithmetic reasoning: *Count-or-Memorization* quantifies learners' preference for counting vs. a simple memorization and *Add-or-Multiply* further probes the learners' preferences in arithmetic operations. We believe these tasks are interesting, as counting is needed in some NLP problems like processing linearized parse trees (Weiss et al., 2018). The third task, *Hierarchical-or-Linear*, contrasts hierarchical and linear inductive reasoning. The hierarchical reasoning bias is believed to be fundamental in learning some syntactical rules in human acquisition of syntax (Chomsky, 1965; 1980). Finally, with the *Composition-or-Memorization* task, we investigate biases for systematic compositionality, which are central for human capabilities in language. Figure 1 illustrates these four tasks.

By a^k we denote a sequence that contains token a repeated k times. For training, we represent sequences in a standard way: the tokens are one-hot-encoded separately, and we append a special end-of-sequence token to each sequence. Input and output vocabularies are disjoint.

Count-or-Memorization: In this task, we contrast learners' preferences for counting vs. memorization. We train models to fit a single training example with input a^l and output b^l (i.e., to perform the mapping $a^l \rightarrow b^l$) and test it on a^m with $m \in [l-10, l+10]$. If a learner learns the constant function, outputting b^l independently of its inputs, then it follows the mem strategy. On the other hand, if it generalizes to the $a^m \rightarrow b^m$ mapping, then the learner is biased toward the count strategy.

Add-or-Multiply: This task is akin to the motivating example in Section 1. The single training example represents a mapping of an input string a^l to an output string b^{2l}. As test inputs, we generate a^m for m in the interval $[l-3, l+3]$. We consider the learned rule to be consistent with mul if for all m, the input/output pairs are consistent with $a^m \rightarrow b^{2m}$. Similarly, if they are consistent with $a^m \rightarrow b^{m+l}$, we say that the learner follows the addition rule, add. Finally, the learner can learn a constant mapping $a^m \rightarrow b^{2l}$ for any m. Again, we call this rule mem.

Hierarchical-or-Linear: For a fixed depth d, we train learners on four training examples $x^d y x^d \rightarrow y$ where $x, y \in \{a, b\}$.[3] Each training example has a nested structure, where d defines its depth. A learner with a hierarchical bias (hierar), would output the middle symbol. We also consider the linear rule (linear) in which the learner outputs the $(d+1)^{th}$ symbol of its input.
To probe learners' biases, we test them on inputs with different depths $m \in [d-2, d+2]$. Note that to examine the linear rule (i.e. if the learner outputs the $(d+1)^{th}$ symbol of any test input of depth m), we need $m \geq \frac{d}{2}$. Similar to the previous tasks, there is no vocabulary sharing between a model's inputs and outputs (input and output tokens a and b are different).

Composition-or-Memorization: We take inspiration from SCAN (Lake and Baroni, 2017), a benchmark used for studying systematic generalization of seq2seq learners.[4] The input vocabulary has N symbols a_i that are one-to-one mapped into N output symbols b_i (i.e., $a_i \rightarrow b_i$). In addition, there is a modifier token $thrice$: when $thrice$ precedes an input symbol a_i, the corresponding output is repeated three times: $thrice\ a_i \rightarrow b_i b_i b_i$.

We train a learner on all non-compositional examples ($a_i \rightarrow b_i$) and M ($M < N$) compositional examples ($thrice\ a_i \rightarrow b_i b_i b_i$). At test time, we feed the learner with the remaining compositional examples ($thrice\ a_i, i > M$). If the learner generalizes to the mapping $thrice\ a_i \rightarrow b_i b_i b_i$ for $i > M$, we consider it to be biased toward a compositional reasoning (comp). As an alternative generalization, we consider a mapping where all inputs containing a_i are mapped into b_i: $thrice\ a_i \rightarrow b_i$ ($i > M$). We call this generalization memorization (mem).

4 METHODOLOGY

4.1 SEQUENCE-TO-SEQUENCE LEARNERS

We experiment with three standard seq2seq models: LSTM-based seq2seq (LSTM-s2s) (Sutskever et al., 2014), CNN-based seq2seq (CNN-s2s) (Gehring et al., 2017), and Transformer (Vaswani et al., 2017). All share a similar Encoder/Decoder architecture (Sutskever et al., 2014).

---

[3]This mapping consist then on four combinations $a^d b a^d \rightarrow b$; $a^d a a^d \rightarrow a$; $b^d a b^d \rightarrow a$ and $b^d b b^d \rightarrow b$.
[4]In Appendix, we report a study of inductive biases on the SCAN data.

LSTM-s2s Both Encoder and Decoder are implemented as LSTM cells (Hochreiter and Schmidhuber, 1997). Encoder encodes its inputs incrementally from left to right. We experiment with architectures without (LSTM-s2s no att.) and with (LSTM-s2s att.) an attention mechanism (Bahdanau et al., 2014). For the first three tasks, both Encoder and Decoder are single-layer LSTM cells with hidden size of 512 and embedding of dimension 16.

CNN-s2s Encoder and Decoder are convolutional networks (LeCun et al., 1990), followed by GLU non-linearities (Dauphin et al., 2017) and an attention layer. To represent positions of input tokens, CNN-s2s uses learned positional embeddings. Encoder and Decoder networks have one layer with 512 filters and a kernel width of 3. We set the embedding size to 16.

Transformer Encoder and Decoder are implemented as a sequence of (self-)attention and feed-forward layers. We use sinusoidal position embeddings. Both Encoder and Decoder contain one transformer layer. The attention modules have 8 heads, feed-forward layers have dimension of 512 and the embedding is of dimension 16.

In Appendix we report experiments where we vary hyperparameters of the learners.

4.2 TRAINING AND EVALUATION

For all tasks, we follow the same training procedure. We train with Adam optimizer (Kingma and Ba, 2014) for 3000 epochs. The learning rate starts at 10^{-5} and increases for the first 1000 warm-up updates till reaching 10^{-3}. We include all available examples in a single batch. We use teacher forcing (Goodfellow et al., 2016) and set the dropout probability to 0.5. For each learner, we perform training and evaluation 100 times, changing random seeds. At generation, to calculate FPA, we select the next token greedily. We use the model implementations from fairseq (Ott et al., 2019).

As discussed in Section 2, when calculating L, we use the training examples as the first transmitted block at $t = 1$. In *Count-or-Memorization* and *Add-or-Multiply* this block contains one example, in *Hierarchical-or-Linear* it has 4 examples, and in *Composition-or-Memorization* it has $N + M$ examples. Next, we transmit examples obtained from the candidate rules in a randomized order, by blocks of size 1, 1, 1, and 4 for *Count-or-Memorization*, *Add-or-Multiply*, *Composition-or-Memorization*, and *Hierarchical-or-Linear* respectively. At each step, the learner is re-trained from the same initialization, using the procedure and hyper-parameters as discussed above.

5 EXPERIMENTS

Count-or-Memorization We investigate here learners' biases toward `count` and `mem` rules. We provide a single example $a^l \rightarrow b^l$ as the training set, varying $l \in \{10, 20, 30, 40\}$. We report the learners' performances in Table 1a. We observe that, independently of the length of the training example l, CNN-s2s and Transformer learners inferred perfectly the `mem` rule with FPA-`mem` > 0.90 (i.e. more than 90% of the random seeds output b^l for any given input a^m).

However, LSTM-based learners demonstrate a more complex behavior. With $l = 10$, both learners (with and without attention) exhibit a preference for `mem`. Indeed, while these learners rarely generalize perfectly to any of the hypothesis (0.0 FPA (no att.), 0.2/0.0 FPA for `mem`/`count` (att.)), they have significantly lower L-`mem`. As l increases, LSTM-based learners become more biased toward `count`. Surprisingly, for $l \geq 30$, most learner instances show sufficiently strong inductive biases to infer *perfectly* the non-trivial `count` hypothesis. With $l = 40$, 99% of random seeds of LSTM-s2s att. and *all* (100%) of LSTM-s2s no att. seeds generalized perfectly to `count`.

Further, we see that if L shows similar trends, it has a higher sensitivity. For example, while both LSTM-based learners have a similar FPA with $l = 40$, L demonstrates that LSTM-s2s no att. has a stronger `count` bias.

Add-or-Multiply In this task, we examine learners' generalization after training on the single example $a^l \rightarrow b^{2l}$. We vary $l \in \{5, 10, 15, 20\}$. In Table 1b, we report FPA and L for the three generalization hypotheses, `add`, `mul`, and `mem`. We observe, similarly to the previous task, that CNN-s2s and Transformer learners always converge perfectly to memorization.

In contrast, LSTM-based learners show non-trivial generalizations. Examining first LSTM-s2s att., when l=5, we note that `mem` has a high FPA and an L considerably lower than others. This is

	length l	FPA count	FPA mem	L, nats count	L, nats mem
LSTM-s2s no att.	40	1.00	0.00	**0.01***	97.51
	30	0.97	0.00	**0.01***	72.67
	20	0.07	0.00	**2.49***	55.67
	10	0.00	0.00	88.27	**48.67***
LSTM-s2s att.	40	0.99	0.00	**7.84***	121.48
	30	0.96	0.02	**1.14***	83.48
	20	0.70	0.16	**5.73***	49.33
	10	0.00	0.20	98.12	**8.46***
CNN-s2s	$\{10, 20, 30, 40\}$	0.00	> 0.90	> 592.92	**<1.31***
Transformer	$\{10, 20, 30, 40\}$	0.00	> 0.97	> 113.30	**<11.14***

(a) Count-or-Memorization

	length l	FPA add	FPA mul	FPA mem	L, nats add	L, nats mul	L, nats mem
LSTM-s2s no att.	20	0.00	0.94	0.00	25.42	**0.31***	57.32
	15	0.07	0.65	0.00	19.24	**4.67***	43.65
	10	0.95	0.01	0.00	**0.68***	26.58	25.15
	5	0.04	0.00	0.00	**17.12**	50.83	18.60
LSTM-s2s att.	20	0.00	0.98	0.00	30.26	**1.40***	58.84
	15	0.15	0.83	0.00	20.18	**4.07***	46.36
	10	0.40	0.28	0.18	**13.69**	18.16	26.44
	5	0.00	0.00	0.97	45.88	77.86	**0.01***
CNN-s2s	$\{5, 10, 15, 20\}$	0.00	0.00	1.0	> 318.12	> 346.19	**0.00***
Transformer	$\{5, 10, 15, 20\}$	0.00	0.00	1.0	> 38.77	> 50.64	**<3.50***

(b) Add-or-Multiply

	FPA hierar	FPA linear	L, nats hierar	L, nats linear
LSTM-s2s no att.	0.05	0.00	**31.04***	61.84
LSTM-s2s att.	0.30	0.00	**26.32***	57.2
CNN-s2s	0.00	1.00	202.64	**0.00***
Transformer	0.69	0.00	**4.84***	35.04

(c) Hierarchical-or-Linear with depth $d = 4$

	M, examples	FPA comp	FPA mem	L, nats comp	L, nats mem
LSTM-s2s no att.	36	0.00	0.00	42.65	**38.55**
	24	0.00	0.00	238.54	**89.36***
	6	0.00	0.00	656.93	**157.55***
LSTM-s2s att.	36	0.00	0.00	**62.34***	70.92
	24	0.00	0.00	263.33	**157.82***
	6	0.00	0.00	659.85	**164.43***
CNN-s2s	36	0.75	0.00	**1.44***	49.92
	24	0.13	0.00	**13.75***	84.55
	6	0.00	0.00	131.63	**29.66***
Transformer	36	0.00	0.00	147.83	**6.36***
	24	0.00	0.00	586.22	**26.46***
	6	0.00	0.00	1235.01	**53.91***

(d) Composition-or-Memorization

Table 1: FPA measures the fraction of seeds that generalize according to a particular rule. Description length L is averaged across examples and seeds. The lowest L are in bold and $*$ denotes stat. sig. difference in L ($p < 10^{-3}$, paired t-test).

consistent with the learner's behavior in the *Count-or-Memorization* task. As we increase l, more interesting behavior emerges. First, L-mem decreases as l increases. Second, mul-type preference increases with l. Finally, L-add presents a U-shaped function of l. That is, for the medium example length l, the majority of learners switch to approximating the add rule (for $l = 10$). However, when l grows further, a considerable fraction of these learners start to follow a mul-type rule. Strikingly, 98% of LSTM-s2s att. seeds generalized perfectly to the non-trivial mul rule. As for LSTM-s2s no att., we do not observe a strong bias to infer any of the rules when $l=5$. However, when increasing l, the LSTM-s2s no att. behaves similarly to LSTM-s2s att.: at first it has a preference for add (FPA-add=0.95, for $l=10$) then for mul (e.g. FPA-mul=0.94, for $l=20$).

Hierarchical-or-Linear We look now at learners' preference for either hierar or linear generalizations. The architectures we use were only able to consistently learn the training examples with the depth d not higher than 4. Hence, in this experiment, we set d to 4.

We report in Table 1c the learners' FPA and L. We observe that CNN-s2s exhibits a strikingly different bias compared to all other learners with a perfect agreement with the linear rule. In contrast, Transformer learners show a clear preference for hierar with a high FPA (0.69) and a low L (1.21). Surprisingly, this preference increases with the embedding size and Transformers with embedding size ≥ 64 admit an FPA-hierar of 1.00 (see Appendix for more details). LSTM-s2s att. learners demonstrate also a similar preference for hierar with an FPA of 0.30 and a considerably lower L than L-hierar. Finally, while only 5% of LSTM-s2s no att. instances generalized to perfect hierar (and none to linear), L confirms their preference for the hierar hypothesis.

Composition-or-Memorization In this task, we set the number of primitives $N = 40$ and vary the number of compositional examples $M \in \{6, 24, 36\}$ seen during *training*. Results are reported in Table 1d. First, we observe that FPA is only informative for CNN-s2s when trained with a large M. Indeed, for $M = 6$, CNN-s2s does not infer any of the candidate rules. However, according to description length L, we note a significant preference for mem over comp. More compositional examples CNN-based learners see at training, more biased they become toward comp. The remaining learners have *zero* FPA for both candidate rules. However, according to description length, LSTM-based learners have preferences similar to CNN-s2s, although weaker. That is, they show a preference for mem for low M, that declines in favor of comp as M increases. In contrast, Transformers show a strong bias for mem with all tested M.

Overall, across all the above experiments, we see that seq2seq learners demonstrate strikingly different biases. In many cases, these biases lead to non-trivial generalizations when facing ambiguity in the training data. This spans tasks that probe for memorization, arithmetic, hierarchical, and compositional reasoning. We found that a single example is sufficient for LSTM-based learners to learn counting, addition, and multiplication. Moreover, within the same task, they can switch from one explanation to another, depending on the training example length, with *Addition-or-Multiplication* being the task where this switch happens twice. In contrast, CNN-s2s and Transformers show a strong bias toward memorization. Furthermore, all learners except for CNN-s2s demonstrate a strong bias toward the hierarchical behavior. In the task of compositional generalization, CNN-s2s shows a strong bias toward compositional reasoning that appears after a few compositional training examples. On the other hand, Transformers show a preference for memorization over compositional generalization.

We see that the conclusions derived from comparing the description length of the candidate rules are in agreement with the results under accuracy-based metrics, but provide a more nuanced picture.

Robustness to hyper-parameters We observe that learners' biases depend, in many cases, on the length/number of the input examples. In Appendix, we examine impact of other hyper-parameters. In particular, we study impact of (1) learners' architecture size, by varying the number of layers, hidden and embedding sizes, and (2) dropout probability. Our results show that in some cases a learner's architecture size can influence the strength of inductive biases, but rarely modify them: among the 136 tested settings, we observe only 3 cases of switching the preferences. We also found that large dropout probabilities are necessary to prevent mem-type generalization.

6 RELATED WORK

Dessì and Baroni (2019) found that, unlike LSTM-s2s learners, CNN-s2s can perform compositional generalization on SCAN. Our experiments indicate that this only happens when enough compositional examples are provided in the training. Moreover, in such a case, attention-enabled LSTM-s2s also start to prefer compositional generalization over memorization.

McCoy et al. (2020) studied inductive biases of recurrent neural architectures in two synthetic tasks, English question formation and tense inflection. They found that only tree-based architectures show robust preference for hierarchical reasoning, in contrast to LSTM-s2s learners that generalized linearly. Our experiments on the hyperparameter robustness, reported in Appendix, indicate that the preferences over linear/hierarchical reasoning are strongly affected by the dropout probability, with learners shifting to linear behavior with low probabilities. As McCoy et al. (2020) experimented with a low dropout probability of 0.1, we believe this explains the misalignment of the conclusions.

Overall, our study shows that the inductive biases is more complicated than it seemed in these prior works and a more careful analysis is crucial. We believe that our extremely controlled setup with very little confounds is a good addition for those studies.

Another line of research investigates theoretically learners' capabilities, that is, the classes of the hypothesis that a learner can discover (Siegelmann and Sontag, 1992; Merrill et al., 2020). For example, Weiss et al. (2018) demonstrated that LSTM cells can count. In turn, we demonstrate that LSTM-s2s learners are not only capable but also *biased* toward arithmetic behavior.

7 DISCUSSION AND CONCLUSION

In this work, we studied inductive biases of standard seq2seq learners, Transformer-, LSTM-, and CNN-based. To do so, we introduced four new tasks, which allowed us to cover an interesting spectrum of behaviors useful for language learning. In particular, we considered arithmetic, hierarchical, and compositional "reasoning". Next, we connected the problem of finding and measuring inductive biases to Solomonoff's theory of induction and proposed to use a dataset's description length under a learner as a tool for sensitive measurement of inductive biases.

In our experiments, we found that the seq2seq learners have strikingly different inductive biases and some of them generalize non-trivially when facing ambiguity. For instance, a single training example is sufficient for LSTM-based learners to learn perfectly how to count, to add and to multiply by a constant. Transformers and, to a lesser degree, LSTM-s2s demonstrated preferences for the hierarchical bias, a bias that has been argued to govern children's acquisition of syntax. Interestingly, such biases arose with no explicit wiring for them. Our results support then Elman et al. (1998)'s theory which states that human's inductive biases can arise from low-level architectural constraints in the brain with no need for an explicit encoding of a linguistic structure. However, how the brain, or, more generally, a learner is wired to admit a specific inductive bias is still an important open question.

Across our experiments, we also observed that description length is consistent with "intuitive" measurements of inductive biases, and, at the same time, it turned out to be more sensitive. This also indicates that, in the presence of ambiguity in the training data, a learner is more likely to follow the alternative with the shorter description length (i.e. the simplest one) when applied on unseen data, showing consistency with the prescriptions of the theory of induction (Solomonoff, 1964). A similar simplicity preference is argued to play a role in human language acquisition (Perfors et al., 2011).

Our findings can provide a guidance for architecture selection in the low-data regimes where inductive biases might have a higher influence on model's generalization performance. Large sparse datasets can also benefit from predictable behavior in few-shot scenarios akin to what we consider.

Finally, our results demonstrate that relatively large deep learning models *can* generalize non-trivially from as little as one example – as long as the task is aligned with the their inductive biases. We believe this should reinforce interest in future work on injecting useful inductive biases in our learners and, we hope, our findings and setup can provide a fertile ground for such work.

REFERENCES

Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. In *NeurIPS*, 2014.

Angela Fan, Mike Lewis, and Yann Dauphin. Hierarchical neural story generation. In *ACL*, 2018.

Daniel Adiwardana, Minh-Thang Luong, David R So, Jamie Hall, Noah Fiedel, Romal Thoppilan, Zi Yang, Apoorv Kulshreshtha, Gaurav Nemade, Yifeng Lu, et al. Towards a human-like open-domain chatbot. *arXiv preprint arXiv:2001.09977*, 2020.

Emmanuel Dupoux. Cognitive science in the era of artificial intelligence: A roadmap for reverse-engineering the infant language-learner. *Cognition*, 173:43–59, 2018.

Joao Loula, Marco Baroni, and Brenden M Lake. Rearranging the familiar: Testing compositional generalization in recurrent networks. *arXiv preprint arXiv:1807.07545*, 2018.

Brenden M Lake and Marco Baroni. Generalization without systematicity: On the compositional skills of sequence-to-sequence recurrent networks. *arXiv preprint arXiv:1711.00350*, 2017.

Joost Bastings, Marco Baroni, Jason Weston, Kyunghyun Cho, and Douwe Kiela. Jump to better conclusions: SCAN both left and right. In *EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, 2018.

Noam Chomsky. *Aspects of the Theory of Syntax*, volume 11. MIT press, 1965.

Brenden M Lake, Tal Linzen, and Marco Baroni. Human few-shot learning of compositional instructions. *arXiv preprint arXiv:1901.04587*, 2019.

Samuel Ritter, David GT Barrett, Adam Santoro, and Matt M Botvinick. Cognitive psychology for deep neural networks: A shape bias case study. In *ICML*, 2017.

Reuben Feinman and Brenden M Lake. Learning inductive biases with simple neural networks. *arXiv preprint arXiv:1802.02745*, 2018.

Noam Chomsky. Rules and representations: behavioral and brain sciences, 1980.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Michael C Mozer, and Yoram Singer. Identity crisis: Memorization and generalization under extreme overparameterization. *arXiv preprint arXiv:1902.04698*, 2019.

Ray J Solomonoff. A formal theory of inductive inference. part i. *Information and control*, 7(1):1–22, 1964.

Jorma Rissanen. Modeling by shortest data description. *Automatica*, 14(5):465–471, 1978.

Peter Grunwald. A tutorial introduction to the minimum description length principle. *arXiv preprint math/0406077*, 2004.

R Thomas McCoy, Robert Frank, and Tal Linzen. Does syntax need to grow on trees? sources of hierarchical inductive bias in sequence-to-sequence networks. *arXiv preprint arXiv:2001.03632*, 2020.

Léonard Blier and Yann Ollivier. The description length of deep learning models. In *NeurIPS*. 2018.

David JC MacKay. *Information theory, inference and learning algorithms*. Cambridge university press, 2003.

Rahma Chaabouni, Eugene Kharitonov, Alessandro Lazaric, Emmanuel Dupoux, and Marco Baroni. Word-order biases in deep-agent emergent communication. *arXiv preprint arXiv:1905.12330*, 2019.

Gail Weiss, Yoav Goldberg, and Eran Yahav. On the practical computational power of finite precision rnns for language recognition. *arXiv preprint arXiv:1805.04908*, 2018.

Jonas Gehring, Michael Auli, David Grangier, Denis Yarats, and Yann N Dauphin. Convolutional sequence to sequence learning. In *ICML*, 2017.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *NeurIPS*, 2017.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*, 2014.

Yann LeCun, Bernhard E Boser, John S Denker, Donnie Henderson, Richard E Howard, Wayne E Hubbard, and Lawrence D Jackel. Handwritten digit recognition with a back-propagation network. In *NeurIPS*, 1990.

Yann N Dauphin, Angela Fan, Michael Auli, and David Grangier. Language modeling with gated convolutional networks. In *ICML*. JMLR. org, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.

Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. fairseq: A fast, extensible toolkit for sequence modeling. In *NAACL-HLT 2019: Demonstrations*, 2019.

Roberto Dessì and Marco Baroni. Cnns found to jump around more skillfully than rnns: Compositional generalization in seq2seq convolutional networks. In *ACL*, 2019.

Hava T. Siegelmann and Eduardo D. Sontag. On the computational power of neural nets. In *COLT*, 1992.

William Merrill, Gail Weiss, Yoav Goldberg, Roy Schwartz, Noah A. Smith, and Eran Yahav. A formal hierarchy of rnn architectures, 2020.

Jeffrey L Elman, Elizabeth A Bates, Mark H Johnson, Annette Karmiloff-Smith, Kim Plunkett, and Domenico Parisi. *Rethinking innateness: A connectionist perspective on development*, volume 10. MIT press, 1998.

Amy Perfors, Joshua B Tenenbaum, and Terry Regier. The learnability of abstract syntactic principles. *Cognition*, 118(3):306–338, 2011.

Léon Bottou, Frank E Curtis, and Jorge Nocedal. Optimization methods for large-scale machine learning. *Siam Review*, 60(2):223–311, 2018.

A CAN SEQ2SEQ LEARNERS MULTIPLY BY 3?

In our experiments on the *Multiply-or-Add* task we saw that LSTM-s2s learners are able to learn to multiply by 2 from a single example. A natural further question is whether these learners can learn to multiply by larger numbers? Here we only provide a preliminary study in a hope to inspire more focused studies.

We build a task that is similar to *Multiply-or-Add*, but centered around multiplication by 3 instead of 2. The single training example represents a mapping of an input string a^l to an output string b^{3l}. As test inputs, we use a^m with m coming from an interval $[l-3, l+3]$.

Since $3x$ can be represented as a combination of addition and multiplication in several ways ($3x = x + 2x = 2x + x$), we consider 4 different candidate rules. As before, by mem we denote the constant mapping from $a^m \rightarrow b^{3l}$. mul1 represents the mapping $a^m \rightarrow b^{2l+m}$. mul2 corresponds to $a^m \rightarrow b^{l+2m}$ and mul3 denotes $a^m \rightarrow b^{3m}$. The "explanation" mul1 is akin to the add rule in the *Multiply-or-Add* task. We use the same hyperparameters and training procedure described in Section 4.

We report the results in Table 2. Like the results observed in the *Multiply-or-Add* task, both CNN-s2s and Transformer learners show a strong preference for the mem rule while LSTM-based learners switch their generalization according to the length of the training example l. Indeed, for CNN-s2s and Transformer, we note an FPA-mem>0.97 independently of l (with L-mem significantly lower than others). LSTM-s2s att. learners start inferring the mem rule for $l = 5$ (FPA=0.64, L=2.44), then switch to comparable preference for mul2 and mul3 when $l = 10$, and finally show a significant bias toward the mul3 hypothesis for $l \in \{15, 20\}$ (e.g. FPA-mul3=0.76 for $l = 15$). LSTM-s2s no att. learners are also subject to a similar switch of preference. That is, for $l = 5$, these learners have a significant bias toward mul1 (FPA=0.49). Strikingly, when $l = 10$, 92% LSTM-s2s no att. learners inferred perfectly the mul2 rule after one training example. Finally, we observe again another switch to approximate mul3 for $l \in \{15, 20\}$.

Overall, while CNN-s2s and Transformer learners show a significant and robust bias toward mem, LSTM-based learners generalize differently depending on the training input length. In particular, our results suggest that these learners avoid adding very large integers by switching to the multiplicative explanation in those cases. Answering our initial question, we see that LSTM-based learners *can* learn to multiply by 3 from a single example.

---

[5]Only 21% of learners succeeded in learning the training example in this setting.

[6]Only 51% of learners succeeded in learning the training example in this setting.

		FPA				L, nats			
	length l	mul1	mul2	mul3	mem	mul1	mul2	mul3	mem
LSTM-s2s no att.	20	0.00	0.01	0.78	0.00	52.27	22.20	**1.17***	77.75
	15	0.00	0.13	0.45	0.00	40.46	13.22	**6.14***	66.10
	10	0.00	0.92	0.00	0.00	26.48	**0.65***	22.26	53.81
	5	0.49	0.00	0.00	0.00	**1.97***	26.50	54.97	36.13
LSTM-s2s att.	20^5	0.00	0.19	0.62	0.00	36.76	20.35	**9.35***	49.34
	15^6	0.00	0.14	0.76	0.00	37.84	18.42	**5.53***	56.43
	10	0.02	0.45	0.49	0.00	29.83	11.67	**8.96**	45.47
	5	0.01	0.03	0.00	0.64	32.97	48.26	60.38	**2.44***
CNN-s2s	20	0.00	0.00	0.00	0.99	263.82	262.01	261.71	**0.02***
	15	0.00	0.00	0.00	1.00	250.97	253.32	253.08	**0.00***
	10	0.00	0.00	0.00	1.00	243.17	245.16	248.28	**0.00***
	5	0.00	0.00	0.00	1.00	258.10	257.79	264.06	**0.00***
Transformer	20	0.00	0.00	0.00	0.97	37.90	51.47	57.57	**5.31***
	15	0.00	0.00	0.00	1.00	40.36	51.62	57.42	**2.50***
	10	0.00	0.00	0.00	1.00	38.05	49.88	55.61	**2.47***
	5	0.00	0.00	0.00	1.00	37.96	51.83	60.19	**0.74***

Table 2: Multiplication by 3. FPA measures the fraction of seeds that generalize according to a particular rule. Description length L is averaged across examples and seeds. The lowest L are in bold and $*$ denotes stat. sig. difference in L ($p < 10^{-3}$, paired t-test).

B ROBUSTNESS TO CHANGES IN ARCHITECTURE

In this section, we examine how changing different hyper-parameters affects learners' preferences for memorization, arithmetic, hierarchical and compositional reasoning. In particular, we vary the number of layers, hidden and embedding sizes of the different learners and test their generalization on *Count-or-Memorization*, *Add-or-Multiply*, *Hierarchical-or-Linear*, and *Composition-or-Memorization* tasks.

In all the experiments, we fix $l = 40$ and $l = 20$ for *Count-or-Memorization* and *Add-or-Multiply* respectively, $d = 4$ for *Hierarchical-or-Linear* and $M = 36$ for *Composition-or-Memorization*. Finally, we keep the same training and evaluation procedure as detailed in Section 4.2 of the main text. However, we use 20 different random seeds instead of 100.

B.1 NUMBER OF HIDDEN LAYERS (N_{Layer})

We experiment with the standard seq2seq learners described in the main paper and vary the number of layers $N_{Layer} \in \{1, 3, 10\}$. Results are reported in Table 3.

First, when looking at the interplay between mem and count (Table 3a), we observe that, independently of N_{Layer}, more than 97% of CNN-s2s and Transformer learners inferred *perfectly* the mem rule (i.e. output b^{40} for any given input a^m). Further, if the preference for count decreases with the increase of N_{Layer}, LSTM-s2s att. learners display in all cases a significant bias toward count with a large FPA and an L significantly lower than L-mem . However, we note a decline of the bias toward count when considering LSTM-s2s no att. learners. For $N_{Layer} = 1$, 100% of the seeds generalize to perfect count, versus 6% for $N_{Layer} = 10$. Note that this lower preference for count is followed by an increase of preference for mem. However, there is no significant switch of preferences according to L.

Second, we consider the *Add-or-Multiply* task where we examine the three generalization hypothesis add, mul and mem. Results are reported in Table 3b. Similarly to the previous task, Transformer and CNN-s2s learners are robust to the number of layers change. They perfectly follow the mem rule with FPA-mem=1.00. However, LSTM-based learners show a more complex behavior: If single-layer LSTM-s2s att. and no att. demonstrate a considerable bias for mul (FPA-mul>0.94), this bias fades in favor of add and memo for larger architectures.

Third, in Table 3c, we observe that larger learners are slightly less biased toward hierar and linear. However, we do not observe any switch of preferences. That is, across different N_{layers}, CNN-s2s learners prefer the linear rule, whereas Transformers and, to a lesser degree, LSTM-based learners show a significant preference for the hierar rule.

Finally, we do not observe an impact of N_{Layer} on the *Composition-or-Memorization* task (see Table 3d), demonstrating the robustness of biases w.r.t. learners' size.

In sum, we note little impact of N_{Layer} on learners' generalizations. Indeed, *LSTM-based learners can learn to perform counting from a single training example, even when experimenting with 10-layer architectures.* For most tested N_{Layer}, they favor `mul` and `add` over `mem`. In contrast, Transformer and CNN-s2s perform systematic memorization of the single training example. Furthermore, independently of N_{Layer}, Transformer and LSTM-based learners show a bias toward the `hierar` hypothesis over the `linear` one, while CNN-based learners do the opposite. Finally, the compositional experiments further support how inductive biases are barely influenced by the change of the number of layers.

B.2   HIDDEN SIZE (S_{Hidden})

We experimented in the main text with standard seq2seq learners when hidden size $S_{Hidden} = 512$. In this section, we look at the effect of S_{Hidden} varying it in $\{128, 512, 1024\}$. We report learners performances in Table 4.

First, Table 4a demonstrates how minor effect hidden size has on learners counting/memorization performances. Indeed, for any given S_{Hidden}, between 84% and 100% of LSTM-based learners learn perfect counting after only one training example. Similarly, and with even a lower variation, more than 91% of Transformer and CNN-s2s learners memorize the single training example outputting b^{40} for any given a^m.

The same observation can be made when studying the interplay between the `hierar` and `linear` biases (Table 4c) and `comp` and `mem` biases (Table 4d). Concretely, Tables 4c and 4d show that learners' generalizations are stable across S_{Hidden} values with the exception of LSTM-based learners that loose significance for some tested S_{Hidden} values. Yet, there is no switch of preference.

Finally, as demonstrated in Table 4b, *all* Transformer and CNN-s2s learners perform perfect memorization when tested on the *Add-or-Multiply* task independently of their hidden sizes. Both LSTM-based learners are significantly biased toward `mul` for $S_{Hidden} \in \{512, 1024\}$. However, when experimenting with smaller S_{Hidden} (=128), we detect a switch of preference for LSTM-s2s no att. learners. The latter start approximating `add`-type rule (with significantly lower L). Lastly, we do not distinguish any significant difference between `add` and `mul` for LSTM-s2s att. when $S_{Hidden} = 128$.

Taken together, learners' biases are quite robust to S_{Hidden} variations. We however note a switch of preference from `mul` to `add` for LSTM-s2s no att. learners when decreasing S_{Hidden}. Furthermore, we see a loss of significant preference in five distinct settings.

B.3   EMBEDDING SIZE (S_{Emb})

We look here at the effect of the embedding size, S_{Emb}, on learners' generalizations. In particular, we vary $S_{Emb} \in \{16, 64, 256\}$. Results are reported in Table 5.

Across sub-tables 5a, 5b and 5c, we see small influence of S_{Emb} on learners' biases. For example, if we consider the *Count-or-Memorization* task when varying S_{Emb} (see Table 5a), between 95% and 100% of LSTM-s2s no att. learners inferred perfectly the `count` hypothesis. More striking, between 99% and 100% of LSTM-s2s att. learners learned the `count` rule after one training example. The same trend is observed for the remaining learners and across the other tasks; *Add-or-Multiply* (Table 5b) and *Hierarchical-or-Linear* (Table 5c). Yet, we still discern in some cases, systematic, but low, effects of S_{Emb}. First, the larger S_{Emb} is, the lower FPA-`mul` of LSTM-s2s no att. learners is (from 0.94 for $S_{Emb} = 16$ to 0.84 for $S_{Emb} = 256$). However, LSTM-s2s no att. learners still have considerable preference for `mul` for any tested S_{Emb}. Second, we see an increase of Transformer's preference for `hierar` with the increase of S_{Emb}. Surprisingly, for $S_{Emb} \geq 64$, 100% of Transformer learners generalize to perfect `hierar` hypothesis.

Finally, when considering the *Composition-or-Memorization* task, we observe in Table 5d, for all learners, a tendency to prefer `comp` generalization when S_{Emb} is large. For example, if, for LSTM-based learners, we note 0.00 `comp`-FPA when $S_{Emb} = 16$, `comp`-FPA≥ 0.85 with $S_{Emb} = 256$. Interestingly, Transformers switch their preference, showing a significant bias toward compositional reasoning with $S_{Emb} = 256$.

In this section, we studied the impact of the number of layers, hidden and embedding sizes on learners' generalizations. We found that, if these hyper-parameters can influence, in some cases, the degree of one learner's preference w.r.t. a given rule, inductive biases are quite robust to their changes. In particular, among all tested combinations, we observe only 3 cases of preference switch (out of 136).

C   ROBUSTNESS TO CHANGES IN TRAINING PARAMETERS

We examine here the effect of the training parameters on learners' biases. As previously, we only consider the *Count-or-Memorization* task with $l = 40$, the *Add-or-Multiply* task with $l = 20$, the *Hierarchical-or-Linear* task

		FPA		L, nats	
	N_{Layer}	count	mem	count	mem
LSTM-s2s no att.	1	1.00	0.00	**0.01***	97.51
	3	0.80	0.00	**0.00***	60.80
	10	0.06	0.47	**16.89**	22.02
LSTM-s2s att.	1	0.99	0.00	**7.84***	121.48
	3	0.50	0.00	**11.30***	57.57
	10	0.39	0.22	**22.86***	45.13
CNN-s2s	1	0.00	0.98	660.73	**0.02***
	3	0.00	1.00	1685.18	**0.00***
	10	-	-	-	-
Transformer	1	0.00	0.97	116.34	**11.10***
	3	0.00	1.00	139.58	**0.31***
	10	-	-	-	-

(a) Count-or-Memorization

		FPA			L, nats		
	N_{Layer}	add	mul	mem	add	mul	mem
LSTM-s2s no att.	1	0.00	0.94	0.00	25.42	**0.31***	57.32
	3	0.15	0.20	0.00	**9.82**	10.11	33.16
	10	0.28	0.00	0.33	**5.83**	23.16	10.01
LSTM-s2s att.	1	0.00	0.98	0.00	30.26	**1.40***	58.84
	3	0.65	0.20	0.00	**5.88***	15.67	27.82
	10	0.11	0.11	0.28	9.66	27.72	**8.26**
CNN-s2s	1	0.00	0.00	1.00	318.12	346.19	**0.00***
	3	0.00	0.00	1.00	1058.27	824.93	**2.31***
	10	-	-	-	-	-	-
Transformer	1	0.00	0.00	1.00	38.77	50.64	**3.50***
	3	0.00	0.00	1.00	40.03	57.73	**0.18***
	10	-	-	-	-	-	-

(b) Add-or-Multiply

		FPA		L, nats	
	N_{Layer}	hierar	linear	hierar	linear
LSTM-s2s no att.	1	0.05	0.00	**31.04***	61.84
	3	0.00	0.00	**29.08***	50.92
	10	-	-	-	-
LSTM-s2s att.	1	0.30	0.00	**26.32***	57.20
	3	0.00	0.00	**32.32***	50.12
	10	-	-	-	-
CNN-s2s	1	0.00	1.00	202.64	**0.00***
	3	0.00	0.70	222.32	**1.84***
	10	-	-	-	-
Transformer	1	0.69	0.00	**4.84***	35.04
	3	0.56	0.00	**5.48***	29.16
	10	-	-	-	-

(c) Hierarchical-or-Linear

		FPA		L, nats	
	N_{Layer}	comp	mem	comp	mem
LSTM-s2s no att.	1	0.00	0.00	42.65	**38.55**
	3	0.00	0.00	37.01	**34.16**
	10	-	-	-	-
LSTM-s2s att.	1	0.00	0.00	**62.34***	70.92
	3	0.00	0.00	**46.10***	58.79
	10	-	-	-	-
CNN-s2s	1	0.75	0.00	**1.44***	49.92
	3	0.95	0.00	**1.79***	66.44
	10	-	-	-	-
Transformer	1	0.00	0.00	147.83	**6.36***
	3	0.00	0.00	98.45	**14.43***
	10	-	-	-	-

(d) Composition-or-Memorization

Table 3: **Effect of the number of layers** (N_{Layer}): FPA measures the fraction of seeds that generalize according to a particular rule. Description length L is averaged across examples and seeds. The lowest L are in bold and $*$ denotes stat. sig. difference in L ($p < 10^{-2}$, paired t-test.). '-' denotes settings where learners have lower than 70% success rate on the train set.

	S_{Hidden}	FPA		L, nats	
		count	mem	count	mem
LSTM-s2s no att.	128	0.84	0.00	**8.25***	109.84
	512	1.00	0.00	**0.01***	97.51
	1024	1.00	0.00	**0.00***	149.86
LSTM-s2s att.	128	0.90	0.00	**0.01***	89.31
	512	0.99	0.00	**7.84***	121.48
	1024	1.00	0.00	**0.00***	300.93
CNN-s2s	128	0.00	1.00	805.01	**0.00***
	512	0.00	0.98	660.73	**0.02***
	1024	0.00	1.00	993.85	**0.00***
Transformer	128	0.00	0.91	110.68	**9.57***
	512	0.00	0.97	116.34	**11.10***
	1024	0.00	0.94	122.38	**1.42***

(a) Count-or-Memorization

	S_{Hidden}	FPA			L, nats		
		add	mul	mem	add	mul	mem
LSTM-s2s no att.	128	0.00	0.00	0.00	**7.56***	19.66	43.72
	512	0.00	0.94	0.00	25.42	**0.31***	57.32
	1024	0.25	0.75	0.00	30.29	**5.26***	77.99
LSTM-s2s att.	128	0.00	0.00	0.00	**15.32**	17.37	45.09
	512	0.00	0.98	0.00	30.26	**1.40***	58.84
	1024	0.00	1.00	0.00	51.70	**3.09***	86.82
CNN-s2s	128	0.00	0.00	1.00	281.34	301.75	**0.02***
	512	0.00	0.00	1.00	318.12	346.19	**0.00***
	1024	0.00	0.00	1.00	520.75	508.75	**0.00***
Transformer	128	0.00	0.00	1.00	35.21	46.07	**2.94***
	512	0.00	0.00	1.00	38.77	50.64	**3.50***
	1024	0.00	0.00	1.00	38.74	51.71	**0.88***

(b) Add-or-Multiply

	S_{Hidden}	FPA		L, nats	
		hierar	linear	hierar	linear
LSTM-s2s no att.	128	0.00	0.00	**30.40***	79.00
	512	0.05	0.00	**31.04***	61.84
	1024	0.00	0.00	60.24	**47.24**
LSTM-s2s att.	128	0.00	0.00	**32.72***	72.28
	512	0.30	0.00	**26.32***	57.2
	1024	0.05	0.00	**65.80**	73.80
CNN-s2s	128	0.00	0.95	178.88	**0.00***
	512	0.00	1.00	202.64	**0.00***
	1024	0.00	0.95	225.36	**0.12***
Transformer	128	0.75	0.00	**2.96***	36.92
	512	0.69	0.00	**4.84***	35.04
	1024	0.75	0.00	**31.04***	61.84

(c) Hierarchical-or-Linear

	S_{Hidden}	FPA		L, nats	
		comp	mem	comp	mem
LSTM-s2s no att.	128	0.00	0.00	**37.67***	58.52
	512	0.00	0.00	42.65	**38.55**
	1024	0.00	0.00	**37.66***	79.71
LSTM-s2s att.	128	0.00	0.00	66.65	**63.84**
	512	0.00	0.00	**62.34***	70.92
	1024	0.00	0.00	**42.38***	73.28
CNN-s2s	128	0.85	0.00	**0.99***	53.38
	512	0.75	0.00	**1.44***	49.92
	1024	0.80	0.00	**1.24***	54.86
Transformer	128	0.00	0.00	155.50	**6.23***
	512	0.00	0.00	147.83	**6.36***
	1024	0.00	0.00	151.70	**6.02***

(d) Composition-or-Memorization

Table 4: **Effect of the hidden size** (S_{Hidden}): FPA measures the fraction of seeds that generalize according to a particular rule. Description length L is averaged across examples and seeds. The lowest L are in bold and $*$ denotes stat. sig. difference in L ($p < 10^{-2}$, paired t-test).

	S_{Emb}	FPA		L, nats	
		count	mem	count	mem
LSTM-s2s no att.	16	1.00	0.00	**0.01***	97.51
	64	0.95	0.00	**0.00***	91.54
	256	1.00	0.00	**0.00***	90.32
LSTM-s2s att.	16	0.99	0.00	**7.84***	121.48
	64	1.00	0.00	**11.12***	117.39
	256	1.00	0.00	**9.79***	127.31
CNN-s2s	16	0.00	0.98	660.73	**0.02***
	64	0.00	1.00	670.53	**0.00***
	256	0.00	0.95	826.23	**0.01***
Transformer	16	0.00	0.97	116.34	**11.10***
	64	0.00	1.00	232.53	**0.00***
	256	0.00	1.00	338.88	**0.00***

(a) Count-or-Memorization

	S_{Emb}	FPA			L, nats		
		add	mul	mem	add	mul	mem
LSTM-s2s no att.	16	0.00	0.94	0.00	25.42	**0.31***	57.32
	64	0.05	0.90	0.00	23.70	**1.41***	51.33
	256	0.05	0.84	0.00	20.42	**1.33***	51.34
LSTM-s2s att.	16	0.00	0.98	0.00	30.26	**1.40***	58.84
	64	0.07	0.93	0.00	26.71	**2.54***	50.65
	256	0.00	1.00	0.00	26.83	**1.94***	51.20
CNN-s2s	16	0.00	0.00	1.00	318.12	346.19	**0.00***
	64	0.00	0.00	1.00	293.86	294.50	**0.00***
	256	0.00	0.00	1.00	486.81	447.20	**0.00***
Transformer	16	0.00	0.00	1.00	38.77	50.64	**3.50***
	64	0.00	0.00	1.00	87.11	142.83	**0.00***
	256	0.00	0.00	1.00	118.34	172.65	**0.00***

(b) Add-or-Multiply

	S_{Emb}	FPA		L, nats	
		hierar	linear	hierar	linear
LSTM-s2s no att.	16	0.05	0.00	**31.04***	61.84
	64	0.10	0.00	**34.44***	72.2
	256	0.00	0.00	**36.32**	76.56
LSTM-s2s att.	16	0.30	0.00	**26.32***	57.2
	64	0.30	0.00	**23.4**	72.68
	256	0.05	0.00	**55.56***	90.76
CNN-s2s	16	0.00	1.00	202.64	**0.00***
	64	0.00	1.00	227.12	**0.08***
	256	0.00	0.94	419.28	**8.84***
Transformer	16	0.69	0.00	**4.84***	35.04
	64	1.00	0.00	**0.00***	81.16
	256	1.00	0.00	**0.56***	121.68

(c) Hierarchical-or-Linear

	S_{Emb}	FPA		L, nats	
		comp	mem	comp	mem
LSTM-s2s no att.	16	0.00	0.00	42.65	**38.55**
	64	0.95	0.00	**0.11***	31.44
	256	0.95	0.00	**2.12***	23.63
LSTM-s2s att.	16	0.00	0.00	**62.34***	70.92
	64	0.95	0.00	**0.36***	47.57
	254	0.85	0.00	**0.86***	49.39
CNN-s2s	16	0.75	0.00	**1.44***	49.92
	64	1.00	0.00	**0.01***	112.09
	256	0.95	0.00	**0.18***	139.51
Transformer	16	0.00	0.00	147.83	**6.36***
	64	0.00	0.00	103.25	**69.07***
	256	0.10	0.00	**70.76***	107.54

(d) Composition-or-Memorization

Table 5: **Effect of the embedding size** (S_{Emb}): FPA measures the fraction of seeds that generalize according to a particular rule. Description length L is averaged across examples and seeds. The lowest L are in bold and * denotes stat. sig. difference in L ($p < 10^{-2}$, paired t-test).

with $d = 4$ and the *Composition-or-Memorization* task with $M = 36$. We experiment with the architectures detailed in the main text; however, we use 20 different random seeds instead of 100.

We consider in this section two different hyperparameters: (1) the choice of the optimizer, and (2) the dropout probability.

Optimizer We experiment with replacing the Adam optimizer (Kingma and Ba, 2014) with SGD (Bottou et al., 2018). We found experimentally that learners failed to learn the training examples consistently in most of the settings. Yet, when successful, they showed the same preferences. In particular, Transformer and CNN-s2s were the only learners that had good performances on *Count-or-Memorization* and *Add-or-Multiply* train sets (success rate higher than 70%). These learners showed a prefect generalization to the mem rule in both tasks.

Dropout We then examine how the dropout probability affects learners' preferences. We use, as mentioned in the main paper, Adam optimizer and vary the dropout probability $dropout \in \{0.0, 0.2, 0.5\}$. Results are reported in Table 6.

Both *Count-or-Memorization* (Table 6a) and *Add-or-Multiply* (Table 6b) tasks show the same trend. First, Transformer and CNN-s2s learners prefer consistently the mem rule. Second, when looking at LSTM-based learners, we distinguish a more complex behavior. For $dropout \geq 0.2$, LSTM-based learners show a significant preference for arithmetic reasoning (count for the *Count-or-Memorization* task and mul for the *Add-or-Multiply* task). However, when $dropout = 0.0$, we see different preferences. In particular, both LSTM-based learners show a preference for mem (not significant for LSTM-s2s att.), LSTM-s2s no att. learners are significantly biased toward add whereas LSTM-s2s att. do not show any significant bias with a slight preference for mem. In sum, the lower $dropout$ is, the more likely learners will overfit the mem rule.

The same observation holds for the *Composition-or-Memorization* task in Table 6d. That is, $dropout$ has no impact on CNN-s2s and Transformer biases (the former show a significant preference for comp while the latter prefers mem for any tested $dropout$ value), but does impact LSTM-based learners' biases, such as a $dropout = 0.0$ favors memorization.

Finally, we consider the *Hierarchical-or-Linear* task (see Table 6c). We observe that, for any $dropout$ value, CNN-s2s and Transformer inductive biases remain the same. Indeed, CNN-s2s learners show a consistent preference for linear with FPA≥ 0.75 while Transformers prefer hierar (note that this preference is not very large for $dropout = 0.0$ with an FPA-hierar of 0.05, compared to an FPA-hierar of 1.00 and 0.69 for $dropout = 0.2$ and 0.5 respectively). On the other hand, $dropout$ has a larger impact on LSTM-based learners. When $dropout = 0.5$, both LSTM-s2s prefer the hierar hypothesis. However, for $dropout = 0.0$, both learners do not show any significant preference for any of the rules (with 0 FPA for both rules and close L values).

	dropout	FPA count	mem	L, nats count	mem
LSTM-s2s no att.	0.0	0.00	0.20	56.23	**16.52***
	0.2	0.95	0.00	**0.17***	60.15
	0.5	1.00	0.00	**0.01***	97.51
LSTM-s2s att.	0.0	0.32	0.68	63.30	**47.68**
	0.2	0.95	0.05	**33.66***	87.36
	0.0	0.99	0.00	**7.84***	121.48
CNN-s2s	0.0	0.00	0.55	1034.67	**0.43***
	0.2	0.00	0.98	999.62	**0.01***
	0.5	0.00	0.98	660.73	**0.02***
Transformer	0.0	0.00	0.65	261.02	**1.17***
	0.2	0.00	1.00	171.31	**0.05***
	0.5	0.00	0.97	116.34	**11.10***

(a) Count-or-Memorization

	dropout	FPA add	mul	mem	L, nats add	mul	mem
LSTM-s2s no att.	0.0	0.25	0.00	0.00	**5.00***	35.55	19.07
	0.2	0.30	0.45	0.00	12.07	**11.04**	37.39
	0.5	0.00	0.94	0.00	25.42	**0.31***	57.32
LSTM-s2s att.	0.0	0.00	0.11	0.58	25.09	36.33	**12.09**
	0.2	0.18	0.53	0.18	22.22	**9.92***	34.48
	0.5	0.00	0.98	0.00	30.26	**1.40***	58.84
CNN-s2s	0.0	0.00	0.00	0.65	236.41	247.52	**0.42***
	0.2	0.00	0.00	1.00	438.06	464.26	**0.00***
	0.5	0.00	0.00	1.00	318.12	346.19	**0.00***
Transformer	0.0	0.00	0.00	0.65	84.58	130.88	**0.96***
	0.2	0.00	0.00	1.00	65.62	99.05	**0.02***
	0.5	0.00	0.00	1.00	38.77	50.64	**3.50***

(b) Add-or-Multiply

	dropout	FPA hierar	linear	L, nats hierar	linear
LSTM-s2s no att.	0.0	0.00	0.00	**16.38**	17.72
	0.2	0.00	0.00	**11.09***	19.87
	0.5	0.05	0.00	**7.76***	15.46
LSTM-s2s att.	0.0	0.00	0.00	31.12	**28.61**
	0.2	0.00	0.00	**10.63**	17.55
	0.5	0.30	0.00	**6.58***	14.30
CNN-s2s	0.0	0.00	0.75	68.48	**0.44***
	0.2	0.00	1.00	99.42	**1.16***
	0.5	0.00	1.00	50.66	**0.00***
Transformer	0.0	0.05	0.00	**3.99***	8.56
	0.2	1.00	0.00	**0.09***	13.09
	0.5	0.69	0.00	**1.21***	8.76

(c) Hierarchical-or-Linear

	dropout	FPA comp	mem	L, nats comp	mem
LSTM-s2s no att.	0.0	0.00	0.00	32.66	**11.15***
	0.2	0.30	0.00	**6.42**	11.01
	0.5	0.00	0.00	42.65	**38.55**
LSTM-s2s att.	0.0	0.00	0.00	22.24	**10.93***
	0.2	0.45	0.00	**4.38***	35.14
	0.5	0.00	0.00	**62.34***	70.92
CNN-s2s	0.0	0.30	0.00	**53.00***	92.06
	0.2	0.75	0.00	**0.37***	110.50
	0.5	0.75	0.00	**1.44***	49.92
Transformer	0.0	0.00	0.00	129.65	**27.12***
	0.2	0.00	0.00	102.90	**27.56***
	0.5	0.00	0.00	147.83	**6.36***

(d) Composition-or-Memorization

Table 6: **Effect of dropout probability**: FPA measures the fraction of seeds that generalize according to a particular rule. Description length L is averaged across examples and seeds. The lowest L are in bold and $*$ denotes stat. sig. difference in L ($p < 10^{-2}$, paired t-test).

D   SCAN

In the main text, we studied preferences of the learners toward compositional generalization in the *Composition-or-Memorization* task. Here, we resort to a larger-scale SCAN task (Lake and Baroni, 2017), which can be thought of as a generalization of *Composition-or-Memorization* with multiple modifiers. In SCAN, inputs are sequences that represent trajectories and outputs are step-wise instructions for following these instructions (see Figure 2). We experiment with the SCAN-jump split of the dataset, where the test set (7706 examples) is obtained by filtering all compositional uses of one of the primitives, `jump`. The train set (14670 examples) contains all uses of all other primitives (including compositional), and lines where `jump` occurs in isolation (only as a primitive). This makes the training data ambiguous only for the `jump` instruction. However, learners can transfer compositional rules across the primitives. We refer to this split simply as SCAN.

We consider two generalizations: (1) all input sequences with `jump` are mapped to a single instruction `JUMP` as memorized from the training examples, or (2) underlying compositional grammar. We call them `mem` and `comp`, respectively. We used the original test as a representative of the `comp` candidate explanation and generated one for `mem` ourselves.

Sequence-to-sequence learners   When experimenting with SCAN, we use the following models:
LSTM-s2s: We chose the architecture used in Lake and Baroni (2017). In particular, Encoder and Decoder are two hidden layers with 200 units and embedding of dimension 32. This architecture gets 0.98 test accuracy on the i.i.d. (simple) split of SCAN, averaged over 10 seeds.
CNN-s2s: We use one of the successful CNN-s2s models of Dessì and Baroni (2019) that has 5 layers and embedding size of 128. We also vary kernel size in $\{3, 5, 8\}$ as it was found to impact the performance on SCAN (Dessì and Baroni, 2019). These architectures reach test accuracy above 0.98 on the i.i.d. split of SCAN, averaged over 10 seeds.
Transformer: We believe our work is the first study of Transformer's performance on SCAN. For both Encoder and Decoder, we use 8 attention heads, 4 layers, embedding size of 64, FFN layer dimension of 256. This architecture gets 0.94 test accuracy on the i.i.d. split of SCAN, averaged over 10 seeds.

Training and evaluation   We follow the same scenario described in the main paper with two differences: (a) when calculating L, we use blocks of size 1024, (b) during training, we sample 10^4 batches with replacement, similar to (Lake and Baroni, 2017). We use batches of size 16 for LSTM-s2s & CNN-s2s, and 256 for Transformer. We repeat the training/evaluation of each learner 10 times, varying the random seed. Again, we use Adam optimizer and a learning rate of 10^{-3}.

Results   Due to the large number of test examples and low performance of the learners, all FPA scores would be equal to zero. Hence, we follow Lake and Baroni (2017) and use per-sequence accuracy, i.e. the ratio of the sequences with all output tokens predicted correctly. We report our results in Table 7. First, we see that CNN-s2s learners have a strong preference to `comp`, both in accuracy and description length. Furthermore, we observe that with an increase in the kernel size, description length of `mem` increases, while description length of `comp` decreases, indicating that the preference for `comp` over `mem` grows with the kernel width. We believe this echoes findings of (Dessì and Baroni, 2019).

While accuracy is well below 0.01 for all other learners/candidate combinations (and rounded to 0.00), according to the description length, Transformer and LSTM-based learners *also* have preference for `comp` over `mem`. This can be due to the transfer from compositional training examples, that can make `comp` explanation most "simple" given the dataset. Hence, the failure for systematic generalization in SCAN comes not from learners' preferences for `mem`. We believe this resonates with the initial qualitative analysis in (Lake and Baroni, 2017).

jump	⇒	JUMP
jump around right	⇒	RTURN JUMP RTURN JUMP RTURN JUMP RTURN JUMP
turn left twice	⇒	LTURN LTURN
jump opposite left after walk around left	⇒	LTURN WALK LTURN WALK LTURN WALK LTURN WALK LTURN LTURN JUMP

Figure 2: Examples of SCAN trajectories and instructions, adopted from (Lake and Baroni, 2017).

	Accuracy		L, $\times 1000$ nats	
	`comp`	`mem`	`comp`	`mem`
LSTM-s2s no att.	0.00	0.00	**8.3***	45.0
LSTM-s2s att.	0.00	0.00	**9.1***	34.8
CNN-s2s, kernel width 3	0.14	0.03	**3.5***	19.0
CNN-s2s, kernel width 5	0.26	0.02	**2.0***	21.8
CNN-s2s, kernel width 8	0.36	0.01	**1.8***	24.3
Transformer	0.00	0.00	**7.3***	23.7

Table 7: SCAN: Accuracy is averaged across seeds and examples. Description length L is averaged across examples and seeds. The lowest L are in bold and $*$ denotes stat. sig. difference in L ($p < 10^{-3}$, paired t-test).