ReMCTS: Reflect-Enhanced Monte Carlo Tree Search Strategy for Code Generation

Abstract

Open-source large language models (LLMs) have achieved substantial progress in code generation and are now capable of producing function-level programs from natural-language prompts. However, many existing approaches still lack systematic mechanisms for execution feedback, error diagnosis, and reflective memory. This limitation often results in repeated errors, unstable repair behavior, and seemingly plausible programs that fail hidden tests. To address these issues, we propose ReMCTS, a **Re**flect-enhanced **M**onte **C**arlo **T**ree **S**earch Strategy for code generation. ReMCTS represents candidate programs as nodes in a search tree and extends Monte Carlo Tree Search (MCTS) with path-level reflection memory, global retrieval of error experiences, and evidence-driven reward modeling, thereby enabling a closed-loop process of "generation–execution–evaluation–reflection–re-search". We evaluate the Qwen3 series from Alibaba Cloud and DeepSeek-V4-Flash from DeepSeek on the HumanEval and MBPP-Sanitized benchmarks. Under hidden evaluation, ReMCTS known outperforms Direct `no_tests` in 8 out of 10 model–dataset pairs and surpasses ReMCTS `no_tests` in all pairs, with average improvements of 9.42 and 7.53 percentage points, respectively. In `no_tests`, ReMCTS gives a smaller positive average gain, showing that proxy evidence is useful but less stable without visible tests.

1 Introduction

Code generation is not merely a one-pass text completion task, but rather a program search problem under partially observable feedback. Even when a model generates syntactically correct code, the program can still fail on boundary conditions, interface constraints, hidden inputs, or complex logic. These failures make feedback-driven revision a necessary part of the generation process. This view is close to how human programmers solve coding tasks, in which they write an initial implementation, run it, inspect errors, reflect on the cause, revise the code, and try again. Current LLM code generation often lacks this closed-loop workflow. If the first solution follows a wrong design, later local repair may only patch symptoms while the underlying algorithm remains wrong. Therefore, an effective inference-time system should explore multiple candidate programs, execute them, record failure experience, and reuse that experience across later attempts. In real-world environments, developers usually verify programs indirectly. Prior work models this practice with compiler feedback (Bi et al., 2024), execution-and-refinement feedback (Zheng et al., 2025), unit-test feedback (Liu et al., 2023), iterative test-and-repair feedback (Tang et al., 2026), static-analysis and test loops (Ravi et al., 2026), and interactive feedback for research-code tasks (Miao et al., 2025). These studies suggest that feedback is essential for code generation. Practical open-source code models benefit from feedback when refining candidates over multiple attempts.

Existing approaches improve code generation from several perspectives. Self-Refine (Madaan et al., 2023), Reflexion (Shinn et al., 2023), and Self-Debugging (Chen et al., 2023b) repair programs with natural language feedback or execution feedback. LATS (Zhou et al., 2024) and MapCoder (Islam et al., 2024) combine language-model reasoning with search, planning, or multi-agent collaboration. CodeRL (Le et al., 2022), RLTF (Liu et al., 2023), and CODERL+ (Jiang et al., 2026) use unit tests or execution semantics to build reward signals. These studies show that feedback, search, planning, and reflection can improve code generation. However, existing approaches still leave three gaps. 1) Single-trajectory self-repair can remain trapped in an early wrong algorithmic direction. This occurs because later revisions are conditioned on the same trajectory and often patch local symptoms rather than reconsider alternative algorithms. 2) Tree-

search methods often rely on numerical rewards and underuse cross-branch natural-language error experience. Scalar rewards can rank candidates, but they do not preserve the textual diagnoses needed to help sibling branches avoid similar failures. 3) No-test tasks require distinguishing missing evidence from genuine success. Without explicit tests, semantic-only acceptance can be over-optimistic, allowing plausible but weakly checked programs to terminate the search too early.

To address these limitations, we propose ReMCTS, a Reflect-Enhanced Monte Carlo Tree Search Strategy for code generation. ReMCTS maintains multiple candidate programs in a search tree instead of repairing one candidate along a single trajectory. The multi-branch design helps the system recover from an early wrong algorithmic direction. Each tree node stores the candidate program, visit statistics, reward information, execution metadata, and path reflection memory. The node states let the search use both program behavior and prior repair experience. A memory-aware selection strategy combines numerical rewards, exploration terms, and semantic memory to allocate the search budget. Sandbox execution and multi-source evidence provide dense rewards that distinguish runnable, partially correct, and risky programs. Failure diagnoses are stored in both path memory and a global memory repository, so later branches can avoid rediscovering the same failure modes.

Our contributions are summarized as follows:

- We propose ReMCTS, a Reflect-enhanced Monte Carlo Tree Search Strategy for code generation. The framework organizes candidate programs in a search tree and uses reflection memory to guide multi-branch refinement. The memory-guided search reduces dependence on a single repair trajectory.

- We propose an evidence-driven reward and acceptance mechanism. The mechanism integrates execution, proxy, semantic, and risk evidence. The design supports both explicit-test and no-explicit-test settings while distinguishing missing evidence from negative evidence.

- We evaluate ReMCTS on multiple non-GPT models across HumanEval and MBPP-Sanitized. The protocol separates search-phase feedback from final hidden evaluation. This separation makes the reported hidden solve rates easier to interpret.

2 Related Work

2.1 One-Shot Code Generation and Candidate Selection

Function-level code generation is often studied as prompt-to-code generation and evaluated with benchmarks such as HumanEval (Chen et al., 2021) and MBPP (Austin et al., 2021). Many methods improve this setting by generating multiple candidates and then selecting among them. CodeT (Chen et al., 2023a) generates tests and uses test agreement to select code candidates. LEVER (Ni et al., 2023) learns to verify language-to-code outputs with execution results. Coder-Reviewer (Zhang et al., 2023) reranks generated code with a reviewer model. These methods improve candidate selection, but they mainly operate after candidates have been generated. They do not maintain a shared search state where execution feedback and reflection from failed candidates guide later branches.

2.2 Feedback-Based Code Repair

Feedback-based methods repair programs after errors are observed. Self-Refine (Madaan et al., 2023) iteratively improves model outputs with self-feedback. Reflexion (Shinn et al., 2023) stores verbal feedback from failures, and Self-Debugging (Chen et al., 2023b) uses execution feedback and explanation to repair programs. OpenCodeInterpreter (Zheng et al., 2025) builds execution-and-refinement data for code models. Other work turns tests or execution semantics into reward signals. RLTF (Liu et al., 2023) extracts rewards from unit-test feedback, and CODERL+ (Jiang et al., 2026) aligns code generation with execution semantics. These studies show that feedback is useful for code generation. However, many repair methods still follow a single trajectory, or use feedback mainly for training, filtering, or reranking. Olausson et al. (2024) further show that self-repair depends strongly on feedback quality and on the model's ability to use that feedback.

2.3 Search-Based and Tree-Based Code Generation

Search and planning methods explore more than one generation path. LATS (Zhou et al., 2024) combines language agents with Monte Carlo tree search. MapCoder (Islam et al., 2024) and Agent-Coder (Huang et al., 2023) use multiple agents for retrieval, planning, coding, testing, or debugging. PlanSearch (Wang et al., 2024) searches over

natural-language plans before code generation. S*
(Li et al., 2025a) studies test-time scaling for code
generation. RethinkMCTS (Li et al., 2025b) applies Monte Carlo tree search to refine erroneous
thoughts in code generation. These methods are
closest to ReMCTS because they use search, planning, or test-time compute. The key difference is
that ReMCTS treats executable programs, rather
than only thoughts, plans, or agent messages, as the
primary search states. Each node carries a runnable
candidate together with execution evidence, reward
traces, and path reflections. This state design makes
failures reusable: diagnoses from one branch can
be retrieved by later branches through a global
memory repository. ReMCTS also makes candidate evaluation availability-aware. Missing tests
are marked as unavailable evidence instead of negative evidence, which allows the same framework
to support both explicit-test and no-explicit-test settings. Thus, ReMCTS turns tree search into an
execution-grounded program search process with
reusable error memory.

3 ReMCTS Methodology

3.1 Overview

Given a natural-language task description P and
an optional visible test set $\mathcal{T}_{vis}$, code generation's
goal is to use a base code model f_θ to produce a
candidate program $S^\star$ that passes the final hidden
tests $\mathcal{T}_{hid}$. During search, the system can only access P and the feedback allowed by the setting.
We consider two search-feedback settings. In the
known setting, the system can use $\mathcal{T}_{vis}$ as execution
feedback. In the no_tests setting, no explicit tests
are available. The system then relies on proxy evidence, such as contracts, static checks, automated
probes, semantic reviews, and risk scans.

ReMCTS formulates the problem as test-time
tree search. The root node corresponds to the original task. Edges correspond to generation or repair
actions from the model. Child nodes correspond to
new candidate programs. Unlike single-trajectory
repair, ReMCTS keeps multiple candidate directions. It reallocates the search budget through
reward backpropagation and reflection memory.
Each search iteration follows a five-stage loop: selection, expansion, execution, reflection, and backpropagation. In the **selection** stage, the system
starts from the root and selects a node for expansion with a memory-augmented Upper Confidence
Bound score (UCB_M). Here UCB_M denotes a
memory-aware version of the standard Upper Confidence Bound (UCB) rule. It balances exploitation
and exploration while adding semantic memory. In
the **expansion** stage, the code model generates b
child candidates. The prompt includes the task, current program, execution feedback, path reflections,
and global experience. In the **execution** stage, the
sandbox runs each candidate and collects test, contract, static, probe, semantic, and risk evidence. In
the **reflection** stage, the system generates a structured reflection when a candidate fails or lacks
evidence. The reflection records the error type,
root cause, and repair hint. In the **backpropagation** stage, the system propagates rewards along
the search path and writes high-value or high-risk
reflections into the global memory repository.

Figure 1 illustrates the leaf-expansion procedure.
The figure shows how selection, expansion, execution, reflection, and backpropagation form one
closed loop. Execution feedback is converted into
both numerical rewards and retrievable semantic
experience. Reflection also affects node selection,
expansion prompts, and candidate acceptance.

3.2 Memory-Guided Monte Carlo Tree Design

Each node represents a candidate program. Each
node also stores statistical value and semantic history. A node is defined as:

$$Node_i = [S_i, V_i, N_i, M_{path,i}^{(k)}, \Phi_i], \qquad (1)$$

where S_i denotes the current candidate program.
V_i and N_i denote cumulative value and visit count.
Φ_i denotes metadata, such as execution feedback,
reward decomposition, risk information, and semantic reviews. The symbol v_i denotes the tree
node whose state vector is $Node_i$. Let the path
from the root to v_i be $\pi_i = (v_0, \ldots, v_i)$. Let M_j be
the structured reflection produced at node v_j, when
such a reflection exists. The k-hop path reflection
memory is:

$$M_{path,i}^{(k)} = \text{Tail}_k\left((M_j)_{v_j \in \pi_i, \, M_j \neq \varnothing}\right), \qquad (2)$$

where $\text{Tail}_k(\cdot)$ denotes the operator that keeps the
most recent k reflections. Here k denotes a fixed
memory-window hyperparameter. $\varnothing$ denotes the
case where no valid reflection is produced at a node.
Each valid M_j denotes a structured record with
error type, failure symptom, root cause, repair hint,
and severity. Thus, a node records two kinds of
information: the generated code and recent errors
on the path with the corresponding repair hints.

Figure 1: Overview of ReMCTS. The search proceeds through selection, expansion, execution, reflection, and backpropagation. Execution evidence is converted into rewards, while path and global reflection memories guide later expansion and candidate acceptance.

Standard MCTS uses UCB to balance high-value nodes and under-visited nodes. Error patterns in code generation are often semantically repetitive. Examples include entry-point mismatches, missing boundary cases, excessive complexity, and task misunderstanding. To exploit this structure, ReMCTS augments UCB with a **memory heuristic**:

$$UCB_M(v_i) = \bar{V}_i + C\sqrt{\frac{\ln(N_{p(i)} + 1)}{N_i + 1}} + H_i, \quad (3)$$

where $\bar{V}_i = V_i/(N_i + \epsilon)$ denotes the average node value. ϵ denotes a small constant for numerical stability. C denotes the exploration coefficient. $N_{p(i)}$ denotes the visit count of the parent node. Path reflections and global error memory jointly determine H_i. This paper instantiates the memory heuristic as:

$$H_i = \alpha Conf(M_{path,i}^{(k)}) - \beta Risk(M_{path,i}^{(k)}, \mathcal{G}). \quad (4)$$

Here $Conf(\cdot)$ estimates whether recent reflections indicate a converging repair direction. $Risk(\cdot, \mathcal{G})$ estimates similarity to high-risk failures in the global memory. α and β control the positive memory bonus and the risk penalty. If the current path shows consistent improvement, its expansion priority increases. If the current candidate resembles historical high-risk failures, its priority decreases.

To avoid repeated local edits around a wrong trajectory, ReMCTS uses two kinds of memory: path memory and global memory. The path memory $M_{path,i}^{(k)}$ stores the most recent k structured reflec-

tions on the current branch. Each reflection contains the error type, failure symptom, root cause, repair hint, and severity. During expansion, the model only reads the recent failure trajectory. This controls context length and keeps the repair direction coherent.

The global memory repository $\mathcal{G}$ stores error experience across branches. It is represented as:

$$\mathcal{G} = \{(M_g, \mathbf{e}_g, Meta_g)\}_{g=1}^{|\mathcal{G}|}, \quad (5)$$

$$\mathbf{e}_g = Embed(M_g). \quad (6)$$

Here M_g denotes a reflection summary. $\mathbf{e}_g$ denotes its embedding vector. $Meta_g$ denotes metadata that stores the source task, node id, error type, reward change, and risk level. When a candidate fails, the system writes its reflection summary, vector representation, and metadata into $\mathcal{G}$. When the system expands later nodes, it retrieves similar experience. The query uses the task, candidate code, and execution feedback. If the current node is close to a high-risk failure pattern, H_i and the expansion prompt reduce its priority. If later execution evidence becomes stronger, the branch can still regain search budget through numerical returns. The mechanism is semantic soft pruning, not a hard node-deletion operation.

3.3 Evidence-Driven Reward and Acceptance Mechanism

This section defines an evidence-driven reward for code generation. ReMCTS evaluates each candidate with executable, interface, behavioral, seman-

Figure 2: Evidence-driven reward and acceptance mechanism. A candidate program is first executed in the sandbox and converted into availability-aware evidence. When explicit tests are absent, unit-test evidence is marked unavailable ($A_{unit} = 0$) rather than failed. The normalizer maps each evidence source to availability, confidence, and score; the reward aggregator combines proxy correctness, execution reachability, semantic consistency, and risk penalties. The acceptance gate further penalizes uncertainty, risk, and task deviation, and rejected candidates return to search.

tic, and risk evidence, instead of relying on a single LLM score or a binary test result. Figure 2 summarizes how these signals are collected, aggregated into rewards, and used for final acceptance.

After a candidate program is generated, the sandbox executes it and collects weighted evidence:

$$\mathcal{E}_i = \{E_{unit}, E_{exec}, E_{contract}, E_{probe}, \\ E_{meta}, E_{static}, E_{sem}, E_{risk}\}. \quad (7)$$

Here $\mathcal{E}_i$ denotes the evidence set collected for candidate program S_i. For each evidence item $E_k = (A_k, C_k, R_k)$, A_k marks availability, C_k is confidence, and R_k is a normalized score. Unit tests provide the strongest signal when available; execution, contract, and static checks verify runnability and interface consistency; probe and meta evidence provide lightweight behavioral constraints in `no_tests`; semantic review and risk checks support final filtering. Unavailable evidence is excluded from reward aggregation, so missing tests are not treated as failed tests. Appendix Table 6 gives the full evidence list.

The final node reward is:

$$R(S_i) = \frac{\sum_{g \in \mathcal{J}} \delta_g \omega_g A_g C_g R_g(S_i)}{\sum_{g \in \mathcal{J}} \omega_g A_g C_g + \epsilon}, \quad (8)$$

$$\mathcal{J} = \{p, e, s, r\}, \quad (9)$$

$$\delta_g = \begin{cases} 1, & g \in \{p, e, s\}, \\ -1, & g = r. \end{cases} \quad (10)$$

where p, e, s, r index proxy correctness, execution reachability, semantic consistency, and risk, respectively. Accordingly, R_p, R_e, R_s, R_r represent $R_{proxy}, R_{exec}, R_{sem}, R_{risk}$, respectively. A_g and C_g are group availability and confidence, ω_g is the group weight, and δ_g assigns positive signs to reward groups and a negative sign to risk. At search termination, the system further computes:

$$Accept(S_i) = R(S_i) - \gamma_1 U_i \\ - \gamma_2 R_{risk}(S_i) - \gamma_3 D_i, \quad (11)$$

Here U_i penalizes low-confidence evidence, R_{risk} penalizes unsafe behavior, and D_i penalizes task-deviation checks such as entry-point, schema, dependency, and code-size violations. Let $\mathcal{A}_i = \{g \in \mathcal{J} \mid A_g = 1\}$. The uncertainty penalty is $U_i = 1 - \frac{1}{|\mathcal{A}_i| + \epsilon} \sum_{g \in \mathcal{A}_i} C_g$, which averages confidence only over available evidence groups. The task-deviation penalty is $D_i = \text{clip}(\sum_{\ell \in \mathcal{L}} \mu_\ell I_\ell(S_i), 0, 1)$. In benchmark settings, a candidate that passes all visible tests can be treated as a success state. In no-test settings, acceptance requires proxy, execution, semantic, and risk thresholds to be satisfied.

Reward Component Details. We next define the item-level rewards used to compute proxy correctness, execution reliability, semantic consistency, and risk-aware acceptance.

The observed reward from explicit unit tests is:

$$R_{unit}^{obs}(S_i) = \frac{1}{m} \sum_{j=1}^{m} p_j(S_i), \quad m > 0, \quad (12)$$

where m is the number of visible unit tests and $p_j(S_i)$ indicates whether S_i passes the j-th test. If $m = 0$, the method sets $A_{unit} = 0$, so missing unit-test evidence is ignored rather than counted as failure.

The integrated proxy-correctness reward is:

$$\mathcal{K}_{proxy} = \{\text{unit}, \text{contract}, \text{probe}, \text{meta}, \text{static}\}, \quad (13)$$

$$R_{proxy}(S_i) = \frac{\sum_{k \in \mathcal{K}_{proxy}} A_k C_k \eta_k R_k(S_i)}{\sum_{k \in \mathcal{K}_{proxy}} A_k C_k \eta_k + \epsilon}, \quad (14)$$

where $\mathcal{K}_{proxy}$ is the item-level evidence set and η_k is the fixed evidence weight. In no_tests, $A_{unit} = 0$, so proxy correctness is computed from contract, probe, meta, and static evidence.

Execution reward has four stages: compilation, loading, entry invocation, and successful completion:

$$R_{exec}(S_i) = \lambda_1 I_{compile} + \lambda_2 I_{load} \\ + \lambda_3 I_{entry} + \lambda_4 I_{finish}. \quad (15)$$

Here the four binary indicators correspond to compilation, module loading, entry invocation, and successful completion without timeout or non-assertion crash. The fixed nonnegative stage weights satisfy $\sum_{r=1}^{4} \lambda_r = 1$. Semantic reward is clipped by execution and correctness evidence to avoid accepting candidates only because of optimistic LLM review:

$$R_{corr}(S_i) = \begin{cases} R_{unit}^{obs}(S_i), & A_{unit} = 1, \\ R_{proxy}(S_i), & A_{unit} = 0, \end{cases} \quad (16)$$

$$R_{sem}(S_i) = \min(R_{sem}^{raw}(S_i), \\ \rho_0 + \rho_1 R_{corr}(S_i) \\ + \rho_2 R_{exec}(S_i)). \quad (17)$$

R_{corr} uses visible unit-test reward when available and proxy correctness otherwise. R_{sem}^{raw} is the raw LLM semantic-review score, and ρ_0, ρ_1, ρ_2 define its evidence-supported upper bound. Larger $R_{risk}(S_i)$ indicates higher safety or complexity risk, so it enters the reward as a penalty.

4 Results

4.1 Experimental Setup

Datasets. This paper uses HumanEval (Chen et al., 2021) and MBPP-Sanitized (Austin et al., 2021), which contain 164 and 427 function-level Python tasks. The protocol separates search feedback from final hidden evaluation. Visible feedback is derived from HumanEval prompt doctests and the first assertion of each MBPP-Sanitized task. File names, hashes, and derivation details are reported in Appendix C.

Models and Methods. This paper mainly focuses on open-source or open-weight non-GPT code models. We evaluate four dense Qwen3 models, Qwen3-1.7B, Qwen3-8B, Qwen3-14B, and Qwen3-32B (Qwen Team, 2025)[1], together with DeepSeek-V4-Flash (DeepSeek-AI, 2026) [2]. The main methods are Direct no_tests, ReMCTS no_tests, and ReMCTS known. Supplementary baselines include Best-of-8, Reflexion-style, pure-MCTS, and MCTS-style, which test repeated sampling, single-trajectory reflection, tree search, and LLM semantic review. We also report two component ablations that remove global memory retrieval or path reflection memory. Appendix D describes model invocation, decoding settings, and budget conventions.

Search Parameters and Metrics. All main ReMCTS experiments use a fixed search budget: 8 iterations, branch factor 5, maximum depth 8, minimum acceptance iteration 3, and complete-branch-before-accept enabled. Experiments use two search-feedback configurations: known uses visible tests during search, while no_tests removes explicit tests and relies on proxy evidence. Direct uses one generation, whereas ReMCTS and tree-search baselines use extra test-time compute. We report hidden solve rate as the main metric, and use average iterations and tree size as compute-budget proxies. Appendix D gives the remaining metric definitions.

4.2 Main Results

The main result is that reliable feedback makes ReMCTS substantially more effective, supporting the central claim that execution-grounded feedback and reflection memory help allocate test-time search budget. Table 1 reports hidden solve rates on HumanEval and MBPP-Sanitized. The known setting is a test-guided mechanism validation: visible feedback can be used during search, while final scoring still uses only hidden tests. Therefore, this setting is not equivalent to standard pass@1. Under this protocol, ReMCTS known improves over Direct no_tests in 8 out of 10 model–dataset pairs, ties in 1 pair, and slightly decreases in 1 pair. It also improves over ReMCTS no_tests in all pairs, showing that reliable feedback is more stable than proxy-only evidence.

---

[1]Qwen3 model collection: `https://huggingface.co/collections/Qwen/Qwen3`

[2]DeepSeek-V4-Flash model: `https://huggingface.co/deepseek-ai/DeepSeek-V4-Flash`

Table 1: Hidden solve rates on HumanEval and MBPP-Sanitized. Parentheses in the two ReMCTS columns report percentage-point differences from Direct no_tests. TG–no_tests is the difference between ReMCTS known and ReMCTS no_tests. known results are used for mechanism validation and are not equivalent to standard pass@1.

Model	Dataset	Direct no_tests	ReMCTS no_tests	ReMCTS known	TG–no_tests (pp)
Qwen3-1.7B	HumanEval	60.37%	69.51% (+9.14)	83.54% (+23.17)	+14.03
Qwen3-1.7B	MBPP	53.40%	51.29% (-2.11)	63.47% (+10.07)	+12.18
Qwen3-8B	HumanEval	79.88%	86.59% (+6.71)	93.90% (+14.02)	+7.31
Qwen3-8B	MBPP	64.17%	66.74% (+2.57)	74.24% (+10.07)	+7.50
Qwen3-14B	HumanEval	82.93%	78.66% (-4.27)	82.93% (+0.00)	+4.27
Qwen3-14B	MBPP	66.98%	60.42% (-6.56)	65.57% (-1.41)	+5.15
Qwen3-32B	HumanEval	89.63%	89.63% (+0.00)	95.12% (+5.49)	+5.49
Qwen3-32B	MBPP	71.90%	70.49% (-1.41)	77.99% (+6.09)	+7.50
DeepSeek-V4-Flash	HumanEval	80.49%	95.12% (+14.63)	98.78% (+18.29)	+3.66
DeepSeek-V4-Flash	MBPP	72.60%	72.83% (+0.23)	81.03% (+8.43)	+8.20

Model Capacity and Proxy Evidence. Two secondary patterns qualify the main gain: improvements depend on model capacity, and proxy-only evidence can still miss hidden semantics. The gaps in Table 1, search-tree statistics in Appendix I, and trajectories in Appendix Table 18 show that weaker models often benefit from execution evidence. Stronger models such as Qwen3-32B mainly recover residual errors. The Qwen3-14B drops and some MBPP no_tests cases expose the proxy-evidence boundary: plausible candidates can pass weak checks while still failing hidden semantics.

Supplementary Baseline Setup. The supplementary baselines test whether repeated sampling, single-path reflection, or tree search alone explains the gains. We compare Best-of-8, Reflexion-style, pure-MCTS, and MCTS-style on Qwen3-8B, Qwen3-32B, and DeepSeek-V4-Flash, without hidden tests for search or selection. MCTS-style is the closest memory-free tree-search baseline: it adds LLM semantic review but disables path memory, global memory, semantic UCB, and LLM probes. Table 2 separates no_tests and known feedback regimes, and Appendix Tables 11 and 12 report acceptance, Oracle Pool, and configuration details.

Sampling and Reflection Baselines. Repeated sampling and single-path reflection are insufficient explanations for the ReMCTS gains because candidate generation, candidate selection, and trajectory choice remain separate sources of error. Best-of-8 is close to ReMCTS no_tests on DeepSeek-V4-Flash, but remains below ReMCTS known, and its Oracle Pool shows that correct programs can exist without being selected. On MBPP, Best-of-8 is also below ReMCTS no_tests for Qwen3-8B and Qwen3-32B. Reflexion-style reaches a strong HumanEval score on Qwen3-32B, but is below ReMCTS no_tests on all three MBPP settings.

Tree-Search Baselines. Tree search alone is also insufficient; memory and evidence are needed for reliable search with modest additional token use. In no_tests, pure-MCTS and MCTS-style improve over simpler controls, but they remain below full ReMCTS on the two MBPP settings and do not close the gap to ReMCTS known. In known, full ReMCTS beats MCTS-style in all six model–dataset pairs by 5.07 points on average. Appendix Table 13 shows that across the twelve comparable ReMCTS/MCTS-style settings, ReMCTS uses only $1.09\times$ the logged tokens of MCTS-style overall.

The known-feedback Reflection-style results show that visible tests can make single-path repair highly competitive on short assertion-style tasks. Full ReMCTS remains higher on HumanEval for all three models, but Reflection-style is stronger on MBPP, reaching 81.97%, 86.89%, and 94.15% on Qwen3-8B, Qwen3-32B, and DeepSeek-V4-Flash. Thus, ReMCTS's advantage is not simply that reflection helps; multi-branch search and reusable memory mainly improve robustness when feedback is incomplete, noisy, or hard to exploit through one trajectory.

4.3 Ablation Results

Memory Ablations. The component ablations show that global memory gives the clearer aggregate contribution, while path memory is more task- and model-dependent. Table 3 summarizes the results. Removing global memory retrieval hurts full ReMCTS by 0.97 percentage points on average across the twelve reported settings. Full ReMCTS is higher than the no-global-memory variant in 8 settings, tied in 1, and lower in 3. The largest differences appear on Qwen MBPP known, where global

Table 2: Unified compact supplementary baseline comparison. All numbers are hidden solve rates (%). Columns under `no_tests` use no visible tests during search. Columns under known use visible tests during search and hidden tests only for final offline evaluation.

Model	Dataset	no_tests feedback					known feedback		
		Best-of-8	Reflexion	pure-MCTS	MCTS-style	ReMCTS	Reflection	MCTS-style	ReMCTS
Qwen3-8B	HumanEval	82.93	81.10	84.76	85.98	86.59	86.59	86.59	93.90
Qwen3-8B	MBPP	60.42	61.59	64.87	64.87	66.74	81.97	66.74	74.24
Qwen3-32B	HumanEval	88.41	90.24	89.02	90.24	89.63	93.29	93.90	95.12
Qwen3-32B	MBPP	63.00	68.85	69.79	69.56	70.49	86.89	71.19	77.99
DeepSeek-V4-Flash	HumanEval	95.73	94.51	92.07	94.51	95.12	96.34	96.34	98.78
DeepSeek-V4-Flash	MBPP	73.54	71.90	70.96	71.19	72.83	94.15	75.88	81.03

Table 3: Memory ablation results, reported as hidden solve rates (%).

Model	Dataset	Setting	Full	No global	W/O path	Full–W/O global
DeepSeek-V4-Flash	HumanEval	known	98.78	99.39	99.39	-0.61
DeepSeek-V4-Flash	HumanEval	no_tests	95.12	94.51	94.51	+0.61
DeepSeek-V4-Flash	MBPP	known	81.03	80.56	80.09	+0.47
DeepSeek-V4-Flash	MBPP	no_tests	72.83	73.07	72.83	-0.24
Qwen3-8B	HumanEval	known	93.90	92.07	95.12	+1.83
Qwen3-8B	HumanEval	no_tests	86.59	85.37	86.59	+1.22
Qwen3-8B	MBPP	known	74.24	69.56	73.54	+4.68
Qwen3-8B	MBPP	no_tests	66.74	66.04	66.51	+0.70
Qwen3-32B	HumanEval	known	95.12	95.12	95.12	+0.00
Qwen3-32B	HumanEval	no_tests	89.63	90.85	89.63	-1.22
Qwen3-32B	MBPP	known	77.99	74.71	78.69	+3.28
Qwen3-32B	MBPP	no_tests	70.49	69.56	70.02	+0.93

memory improves Qwen3-8B by 4.68 points and Qwen3-32B by 3.28 points. Removing path memory gives a more mixed pattern: full ReMCTS is only 0.04 points higher on average, with 5 wins, 4 ties, and 3 losses.

Search-Tree Behavior. Search-tree statistics indicate that ReMCTS usually performs shallow multi-branch exploration rather than long repair chains. Appendix Table 15 gives the full per-model values. The average tree size ranges from 3.389 to 11.593 nodes, the median mostly falls between 3 and 8 nodes, and the average maximum depth is about 1.23–1.61. A smaller actual tree does not mean the parameters are inconsistent: `branch_factor=5` is only an upper bound, and parsing failures, duplicate code, cross-node deduplication, and early acceptance all reduce the number of effective children.

Minimum Acceptance Iteration. The minimum-acceptance ablation further shows that ReMCTS is most effective with trustworthy execution evidence, while no-test deployment needs stronger uncertainty control, proxy construction, and human review for high-risk cases. Table 4 compares an earlier minimum acceptance iteration of 1 with the current `min_accept_iterations=3`. Increasing the minimum to 3 improves hidden solve rate in 7 of 10 `no_tests` combinations, with an average

Table 4: No-test minimum acceptance ablation. ΔScore is Score@3–Score@1.

Model	Dataset	Score@1	Score@3	ΔScore
Qwen3-1.7B	HumanEval	64.02	69.51	+5.49
Qwen3-1.7B	MBPP	51.99	51.29	-0.70
Qwen3-8B	HumanEval	87.20	86.59	-0.61
Qwen3-8B	MBPP	63.93	66.74	+2.81
Qwen3-14B	HumanEval	77.44	78.66	+1.22
Qwen3-14B	MBPP	59.02	60.42	+1.41
Qwen3-32B	HumanEval	90.24	89.63	-0.61
Qwen3-32B	MBPP	68.38	70.49	+2.11
DeepSeek-V4-Flash	HumanEval	93.29	95.12	+1.83
DeepSeek-V4-Flash	MBPP	70.26	72.83	+2.58

gain of 1.55 percentage points. Full known results and search-scale changes are reported in Appendix Tables 16 and 17.

5 Conclusions

This paper presents ReMCTS, an inference-time framework combining multi-branch search, execution-grounded rewards, and reflection memory. On HumanEval and MBPP-Sanitized, visible feedback gives the strongest hidden-test gains, while `no_tests` remains positive but less stable. Baselines and ablations rule out sampling, single-path reflection, and memory-free tree search as sufficient explanations, and identify global memory as the clearest contributor. Future work should strengthen `no_tests` feedback with automatic tests and uncertainty calibration, especially for hidden semantics and boundary cases, to reduce false acceptance.

Limitations

This work should be interpreted as a controlled evaluation of an inference-time search mechanism, rather than as a single leaderboard-style pass@1 comparison. In the known setting, visible tests are available during search and hidden tests are used only for final offline scoring, so this setting is best viewed as test-guided mechanism validation. The `no_tests` setting is closer to deployment scenarios without explicit tests, but our benchmarks are still function-level HumanEval and MBPP-Sanitized tasks. They do not fully capture repository-level dependencies, environment configuration, permission constraints, long-horizon debugging, or security-sensitive software changes.

A second limitation is that `no_tests` search relies on proxy feedback, including contract checks, static checks, automated probes, and LLM semantic review. These signals can miss hidden boundary cases and lead to false acceptance, consistent with prior evidence that self-repair depends strongly on feedback quality (Olausson et al., 2024). Our minimum-acceptance ablation and search-tree statistics suggest that stronger automatic tests and better uncertainty calibration are important for reducing premature acceptance. Finally, ReMCTS requires additional test-time model calls, and although the supplementary baselines and component ablations cover several key alternatives, they do not exhaustively isolate every design choice, such as semantic UCB, reward weighting, probe construction, and risk thresholds.

References

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and Charles Sutton. 2021. Program synthesis with large language models. *Preprint*, arXiv:2108.07732.

Zhangqian Bi, Yao Wan, Zheng Wang, Hongyu Zhang, Batu Guan, Fangxin Lu, Zili Zhang, Yulei Sui, Hai Jin, and Xuanhua Shi. 2024. Iterative refinement of project-level code context for precise code generation with compiler feedback. *Preprint*, arXiv:2403.16792.

Bei Chen, Fengji Zhang, Anh Nguyen, Daoguang Zan, Zeqi Lin, Jian-Guang Lou, and Weizhu Chen. 2023a. CodeT: Code generation with generated tests. In *International Conference on Learning Representations*.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, and 39 others. 2021. Evaluating large language models trained on code. *Preprint*, arXiv:2107.03374.

Xinyun Chen, Maxwell Lin, Nathanael Schärli, and Denny Zhou. 2023b. Teaching large language models to self-debug. *Preprint*, arXiv:2304.05128.

DeepSeek-AI. 2026. DeepSeek-V4: Towards highly efficient million-token context intelligence.

Dong Huang, Jie M. Zhang, Michael Luck, Qingwen Bu, Yuhao Qing, and Heming Cui. 2023. AgentCoder: Multi-agent-based code generation with iterative testing and optimisation. *Preprint*, arXiv:2312.13010.

Md. Ashraful Islam, Mohammed Eunus Ali, and Md Rizwan Parvez. 2024. MapCoder: Multi-agent code generation for competitive problem solving. *Preprint*, arXiv:2405.11403.

Xue Jiang, Yihong Dong, Mengyang Liu, Hongyi Deng, Tian Wang, Yongding Tao, Rongyu Cao, Binhua Li, Zhi Jin, Wenpin Jiao, Fei Huang, Yongbin Li, and Ge Li. 2026. CodeRL+: Improving code generation via reinforcement with execution semantics alignment. *Preprint*, arXiv:2510.18471.

Hung Le, Yue Wang, Akhilesh Deepak Gotmare, Silvio Savarese, and Steven C. H. Hoi. 2022. CodeRL: Mastering code generation through pretrained models and deep reinforcement learning. *Preprint*, arXiv:2207.01780.

Dacheng Li, Shiyi Cao, Chengkun Cao, Xiuyu Li, Shangyin Tan, Kurt Keutzer, Jiarong Xing, Joseph E. Gonzalez, and Ion Stoica. 2025a. S*: Test time scaling for code generation. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 15964–15978, Suzhou, China. Association for Computational Linguistics.

Qingyao Li, Wei Xia, Xinyi Dai, Kounianhua Du, Weiwen Liu, Yasheng Wang, Ruiming Tang, Yong Yu, and Weinan Zhang. 2025b. RethinkMCTS: Refining erroneous thoughts in monte carlo tree search for code generation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 8092–8110, Suzhou, China. Association for Computational Linguistics.

Jiate Liu, Yiqin Zhu, Kaiwen Xiao, Qiang Fu, Xiao Han, Wei Yang, and Deheng Ye. 2023. RLTF: Reinforcement learning from unit test feedback. *Preprint*, arXiv:2307.04349.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. 2023. Self-refine: Iterative refinement with self-feedback. *Preprint*, arXiv:2303.17651.

Chunyu Miao, Henry Peng Zou, Yangning Li, Yankai Chen, Yibo Wang, Fangxin Wang, Yifan Li, Wooseong Yang, Bowei He, Xinni Zhang, Dianzhi Yu, Hanchen Yang, Hoang H. Nguyen, Yue Zhou, Jie Yang, Jizhou Guo, Wenzhe Fan, Chin-Yuan Yeh, Panpan Meng, and 12 others. 2025. RECODE-H: A benchmark for research code development with interactive human feedback. *Preprint*, arXiv:2510.06186.

Ansong Ni, Srini Iyer, Dragomir Radev, Veselin Stoyanov, Wen-Tau Yih, Sida Wang, and Xi Victoria Lin. 2023. LEVER: Learning to verify language-to-code generation with execution. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 26106–26128. PMLR.

Theo X. Olausson, Jeevana Priya Inala, Chenglong Wang, Jianfeng Gao, and Armando Solar-Lezama. 2024. Is self-repair a silver bullet for code generation? In *International Conference on Learning Representations*.

Qwen Team. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Ravin Ravi, Dylan Bradshaw, Stefano Ruberto, Gunel Jahangirova, and Valerio Terragni. 2026. LLM-LOOP: Improving llm-generated code and tests through automated iterative feedback loops. *Preprint*, arXiv:2603.23613.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. *Preprint*, arXiv:2303.11366.

Lingxiao Tang, Muyang Ye, Zhaoyang Chu, Xiaoxue Ren, Zhongxin Liu, Lingfeng Bao, and He Ye. 2026. An iterative test-and-repair framework for competitive code generation. *Preprint*, arXiv:2604.05560.

Evan Wang, Federico Cassano, Catherine Wu, Yunfeng Bai, Will Song, Vaskar Nath, Ziwen Han, Sean Hendryx, Summer Yue, and Hugh Zhang. 2024. Planning in natural language improves llm search for code generation. *Preprint*, arXiv:2409.03733.

Tianyi Zhang, Tao Yu, Tatsunori Hashimoto, Mike Lewis, Wen-Tau Yih, Daniel Fried, and Sida Wang. 2023. Coder reviewer reranking for code generation. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 41832–41846. PMLR.

Tianyu Zheng, Ge Zhang, Tianhao Shen, Xueling Liu, Bill Yuchen Lin, Jie Fu, Wenhu Chen, and Xiang Yue. 2025. OpenCodeInterpreter: Integrating code generation with execution and refinement. *Preprint*, arXiv:2402.14658.

Andy Zhou, Kai Yan, Michal Shlapentokh-Rothman, Haohan Wang, and Yu-Xiong Wang. 2024. Language agent tree search unifies reasoning, acting, and planning in language models. *Preprint*, arXiv:2310.04406.

A ReMCTS Pseudocode

Algorithm 1 summarizes the full search procedure. The pseudocode uses the same evidence and memory terms defined in Section 3. In known, visible tests are available during evidence collection. In `no_tests`, unit-test evidence is marked unavailable, and the reward is computed from proxy, execution, semantic, and risk evidence.

Algorithm 1 ReMCTS search procedure

Require: Task P, optional visible tests $\mathcal{T}_{vis}$, model f_θ
Require: Budget B, branch factor b, max depth d, memory window k
Ensure: Final candidate program $S^\star$
1: Initialize root node v_0 and global memory $\mathcal{G} \leftarrow \varnothing$
2: $S^\star \leftarrow \varnothing, score^\star \leftarrow -\infty$
3: **for** $iter = 1$ to B **do**
4:     $v \leftarrow \text{SELECT}(v_0, UCB_M, d)$
5:     $M_{path} \leftarrow \text{PATHMEMORY}(v, k)$
6:     $M_{global} \leftarrow \text{RETRIEVE}(\mathcal{G}, P, S_v, \Phi_v)$
7:     $X \leftarrow \text{BUILDPROMPT}(P, S_v, \Phi_v, M_{path}, M_{global})$
8:     $\mathcal{C} \leftarrow \text{GENERATE}(f_\theta, X, b)$
9:     **for all** $S_i \in \mathcal{C}$ **do**
10:         $\mathcal{E}_i \leftarrow \text{COLLECTEVIDENCE}(P, S_i, \mathcal{T}_{vis})$
11:         **if** $\mathcal{T}_{vis} = \varnothing$ **then**
12:             Set $A_{unit} \leftarrow 0$
13:         **end if**
14:         $R_i \leftarrow \text{EVIDENCEREWARD}(\mathcal{E}_i)$
15:         $M_i \leftarrow \text{REFLECT}(P, S_i, \mathcal{E}_i, M_{path}, M_{global})$
16:         $u \leftarrow \text{ADDCHILD}(v, S_i, R_i, \mathcal{E}_i, M_i)$
17:         $\text{BACKPROPAGATE}(u, R_i)$
18:         **if** $\text{STOREABLE}(M_i, \mathcal{E}_i)$ **then**
19:             $\mathcal{G} \leftarrow \mathcal{G} \cup \{(M_i, \text{EMBED}(M_i), Meta_i)\}$
20:         **end if**
21:         $a_i \leftarrow \text{ACCEPTANCESCORE}(S_i, \mathcal{E}_i, R_i)$
22:         **if** $a_i > score^\star$ **then**
23:             $S^\star \leftarrow S_i, score^\star \leftarrow a_i$
24:         **end if**
25:         **if** $\text{ACCEPT}(a_i, \mathcal{E}_i, iter)$ **then**
26:             **return** S_i
27:         **end if**
28:     **end for**
29: **end for**
30: **return** $S^\star$

B Reward and Evidence Details

Symbols in the method formulas fall into three categories. The first category is predefined hyperparameters, including the search budget, C, memory window k, global retrieval count t, semantic heuristic weights α, β, reward weights ω_g, acceptance penalties γ_j, and thresholds τ_*. The second category is runtime evidence quantities, including A_k, C_k, R_k and reward components derived from them. The third category is heuristic or LLM-assisted scores, including H_i, semantic reviews, risk scans, and the deviation penalty D_i. Hyperparameters are fixed before evaluation and are not learned from tasks. Sandbox execution, static checks, rule-based functions, and LLM reviews compute evidence quan-

tities and heuristic scores during search. During search, only node visit statistics, cumulative returns, and reflection memory are updated.

Table 5 summarizes these symbol categories and fixed hyperparameter settings. Table 6 lists the evidence items used to evaluate candidate programs. If an evidence item is unavailable, $A_k = 0$, and the missing item is ignored by the reward denominator.

C Datasets and Input Settings

Table 7 lists the data files, task counts, and source summaries. Complete SHA-256 hashes, byte counts, and derivation relations are recorded in `data/dataset_manifest.json`.

D Search Parameters and Evaluation Metrics

Table 8 reports model invocation and decoding settings. All models are called through an OpenAI-compatible API. They are identified by the API aliases in our experiment records. API-served models are subject to server-side updates. Therefore, we fix the experimental protocol with aliases, run time, decoding parameters, and data hashes.

Table 9 gives the search budget used in the main experiments. To make known and `no_tests` comparable, they use the same maximum iterations, branch factor, maximum depth, and minimum acceptance iterations. Direct is a single-generation baseline. Best-of-8 generates exactly 8 candidates. Reflexion-style runs up to 8 single-path feedback rounds. ReMCTS, pure-MCTS, and MCTS-style use the same tree-search budget. If a tree has n nodes, then the $n - 1$ non-root nodes correspond to generated and executed program candidates. Semantic reviews, reflections, and LLM probes add auxiliary calls when they are enabled. Different API services do not expose perfectly consistent token accounting, so the main analysis uses average iterations and search-tree size as compute-budget proxies across models and methods. For the direct ReMCTS/MCTS-style comparison, Appendix Table 13 additionally reports logged prompt-plus-completion token totals from the corresponding experiment reports.

Let $a_i \in \{0, 1\}$ indicate whether the internal acceptor of a method automatically accepts task i. Let $h_i \in \{0, 1\}$ indicate whether the final returned candidate passes hidden tests. Hidden Solve Rate is computed over all tasks as $\frac{1}{n} \sum_i h_i$. It does not depend on automatic acceptance. Ac-

Table 5: Symbol categories and hyperparameter settings.

Symbol	Type	Definition
C, k, t, α, β	Search and semantic-heuristic hyperparameters	$C = 1.4$, $k = 3$, $t = 2$; ReMCTS uses $\alpha = 0.4, \beta = 0.6$, while pure-MCTS/MCTS-style ablations set the memory heuristic to zero.
$\omega_g, \gamma_j, \tau_*$	Reward and acceptance hyperparameters	known mainly uses unit/exec/semantic weights; no_tests uses proxy/exec/semantic/risk weights $(0.4, 0.2, 0.3, 0.1)$. Acceptance penalties are $\gamma = (0.10, 0.35, 0.10)$, and main thresholds are $\tau_{proxy} = 0.50$, $\tau_{exec} = 0.60$, $\tau_{sem} = 0.45$, $\tau_{risk} = 0.25$, and $\tau_{accept} = 0.62$.
$\eta_k, \lambda_r, \rho_j, \mu_\ell$	Fixed heuristic weights	Used for proxy-evidence weighting, execution-stage weighting, semantic-reward upper bounds, and deviation penalties; set and normalized before evaluation, not learned from data.
$A_k, C_k, R_k, I., R., U_i$	Runtime evidence quantities	Produced by visible tests, sandbox execution, contract checks, probes, property checks, static checks, risk scans, and LLM reviews; U_i is computed from the confidence of available evidence groups.
H_i, D_i, R_{sem}^{raw}	Heuristic or LLM-assisted scores	H_i comes from path-reflection confidence and global error similarity; D_i comes from rule checks such as interface consistency and code size; R_{sem}^{raw} comes from LLM semantic review.
ϵ	Numerical stability term	Used only to avoid division by zero; not a tunable experimental parameter.

Table 6: Evidence items used in reward computation.

Evidence	Meaning	Role
Unit	Visible unit tests or assertions	Provides the highest-confidence functional feedback in known
Exec	Compilation, loading, entry call, timeout, and crash status	Checks whether the candidate is runnable and callable
Contract	Function name, argument count, return form, or schema	Prevents interface mismatches and entry-point errors
Probe	Automatically generated lightweight smoke tests	Provides low-cost behavioral signals without explicit tests
Meta	Properties or metamorphic relations extracted from the requirement	Checks task properties such as sorting, length, idempotence, and reversal
Static	Syntax, dependency, type, and safe-import checks	Filters obviously non-runnable or dangerous code
Semantic	LLM semantic review	Estimates consistency between the candidate approach and task description
Risk	Dangerous system calls, unauthorized file access, abnormal complexity, etc.	Provides risk penalties for production-style acceptance

Table 7: Experimental data files and usage.

File	Tasks	Use	Source or Description
HumanEval_feedback.jsonl	164	known input	Visible feedback parsed from doctest examples in HumanEval prompts; some tasks have no visible examples
HumanEval_no_tests.jsonl	164	no_tests input	Explicit tests removed; only the prompt and entry point are retained
HumanEval_eval.jsonl	164	hidden eval	Original HumanEval test fields retained only for final offline evaluation
mbpp_sanitized_feedback_split.json	427	known input	Converted from Google Research sanitized-mbpp.json; only the first assertion per task is used as search feedback
mbpp_sanitized_no_tests.json	427	no_tests input	Explicit assertions removed; only task description and entry point are retained
mbpp_sanitized_eval_split.json	427	hidden eval	Setup/imports and remaining assertions retained for final evaluation

cepted Rate is $\frac{1}{n}\sum_i a_i$. Acceptance Precision is $\frac{\sum_i a_i h_i}{\sum_i a_i + \epsilon}$. False Acceptance Rate is $\frac{\sum_i a_i(1-h_i)}{\sum_i a_i + \epsilon}$. For

Table 8: Model invocation and decoding settings.

Item	Setting
Model alias	Qwen3-1.7B, Qwen3-8B, Qwen3-14B, Qwen3-32B, DeepSeek-V4-Flash
Invocation	OpenAI-compatible API; main experiments and supplementary baselines were run in May 2026
Direct, ReMCTS, and tree-search baselines	Code-generation temperature 0.2, maximum output length 1024 tokens, and API request timeout 90 seconds
Best-of-8	8 independent candidates per task, generation temperature 0.7, and 5 self-generated assertion tests for selection
Reflexion-style	Up to 8 Actor–Evaluator–Self-Reflection rounds; Actor, Evaluator, and reflection temperatures are all 0.2
Sandbox execution	Python sandbox timeout 5 seconds; hidden tests are used only for final offline evaluation and Oracle Pool statistics

Table 9: Search parameters for the main ReMCTS experiments.

Parameter	Value
max_iterations	8
branch_factor	5
max_depth	8
no_improve_patience	8
min_accept_iterations	3
complete_branch_before_accept	true
Final metric	hidden solve rate

ReMCTS, pure-MCTS, and MCTS-style, a_i comes from their acceptance thresholds. For Best-of-8 and Reflexion-style, a_i means that self-generated tests or the evaluator accepted a candidate. If $a_i = 0$, the system still returns the current best candidate for hidden evaluation. Thus, the task affects Hidden Solve Rate, but it is not included in the denominator of acceptance precision or false acceptance. Table 10 summarizes these metric definitions.

E Supplementary Baseline Results

Table 11 reports the full supplementary results for Best-of-8, Reflexion-style, pure-MCTS, and MCTS-style. Hidden tests are used only for final offline evaluation. They are never used for candidate selection.

F Known-Feedback Baseline Results

Table 12 reports the completed known-feedback baseline results. These runs use visible tests as feedback during search and hidden tests only for final offline evaluation. Reflection-style is a single-path Actor–Evaluator–Self-Reflection loop. MCTS-style keeps tree search but disables path memory, global memory retrieval, semantic UCB, and LLM probes.

G Logged Token Comparison

Table 13 compares the logged token use of full ReMCTS and MCTS-style on the same model–dataset–feedback settings used in the compact baseline comparison. Tokens are the sum of logged prompt and completion tokens in the experiment reports. Across all twelve comparable settings, ReMCTS uses $1.09\times$ the total tokens of MCTS-style. The ratio is $1.14\times$ in no_tests and $1.04\times$ in known.

H Memory Ablation Results

Table 14 reports the full memory ablation results. The no-global-memory variant sets global_memory_top_t=0. The no-path-memory variant sets path_memory_k=0. These ablations use the same final hidden-evaluation protocol as the main experiments.

I Search-Tree Structure Statistics

Table 15 reports search-tree statistics for all main ReMCTS experiments. For known, we use the latest hidden-eval reruns. For no_tests, we use the v2 results adopted in the main table. Effective branch is the micro-average number of child nodes over non-leaf nodes. It equals total edges divided by total non-leaf nodes.

J Minimum Search Iteration Ablation

Tables 16 and 17 compare early experiments with the current main experiments. The early experiments set the minimum number of search iterations to 1. To make correctness metrics comparable,

Table 10: Definitions of evaluation metrics.

Metric	Definition	Applicable Settings
Hidden Solve Rate	Fraction of tasks whose final candidate passes hidden tests	All experiments
Accepted Rate	Fraction of tasks whose candidate is automatically accepted	ReMCTS `no_tests` and known
Acceptance Precision	Fraction of automatically accepted candidates that pass hidden tests	No-test acceptance analysis
False Acceptance Rate	Fraction of automatically accepted candidates that fail hidden tests	No-test acceptance analysis
Avg. Iterations	Average search iterations per task	Search efficiency analysis
Avg. Tree Size	Average search-tree nodes per task	Search efficiency analysis
Oracle Pool Hidden Rate	Fraction of tasks where at least one candidate in the pool passes hidden tests	Offline analysis for multi-candidate and tree-search methods

Score@1 for older known runs is obtained by re-running hidden tests offline. These tests use the final candidate code recorded in the early run directories. Older `no_tests` runs directly use the hidden solve rates in the original reports. The current `min_accept_iterations=3` generally gives more stable hidden solve rates in `no_tests`. In known, it mainly changes search scale and leaves scores nearly unchanged.

K Qualitative Case Analysis

The causal interpretation in Section 4.3 is not inferred from aggregate accuracy alone. We also inspect representative search trajectories where Direct and ReMCTS differ. These cases are illustrative. They are not a full manual audit. However, they show how the same mechanisms behind the aggregate trends appear in concrete tasks.

L Evaluation Protocol Notes

All tables use hidden tests as the final correctness metric. The known setting allows visible test feedback during search. Therefore, its results are interpreted as test-guided mechanism validation. They are not fully equivalent to standard pass@1. The `no_tests` setting uses no explicit tests. It is closer to production-style code generation without test cases. However, HumanEval and MBPP-Sanitized are still function-level benchmarks. They cannot fully cover cross-file context, dependency installation, permission control, or security risks in real software projects.

The Best-of-8, Reflexion-style, pure-MCTS, and MCTS-style baselines are run on Qwen3-8B, Qwen3-32B, and DeepSeek-V4-Flash. They test whether diverse sampling, single-path reflection, reflection-free tree search, or tree search with only LLM semantic review can explain the gains of ReMCTS. None of the four methods uses hidden tests for candidate selection. Hidden tests are used only for final offline evaluation and Oracle Pool upper-bound statistics. For pure-MCTS and MCTS-style, Oracle Pool uses non-root nodes generated in the search tree as the candidate pool.

Table 11: Supplementary baselines for Best-of-8, Reflexion-style, pure-MCTS, and MCTS-style. Accepted is the number of tasks accepted by the method's internal acceptor. It is not the number of final returned tasks. Hidden Solve is always computed with the final returned candidate for each task. Oracle Pool is the offline upper bound indicating whether at least one candidate in the pool passes hidden tests. Best-of-8 uses 8 independent candidates. Reflexion-style uses all attempts. pure-MCTS and MCTS-style use non-root nodes generated in the search tree. `DeepSeek` abbreviates DeepSeek-V4-Flash.

Parameter note: Best-of-8 uses $n = 8$ independent candidates. It uses a candidate-generation temperature of 0.7 and 5 self-generated assertion tests for selection. Reflection/Reflexion-style runs up to 8 Actor–Evaluator–Self-Reflection rounds. Actor and reflection generation temperatures are both 0.2. The Evaluator uses the same 5 self-generated assertion tests. pure-MCTS uses the same search budget as the main experiments. The settings are `max_iterations=8`, `branch_factor=5`, `max_depth=8`, `min_accept_iterations=3`, and `complete_branch_before_accept=true`. The UCB exploration coefficient is $C = 1.4$. pure-MCTS sets `path_memory_k=0`, `global_memory_top_t=0`, and semantic heuristic $\alpha = \beta = 0$. It also disables LLM semantic scoring and LLM probes. MCTS-style uses the same search budget as pure-MCTS. It also disables path memory, global memory, semantic UCB, and LLM probes. It enables LLM semantic scoring as a production-style reward and acceptance component. The settings are `w_semantic=0.3` and `semantic_threshold=0.45`.

Model	Dataset	Method	Hidden Solve	Accepted	Acc. Prec.	False Acc.	Oracle Pool
`Qwen3-8B`	HumanEval	Best-of-8	82.93%	95/164	98.95%	1.05%	82.93%
`Qwen3-8B`	HumanEval	Reflexion	81.10%	99/164	96.97%	3.03%	84.15%
`Qwen3-8B`	HumanEval	pure-MCTS	84.76%	163/164	84.66%	15.34%	87.20%
`Qwen3-8B`	HumanEval	MCTS-style	85.98%	90/164	90.00%	10.00%	86.59%
`Qwen3-8B`	MBPP	Best-of-8	60.42%	190/427	80.53%	19.47%	61.83%
`Qwen3-8B`	MBPP	Reflexion	61.59%	234/427	74.36%	25.64%	64.17%
`Qwen3-8B`	MBPP	pure-MCTS	64.87%	427/427	64.87%	35.13%	66.51%
`Qwen3-8B`	MBPP	MCTS-style	64.87%	302/427	65.23%	34.77%	65.81%
`Qwen3-32B`	HumanEval	Best-of-8	88.41%	108/164	96.30%	3.70%	88.41%
`Qwen3-32B`	HumanEval	Reflexion	90.24%	118/164	97.46%	2.54%	90.85%
`Qwen3-32B`	HumanEval	pure-MCTS	89.02%	162/164	89.51%	10.49%	92.68%
`Qwen3-32B`	HumanEval	MCTS-style	90.24%	125/164	94.40%	5.60%	92.68%
`Qwen3-32B`	MBPP	Best-of-8	63.00%	207/427	80.68%	19.32%	63.47%
`Qwen3-32B`	MBPP	Reflexion	68.85%	289/427	78.55%	21.45%	70.26%
`Qwen3-32B`	MBPP	pure-MCTS	69.79%	427/427	69.79%	30.21%	70.49%
`Qwen3-32B`	MBPP	MCTS-style	69.56%	361/427	67.59%	32.41%	71.43%
`DeepSeek`	HumanEval	Best-of-8	95.73%	131/164	98.47%	1.53%	96.34%
`DeepSeek`	HumanEval	Reflexion	94.51%	138/164	97.83%	2.17%	96.95%
`DeepSeek`	HumanEval	pure-MCTS	92.07%	164/164	92.07%	7.93%	95.73%
`DeepSeek`	HumanEval	MCTS-style	94.51%	162/164	94.44%	5.56%	95.73%
`DeepSeek`	MBPP	Best-of-8	73.54%	322/427	78.88%	21.12%	77.52%
`DeepSeek`	MBPP	Reflexion	71.90%	356/427	77.81%	22.19%	74.47%
`DeepSeek`	MBPP	pure-MCTS	70.96%	427/427	70.96%	29.04%	76.35%
`DeepSeek`	MBPP	MCTS-style	71.19%	425/427	71.29%	28.71%	76.58%

Table 12: Known-feedback baseline completion results. Hidden Solve, Accepted, Acc. Prec., and False Acc. are percentages.

Model	Dataset	Method	Hidden Solve	Accepted	Acc. Prec.	False Acc.	Avg. Iter.
DeepSeek-V4-Flash	HumanEval	Reflection-style	96.34	96.34	100.00	0.00	1.360
DeepSeek-V4-Flash	HumanEval	MCTS-style	96.34	96.34	100.00	0.00	3.183
DeepSeek-V4-Flash	MBPP	Reflection-style	94.15	93.21	100.00	0.00	1.684
DeepSeek-V4-Flash	MBPP	MCTS-style	75.88	74.24	100.00	0.00	4.288
Qwen3-8B	HumanEval	Reflection-style	86.59	86.59	100.00	0.00	2.098
Qwen3-8B	HumanEval	MCTS-style	86.59	86.59	100.00	0.00	3.445
Qwen3-8B	MBPP	Reflection-style	81.97	79.86	100.00	0.00	2.611
Qwen3-8B	MBPP	MCTS-style	66.74	64.64	100.00	0.00	4.002
Qwen3-32B	HumanEval	Reflection-style	93.29	93.29	100.00	0.00	1.604
Qwen3-32B	HumanEval	MCTS-style	93.90	93.90	100.00	0.00	3.244
Qwen3-32B	MBPP	Reflection-style	86.89	85.71	100.00	0.00	2.150
Qwen3-32B	MBPP	MCTS-style	71.19	69.56	100.00	0.00	3.979

Table 13: Logged token comparison between full ReMCTS and MCTS-style. Token counts are prompt-plus-completion totals in millions (M). Ratio is ReMCTS tokens divided by MCTS-style tokens.

Model	Dataset	Setting	ReMCTS Tok. (M)	MCTS-style Tok. (M)	Ratio
Qwen3-8B	HumanEval	no_tests	2.52	2.26	1.12
Qwen3-8B	HumanEval	known	1.07	1.74	0.61
Qwen3-8B	MBPP	no_tests	4.40	3.96	1.11
Qwen3-8B	MBPP	known	3.93	3.77	1.04
Qwen3-32B	HumanEval	no_tests	2.32	2.23	1.04
Qwen3-32B	HumanEval	known	0.80	1.72	0.46
Qwen3-32B	MBPP	no_tests	4.16	3.58	1.16
Qwen3-32B	MBPP	known	4.01	3.52	1.14
DeepSeek-V4-Flash	HumanEval	no_tests	3.01	2.74	1.10
DeepSeek-V4-Flash	HumanEval	known	0.80	1.64	0.49
DeepSeek-V4-Flash	MBPP	no_tests	7.43	6.20	1.20
DeepSeek-V4-Flash	MBPP	known	7.66	5.13	1.49
no_tests total			23.83	20.97	1.14
known total			18.26	17.51	1.04
Overall total			42.09	38.48	1.09

Table 14: Memory ablation results. Hidden Solve, Accepted, and False Acc. are percentages.

Model	Dataset	Method	Hidden Solve	Accepted	False Acc.	Avg. Iter.	Avg. Tree
DeepSeek-V4-Flash	HumanEval known	No global	99.39	99.39	0.00	3.043	7.165
DeepSeek-V4-Flash	HumanEval known	No path	99.39	99.39	0.00	3.030	7.238
DeepSeek-V4-Flash	HumanEval no_tests	No global	94.51	99.39	5.52	3.030	6.835
DeepSeek-V4-Flash	HumanEval no_tests	No path	94.51	100.00	5.49	3.000	6.695
DeepSeek-V4-Flash	MBPP known	No global	80.56	79.39	0.00	4.082	10.761
DeepSeek-V4-Flash	MBPP known	No path	80.09	78.45	0.00	4.082	11.354
DeepSeek-V4-Flash	MBPP no_tests	No global	73.07	99.77	26.76	3.014	7.862
DeepSeek-V4-Flash	MBPP no_tests	No path	72.83	100.00	27.17	3.000	7.621
Qwen3-8B	HumanEval known	No global	92.07	92.07	0.00	3.341	3.159
Qwen3-8B	HumanEval known	No path	95.12	95.12	0.00	3.213	3.366
Qwen3-8B	HumanEval no_tests	No global	85.37	87.80	13.19	3.354	3.262
Qwen3-8B	HumanEval no_tests	No path	86.59	88.41	12.41	3.518	3.689
Qwen3-8B	MBPP known	No global	69.56	67.68	0.00	4.124	3.471
Qwen3-8B	MBPP known	No path	73.54	71.43	0.00	4.389	4.370
Qwen3-8B	MBPP no_tests	No global	66.04	92.97	31.49	3.204	3.162
Qwen3-8B	MBPP no_tests	No path	66.51	94.85	31.60	3.239	3.290
Qwen3-32B	HumanEval known	No global	95.12	95.12	0.00	3.213	3.665
Qwen3-32B	HumanEval known	No path	95.12	95.12	0.00	3.226	3.811
Qwen3-32B	HumanEval no_tests	No global	90.85	97.56	8.13	3.098	3.567
Qwen3-32B	HumanEval no_tests	No path	89.63	98.17	8.70	3.091	3.677
Qwen3-32B	MBPP known	No global	74.71	72.83	0.00	4.115	4.052
Qwen3-32B	MBPP known	No path	78.69	77.28	0.00	4.145	4.934
Qwen3-32B	MBPP no_tests	No global	69.56	96.72	28.33	3.178	3.515
Qwen3-32B	MBPP no_tests	No path	70.02	98.59	28.98	3.098	3.548

Table 15: Search-tree structure statistics for all main ReMCTS experiments. Range gives the minimum and maximum number of tree nodes per task. Eff. Branch is the micro-average effective branch factor over non-leaf nodes.

Model	Dataset	Setting	Avg. Iter.	Avg. Tree	Median	Range	Avg. Depth	Eff. Branch
Qwen3-1.7B	HumanEval	no_tests	3.098	5.165	5	2–17	1.396	2.858
Qwen3-1.7B	HumanEval	known	3.835	5.762	5	2–21	1.384	2.861
Qwen3-1.7B	MBPP	no_tests	3.068	5.433	5	2–15	1.412	2.967
Qwen3-1.7B	MBPP	known	4.974	7.651	7	2–29	1.609	2.820
Qwen3-8B	HumanEval	no_tests	3.500	3.671	3	2–12	1.341	1.904
Qwen3-8B	HumanEval	known	3.354	3.537	3	2–21	1.366	1.741
Qwen3-8B	MBPP	no_tests	3.232	3.389	3	2–27	1.241	1.828
Qwen3-8B	MBPP	known	4.361	4.344	3	2–22	1.283	2.112
Qwen3-14B	HumanEval	no_tests	3.762	5.793	5	2–29	1.360	2.989
Qwen3-14B	HumanEval	known	3.823	5.335	4	2–27	1.317	2.938
Qwen3-14B	MBPP	no_tests	4.162	6.719	5	2–37	1.342	2.942
Qwen3-14B	MBPP	known	4.696	6.260	5	2–28	1.279	2.999
Qwen3-32B	HumanEval	no_tests	3.079	3.683	3	2–27	1.317	1.956
Qwen3-32B	HumanEval	known	3.256	3.604	3	2–16	1.317	1.889
Qwen3-32B	MBPP	no_tests	3.131	3.628	3	2–24	1.283	1.941
Qwen3-32B	MBPP	known	4.204	5.096	3	2–22	1.372	2.141
DeepSeek-V4-Flash	HumanEval	no_tests	3.006	7.116	6	2–21	1.232	4.438
DeepSeek-V4-Flash	HumanEval	known	3.061	7.463	6	2–31	1.293	4.435
DeepSeek-V4-Flash	MBPP	no_tests	3.030	8.019	6	3–33	1.365	4.440
DeepSeek-V4-Flash	MBPP	known	4.056	11.593	8	3–40	1.564	4.578

Table 16: Effect of changing the minimum search iterations from 1 to 3 on hidden solve rate. Score@1 and Score@3 are percentages. ΔScore is the percentage-point difference.

Model	Dataset	Setting	Score@1	Score@3	ΔScore
Qwen3-1.7B	HumanEval	no_tests	64.02	69.51	+5.49
Qwen3-1.7B	HumanEval	known	82.32	83.54	+1.22
Qwen3-1.7B	MBPP	no_tests	51.99	51.29	-0.70
Qwen3-1.7B	MBPP	known	63.70	63.47	-0.23
Qwen3-8B	HumanEval	no_tests	87.20	86.59	-0.61
Qwen3-8B	HumanEval	known	93.29	93.90	+0.61
Qwen3-8B	MBPP	no_tests	63.93	66.74	+2.81
Qwen3-8B	MBPP	known	74.47	74.24	-0.23
Qwen3-14B	HumanEval	no_tests	77.44	78.66	+1.22
Qwen3-14B	HumanEval	known	82.32	82.93	+0.61
Qwen3-14B	MBPP	no_tests	59.02	60.42	+1.41
Qwen3-14B	MBPP	known	66.28	65.57	-0.70
Qwen3-32B	HumanEval	no_tests	90.24	89.63	-0.61
Qwen3-32B	HumanEval	known	96.34	95.12	-1.22
Qwen3-32B	MBPP	no_tests	68.38	70.49	+2.11
Qwen3-32B	MBPP	known	78.92	77.99	-0.94
DeepSeek-V4-Flash	HumanEval	no_tests	93.29	95.12	+1.83
DeepSeek-V4-Flash	HumanEval	known	99.39	98.78	-0.61
DeepSeek-V4-Flash	MBPP	no_tests	70.26	72.83	+2.58
DeepSeek-V4-Flash	MBPP	known	81.03	81.03	+0.00

Table 17: Effect of changing the minimum search iterations from 1 to 3 on search scale. Iter@1/Tree@1 come from early experiments without the current lower bound. Iter@3/Tree@3 come from the current main experiments. ΔTree is the change in average search-tree size.

Model	Dataset	Setting	Iter@1	Iter@3	Tree@1	Tree@3	ΔTree
`Qwen3-1.7B`	HumanEval	`no_tests`	1.293	3.098	2.591	5.165	+2.573
`Qwen3-1.7B`	HumanEval	`known`	2.317	3.835	3.927	5.762	+1.835
`Qwen3-1.7B`	MBPP	`no_tests`	1.237	3.068	2.506	5.433	+2.927
`Qwen3-1.7B`	MBPP	`known`	3.864	4.974	6.129	7.651	+1.522
`Qwen3-8B`	HumanEval	`no_tests`	3.677	3.500	4.073	3.671	-0.402
`Qwen3-8B`	HumanEval	`known`	1.585	3.354	2.677	3.537	+0.860
`Qwen3-8B`	MBPP	`no_tests`	2.494	3.232	3.410	3.389	-0.021
`Qwen3-8B`	MBPP	`known`	2.993	4.361	3.710	4.344	+0.635
`Qwen3-14B`	HumanEval	`no_tests`	2.640	3.762	4.244	5.793	+1.549
`Qwen3-14B`	HumanEval	`known`	2.244	3.823	3.159	5.335	+2.177
`Qwen3-14B`	MBPP	`no_tests`	2.419	4.162	4.473	6.719	+2.246
`Qwen3-14B`	MBPP	`known`	3.471	4.696	4.799	6.260	+1.461
`Qwen3-32B`	HumanEval	`no_tests`	2.329	3.079	3.622	3.683	+0.061
`Qwen3-32B`	HumanEval	`known`	1.354	3.256	2.470	3.604	+1.134
`Qwen3-32B`	MBPP	`no_tests`	1.644	3.131	2.895	3.628	+0.733
`Qwen3-32B`	MBPP	`known`	2.705	4.204	4.098	5.096	+0.998
`DeepSeek-V4-Flash`	HumanEval	`no_tests`	1.104	3.006	2.463	7.116	+4.652
`DeepSeek-V4-Flash`	HumanEval	`known`	1.116	3.061	2.530	7.463	+4.933
`DeepSeek-V4-Flash`	MBPP	`no_tests`	1.014	3.030	2.136	8.019	+5.883
`DeepSeek-V4-Flash`	MBPP	`known`	2.525	4.056	7.005	11.593	+4.588

Table 18: Representative trajectories used to interpret the aggregate trends. The examples are selected from the latest main-result runs. They use hidden tests only for offline analysis.

Case	Observation
Qwen3-1.7B, HumanEval/5, known	Direct fails hidden evaluation on `intersperse`. In the ReMCTS run, the search tree has 10 nodes. Three root candidates fail all visible tests. Several sibling candidates pass all 3 visible tests. The selected candidate inserts the delimiter only between adjacent elements. It passes hidden evaluation. This supports the view that weaker models often benefit from sandbox filtering and evidence-based selection.
Qwen3-8B, HumanEval/26, known	Direct fails hidden evaluation on `remove_duplicates`. The ReMCTS run needs 7 iterations and reaches depth 3. Early nodes repeatedly fail visible tests. The reflection memory records two issues. The model confuses "keep first occurrence" with "keep elements that occur once". It also misses a `List` import. The final node counts element frequencies. It keeps only elements with count one. It passes all 3 visible tests and hidden evaluation. This shows how path reflections can prevent repeated repair mistakes.
Qwen3-32B, HumanEval/83, known	Direct fails hidden evaluation on `starts_one_ends`. It overcounts numbers ending in 1. Qwen3-32B Direct is already strong overall. Thus, this is a residual error rather than a broad failure mode. ReMCTS explores 10 nodes over 8 iterations. The reflection memory points to an inclusion–exclusion error and the special case $n = 1$. The selected candidate passes all 7 visible tests and hidden evaluation. This supports the claim that stronger models mainly benefit by recovering a smaller set of missed implementations.
Qwen3-14B, MBPP task 9, no_tests	The task asks for the minimum positive rotation needed to obtain the same string. In `no_tests`, ReMCTS accepts a candidate that returns `-1` for strings with no smaller period. Hidden evaluation expects full-length rotations, e.g., `find_Rotations("ab")==2` and `find_Rotations("abc")==3`. Probe evidence partially fails. Contract and static checks pass. The LLM semantic review remains optimistic. This produces a false acceptance. This case shows why proxy evidence can be insufficient on MBPP. It also shows why `no_tests` improvements are less stable.