"We Demand Justice!": Towards Social Context Grounding of Political Texts

Abstract

Social media discourse from US politicians frequently consists of 'seemingly similar language used by opposing sides of the political spectrum'. But often, it translates to starkly contrasting real-world actions. For instance, *"We need to keep our students safe from mass shootings"* may signal either *"arming teachers to stop the shooter"* or *"banning guns to reduce mass shootings"* depending on who says it and their political stance on the issue. In this paper, we define and characterize the context that is required to fully understand such ambiguous statements in a computational setting and ground them in real-world entities, actions, and attitudes. To that end, we propose two challenging datasets that require an understanding of the real-world context of the text to be solved effectively. We benchmark these datasets against baselines built upon large pre-trained models such as BERT, RoBERTa, GPT-3, etc,. Additionally, we develop and benchmark more structured baselines building upon existing *Discourse Contextualization Framework* and *Political Actor Representation* models. We perform analysis of the datasets and baseline predictions to obtain further insights into the pragmatic language understanding challenges posed by the proposed social grounding tasks.

1 Introduction

Over the past decade or so, micro-blogging websites, such as Twitter have become the primary channel of engagement between politicians and people in the US. This resulted in political discourse becoming succinct. Politicians from the same party often coordinate the phrasing of social messaging in developing events to amplify their impact (Vaes et al., 2011; Weber and Neumann, 2021). Hence, repetitive phrases such as *'Thoughts and Prayers'* are extensively used to signal more nuanced stances across several events. These platforms also allow for interactivity among politicians

Figure 1: An example of varied *intended meanings* behind the same political message depending on the Author and Event in context

from opposing parties. This causes messaging that is phrased similarly but intended to signal opposing real-world actions. For example, *'Thoughts and Prayers'* is used to express condolences by Republicans in mass shooting events. Whereas it is used in an *angry* or *sarcastic* sense by Democrats as a call for action demanding *'tighter gun control measures'*. The example in fig. 1 shows contrasting interpretations of the phrase *"We need to keep our teachers safe!"* depending on the context.

Humans familiar with the stances of a politician and, possessing knowledge about the event from the news, can easily understand the *intended meaning*. But, computationally understanding the correct meaning of such language is challenging. Our main question in this paper is - ***Can an NLP model find the right meaning?*** From a linguistic perspective, we follow the distinction (Bach, 2008) between *semantic* interpretation (where the meaning is encoded in the utterance directly and does not change based on its external context), and *pragmatic* interpretation (that depends on extra-

Tweet Target Entity and Sentiment		Vague Text Disambiguation
Tweet: As if we needed more evidence.		**Vague Text:** First, but not the last.
		Event: US withdraws from Paris climate agreement that enforces environmental
Event: Kavanaugh Supreme Court Nomination		targets after three years
		Author Party: Republican
Author: Earl Blumenauer (Democrat Politician)		**Disambiguation:** The withdrawal from the Paris climate agreement is the first step
		of many to come for the Trump administration. It will not be the last, as more
Targets: Brett Kavanaugh (negative), Julie Swetnick (positive)		positive changes are sure to follow.
Christine Ford (positive), Deborah Ramirez (positive)		

Incorrect Disambiguations:
1) Joe Biden's inauguration marks the first day of a new era of progress and prosperity, more lasting positive changes are coming. (Incorrect Event)
2) The Paris climate agreement withdrawal is the first of many backward steps this Trump administration is sure to take in destroying our environment. (Incorrect Stance)
3) This is the time for America to move forward and make progress without being held back by a global agreement that doesn't serve our interests. (Doesn't match the vague text)

Target Task Data Statistics		Vague Text Data Statistics	
Unique Tweets	865	Unique Vague Texts	93
Positive Targets	1513	Positive Examples	739
Negative Targets	1085	Negative Examples	2217
Neutral Targets	784	Total Examples	2956
Non-Targets	2509	Number of Events	9
Total Data Examples	5891		
Number of Events	3		

Table 1: Examples of Annotated Datasets and their statistics

linguistic information). The latter has gathered significant interest in the NLP community recently (Bender and Koller, 2020; Bisk et al., 2020), focusing on language understanding, when grounded in an external context (Fried et al., 2023). To a large extent, the focus of such studies was on grounding language in a perceptual environment (e.g., image captioning (Andreas and Klein, 2016; Sharma et al., 2018; Alikhani et al., 2020), instruction following (Wang et al., 2016; Suhr et al., 2019; Lachmy et al., 2022), and game playing (Potts, 2012; Udagawa and Aizawa, 2019) tasks). Unlike these works, in this paper, we focus on *grounding language in a social context*, i.e., modeling the common ground (Clark and Brennan, 1991; Traum, 1994; Stalnaker, 2002) between the author and their social media followers that enables understanding what would otherwise be highly ambiguous utterances.

The *Social Context Understanding*, needed for building successful models for such tasks, can come from a wide variety of sources. The politician's party affiliation, historical stances on the issue, social relationships, knowledge about the involved entities, and related prior and upcoming events, etc, are a few examples of the relevant social context. For example, in fig. 1 event #1, if we model the pragmatic context that Kamala Harris almost always expresses negative sentiment towards guns in her discourse while Mike Pence expresses positive sentiment, it would facilitate understanding the *intended meaning* of the text better.

In this paper, we propose tasks that test the pragmatic understanding of political text in its social context. We benchmark the performance of a wide range of models including LLMs (Brown et al., 2020a; Black et al., 2022) and state-of-the-art Contextual Understanding Models (Pujari and Gold-

wasser, 2021; Feng et al., 2022) on these tasks.

We break down *'Social Context Grounding'* into *three* foundation components: *target entities*, *sentiment towards the targets*, and *intended meaning*. We present two datasets, namely, *'Target Entity and Sentiment Detection'* and *'Vague Text Disambiguation'*. In *'Target Entity and Sentiment Detection'*, the goal is to predict: 1) whether a given entity is the *intended target* of a politician's tweet and 2) the sentiment towards the intended targets. We explicitly focus on tweets that *don't always mention the targets* in their text to incentivize modeling pragmatic communicative intent of the text. In *'Vague Text Disambiguation'*, given an ambiguous political message such as *"We demand justice"* and its social context (*associated event*, & the *author's party affiliation*), the task is to identify a *plausible* unambiguous explanation of the message. We show examples of each task in table 1. We describe the datasets in detail in section 3.

Further, we evaluate the performance of various baselines including pre-trained LM-based classifiers, and LLM in-context learning, which use a textual representation of the social context. We adopt an existing graph-based discourse contextualization framework (Pujari and Goldwasser, 2021) to explicitly model the social context needed to solve the proposed tasks. Our empirical results demonstrate that discourse contextualization models outperform other models, including GPT-3, on both tasks. We present an error analysis of the outputs to gain further insights. We describe the models in section 4 and the results in section 5.

We also present qualitative visualization of a political event, *Brett Kavanaugh Supreme Court Nomination* in section 6.3 from the lens of target entity-sentiment to showcase a unique summary

of the event discourse. Then, we perform human evaluation on *'Vague Text Disambiguation'* and observe that humans find the task much easier than the evaluated models. We also present observations of human vs. LLM errors in disambiguations. Our contributions can be summarized as:

1. Defining and operationalizing the '*Social Context Grounding*' task in political discourse

2. Evaluating various state-of-the-art context representation models on the task. Adopting existing discourse contextualization framework for the proposed tasks and evaluating GPT-3 in-context learning performance on the tasks

3. Performing human studies to benchmark the dataset difficulty and GPT-3 generation performance comparison with human workers[1]

2 Related Work

Pragmatic Language Grounding gained significant focus recently (Bender and Koller, 2020; Bisk et al., 2020) following the rise of Pretrained Language Models (Devlin et al., 2019; Liu et al., 2019; Brown et al., 2020a) as unified NLP models. Most grounding tasks address multi-modal or physical environment descriptions (Barnard et al., 2003; Vogel and Jurafsky, 2010; Chen and Mooney, 2011; Tellex et al., 2011; Mitchell et al., 2012; Anderson et al., 2018). We refer the reader to (Fried et al., 2023) for a thorough overview. In contrast, we focus on grounding language in a *social* context.

Social Context Modeling Hovy and Yang (2021) show that modeling social context is necessary for human-level NLU. As political messages are often targeted at the voter base aware of the political context (Weber and Neumann, 2021; Vaes et al., 2011), they are vague by design. Several previous works model social context for entity linking (Yang et al., 2016), social media connections relationship for fake news detection (Baly et al., 2018; Mehta et al., 2022) and, political bias detection (Li and Goldwasser, 2019; Baly et al., 2020). These works model partial aspects of social context, relevant to their tasks. Two recent frameworks aim to capture social context holistically (Pujari and Goldwasser, 2021; Feng et al., 2022). Evaluation tasks presented in both works show interesting social context understanding but are not fully representative of the challenges of *Social Context Grounding*. Zhan et al. (2023) propose a dataset for dialogue understanding addressing general social commonsense.

---

[1]Our data and code will be released under MIT license

Related Semantic and Pragmatic tasks closest to our *Target Entity Sentiment Identification* task is *Stance Detection* in social media (Mohammad et al., 2016; AlDayel and Magdy, 2020). To clarify our contribution, Mohammad et al. (2016), a popular SemEval task, looks at sentiment towards 5 targets, while our data has 362 unique targets. Allaway and McKeown (2020) and Zhang et al. (2022) also propose stance datasets on tweets. But, they focus mainly on semantic understanding of text that allows them to predict agreement or disagreement with well-defined statements. Our *Vague Text Disambiguation* task is related to recent works that study implicit inferences (Hoyle et al., 2023), and pragmatic understanding (Hu et al., 2023). However, our tasks evaluate pragmatic understanding using an explicit context, absent in those tasks.

3 Datasets

We design and collect two datasets for '*Social Context Grounding*' evaluation. As discussed in section 1, we focus mainly on three components of '*Social Context*': *target entities*, *sentiment towards the targets*, and *intended meaning of vague text with context*. Tweet Target Entity and Sentiment task requires identifying *targets* and *sentiment towards them*. *Vague Text Disambiguation Task* evaluates identifying the correct *intended meaning*.

In the *Tweet Target Entity and Sentiment* dataset, we collect annotations of opinionated tweets from known politicians for their intended targets and sentiments towards them. We focus on *three* political events for this task. The dataset and its collection process are described in detail below in section 3.1.

In the *Vague Text Disambiguation Task*, we collect plausible explanations of vague texts, given the social context. Social context consists of *author affiliation* and *specific event*. We focus on *eight* political events. This dataset is detailed in section 3.2. Examples and data statistics are shown in table 1.

3.1 Tweet Target Entity and Sentiment Task

In this task, given a tweet T, its context, and an entity E, the objective is to predict whether or not E is an intended target of T and the sentiment towards E. Political discourse often contains opinionated discourse about world events and social issues. Understanding the entities which are the focal points of the discussion and the sentiment expressed toward them forms a major part of understanding the discussion. We collect tweets that don't directly

mention the target entities. Thus, understanding the event details and the author's general stances about the entities involved in the event is necessary to solve this task effectively.

We focus our tweet collection on three recent divisive events: *George Floyd Protests*, *2021 US Capitol Attacks*, and *Brett Kavanaugh's Supreme Court Nomination*. We pick the events such that they have contrasting talking points from the left and right-leaning politicians in the US. We identify relevant participating entities for each of the three events. Examples of focal talking points and involved entities for the event *George Floyd Protests* are listed below.

- **Left**: police brutality, systemic racism against black people, need for action to cleanse the police structures
- **Right**: support for the police organization while condemning the specific incident, general lawlessness, and violence of the protests, corruption among BLM organization

Involved Entities: *George Floyd, United States Police, Derek Chauvin, Donald Trump, Joe Biden, United States Congress, Black people, Democratic Party, Republican Party, BLM, Antifa*

3.1.1 Target-Sentiment Data Collection

We filter $3,454$ tweets for the *three* events using hashtags, keyword-based querying, and the dates of the event-based filtering from the Congress Tweets repository corpus[2]. We collect a subset of $1,779$ tweets that contain media (images/video) to increase the chances of the tweet text not containing the target entity mentions. Then, we use 6 in-house human annotators and Amazon Mechanical Turk (AMT) workers who are familiar with the event context for annotation. We ask them to annotate the targeted entities and sentiments towards the targets. The authors of this paper also participated in the annotation process. We provide them with entity options based on the event in the focus of the tweet. Annotators are allowed to add additional options if needed. We also ask the annotators to mark non-targets for each tweet. We instruct them to keep the non-targets as relevant to the event as possible to create harder negative examples. Each tweet is annotated by three annotators. We filter 865 unique tweets with $5,891$ annotations, with majority agreement on each tweet. All the AMT annotations were additionally verified by in-house annotators for correctness. AMT workers were

[2]https://github.com/alexlitel/congresstweets

paid USD 1 per tweet. It took 3 minutes on average for each assignment, resulting in an hourly pay of USD 20. We include screenshots of the collection task GUIs in the appendix.

We split the train, and test sets by events, authors, and targets to incentivize testing the general social grounding capabilities of the models. The test set also consists of authors, targets, and events not seen in the training set. We use *Capitol Riots* event for the test set of *Target Entity and Sentiment* Task. We split the examples into $4,370$ train, 511 development, and $1,009$ test examples.

3.2 Vague Text Disambiguation Task

The task of *Vague Text Disambiguation* evaluates the model's ability to identify a plausible explanation of an ambiguous quote given the event context and author affiliation. The rationale behind this task is that "*ambiguous language could be assigned grounded meaning when we know who is saying it and in which context*". For instance "*protecting our children from mass shootings*" could easily be disambiguated as either "*ban guns*" or "*arm teachers*" when we know the stance of the politician on the issue of '*gun rights*'.

We collect ambiguous quote candidates that have opposing interpretations in the context of the given event. We use AMT workers to obtain initial explanations for the quotes. We validate and filter the data using expert annotation. We use the validated data as in-context examples for large language models to generate more candidates. Human annotators filter good generations while also analyzing the performance of LLMs on this task. These data points are further added to the dataset.

3.2.1 Vague Text Data Collection

Initially, we collect vague text candidates from tweets by US politicians (i.e. senators and representatives) between the years 2019 to 2021 from Congress Tweets corpus. We identify a list of 9 well-known events from that period. We filter tweets related to these events using the time frame of the events and relevant hashtags. By using a pre-trained named entity recognition (NER) model based on BERT (Devlin et al., 2019), we collect tweets that do not contain any entity mentions to identify potential candidates for vague texts. Then, we manually inspect and identify examples that could be interpreted in contrasting senses by flipping their social context. We obtain 93 vague text candidates via this process.

We match the 93 ambiguous tweets with different events that fit them. We use both Democrat and Republican as the author party affiliation. We obtain 600 *context-tweet* pairs for AMT annotation. For each tweet, we ask AMT workers to annotate the following two aspects: 1) sentiment towards the three most relevant entities in the event (sanity check) and 2) a detailed explanation of the *intended meaning* given the event and author's party affiliation. We obtain 469 reasonable annotations. After this step, each annotation was screened by in-house annotators. We ask three in-house annotators to vote on the *correctness*, *appropriateness*, and *plausibility* of the annotation given the context. Thus, we create a total of 374 examples.

Using these examples, we further generate candidates for the task using LLM few-shot prompting. We use the examples from the previous step as in-context few-shot examples in the prompt. We use GPT-NeoX (Black et al., 2022) and GPT-3 (Brown et al., 2020a) for candidate generation. For each generated answer, manual inspection by three in-house annotators is performed to ensure data quality. We generate 928 candidates using GPT-NeoX and GPT-3. Human expert filtering results in 650 generations that pass the quality check. After removing redundant samples, we obtain 365 examples. Thus, we obtain a total of 739 annotations for this task. Then, for each of the 739 examples, we ask in-house annotators to select 3 relevant negative options from the pool of explanations. We instruct them to pick hard examples that might contain similar entities as the correct interpretation. This results in 2, 956 binary classification data samples. We analyze and discuss the results of human validation of large LM generations in section 6.

Similar to the previous task, we split the train, test sets by events, and vague text to test the general social understanding capabilities of the model. We reserve *Donald Trump's second impeachment verdict* event for the test set. We also reserve Democratic examples of 2 events and Republican examples of 2 events exclusively for the test set. We split the dataset into 1, 916 train examples, 460 development examples, and 580 test examples.

4 Baselines

We conduct experiments in *four* phases: (1) Pretrained Language Model (PLM) baselines, (2) Large Language Model (LLM) baselines, (3) Contextualized embedding baselines, and (4) Discourse Contextualization Model baselines. The rationale behind our experimental design is to evaluate a broad spectrum of social context modeling for both tasks. We make a distinction between PLMs and LLMs. PLMs are pre-trained LMs that we can fine-tune for the task data (BERT, RoBERTa, etc.). LLMs are LMs that we only use for inference in an in-context learning setup (GPT-* models).

In the first phase, we evaluate the performance of the fine-tuned pre-trained language models (PLM). We experiment with three stages of modeling context. Firstly, we evaluate no contextual information setting. Second, we include the authors' twitter bios as context. Finally, we evaluate the information from the author, event, and target entity Wikipedia pages as context. We use BERT (Devlin et al., 2019) and RoBERTa (Liu et al., 2019) PLMs for our experiments. We report the results of all our baseline experiments in table 2 and table 3.

In the second phase, we evaluate GPT-3 in *zero-shot* and *four-shot* in-context learning paradigm on both tasks. We provide contextual information in the prompt in the form of short event descriptions and authors' affiliation descriptions. As GPT-3 is trained on news data until September 2021, GPT-3 is trained on data about the events in our dataset.

In the third phase, we evaluate the performance of politician embeddings from Political Actor Representation (PAR) (Feng et al., 2022) and Discourse Contextualizaton Framework (DCF) (Pujari and Goldwasser, 2021) models. We use PAR embeddings available on their GitHub repository[3]. For DCF model, we use released pre-trained models from GitHub repository[4] to generate author, event, text, and target entity embeddings. We evaluate the embeddings on both tasks. We give a brief overview of these models in section 4.1 & section 4.2.

In the fourth phase, we use tweets of politicians from related previous events and build context graphs for each data example as proposed in Pujari and Goldwasser (2021). We use Wikipedia pages of authors, events, and target entities to add social context information to the graph. Then, we train the Discourse Contextualization Framework (DCF) for each task and evaluate its performance on both tasks. Further details of our baseline experiments are presented in subsection section 4.3. Results of our baseline experiments are discussed in section 5.

---

[3]https://github.com/BunsenFeng/PAR
[4]https://github.com/pujari-rajkumar/compositional_learner

Model	Target Identification				Sentiment Identification			
	Prec	**Rec**	**Macro-F1**	**Acc**	**Prec**	**Rec**	**Macro-F1**	**Acc**
PLM Baselines - No Context								
BERT-large	69.09	72.35	68.83	70.56	58.74	60.17	58.95	58.37
RoBERTa-base	66.58	69.54	65.14	66.40	61.68	61.27	61.36	60.65
PLM Baselines + Twitter Bio Context								
BERT-large + user-bio	69.03	71.86	69.34	71.66	60.02	60.44	60.13	59.86
RoBERTa-base + user-bio	65.83	68.65	64.79	66.30	60.06	59.91	59.94	59.46
PLM Baseline + Wikipedia Context								
BERT-large + wiki	63.58	65.78	60.33	61.05	53.48	56.44	53.9	53.32
RoBERTa-base + wiki	69.02	72.32	68.62	70.27	57.62	59.1	58.07	58.28
LLM Baseline								
GPT-3 0-shot	69.25	70.58	69.77	73.78	56.2	55.04	54.18	56.80
GPT-3 4-shot	69.81	72.99	66.45	67.03	58.12	57.10	55.00	57.51
Static Contextutalized Embeddings								
BERT-large + PAR Embs	65.4	67.33	60.25	60.56	55.24	57.54	55.89	55.80
RoBERTa-base + PAR Embs	68.38	71.63	67.67	69.18	55.01	56.89	55.51	55.40
BERT-large + DCF Embs	68.76	72.02	68.32	69.97	61.59	63.25	61.22	60.75
RoBERTa-base + DCF Embs	72.89	75.95	73.56	75.82	63.05	63.52	62.90	63.03
Discourse Contextualization Model								
BERT-large + DCF	71.12	74.61	71.17	72.94	65.81	65.25	65.34	65.31
RoBERTa-base + DCF	70.44	73.86	70.39	72.15	63.45	63.34	63.37	63.23

Table 2: Results of baseline experiments on *Target Entity and Sentiment* test sets. *Target Identification* is a binary-classification task. Sentiment Identification is a 4-class classification task. We report macro-averaged Precision, macro-averaged Recall, macro-averaged F1, and Accuracy metrics.

Model	Vague Text Disambiguation			
	Prec	**Rec**	**Macro-F1**	**Acc**
PLM Baselines - No Context				
BERT-large	52.24	55.58	50.28	53.75
RoBERTa-base	55.3	51.82	54.53	56.08
PLM Baseline + Wikipedia Context				
BERT-large + wiki	52.31	46.9	66.87	76.03
BERT-base + wiki	51.85	38.62	64.36	75.69
LLM Baseline				
GPT-3 0-shot	63.10	62.92	62.58	63.5
GPT-3 4-shot	62.05	62.29	61.86	62.04
Static Contextutalized Embeddings				
BERT-large + PAR	47.68	49.66	65.53	73.79
BERT-base + PAR	45.93	54.48	65.49	72.59
BERT-large + DCF Embs	47.18	63.45	67.55	73.10
BERT-base + DCF Embs	56.58	59.31	71.71	78.45
Discourse Contextualization Model				
BERT-large + DCF	52.76	59.31	69.94	76.55
BERT-base + DCF	52.73	60.00	70.06	76.55

Table 3: Results of baseline experiments on *Vague Text Disambiguation* dataset test split. This task is designed as a binary classification task. We report macro-averaged Precision, macro-averaged Recall, macro-averaged F1, and Accuracy metrics

4.1 Discourse Contextualization Framework

Discourse Contextualization Framework (DCF), proposed in Pujari and Goldwasser (2021), leverages the relationships between several components of social context to learn context-enriched representations for text, politicians, events, issues, and other relevant entities. Their framework consists of *encoder* and *composer* modules that compute holistic representations for each component in the context graph. The encoder creates initial representations for of the nodes. Composer propagates the information within the graph to update node representations. They further define link prediction learning tasks over context graphs to train the model. They show that their representations significantly outperform several PLM-based baselines trained using the same learning tasks with the same data. They further present qualitative evaluations to show that their representations capture interesting aspects of contextual information effectively.

4.2 Political Actor Representation

Feng et al. (2022) propose the *Political Actor Representation* (PAR) framework, a graph-based approach to learn more effective politician embeddings. They propose three learning tasks, namely, 1) Expert Knowledge Alignment 2) Stance Consistency training & 3) Echo chamber simulation, to infuse social context into the politician representations. They show that PAR representations outperform state-of-the-art models on *Roll Call Vote Prediction* and *Political Perspective Detection*.

4.3 Experimental Setup

Target Entity Identification is set up as a binary classification task. Input is a tuple of (*author, event, tweet, target-entity*). The task is to predict whether or not the given *entity* is an intended target of the tweet. *Sentiment Identification* is set up as 4-way classification. Input is similar to *Target Entity Identification* task. The task is to predict the sentiment towards the given *entity* as one of: [*positive, neutral, negative, non-target*]. *Vague Text Disambiguation* is set up as a binary classification task. Input is a tuple of (*party-affiliation, event, vague-text, explanation-text*). The task is to predict whether or not the explanation matches the given context.

In the first phase, for no-context experiments, we use the author, event, tweet text, and target embeddings obtained using PLM. We concatenate all the embeddings as input. For Twitter bio context experiments, we replace author embedding with the embedding of their Twitter bio. For Wikipedia context experiments, we replace author, event, and target embeddings with the embeddings of their respective Wikipedia pages. *It is interesting to note that the Wikipedia context baseline contains all the necessary and sufficient information for humans to solve all the tasks.*

In the second phase, we use training examples as in-context few-shot examples. We provide a task description and event description summaries in the prompt.

In the third phase, for PAR experiments, we replace the author embedding with the PAR politician embeddings from their GitHub repository. We replace missing author embeddings with their Wikipedia embeddings. For the *Vague Text* task, we average PAR embeddings for all politicians of the party to obtain party embeddings. To get DCF embeddings, we generate embeddings for the author, event, tweet, entity, vague text, and explanation using context graphs we build using author tweets from relevant past events. We build the graph using author, event, given tweet, relevant tweets, and target entity nodes for the first task. We use similar graphs for the other tasks as well.

In the fourth phase, we use the same setup as the DCF embedding baseline from earlier. In addition, we also back-propagate the loss from the task training to the DCF parameters. This allows us to fine-tune the DCF representations of text and other nodes in the context graph for our tasks.

5 Results

We show the results of our baseline experiments in table 2 and table 3. We evaluate our models using macro-averaged precision, macro-averaged-recall, macro-F1, and accuracy metrics. As the classes are not balanced, macro-F1 is the main metric we use to benchmark the results. Overall, the results indicate that explicitly modeling social context helps with our tasks. DCF model mainly represents the social context in the form of text documents for all nodes. Further symbolic addition of other types of context such as social relationships among politicians and relationships between various nodes could further help in achieving better performance on these tasks.

In the *Target Entity* task, RoBERTa-base + DCF embeddings obtains the best performance of 73.56 F1 compared to 68.83 F1 for the best no-context baselines. Twitter bio context and wiki-context hardly improve upon Target Entity and Sentiment tasks. We hypothesize that this shows the effectiveness of modeling contextual information explicitly vs. concatenating context as text documents. The wiki-context model has all the information necessary to solve the tasks but it is not explicitly modeled. No context performance well above the random performance of 50 F1 indicates the bias in the target entity distribution among classes. We discuss this in section 6.3. In *Sentiment Identification* task, we see that BERT-large + DCF back-propagation outperforms all the other models with 65.34 F1. Wiki-context models perform worse than no-context baselines indicating that PLM embeddings might be adding noise.

Vague Text Disambiguation task results in table 3 show that DCF models outperform other models significantly. 71.71 F1 is obtained by BERT-base + DCF embeddings. BERT-base performing better than bigger PLMs might be due to DCF model's original learning tasks being trained on top of BERT-base embeddings. For this task, we initiate DCF experiments with the trained MLP layers of the wiki-context model. We observe that this initialization gives a performance increase of around 0.85 F1 on the best model.

6 Analysis and Discussion

6.1 Vague Text LLM Generation Quality

We look into the quality of our LLM-generated disambiguation texts. While GPT-NeoX (Black et al., 2022) produced only 98 good examples out of the

Democrat Only Entities		Common Entities					Republican Only Entities	
		Agreed-Upon Entities		Divisive Entities				
Target	Sentiment	Target	Sentiment	Sentiment (D)	Target	Sentiment (R)	Target	Sentiment
Anita Hill	Positive	US Supreme Court	Neutral	Positive	Christine Blasey Ford	Negative	Susan Collins	Positive
Patty Murray	Positive	US Senate	Neutral	Positive	Deborah Ramirez	Negative	Chuck Grassley	Positive
Merrick Garland	Positive	FBI	Neutral	Positive	Julie Swetnick	Negative	Diane Feinstein	Negative
Jeff Flake	Negative	Judiciary Committee	Neutral	Negative	Brett Kavanaugh	Positive	Chuck Schumer	Negative
				Negative	Donald Trump	Positive	Sean Hannity	Neutral
					Mitch McConnell	Positive		

Table 4: Target Entity-Sentiment centric view of *Kavanaugh Supreme Court Nomination* discourse

498 generated instances with the rest being redundant, GPT-3 (Brown et al., 2020a) performed much better. Among the 430 generated instances, 315 were annotated as good which converts to an acceptance rate of 20.04% for GPT-NeoX and 73.26% for GPT-3 respectively. In-house annotators evaluated the quality of the generated responses for how well they aligned with the contextual information. They rejected examples that were either too vague, align with the wrong ideology, or were irrelevant. In the prompt, we condition the input examples in all the few shots to the same event and affiliation as the input vague text. In comparison, the validation of AMT annotations for the same task yielded 79.8% good examples even after extensive training and qualification tests. Most of the rejections from AMT were attributed to careless annotations.

6.2 Vague Text Human Performance

We look into how humans perform on the *Vague Text Disambiguation* task. To that end, we randomly sample 97 questions from the dataset and ask in-house annotators to answer them as multiple-choice questions. Each vague text-context pair was given 4 choices out of which only one was correct. We provide a brief event description along with all the metadata available to the annotator. Each question was answered by 3 annotators. Among the 97 questions that were answered, we observe an accuracy to be 94.85%, which shows this task is easy for humans who understand the context.

6.3 Target Entity Visualization

In table 4, we study an event, *Kavanaugh Supreme Court Nomination*, using entity target sentiment annotations. We identify entities that are discussed by both parties. We further separate them into divisive and agreed-upon entities based on expressed sentiments. We also show partisan discussed entities for the event. This analysis paints a very accurate picture of the discussed event. We observe that the main entities of Trump, Dr. Ford, Kavanaugh, Sen. McConnell, and other accusers/survivors emerge as divisive entities. Entities such as Susan Collins and Anita Hill who were vocal mouthpieces of the respective party stances but didn't directly participate in the event emerge as partisan entities. Supreme Court, FBI, and other entities occur in the discourse but only as neutral entities. This analysis shows the usefulness of the *Target Entity and Sentiment* identification in accurately summarizing events. Successful models on these tasks could greatly help in understanding political events better.

6.4 DCF Context Understanding

We look into examples that are incorrectly predicted using Wikipedia pages but correctly predicted when using the DCF model. We report some of the examples in table 5 in the appendix. In examples 1 & 2 of *Target Entity-Sentiment* task, we see that when the entity is not explicitly mentioned in the tweet, the Wiki-Context model fails to identify them as the target entities. We posit that while the Wikipedia page of each relevant event will contain these names, explicit modeling of entities in DCF model allows these examples to be correctly classified. Examples $1-3$ of *Vague Text Disambiguation* task show that when no clear terms indicate the sentiment towards a view, the Wiki-Context model fails to disambiguate the tweet text. Explicit modeling of politician nodes in the DCF model might allow these texts to be correctly disambiguated.

7 Conclusion and Future Work

In this paper, we motivate, define, and operationalize "*Social Context Grounding*" for political discourse. We build two datasets that are useful to evaluate social context grounding in NLP models. We experiment with many types of context modeling and benchmark existing SOTA models. We show that explicit modeling of social context outperforms naive concatenation of context and large models such as GPT-3. Future work includes building datasets for other components of Social Context Grounding and building models that account for context in various forms.

Limitations

Our work only addresses English language text in US political domain. We also build upon large language models and large PLMs which are trained upon huge amounts of uncurated data. Although we employed human validation at each stage, biases could creep into the datasets. We also don't account for the completeness of out datasets as it is a pioneering work on a new problem. Social context is vast and could have myriad of components. We only take a step in the direction of social context grounding in this work. The performance on these datasets might not indicate full social context understanding but they should help in sparking research in the direction of models that explicitly model such context. Although we tuned our prompts a lot, it is possible that better prompts and evolving models might produce better results on the LLM baselines. Our qualitative analysis is predicated on a handful of examples. They are attempts to interpret the results of large neural models and hence don't carry as much confidence as our empirical observations.

Ethics Statement

In this work, our data collection process consists of using both AMT and GPT-3. For the *Target Entity and Sentiment* task, we pay AMT workers $1 per HIT and expect an average work time of 3 minutes. This translates to an hourly rate of $20 which is above the federal minimum wage. For the *Vague Text Disambiguation* task, we pay AMT workers $1.10 per HIT and expect an average work time of 3 minutes. This translated to an hourly rate of $22.

We recognize collecting political views from AMT and GPT-3 may come with bias or explicit results and employ expert gatekeepers to filter out unqualified workers and remove explicit results from the dataset. Domain experts used for annotation are chosen to ensure that they are fully familiar with the events in focus. Domain experts were provided with the context related to the events via their Wikipedia pages, background on the general issue in focus, fully contextualized quotes, and authors' historical discourse obtained from ontheissues.org. We have an annotation quid-pro-quo system in our lab which allows us to have a network of in-house annotators. In-house domain experts are researchers in the CSS area with familiarity with a range of issues and stances in the US political scene. They are given the information necessary to understand the events in focus in the form of Wikipedia articles, quotes from the politicians in focus obtained from ontheissues.org, and news articles related to the event. We make the annotation process as unambiguous as possible. In our annotation exercise, we ask the annotators to mark only high-confidence annotations that can be clearly explained. We use a majority vote from 3 annotators to validate the annotations for the target entity task.

Our task is aimed at understanding and grounding polarized text in its intended meaning. We take examples where the intended meaning is clearly backed by several existing real-world quotes. We do not manufacture the meaning to the vague statements, we only write down unambiguous explanations where context clearly dictates the provided meaning. Applications of our research as we envision would be adding necessary context to short texts by being able to identify past discourse from the authors that are relevant to the particular text in its context. It would also be able to ground the text in news articles that expand upon the short texts to provide full context.

References

Abeer AlDayel and Walid Magdy. 2020. Stance detection on social media: State of the art and trends. *CoRR*, abs/2006.03644.

Malihe Alikhani, Piyush Sharma, Shengjie Li, Radu Soricut, and Matthew Stone. 2020. Cross-modal coherence modeling for caption generation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 6525–6535, Online. Association for Computational Linguistics.

Emily Allaway and Kathleen McKeown. 2020. Zero-Shot Stance Detection: A Dataset and Model using Generalized Topic Representations. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 8913–8931, Online. Association for Computational Linguistics.

Peter Anderson, Qi Wu, Damien Teney, Jake Bruce, Mark Johnson, Niko Sünderhauf, Ian Reid, Stephen Gould, and Anton Van Den Hengel. 2018. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3674–3683.

Jacob Andreas and Dan Klein. 2016. Reasoning about pragmatics with neural listeners and speakers. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 1173–

1182, Austin, Texas. Association for Computational Linguistics.

Kent Bach. 2008. *Pragmatics and the Philosophy of Language*, pages 463 – 487. Wiley Online Library.

Ramy Baly, Giovanni Da San Martino, James Glass, and Preslav Nakov. 2020. We can detect your bias: Predicting the political ideology of news articles. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 4982–4991.

Ramy Baly, Georgi Karadzhov, Dimitar Alexandrov, James Glass, and Preslav Nakov. 2018. Predicting factuality of reporting and bias of news media sources. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 3528–3539, Brussels, Belgium. Association for Computational Linguistics.

Kobus Barnard, Pinar Duygulu, David Forsyth, Nando De Freitas, David M Blei, and Michael I Jordan. 2003. Matching words and pictures. *The Journal of Machine Learning Research*, 3:1107–1135.

Emily M. Bender and Alexander Koller. 2020. Climbing towards NLU: On meaning, form, and understanding in the age of data. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5185–5198, Online. Association for Computational Linguistics.

Yonatan Bisk, Ari Holtzman, Jesse Thomason, Jacob Andreas, Yoshua Bengio, Joyce Chai, Mirella Lapata, Angeliki Lazaridou, Jonathan May, Aleksandr Nisnevich, Nicolas Pinto, and Joseph Turian. 2020. Experience grounds language. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 8718–8735, Online. Association for Computational Linguistics.

Sid Black, Stella Biderman, Eric Hallahan, Quentin Anthony, Leo Gao, Laurence Golding, Horace He, Connor Leahy, Kyle McDonell, Jason Phang, Michael Pieler, USVSN Sai Prashanth, Shivanshu Purohit, Laria Reynolds, Jonathan Tow, Ben Wang, and Samuel Weinbach. 2022. GPT-NeoX-20B: An open-source autoregressive language model. In *Proceedings of the ACL Workshop on Challenges & Perspectives in Creating Large Language Models*.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020a. Language models are few-shot learners.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam Mc-Candlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020b. Language models are few-shot learners. *CoRR*, abs/2005.14165.

David Chen and Raymond Mooney. 2011. Learning to interpret natural language navigation instructions from observations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 25, pages 859–865.

Herbert H Clark and Susan E Brennan. 1991. Grounding in communication. *Perspectives on Socially Shared Cognition*, pages 127 – 149.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Shangbin Feng, Zhaoxuan Tan, Zilong Chen, Ningnan Wang, Peisheng Yu, Qinghua Zheng, Xiaojun Chang, and Minnan Luo. 2022. Par: Political actor representation learning with social context and expert knowledge. *arXiv preprint arXiv:2210.08362*.

Daniel Fried, Nicholas Tomlin, Jennifer Hu, Roma Patel, and Aida Nematzadeh. 2023. Pragmatics in language grounding: Phenomena, tasks, and modeling approaches. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 12619–12640, Singapore. Association for Computational Linguistics.

Dirk Hovy and Diyi Yang. 2021. The importance of modeling social factors of language: Theory and practice. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 588–602, Online. Association for Computational Linguistics.

Alexander Hoyle, Rupak Sarkar, Pranav Goel, and Philip Resnik. 2023. Natural language decompositions of implicit content enable better text representations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 13188–13214, Singapore. Association for Computational Linguistics.

Jennifer Hu, Sammy Floyd, Olessia Jouravlev, Evelina Fedorenko, and Edward Gibson. 2023. A fine-grained comparison of pragmatic language understanding in humans and language models. In *Pro-*

ceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 4194–4213, Toronto, Canada. Association for Computational Linguistics.

Royi Lachmy, Valentina Pyatkin, Avshalom Manevich, and Reut Tsarfaty. 2022. Draw me a flower: Processing and grounding abstraction in natural language. Transactions of the Association for Computational Linguistics, 10:1341–1356.

Chang Li and Dan Goldwasser. 2019. Encoding social information with graph convolutional networks forPolitical perspective detection in news media. In Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics, pages 2594–2604, Florence, Italy. Association for Computational Linguistics.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. ArXiv, abs/1907.11692.

Nikhil Mehta, María Leonor Pacheco, and Dan Goldwasser. 2022. Tackling fake news detection by continually improving social context representations using graph neural networks. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 1363–1380.

Margaret Mitchell, Jesse Dodge, Amit Goyal, Kota Yamaguchi, Karl Stratos, Xufeng Han, Alyssa Mensch, Alexander Berg, Tamara Berg, and Hal Daumé III. 2012. Midge: Generating image descriptions from computer vision detections. In Proceedings of the 13th Conference of the European Chapter of the Association for Computational Linguistics, pages 747–756.

Saif M. Mohammad, Parinaz Sobhani, and Svetlana Kiritchenko. 2016. Stance and sentiment in tweets. CoRR, abs/1605.01655.

Christopher Potts. 2012. Goal-driven answers in the cards dialogue corpus. In Proceedings of the 30th west coast conference on formal linguistics, pages 1–20. Cascadilla Proceedings Project Somerville, MA.

Rajkumar Pujari and Dan Goldwasser. 2021. Understanding politics via contextualized discourse processing. In Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, pages 1353–1367, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Piyush Sharma, Nan Ding, Sebastian Goodman, and Radu Soricut. 2018. Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning. In Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 2556–2565, Melbourne, Australia. Association for Computational Linguistics.

Robert Stalnaker. 2002. Common ground. Linguistics and philosophy, 25(5/6):701–721.

Alane Suhr, Claudia Yan, Jack Schluger, Stanley Yu, Hadi Khader, Marwa Mouallem, Iris Zhang, and Yoav Artzi. 2019. Executing instructions in situated collaborative interactions. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 2119–2130, Hong Kong, China. Association for Computational Linguistics.

Stefanie Tellex, Thomas Kollar, Steven Dickerson, Matthew Walter, Ashis Banerjee, Seth Teller, and Nicholas Roy. 2011. Understanding natural language commands for robotic navigation and mobile manipulation. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 25, pages 1507–1514.

David Traum. 1994. A computational theory of grounding in natural language conversation.

Takuma Udagawa and Akiko Aizawa. 2019. A natural language corpus of common grounding under continuous and partially-observable context. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 33, pages 7120–7127.

Jeroen Vaes, Maria Paola Paladino, and Chiara Magagnotti. 2011. The human message in politics: The impact of emotional slogans on subtle conformity. The Journal of Social Psychology, 151(2):162–179. PMID: 21476460.

Adam Vogel and Dan Jurafsky. 2010. Learning to follow navigational directions. In Proceedings of the 48th annual meeting of the association for computational linguistics, pages 806–814.

Sida I. Wang, Percy Liang, and Christopher D. Manning. 2016. Learning language games through interaction. In Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 2368–2378, Berlin, Germany. Association for Computational Linguistics.

Derek Weber and Frank Neumann. 2021. Amplifying influence through coordinated behaviour in social networks. Social Network Analysis and Mining, 11.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Remi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander Rush. 2020. Transformers: State-of-the-art natural language processing. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, pages 38–45, Online. Association for Computational Linguistics.

Yi Yang, Ming-Wei Chang, and Jacob Eisenstein. 2016. Toward socially-infused information extraction: Embedding authors, mentions, and entities. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 1452–1461, Austin, Texas. Association for Computational Linguistics.

Haolan Zhan, Zhuang Li, Yufei Wang, Linhao Luo, Tao Feng, Xiaoxi Kang, Yuncheng Hua, Lizhen Qu, Lay-Ki Soon, Suraj Sharma, Ingrid Zukerman, Zhaleh Semnani-Azad, and Gholamreza Haffari. 2023. Socialdial: A benchmark for socially-aware dialogue systems.

Xinliang Frederick Zhang, Nick Beauchamp, and Lu Wang. 2022. Generative entity-to-entity stance detection with knowledge graph augmentation. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 9950–9969, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

A Reproducibility

We use the HuggingFace Transformers (Wolf et al., 2020) library for PLMs. We use GPT-NeoX implementation by ElutherAI (Black et al., 2022) and GPT-3 (Brown et al., 2020b) via OpenAI API for our LLM baselines. We run 100 epochs for all experiments. We use 10 NVIDIA GeForce 1080i GPUs for our experiments. We use the train, development, and test splits detailed in section 3 for our experiments. We use the development macro-F1 for early stopping. We run all our experiments using random seeds to ensure reproducibility. We experiment with a random seed value set to {13}. We report the results of the 3 fold cross-validation. We report only the mean on all the cross-fold validation results for clarity. All our code, datasets, and result logs will be released publicly upon acceptance. We experiment with 3, 5, and 10 fold cross-validation. As the results on the development data are almost identical, we report the results of 3 fold cross-validation in all our experiments.

B Error Analysis

C Annotation Interfaces

Target Entity and Sentiment Task	Vague Text Disambiguation Task
Tweet: Republicans held Justice Scalia's seat open for more than 400 days. Justice Kennedy's seat has been vacant for less than two months. It's more important to investigate a serious allegation of sexual assault than to rush Kavanaugh onto the Supreme Court for a lifetime appointment.
Author: Adam Schiff (Democrat)
Event: Brett Kavanaugh Supreme Court nomination

Entity: Christine Blasey Ford

Wiki-Context Prediction: Not Target \| **DCF Prediction**: Target (correct) | **Tweet**: Thanks for this.

Affiliation: Democrat
Event: United States withdrawal from the Paris Agreement
Paraphrase: There's nothing surprising in withdrawing from the Paris agreement. Thanks for not caring our environment and future generations.

Wiki-Context Prediction: No \| **DCF Prediction**: Yes (correct) |
| **Tweet**: We will not be intimidated. Democracy will not be intimidated. We must hold the individuals responsible for the Jan. 6th attack on the U.S. Capitol responsible. Thank you @RepAOC for tonight's Special Order Hour and we will continue our efforts to #HoldThemAllAccountable.
Author: Adriano Espaillat (Democrat)

Event: January 6 United States Capitol attack

Entity: Donald Trump

Wiki-Context Predicted: Not Target \| **DCF Prediction**: Target (correct) | **Tweet**: Let us say enough. Enough.

Affiliation: Democrat
Event: Second impeachment of Donald Trump ended with not guilty
Paraphrase: The failure of the Democrats to impeach Donald Trump is a strong moment for our legislature which can get back to its work helping the American people. Today we've been able to tell the American people what we have known all along, that Donald Trump was not guilty of these charges.

Wiki-Context Predicted: Yes \| **DCF Prediction**: No (correct) |
| **Tweet**: #GeorgeFloyd #BlackLivesMatter #justiceinpolicing QT @OmarJimenez Former Minneapolis police officer Derek Chauvin is in the process of being released from the Hennepin County correctional facility his attorney tells us. He is one of the four officers charged in the death of George Floyd. He faces murder and manslaughter charges.
Author: Adriano Espaillat (Democrat)
Event: George Floyd protests

Entity: Derek Chauvin

Wiki-Context Predicted Sentiment: Positive \| **DCF Prediction**: Negative (correct) | **Tweet**: Lots of honking and screaming from balconies. Something must be going on.

Affiliation: Democrat
Event: Presidential election of 2020
Paraphrase: I'm sure that the people are celebrating the election results.

Wiki-Context Prediction: No \| **DCF Prediction**: Yes (correct) |

Table 5: Examples where baseline model fails but DCF works

Figure 2: An example of *Tweet Target Entity and Sentiment Annotation* GUI

Figure 3: An example of *Vague Text Disambiguation* GUI