DiBS: Differentiable Bayesian Structure Learning

Abstract

Bayesian structure learning allows inferring Bayesian network structure from data while reasoning about the epistemic uncertainty—a key element towards enabling active causal discovery and designing interventions in real world systems. In this work, we propose a general, fully *differentiable* framework for *Bayesian structure learning (DiBS)* that operates in the continuous space of a latent probabilistic graph representation. Building on recent advances in variational inference, we use DiBS to devise an efficient method for approximating posteriors over structural models. Contrary to existing work, DiBS is agnostic to the form of the local conditional distributions and allows for joint posterior inference of both the graph structure and the conditional distribution parameters. This makes our method directly applicable to posterior inference of nonstandard Bayesian network models, e.g., with nonlinear dependencies encoded by neural networks. In evaluations on simulated and real-world data, DiBS significantly outperforms related approaches to joint posterior inference.

1 Introduction

Discovering the statistical and causal dependencies that underlie the variables of a data-generating system is of central scientific interest. Bayesian networks (BNs) [1] and structural equation models are commonly used for this purpose [2–7]. Structure learning, the task of learning a BN from observations of its variables, is well-studied, but computationally very challenging due to the combinatorially large number of candidate graphs and the constraint of graph acyclicity.

While structure learning methods arrive at a single plausible graph or its Markov equivalence class (MEC), e.g., [8–11], *Bayesian structure learning* aims to infer a full posterior distribution over BNs given the observations. A distribution over structures allows quantifying the epistemic uncertainty and the degree of confidence in any given BN model, e.g., when the amount of data is small. Most importantly, downstream tasks such as experimental design and active learning rely on a posterior distribution over BNs to quantify the information gain from specific interventions and to uncover the causal structure in a small number of experiments [12–16].

A key challenge in Bayesian structure learning is working with a posterior over BNs—a distribution over the joint space of (discrete) directed acyclic graphs and (continuous) conditional distribution parameters. Most of the practically viable approaches to Bayesian structure learning revolve around Markov chain Monte Carlo (MCMC) sampling in combinatorial spaces and bootstrapping of classical score and constraint-based structure learning methods, e.g., in causal discovery [12–16]. However, to remain tractable while marginalizing out the parameters, these methods typically require a closed form for the marginal likelihood of the observations given the graph. This limits inference to simple and by now well-studied linear Gaussian and Categorical BN models [17–19] and makes it difficult to infer more expressive BNs that, e.g., model nonlinear relationships among the variables. Due to the discrete nature of these approaches, recent advances in approximate inference and gradient-based optimization could not yet be translated into similar performance improvements in Bayesian structure learning.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

In this work, we propose a novel, *fully differentiable framework for Bayesian structure learning* that operates in the continuous space of a latent probabilistic graph representation. Contrary to existing work, our formulation is agnostic to the distributional form of the BN and allows for inference of the joint posterior of both the conditional distribution parameters and the graph structure. This makes our approach directly applicable to nonstandard BN models where neither the marginal likelihood nor the maximum likelihood parameter estimate have a closed form. We instantiate our framework with the particle variational inference method of Liu and Wang [20] and present a general purpose method for approximate Bayesian structure learning. In our experiments on synthetic and real-world data, our method outperforms all alternative approaches to joint posterior inference of graphs and parameters and when modeling nonlinear interactions among the variables, often by a significant margin. This allows us to narrow down plausible causal graphs with greater precision and make better predictions under interventions—an important stepping stone towards active causal discovery.

2 Background

Bayesian networks   A Bayesian network $(\mathbf{G}, \mathbf{\Theta})$ models the joint density $p(\mathbf{x})$ of a set of d variables $\mathbf{x} = x_{1:d}$ using (1) a directed acyclic graph (DAG) $\mathbf{G}$ encoding the conditional independencies of $\mathbf{x}$ and (2) parameters $\mathbf{\Theta}$ defining the local conditional distributions of each variable given its parents in the DAG. When modeling $p(\mathbf{x})$ using a BN, each variable is assumed to be independent of its non-descendants given its parents, thus allowing for a compact factorization of the joint $p(\mathbf{x} \,|\, \mathbf{G}, \mathbf{\Theta})$ into a product of local conditional distributions for each variable and its parents in $\mathbf{G}$.

Bayesian inference of BNs   Given independent observations $\mathcal{D} = \{\mathbf{x}^{(1)}, \ldots, \mathbf{x}^{(N)}\}$, we consider the task of inferring a *full posterior* density over Bayesian networks that model the observations. Following Friedman and Koller [21], given a prior distribution over DAGs $p(\mathbf{G})$ and a prior over BN parameters $p(\mathbf{\Theta} \,|\, \mathbf{G})$, Bayes' Theorem yields the marginal and joint posterior distributions

$$p(\mathbf{G} \,|\, \mathcal{D}) \propto p(\mathbf{G})p(\mathcal{D} \,|\, \mathbf{G}) \,, \tag{1}$$

$$p(\mathbf{G}, \mathbf{\Theta} \,|\, \mathcal{D}) \propto p(\mathbf{G})p(\mathbf{\Theta} \,|\, \mathbf{G})p(\mathcal{D} \,|\, \mathbf{G}, \mathbf{\Theta}) \tag{2}$$

where $p(\mathcal{D} \,|\, \mathbf{G}) = \int p(\mathbf{\Theta} \,|\, \mathbf{G})p(\mathcal{D} \,|\, \mathbf{G}, \mathbf{\Theta})d\mathbf{\Theta}$ is the marginal likelihood. Thus, $p(\mathbf{G} \,|\, \mathcal{D})$ in (1) is only tractable in special conjugate cases where the integral over $\mathbf{\Theta}$ can be computed in closed form. The Bayesian formalism allows us to compute expectations of the form

$$\mathbb{E}_{\mathbf{G} \,|\, \mathcal{D}}\Big[f(\mathbf{G})\Big] \qquad \text{or} \qquad \mathbb{E}_{\mathbf{G}, \mathbf{\Theta} \,|\, \mathcal{D}}\Big[f(\mathbf{G}, \mathbf{\Theta})\Big] \tag{3}$$

for any function f of interest. For instance, to perform Bayesian model averaging, we would use $f(\mathbf{G}) = p(\mathbf{x} \,|\, \mathbf{G})$ or $f(\mathbf{G}, \mathbf{\Theta}) = p(\mathbf{x} \,|\, \mathbf{G}, \mathbf{\Theta})$, respectively [22, 23]. In active learning of causal BN structures, a commonly used f is the expected decrease in entropy of $\mathbf{G}$ after an intervention [12–14, 16]. Inferring either posterior is computationally challenging because there are $\mathcal{O}(d!2^{\binom{d}{2}})$ possible DAGs with d nodes [24]. Thus, computing the normalization constant $p(\mathcal{D})$ is generally intractable.

Continuous characterization of acyclic graphs   Orthogonal to the work on Bayesian inference, Zheng et al. [11] have recently proposed a differentiable characterization of acyclic graphs for structure learning. In this work, we adopt the formulation of Yu et al. [25], who show that a graph with adjacency matrix $\mathbf{G} \in \{0, 1\}^{d \times d}$ does not have any cycles if and only if $h(\mathbf{G}) = 0$, where

$$h(\mathbf{G}) := \text{tr}\left[(\mathbf{I} + \tfrac{1}{d}\mathbf{G})^d\right] - d \,. \tag{4}$$

If $h(\mathbf{G}) > 0$, the function can be interpreted as quantifying the *cyclicity* or *non-DAG-ness* of $\mathbf{G}$. Follow-up work has leveraged this insight to model nonlinear relationships [25–28], time-series data [29], in the context of generative modeling [30, 31], for causal inference [32], and contributed to its theoretical understanding [33, 34]. So far, a connection to Bayesian structure learning has been missing.

3 Related Work

The existing literature on Bayesian Structure Learning predominantly focuses on inferring the marginal graph posterior $p(\mathbf{G} \,|\, \mathcal{D})$. Since this requires $p(\mathcal{D} \,|\, \mathbf{G})$ to be tractable, inference is mostly limited to BNs with linear Gaussian or Categorical conditional distributions [17–19]. By contrast, the

82 formulation we introduce overcomes this fundamental restriction by allowing for joint inference of the
83 graph and the parameters, thereby facilitating the active (causal) discovery of more expressive BNs.

84 **MCMC** Sampling from the posterior over graphs is the most general approach to approximate
85 Bayesian structure learning. Structure MCMC (MC^3) [35, 36] performs Metropolis-Hastings in the
86 space of DAGs by changing one edge at a time. Several works try to remedy its poor mixing behavior
87 [37–39]. Alternatively, order MCMC draws samples in the smaller but still exponential space of node
88 orders, which typically requires a hard limit on the maximum parent set size [21]. Attempts to correct
89 for its unintended structural bias are themselves NP-hard to compute and/or limit the parent size
90 [37, 40]. By performing variational inference in a continuous latent space, the method we propose
91 circumvents such mixing issues and parent size limitations.

92 **Bootstrapping** The nonparametric DAG bootstrap [41] performs model averaging by bootstrap-
93 ping $\mathcal{D}$, where each resampled data set is used to learn a single graph, e.g., using the GES or PC
94 algorithms [8, 9]. The obtained set of graphs approximates the posterior by weighting each unique
95 graph by its unnormalized posterior probability. In simple cases, a closed-form maximum likelihood
96 parameter estimate may be used to approximate the joint posterior [16], but only if $p(\mathcal{D} \,|\, \mathbf{G})$ is
97 tractable in the first place.

98 **Exact methods** A few notable exceptions use dynamic programming to achieve exact marginal
99 inference in time $O(d2^d)$, which is only feasible for $d \leq 20$ nodes [42, 43]. In special cases, e.g., for
100 tree structures or known node orderings, exact inference can be performed more efficiently [44, 45].

4 A Fully Differentiable Framework for Bayesian Structure Learning

4.1 General Approach

103 With the goal of moving beyond the restrictive conjugate setups
104 required by most discrete sampling methods for Bayesian structure
105 learning, we propose to transfer the posterior inference task into
106 the latent space of a probabilistic graph representation. Our result-
107 ing framework is *consistent* with the original Bayesian structure
108 learning task in (3), enforces the *acyclicity* of $\mathbf{G}$ via the latent
109 space prior, and provides the *score* of the continuous latent pos-
110 terior, thus making general purpose inference methods applicable
111 off-the-shelf.

Figure 1: Generative model
of BNs with latent variable $\mathbf{Z}$.
This formulation generalizes the
standard Bayesian setup in (2)
where only $\mathbf{G}$, $\boldsymbol{\Theta}$, and $\mathbf{x}$ are
modeled explicitly.

112 Without loss of generality, we assume that there exists a latent
113 variable $\mathbf{Z}$ that models the generative process of $\mathbf{G}$. Specifically,
114 the default generative model described in Section 2 is generalized
115 into the following factorization:

$$p(\mathbf{Z}, \mathbf{G}, \boldsymbol{\Theta}, \mathcal{D}) = p(\mathbf{Z})p(\mathbf{G} \,|\, \mathbf{Z})p(\boldsymbol{\Theta} \,|\, \mathbf{G})p(\mathcal{D} \,|\, \mathbf{G}, \boldsymbol{\Theta}) \qquad (5)$$

116 Figure 1 displays the corresponding graphical model. The following insight provides us with an
117 equivalence between the expectation we ultimately want to approximate and an expectation over the
118 posterior of the continuous variable $\mathbf{Z}$:

119 **Proposition 1** (Latent posterior expectation). *Under the generative model in (5), it holds that*

120 *(a)* $\mathbb{E}_{\mathbf{G} \,|\, \mathcal{D}}\Big[f(\mathbf{G})\Big] = \mathbb{E}_{\mathbf{Z} \,|\, \mathcal{D}}\left[\dfrac{\mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[f(\mathbf{G})p(\mathcal{D} \,|\, \mathbf{G})\right]}{\mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[p(\mathcal{D} \,|\, \mathbf{G})\right]}\right]$, *and*

121 *(b)* $\mathbb{E}_{\mathbf{G}, \boldsymbol{\Theta} \,|\, \mathcal{D}}\Big[f(\mathbf{G}, \boldsymbol{\Theta})\Big] = \mathbb{E}_{\mathbf{Z}, \boldsymbol{\Theta} \,|\, \mathcal{D}}\left[\dfrac{\mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[f(\mathbf{G}, \boldsymbol{\Theta})p(\boldsymbol{\Theta} \,|\, \mathbf{G})p(\mathcal{D} \,|\, \mathbf{G}, \boldsymbol{\Theta})\right]}{\mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[p(\boldsymbol{\Theta} \,|\, \mathbf{G})p(\mathcal{D} \,|\, \mathbf{G}, \boldsymbol{\Theta})\right]}\right]$.

122 A proof is provided in Appendix A.1. Rather than approximating $p(\mathbf{G} \,|\, \mathcal{D})$ or $p(\mathbf{G}, \boldsymbol{\Theta} \,|\, \mathcal{D})$, our
123 goal will be to infer $p(\mathbf{Z} \,|\, \mathcal{D})$ or $p(\mathbf{Z}, \boldsymbol{\Theta} \,|\, \mathcal{D})$ instead, which by Proposition 1 allows us to compute
124 expectations of the form in (3). In the following, we first discuss how to define the two factors
125 $p(\mathbf{G} \,|\, \mathbf{Z})$ and $p(\mathbf{Z})$ in a way that models only acyclic graphs. Then, we provide the details necessary
126 to perform black box inference of the posteriors of the continuous latent variable $\mathbf{Z}$.

4.2 Representing DAGs in a Continuous Latent Space

Generative graph model We consider the latent variable $\mathbf{Z}$ to be the collection of two embedding matrices $\mathbf{U}, \mathbf{V} \in \mathbb{R}^{k \times d}$, i.e., $\mathbf{Z} = [\mathbf{U}, \mathbf{V}]$. Inspired by Kipf and Welling [46], the generative model of the graph adjacency matrix $\mathbf{G} \in \{0, 1\}^{d \times d}$ is given by an inner product between the latent variables $\mathbf{Z}$:

$$p_\alpha(\mathbf{G} \,|\, \mathbf{Z}) = \prod_{i=1}^{d} \prod_{j \neq i}^{d} p_\alpha(g_{ij} \,|\, \mathbf{u}_i, \mathbf{v}_j) \quad \text{with } p_\alpha(g_{ij} = 1 \,|\, \mathbf{u}_i, \mathbf{v}_j) = \sigma_\alpha(\mathbf{u}_i^\top \mathbf{v}_j) \tag{6}$$

where $\sigma_\alpha(x) = 1/(1 + \exp(-\alpha x))$ denotes the sigmoid function with temperature parameter α. We denote the corresponding matrix of edge probabilities in $\mathbf{G}$ given $\mathbf{Z}$ by $\mathbf{G}_\alpha(\mathbf{Z}) \in [0, 1]^{d \times d}$ with

$$\mathbf{G}_\alpha(\mathbf{Z})_{ij} := p_\alpha(g_{ij} = 1 \,|\, \mathbf{U}, \mathbf{V}) . \tag{7}$$

Since we model acyclic graphs, which do not contain self-loops, we set the diagonal elements of $\mathbf{G}_\alpha(\mathbf{Z})$ to be zero. The latent dimensionality k trades off the complexity of the variable interactions with tractability during inference. For $k \geq d$, the matrix of edge probabilities $\mathbf{G}_\alpha(\mathbf{Z})$ is not constrained in rank, and the generative model in (6) can represent any adjacency matrix without self-loops. That said, the size of the latent representation $\mathbf{Z}$ only grows $\mathcal{O}(d \cdot k)$ and, in principle, k can be chosen independently of d. Note that the formulation in (6) models *directed* graphs since $\sigma_\alpha(\mathbf{u}_i^\top \mathbf{v}_j) \neq \sigma_\alpha(\mathbf{u}_j^\top \mathbf{v}_i)$. We can even interpret $\mathbf{u}_i$ and $\mathbf{v}_i$ as node embeddings that may encode more information than mere edge probabilities, e.g., for graph neural networks. The fact that $p_\alpha(\mathbf{G} \,|\, \mathbf{Z})$ is invariant to orthogonal transformations of $\mathbf{U}$ and $\mathbf{V}$ is not an issue in practice.

Acyclicity via the latent prior distribution A major constraint in learning BNs is the acyclicity of $\mathbf{G}$. With the latent graph model $p_\alpha(\mathbf{G} \,|\, \mathbf{Z})$ in place, we design the prior $p_\beta(\mathbf{Z})$ to act as a soft constraint enforcing that only DAGs are modeled. Specifically, we define the prior of $\mathbf{Z}$ as the product of independent Gaussians with a Gibbs distribution that penalizes the *expected cyclicity* of $\mathbf{G}$ given $\mathbf{Z}$:

$$p_\beta(\mathbf{Z}) \propto \exp\left(-\beta \, \mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[h(\mathbf{G})\right]\right) \prod_{ijk} \mathcal{N}(z_{ijk}; 0, \sigma_z^2) \tag{8}$$

Here, $h(\cdot)$ is the DAG constraint function given in (4) and β is a temperature parameter that controls how strongly the acyclicity is enforced. As $\beta \to \infty$, the support of $p_\beta(\mathbf{Z})$ reduces to all $\mathbf{Z}$ that only model valid DAGs. The Gaussian component ensures that the norm of $\mathbf{Z}$ is well-behaved. Traditional graph priors of the form $p(\mathbf{G}) \propto f(\mathbf{G})$ that induce, e.g., sparsity of $\mathbf{G}$, can be flexibly incorporated into $p_\beta(\mathbf{Z})$ by means of an additional factor involving $f(\mathbf{G}_\alpha(\mathbf{Z}))$ or $\mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}[f(\mathbf{G})]$.

4.3 Black Box Bayesian Inference

The extended generative model in (5) not only allows us to incorporate the notoriously difficult acyclicity constraint into the Bayesian framework. By rephrasing the posteriors $p(\mathbf{G} \,|\, \mathcal{D})$ and $p(\mathbf{G}, \boldsymbol{\Theta} \,|\, \mathcal{D})$ in terms of $p(\mathbf{Z} \,|\, D)$ and $p(\mathbf{Z}, \boldsymbol{\Theta} \,|\, D)$, respectively, it also makes Bayesian structure learning amenable to variational inference techniques that operate in continuous space and rely on the gradient of the unnormalized log posterior, also known as the *score*. The following result provides us with the score of both latent posteriors. Detailed derivations can be found in Appendix A.2.

Proposition 2 (Latent posterior score). *Under the generative graph model defined in (5), the gradient of the log posterior density of $\mathbf{Z}$ is given by*

$$(a) \qquad \nabla_{\mathbf{Z}} \log p(\mathbf{Z} \,|\, \mathcal{D}) = \nabla_{\mathbf{Z}} \log p(\mathbf{Z}) + \frac{\nabla_{\mathbf{Z}} \, \mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[p(\mathcal{D} \,|\, \mathbf{G})\right]}{\mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[p(\mathcal{D} \,|\, \mathbf{G})\right]} \tag{9}$$

which is relevant when the marginal likelihood $p(\mathcal{D} \,|\, \mathbf{G})$ can be computed efficiently. In the general case, when inferring the joint posterior of $\mathbf{Z}$ and $\boldsymbol{\Theta}$, the gradients of the log posterior are given by

$$(b) \qquad \nabla_{\mathbf{Z}} \log p(\mathbf{Z}, \boldsymbol{\Theta} \,|\, \mathcal{D}) = \nabla_{\mathbf{Z}} \log p(\mathbf{Z}) + \frac{\nabla_{\mathbf{Z}} \, \mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[p(\boldsymbol{\Theta}, \mathcal{D} \,|\, \mathbf{G})\right]}{\mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[p(\boldsymbol{\Theta}, \mathcal{D} \,|\, \mathbf{G})\right]} \tag{10}$$

$$(c) \qquad \nabla_{\boldsymbol{\Theta}} \log p(\mathbf{Z}, \boldsymbol{\Theta} \,|\, \mathcal{D}) = \frac{\mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[\nabla_{\boldsymbol{\Theta}} p(\boldsymbol{\Theta}, \mathcal{D} \,|\, \mathbf{G})\right]}{\mathbb{E}_{\mathbf{G} \,|\, \mathbf{Z}}\left[p(\boldsymbol{\Theta}, \mathcal{D} \,|\, \mathbf{G})\right]} \tag{11}$$

where $p(\boldsymbol{\Theta}, \mathcal{D} \,|\, \mathbf{G}) = p(\boldsymbol{\Theta} \,|\, \mathbf{G})p(\mathcal{D} \,|\, \mathbf{G}, \boldsymbol{\Theta})$, which is efficient to compute by construction.

The expectations have tractable Monte Carlo approximations because sampling from $p_\alpha(\mathbf{G} \mid \mathbf{Z})$ in (6) is simple and parallelizable. The gradient terms of the form $\nabla_\mathbf{Z} \mathbb{E}_{\mathbf{G} \mid \mathbf{Z}}[\,\cdot\,]$, which also appear inside $\nabla_\mathbf{Z} \log p_\beta(\mathbf{Z})$, can be estimated using two different techniques, depending on the BN model inferred.

Differentiable (marginal) likelihood   Using the Gumbel-softmax trick [47, 48], we can separate the randomness from $\mathbf{Z}$ when sampling from $p_\alpha(\mathbf{G} \mid \mathbf{Z})$ and obtain the following estimator:

$$\nabla_\mathbf{Z} \mathbb{E}_{\mathbf{G} \mid \mathbf{Z}}\big[p(\mathcal{D} \mid \mathbf{G})\big] \approx \mathbb{E}_\mathbf{L}\Big[\nabla_\mathbf{G}\, p(\mathcal{D} \mid \mathbf{G})\big|_{\mathbf{G}=\mathbf{G}_\tau(\mathbf{L},\mathbf{Z})} \cdot \nabla_\mathbf{Z}\, \mathbf{G}_\tau(\mathbf{L},\mathbf{Z})\Big] \tag{12}$$

where $\mathbf{L} \sim \text{Logistic}(0,1)^{d \times d}$ i.i.d.. The matrix-valued function $\mathbf{G}_\tau(\cdot)$ is defined elementwise as

$$\mathbf{G}_\tau(\mathbf{L},\mathbf{Z})_{ij} := \begin{cases} \sigma_\tau\left(l_{ij} + \alpha \mathbf{u}_i^\top \mathbf{v}_j\right) & \text{if } i \neq j \\ 0 & \text{if } i = j \end{cases} \tag{13}$$

The estimator also applies to $p(\mathbf{\Theta}, \mathcal{D} \mid \mathbf{G})$. However, the gradients $\nabla_\mathbf{G} p(\mathcal{D} \mid \mathbf{G})$ or $\nabla_\mathbf{G} p(\mathcal{D}, \mathbf{\Theta} \mid \mathbf{G})$, respectively, need to be well-defined and computable, which depends on the parameterization of the BN model we aim to infer. In case $p(\mathcal{D} \mid \mathbf{G})$ or $p(\mathbf{\Theta}, \mathcal{D} \mid \mathbf{G})$ is only defined for discrete $\mathbf{G}$, it is possible to evaluate $\nabla_\mathbf{G} p(\mathcal{D} \mid \mathbf{G})$ or $\nabla_\mathbf{G} p(\mathbf{\Theta}, \mathcal{D} \mid \mathbf{G})$ using hard Gumbel-max samples of $\mathbf{G}$ (i.e., with $\tau = \infty$) and a straight-through gradient estimator. Since the DAG constraint $h(\cdot)$ is differentiable, the Gumbel-softmax trick can always be applied inside $\nabla_\mathbf{Z} \log p_\beta(\mathbf{Z})$. In practice, we always use $\tau = 1$.

Non-differentiable (marginal) likelihood   In general, $\nabla_\mathbf{G} p(\mathcal{D} \mid \mathbf{G})$ or $\nabla_\mathbf{G} p(\mathcal{D}, \mathbf{\Theta} \mid \mathbf{G})$, depending on the inference task, might be not available or ill-defined. In this setting, the score function estimator provides us with a way to estimate the gradient we need [49]:

$$\nabla_\mathbf{Z} \mathbb{E}_{\mathbf{G} \mid \mathbf{Z}}\big[p(\mathcal{D} \mid \mathbf{G})\big] = \mathbb{E}_{\mathbf{G} \mid \mathbf{Z}}\Big[\big(p(\mathcal{D} \mid \mathbf{G}) - b\big)\, \nabla_\mathbf{Z} \log p_\alpha(\mathbf{G} \mid \mathbf{Z})\Big] \tag{14}$$

and again likewise for $p(\mathbf{\Theta}, \mathcal{D} \mid \mathbf{G})$ in place of $p(\mathcal{D} \mid \mathbf{G})$. Here, b is a constant with respect to $\mathbf{G}$ that can be used for variance reduction [50], and $\nabla_\mathbf{Z} \log p_\alpha(\mathbf{G} \mid \mathbf{Z})$ is trivial to compute. The derivations of both (12) and (14), alongside a more detailed discussion, can be found in Appendix B.

5   Particle Variational Inference for Structure Learning

In the previous section, we have proposed a *differentiable* formulation for *Bayesian structure learning (DiBS)* that is agnostic to the form of the local BN conditionals and, more importantly, translates learning discrete graph structures into an inference problem over the continuous variable $\mathbf{Z}$. In the following, we overcome the remaining challenge of inferring the intractable DiBS posteriors $p(\mathbf{Z} \mid \mathcal{D})$ and $p(\mathbf{Z}, \mathbf{\Theta} \mid \mathcal{D})$ by employing Stein variational gradient descent (SVGD) [20], a gradient-based and general purpose variational inference method. The resulting algorithm infers a particle approximation of the marginal or joint posterior density over BNs given observational data.

SVGD for posterior inference   Since Proposition 2 provides us with the gradient of the latent posterior score functions, we can apply SVGD off-the-shelf. SVGD minimizes the KL divergence to a target distribution by iteratively *transporting* a set of particles using a sequence of kernel-based transformation steps. Following this paradigm for DiBS, we iteratively update a fixed set $\{\mathbf{Z}^{(m)}\}_{m=1}^M$ or $\{\mathbf{Z}^{(m)}, \mathbf{\Theta}^{(m)}\}_{m=1}^M$ to approximate $p(\mathbf{Z} \mid \mathcal{D})$ or $p(\mathbf{Z}, \mathbf{\Theta} \mid \mathcal{D})$, respectively. If the BN model we aim to infer has a properly-defined likelihood gradient with respect to $\mathbf{G}$, we use the Gumbel-softmax estimator in (12) to approximate the posterior score. Otherwise, we resort to the score function estimator in (14). When inferring $p(\mathbf{Z}, \mathbf{\Theta} \mid \mathcal{D})$, we use a simple SE kernel in the SVGD iterations:

$$k\big((\mathbf{Z}, \mathbf{\Theta}), (\mathbf{Z}', \mathbf{\Theta}')\big) := \exp\left(-\frac{1}{\gamma_z}\|\mathbf{Z} - \mathbf{Z}'\|_2^2\right) + \exp\left(-\frac{1}{\gamma_\theta}\|\mathbf{\Theta} - \mathbf{\Theta}'\|_2^2\right) \tag{15}$$

with bandwidths γ_z, γ_θ. For inference of $p(\mathbf{Z} \mid \mathcal{D})$, we leave out the second term involving $\mathbf{\Theta}, \mathbf{\Theta}'$. While $\mathbf{Z}$ is invariant to orthogonal transformations, more elaborate kernels that are, e.g., invariant to such transforms empirically perform worse in our experiments.

Annealing α and β   The latent variable $\mathbf{Z}$ not only probabilistically models the graph $\mathbf{G}$, but can also be viewed as a continuous relaxation of $\mathbf{G}$, with α trading off smoothness with accuracy. As $\alpha \to \infty$, the sigmoid $\sigma_\alpha(\cdot)$ converges to the unit step function. Hence, as $\alpha \to \infty$ in the graph model $p_\alpha(\mathbf{G} \mid \mathbf{Z})$ in (6), the expectations in Proposition 1 simplify to:

$$\begin{aligned} \mathbb{E}_{\mathbf{G} \mid \mathcal{D}}\Big[f(\mathbf{G})\Big] &\to \mathbb{E}_{\mathbf{Z} \mid \mathcal{D}}\Big[f\big(\mathbf{G}_\infty(\mathbf{Z})\big)\Big] \\ \mathbb{E}_{\mathbf{G}, \mathbf{\Theta} \mid \mathcal{D}}\Big[f(\mathbf{G}, \mathbf{\Theta})\Big] &\to \mathbb{E}_{\mathbf{Z}, \mathbf{\Theta} \mid \mathcal{D}}\Big[f\big(\mathbf{G}_\infty(\mathbf{Z}), \mathbf{\Theta}\big)\Big] \end{aligned} \tag{16}$$

Algorithm 1 DiBS for $p(\mathbf{G} \,|\, \mathcal{D})$ using Stein variational gradient descent [20]

Input: Initial set of latent particles $\{\mathbf{Z}_0^{(m)}\}_{m=1}^M$, kernel $k(\cdot, \cdot)$, schedules for $\alpha(t), \beta(t)$, and stepsize $\eta(t)$
Output: Set of discrete graph particles $\{\mathbf{G}^{(m)}\}_{m=1}^M$ approximating $p(\mathbf{G} \,|\, \mathcal{D})$

1: Incorporate prior belief of $p(\mathbf{G})$ into $p_\beta(\mathbf{Z})$ ▷ See Section 4.2
2: **for** iteration $t = 0$ to $T - 1$ **do**
3:     Estimate score $\nabla_{\mathbf{Z}} \log p(\mathbf{Z} \,|\, \mathcal{D})$ given in (9) for each $\mathbf{Z}_t^{(m)}$ ▷ See (12) and (14)
4:     **for** particle $m = 1$ to M **do**
5:        $\mathbf{Z}_{t+1}^{(m)} \leftarrow \mathbf{Z}_t^{(m)} + \eta(t) \, \phi_t(\mathbf{Z}_t^{(m)})$ ▷ SVGD transport step

     where $\phi_t(\cdot) := \dfrac{1}{M} \sum\limits_{k=1}^M \left[k(\mathbf{Z}_t^{(k)}, \cdot) \, \nabla_{\mathbf{Z}_t^{(k)}} \log p(\mathbf{Z}_t^{(k)} \,|\, \mathcal{D}) + \nabla_{\mathbf{Z}_t^{(k)}} k(\mathbf{Z}_t^{(k)}, \cdot) \right]$

6: **return** $\{\mathbf{G}_\infty(\mathbf{Z}_T^{(m)})\}_{m=1}^M$ ▷ See (16) and (17)
---

where $\mathbf{G}_\infty(\mathbf{Z})$ denotes the single limiting graph implied b $\mathbf{Z} = [\mathbf{U}, \mathbf{V}]$ and is defined as

$$\mathbf{G}_\infty(\mathbf{Z})_{ij} := \begin{cases} 1 & \text{if } \mathbf{u}_i^\top \mathbf{v}_j > 0 \text{ and } i \neq j \\ 0 & \text{otherwise} \end{cases} \tag{17}$$

See Appendix A.3. In this case, $p_\alpha(\mathbf{G} \,|\, \mathbf{Z})$ converges to representing only a *single graph*. To be able to invoke this simplification, we anneal $\alpha \to \infty$ over the iterations of SVGD and, upon termination, convert the latent variables $\mathbf{Z}$ to the single discrete $\mathbf{G}_\infty(\mathbf{Z})$. Furthermore, we similarly let $\beta \to \infty$ in the latent prior $p_\beta(\mathbf{Z})$ over the iterations to enforce that the latent representation of $\mathbf{G}$ only models DAGs. By Equation (16), the resulting DAGs form a consistent particle approximation of $p(\mathbf{G} \,|\, \mathcal{D})$ or $p(\mathbf{G}, \mathbf{\Theta} \,|\, \mathcal{D})$, respectively. Algorithm 1 summarizes DiBS instantiated with SVGD for inference of $p(\mathbf{G} \,|\, \mathcal{D})$. The general case of inferring $p(\mathbf{G}, \mathbf{\Theta} \,|\, \mathcal{D})$ is given in Algorithm 2 of Appendix C.

Single-particle approximation   SVGD reduces to regular gradient ascent for the maximum a posteriori estimate when transporting only a *single* particle [20]. In this special case, DiBS with SVGD recovers some of the existing continuous structure learning methods: gradient ascent on a linear Gaussian likelihood solves an optimization problem similar to NOTEARS [11]. The cyclicity penalizer acts analogously. However, not only does DiBS automatically turn into a full Bayesian approach when using more particles, it is also not limited to settings such as linear Gaussian conditionals, where the adjacency matrix $\mathbf{G}$ and the parameters $\mathbf{\Theta}$ can be modeled together by a weighted adjacency matrix.

Weighted particle mixture   In high dimensional settings, it may be beneficial to move beyond a uniform weighting of the inferred particles of BN models to approximate $p(\mathbf{G} \,|\, \mathcal{D})$ or $p(\mathbf{G}, \mathbf{\Theta} \,|\, \mathcal{D})$. We consider a particle mixture that weights each particle by its unnormalized posterior probability $p(\mathbf{G}, \mathcal{D})$ or $p(\mathbf{G}, \mathbf{\Theta}, \mathcal{D})$, respectively, under the BN model. In our experiments, DiBS and its instantiation with SVGD are used interchangeably, and DiBS+ denotes the weighted particle mixture.

6 Evaluation on Synthetic Data

6.1 Experimental Setup

Synthetic data   We compare DiBS to a set of related methods in marginal and joint posterior inference of synthetic linear and nonlinear Gaussian BNs. Our setup follows [11, 25, 28, 51], who consider inferring BNs with Erdős-Rényi and scale-free random structures [52, 53]. For each graph, here with $d \in \{20, 50\}$ nodes and $2d$ edges in expectation, we sample a set of ground truth parameters and then generate training, held-out, and interventional data sets. In all settings, we use $N = 100$ observations for inference, emulating the use case of Bayesian structure learning where the uncertainty about the graph structure is significant. Gaussian BNs are defined in Appendix D.1.

Graph priors   For Erdős-Rényi graphs, all methods use the prior $p(\mathbf{G}) \propto q^{\|\mathbf{G}\|_1} (1-q)^{\binom{d}{2} - \|\mathbf{G}\|_1}$, capturing that each edge exists independently w.p. q [52]. For scale-free graphs, we define the prior $p(\mathbf{G}) \propto \prod_{i=1}^d (1 + \|\mathbf{G}_i^\top\|_1)^{-3}$, analogous to their power law degree distribution $p(\deg) \sim \deg^{-3}$ [53]. Here, $\mathbf{G}_i^\top$ is the i-th column of the adjacency matrix. DiBS implements either prior by using the corresponding term above as an additional factor in $p(\mathbf{Z})$ with $\mathbf{G} := \mathbf{G}_\alpha(\mathbf{Z})$ (see Section 4.2).

Metrics   Since neither density nor samples of the ground truth posteriors are available for BNs of $d \in \{20, 50\}$ variables, we follow the evaluation metrics used by previous work. We define the

Figure 2: Marginal posterior inference of 20-node linear Gaussian BNs using the BGe marginal likelihood. Higher scores on AUROC and lower scores on $\mathbb{E}$-SHD, neg. MLL, neg. I-MLL are preferred. DiBS+ performs competitively across all metrics, in particular $\mathbb{E}$-SHD and neg. (I-)MLL.

expected structural Hamming distance to the ground truth graph $\mathbf{G}^*$ under the inferred posterior as

$$\mathbb{E}\text{-SHD}(p, \mathbf{G}^*) := \sum_{\mathbf{G}} p(\mathbf{G} \,|\, \mathcal{D}) \cdot \text{SHD}(\mathbf{G}, \mathbf{G}^*) \tag{18}$$

where $\text{SHD}(\mathbf{G}, \mathbf{G}^*)$ counts the edge changes that separate the essential graphs representing the MECs of $\mathbf{G}$ and $\mathbf{G}^*$ [10, 54]. In addition, we follow Friedman and Koller [21] and Ellis and Wong [40] and compute the *area under the receiver operating characteristic curve (AUROC)* [55] for pairwise edge predictions when varying the confidence threshold under the inferred marginal $p(g_{ij} = 1 \,|\, \mathcal{D})$. Finally, following Murphy [12], we also evaluate the ability to predict future observations by computing the average *negative (marginal) log likelihood* on 100 held-out observations $\mathcal{D}^{\text{test}}$:

$$\text{neg. LL}(p, \mathcal{D}^{\text{test}}) := - \sum_{\mathbf{G}, \mathbf{\Theta}} p(\mathbf{G}, \mathbf{\Theta} \,|\, \mathcal{D}) \cdot \log p(\mathcal{D}^{\text{test}} \,|\, \mathbf{G}, \mathbf{\Theta}) \tag{19}$$

When inferring $p(\mathbf{G} \,|\, \mathcal{D})$, the corresponding neg. MLL metric instead uses $p(\mathcal{D}^{\text{test}} \,|\, \mathbf{G})$. Analogously, we also compute the *interventional* log likelihoods I-LL and I-MLL, a relevant metric in causal inference [12, 14]. Here, an interventional data set $(\mathcal{D}^{\text{int}}, \mathcal{I})$ is instead used to compute $p(\mathcal{D}^{\text{int}} \,|\, \mathbf{G}, \mathbf{\Theta}, \mathcal{I})$ and $p(\mathcal{D}^{\text{int}} \,|\, \mathbf{G}, \mathcal{I})$ in (19), respectively. For this, we randomly select 10% of the variables and clamp them to zero in the data-generating process. Scores are the average of 10 interventional data sets. All of the reported metrics in this section are aggregated for inference of 30 random synthetic BNs.

In the remainder, DiBS is always run for 3,000 iterations and with $k = d$ for inference of d-variable BNs, which leaves the matrix of edge probabilities unconstrained in rank. We discard a DiBS particle in the rare case that a returned graph is cyclic. Specific hyperparameters are provided in Appendix D.2.

6.2 Linear Gaussian Bayesian Networks

Marginal posterior inference For linear Gaussian BNs, we first evaluate the classical setting of inferring the marginal posterior $p(\mathbf{G} \,|\, \mathcal{D})$ since $p(\mathcal{D} \,|\, \mathbf{G})$ can be computed in closed form. To this end, we employ the commonly used Bayesian Gaussian Equivalent (BGe) marginal likelihood, which scores Markov equivalent structures equally [17, 18]. The form of the BGe score requires DiBS to use the score function estimator in (14).

We compare DiBS with the nonparametric DAG bootstrap [41] using the constraint-based PC [9] and the score-based GES [8] algorithms (BPC and BGES). For MCMC, we only consider structure MCMC (MC^3) [36] as a comparison. Order MCMC or hybrid DP approaches bound the number of parents and thus often exclude the ground truth graph a priori, especially for scale-free BN structures. Burn-in and thinning for MC^3 are chosen to make the runtime comparable with DiBS. The DAG bootstrap methods typically run significantly faster. Further details are provided in Appendix D.3. In the remainder of the paper, each method uses 30 samples to approximate the posterior over BNs.

Figure 2 summarizes the results for 30 randomly generated BNs with $d = 20$ nodes. We find that DiBS+ performs well compared to the other methods, all of which were specifically developed for the marginal inference scenario evaluated here. DiBS+ appears to be preferable to DiBS.

Figure 3: Joint posterior inference of graphs and parameters of linear Gaussian networks with $d = 20$ nodes. DiBS+ performs best across all of the metrics. BGES*, the next-best alternative, yields substantially worse performance in $\mathbb{E}$-SHD, i.e., in recovering the overall graph structure and MEC. Recall that higher AUROC and lower $\mathbb{E}$-SHD, neg. LL, and neg. I-LL scores are preferable.

Joint posterior inference When inferring the joint posterior $p(\mathbf{G}, \mathbf{\Theta} \,|\, \mathcal{D})$, we can employ a more explicit representation of linear Gaussian BNs, where the conditional distribution parameters are standard Gaussian, and DiBS can employ the Gumbel-softmax estimator in (12) (see Appendix D.1). To provide a comparison with DiBS in the absence of a comparable MCMC method, we propose two variants of MC³ as baselines. Metropolis-Hastings MC³ (M-MC³) jointly samples parameters and structures, and Metropolis-within-Gibbs MC³ (G-MC³) alternates in proposing structure and parameters [56]. Moreover, we extend the bootstrap methods by taking the maximum likelihood estimate [57] as the posterior parameter sample for a given graph inferred using the BGe score (BPC* and BGES*), an approach taken in, e.g., causal BN learning [16].

Figure 3 shows the results for $d = 20$ nodes, where $\mathbb{E}$-SHD and AUROC are computed by empirically marginalizing out the parameters. We find that DiBS+ is the only considered method that performs well across all of the metrics, often outperforming the baselines by a significant margin. As for marginal posterior inference of linear Gaussian BNs, DiBS+ performs slightly better than DiBS.

6.3 Nonlinear Gaussian Bayesian Networks

We also consider joint inference of *nonlinear* Gaussian BNs where the mean of each local conditional Gaussian is parameterized by a 2-layer dense neural network with five hidden nodes and ReLU activation functions (see Appendix D.1). Since the marginal likelihood does not have a closed form, we are unable to use BPC* and BGES* as a means of comparison. Figure 4 displays the results for $d = 20$ variables, where a given BN model has $|\mathbf{\Theta}| = 2{,}220$ weights and biases. Analogous to joint inference of linear Gaussian BNs, DiBS and DiBS+ outperform the MCMC baselines across the considered metrics. To the best of our knowledge, this is the first time that such nonlinear Gaussian BN models have been inferred under the Bayesian paradigm, which opens up exciting avenues in the active learning of more sophisticated causal structures.

Appendix D.5 complements Sections 6.2 and 6.3 with results for $d = 50$ variables, where DiBS+ likewise performs particularly favorably when jointly inferring $p(\mathbf{G}, \mathbf{\Theta} \,|\, \mathcal{D})$.

6.4 DiBS with SVGD: Additional Analyses and Ablation Studies

Having compared DiBS and its instantiation with SVGD to several existing approaches, we devote Appendix E to empirically analyzing some of the algorithm's properties. One of our key results is that, all other things held equal, substituting our inner product model in (6) with $p_\sigma(g_{ij} = 1 \,|\, \mathbf{Z}) = \sigma_\alpha(z_{ij})$, where single *scalars* encode the edge probabilities, results in significantly worse evaluation metrics.

We additionally study the uncertainty quantification in (non)identifiable edge structures and show the effects of reducing the latent dimensionality k or the number of iterations T. Our findings suggest that reducing either hyperparameter still allows for competitive posterior approximations and enables trading off posterior inference quality with computational efficiency, e.g., in large-scale applications.

Figure 4: Joint posterior inference of nonlinear Gaussian BNs with $d = 20$ nodes. Here, the mean of the local conditional distribution of each node is parameterized by a 2-layer neural network with five hidden nodes. DiBS and DiBS+ perform favorably across the board, particularly in the graph metrics.

7 Application: Inferring Protein Signaling Networks From Cell Data

A widely used benchmark in structure learning is the proteomics data set by Sachs et al. [3]. The data contain $N = 7,466$ continuous measurements of $d = 11$ proteins involved in human immune system cells as well as an established causal network of their signaling interactions.

We infer both linear and nonlinear Gaussian BNs with Erdős-Rényi graph priors exactly as in Section 6. The AUROC results in Table 1 indicate that the posterior by DiBS under the BGe model provides the most calibrated edge confidence scores. Not penalizing model complexity as much, the marginal BGe posterior of DiBS (DiBS+) averages a high expected number of 39.0 (35.0) edges, compared to 12.7 (14.2) and 12.6 (14.2) for its joint posteriors over linear and nonlinear BNs, respectively. Appendix F provides further details and analyses on this matter. The $\mathbb{E}$-SHD scores show that, among all the methods, DiBS is closest in structure to the consensus network when performing joint inference with nonlinear Gaussian BNs. This further highlights the need for nonlinear conditionals and joint inference of the graph and parameters in complex real-world settings.

Table 1: Inference of protein signaling pathways with Gaussian BNs. Metrics are the mean $\pm$ SD of 30 random restarts.

		$\mathbb{E}$-**SHD**	**AUROC**
†	MC^3	34.0 ± 0.7	0.616 ± 0.027
	BPC	25.5 ± 2.3	0.566 ± 0.020
	BGES	33.7 ± 1.7	0.641 ± 0.030
	DiBS	37.4 ± 0.5	$\mathbf{0.647 \pm 0.047}$
	DiBS+	34.7 ± 1.5	0.629 ± 0.045
§	M-MC^3	37.3 ± 3.5	0.551 ± 0.078
	G-MC^3	30.5 ± 3.2	0.527 ± 0.067
	DiBS	23.4 ± 0.5	0.598 ± 0.052
	DiBS+	22.9 ± 2.7	0.557 ± 0.052
¶	M-MC^3	25.2 ± 3.0	0.526 ± 0.084
	G-MC^3	35.1 ± 3.2	0.540 ± 0.080
	DiBS	$\mathbf{22.6 \pm 0.5}$	0.577 ± 0.039
	DiBS+	22.8 ± 1.9	0.535 ± 0.041

† Linear Gaussian BN; graph only via BGe marginal lik.
§ Linear Gaussian BN; graph and parameters jointly
¶ Nonlinear Gaussian BN; graph and parameters jointly

8 Conclusion

We have presented a general, fully differentiable approach to inference of posterior distributions over BNs. Our framework is based on a continuous latent representation of DAGs, whose posterior can be equivalently inferred—without loss of generality and using existing black box inference methods. While we have used SVGD [20] for this purpose, our general approach could also be instantiated with, e.g., gradient-based sampling methods [58, 59]. This may improve upon the asymptotic runtime of DiBS with SVGD, which scales quadratically in the number of sampled particles. We expect that our end-to-end approach can be extended to handle missing and interventional data as well as to amortized contexts, where rich unstructured data is available.

Broader impact Our work is relevant to any scientific discipline that aims at inferring the (causal) structure of a system or reasoning about the effects of interventions. If algorithms and decisions are grounded in the structural understanding of a data-generating system and take into account the epistemic uncertainty, we expect them to be more robust and have fewer unforeseen side-effects. However, the assumptions allowing for a causal interpretation of DAGs, e.g., the absence of unmeasured confounders, are often untestable and to be taken with care [60], particularly in safety-critical and societally-sensitive applications. Hence, while potential misuse can never be ruled out, our presented method predominantly promises positive societal and scientific impact.

References

[1] Judea Pearl. *Probabilistic reasoning in intelligent systems: networks of plausible inference*. 1988.

[2] Dana Pe'er, Aviv Regev, Gal Elidan, and Nir Friedman. Inferring subnetworks from perturbed expression profiles. *Bioinformatics*, 17:S215–S224, 2001.

[3] Karen Sachs, Omar Perez, Dana Pe'er, Douglas A Lauffenburger, and Garry P Nolan. Causal protein-signaling networks derived from multiparameter single-cell data. *Science*, 308(5721):523–529, 2005.

[4] Chikako Van Koten and AR Gray. An application of bayesian network for predicting object-oriented software maintainability. *Information and Software Technology*, 48(1):59–67, 2006.

[5] Philippe Weber, Gabriela Medina-Oliva, Christophe Simon, and Benoît Iung. Overview on bayesian networks applications for dependability, risk analysis and maintenance areas. *Engineering Applications of Artificial Intelligence*, 25(4):671–682, 2012.

[6] Rupesh Agrahari, Amir Foroushani, T Roderick Docking, Linda Chang, Gerben Duns, Monika Hudoba, Aly Karsan, and Habil Zare. Applications of bayesian network models in predicting types of hematological malignancies. *Scientific reports*, 8(1):1–12, 2018.

[7] Al-Amin Baksh, Rouzbeh Abbassi, Vikram Garaniya, and Faisal Khan. Marine transportation risk assessment using bayesian network: Application to arctic waters. *Ocean Engineering*, 159:422–436, 2018.

[8] David Maxwell Chickering. Optimal structure identification with greedy search. *J. Mach. Learn. Res.*, 3: 507–554, March 2003.

[9] Peter Spirtes, Clark N. Glymour, and Richard Scheines. *Causation, prediction, and search*. Adaptive computation and machine learning. MIT Press, Cambridge, Mass, 2nd ed edition, 2000.

[10] Ioannis Tsamardinos, Laura E Brown, and Constantin F Aliferis. The max-min hill-climbing bayesian network structure learning algorithm. *Machine learning*, 65(1):31–78, 2006.

[11] Xun Zheng, Bryon Aragam, Pradeep K Ravikumar, and Eric P Xing. DAGs with NO TEARS: Continuous optimization for structure learning. In *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

[12] Kevin P Murphy. Active learning of causal bayes net structure. 2001.

[13] Simon Tong and Daphne Koller. Active learning for structure in bayesian networks. In *International joint conference on artificial intelligence*, volume 17, pages 863–869, 2001.

[14] Hyunghoon Cho, Bonnie Berger, and Jian Peng. Reconstructing causal biological networks through active learning. *PloS one*, 11(3):e0150611, 2016.

[15] Robert Osazuwa Ness, Karen Sachs, Parag Mallick, and Olga Vitek. A bayesian active learning experimental design for inferring signaling networks. In *International Conference on Research in Computational Molecular Biology*, pages 134–156. Springer, 2017.

[16] Raj Agrawal, Chandler Squires, Karren Yang, Karthikeyan Shanmugam, and Caroline Uhler. ABCD-Strategy: Budgeted experimental design for targeted causal structure discovery. In *Proceedings of Machine Learning Research*, volume 89, pages 3400–3409. PMLR, 16–18 Apr 2019.

[17] Dan Geiger and David Heckerman. Learning gaussian networks. In *Proceedings of the Tenth International Conference on Uncertainty in Artificial Intelligence*, UAI'94, page 235–243, San Francisco, CA, USA, 1994.

[18] Dan Geiger and David Heckerman. Parameter priors for directed acyclic graphical models and the characterization of several probability distributions. *Ann. Statist.*, 30(5):1412–1440, October 2002. Publisher: The Institute of Mathematical Statistics.

[19] David Heckerman, Dan Geiger, and David M. Chickering. Learning Bayesian Networks: The Combination of Knowledge and Statistical Data. *Machine Learning*, 20(3):197–243, September 1995.

[20] Qiang Liu and Dilin Wang. Stein variational gradient descent: A general purpose bayesian inference algorithm. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, NIPS'16, page 2378–2386, 2016.

[21] Nir Friedman and Daphne Koller. Being Bayesian About Network Structure. A Bayesian Approach to Structure Discovery in Bayesian Networks. *Machine Learning*, 50(1):95–125, January 2003.

[22] David Madigan and Adrian E Raftery. Model selection and accounting for model uncertainty in graphical models using occam's window. *Journal of the American Statistical Association*, 89(428):1535–1546, 1994.

[23] David Madigan, Jonathan Gavrin, and Adrian E Raftery. Eliciting prior information to enhance the predictive performance of bayesian graphical models. *Communications in Statistics-Theory and Methods*, 24(9):2271–2292, 1995.

[24] R.W. Robinson. Counting labeled acyclic digraphs. *New Directions in the Theory of Graphs*, 1973.

[25] Yue Yu, Jie Chen, Tian Gao, and Mo Yu. DAG-GNN: DAG structure learning with graph neural networks. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 7154–7163. PMLR, 09–15 Jun 2019.

[26] Sébastien Lachapelle, Philippe Brouillard, Tristan Deleu, and Simon Lacoste-Julien. Gradient-based neural dag learning. In *International Conference on Learning Representations*, 2020.

[27] Ignavier Ng, Shengyu Zhu, Zhitang Chen, and Zhuangyan Fang. A graph autoencoder approach to causal structure learning. In *NeurIPS 2019 Workshop "Do the right thing": machine learning and causal inference for improved decision making*, 2019.

[28] Xun Zheng, Chen Dan, Bryon Aragam, Pradeep Ravikumar, and Eric Xing. Learning sparse nonparametric dags. In *International Conference on Artificial Intelligence and Statistics*, pages 3414–3425. PMLR, 2020.

[29] Roxana Pamfil, Nisara Sriwattanaworachai, Shaan Desai, Philip Pilgerstorfer, Konstantinos Georgatzis, Paul Beaumont, and Bryon Aragam. Dynotears: Structure learning from time-series data. In *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, volume 108 of *Proceedings of Machine Learning Research*, pages 1595–1605. PMLR, 2020.

[30] Mengyue Yang, Furui Liu, Zhitang Chen, Xinwei Shen, Jianye Hao, and Jun Wang. Causalvae: Disentangled representation learning via neural structural causal models, 2020.

[31] Muhan Zhang, Shali Jiang, Zhicheng Cui, Roman Garnett, and Yixin Chen. D-vae: A variational autoencoder for directed acyclic graphs. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

[32] Nan Rosemary Ke, Olexa Bilaniuk, Anirudh Goyal, Stefan Bauer, Hugo Larochelle, Chris Pal, and Yoshua Bengio. Learning neural causal models from unknown interventions, 2019.

[33] Dennis Wei, Tian Gao, and Yue Yu. Dags with no fears: A closer look at continuous optimization for learning bayesian networks. *Advances in Neural Information Processing Systems*, 2020.

[34] Ignavier Ng, Sébastien Lachapelle, Nan Rosemary Ke, and Simon Lacoste-Julien. On the convergence of continuous constrained optimization for structure learning. 2020.

[35] David Madigan, Jeremy York, and Denis Allard. Bayesian graphical models for discrete data. *International Statistical Review/Revue Internationale de Statistique*, pages 215–232, 1995.

[36] Paolo Giudici and Robert Castelo. Improving markov chain monte carlo model search for data mining. *Machine learning*, 50(1-2):127–158, 2003.

[37] Daniel Eaton and Kevin Murphy. Bayesian structure learning using dynamic programming and MCMC. In *Proceedings of the Twenty-Third Conference on Uncertainty in Artificial Intelligence (UAI)*, 2007.

[38] Marco Grzegorczyk and Dirk Husmeier. Improving the structure MCMC sampler for Bayesian networks by introducing a new edge reversal move. *Machine Learning*, 71(2):265, April 2008.

[39] Jack Kuipers and Giusi Moffa. Partition mcmc for inference on acyclic digraphs. *Journal of the American Statistical Association*, 112(517):282–299, 2017.

[40] Byron Ellis and Wing Hung Wong. Learning causal bayesian network structures from experimental data. *Journal of the American Statistical Association*, 103(482):778–789, 2008.

[41] N. Friedman, M. Goldszmidt, and A. J. Wyner. Data analysis with Bayesian networks: A bootstrap approach. In *Proceedings of the Fifteenth Conference on Uncertainty in Artificial Intelligence*, 1999.

[42] Mikko Koivisto and Kismat Sood. Exact bayesian structure discovery in bayesian networks. *Journal of Machine Learning Research*, 5(May):549–573, 2004.

[43] Mikko Koivisto. Advances in exact bayesian structure discovery in bayesian networks. In *Proceedings of the Twenty-Second Conference on Uncertainty in Artificial Intelligence*, page 241–248, 2006.

[44] Marina Meila and Tommi S Jaakkola. Tractable bayesian learning of tree belief networks. *Statistics and Computing*, (16):77–92, 2006.

[45] Denver Dash and Gregory F Cooper. Model averaging for prediction with discrete bayesian networks. *Journal of Machine Learning Research*, 5(Sep):1177–1203, 2004.

[46] Thomas N Kipf and Max Welling. Variational graph auto-encoders. 2016.

[47] Chris J. Maddison, Andriy Mnih, and Yee Whye Teh. The concrete distribution: A continuous relaxation of discrete random variables. In *Proceedings International Conference on Learning Representations*, 2017.

[48] Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparametrization with gumbel-softmax. In *Proceedings International Conference on Learning Representations 2017*, April 2017.

[49] Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

[50] Shakir Mohamed, Mihaela Rosca, Michael Figurnov, and Andriy Mnih. Monte carlo gradient estimation in machine learning. *Journal of Machine Learning Research*, 21(132):1–62, 2020.

[51] Ignavier Ng, AmirEmad Ghassami, and Kun Zhang. On the role of sparsity and dag constraints for learning linear dags. *Advances in Neural Information Processing Systems*, 2020.

[52] P. Erdős and A Rényi. On random graphs. *Publicationes Mathematicae*, 6:290–297, 1959.

[53] Albert-László Barabási and Réka Albert. Emergence of scaling in random networks. *Science*, 286(5439): 509–512, 1999.

[54] Steen A Andersson, David Madigan, Michael D Perlman, et al. A characterization of markov equivalence classes for acyclic digraphs. *Annals of statistics*, 25(2):505–541, 1997.

[55] Tom Fawcett. ROC graphs: Notes and practical considerations for researchers. *Machine learning*, 31(1): 1–38, 2004.

[56] W Keith Hastings. Monte carlo sampling methods using markov chains and their applications. 1970.

[57] Alain Hauser and Peter Bühlmann. Jointly interventional and observational data: estimation of interventional markov equivalence classes of directed acyclic graphs. *Journal of the Royal Statistical Society: Series B: Statistical Methodology*, pages 291–318, 2015.

[58] Radford M Neal et al. Mcmc using hamiltonian dynamics. *Handbook of Markov chain Monte Carlo*, 2 (11):2, 2011.

[59] Max Welling and Yee Whye Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th International Conference on International Conference on Machine Learning*, ICML'11, page 681–688, 2011.

[60] A. Philip Dawid. Beware of the DAG! In *Proceedings of Workshop on Causality: Objectives and Assessment at NIPS 2008*, pages 59–86, 2010.

[61] Jack Kuipers, Giusi Moffa, and David Heckerman. Addendum on the scoring of Gaussian directed acyclic graphical models. *Ann. Statist.*, 42(4):1689–1691, August 2014. Publisher: The Institute of Mathematical Statistics.

[62] Diviyan Kalainathan, Olivier Goudet, Isabelle Guyon, David Lopez-Paz, and Michèle Sebag. Structural agnostic modeling: Adversarial learning of causal graphs. *arXiv preprint arXiv:1803.04929*, 2018.

[63] Geoffrey Hinton, Nitish Srivastava, and Kevin Swersky. Neural networks for machine learning lecture 6a overview of mini-batch gradient descent. 2012.

[64] Chris Sherlock, Paul Fearnhead, Gareth O Roberts, et al. The random walk metropolis: linking theory and practice through a case study. *Statistical Science*, 25(2):172–190, 2010.

[65] Dorit Dor and Michael Tarsi. A simple algorithm to construct a consistent extension of a partially oriented graph. 1992.

[66] Yangbo He, Jinzhu Jia, and Bin Yu. Counting and exploring sizes of markov equivalence classes of directed acyclic graphs. *The Journal of Machine Learning Research*, 16(1):2589–2609, 2015.

[67] Diviyan Kalainathan and Olivier Goudet. Causal discovery toolbox: Uncover causal relationships in python, 2019.

[68] James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. JAX: composable transformations of Python+NumPy programs, 2018. URL http://github.com/google/jax.

[69] Yoshua Bengio, Tristan Deleu, Nasim Rahaman, Nan Rosemary Ke, Sebastien Lachapelle, Olexa Bilaniuk, Anirudh Goyal, and Christopher Pal. A meta-transfer objective for learning to disentangle causal mechanisms. In *International Conference on Learning Representations*, 2020.

[70] Zhuangyan Fang, Shengyu Zhu, Jiji Zhang, Yue Liu, Zhitang Chen, and Yangbo He. Low rank directed acyclic graphs and causal structure learning, 2020.