BAST: Bayesian Additive Regression Spanning Trees for Complex Constrained Domain

Abstract

Nonparametric regression on complex domains has been a challenging task as most existing methods, such as ensemble models based on binary decision trees, are not designed to account for intrinsic geometries and domain boundaries. This article proposes a Bayesian additive regression spanning trees (BAST) model for nonparametric regressions on manifolds, with an emphasis on complex constrained domains or irregularly shaped spaces embedded in Euclidean spaces. Our model is built upon a random spanning tree manifold partition model as each weak learner, which is capable of capturing any irregularly shaped partitions while respecting intrinsic geometries and domain boundary constraints. Utilizing many nice properties of spanning tree structures, we design an efficient Bayesian inference algorithm. Equipped with a soft prediction scheme, BAST is demonstrated to significantly outperform other competing methods in simulation experiments and in an application to the chlorophyll data in Aral Sea, due to its strong local adaptivity to different levels of smoothness.

1 Introduction

Over the past few decades, data collected from complex constrained domains have attracted much attention in machine learning and spatial statistics. Domains with non-trivial geometries, such as irregular boundaries, sharp concavities, and/or interior holes due to geographic constraints (e.g., lakes), impose challenges on statistical modeling, as the Euclidean assumption underpinning many traditional statistical and machine learning methods no longer holds for data with intrinsic geometries.

In this paper, we consider nonparametric regression problems with features lying on constrained domains or, more generally, compact Riemannian manifolds. To be more specific, we model the response variable $Y(\mathbf{s}) \in \mathbb{R}$ at a location $\mathbf{s}$ on a compact Riemannian manifold M as

$$Y(\mathbf{s}) = f(\mathbf{s}) + \epsilon(\mathbf{s}), \quad \epsilon(\mathbf{s}) \stackrel{\text{iid}}{\sim} N(0, \sigma^2), \tag{1}$$

for some unknown function $f : M \to \mathbb{R}$ and noise variance σ^2. In many applications, the true function $f(\cdot)$ may not be globally smooth but has discontinuities/abrupt changes across some narrow regions in the domain. For example, housing prices can be substantially different in two neighboring communities. It is of great need to develop new methodologies that can both respect intrinsic geometries of the domain and capture complicated local discontinuity patterns in the true function.

There is growing literature on nonparametric regressions and smoothing for complex domains. Spline smoothing methods [34, 22, 42, 44, 38] have been developed for constrained domains, but most of them focus on domains in $\mathbb{R}^2$. Sangalli et al. [37] generalized the spline methods for constrained regions in $\mathbb{R}^3$. For more general Riemannian manifolds, kernel based smoothing models, including kernel regressions [33, 19] and local regressions [8, 2, 12], were developed. Gaussian process (GP) regressions are another popular tools for nonparametric regression problems, and many works focus on developing valid covariance kernels on spheres [see 20, 16, 15, among others]. More recently, a few practical GP models for constrained domains and Riemannian manifolds were studied in the

literature, including extrinsic GPs [24], intrinsic GPs [32], Matérn GPs [5, 25], and diffusion-based GPs [13]. However, most of the aforementioned approaches assume globally smooth true functions and thus may not fully adapt to the ones with local discontinuities.

Ensemble tree models [6, 7] have been widely used in traditional nonparametric regression problems. One prominent example is the Bayesian additive regression trees (BART) model [10], due to its versatility and capability of producing uncertainty measures. However, to our knowledge, ensemble methods have not been used for nonparametric regression on complex constrained domains, and almost all ensemble tree methods rely on binary decision tree partition models as their ensemble members (weak learners). Nevertheless, binary trees may not be ideal to capture possibly highly irregular partitions on complex domains as they can only make Euclidean axis parallel splits. For instance, in the U-shape domain shown in Figure 1(c), a complicated and over-clustered binary treed partition is needed to approximate a simple partition with three clusters (marked by different colors). Moreover, the rectangular partitions do not comply to domain constraints, which may cause "leakage" problems on complex domains. With a similar partitioning idea, Menafoglio et al. [29] proposed a Voronoi tessellation based model to account for domain constraints, but their method imposes convexity restrictions on partitions. Most recently, spanning treed partition models have been demonstrated as an effective tool for recovering partitions with flexible shapes [23, 40, 27], but their focus is on traditional two-dimensional Euclidean spaces and linear regression settings.

Our contribution in this paper is to propose a novel Bayesian additive regression spanning trees (BAST) model for nonparametric regressions on complex constrained domains with efficient Bayesian inference algorithms. The backbone of BAST is a new random spanning tree (RST) manifold partition model, which replaces binary decision trees in each weak learner. RST is capable of capturing irregularly shaped partitions with a small number of spanning tree cuts while respecting intrinsic geometries and domain boundary constraints. Equipped with a *soft* prediction scheme, we show that BAST achieves a superior prediction performance over other competing methods on various tasks, thanks to its strong local adaptivity to different levels of smoothness.

The rest of the paper proceeds as follows. In Section 2, we present the RST partition models on manifolds and develop a new Bayesian nonparametric regression model with RST ensembles. Section 3 discusses algorithms for Bayesian inference. In Sections 4, we illustrate the model performance by simulation experiments and a real chlorophyll data set in Aral Sea. Section 5 concludes the paper with some discussions. Additional details on Bayesian inference and simulation results are provided in Supplementary Materials.

2 Bayesian Nonparametric Regressions with Additive Spanning Trees

2.1 A Spanning Treed Partition Model on Manifolds

Our novel nonparametric regression model is built upon an ensemble of partitions of observations. In this subsection, we introduce a stochastic partition model for locations on a manifold via random spanning trees (RSTs), which will serve as a building block to develop the sum-of-spanning-trees model in Section 2.2.

Let M be a d-dimensional compact Riemannian manifold that is known *a priori*, and $\mathcal{S} = \{\mathbf{s}_1, \ldots, \mathbf{s}_n\} \subseteq M$ be a finite set of locations on M where the data are observed. We are interested in partitioning $\mathcal{S}$ into several disjoint subsets such that each subset consists of nearby locations where the data are relatively homogeneous and can be modeled separately. For spatial data, it is often desired to impose continuity constrains on partitions. Below, we introduce the notion of spatially contiguous partitions on a manifold based on a spatial graph whose edges encode the relationship of spatial adjacency or neighborhood. Let $\mathcal{G} = (\mathcal{S}, \mathcal{E})$ be a connected undirected graph with vertex set $\mathcal{S}$ and edge set $\mathcal{E}$ that connects $\mathbf{s} \in \mathcal{S}$ to its "close neighbors". The construction of spatial graphs on a manifold will be discussed later in this subsection. We say $\pi(\mathcal{S}) = \{\mathcal{S}_1, \ldots, \mathcal{S}_k\}$, where $\mathcal{S}_j \subseteq \mathcal{S}$ for $j = 1, \ldots, k$, is a *spatially contiguous partition* of $\mathcal{S}$ with respect to $\mathcal{G}$ if $\cup_{j=1}^k \mathcal{S}_j = \mathcal{S}$, $\mathcal{S}_j \cap \mathcal{S}_{j'} = \emptyset$ for all $j \neq j'$, and there exists a connected subgraph $\mathcal{G}_j = (\mathcal{S}_j, \mathcal{E}_j)$ of $\mathcal{G}$ for each j. We also call each $\mathcal{S}_j$ a cluster, which consists of locations that are connected to each other and thus is spatially contiguous with respect to the spatial graph. Henceforth, when there is no risk of confusion, we will refer to spatially contiguous partitions simply as partitions. Figure 1(a) shows an example of a partition with three clusters.

Figure 1: (a) A constrained Delaunay triangulation graph on a U-shaped domain. (b) A partition with three clusters obtained by removing the red edges in a spanning tree. (c) A binary treed partition that induces a partition nested in the three-cluster partition in (a, b).

For constrained domains in $\mathbb{R}^2$ such as the U-shaped domain in Figure 1, spatial graphs can be constructed via constrained Delaunay triangulations [CDTs; 9]. Specifically, let $\mathcal{G}_0$ be a CDT mesh on $\mathcal{S} \cup \mathcal{S}_B$, where $\mathcal{S}_B$ is a set of locations on the domain boundaries. Then the induced subgraph of $\mathcal{G}_0$ on $\mathcal{S}$ can be chosen as a spatial graph $\mathcal{G}$. Edges longer than a certain threshold can be removed if desired. See Figure 1(a) for an example of $\mathcal{G}$ constructed via CDT. For a general manifold, motivated by the adaptive properties of nonparametric regressions based on K nearest neighbor (K-NN) graphs on manifolds [28, 21], one can construct $\mathcal{G}$ by a K-NN graph that connects $\mathbf{s} \in \mathcal{S}$ to its K nearest neighbours with respect to geodesic distance.

Motivated by the success of spanning treed models for partitions in two-dimensional Euclidean spaces [23, 40, 27], we opt to model partitions on manifolds in a similar spirit. Specifically, a connected subgraph $\mathcal{T} = (\mathcal{S}, \mathcal{E}_{\mathcal{T}})$ is called a spanning tree of $\mathcal{G}$ if it has no circle. A well-known property of spanning trees is that if a set of $k-1$ edges in $\mathcal{E}_{\mathcal{T}}$ is removed, we obtain a disconnected subgraph of $\mathcal{T}$ with k connected components, which defines a partition $\pi(\mathcal{S})$ with k clusters when the vertex set of the jth component is taken as $\mathcal{S}_j$. In this case, we say $\pi(\mathcal{S})$ is *induced* by $\mathcal{T}$. See Figure 1(b) for an example. This property implies that we can simplify a complicated graph partition modeling problem to modeling spanning trees as well as the number and locations of removed edges.

Mathematically, conditional on $\mathcal{T}$ and k we assume a discrete uniform distribution on all possible partitions induced by $\mathcal{T}$:
$$p\left\{\pi(\mathcal{S}) \mid k, \mathcal{T}\right\} \propto \mathbb{1}\left\{\pi(\mathcal{S}) \text{ is induced by } \mathcal{T} \text{ and has } k \text{ clusters}\right\}. \tag{2}$$
Next, we consider a probabilistic model on the spanning tree space. Let ω_e be the weight for an edge $e \in \mathcal{E}$ and $\boldsymbol{\omega} = \{\omega_e : e \in \mathcal{E}\}$. We assume an iid uniform distribution on the edge weights and let $\mathcal{T}$ be the resulting minimum spanning tree (MST), i.e., the spanning tree with minimum $\sum_{e \in \mathcal{E}_{\mathcal{T}}} \omega_e$:
$$\mathcal{T} = \text{MST}(\boldsymbol{\omega}), \quad \omega_e \overset{\text{iid}}{\sim} \text{Unif}(0, 1), \tag{3}$$
where $\text{MST}(\boldsymbol{\omega})$ denotes an MST of the graph $\mathcal{G}$ based on edge weights $\boldsymbol{\omega}$. Note that we are not assuming a uniform distribution on the spanning tree space, with which it is challenging to sample spanning trees for Bayesian inference. As we will show in Section 3.1, our model specification leads to an exact and fast spanning tree sampler, taking advantage of the Prim's algorithm for MST constructions. Finally, we assume a truncated Poisson distribution with mean parameter λ_k on the number of clusters:
$$k \sim \text{Poisson}(\lambda_k) \cdot \mathbb{1}(1 \le k \le \bar{k}), \tag{4}$$
where $\bar{k}$ is the pre-specified maximum number of clusters. The following proposition states that the support of RST is rich enough to accommodate all possible partitions on a manifold with no more than $\bar{k}$ clusters. The proof is postponed to Appendix C. Note that similar result does not hold for binary treed partition models. See Figure 1(c) for a counterexample where there does not exist a rectangle containing all the blue points exclusively.

Proposition 1 *Let $\pi(\mathcal{S}) = \{\mathcal{S}_1, \ldots, \mathcal{S}_k\}$ be an arbitrary spatially contiguous partition. Then $\pi(\mathcal{S})$ is within the support of the partition model defined by (2), (3), and (4) if $k \le \bar{k}$.*

2.2 A Sum-of-spanning-trees Regression Model

Given the data $\{Y(\mathbf{s}_i), \mathbf{s}_i\}_{i=1}^n$, we consider the nonparametric regression problem (1). Instead of assuming global continuity, we assume $f(\cdot)$ belongs to a broad class of piecewise smooth functions. We propose to model $f(\cdot)$ using a summation of weak learners based on the flexible RST partitions.

Figure 2: Demonstration of the partition obtained by adding two spanning treed partitions.

Given a partition $\pi(\mathcal{S})$ induced by $\mathcal{T}$ with k clusters and $\boldsymbol{\mu} = (\mu_1, \ldots, \mu_k) \in \mathbb{R}^k$, we define a mapping from $\mathcal{S}$ to $\mathbb{R}$ as

$$g(\mathbf{s}|\pi, \mathcal{T}, k, \boldsymbol{\mu}) = \mu_j \quad \text{if } \mathbf{s} \in \mathcal{S}_j,$$

where we write $\pi = \pi(\mathcal{S})$ for conciseness. This piecewise constant function on $\mathcal{S}$ serves as a weak learner for $f(\cdot)$, which approximates $f(\cdot)$ by μ_j locally in $\mathcal{S}_j$. A Bayesian additive spanning trees (BAST) model is a summation of piecewise constant functions based on various spanning-treed partitions. Specifically, for a pre-specified $M \in \mathbb{N}$, BAST models $f(\cdot)$ as

$$f(\mathbf{s}) = \sum_{m=1}^{M} g(\mathbf{s}|\pi_m, \mathcal{T}_m, k_m, \boldsymbol{\mu}_m), \quad \mathbf{s} \in \mathcal{S} \tag{5}$$

where $\pi_m = \pi_m(\mathcal{S}) = \{\mathcal{S}_1^m, \ldots, \mathcal{S}_{k_m}^m\}$ is a partition with k_m clusters induced by a spanning tree $\mathcal{T}_m$ of $\mathcal{G}$ and $\boldsymbol{\mu}_m = (\mu_{m1}, \ldots, \mu_{mk_m})$. Although in principle the spatial graphs for each weak learner need not be identical, we focus on the case where they share a common $\mathcal{G}$ for simplicity.

For $\mathbf{s} \in \mathcal{S}$, the additive structure (5) implies that $f(\mathbf{s})$ equals the summation of the μ_{mj}'s corresponding to the clusters that $\mathbf{s}$ lies in. Figure 2 illustrates a summation of two spanning treed partitions. This together with the shrinkage priors to be discussed in Section 2.3 allows each weak learner to explain a small amount of the variation in the response variable. The step function approximation also allows for capturing both smoothness and discontinuities/abrupt changes in $f(\cdot)$ [36]. In particular, our model is more efficient than some existing ensemble binary tree and smoothing methods in recovering irregularly shaped regions where discontinuities happen, thanks to the versatility of RST partition models in capturing highly flexible cluster shapes for complex constrained domains. For an out-of-sample observation $\mathbf{u} \notin \mathcal{S}$, a Bayesian prediction for $f(\mathbf{u})$ will be discussed in Section 3.2.

Finally, we remark that although we focus on Gaussian regressions, it is straightforward to extend BAST for binary, multinomial, and count responses by utilizing conjugate models or data augmentation tricks [1, 10, 31].

2.3 Prior Specifications

Similar to BART [10], shrinkage priors play an important role in regularizing weak learners and preventing overfitting for BAST. In this subsection we discuss the specification of prior models, which admits the form

$$p\left(\{\pi_m, \mathcal{T}_m, k_m, \boldsymbol{\mu}_m\}_{m=1}^{M}, \sigma^2\right) = \left\{\prod_{m=1}^{M} p(\boldsymbol{\mu}_m|\pi_m, \mathcal{T}_m, k_m)p(\pi_m, \mathcal{T}_m, k_m)\right\} p(\sigma^2).$$

We assign an iid RST prior for $(\pi_m, \mathcal{T}_m, k_m)$ given by (2), (3), and (4). Small values of λ_k and $\bar{k}$ in (4) are typically chosen to restrict the number of clusters in each partition, leading to simpler piecewise constant structures in each weak learner which prevent overfitting and encourage better mixing in Markov chain Monte Carlo.

Rescaling $Y(\mathbf{s})$ into $[-0.5, 0.5]$, we opt to place a shrinkage prior that concentrates around 0 for $\boldsymbol{\mu}_m$ following [10]. Conditional on $(\pi_m, \mathcal{T}_m, k_m)$, we choose a conjugate prior for $\boldsymbol{\mu}_m$ given by

$$\boldsymbol{\mu}_m|\pi_m, \mathcal{T}_m, k_m \sim \mathrm{N}_{k_m}(\mathbf{0}, \sigma_\mu^2 \mathbf{I}_{k_m}), \tag{6}$$

independently for $m = 1, \ldots, M$, where σ_μ is assumed to depend on the number of weak learners, specifically, $\sigma_\mu = 0.5/(a\sqrt{M})$ with $a > 0$. Intuitively, when we have a larger number of weak learners, it is desired to impose stronger shrinkage effects by choosing a smaller σ_μ such that each

| (a) Original Partition | (b) A Birth Move | (c) A Death Move | (d) A Hyper Move |

Figure 3: Partitions and spanning trees obtained after (b) a birth, (c) a death, or (d) a hyper move from the original partition and tree in (a).

learner is not too influential to the overall fit. A default choice of a can be $a = 2$, which assigns 0.95 prior probability for $f(\mathbf{s})$ that lies in $[-0.5, 0.5]$.

Finally, we assign a conjugate inverse-χ^2 prior on σ^2: $\sigma^2 \sim \nu\lambda_s/\chi^2_\nu$. We fix $\nu = 3$ and choose λ_s in a data-driven way such that the prior satisfies $\mathbb{P}(\sigma^2 < \hat{\sigma}^2) = 0.90$ similarly as in BART [10], where $\hat{\sigma}^2$ is the sample variance of $\mathbf{Y} = \{Y(\mathbf{s}_1), \dots, Y(\mathbf{s}_n)\}$.

3 Bayesian Inference

3.1 Estimation

Inference of BAST is based on a tailored backfitting Markov chain Monte Carlo (MCMC) algorithm [18], in which we successively sample $(\pi_1, \mathcal{T}_1, k_1, \boldsymbol{\mu}_1), \dots, (\pi_M, \mathcal{T}_M, k_M, \boldsymbol{\mu}_M)$, and σ^2 from their respective full conditionals. Our sampler for the full conditional $p(\pi_m, \mathcal{T}_m, k_m, \boldsymbol{\mu}_m|-)$, where $-$ stands for all other parameters and the data $\mathbf{Y}$, consists of two successive steps: (i) we first analytically integrate $\boldsymbol{\mu}_m$ out and sample from the collapsed conditional distribution for the partition $p(\pi_m, \mathcal{T}_m, k_m|-)$, and (ii) we then sample $\boldsymbol{\mu}_m$ from $p(\boldsymbol{\mu}_m|\pi_m, \mathcal{T}_m, k_m, -)$. This design leads to better mixing and convergence performance of the sampler by avoiding the trans-dimensional problem for $\boldsymbol{\mu}_m$'s. Thanks to the conjugate priors, sampling from $p(\mu_m|\pi_m, \mathcal{T}_m, -)$ and $p(\sigma^2|-)$ follows standard procedures, and we leave the details to Appendix A.1.

Below, we focus on the adaptive estimation for the RST partitions. To draw samples for $(\pi_m, \mathcal{T}_m, k_m)$, one of the four moves — *birth*, *death*, *change*, and *hyper* — is performed with probabilities $r_b(k_m)$, $r_d(k_m)$, $r_c(k_m)$, and $r_h(k_m)$, respectively [27]. The first three moves modify the partition by proposing a new partition induced by the current spanning tree, and the hyper move updates $\mathcal{T}_m$ by sampling from its full conditional via an efficient sampling algorithm. Each move is detailed below and some of them are visualized in Figure 3.

In a birth move, one of the k_m clusters in π_m is randomly chosen with equal probabilities, and then the chosen cluster is split into two by randomly removing an edge in $\mathcal{T}_m$ that connects vertices in the cluster. Denoting the new partition by π_m^*, the Metropolis-Hastings (M-H) acceptance ratio is given by

$$\min\left\{1, \ \frac{\lambda}{(k_m + 1)} \times \frac{r_d(k_m + 1)}{r_b(k_m)} \times \frac{\mathcal{L}(\mathbf{Y}|\pi_m^*, \mathcal{T}_m, k_m + 1, -)}{\mathcal{L}(\mathbf{Y}|\pi_m, \mathcal{T}_m, k_m, -)}\right\}, \tag{7}$$

where $\mathcal{L}(\mathbf{Y}|\pi_m, \mathcal{T}_m, k_m, -)$ is the integrated likelihood with $\boldsymbol{\mu}_m$ marginalized out, whose closed form can be found in Appendix A.1. Opposite to the birth move, a death move randomly merges two adjacent clusters in π_m. Specifically, an edge in $\mathcal{T}_m$ that connects two distinct clusters in π_m is uniformly selected and then the two clusters are merged into one. The M-H ratio is analogous to (7). In a change move, a death move is performed followed by a birth move, so that the number of clusters is unchanged. This move is designed to encourage better mixing of the sampler.

Finally, a hyper move updates $\mathcal{T}_m$ using an exact sampler, which adaptively learns a spanning treed spatial order so that we can obtain a partition that is more compatible to the homogeneity pattern of data in subsequent MCMC iterations. Specifically, we sample the edge weight ω_e of $\mathcal{G}$ from iid $\mathrm{Unif}(1/2, 1)$ if two endpoints of e are in different clusters under π_m, and otherwise from iid $\mathrm{Unif}(0, 1/2)$. A new spanning tree is the MST generated by Prim's algorithm using the new edge weights. It can be shown that the resulting MST induces the current partition [40] and is an exact sample from its full conditional distribution [27].

3.2 Prediction

The prediction at an unobserved location $\mathbf{u} \notin \mathcal{S}$ is based on the spatial graph and manifold structures, and a *soft* prediction scheme in a similar spirit to Linero and Yang [26]. We define the neighbor set $N_{\mathbf{u}} \subseteq \mathcal{S}$ of $\mathbf{u}$ as follows. For a constrained domain in $\mathbb{R}^2$, $N_{\mathbf{u}}$ is chosen as the set of the vertices of the triangle containing $\mathbf{u}$ in the CDT mesh that belong to $\mathcal{S}$ (i.e., vertices on the domain boundary are excluded; see Appendix A.2 for detailed discussions). For a general manifold, $N_{\mathbf{u}}$ is specified as the set of K nearest neighbors of $\mathbf{u}$ in $\mathcal{S}$ with respect to the geodesic distance.

Let $z_m(\mathbf{v}) \in \{1, \ldots, k_m\}$ be the cluster membership of a generic location $\mathbf{v} \in M$ from the mth weak learner such that $z_m(\mathbf{s}) = j$ if $\mathbf{s} \in \mathcal{S}_j^m$. Intuitively, $\mathbf{u}$ is expected to share the same cluster membership as one of its neighbors in $\mathcal{S}$, and if $\mathbf{u}$ is near the boundary of a cluster in a partition, it is more ideal to assign $z(\mathbf{u})$ probabilistically to reflect the partitioning uncertainty and adapt for smoother functions. This motivates us to consider the following random assignment for $z_m(\mathbf{u})$'s: given $N_{\mathbf{u}}$ and a posterior sample of the partitions, $z_m(\mathbf{u})$ is sampled independently such that $\mathbb{P}\{z_m(\mathbf{u}) = z_m(N_{\mathbf{u},\ell})\} = \alpha_\ell$, for $\ell = 1, \ldots, |N_{\mathbf{u}}|$, where $N_{\mathbf{u},\ell}$ is the ℓth element in $N_{\mathbf{u}}$ and α_ℓ satisfies $\sum_{\ell=1}^{|N_{\mathbf{u}}|} \alpha_\ell = 1$. One can specify α_ℓ by setting $\alpha_\ell = 1/|N_{\mathbf{u}}|$ for all ℓ (i.e., sampling $z_m(\mathbf{u})$ from a discrete uniform distribution), or via inverse geodesic distance weighting such as $\alpha_\ell \propto 1/d_g^b(\mathbf{u}, N_{\mathbf{u},\ell})$, where $d_g(\cdot, \cdot)$ is the geodesic distance and b is some positive power. A posterior predictive sample of $Y(\mathbf{u})$ is then obtained by summing $\mu_{m, z_m(\mathbf{u})}$ over $m = 1, \ldots, M$, and a point predictor for $Y(\mathbf{u})$ can be taken as the average of the posterior draws, which allows us to average models with different RST partition structures. Finally, we remark that the prediction algorithm is highly parallelizable, as the predictive sampling for each RST partition is independent.

4 Experiments

4.1 U-shape Example

We first examine the BAST's performance of recovering piecewise smooth functions via some simulation experiments on a rotated U-shaped domain shown in Figure 4(a). Our true function $f(\cdot)$ is constructed based on the one in Ramsay [34], denoted as $f_R(\cdot)$. We create discontinuities along a circle of radius 0.9 centered at the origin as follows. For locations inside the circle, we flip f_R by setting $f = -f_R$. For locations outside the circle, we set $f = 2f_R$ for those in the lower arm of the domain, and $f = f_R$ for those in the upper arm, such that the jump in the lower arm has larger magnitude. We uniformly generate $n = 500$ locations in the domain as training data and 200 locations for prediction. Figure 4(a) shows the true function in the training data. The responses are generated according to (1) with different levels of noise $\sigma = 0.1, 0.5, 1$, and each noise level is replicated for 50 times.

The spatial graph $\mathcal{G}$ is constructed via CDT. We use $M = 20$ weak learners and set $\lambda_k = 4$ and $\bar{k} = 10$ to restrict the size of each partition. The prediction is based on the CDT graph, and we use inverse distance weighting with $b = 1$ to sample cluster memberships. We compare BAST with BART [10], and two other nonparametric regression methods for constrained domains, the soap film smoothing [SFS; 44] and the sparse intrinsic Gaussian process (inGP) regression [32]. For BART, We use the same number of weak learners as in BAST and use its default settings. We run the MCMC for both BAST and BART for 20, 000 iterations, discarding the first half and retaining samples every 5 iterations. We specify 32 equally spaced knots for SFS and set its basis dimension as 40. For sparse inGP, we use 24 equally spaced knots and simulate Brownion motions for 100, 000 times. The prediction performance is assessed by mean squared prediction errors (MSPEs) and mean absolute prediction errors (MAPEs). For the two Bayesian approaches BAST and BART, we also compare their probabilistic prediction performance gauged by continuous ranked probability scores (CRPSs) based on their posterior predictive distributions [see, e.g., 14]. For all the metrics, lower values indicate better performance.

Table 1 summarizes the average performance metrics over 50 replicates for each noise level. BAST outperforms all its competitors in terms of all the metrics under all the noise levels. This is because BAST partitions the training data in a way that adapts to both the domain constraints and the irregularly shaped discontinuity boundaries, thanks to the flexible RST partitions. In contrast, the binary treed partitions adapt to neither types of boundaries, and neither of SPS and inGP captures discontinuities in the true function. This is also evidenced by Figure 4(b-e), where absolute prediction errors (APEs)

Table 1: Prediction performance of BAST and its competing methods in the U-shape domain example. Standard errors are given in parentheses.

		BAST	BART	SFS	inGP
$\sigma = 0.1$	MSPE	**0.189** (0.009)	1.541 (0.530)	0.418 (0.009)	0.814 (0.012)
	MAPE	**0.188** (0.007)	0.436 (0.068)	0.340 (0.005)	0.610 (0.007)
	Mean CRPS	**0.142** (0.008)	0.380 (0.066)	—	—
$\sigma = 0.5$	MSPE	**0.464** (0.044)	1.704 (0.376)	0.680 (0.053)	1.057 (0.072)
	MAPE	**0.491** (0.025)	0.686 (0.053)	0.591 (0.026)	0.752 (0.031)
	Mean CRPS	**0.371** (0.021)	0.575 (0.050)	—	—
$\sigma = 1$	MSPE	**1.283** (0.127)	2.650 (0.397)	1.491 (0.142)	1.823 (0.176)
	MAPE	**0.888** (0.049)	1.072 (0.058)	0.951 (0.050)	1.051 (0.057)
	Mean CRPS	**0.693** (0.042)	0.889 (0.055)	—	—

Figure 4: (a) True function in the training data. (b-e) APEs of one test data set with $\sigma = 0.1$. The discontinuity boundaries are marked as red circles. Black squares in (c) indicate APE > 4.10.

of the test data in one replicate with $\sigma = 0.1$ are shown. The APEs from BAST are small for most locations except for those near the discontinuity boundaries. SFS also has similar patterns; however, errors near the discontinuity boundaries are much higher due to the global smoothness assumption in SFS. The general APE pattern for inGP is similar to SFS, except that it has larger errors, possibly due to the low-rank approximation of covariance functions. With the same number of weak learners, BART has large errors near the upper discontinuity boundary, as more rectangular partitions are needed to well approximate irregular boundaries. Moreover, it also gives poor prediction at some locations near the domain boundary between the two arms, probably because binary treed partitions do not take into account the domain boundary when making axis parallel split, and hence force some boundary locations in one arm to share the same cluster memberships with those locations in the other arm. We have also experimented using more weak learners in BART, and the results in Appendix B.1 suggest that BAST with a fewer number of weak learners still outperforms BART.

4.2 Bitten Torus Example

To illustrate BAST for more general manifolds, we consider a bitten torus example similar to Niu et al. [32]. A torus is a two-dimensional manifold embedded in $\mathbb{R}^3$ that is parameterized by (θ, ϕ), where θ is the angle for the torus and ϕ is the angle for the tube. Let R be the fixed distance from the center of the tube to the center of the torus, and r be the fixed radius of the tube. The Cartesian coordinate (x, y, z) on a torus can be written as $x = (R + r\cos\theta)\cos\phi$, $y = (R + r\cos\theta)\sin\phi$, and $z = r\sin\theta$. We create a bitten torus by setting $\phi \in [\pi/6, 1.7\pi]$ and $\theta \in [0, 2\pi]$.

We consider a piecewise smooth true function $f(x, y, z)$ defined on the bitten torus. We divide the torus into three subregions corresponding to $\theta \in [\pi/6, 3\pi/4]$, $\theta \in (3\pi/4, 5\pi/4]$, and $\theta \in (5\pi/4, 1.7\pi]$, respectively. The true functions in the first and the third regions are the same as the one used in Niu et al. [32], while we set the one in the second region as the negative of the function in Niu et al. [32], such that there are jumps along $\theta = 3\pi/4$ and $5\pi/4$. We generate responses at $n = 500$ random locations according to (1) with $\sigma = 0.1$ as training data. The true function and the training locations are shown in Figure 5.

We construct the spatial graph by a 10-NN graph based on the geodesic distance. Since the geodesic distance of a torus has no analytic form, we approximate it as in Isomap algorithm [41]. Specifically,

Figure 5: (a) True function and training locations (marked as black dots). (b-d) Predictive surfaces of BAST and its competing methods. All plots are viewed along the negative direction of the z-axis.

Table 2: Prediction performance of BAST and its competing methods in the bitten torus example. Standard errors are given in parentheses.

	BAST	BART	inGP
MSPE	**0.487** (0.012)	1.115 (0.287)	2.283 (0.037)
MAPE	**0.307** (0.006)	0.406 (0.062)	1.159 (0.022)
Mean CRPS	**0.225** (0.017)	0.355 (0.059)	—

we first construct a weighted, Euclidean distance based nearest neighbor graph on some fine grids and the training locations. Then we approximate the geodesic distance between two training locations by the length of the shortest path between them in the graph. For prediction at an unobserved location $\mathbf{u}$, we use its 5 nearest neighbors in $\mathcal{S}$ based on the geodesic distance as its neighbor set $N_{\mathbf{u}}$. We compare BAST with BART that uses Cartesian coordinates as features and sparse inGP that uses 24 equally spaced knots, as SFS is only applicable for domains in $\mathbb{R}^2$. Other model specifications are the same as those in Section 4.1.

As in the previous experiment, we compare the prediction performance at 200 random locations. The average performance metrics over 50 replicates in Table 2 suggest that BAST provides the most accurate prediction. We further compare the predictive surfaces of the three methods based on $2,500$ grid points in Figure 5(b-d). As expected, both BAST and BART capture the piecewise structure in the true function, whereas inGP does not. In the interior of each subregion, BAST and BART approximate the true smooth functions fairly accurately. The major difference between the two methods occurs near the discontinuity boundaries. In the surface from BART, some partition boundaries are parallel to the axes such as those near $x = -5$ and $y = \pm 2$, due to the use of binary trees, while this pattern does not appear in the one from BAST. Overall, the blue subregion recovered by BAST is more consistent with the truth. Notice that the estimated function at the discontinuity boundaries from BAST is smoother thanks to its soft prediction scheme. We have also experimented with different noise levels in Appendix B.2, and the findings are consistent.

4.3 Application to Chlorophyll Data

We apply BAST to analyze average remote sensed chlorophyll data in the Aral data over 1998-2002, which are available in the R package `gamair` [43]. The chlorophyll measurements at 485 equally spaced sampled locations are shown in Figure 6(a). The southern part of the sampling domain is separated by the isthmus of the peninsula near 59°E, and both shores of the peninsula have substantially different chlorophyll levels. It is thus desired to take into account this geographical constraints when modeling the data. The goal of our analysis is to assess how well BAST captures the patterns of chlorophyll and predicts for unobserved locations in the complex spatial domain.

We follow Niu et al. [32] to rescale the domain and model the chlorophyll level as a function of the scaled longitude and latitude plus some Gaussian noise. We use a same setup for BAST as in Section 4.1, except that we set $M = 30$ and $\bar{k} = 5$ to encourage smaller sizes of partitions as the number of weak learners is increased. For prediction, we sample the cluster memberships of unobserved locations from discrete uniform distributions. For BART, SFS, and sparse inGP, we also use the same settings as in the simulation experiments but with 30 trees for BART and 42 equally

Table 3: Prediction performance of BAST and its competing methods for the chlorophyll data.

	BAST	BART	SFS	inGP
MSPE	**2.339**	2.933	2.894	3.191
MAPE	**0.926**	1.172	1.071	1.200
Mean CRPS	**0.641**	0.955	—	—

Figure 6: (a) Observed chlorophyll data. (b-e) Predictive surfaces from BAST and its competitors.

spaced knots for both SFS and inGP. The MCMC algorithms for BAST and BART are run for $30,000$ iterations, keeping samples every 5 iterations from the second half.

We first compare the prediction performance of all the models via 10-fold cross validation. In the end, the chlorophyll level at each observed location is predicted exactly once, and we compare MSPEs and MAPEs based on all locations in the data set. Similarly, the mean CRPSs over all locations are compared between BAST and BART. Table 3 shows prediction performance metrics for four models. BAST achieves the best performance among all the models.

Next, we turn to the predictive surfaces from each model, which are shown in Figure 6(b-e). All models capture the general patterns of the data. The predictive surfaces from SFS and inGP are fairly smooth, while the one from BART is least smooth where some sharp jumps can be observed. The surface from BAST is somewhat in between, and preserves small-scale spatial dependence of the data. At the southern part of the eastern basin, BART identifies a rectangular region with high chlorophyll level, while the corresponding region obtained from BAST has irregular shape, which is more consistent with the data and the results from SFS and inGP. This is due to the highly flexible RST partition model that can give irregular shaped clusters.

5   Conclusion and Discussion

We developed a novel Bayesian nonparametric regression model on known manifolds and complex constrained domains using additive RST partitions. The RST weak learner enjoys flexibly shaped partitions while respecting the intrinsic geometries and domain constraints. The additive piecewise constant structure further allows BAST to approximate piecewise smooth functions with irregular boundaries for discontinuities, as evidenced by our simulation studies and real data analysis. In the case where the manifold is unknown, one may estimate the geodesic distance from the data [see, e.g., 30, and references therein] to construct spatial graphs. We leave this scenario for future research.

Similar to its binary treed counterpart BART, BAST is promising to serve as prior models in many other Bayesian hierarchical modeling settings, such as survival analysis [3, 39], casual inference [17], and varying coefficient regressions [11]. As BAST is built upon a spatial graph, it is an interesting direction to extend our methodology for classification and prediction on general graphs and networks [e.g., 4]. Finally, theoretical justifications are important but usually challenging for ensemble methods. For example, theoretical studies of BART have begun emerging only very recently [36, 35]. Posterior concentration results of BAST for estimating the true function can be potentially established in similar manners as BART, but non-trivial extensions are required to theoretically handle the complex spanning tree partition on manifolds and hence beyond the scope of this work. This work has no foreseeable negative societal impacts, but users of BAST should be cautious of prediction outcomes based on ethically biased input data.

References

[1] Albert, J. H. and Chib, S. (1993). Bayesian analysis of binary and polychotomous response data. *Journal of the American statistical Association*, 88(422):669–679.

[2] Aswani, A., Bickel, P., and Tomlin, C. (2011). Regression on manifolds: Estimation of the exterior derivative. *The Annals of Statistics*, 39(1):48–81.

[3] Bonato, V., Baladandayuthapani, V., Broom, B. M., Sulman, E. P., Aldape, K. D., and Do, K.-A. (2011). Bayesian ensemble methods for survival prediction in gene expression data. *Bioinformatics*, 27(3):359–367.

[4] Borovitskiy, V., Azangulov, I., Terenin, A., Mostowsky, P., Deisenroth, M. P., and Durrande, N. (2021). Matérn Gaussian processes on graphs. In *International Conference on Artificial Intelligence and Statistics*. PMLR.

[5] Borovitskiy, V., Terenin, A., Mostowsky, P., and Deisenroth, M. P. (2020). Matérn Gaussian processes on Riemannian manifolds. In *Proceedings of Advances in Neural Information Processing Systems (NeurIPS)*.

[6] Breiman, L. (2001). Random forests. *Machine learning*, 45(1):5–32.

[7] Chen, T. and Guestrin, C. (2016). Xgboost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pages 785–794.

[8] Cheng, M.-Y. and Wu, H.-T. (2013). Local linear regression on manifolds and its geometric interpretation. *Journal of the American Statistical Association*, 108(504):1421–1434.

[9] Chew, L. P. (1989). Constrained Delaunay triangulations. *Algorithmica*, 4(1):97–108.

[10] Chipman, H. A., George, E. I., and McCulloch, R. E. (2010). BART: Bayesian additive regression trees. *The Annals of Applied Statistics*, 4(1):266–298.

[11] Deshpande, S. K., Bai, R., Balocchi, C., Starling, J. E., and Weiss, J. (2020). VCBART: Bayesian trees for varying coefficients. *arXiv preprint arXiv:2003.06416*.

[12] Di Marzio, M., Panzera, A., and Taylor, C. C. (2014). Nonparametric regression for spherical data. *Journal of the American Statistical Association*, 109(506):748–763.

[13] Dunson, D. B., Wu, H.-T., and Wu, N. (2020). Diffusion based Gaussian processes on restricted domains. *arXiv preprint arXiv:2010.07242*.

[14] Gneiting, T. and Raftery, A. E. (2007). Strictly proper scoring rules, prediction, and estimation. *Journal of the American statistical Association*, 102(477):359–378.

[15] Guella, J. C., Menegatto, V. A., and Porcu, E. (2018). Strictly positive definite multivariate covariance functions on spheres. *Journal of Multivariate Analysis*, 166:150–159.

[16] Guinness, J. and Fuentes, M. (2016). Isotropic covariance functions on spheres: Some properties and modeling considerations. *Journal of Multivariate Analysis*, 143:143–152.

[17] Hahn, P. R., Murray, J. S., and Carvalho, C. M. (2020). Bayesian regression tree models for causal inference: Regularization, confounding, and heterogeneous effects (with discussion). *Bayesian Analysis*, 15(3):965–1056.

[18] Hastie, T. and Tibshirani, R. (2000). Bayesian backfitting (with comments and a rejoinder by the authors). *Statistical Science*, 15(3):196–223.

[19] Henry, G. and Rodriguez, D. (2009). Robust nonparametric regression on Riemannian manifolds. *Journal of Nonparametric Statistics*, 21(5):611–628.

[20] Jeong, J. and Jun, M. (2015). A class of Matérn-like covariance functions for smooth processes on a sphere. *Spatial Statistics*, 11:1–18.

[21] Kpotufe, S. (2011). k-NN regression adapts to local intrinsic dimension. In Shawe-Taylor, J., Zemel, R., Bartlett, P., Pereira, F., and Weinberger, K. Q., editors, *Advances in Neural Information Processing Systems*, volume 24. Curran Associates, Inc.

[22] Lai, M.-J. and Schumaker, L. L. (2007). *Spline functions on triangulations*, volume 110. Cambridge University Press.

[23] Li, F. and Sang, H. (2019). Spatial homogeneity pursuit of regression coefficients for large datasets. *Journal of the American Statistical Association*, 114(527):1050–1062.

[24] Lin, L., Mu, N., Cheung, P., and Dunson, D. (2019). Extrinsic Gaussian processes for regression and classification on manifolds. *Bayesian Analysis*, 14(3):887–906.

[25] Lindgren, F., Rue, H., and Lindström, J. (2011). An explicit link between Gaussian fields and Gaussian Markov random fields: the stochastic partial differential equation approach. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 73(4):423–498.

[26] Linero, A. R. and Yang, Y. (2018). Bayesian regression tree ensembles that adapt to smoothness and sparsity. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 80(5):1087–1110.

[27] Luo, Z. T., Sang, H., and Mallick, B. (2021). A Bayesian contiguous partitioning method for learning clustered latent variables. *Journal of Machine Learning Research*, 22(37):1–52.

[28] Madrid Padilla, O. H., Sharpnack, J., Chen, Y., and Witten, D. M. (2020). Adaptive nonparametric regression with the k-nearest neighbour fused lasso. *Biometrika*, 107(2):293–310.

[29] Menafoglio, A., Gaetani, G., and Secchi, P. (2018). Random domain decompositions for object-oriented kriging over complex domains. *Stochastic environmental research and risk assessment*, 32(12):3421–3437.

[30] Meng, D., Leung, Y., Xu, Z., Fung, T., and Zhang, Q. (2008). Improving geodesic distance estimation based on locally linear assumption. *Pattern Recognition Letters*, 29(7):862–870.

[31] Murray, J. S. (2020). Log-linear Bayesian additive regression trees for multinomial logistic and count regression models. *Journal of the American Statistical Association*, (just-accepted):1–35.

[32] Niu, M., Cheung, P., Lin, L., Dai, Z., Lawrence, N., and Dunson, D. (2019). Intrinsic Gaussian processes on complex constrained domains. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 81(3):603–627.

[33] Pelletier, B. (2006). Non-parametric regression estimation on closed Riemannian manifolds. *Journal of Nonparametric Statistics*, 18(1):57–67.

[34] Ramsay, T. (2002). Spline smoothing over difficult regions. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 64(2):307–319.

[35] Ročková, V. and Saha, E. (2019). On theory for BART. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 2839–2848. PMLR.

[36] Ročková, V. and van der Pas, S. (2020). Posterior concentration for Bayesian regression trees and forests. *Annals of Statistics*, 48(4):2108–2131.

[37] Sangalli, L. M., Ramsay, J. O., and Ramsay, T. O. (2013). Spatial spline regression models. *Journal of the Royal Statistical Society: Series B: Statistical Methodology*, pages 681–703.

[38] Scott-Hayward, L. A. S., MacKenzie, M. L., Donovan, C. R., Walker, C., and Ashe, E. (2014). Complex region spatial smoother (CReSS). *Journal of Computational and Graphical Statistics*, 23(2):340–360.

[39] Sivaganesan, S., Müller, P., and Huang, B. (2017). Subgroup finding via Bayesian additive regression trees. *Statistics in medicine*, 36(15):2391–2403.

[40] Teixeira, L. V., Assunção, R. M., and Loschi, R. H. (2019). Bayesian space-time partitioning by sampling and pruning spanning trees. *Journal of Machine Learning Research*, 20:85–1.

[41] Tenenbaum, J. B., De Silva, V., and Langford, J. C. (2000). A global geometric framework for nonlinear dimensionality reduction. *science*, 290(5500):2319–2323.

[42] Wang, H. and Ranalli, M. G. (2007). Low-rank smoothing splines on complicated domains. *Biometrics*, 63(1):209–217.

[43] Wood, S. N. (2006). *Generalized Additive Models: An Introduction with R*. Chapman & Hall/CRC, Boca Raton, Florida, first edition. ISBN 1-58488-474-6.

[44] Wood, S. N., Bravington, M. V., and Hedley, S. L. (2008). Soap film smoothing. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 70(5):931–955.