MultiScan: Scalable RGBD scanning for 3D environments with articulated objects

Figure 1: MultiScan offers 3D reconstructions of indoor scenes with multiple scans, capturing objects in multiple states, and with multiple levels of annotations. For each scene, we provide multiple scans (leftmost column) with objects in varied states (second column). Each scan is densely annotated with semantic object instances (third column) that are corresponded across scans. Each object is annotated with parts and part articulation parameters (fourth column). Different scans capture objects in different articulation states (e.g., the cabinet door is opened in the bottom row). The MultiScan pipeline and dataset enable investigation of holistic 3D scene understanding with articulated objects by supporting tasks that reason at multiple levels of a 3D scene (rightmost column).

Abstract

We introduce MultiScan, a scalable RGBD dataset construction pipeline leveraging commodity mobile devices to scan indoor scenes with articulated objects and web-based semantic annotation interfaces to efficiently annotate object and part semantics and part mobility parameters. We use this pipeline to collect 230 scans of 108 indoor scenes containing 9458 objects and 4331 parts. The resulting MultiScan dataset provides RGBD streams with per-frame camera poses, textured 3D surface meshes, richly annotated part-level and object-level semantic labels, and part mobility parameters. We validate our dataset on instance segmentation and part mobility estimation tasks and benchmark methods for these tasks from prior work. Our experiments show that part segmentation and mobility estimation in real 3D scenes remain challenging despite recent progress in 3D object segmentation.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

1 Introduction

Datasets of 3D indoor environments are increasingly used for computer vision, robotics, and machine learning. ScanNet [7] and Replica [37] enabled much work on 3D semantic segmentation and object detection. Gibson [45] and Matterport3D [3] enabled work on vision-and-language, visual navigation, and many other embodied AI tasks. Even though the impact of such work is high, efforts are few and far between, typically limited by the availability of usable hardware and software infrastructure, and the significant time commitment required for data collection and annotation.

Moreover, these real-world 3D reconstruction datasets are not interactive. Reconstructions capture a static scene, providing a "frozen in time" snapshot that does not allow the kinds of rich interactions possible in the real world (e.g., opening and closing kitchen cabinetry). Thus, existing real scene datasets do not contain information about how objects can be rigidly moved and how object parts can articulate to open and close.

To address this challenge, we design MultiScan, a scalable 3D environment acquisition pipeline based on commodity devices (smartphones and tablets). Our pipeline allows for collection of and processing of raw RGBD data to produce 3D surface mesh reconstructions with textures. Rapid turnaround times for processing paired with a set of web-based annotation interfaces for semantic annotation at both object and part levels and annotation of part mobility parameters allow for efficient and scalable construction of articulated, real-world 3D scene datasets.

Using our software infrastructure, we collect a dataset of diverse real interiors each scanned at multiple points in time. Multiple scans per interior allow us to annotate and correspond objects that move rigidly and object parts that articulate. Unlike prior work on static 3D reconstruction datasets, we capture container interiors (cabinetry, fridges etc.) and collect multiple observations of the same objects and object parts in different states. These properties of the dataset allow us to carry out a dense multi-scale semantic annotation at the scene, object, and part levels.

We use the MultiScan dataset to systematically benchmark tasks at several levels (object segmentation, part segmentation and motion estimation) and evaluate the consistency of approaches for these tasks between scans of the same scene. We show that current methods for each of these tasks exhibit prevalent failure modes and leave much space for improvement. Moreover, consistency of predictions across observations of the same scene is low, showing that there is much work to be done to achieve consistent holistic 3D scene understanding.

In summary, we contribute: 1) a scalable real-world 3D environment acquisition and annotation pipeline; 2) a dataset of densely annotated 3D interiors with object, part, and part mobility annotations; 3) a systematic benchmark of methods for object and part segmentation and mobility estimation.

2 Related Work

We summarize related work on semantically annotated real-world scenes and interactive (i.e. articulated) objects. See Table 1 for a comparison against relevant prior work.

Reconstructed 3D environments. Existing reconstructed indoor environments are limited in multiple observations of the same scene, object part level and mobility information. SceneNN [13], ScanNet [7] and Replica [37] contain mostly single room scale reconstructions with dense semantic object annotations on mesh vertices. ARKitScenes [8] is the largest room-scale 3D dataset with 5,048 scans of 1,661 unique scenes but only 3D object bounding boxes are annotated. Matterport3D [3], Gibson [45], and HM3D [33] are all building-scale 3D datasets. Only Matterport3D [3] has manual semantic annotations at the object level. Armeni et al. [2] offer semi-automatic annotations based on MaskRCNN [11] for a limited number of categories in a subset of Gibson [34] scenes. Unlike our work, none of these datasets extend object level annotations to the object part and part motion levels.

The ScanNet [7] dataset contains several scans of the same environments. However, there was no control for whether objects are moved and no explicit mapping between object instances in different scans. RIO [41] and Rescan [9] both capture multiple scans of each environment with objects moved around and corresponded across scans. However, they do not capture or annotate articulated objects with different articulation states. To the best of our knowledge, our work provides the first dataset capturing a scene with multiple scans at multiple points in time, with multiple states, and multiple levels of semantic annotation at the object, object part, and part motion levels.

Dataset	Scenes	Scans	Objects	Parts	RGBD	Multi-state	Part articulations	Scene-obj-part hierarchy
SceneNN [13]	100	100	1667	✗	✓	✗	✗	✗
Replica [37]	18	35	2843	✗	✗	✗	✗	✗
ScanNet [7]	707	1513	36213	✗	✓	✗	✗	✗
Matterport3D [3]	90	90	50851	✗	✓	✗	✗	✗
ARKitScenes [8]	1661	5048	67791	✗	✓	✗	✗	✗
Rescan [9]	13	45	1021	✗	✓	✓	✗	✗
3RScan [41]	478	1482	43006	✗	✓	✓	✗	✗
OPDReal [18]	—	—	231	787	✓	✓	✓	✗
AKB-48 [25]	—	—	2037	≈4074	✗	✗	✓	✗
MultiScan	108	230	9458	4331	✓	✓	✓	✓

Table 1: Comparison of semantically-annotated real-world scene and articulated object datasets. MultiScan provides semantic annotations at both the object and part levels, unlike prior work. In addition, articulated parts are annotated with motion parameters and multiple scans capture the scene at different points in time with objects in varying articulation states (multi-state). Raw RGBD video sensor streams are also preserved. Unlike datasets that focus on single objects [18, 25], MultiScan objects are observed in scenes with realistic context, and annotated hierarchically (scene-obj-part).

Interactive environments and objects. Current methods for obtaining interactive environments suffer from a lack of scalability. Typically datasets with interactive scenes consist of synthetic assets designed by artists from scratch [22, 31, 48], or based on real world reconstructions [38]. Some prior work [10, 34] creates functionally-equivalent interactive scenes by basing the arrangement of objects on semantically annotated 3D reconstructions and replacing scanned objects with objects from existing synthetic datasets [42, 46]. Instead, we directly annotate articulations on the reconstructed objects, so that objects have more realistic and varied geometry and textured appearance.

The datasets of articulated objects that the above prior work draws upon are also limited in scale and quality, consisting mostly of synthetic 3D models [12, 42, 46, 49]. Martín-Martín et al. [28] created the RBO dataset consisting of 14 real-world articulated objects. More recently, larger datasets of real-world articulated objects were introduced with AKB-48 [25] focusing on small tabletop objects and OPDNet [18] on objects with openable parts. All three datasets are limited to isolated objects that are not arranged in scenes. We collect a dataset of 3D indoor environments with articulated objects. This allows for the study of holistic understanding of articulated objects in real scenes.

Reconstruction of articulated objects. Reconstruction of dynamically changing scenes is a challenging research problem. There is some recent work on reconstructing scenes in the presence of a few rigidly moving objects [44], but scenes with object articulations such as kitchen cabinetry remain challenging to reconstruct due to severe occlusions and partial observation in the presence of a manipulating human. Recently, there has been increasing interest in predicting part mobility from 3D meshes [12], single point clouds [23, 42, 49], multiple point clouds [35, 36], images [1, 18, 51], and depth sequences [15, 16]. Identifying movable parts and motion parameters for articulated objects that are statically reconstructed is a strategy for bypassing dynamic reconstruction. However, static reconstruction methods cannot directly handle multiple scans of the same object in different articulation states. To address this, flow-based methods to correspond points from multiple point clouds have been proposed [14, 50]. Other work jointly predicts motion and performs reconstruction by using implicit functions [20, 29, 43, 52] or neural radiance fields [39]. All the above work focuses on mobility prediction for isolated single articulated objects, and does not consider the placement of the objects in a realistic 3D environment. Moreover, these recent advances were enabled in part by the availability of articulated object datasets [42, 46]. As a step toward encouraging more work in this direction at the scene level, we provide the first dataset of articulated real-world scenes.

3 Approach

We follow an approach similar to the ScanNet [7] data collection pipeline for acquiring and semantically annotating 3D reconstructions of indoor environments. Key differences are that our framework produces: 1) textured meshes with dense semantic annotations on mesh triangles (vs only at vertex points); 2) multi-level hierarchical annotations of object instances and parts; 3) object articulation and motion annotations; and 4) correspondences between instances in scans of the same scene. Our pipeline also provides data collection apps for iOS and Android commodity devices.

Figure 2: Overview of the MultiScan pipeline. During **acquisition** we use mobile devices to collect RGBD sequences and camera trajectories in a given scene. Then, in the **processing** stage we reconstruct aligned textured 3D meshes and compute an unsupervised multi-scale segmentation that will be used for annotation. During **annotation** we use a set of web-based interfaces to semantically annotate object and part instances in each scan, and part articulation parameters.

Figure 2 illustrates the MultiScan reconstruction and annotation pipeline. The iOS and Android scanning apps we developed use built-in LiDAR sensors, stereo camera pairs, or single RGB cameras with monocular depth estimation (Section 3.1). This allows us to acquire scans with a variety of devices and sensor types. We then carry out RGBD fusion to produce the 3D mesh geometry and compute textures for the geometry using the aligned RGBD image sequence (Section 3.2). We semantically annotate object instances in each scan, correlating instances across scans of the same scene, and specifying articulated parts and their motion parameters (Section 3.3).

3.1 Acquisition

We developed scanning applications for iOS and Android mobile devices. These applications capture RGB, depth, depth confidence and IMU sensor streams, as well as camera pose trajectories. An associated UI allows the operator to specify metadata (scene description etc.), and to upload the scan to a server for reconstruction (see supplement for details). A web interface is also available to browse all uploaded data and check reconstruction quality to determine if scanning again is required.

To create the dataset in this paper, five volunteers used the iOS scanning app with three iPad Pro 2020 and two iPhone12 Pro devices to collect scans from residences, schools, and public spaces in several geographic locations in Canada, the United States, and China. Consent was obtained from the volunteers and from space owners for any non-public spaces that were scanned. No people or personally identifiable information was scanned. During scanning, users move freely through the scene with the device in hand and record an RGBD video. Each scene is scanned multiple times after objects and their parts are moved to different configurations. During the first scan, most of the articulated objects (e.g. drawers and cabinets) are left in a closed state. For additional scans, we open parts such as drawers and cabinets, and reposition objects that are commonly moved during daily use (e.g., chairs, pillows, kitchen utensils) to obtain scans of the scene in a different state.

Collected data are captured at 60 Hz with synchronized device timestamps allowing for alignment between data modalities. RGB video frames have a resolution 1920x1440, while depth and depth confidence frames are 256x192. In total, we captured about 3.84M frames (17.7 hours) of RGBD video data. The median scan duration is about 15.6K frames (4.3 minutes).

3.2 Processing

We first filter the recorded depth frames in a pre-processing step. Depth acquired with mobile devices typically contains noise and outliers that introduce artifacts during reconstruction. To ensure that we only consider high-quality depth values, we keep only depth values with high-confidence depth estimates. We also filter out pixels where depth changes by more than 5cm between adjacent frames.

We fuse depth frames into a Truncated Signed Distance Field (TSDF) volume using the camera trajectory captured from the device, and extract a surface mesh reconstruction using the marching cubes algorithm [26] from Open3D [53]. We use a voxel size of 9.77 mm, and a truncation value of 0.08m. We simplify the surface mesh using InstantMeshes [17] to reduce the total number of vertices and faces. Then, we clean the mesh using MeshLab [6] to remove isolated components and degenerate faces, and to align scans of each scene to a common coordinate frame. We then generate textures for the surface mesh using the multi-view stereo texturing approach of Waechter et al. [40].

The textured mesh preserves high frequency color details on the surface geometry, allowing us to distinguish and annotate kitchen cabinetry, plates etc. that would otherwise be merged into other surfaces.

To enable efficient annotation, the resulting mesh is segmented using an unsupervised hierarchical graph-based segmentation algorithm as employed by ScanNet [7], treating the triangle mesh as a connected graph with mesh vertices (or faces) at the nodes, and mesh edges (or face-face adjacency edges) at the edges. We create a coarse and fine segmentation. The coarse segmentation uses only mesh vertex normal or face normal differences to compute edge weights for the graph cut algorithm. The fine segmentation also includes RGB colors to break coarse clusters based on surface appearance.

The processing steps above are done automatically for each uploaded scan on a processing server (Intel i9-10900F CPU, 32GB RAM, Nvidia RTX 3090Ti GPU). The median processing time per scan is approximately 8 minutes, with initial surface reconstructions typically being available for viewing on a web portal within about a minute. The relatively fast turnaround time enables repeated scanning at each location, and scalability of the pipeline with commodity devices and novice operators.

3.3 Annotation

Our annotation framework consists of several phases: 1) reconstruction quality check and scan alignment; 2) semantic annotation of objects and parts; 3) motion annotation; and 4) verification. We densely annotate objects in the scene with object and part labels, also defining a semantic front and up direction for each object to produce semantically-oriented bounding boxes (OBBs) that give the pose of the object in each scene. Object and part instances are correlated across scans of the same scene with consistent object and part IDs. Unlike prior work on semantic annotation tools for 3D reconstructions [7], our pipeline allows for fine-grained triangle-based annotation in addition to pre-segmented clusters. Our motion parameter annotation tools allow for annotating semantically meaningful motion ranges (consistently defined opened and closed state values in a motion range), unlike related prior work [46, 47]. See the supplement for more implementation details.

4 Dataset

In this section, we describe the MultiScan dataset and provide summary statistics of the scene, object, and part level annotations. MultiScan includes 230 scans of 108 indoor scenes across 11 scene types, with at least 2 scans per scene for 91 scenes.[1] The spaces captured in the MultiScan dataset are mostly single rooms with the size of a room ranging from a small bathroom or laundry room to large living rooms and library rooms. In rescans of the same scene, the states of articulated objects and the positions of movable objects are changed. We define an articulated object to be an object consisting of rigid parts that are connected by joints, and a movable object to be an object that is not attached to the architecture, and small enough to be easily moved.

Overall, 9458 total object instances were annotated, of which 1721 are architectural elements (wall, ceiling, floor), 7737 are non-architectural objects, and 979 are articulated objects. We annotated a total of 4331 parts, out of which 2568 were moving parts (1742 exhibiting rotation, and 826 translation). During annotation, annotators used 437 fine-grained category names that were later grouped into coarser labels for our benchmark tasks. The supplement provides more statistics including the distributions over room categories, object and part categories, and number of parts per object.

The scans were annotated by 8 student volunteers. Annotation took on average 1h and 22m per scan with the bulk being spent on semantic segmentation (approximately 1hr and 12min for segmentation, 9min for articulation, and 1min for semantic OBBs). Verification was performed by the authors (~10min per scan, with 6min for segmentation, 3min for articulation, and 1min for OBB verification).

5 Experiments

We showcase the value of our dataset on the following tasks: 3D instance segmentation of objects and parts, and articulated object mobility prediction, evaluating recent methods for each task. We

---

[1]Some rescans did not result in acceptable reconstructions.

Table 2: Object instance segmentation results on the val set. Values are mean AP scores. All methods have fairly low scores for most categories, except chairs and toilets which are frequent and distinctive objects. SSTNet has the best overall performance, followed by HAIS and PointGroup.

	all	door	table	chair	cab	win	sofa	pillow	tv	curt	bin	sink	bpk	bed	fridge	toilet
PointGroup [19]	22.9	24.0	36.4	67.6	7.3	**12.2**	24.7	6.7	27.1	1.6	27.0	37.2	**2.0**	38.0	3.4	74.9
SSTNet [24]	**29.9**	**24.6**	**49.8**	**71.3**	**7.8**	6.9	36.4	**16.9**	**53.3**	0.1	**40.6**	**45.5**	**2.0**	**49.6**	**21.5**	**81.5**
HAIS [4]	23.7	20.5	33.7	67.5	4.3	9.0	**36.5**	11.7	37.5	**5.4**	35.1	40.0	0.0	49.3	9.5	42.6

Table 3: Part instance segmentation results on the val set. Values are AP scores using ground-truth (left) and predicted (right) object instance segmentation. When using predicted objects, we use the same method for both object and part segmentation. The simpler PointGroup method outperforms SSTNet and HAIS for part segmentation.

	Ground-truth segmentation						Predicted segmentation					
	all	static	door	drwr	win	lid	**all**	static	door	drwr	win	lid
PointGroup [19]	**29.9**	51.8	**21.8**	**12.8**	**12.4**	**50.7**	**11.9**	3.1	6.4	**5.9**	0.0	**44.0**
SSTNet [24]	28.4	55.6	19.2	**12.8**	12.1	42.2	11.1	**5.5**	6.5	2.0	**8.1**	33.3
HAIS [4]	28.5	**59.1**	21.0	10.4	10.4	41.8	9.2	2.5	**6.6**	4.6	0.0	32.4

also introduce and measure object detection consistency across multiple scans for the same scene. We include results and examples for the val set in the main paper, and the test set in the supplement.

Task dataset preparation. We benchmark several point-cloud based methods on our MultiScan dataset. To get per-point semantic labels from our triangle based annotation, we assign the same semantic label to the three vertices of each triangle. We select the top 17 most common object categories, excluding room architecture (floor, wall, beam, etc.) and small objects (bounding box volume below $0.008 \ m^3$, slightly smaller than a pillow). For part segmentation and mobility prediction, we predict articulated parts from objects extracted from a scene, and use either the ground truth or predicted object segmentation. To ensure that extracted objects have sufficient point samples, if an object has fewer than 4096 points we sample additional points from the surface mesh distributed uniformly based on triangle area. To allow for reproducible benchmarks, we split the data into approximately 70/15/15% train/val/test sets partitioned by scene (see supplement for statistics).

5.1 Object and part instance segmentation

We compare three methods with good performance on the ScanNet benchmark [7]: PointGroup [19], SSTNet [24], and HAIS [4]. All three methods rely on a SparseConv UNet backbone network for extracting per-point features, that are then clustered and scored. SSTNet [24] and HAIS [4] build on PointGroup [19] with hierarchical grouping of points into object instances. Object segmentation is done with the 17 most common categories, while part segmentation is done with common moving part categories (door, drawer, window, lid) and the static base part.

Implementation details. For each method, we apply the same settings for both object and part segmentation experiments. In our experiments, we use point clouds with position (xyz) and color (rgb) information. For SSTNet [24] and HAIS [4], we train using the original implementations with a learning rate of 1e-3, AdamW [27] and Adam [21] as the optimizer, respectively. For PointGroup [19], we train using a re-implementation with Minkowski Engine [5] as the backbone with a learning rate of 2e-3 and Adam [21] as the optimizer. We apply data augmentation during training for all three methods: random jitter and mirror in the horizontal plane. We train all methods on the MultiScan train split for 512 epochs. We set batch size 4 and 16 for object and part segmentation, respectively.

Metrics. We report AP, the average of mean Average Precision over different IoU thresholds from 0.5 to 0.95. See the supplement for the AP scores at IoU thresholds of 0.25 and 0.5 (AP_{25} and AP_{50}).

Results. We report the performance of the three methods on object (Table 2) and part instance segmentation (Table 3). For object-level segmentation, we see a similar trend as the ScanNet benchmark [7] with SSTNet [24] and HAIS [4] performing better than PointGroup [19]. Note we omit from Table 2 categories (suitcase, microwave) that appear rarely (<2 instances), as all methods performs poorly and fail to predict these objects. We also observe that these three models

Table 4: Breakdown of part instance segmentation for open and closed parts on the val set. Overall, all three method perform better for open parts. For `door` and `drawer` the part is easier to detect when opened, but for `window` and `lid`, it is easier when it is closed. Windows are likely challenging opened as the window surface would not be there (e.g., parallel sliding windows). The `lid` category mostly represents toilet lids which are against the base when closed and against the water tank when opened. Both cases are challenging, with the closed case likely more prevalent in our data.

	Opened parts				Closed parts				
	all	door	drwr	win	lid	**all**	door	drwr	win	lid
PointGroup [19]	20.9	19.6	40.0	0.0	**24.1**	28.5	**13.2**	0.2	**34.0**	66.7
SSTNet [24]	**21.7**	30.1	**43.4**	0.0	13.3	**30.1**	9.4	0.0	33.3	**77.8**
HAIS [4]	19.8	**34.6**	27.2	0.0	17.2	26.3	9.1	**1.1**	28.5	66.7

Input	GT	PointGroup [19]	SSTNet [24]	HAIS [4]

Figure 3: Object instance segmentations on val set. We show two scans of the same scene with objects in different states. Objects with color matching the ground-truth (GT) are correctly predicted instances. Objects with different colors indicate incorrect semantic labels. We see that object instance segmentation is quite challenging for real articulated scenes. All methods struggle to segment the kitchen cabinet at the top, and the fridge is only correctly predicted by SSTNet.

have better performance on large and typical-looking objects with few variations in appearance, such as toilets, beds and doors. In contrast, all methods struggle on small objects such as backpacks, pillows and suitcases. We find that refrigerators and microwaves are challenging as often they are embedded in cabinets and poorly reconstructed. Figure 3 shows example object instance predictions.

For part-level segmentation, we first extract the points for the object from the scene mesh and then center and align the points. We experiment with using both ground-truth object instances as well as predicted object instances. In both cases, we align and center the extracted points using the ground-truth semantic up/front directions. From Table 3, we find that the simpler PointGroup [19]

Input	GT	PointGroup [19]	SSTNet [24]	HAIS [4]

Figure 4: Part instance segmentation for two states of a kitchen cabinetry unit from the val set. Note that it is challenging to segment the boundary of the cabinet doors in the closed state (top). The static part (interior) is also largely unobserved in the closed state.

Table 5: Object instance segmentation consistency on val set. SSTNet provides the most consistent object segmentations across scans of the same scene. Office scenes are overall easiest, while bathroom and kitchen scenes are quite challenging likely due to the prevalence of hard-to-segment cabinetry.

	all	bath	bed	bks/lib	hall	kitchen	laundry	living	office	misc.
PointGroup [19]	45.38	27.50	**41.98**	47.88	36.67	30.10	66.67	51.67	88.17	12.50
SSTNet [24]	**51.11**	**31.25**	41.73	**56.35**	**39.44**	**40.98**	**75.00**	**57.50**	**96.88**	**18.75**
HAIS [4]	41.32	10.00	32.21	52.78	33.89	29.90	66.67	49.17	81.92	12.50

Table 6: Mobility estimation on the val set comparing OPDPN [18] and Shape2Motion [42] on objects extracted using ground-truth (GT) and predicted segmentations from SSTNet [24].

seg	method	IoU↑	EPE↓	MD↓	OE↓	TA↑	Movable part			Motion type			Motion+Axis			Motion+Axis+Origin		
							R	P	F1	R	P	F1	R	P	F1	R	P	F1
GT	OPDPN	62.36	**0.6578**	**0.3310**	5.707	**100.00**	4.74	11.89	6.77	4.74	11.89	6.77	4.46	11.19	6.37	3.34	8.39	4.78
GT	S2M	**69.25**	0.8026	0.3907	6.543	86.00	16.43	**53.15**	**25.11**	11.98	**21.18**	**15.30**	11.14	**19.70**	**14.23**	6.13	**10.84**	7.83
GT	S2M (aug)	68.80	0.6652	0.3427	**0.493**	96.77	**17.27**	20.88	18.90	**16.71**	11.13	13.36	**16.71**	11.13	13.36	**11.42**	7.61	**9.13**
SSTNet	S2M	**71.93**	0.9659	0.4675	5.552	94.44	19.57	**20.00**	**19.71**	4.74	**19.54**	7.62	4.46	**18.39**	7.17	2.51	**10.34**	4.04
SSTNet	S2M (aug)	70.32	**0.5647**	**0.2836**	0.521	**100.00**	**20.36**	16.92	17.82	**7.24**	10.92	**8.71**	**7.24**	10.92	**8.71**	**5.01**	7.56	**6.03**

outperforms both SSTNet [24] and HAIS [4] for part segmentation. This may be due to extra parameters that need to be tuned for part-level segmentation for the other methods. Part-level segmentation is also challenging due to small parts and fine-grained details (e.g., thin edges of doors, or door handles). With ground-truth object segmentation, the methods do a fair job at predicting the static part, but fail miserably when using predicted object segmentations. In particular, static part segmentation drops considerably with predicted segmentations. Table 4 shows that `door` and `drawer` are more challenging in the closed state that in the open state, while the opposite holds for `window` and `lid`. In the closed state it is challenging to identify boundaries between adjacent doors (see Figure 4) and identify the static part, which is largely occluded. These results indicate that part segmentation at the scene level would be quite challenging. In initial experiments for direct part segmentation at the scene level (without predicting object instances first), we saw even poorer results.

Segmentation consistency. We also evaluate the consistency of segmentation across scans of the same scene. For a scene with K scans, we define $C_{\text{scene}}(S)$, the consistency score for a scene S, to be the average consistency between each pair of scans (s_i, s_j) for the scene. The overall consistency score C is then the average over the scenes. To compute $C_{\text{scan}}(s_i, s_j)$, we consider the M_{ij} objects that are common between two scans, and evaluate whether each ground truth object instance o_m has an instance segmentation prediction. For each object o_m, we check if o_m has a prediction in both s_i and s_j. We match predicted objects to ground truth by taking the predicted object with the highest IOU > 0.5 for each ground truth object. We enforce that at most one predicted object is matched to each ground truth object. The consistency score of the scan is the average over the M_{ij} objects in the scene that are shared between the two scans. We report the object segmentation consistency across scans in Table 5. We note that SSTNet [24] gives the highest consistency scores.

5.2 Mobility Prediction

As a key feature of MultiScan is the annotation of motion parameters for real-world objects, we benchmark methods for part mobility estimation. We compare two category-agnostic methods that operate on point clouds: Shape2Motion (S2M) [42] and OPDPN [18]. Both use a PointNet++ [32]-backbone. Note that unlike the part instance segmentation task, we do not differentiate between the semantic label of the moving parts (i.e. a part is either `moving` or `static`). Given an input point cloud $Q = \{q_i \in \mathbb{R}^3\}_{i=1}^N$, we predict the part for each point, and the motion parameters for each part, by outputting the set of moving parts $P = \{p_k\}_{k=1}^K$, and their joint parameters $J = \{j_k\}_{k=1}^K$. We assume each moving part p_k is associated with a single joint $j_k = \langle t_k, a_k, o_k, \rangle$ with joint type $t_k = \{\texttt{rotation}, \texttt{translation}\}$, joint axis direction $a_k \in \mathbb{R}^3$, and joint origin $o_k \in \mathbb{R}^3$.

Implementation details. We use the released implementation of OPDPN and train using the Adam optimizer with learning rate of 0.001, batch size 32 for 600 epochs. We reimplement S2M in PyTorch. Compared to the original implementation, our re-implementation is faster and easier to run, and gives comparable performance (see supplement). We train MPN (1st stage of S2M) with batch size 8 for 500 epochs, PMM (2nd stage) with batch size 16 for 100 epochs. and MON (3rd stage) with batch size 8 for 100 epochs. All stages use Adam [21] with a learning rate of 0.001. As data augmentation

Table 7: Comparison of Shape2Motion [42] performance on open vs closed parts, evaluated on the val set with ground truth object instances.

State	IoU↑	EPE↓	MD↓	OE↓	TA↑	Movable part			Motion type			Motion+Axis			Motion+Axis+Origin		
						R	P	F1	R	P	F1	R	P	F1	R	P	F1
Closed	67.92	0.7189	0.3745	**42.97**	**97.87**	15.06	**18.88**	16.76	14.74	**9.47**	11.53	14.74	**9.47**	11.53	9.29	5.97	7.27
Opened	**71.55**	**0.4888**	**0.2431**	0.6818	93.33	**31.91**	15.79	**21.13**	**29.79**	8.24	**12.90**	**29.79**	8.24	**12.90**	**25.53**	**7.06**	**11.06**

267 for point positions we jitter and mirror in the horizontal plane, and for point color channels shift
268 randomly by a sample drawn from $\mathcal{N}(0, 0.0025)$ (RGB channels are normalized to [-1,1]).

269 **Metrics.** We evaluate the mobility predictions using two sets of metrics. Following
270 Shape2Motion [42], we report mean IoU, Endpoint Error (EPE), Minimum Distance (MD), Orienta-
271 tion Error (OE), and Motion Type Accuracy (TA) for matched parts. IoU measures the quality of the
272 movable part segmentation, while the other metrics measure motion parameter accuracy. EPE [30] is
273 used for 3D motion flow and measures the average distance between points of the moving part (we
274 take the ground-truth part segmentation) as the part is moved according to the predicted motion vs the
275 ground-truth motion (for rotation, the part is rotated to $180°$, and for translation, the part is moved
276 by 1m). MD and OE measure the minimum distance and the angle between the ground-truth axis
277 direction and the predicted motion axis. Note this set of metrics is computed over the matched parts
278 (with IOU>0.5). EPE, OE, and MD are all computed when the motion type is predicted correctly,
279 and MD is only computed for rotation (as only the direction is relevant for translational motions).
280 Because this set of metrics is only for matched parts it does not measure how many ground truth parts
281 are predicted or how many predicted parts are valid movable parts. Thus, we also report the recall
282 (R), precision (P), and F1 for predicting if a part is movable, the motion type, and whether it correctly
283 predicted the motion axis direction (OE$< 10°$) and origin (MD<0.25 of the diagonal of the object).

284 **Results.** We report the performance of OPDPN and S2M on extracted objects with ground truth and
285 predicted object segmentation (we use the best performing model SSTNet) in Table 6. Compared to
286 the synthetic S2M dataset, our MultiScan dataset is considerably more challenging due to partial and
287 noisy reconstructions. On the MultiScan dataset, we also experiment with different input features
288 and data augmentation (see supplement). Our experiments in the main paper are with position, color
289 and normal since our results show that including color consistently improves all metrics and that
290 using the normal is also helpful. The much simpler OPDPN performs slightly worse than S2M for
291 the matched parts. However, when we consider the recall, precision, and F1 metrics, we find that
292 the performance of OPDPN is considerably worse. Again, we note that parts that are in the closed
293 state are more challenging to detect than those in the open state (higher IoU and F1 in Table 7). The
294 MD is also lower for the opened parts, indicating that the joint origin is easier to detect when the part
295 is open. Interestingly, for the matched parts the orientation error for closed parts is lower than for
296 opened parts (lower OE in Table 7). See the supplement for qualitative examples.

6 Conclusion

298 **Limitations.** Though our focus was on scalable articulated scene acquisition we had access to a
299 limited number of spaces. Thus, our data exhibits biases in the types of scenes and types of objects
300 observed and does not capture the full diversity of real interiors. This may lead to negative societal
301 impacts due to under-representation of spaces for communities that are not geographically close to
302 us. Moreover, our reconstruction pipeline is limited by geometric resolution constraints making it
303 challenging to represent and annotate smaller parts and objects. Also, our experiments only evaluate
304 point-cloud based methods for segmentation and mobility estimation. Experiments with alternative
305 methods and settings may reveal different trends, and are an interesting direction for future work.

306 We described the design and implementation of MultiScan: a scalable articulated RGBD scene dataset
307 construction pipeline. We used this pipeline to scan interiors with multiple states of articulated and
308 rigidly-movable objects. We richly annotated the resulting dataset with multiple levels of semantic
309 and motion parameter information, at the scene, object, and part levels. Using this dataset, we
310 benchmarked methods for object and part instance segmentation, and part mobility estimation. We
311 found that segmentation and motion parameter estimation for articulated objects remain challenging
312 with much space for improvement. We believe MultiScan will catalyze work on holistic understanding
313 of interactive 3D environments and enable progress in perception for embodied AI and robotics.

References

[1] Ben Abbatematteo, Stefanie Tellex, and George Konidaris. Learning to generalize kinematic models to novel objects. In *Proceedings of the 3rd Conference on Robot Learning*, 2019.

[2] Iro Armeni, Zhi-Yang He, JunYoung Gwak, Amir R Zamir, Martin Fischer, Jitendra Malik, and Silvio Savarese. 3D scene graph: A structure for unified semantics, 3D space, and camera. In *Proc. of the International Conference on Computer Vision (ICCV)*, pages 5664–5673, 2019.

[3] Angel Chang, Angela Dai, Thomas Funkhouser, Maciej Halber, Matthias Niebner, Manolis Savva, Shuran Song, Andy Zeng, and Yinda Zhang. Matterport3D: Learning from RGB-D data in indoor environments. In *Proc. of the International Conference on 3D Vision (3DV)*, pages 667–676. IEEE, 2017.

[4] Shaoyu Chen, Jiemin Fang, Qian Zhang, Wenyu Liu, and Xinggang Wang. Hierarchical aggregation for 3D instance segmentation. In *Proc. of the International Conference on Computer Vision (ICCV)*, pages 15467–15476, 2021.

[5] Christopher Choy, JunYoung Gwak, and Silvio Savarese. 4D spatio-temporal convnets: Minkowski convolutional neural networks. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3075–3084, 2019.

[6] Paolo Cignoni, Marco Callieri, Massimiliano Corsini, Matteo Dellepiane, Fabio Ganovelli, and Guido Ranzuglia. MeshLab: an open-source mesh processing tool. In *Eurographics Italian Chapter Conference*. The Eurographics Association, 2008.

[7] Angela Dai, Angel X. Chang, Manolis Savva, Maciej Halber, Thomas Funkhouser, and Matthias Nießner. ScanNet: Richly-annotated 3D reconstructions of indoor scenes. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

[8] Afshin Dehghan, Gilad Baruch, Zhuoyuan Chen, Yuri Feigin, Peter Fu, Thomas Gebauer, Daniel Kurz, Tal Dimry, Brandon Joffe, Arik Schwartz, and Elad Shulman. ARKitScenes-a diverse real-world dataset for 3D indoor scene understanding using mobile RGB-D data. In *NeurIPS Datasets and Benchmarks*, 2021.

[9] Maciej Halber, Yifei Shi, Kai Xu, and Thomas Funkhouser. Rescan: Inductive instance segmentation for indoor RGBD scans. In *Proc. of the International Conference on Computer Vision (ICCV)*, pages 2541–2550, 2019.

[10] Muzhi Han, Zeyu Zhang, Ziyuan Jiao, Xu Xie, Yixin Zhu, Song-Chun Zhu, and Hangxin Liu. Reconstructing interactive 3D scenes by panoptic mapping and CAD model alignments. In *International Conference on Robotics and Automation (ICRA)*, 2021.

[11] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask R-CNN. In *Proc. of the International Conference on Computer Vision (ICCV)*, pages 2961–2969, 2017.

[12] Ruizhen Hu, Wenchao Li, Oliver Van Kaick, Ariel Shamir, Hao Zhang, and Hui Huang. Learning to predict part mobility from a single static snapshot. *ACM Transactions on Graphics (TOG), Proc. SIGGRAPH Asia*, 36(6):227, 2017.

[13] Binh-Son Hua, Quang-Hieu Pham, Duc Thanh Nguyen, Minh-Khoi Tran, Lap-Fai Yu, and Sai-Kit Yeung. SceneNN: A scene meshes dataset with annotations. In *Proc. of the International Conference on 3D Vision (3DV)*, pages 92–101. IEEE, 2016.

[14] Jiahui Huang, He Wang, Tolga Birdal, Minhyuk Sung, Federica Arrigoni, Shi-Min Hu, and Leonidas Guibas. MultiBodySync: Multi-body segmentation and motion estimation via 3D scan synchronization. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.

[15] Ajinkya Jain, Rudolf Lioutikov, and Scott Niekum. ScrewNet: Category-independent articulation model estimation from depth images using screw theory. *arXiv preprint arXiv:2008.10518*, 2020.

[16] Ajinkya Jain, Stephen Giguere, Rudolf Lioutikov, and Scott Niekum. Distributional depth-based estimation of object articulation models. In *Proc. of the Conference on Robot Learning (CoRL)*, pages 1611–1621. PMLR, 2022.

[17] Wenzel Jakob, Marco Tarini, Daniele Panozzo, and Olga Sorkine-Hornung. Instant field-aligned meshes. *ACM Transactions on Graphics (TOG), Proc. SIGGRAPH Asia*, 34(6), November 2015. doi: 10.1145/2816795.2818078.

[18] Hanxiao Jiang, Yongsen Mao, Manolis Savva, and Angel X Chang. OPD: Single-view 3D openable part detection. *arXiv preprint arXiv:2203.16421*, 2022.

[19] Li Jiang, Hengshuang Zhao, Shaoshuai Shi, Shu Liu, Chi-Wing Fu, and Jiaya Jia. PointGroup: Dual-set point grouping for 3D instance segmentation. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 4867–4876, 2020.

[20] Zhenyu Jiang, Cheng-Chun Hsu, and Yuke Zhu. Ditto: Building digital twins of articulated objects from interaction. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.

[21] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[22] Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Daniel Gordon, Yuke Zhu, Abhinav Gupta, and Ali Farhadi. AI2-Thor: An interactive 3D environment for visual AI. *arXiv preprint arXiv:1712.05474*, 2017.

[23] Xiaolong Li, He Wang, Li Yi, Leonidas Guibas, A Lynn Abbott, and Shuran Song. Category-level articulated object pose estimation. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[24] Zhihao Liang, Zhihao Li, Songcen Xu, Mingkui Tan, and Kui Jia. Instance segmentation in 3D scenes using semantic superpoint tree networks. In *Proc. of the International Conference on Computer Vision (ICCV)*, pages 2783–2792, 2021.

[25] Liu Liu, Wenqiang Xu, Haoyuan Fu, Sucheng Qian, Yang Han, and Cewu Lu. AKB-48: A real-world articulated object knowledge base. *arXiv preprint arXiv:2202.08432*, 2022.

[26] William E Lorensen and Harvey E Cline. Marching cubes: A high resolution 3D surface construction algorithm. *ACM siggraph computer graphics*, 21(4):163–169, 1987.

[27] Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

[28] Roberto Martín-Martín, Clemens Eppner, and Oliver Brock. The RBO dataset of articulated objects and interactions. *The International Journal of Robotics Research*, 38(9):1013–1019, 2019.

[29] Jiteng Mu, Weichao Qiu, Adam Kortylewski, Alan Yuille, Nuno Vasconcelos, and Xiaolong Wang. A-SDF: Learning disentangled signed distance functions for articulated shape representation. In *Proc. of the International Conference on Computer Vision (ICCV)*, pages 13001–13011, 2021.

[30] Michael Otte and H-H Nagel. Optical flow estimation: advances and comparisons. In *Proc. of the European Conference on Computer Vision (ECCV)*, pages 49–60, 1994.

[31] Xavier Puig, Kevin Ra, Marko Boben, Jiaman Li, Tingwu Wang, Sanja Fidler, and Antonio Torralba. VirtualHome: Simulating household activities via programs. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 8494–8502, 2018.

[32] Charles Ruizhongtai Qi, Li Yi, Hao Su, and Leonidas J Guibas. PointNet++: Deep hierarchical feature learning on point sets in a metric space. *Advances in neural information processing systems*, 30, 2017.

[33] Santhosh Kumar Ramakrishnan, Aaron Gokaslan, Erik Wijmans, Oleksandr Maksymets, Alexander Clegg, John M Turner, Eric Undersander, Wojciech Galuba, Andrew Westbury, Angel X Chang, Manolis Savva, Yili Zhao, and Dhruv Batra. Habitat-Matterport 3D Dataset: 1000 large-scale 3D environments for embodied AI. In *NeurIPS Datasets and Benchmarks*, 2021.

[34] Bokui Shen, Fei Xia, Chengshu Li, Roberto Martín-Martín, Linxi Fan, Guanzhi Wang, Claudia Pérez-D'Arpino, Shyamal Buch, Sanjana Srivastava, Lyne Tchapmi, et al. igibson 1.0: A simulation environment for interactive tasks in large realistic scenes. In *International Conference on Intelligent Robots and Systems*, 2020.

[35] Yahao Shi, Xinyu Cao, and Bin Zhou. Self-supervised learning of part mobility from point cloud sequence. In *Computer Graphics Forum*, volume 40, pages 104–116. Wiley Online Library, 2021.

[36] Yahao Shi, Xinyu Cao, Feixiang Lu, and Bin Zhou. P3-net: Part mobility parsing from point cloud sequences via learning explicit point correspondence. In *AAAI Conference on Artificial Intelligence*, 2022.

[37] Julian Straub, Thomas Whelan, Lingni Ma, Yufan Chen, Erik Wijmans, Simon Green, Jakob J Engel, Raul Mur-Artal, Carl Ren, Shobhit Verma, et al. The replica dataset: A digital replica of indoor spaces. *arXiv preprint arXiv:1906.05797*, 2019.

[38] Andrew Szot, Alex Clegg, Eric Undersander, Erik Wijmans, Yili Zhao, John Turner, Noah Maestre, Mustafa Mukadam, Devendra Chaplot, Oleksandr Maksymets, Aaron Gokaslan, Vladimir Vondrus, Sameer Dharur, Franziska Meier, Wojciech Galuba, Angel Chang, Zsolt Kira, Vladlen Koltun, Jitendra Malik, Manolis Savva, and Dhruv Batra. Habitat 2.0: Training home assistants to rearrange their habitat. *Advances in Neural Information Processing Systems*, 2021.

[39] Wei-Cheng Tseng, Hung-Ju Liao, Lin Yen-Chen, and Min Sun. CLA-NeRF: Category-level articulated neural radiance field. *arXiv preprint arXiv:2202.00181*, 2022.

[40] Michael Waechter, Nils Moehrle, and Michael Goesele. Let there be color! — Large-scale texturing of 3D reconstructions. In *Proc. of the European Conference on Computer Vision (ECCV)*. Springer, 2014.

[41] Johanna Wald, Armen Avetisyan, Nassir Navab, Federico Tombari, and Matthias Nießner. RIO: 3D object instance re-localization in changing indoor environments. In *Proc. of the International Conference on Computer Vision (ICCV)*, pages 7658–7667, 2019.

[42] Xiaogang Wang, Bin Zhou, Yahao Shi, Xiaowu Chen, Qinping Zhao, and Kai Xu. Shape2Motion: Joint analysis of motion parts and attributes from 3D shapes. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 8876–8884, 2019.

[43] Fangyin Wei, Rohan Chabra, Lingni Ma, Christoph Lassner, Michael Zollhoefer, Szymon Rusinkiewicz, Chris Sweeney, Richard Newcombe, and Mira Slavcheva. Self-supervised neural articulated shape and appearance models. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.

[44] Yu-Shiang Wong, Changjian Li, Matthias Nießner, and Niloy J Mitra. RigidFusion: RGB-D scene reconstruction with rigidly-moving objects. In *Proc. of the European Association for Computer Graphics (Eurographics)*, 2021.

[45] Fei Xia, Amir R. Zamir, Zhi-Yang He, Alexander Sax, Jitendra Malik, and Silvio Savarese. Gibson Env: real-world perception for embodied agents. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

[46] Fanbo Xiang, Yuzhe Qin, Kaichun Mo, Yikuan Xia, Hao Zhu, Fangchen Liu, Minghua Liu, Hanxiao Jiang, Yifu Yuan, He Wang, Li Yi, Angel X. Chang, Leonidas J. Guibas, and Hao Su. SAPIEN: A simulated part-based interactive environment. In *Proc. of the Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

[47] Xianghao Xu, David Charatan, Sonia Raychaudhuri, Hanxiao Jiang, Mae Heitmann, Vladimir Kim, Siddhartha Chaudhuri, Manolis Savva, Angel X Chang, and Daniel Ritchie. Motion annotation programs: A scalable approach to annotating kinematic articulations in large 3d shape collections. In *Proc. of the International Conference on 3D Vision (3DV)*, pages 613–622. IEEE, 2020.

[48] Claudia Yan, Dipendra Misra, Andrew Bennnett, Aaron Walsman, Yonatan Bisk, and Yoav Artzi. Chalet: Cornell house agent learning environment. *arXiv preprint arXiv:1801.07357*, 2018.

[49] Zihao Yan, Ruizhen Hu, Xingguang Yan, Luanmin Chen, Oliver Van Kaick, Hao Zhang, and Hui Huang. RPM-Net: recurrent prediction of motion and parts from point cloud. *ACM Transactions on Graphics (TOG), Proc. SIGGRAPH Asia*, 38(6):240, 2019.

[50] Li Yi, Haibin Huang, Difan Liu, Evangelos Kalogerakis, Hao Su, and Leonidas Guibas. Deep part induction from articulated object pairs. *ACM Transactions on Graphics (TOG), Proc. SIGGRAPH Asia*, 2018.

[51] Vicky Zeng, Timothy E Lee, Jacky Liang, and Oliver Kroemer. Visual identification of articulated object parts. In *International Conference on Intelligent Robots and Systems*, pages 2443–2450. IEEE, 2020.

[52] Ge Zhang, Or Litany, Srinath Sridhar, and Leonidas Guibas. StrobeNet: Category-level multiview reconstruction of articulated objects. *arXiv preprint arXiv:2105.08016*, 2021.

[53] Qian-Yi Zhou, Jaesik Park, and Vladlen Koltun. Open3D: A modern library for 3D data processing. *arXiv:1801.09847*, 2018.