Replication: Fairness without demographics through Adversarially Reweighted Learning

Reproducibility Summary

Scope of Reproducibility

We test the claim that Adversarially Reweighted Learning (ARL) improves Rawlsian Max-Min fairness for supervised classification compared to previous methods and simple baselines in the case of missing demographic data.

Methodology

We completely re-implemented all models and training routines in PyTorch, using the paper and the published code as a reference. We compared our implementation to the one provided by the authors and then reproduced the hyperparameter search as described in the paper using our implementation. In addition, we applied the method to image data, in order to test how well it generalizes across modalities.

Due to the general simplicity of the used models, it was straightforward to implement the code base from scratch and run the experiments. Parts of the experiments were run on a computing cluster with 12 CPUs and parts on Google Colab (GPU). Overall, it took 4 weeks to produce the results, with four people working on it. A complete grid search took 4 hours and producing the final results with fixed hyperparameters 5 hours, of which a single training run of one model on one dataset took about 2 minutes.

Results

We could not replicate the advantage of ARL over the investigated baselines. This seems to be mainly due to a better baseline performance than reported in the paper. Our baseline's performance is on average 2.615 standard deviations higher than the authors'. Our ARL results are not deviating significantly from the papers' result, they are on average 0.107 standard deviations higher.

What was easy

ARL itself was very easy to implement. We were also able to run the code provided by the authors quite easily. Running the experiments required little computational resources because of the small datasets and models.

What was difficult

Pre-processing the data took time because the notebooks provided by the authors contained some errors that we needed to debug. We had to replicate the grid search for hyperparameter optimization of all models on all dataset since the authors did not provide the hyperparameters they found by their grid search. We had to limit the training duration to a maximum of 5k steps in order to finish all experiments on time. Having to replicate the grid search was unnecessarily time-consuming and made it harder to compare our results.

Communication with original authors

We asked the authors about details regarding their training procedure. We tried to get in touch via email and openreview, but did not receive an answer by the submission deadline.

1   Introduction

As machine learning (ML) systems are increasingly often applied to high-stakes situations, it is becoming more important to ensure that they do not discriminate against groups of individuals based on features such as race and sex. Lahoti et al. present an approach called *Adversarially Reweighted Learning* (ARL) that aims to improve a model's performance measured according to the Rawlsian Max-Min fairness principle by reformulating the training procedure as an adversarial min-max game [1]. While previous work mainly addresses the case where protected features are part of the dataset, ARL does not require such information. As Lahoti et al. point out, such an approach is important because information about group membership is often sensitive and not available in many real-world scenarios, for example due to privacy concerns.

1.1   Replication of Main Experiments

The main empirical claim of Lahoti et al. is that ARL outperforms several other methods across several (tabular) datasets in terms of both performance and fairness. Their most important comparison models are Distributionally robust optimization (DRO) [2], inverse probability weighting (IPW) and a simple empiricial risk minimization baseline. The focus of our reproducibility study is therefore whether we can replicate an advantage of ARL over these methods.

We implemented all of the methods ourselves in PyTorch [3]. For ARL, IPW and the baseline, we mostly relied on the description in the paper and referred to the authors' TensorFlow [4] code where necessary. For DRO, we adapted the publicly available implementation to our framework. Our own code is available in the supplementary material.

Following the paper, we performed a grid search over hyperparameters. We report the performance of our own implementation on the same datasets as used by the authors, namely UCI Adult, LSAC and COMPAS. Based on our own results and the process of obtaining these, we evaluate the replicability of the paper. We pay special attention to the following criteria:

- Are our own results in line with the results reported by the authors?
- What challenges did we meet when replicating the authors' method?
- What differences exist between the authors' paper and their code?
- Can we support the explicit and implicit assumptions made by the authors to substantiate their method?

1.2   Additional Contributions

Given the tabular nature of the UCI Adult, LSAC and COMPAS datasets, the authors apply their method to fully-connected networks. Adversarial reweighting is, however, not limited to fully-connected networks, but serves as a general framework to modify optimization such that worst-case performance over unobserved protected groups is improved. We therefore applied the method to image data, in order to test how well it generalizes across modalities. For this, we trained a convolutional ARL on a custom image dataset based on EMNIST.

2   Methodology

2.1   Model Descriptions

ARL, DRO and IPW have in common that they modify the optimization objective in order to improve fairness. Even though the ARL introduces an additional adversary network to dynamically learn the exact form of this modification, the network architecture of the inference model is identical for all different methods. (Note that this does not transfer to the adversary network of ARL, which is not used for inference.)

For training on the UCI Adult, LSAC and COMPAS datasets, we used a simple fully-connected feed forward neural network. As in the paper, the network consists of two hidden layers with 64 and 32 units respectively, and ReLU activation functions applied after each hidden layer. For the given binary classification tasks, the output layer consists of one output unit.

Adversarially Reweighted Learning (ARL)

The key component to ARL is its adversarial setting. Concretely, a so-called *learner* is trained to minimize a task-specific loss function. Alternatingly, a so-called *adversary* is trained to reweight the loss terms that are produced by the

learner for each individual training sample in order to maximize the overall loss. Using θ and ϕ to respectively denote the parameters of the learner and the adversary, the overall training objective for n training samples is formulated as:

$$J(\theta, \lambda) := \min_\theta \max_\phi \sum_{i=1}^n \lambda_\phi(x_i, y_i)\ell(h_\theta(x_i), y_i),$$

where $\ell : \hat{Y} \times Y \to \mathbb{R}$ denotes the loss function of the underlying task and $h_\theta : X \to \hat{Y}$ denotes the function that is implemented by the learner. The weights $\lambda_\phi(X, Y)$ are produced by the adversary as follows:

$$\lambda_\phi(x_i, y_i) = 1 + n \cdot \frac{f_\phi(x_i, y_i)}{\sum_{j=1}^n f_\phi(x_j, y_j)},$$

where $f_\phi(x_i, y_i)$ is the adversaries output. During training, the adversary implicitly learns to identify areas in the input space that lead to high losses ℓ. By assigning higher weights to samples from these areas, it drives the learner towards improving in the identified subspaces. The authors claim that this ultimately leads to improved performance for protected groups whose sensible characteristic features are not included in the input data X, i.e. the groups that are identified by the adversary correspond to a certain degree to the groups that are to be protected.

We implemented the adversary with one linear layer, followed by a sigmoid function and the normalization, scaling and shifting as stated above. Instead of using the sum of single reweighted losses, we used the mean, following the authors' code. In their code they used two consecutive linear layers, which is not perfectly in line with the paper. Their code also reveals that the learner network was pretrained, which they do not mention in their paper.

Empiricial Risk Minimization (Baseline)

This model is identical to the learner in ARL. The authors note that they increased the number of hidden units in this model to compensate for the added capacity in form of the adversary in ARL. However, it was neither clear from the paper how they implemented this, nor evident from their code that they actually did. Going by parameter count, a single additional unit would already result in more parameters than for ARL. Since the simple fully-connected model did already match the performance of ARL (see Table 1), we did not investigate the effect of adding more units. The fully-connected model will also be referred to as 'baseline' in the rest of the text.

Inverse Probability Weighting (IPW)

Instead of learning the weights to reweight the loss function dynamically, a simpler approach is to weight each sample with the inverse probability of drawing this sample from the dataset. This gives underrepresented groups in the dataset a larger weight. In the IPW(S) approach, the probabilities are calculated based only on the membership to protected groups (e.g. "sex" or "race"), resulting in weights of the form $1/p(s)$. Additionally to the protected group we can take into account the label, resulting in a model called IPW(S+Y). Here, the probabilities are calculated as the joint probabilities of being in a certain protected group and belonging to a certain label (e.g. "being black" *and* "earning more than fifty thousand dollars a year"). This results in weights of the form $1/p(s, y)$.

IPW can only be used if group probabilities are known. It therefore offers a comparison of the ARL's claim of improving fairness *without* demographics to a method that improves fairness *with* demographics.

Distributionally Robust Optimization (DRO)

Similar to ARL, DRO aims to improve Rawlsian Max-Min Fairness for tasks where protected groups are unknown. Hashimoto et al. propose the following optimization objective:

$$\min_{\theta \in \Theta} \mathbb{E}_P \left[\ell(\theta; Z) - \eta\right]_+^2$$

P denotes the data generating distribution, $\ell(\theta; Z)$ the loss of a query Z under the model with parameters θ, and η a hyperparameter to threshold the losses. In the publicly available code by Hashimoto et al. that we used in our implementation, a ReLU activation function is applied after subtracting η from losses of single data points, ensuring that only positive losses remain. The method focuses on the worst-case group by only considering losses for optimization that exceed the threshold η, which implicitly decides about the size of the worst-case group. Squaring the thresholded losses upweights the influence of higher losses on the learning objective further.

2.2 Datasets

We use the three datasets also used in the paper: UCI Adult [5], COMPAS [6] and LSAC [7], all of which are publicly available. Every dataset describes a binary prediction task. In UCI Adult, the income of a person is to be predicted to be above fifty thousand dollars. COMPAS is concerned with predicting the recidivism of indviduals convicted of crimes. For LSAC, the task is to predict whether a given law student will pass the bar exam.

All datasets exhibit some form of imbalance and include information about sensitive attributes like sex and race which makes them suitable for evaluating model fairness. UCI Adult consists of 48,842 records, of which 67% are male and 85% white (10% black). The dataset is also imbalanced in its target class, as only 24% have an income of more than fifty thousand dollars. LSAC consists of 26,551 samples, of which 56% are male and 83% white (6% black). COMPAS consists of 7,185 records with 81% being male and 37% white (51% black). In all datasets, there exists some correlation between sensitive attributes and target class [8, 7, 9].

Pipeline

We split each dataset randomly into 70% training data and 30% test data, except for UCI Adult, where a split is already provided. For our main experiments, the sensitive columns race and sex were removed from the features, such that these demographics were not available to the models. To access sensitive information during evaluation, each data element was categorized as being a member of one of the following groups: "not black and male", "not black and female", "black and male", "black and female". Of these, the group with the fewest members is referred to as minority. This treatment of the subgroups was inferred from the publicly available code. The paper however used the term "white" instead of "not black", which does not accurately reflect the work done in their code. We will adopt their term usage from hereon for better comparability.

We represented categorical features using one-hot encoding and normalized numerical features to have zero mean and unit standard deviation. All features of a datapoint were then appended into one feature vector. A script to download and preprocess the datasets is available as part of our code base.

2.3 Hyperparameters

We determined the optimal batch size and learning rate for each method using a grid search and 5-fold cross validation over the same search space as described in the appendix to the paper. For DRO, we also tuned η in this grid search (this corresponds to the "DRO(auc)" method in the paper).

All results were obtained by training from scratch with the obtained optimal hyperparameters using ten different random seeds, then evaluating on the test set and averaging the results. We pretrained the learner for ARL for 250 steps, which is the default in the code provided by the authors. We used AdaGrad as the optimizer, following the paper. Initialization for the weights and the optimizer were chosen to agree with TensorFlow defaults. In the initial experiments, we ran each grid search for 5000 training steps, with early stopping if the overall AUC on the validation set had not improved for 10 epochs.

For the grid search space and the optimal hyperparameters found, see Appendix B. Since Lahoti et al. do not mention the exact optimal hyperparameters found by their grid search, we can not directly compare our found parameters.

2.4 Computational Requirements

The grid searches took about 3-4h on twelve CPUs for the 5k step runs on tabular data and an additional 10h on a GPU for the image grid searches. The 100k step grid seach too much longer, about 1-2 days. The final results (training each model on ten different random seeds) were obtained from a notebook that ran about 5h on Google Colab with a GPU.

3 Results

Table 1 shows the results of comparing ARL to DRO and the baseline model. We observe that all methods obtain very similar results for each dataset and metric. Only for COMPAS we observe that ARL is performing (slightly) better than the other methods, reversing the results of the original paper. Since some training runs did not end via early stopping but rather due to the maximum number of training steps being reached, we repeated the grid search and evaluation with ten seeds using a maximum number of 100k instead of 5k steps. We did not observe a significant increase in performance for any of the used methods, so we can probably rule out that training for too few training steps distorted our results. The exact results for 100k training steps can be found in Table 8. In the remainder of the main body of this report we use 5k training steps if not stated otherwise.

Dataset	Method	AUC avg	AUC macro-avg	AUC min	AUC minority	Accuracy
Adult	baseline	0.9093 ± 0.0016	$\mathbf{0.9193 \pm 0.0011}$	0.8842 ± 0.0019	$\mathbf{0.9440 \pm 0.0040}$	0.8498 ± 0.0070
Adult	DRO	$\mathbf{0.9102 \pm 0.0007}$	0.9187 ± 0.0018	$\mathbf{0.8853 \pm 0.0007}$	0.9414 ± 0.0059	$\mathbf{0.8574 \pm 0.0015}$
Adult	ARL	0.9090 ± 0.0007	0.9178 ± 0.0008	0.8840 ± 0.0009	0.9393 ± 0.0031	0.8504 ± 0.0028
LSAC	baseline	$\mathbf{0.8309 \pm 0.0061}$	$\mathbf{0.8263 \pm 0.0063}$	$\mathbf{0.8096 \pm 0.0073}$	$\mathbf{0.8371 \pm 0.0087}$	$\mathbf{0.8604 \pm 0.0047}$
LSAC	DRO	0.8242 ± 0.0051	0.8217 ± 0.0053	0.8024 ± 0.0055	0.8361 ± 0.0088	0.8570 ± 0.0057
LSAC	ARL	0.8122 ± 0.0063	0.8063 ± 0.0091	0.7870 ± 0.0066	0.8264 ± 0.0199	0.7501 ± 0.0290
COMPAS	baseline	0.7357 ± 0.0025	0.7340 ± 0.0027	0.6995 ± 0.0029	0.7475 ± 0.0024	0.6735 ± 0.0057
COMPAS	DRO	0.7361 ± 0.0030	0.7347 ± 0.0032	0.6997 ± 0.0035	$\mathbf{0.7533 \pm 0.0044}$	0.6688 ± 0.0071
COMPAS	ARL	$\mathbf{0.7364 \pm 0.0026}$	$\mathbf{0.7347 \pm 0.0032}$	$\mathbf{0.7008 \pm 0.0023}$	0.7481 ± 0.0080	$\mathbf{0.6756 \pm 0.0091}$

Table 1: Main results: Baseline vs ARL vs DRO, best results for each dataset are marked bold

(a) Micro-average (overall) AUC   (b) Minimum group AUC   (c) AUC of minority group

Figure 1: Different AUC values during training of ARL, baseline and DRO on the validation set of LSAC. Average and standard deviation over 10 random seeds.

Figure 1 shows the micro-average AUC, minimum group AUC and the AUC of the minority group of ARL, baseline and DRO on the validation split of the LSAC dataset. As can be seen, ARL shows no consistent advantage in any of the metrics over the other models. Figure 1c shows that, depending on the point in time where the model is saved, there exist some points of comparison where ARL seems to outperform the other models. Given these fluctuations, it is vital to know for how many steps the authors trained their models and if they used early stopping. We tried to get in touch with the authors over this, but did not receive any response. Lacking this information poses a major shortcoming in the reproducibility of the paper.

Table 2 shows the deviation of our results in Table 1 to those reported in the paper. Positive numbers mean that our performance was higher, negative that it was lower than that from the paper. All numbers are measured in multiples of the standard error of the difference, calculated as $\sqrt{\sigma_{\text{ours}}^2 + \sigma_{\text{theirs}}^2}$, where σ_{ours} and σ_{theirs} are the standard deviations of our and their results over the 10 runs with different seeds. Because Lahoti et al. do not report standard deviations for macro-avg, minimum and minority AUC, we calculated the errors for those measure using error propagation from the values they report for all protected subgroups (tables 6 to 8 in their supplementary material). Our results for baseline and DRO are significantly better than in [1], but ARL performs similarly well.

Dataset	Method	AUC avg	AUC macro-avg	AUC min	AUC minority
Adult	baseline	**6.88**	**8.08**	0.38	**2.82**
	DRO	**14.13**	**5.10**	**17.04**	1.41
	ARL	1.77	0.41	1.97	-0.20
LSAC	baseline	**2.70**	**2.11**	**2.46**	1.29
	DRO	**22.78**	**21.16**	**21.90**	**12.00**
	ARL	-1.45	-1.14	-1.26	-0.21
COMPAS	baseline	**-2.85**	1.66	**8.20**	**-2.35**
	DRO	**6.44**	**10.73**	**6.22**	**2.88**
	ARL	-1.77	**2.08**	**4.47**	**-3.39**

Table 2: Relative deviations between our results and those reported in the paper (difference divided by standard deviation across runs, see main text for details). Deviations of more than 2 standard deviations are marked bold. Accuracy was not reported by the authors and is thus missing.

In Table 3, we compare the results between ARL and the naive reweighting approach IPW, either using only protected groups (S) or using protected groups and labels (S+Y) to compute the inverse probability weights. Similarly to the results in Table 1, ARL only performs best on the COMPAS dataset.

Dataset	Method	AUC avg	AUC macro-avg	AUC min	AUC minority	Accuracy
Adult	ARL	0.9090 ± 0.0007	0.9178 ± 0.0008	0.8840 ± 0.0009	0.9393 ± 0.0031	0.8504 ± 0.0028
Adult	IPW(S)	0.9085 ± 0.0004	0.9179 ± 0.0007	0.8826 ± 0.0005	0.9434 ± 0.0018	$\mathbf{0.8557 \pm 0.0010}$
Adult	IPW(S+Y)	$\mathbf{0.9110 \pm 0.0009}$	$\mathbf{0.9209 \pm 0.0020}$	$\mathbf{0.8859 \pm 0.0010}$	$\mathbf{0.9465 \pm 0.0047}$	0.7428 ± 0.0160
LSAC	ARL	0.8122 ± 0.0063	0.8063 ± 0.0091	0.7870 ± 0.0066	0.8264 ± 0.0199	0.7501 ± 0.0290
LSAC	IPW(S)	0.8147 ± 0.0066	0.8088 ± 0.0056	0.7933 ± 0.0089	0.8162 ± 0.0090	$\mathbf{0.8483 \pm 0.0033}$
LSAC	IPW(S+Y)	$\mathbf{0.8371 \pm 0.0038}$	$\mathbf{0.8302 \pm 0.0030}$	$\mathbf{0.8150 \pm 0.0054}$	$\mathbf{0.8374 \pm 0.0072}$	0.8352 ± 0.0108
COMPAS	ARL	$\mathbf{0.7364 \pm 0.0026}$	$\mathbf{0.7347 \pm 0.0032}$	$\mathbf{0.7008 \pm 0.0023}$	0.7481 ± 0.0080	$\mathbf{0.6756 \pm 0.0091}$
COMPAS	IPW(S)	0.7300 ± 0.0040	0.7294 ± 0.0058	0.6914 ± 0.0024	0.7399 ± 0.0124	0.6661 ± 0.0159
COMPAS	IPW(S+Y)	0.7362 ± 0.0029	0.7346 ± 0.0031	0.6998 ± 0.0029	$\mathbf{0.7526 \pm 0.0043}$	0.6733 ± 0.0096

Table 3: Comparison ARL vs IPW for 5k maximum training steps

3.1 Computational Identifiability

To investigate whether a linear adversary is actually capable of identifying protected groups based on the observed features and labels, the authors trained a linear model to predict race or sex based on the features and the labels. They did not provide further detail about their training method. Since we only want to test whether the adversary is in principle capable of performing this task and precise accuracies are thus not important, we limit ourselves to a single run.

		Adult	LSAC	COMPAS
Race	total	0.907	0.943	0.618
	White	0.997	0.988	0.603
	Black	0.058	0.325	0.631
Sex	total	0.842	0.585	0.802
	Male	0.876	0.807	1.000
	Female	0.774	0.298	0.000

Table 4: Accuracies of a linear model trained to predict race or sex.

Training, validation and testing are performed with the optimal hyperparameters found via the grid search in the previous section. The obtained test accuracies for predicting race or sex are shown in Table 4. The results are broadly consistent with the results from the original paper.

The per-group accuracies show that the linear model achieves its performance by concentrating on the majority class, indicating that the adversary is not able to adequately identify and differentially upweight minority groups.

3.2 Adversary Outputs

To inspect whether the adversary learns meaningful weights, the authors plotted the weights returned by the adversary on the training set of UCI Adult. We evaluate the adversary on the test set of UCI Adult to see whether it has meaningful weights on the test set as well. We perform kernel density estimation with a Gaussian kernel with a bandwidth parameter of 0.3 on the test weights to produce continuous distributions over λ. Results obtained using scikit-learn [10] are shown in Figure 2.

The computed densities roughly match the authors' results. Thus, we can support their claim that ARL learns to upweight not only misclassified examples, but also underrepresented classes (bottom-right quadrant of Figure 2. Recall that the UCI Adult dataset exhibits a strong class imbalance and as we can see the adversary places larger weights on the less frequent class.

Figure 2: Output of the adversary on the Adult test set.

It is important to point out that ARL apparently *does not* place higher weights on underrepresented demographics (see the orange and red curves in Figure 2). This is in line with the results from Lahoti et al. but does not agree with the original motivation for ARL.

Dataset	Method	AUC avg	AUC macro-avg	AUC min	AUC minority	Accuracy
EMNIST_35	baseline	**0.9507 ± 0.0037**	**0.9436 ± 0.0041**	**0.9256 ± 0.0055**	**0.9256 ± 0.0055**	**0.8778 ± 0.0059**
EMNIST_35	ARL	0.9370 ± 0.0044	0.9281 ± 0.0052	0.9051 ± 0.0072	0.9051 ± 0.0072	0.8616 ± 0.0057

Table 5: Baseline vs ARL on image data, best results for each dataset are marked bold. Models were trained for 5k steps or until the early stopping criterion was reached. Reported numbers are averages over 10 seeds.

4 Extension of the Presented Method

Not just tabular data, but also other modalities are in principle prone to issues regarding fairness. This is why an evaluation of ARL on a different type of data marks a straightforward extension to the analyses presented by Lahoti et al. In this section, we present and evaluate a simple extension of ARL to image data.

4.1 Dataset

We resorted to building a custom dataset for the evaluation in order to meet our limited computational resources and maintain the ability to easily tailor the input data to our experiments. The dataset is based on balanced EMNIST [11], a character classification dataset similar to MNIST [12] containing a balanced set of 47 different greyscale characters. We customized the dataset, which we refer to as EMNIST_35, such that the task is a binary prediction with balanced labels, and artificially created one protected minority subgroup. The minority is represented by 35% of the data for both labels. Further details and different data configurations are presented in Appendix E.1.

4.2 Model Architecture

Both the learner of ARL and the baseline model contain a single convolutional layer with 64 filters and a 3×3 kernel with stride 1. Subsequently, a max-pooling layer with kernel size 2×2 with stride 1 is employed. The adversary uses a similar setup with 32 filters. Both learner and baseline then use two fully connected layers with 64 and 32 neurons with a ReLU activation function in-between. In the adversary, the sample label is appended to the flattened output of the convolutional section and the model output is produced as a linear combination of the resulting vector for each sample. The training procedure and hyperparameters of all image models are further described in Appendix E.3.

4.3 Results and Analysis

The model performances regarding the different AUC metrics and the classification accuracy are listed in Table 5. The baseline clearly outperforms ARL on all evaluation criteria. Further experiments showed that the adversary is unable to identify protected groups in the adversarial setting and tends to weight few individual samples with very high weights.

Since the architecture for the learner and the baseline is the same, we further considered the influence of the adversary by investigating if it is capable of identifying the protected groups in a supervised setting. It turns out that the adversary resorts to predicting the majority class in most cases. We ran several experiments with different architectures for the adversary but were not able to produce a performance boost over the reference models similar to those reported by Lahoti et al. on tabular data. Details regarding the results of our experiments are given in Appendix E.

5 Discussion

In this report we re-implemented the *Adversarially Reweighted Learning* (ARL) framework by Lahoti et al. in PyTorch. This framework promises a general approach to dealing with group fairness if demographic data are lacking or unknown. However, as shown in Tables 1 and 3 and the analyses that followed, we could not replicate the advantage of ARL over the investigated baselines. This seems to be mainly due to a better baseline performance than in Lahoti et al. As displayed in Table 2, our ARL results are not deviating significantly (mostly $< 3\sigma$) from the papers' result, but our baselines are considerably better than in the original paper.

Contrary to the authors' results, our ARL implementation performs best on the COMPAS dataset, although not significantly better than the baseline. As can be seen from the learning curves in Figure 4 in the appendix, this might be due to the fluctuations in performance that occurred during training on the COMPAS dataset. In all datasets, differences resulting solely or mainly from the used deep learning framework or erroneous implementation can be ruled out, which we show in Table 6.

The authors claim that the adversary is in principle powerful enough to identify protected subgroups. We can confirm this assumption only to a certain degree, as the authors did not consider class imbalances when checking for computational identifiability. We can, however, confirm the authors' claim that the adversary is capable to learn meaningful weights when it comes to class imbalance. As pointed out by Yan, Kao, and Ferrara, post hoc methods of balancing classes bear the risk of further amplifying already existent subgroup imbalances if the upweighted class exhibits an even stronger subgroup imbalance [13], as is the case with e.g. the Adult dataset where minorities are even less present in the high-income class. This means that in such cases, ARL runs the risk of amplifying subgroup imbalances further.

By choosing UCI Adult, LSAC and COMPAS to test ARL, the authors implicitly make the assumption that these datasets are suitable to evaluate the performance of their method. To us, the results suggest that these datasets are in fact not a good choice: The baseline model is already quite fair towards subgroups, not leaving much space for the ARL to show any differential advantage. Experiments by Zhong suggest that reweighting and oversampling, both methods related to ARL, are not effective at improving fairness in these datasets [14], which further supports our impression of the datasets not being suitable.

Our experiments with ARL on image data show that such an extension is not trivial, at the very least. Including an adversary lead to deteriorating performance compared to the baseline which could be explained by real-world images generally containing large amounts of noise. An extensive investigation regarding this and other potential sources of error are left as future work.

When trying to reproduce the authors' paper, we faced several challenges which might have contributed to the differences in results. Vital information about training duration and choice of hyperparameters was not provided by the authors. Their code and paper differ in several points, most of which are minor by themselves, but in their quantity eventually diminish reproducibility as well as transparency of their work. Unfortunately, the authors did not respond to our inquiries, which could have helped explain differences in our results.

At this point we also want to point out that the advantage of ARL over the baseline, as reported in the appendix of Lahoti et al., is not very large, neither in absolute terms, nor in relative terms (scaled by standard deviations). Also, as already touched upon in the previous section, the weights learned by ARL do not support the original motivation of ARL, neither in this report, nor in Lahoti et al.

In conclusion, we did not find an advantage of ARL over baseline models, neither for the datasets used by the authos nor for image data. Given that the the results of the original paper favor ARL only very slightly and that the adversary apparently does not weight minorities higher, we do not believe that ARL in its current form can improve fairness on these datasets. However, since the theoretical motivation appears sound, it may be promising to apply ARL to datasets where baselines suffer from more severe fairness issues, or to further investigate whether the capacity of the adversary can be adjusted to improve performance.

References

[1] Preethi Lahoti et al. *Fairness without Demographics through Adversarially Reweighted Learning*. 2020. arXiv: 2006.13114 [cs.LG].

[2] Tatsunori B. Hashimoto et al. *Fairness Without Demographics in Repeated Loss Minimization*. 2018. arXiv: 1806.08010 [stat.ML].

[3] Adam Paszke et al. "PyTorch: An Imperative Style, High-Performance Deep Learning Library". In: *Advances in Neural Information Processing Systems 32*. Ed. by H. Wallach et al. Curran Associates, Inc., 2019, pp. 8024–8035. URL: http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

[4] Martın Abadi et al. *TensorFlow: Large-Scale Machine Learning on Heterogeneous Systems*. Software available from tensorflow.org. 2015. URL: http://tensorflow.org/.

[5] Dheeru Dua and Casey Graff. *UCI Machine Learning Repository*. 2017. URL: http://archive.ics.uci.edu/ml.

[6] ProPublica. *COMPAS Recidivism Risk Score Data and Analysis*. Data retrieved from Github, https://github.com/propublica/compas-analysis/. 2016.

[7] Linda F. Wightman. *LSAC National Longitudinal Bar Passage Study. LSAC Research Report Series*. Data retrieved from Project SEAPHE, http://www.seaphe.org/databases.php. 1998.

[8] Christina Wadsworth, Francesca Vera, and Chris Piech. *Achieving Fairness through Adversarial Learning: an Application to Recidivism Prediction*. 2018. arXiv: 1807.00199 [cs.LG].

[9] Ninareh Mehrabi et al. *A survey on bias and fairness in machine learning*. 2019.

[10] F. Pedregosa et al. "Scikit-learn: Machine Learning in Python". In: *Journal of Machine Learning Research* 12 (2011), pp. 2825–2830.

[11] Gregory Cohen et al. "EMNIST: an extension of MNIST to handwritten letters". In: *CoRR* abs/1702.05373 (2017). arXiv: 1702.05373. URL: http://arxiv.org/abs/1702.05373.

[12] Yann LeCun and Corinna Cortes. "MNIST handwritten digit database". In: (2010). URL: http://yann.lecun.com/exdb/mnist/.

[13] Shen Yan, Hsien-te Kao, and Emilio Ferrara. "Fair Class Balancing: Enhancing Model Fairness without Observing Sensitive Attributes". In: *Proceedings of the 29th ACM International Conference on Information Knowledge Management*. New York, NY, USA: Association for Computing Machinery, 2020, pp. 1715–1724. ISBN: 9781450368599. URL: https://doi.org/10.1145/3340531.3411980.

[14] Ziyuan Zhong. *A Tutorial on Fairness in Machine Learning*. 2018. URL: https://towardsdatascience.com/a-tutorial-on-fairness-in-machine-learning-3ff8ba1040cb (visited on 01/29/2021).

A Comparison of Implementations

Dataset	Method	AUC avg	AUC minority	Accuracy
Adult	baseline	**11.158**	**9.240**	-0.695
Adult	ARL	**11.221**	**7.640**	**2.303**
Adult	IPW(S)	**6.796**	**11.547**	-0.424
LSAC	baseline	**6.443**	**6.544**	-0.463
LSAC	ARL	**8.425**	**5.162**	-0.535
LSAC	IPW(S)	**2.752**	**7.051**	-0.635
COMPAS	baseline	1.891	**2.124**	0.440
COMPAS	ARL	**5.106**	1.691	1.171
COMPAS	IPW(S)	**4.376**	0.429	1.414

Table 6: Relative deviation between results with our PyTorch implementation and the TensorFlow implementation by the authors. All results are based on runs with 100 steps, a learning rate of 0.1 and a batch size of 128. Positive numbers mean that our implementation achieved higher performance. All numbers are in multiples of the standard error of the difference (calculated as for Table 2, see Section 3 for details). Deviations of more than two standard errors are bold. Since the authors' code does not save macro-avg AUC nor min AUC, these metrics are missing.

B Optimal Hyperparameters

We performed grid search to determine optimal hyperparameters. The search space for (batch size, learning rate, η) consisted of the following values:

$$[32, 64, 128, 256, 512] \times [0.001, 0.01, 0.1, 1, 2, 5] \times [0.5, 0.6, 0.7, 0.8, 0.9, 1],$$

where in the case of methods other than DRO, the η parameter was not searched over. Table 7 shows the optimal hyperparameters for each dataset and model combination, when optimized for overall AUC.

Dataset	Method	batch size	learning rate	η
Adult	baseline	512	2	-
Adult	DRO	128	1	0.5
Adult	ARL	128	0.1	-
Adult	IPW(S)	128	0.01	-
Adult	IPW(S+Y)	256	0.1	-
LSAC	baseline	64	0.1	-
LSAC	DRO	128	1	0.6
LSAC	ARL	64	0.1	-
LSAC	IPW(S)	256	0.1	-
LSAC	IPW(S+Y)	64	0.1	-
COMPAS	baseline	256	0.1	-
COMPAS	DRO	256	1	0.6
COMPAS	ARL	256	0.1	-
COMPAS	IPW(S)	256	0.1	-
COMPAS	IPW(S+Y)	512	0.1	-

Table 7: Hyperparameters with the best overall AUC for each dataset and training method. Models were trained for 5k steps or until the early stopping criterion was reached.

C AUC learning curves

Figure 3 shows the AUC learning curves of ARL, IPW(S) and IPW(S+Y) on the validation set of LSAC. ARL does not show a consistent advantage over IPW. Even though ARLs performance seems to gain advantage towards the end of the training, our results from comparing the models after training for 100k maximum training steps (Table 9) show that ARL is still outperformed by IPW, even when allowing for longer training duration.

Figure 3 shows the AUC learning curves of baseline, ARL and DRO on the validation set of COMPAS. The curves of baseline and ARL are very close during the most part of the training. This is in line with our final results on the test set,

| (a) Micro-average (overall) AUC | (b) Minimum group AUC | (c) AUC of minority group |

Figure 3: Different AUC values during training of ARL, IPW(S) and IPW(S+Y) on the validation set of LSAC. Average and standard deviation over 10 random seeds.

which show a neglectable advantage of ARL (Table 8). The performance on validation and test set suggests that ARL can keep up with the baseline model on the COMPAS dataset, but does not significantly outperform it.

| (a) Micro-average (overall) AUC | (b) Minimum group AUC | (c) AUC of minority group |

Figure 4: Different AUC values during training of baseline, ARL, and DRO on the validation set of COMPAS. Average and standard deviation over 10 random seeds.

D Results for 100k maximum training steps

As can be seen from Tables 8 and 9, changing the maximum number of training steps from 5k to 100k did not change performance significantly. We did not have enough computational resources to train the DRO model on the Adult dataset, but given the rest of the results it seems unlikely it would have yielded different results.

Dataset	Method	AUC avg	AUC macro-avg	AUC min	AUC minority	Accuracy
Adult	baseline	**0.9106 ± 0.0009**	**0.9197 ± 0.0015**	**0.8854 ± 0.0010**	**0.9430 ± 0.0042**	0.8523 ± 0.0049
Adult	DRO	-	-	-	-	-
Adult	ARL	0.9098 ± 0.0007	0.9182 ± 0.0006	0.8852 ± 0.0009	0.9400 ± 0.0025	**0.8540 ± 0.0020**
LSAC	baseline	**0.8370 ± 0.0037**	**0.8295 ± 0.0044**	**0.8151 ± 0.0045**	**0.8347 ± 0.0086**	**0.8655 ± 0.0036**
LSAC	DRO	0.8291 ± 0.0043	0.8219 ± 0.0048	0.8084 ± 0.0063	0.8284 ± 0.0148	0.8587 ± 0.0041
LSAC	ARL	0.8208 ± 0.0052	0.8130 ± 0.0058	0.7983 ± 0.0067	0.8227 ± 0.0087	0.8025 ± 0.0147
COMPAS	baseline	0.7356 ± 0.0024	0.7340 ± 0.0030	0.6998 ± 0.0027	**0.7552 ± 0.0071**	0.6731 ± 0.0054
COMPAS	DRO	0.7361 ± 0.0031	**0.7348 ± 0.0032**	0.7004 ± 0.0028	0.7509 ± 0.0101	0.6697 ± 0.0075
COMPAS	ARL	**0.7364 ± 0.0026**	0.7347 ± 0.0032	**0.7008 ± 0.0023**	0.7481 ± 0.0080	**0.6756 ± 0.0091**

Table 8: Main results for 100k max steps: Baseline vs ARL vs DRO, best results for each dataset are marked bold

Dataset	Method	AUC avg	AUC macro-avg	AUC min	AUC minority	Accuracy
Adult	ARL	0.9098 ± 0.0007	0.9182 ± 0.0006	0.8852 ± 0.0009	0.9400 ± 0.0025	0.8540 ± 0.0020
Adult	IPW(S)	0.9087 ± 0.0005	0.9181 ± 0.0007	0.8826 ± 0.0008	0.9437 ± 0.0012	$\mathbf{0.8552 \pm 0.0010}$
Adult	IPW(S+Y)	$\mathbf{0.9108 \pm 0.0007}$	$\mathbf{0.9209 \pm 0.0015}$	$\mathbf{0.8854 \pm 0.0008}$	$\mathbf{0.9471 \pm 0.0045}$	0.7499 ± 0.0155
LSAC	ARL	0.8208 ± 0.0052	0.8130 ± 0.0058	0.7983 ± 0.0067	0.8227 ± 0.0087	0.8025 ± 0.0147
LSAC	IPW(S)	0.8202 ± 0.0041	0.8158 ± 0.0046	0.7982 ± 0.0049	0.8222 ± 0.0090	$\mathbf{0.8543 \pm 0.0029}$
LSAC	IPW(S+Y)	$\mathbf{0.8369 \pm 0.0037}$	$\mathbf{0.8288 \pm 0.0046}$	$\mathbf{0.8139 \pm 0.0046}$	$\mathbf{0.8336 \pm 0.0074}$	0.8367 ± 0.0088
COMPAS	ARL	$\mathbf{0.7364 \pm 0.0026}$	$\mathbf{0.7347 \pm 0.0032}$	$\mathbf{0.7008 \pm 0.0023}$	$\mathbf{0.7481 \pm 0.0080}$	$\mathbf{0.6756 \pm 0.0091}$
COMPAS	IPW(S)	0.7312 ± 0.0020	0.7303 ± 0.0027	0.6918 ± 0.0029	0.7423 ± 0.0086	0.6670 ± 0.0086
COMPAS	IPW(S+Y)	0.7348 ± 0.0034	0.7327 ± 0.0039	0.6979 ± 0.0033	0.7458 ± 0.0079	0.6701 ± 0.0062

Table 9: Comparison ARL vs IPW for 100k maximum training steps.

Dataset	Method	AUC avg	AUC macro-avg	AUC min	AUC minority	Accuracy
EMNIST_35	baseline	$\mathbf{0.9507 \pm 0.0037}$	$\mathbf{0.9436 \pm 0.0041}$	$\mathbf{0.9256 \pm 0.0055}$	$\mathbf{0.9256 \pm 0.0055}$	$\mathbf{0.8778 \pm 0.0059}$
EMNIST_35	ARL	0.9370 ± 0.0044	0.9281 ± 0.0052	0.9051 ± 0.0072	0.9051 ± 0.0072	0.8616 ± 0.0057
EMNIST_35	ARL_weak	0.9354 ± 0.0072	0.9260 ± 0.0082	0.9017 ± 0.0112	0.9017 ± 0.0112	0.8587 ± 0.0095
EMNIST_10	baseline	$\mathbf{0.9624 \pm 0.0013}$	$\mathbf{0.9170 \pm 0.0022}$	$\mathbf{0.8645 \pm 0.0040}$	$\mathbf{0.8645 \pm 0.0040}$	$\mathbf{0.8983 \pm 0.0025}$
EMNIST_10	ARL	0.8709 ± 0.0696	0.7873 ± 0.0875	0.6881 ± 0.1117	0.6881 ± 0.1117	0.7924 ± 0.0731
EMNIST_10	ARL_weak	0.9524 ± 0.0032	0.8983 ± 0.0077	0.8356 ± 0.0132	0.8356 ± 0.0132	0.8836 ± 0.0055

Table 10: Extended experiments: Baseline vs ARL on image data, best results for each dataset are marked bold.

E   Extended Experiments on Image Classification

In order to investigate the performance of ARL on our custom image dataset, we ran a series of different experiments. However, drawing definite conclusions from the obtained results and proposing alterations is beyond the scope of this paper and is thus left as future work.

E.1   Dataset Details

For keeping the classification task binary, all original class labels larger than 23 were given the new label 1 and all other original class labels were given the new label 0. For each new label, half of the original classes were assigned as belonging to a protected group. To introduce noise, this re-assignment happens with a probability of 0.9. Samples with original labels that are not part of this re-assignment have a probability of 0.1 of becoming a member of a protected group. To eschew the ratio of protected/non-protected samples, samples that become a member of a protected group are discarded from the dataset with a certain probability. In the dataset EMNIST_35, this probability is 0.5 and in the dataset EMNIST_10, this probability is 0.9. This results in about 10% of the samples belonging to the protected group in EMNIST_10 and about 35% of the samples belonging to the protected group in EMNIST_35. The new binary labels are balanced with about 48% of the samples belonging to the new class 1 in both datasets. The dataset reflects that non-noise members of protected groups can be structurally different from non-members with regards to their features. For EMNIST_35, the training set contains approximately 84000 samples and the test set contains approximately 14000 samples while for EMNIST_10, the training set contains approximately 61000 samples and the test set contains approximately 10000 samples.

E.2   Different Adversary Architectures

We tested a total of three different architectures for the ARL adversary. All consist of a single convolutional layer with 3×3 kernels and stride 1, a max-pooling layer with a 2×2 kernel and stride 1 and a subsequent single linear layer that directly maps the flattened output of the previous layer with appended target label to the scalar output. This setup was chosen in order to stay close to the original architecture for tabular data, as proposed by Lahoti et al. The model *ARL_strong* uses 64 filters, the model *ARL* uses 32 filters and the model *ARL_weak* uses 2 filters in the convolutional layer. The learner and the baseline are kept as described in Section 4.2.

E.3   Training Procedure and Optimal Hyperparameters

The learning rate and batch size of all image models were determined by performing a grid search over the same hyperparameter space as defined for the other datasets in Appendix B. The grid search procedure is the same as in Section 2.3 but with reserving 10% of the training set as validation set instead of performing cross validation. For all

Dataset	Method	batch size	learning rate
EMNIST_10	baseline	512	0.01
EMNIST_10	ARL_weak	256	0.01
EMNIST_10	ARL	256	0.1
EMNIST_10	ARL_strong	512	0.01
EMNIST_35	baseline	512	0.01
EMNIST_35	ARL_weak	512	0.01
EMNIST_35	ARL	512	0.01
EMNIST_35	ARL_strong	512	0.1

Table 11: Hyperparameters with the best overall AUC for each dataset and training method. Models were trained for 5k steps or until the early stopping criterion was reached.

	EMNIST_10			EMNIST_35		
	ARL_strong	ARL	ARL_weak	ARL_strong	ARL	ARL_weak
Overall	0.91	0.91	0.91	0.73	0.73	0.71
Majority	1.00	1.00	1.00	0.87	0.89	0.90
Minority	0.00	0.01	0.00	0.47	0.43	0.34

Table 12: Accuracies of predicting the protected sub-group in a supervised setting.

image models, the hyperparameters are listed in Table 11. All image models were trained using the AdaGrad optimizer and all reported results are obtained from models that were trained for 5k steps or until the early stopping criterion, that is the overall AUC on the validation set had not improved for 10 epochs, is reached.

E.4 The Effects of Different Datasets

Table 10 shows the extended results for ARL on the different datasets. In our experiments on image data, the claim of Lahoti et al. that ARL improves the performance on the worst-off group could not be confirmed to hold. Rather, ARL leads to an even lower performance on the minority sub-group which stands in contrast to the original motivation of ARL, that is to increase the performance on the worst-off group. This is independent from the ratio of protected to non-protected samples in the dataset as it happens in both EMNIST_35 and EMNIST_10. It is notable that ARL sees a large performance drop over ARL_weak on EMNIST_10 but not on EMNIST_35.

E.5 Computational Identifiability

Similar to Section 3.1, we tested whether the adversary is in principle capable of predicting the protected group in a supervised setting. Table 12 shows the accuracies that the different settings for ARL achieve on this task. Due to computational constraints, the reported numbers are results from a single training run of 5000 steps using the hyperparameters that were obtained in the grid search of the complete learner/adversary setting. ARL has major difficulties identifying the minority sub-group in the strongly imbalanced dataset EMNIST_10. The performance on the minority sub-group increases with increasing representation in the dataset as the results on EMNIST_35 show. This is in line with our expectations of a classifier whose optimization target is to improve the overall performance. Further, increasing the complexity of the adversary heavily increases the performance on the minority sub-group while the overall performance and performance on the majority sub-group is only slightly reduced.