On the Feasibility of Compressing Certifiably Robust Neural Networks

Abstract

Knowledge distillation is a popular approach to compress high-performance neural networks for use in resource-constrained environments. However, the threat of adversarial machine learning poses the question: Is it possible to compress adversarially robust networks and achieve similar or better adversarial robustness as the original network? In this paper, we explore this question with respect to *certifiable robustness defenses*, in which the defense establishes a formal robustness guarantee irrespective of the adversarial attack methodology. We present our preliminary findings answering two main questions: 1) Is the traditional knowledge distillation sufficient to compress certifiably robust neural networks? and 2) What aspects of the transfer process can we modify to improve the compression effectiveness? Our work represents the first study of the interaction between machine learning model compression and certifiable robustness.

1 Introduction

The existence of adversarial inputs [8, 20], *i.e.,* imperceptibly perturbed inputs that reliably cause erroneous outputs, have heightened concerns regarding the use of neural networks in sensitive real-world settings. In response, several methods have been proposed to harden neural networks against such inputs, enhancing their reliability in adversarial environments [15, 13, 19, 5]. One such category of methods focuses on computing the size of the largest neighborhood around a given input within which a classifier's output remains constant. Such a classifier is said to be *certifiably robust* for the given input inside this neighborhood. Since these methods provide a guarantee of robustness, they are highly desirable in safety- and privacy-critical applications such as payment systems, access control systems, self-driving cars, and security surveillance [14]. However, the expanded usage of neural networks in resource-limited computing platforms, such as IoT systems, has introduced a new challenge in this space: when training to generalize over adversarial data rather than the standard data distribution, larger networks are necessary [4, 16], making robust networks more resource demanding compared to their non-robust counterparts.

Knowledge distillation (KD) [3, 9] is a technique which uses a teacher-student training pipeline to compress the performance of larger networks into a smaller architecture. On the standard (*i.e.,* non-adversarial) classification task, KD improves the performance of the smaller student network and often results in performance compared to the large teacher network. Thus, a question arises: can knowledge distillation be used in an adversarial context to compress highly robust neural networks? Several works have explored this question with respect to *empirical robustness*, in which adversarial robustness is measured with respect to a specific attack algorithm [7, 1, 22, 23]. We note, though, no work has explored this question with respect to certifiable robustness, which is more given that it establishes a security guarantee irrespective of the attack methodology. To address the gap in literature, we perform the first study on compressing certifiably robust networks.

Submitted to 2022 Trustworthy and Socially Responsible Machine Learning (TSRML 2022). Do not distribute.

In this paper, we make the following **contributions**:

- We study the various strategies used for KD in context of certifiable robustness. We discover shortfalls in naive application of KD in these settings.
- We propose a more effective strategy for distilling certified robustness into small networks, which allows us to bridge the gap between the robustness of the student and the teacher.
- We identify that distilling certifiable robustness imposes stricter requirements than distilling standard performance or empirical robustness. Specifically, a smaller size gap between the student and the teacher networks might be required for effective distillation.

2 Background and Related Work

In this work, we study the certifiable robustness of neural network based image classifiers trained using knowledge distillation (KD). We use this section to define our problem, provide relevant background, and discuss related prior works.

2.1 Preliminaries

Consider a neural network classifier f parameterized by θ (denoted as f_θ) that is trained to map a given image $x \in \mathbb{R}^d$ to a set of discrete labels $\mathcal{Y}$ using a set of *i.i.d.* samples $\mathcal{S} = \{(x_1, y_1), (x_1, y_1), \cdots, (x_n, y_n)\}$ drawn from some data distribution. The output of the classifier can be written as $f_\theta(x) = \mathrm{argmax}_{c \in \mathcal{Y}} z_\theta^c(x)$. Here $z_\theta(x)$ is the softmax output of the classifier and $z_\theta^c(x)$ denotes the probability that image x belongs to class c. The process of training of a classifier involves minimizing the cross-entropy loss on the standard data distribution, which is approximated through $\mathcal{S}$.

2.2 Adversarial Robustness

In the ℓ_p-norm space, an adversarial perturbation is defined as any perturbation $\delta \in \mathbb{R}^d$ such that $\|\delta\|_p \leq \epsilon$, that an adversary can use to change the classifier's output *i.e.,* $f_\theta(x) \neq f_\theta(x + \delta)$. Here, ϵ defines the adversarial perturbation budget in terms of the maximum allowed magnitude of the perturbation vector.

The adversarial robustness of a neural network is often characterized by its *empirical* or *certified* robustness. The empirical adversarial robustness of a neural network is the accuracy of the network against adversarial samples generated by a given attack algorithm. Many early proposed defenses that were thought to be effective based on their reported empirical robustness were later found to have poor true robustness [2]. In contrast, the certified adversarial robustness of a neural network represents the true worst-case performance and is measured by the lower bound accuracy of the network against *all* adversarial samples within a given ϵ neighborhood.

2.2.1 Certified Robustness

The certified robustness of a network can be measured by its lower bound accuracy within a pre-determined neighborhood. Alternatively, it can be measured based on the radius of the largest neighborhood within which a classifier's output remains (correct and) constant. For a given input x, the classifier f_θ is said to be certifiably robust if $f_\theta(x)$ is provably constant within some large neighborhood around x. The radius of this neighborhood (or, robust radius) is defined using the ℓ_p-norm metric as follows:

$$R(f_\theta; x, y) = \begin{cases} \inf_{f_\theta(x') \neq f_\theta(x)} \|x' - x\|_p & \text{, when } f_\theta(x) = y \\ 0 & \text{, when } f_\theta(x) \neq y \end{cases} \tag{1}$$

Intuitively, the robust radius $R(f_\theta; x, y)$ establishes a region within which the classifier's prediction remains constant, ensuring that an adversary with a budget $\epsilon \leq R$ can not succeed. Therefore, training networks to maximize the robust radius would harden a classifier against manipulations of all sorts, including adversarial ones. However, as computing the robust radius of a neural network for a given input x is NP-hard [12], recent certified training methods instead propose computing a lower bound of the robust radius, known as the *certified radius*.

Randomized Smoothing. Cohen *et al.* [6] presented a scalable method for creating certifiably robust image classifiers using randomized smoothing. This involves converting a given classifier (termed *base classifier*) into a *smooth classifier*.

Definition 2.1. For a given (base) classifier f_θ and $\sigma > 0$, the corresponding smooth classifier g_θ is defined as follows:

$$g_\theta(x) = \underset{c \in \mathcal{Y}}{\arg\max} \, P_{\eta \sim \mathcal{N}(0,\sigma^2 I)}(f_\theta(x+\eta) = c) \tag{2}$$

Simply put, g_θ returns the class c, which has the highest probability mass under the Gaussian distribution $\mathcal{N}(x,\sigma^2 I)$. The authors provide theoretical proof for the certified robustness of a smooth classifier. This theoretical work can be summarized using Theorem 2.2.

Theorem 2.2. *Let $f_\theta : \mathbb{R}^d \mapsto \mathcal{Y}$ be a classifier and g_θ be its smoothed version (as defined in Equation 2). For a given input $x \in \mathbb{R}^d$ and corresponding ground truth output $y \in \mathcal{Y}$, if g_θ correctly classifies x as y such that*

$$P_\eta(f_\theta(x+\eta) = y) \geq \max_{y' \neq y} P_\eta(f_\theta(x+\eta) = y') \tag{3}$$

then g_θ is provably robust at x within the certified radius R given by:

$$CR(g_\theta; x, y) = \frac{\sigma}{2}[\Phi^{-1}(P_\eta(f_\theta(x+\eta) = y)) - \Phi^{-1}(\max_{y' \neq y} P_\eta(f_\theta(x+\eta) = y'))] \tag{4}$$

where, Φ is the c.d.f. of the standard Gaussian distribution.

Furthermore, the authors demonstrate that training the base classifier to minimize cross-entropy loss on inputs perturbed with Gaussian noise (Gaussian data augmentation) increases the certified radius of the smooth classifier. More generally, improving the base classifier's robustness to Gaussian noise is a successful strategy for increasing certified radius and has been utilized by several other prior works [18, 21, 11].

2.3 Knowledge Distillation (KD)

For the standard classification task, small neural networks are able to learn similar classification functions as large ones through a process known as knowledge distillation [3, 9]. Traditional KD involves training the small network (*student*) to mimic the outputs of a much larger network (*teacher*) for a given task (*e.g.,* classification). The student's training objective, also referred to as the *distillation objective*, is formalized as follows:

$$\min_\theta \mathbb{E}_{(x,y) \sim \mathcal{S}}[(1-\alpha)\mathcal{L}_{CE}(z_\theta(x), y) + \alpha t^2 \mathcal{L}_M(z_\theta^t(x), z_\phi^t(x))] \tag{5}$$

where $z_\theta(x)$ and $z_\phi(x)$ are the softmax outputs of the student S_θ and teacher T_ϕ, respectively; $\mathcal{L}_{CE}$ is the cross-entropy loss; $\mathcal{L}_M$ is the "mimic loss" (KL-Divergence, Euclidean distance *etc*); α is an hyperparameter used to weigh the two loss terms; and t is the softmax temperature. The value of α is usually set to 1, implying that the student is solely trained to mimic the teacher and in the process learns to perform well on the task. Training with the supervision of a teacher improves the student's performance as compared to training it independently. This is due to the small student benefits from the inter-class relationships learned by the large teacher (with higher modelling capacity). By distilling the knowledge of a large network into a small network, we essentially perform model compression, as the small network encodes the performance of the large network but with fewer parameters. This, in turn, allows for the use of high performance networks in resource-restricted devices.

2.4 Adversarial Robustness and Knowledge Distillation

Using the lessons learned from KD, several successful attempts have been made at improving the adversarial robustness of small networks by training them under the supervision of larger, robust networks. Goldblum *et al.* [7] propose *Adversarially Robust Distillation* (ARD), that combines KD with Adversarial Training [15]: the student is trained to match the teacher's outputs on adversarial inputs. ARD improves the robustness of small networks against gradient-based attacks relative to standalone adversarial training. Zi *et al.* [23] propose *Robust Soft Label Adversarial Distillation* (RSLAD), which improves upon ARD by using soft labels from a robust teacher rather than hard labels in all supervision loss terms. An important commonality between all these prior works is that they limit their experimentation to adversarial training, which is an empirical robustness method. Therefore, the robustness claims made by them can potentially be invalidated by a future adversary.

Table 1: The mimic loss used in different distillation objectives proposed by prior works. z_θ and z_ϕ are softmax outputs of the student and teacher network respectively, and t represents the temperature parameter. Note that since α is usually set to 1 (see Equation 5), we only report the loss terms that the student is actually trained with.

METHOD	$\mathcal{L}_\mathcal{M}$
KD [3, 9]	KL-DIV$(z_\theta^t(x), z_\phi^t(x))$ OR $\|z_\theta(x) - z_\phi(x)\|_2$
ARD [7]*	KL-DIV$(z_\theta^t(x+\delta), z_\phi^t(x))$
RSLAD [23]*	KL-DIV$(z_\theta(x), z_\phi(x)) + $ KL-DIV$(z_\theta(x+\delta), z_\phi(x))$

* For δ we use Gaussian noise instead of adversarial noise.

3 Distilling Certified Robustness

In order to promote deployment of safe machine learning models in resource-limited settings, it is important to study if certifiably robust neural networks can be effectively compressed. Knowledge distillation (KD) is one of the most effective approaches for doing this. Therefore, in this section we examine the effectiveness of KD towards compressing certifiably robust neural networks. We begin by describing our experimental setup in Section 3.1. In Section 3.2, we study the effectiveness of existing distillation objectives in distilling certified robustness. In Section 3.3, we propose a distillation objective using the traditional KD strategy that improves the distillation process by addressing the shortcoming of existing objectives.

3.1 Experimental Setup

In our experiments, we focus on certified robustness of image classifiers in the ℓ_2-space. Following the work by Cohen *et al.* [6], we use randomized smoothing to achieve certifiably robust classifiers. All our experiments are conducted using the CIFAR-10 dataset. To measure certified robustness, we follow prior works and report certified accuracy (or, the prediction accuracy of the smooth classifier) at different ℓ_2 radius [6, 18, 11]. The certified accuracy at radius$= 0$ is equivalent to the prediction accuracy of the smooth classifier on clean inputs. Additionally, we report the *average certified radius* (ACR) computed over the entire test set [21]. Our code is implemented in PyTorch [17] and is publicly available at `[REDACTED]` [1][2].

3.2 Can existing distillation objectives be used to distill certified robustness?

Knowledge distillation is effectively a method for "transferring" the knowledge of one network to another. Traditionally, this is achieved by training one network to mimic the other using some sort of mimic loss (*i.e.,* $\mathcal{L}_\mathcal{M}$ from Equation 5). Prior works on distilling adversarial robustness [7, 23, 22] also follow the traditional KD strategy, but propose different versions of $\mathcal{L}_\mathcal{M}$ (see Table 1). In this section, we evaluate whether these existing distillation objectives can be used to distill certified robustness. Note that since ARD and RSLAD were designed for adversarial training [15], they are not compatible with the certified robustness methods that we wish to study. To make them compatible, we use Gaussian noise in place of the adversarial noise therm (δ) in their distillation objective.

For experimentation, we use a ResNet-110 network as the teacher and train it on the CIFAR-10 dataset. To obtain non-trivial certified robustness for this network, we train it using the Gaussian data augmentation method proposed by Cohen *et al.* [6]. We then distill its robustness to a much smaller ResNet-20 network using the different existing distillation objectives. The results are summarized in Table 2. For comparison, we also report the student and teacher network's robustness when trained independently using Gaussian data augmentation. The first observation we make is that traditional distillation (KD) completely fails at distilling certified robustness as the student exhibits trivial ACR and certified accuracy for all values of r. The student network trained with RSLAD appears to have non-trivial certified robustness, however, the distilled ResNet-20 network exhibits poorer robustness than the one trained independently. This implies that the RSLAD objective is also unsuitable for our use case. Only the ARD objective seems to be successful at distilling certified robustness as the distilled ResNet-20 exhibits higher robustness than a ResNet-20 trained independently.

---

[1]To maintain anonymity, we have temporarily redacted the URL to the code repository.

[2]For certification, we borrow code from Cohen *et al.* [6]: `https://github.com/locuslab/smoothing`

Table 2: Comparing the robustness of a student network trained using different variants of knowledge distillation. We denote the distillation process as "teacher $\xrightarrow{\text{method}}$ student". Among all the methods, only ARD is able to successfully distill certified robustness, presenting higher robustness than the independently-trained student.

	ACR	0.00	0.25	0.50	0.75
RESNET-110	0.486	81.41	67.75	49.67	32.37
RESNET-20	0.451	79.62	63.78	45.65	28.01
RESNET-110 $\xrightarrow{\text{KD}}$ RESNET-20	0.090	10.93	10.16	9.86	9.03
RESNET-110 $\xrightarrow{\text{RSLAD}}$ RESNET-20	0.431	77.46	61.98	43.57	25.62
RESNET-110 $\xrightarrow{\text{ARD}}$ RESNET-20	0.456	76.50	62.80	46.87	30.29

Table 3: Evaluating the effectiveness of CRD in distilling certified robustness. CRD performs better than distillation objectives proposed by prior works. Furthermore, CRD trained student exhibits comparable robustness to its teacher (Table 2, 1^{st} row).

	ACR	0.00	0.25	0.50	0.75
RESNET-110 $\xrightarrow{\text{CRD}}$ RESNET-20	0.483	80.06	66.19	49.62	32.74

3.3 Adapting traditional KD strategy to distill certified robustness

From the results in Table 2, we observe that even for the best performing objective (*i.e.,* ARD), there exists a gap between the teacher's and the student's robustness. In this section we explore whether it is possible to bridge this gap while using the traditional KD strategy of mimicking outputs. We note that formulation of $\mathcal{L}_M$ used by prior works on distilling adversarial robustness was motivated by wanting the student to learn a similar output distribution for clean and adversarial inputs (generated using some attack). This motivation, however, doesn't translate to our use case very well. In the randomized smoothing paradigm, higher certified robustness comes from higher robustness to Gaussian noise. In fact, Jeong *et al.* [10] note that there is a direct correlation between the robustness of a smooth classifier and its prediction confidence (tied to confidence of base classifier on inputs perturbed with Gaussian noise). Based on this, we propose the following $\mathcal{L}_M$ which is tailored for certified robustness distillation:

$$\min_{\theta} \mathbb{E}_{(x,y)\sim\mathcal{S};\delta\sim\mathcal{N}(0,\sigma^2 I)}[(1-\alpha)\mathcal{L}_{CE}(z_{\theta}(x+\delta),y) + \alpha t^2 \|z_{\theta}^t(x+\delta) - z_{\phi}^t(x+\delta)\|_2] \quad (6)$$

We refer to this distillation objective as *Certified Robust Distillation* (CRD). Simply put, we are training the student to mimic the teacher's output not only at the given input x, but also in the Gaussian neighborhood around it. The robustness of a ResNet-20 distilled from a ResNet-110 using CRD is reported in Table 3. Comparing with the results in Table 2, we observe that CRD is successful at bridging the gap between the robustness of the student and the teacher. This makes CRD a more successful objective for distilling certified robustness than objectives proposed by prior works.

4 Limitations of CRD

In this section, we address the existing limitations of CRD. It is known that robustness training requires the network to learn more complicated functions than standard training [4, 16]. Therefore, we suspect that it might be more difficult to distill networks with high robustness as compared to distilling networks with high standard performance (*e.g.,* accuracy on test set). To investigate this, we repeat the experiment from previous section, this time training the teacher to be more robust by using training methods that are better than Gaussian data augmentation training. Specifically, we use MACER [21] and SmoothMix [10]. The results are reported in Table 4. For comparison, we also report the robustness of student and teacher networks independently trained using MACER and SmoothMix. Overall, we observe that for all teacher training methods that we use in this section, the process of distillation is not as effective as it was in the previous section. In all cases, there is a large gap between the robustness of the student and the teacher networks. Furthermore, only in one case (*i.e.,* MACER) we observe that the distilled ResNet-20 has higher robustness than the independently trained ResNet-20.

Table 4: Evaluating the effectiveness of CRD in distilling certified robustness from ResNet-110 teachers with progressively higher robustness. It is harder for a student to mimic a more robust teacher.

	ACR	0.00	0.25	0.50	0.75
MACER [21]					
RESNET-110	0.531	79.11	68.39	55.90	40.61
RESNET-20	0.507	76.44	65.81	52.87	38.75
RESNET-110 $\xrightarrow{\text{CRD}}$ RESNET-20	0.508	78.30	66.80	53.15	37.75
SMOOTHMIX [10]					
RESNET-110	0.550	76.89	68.25	57.42	46.26
RESNET-20	0.522	75.55	65.53	54.72	42.62
RESNET-110 $\xrightarrow{\text{CRD}}$ RESNET-20	0.514	76.33	65.85	53.83	40.28

Table 5: Testing the network capacity limitation of CRD using SmoothMix [10]. Networks of larger sizes are required to effectively mimic teachers possessing high certified robustness.

	ACR	0.00	0.25	0.50	0.75
RESNET-110	0.550	76.89	68.25	57.42	46.26
RESNET-32	0.537	76.44	67.17	56.19	44.00
RESNET-110 $\xrightarrow{\text{CRD}}$ RESNET-32	0.530	76.81	67.57	55.52	42.48
RESNET-44	0.545	76.55	67.33	57.18	45.85
RESNET-110 $\xrightarrow{\text{CRD}}$ RESNET-44	0.541	77.34	68.11	56.84	43.92
RESNET-56	0.545	77.01	68.17	56.89	45.05
RESNET-110 $\xrightarrow{\text{CRD}}$ RESNET-56	0.547	77.60	68.24	57.72	44.97

We run additional experiments to further investigate this student network capacity limitation of CRD. Starting with a ResNet-110 teacher trained using SmoothMix, we distill it into networks of various sizes using CRD. The results for this experiment are reported in Table 5. We observe that as we increase the size of the student network, the effectiveness of the distillation process improves. For ResNet-56, which is about half the size of ResNet-110, we observe that CRD succeeds at achieving comparable robustness between the student and the teacher. The gap between the robustness of the student and the teacher gets progressively worse as we reduce the size of the student. These results further corroborate that CRD, in its current form, is unable to distill complicated functions learnt by state-of-the-art robustness methods into networks of certain size. This result in unlike what prior works have reported in context of distilling both standard performance and adversarial robustness where we see that distillation can be successfully performed between student and teacher networks with larger size differences than the ones we use (*e.g.,* WideResNet-34-10 to ResNet-20) [3, 7, 23].

5 Conclusion & Future Work

In this paper, we presented the first study of knowledge distillation (KD) in the context of certified robustness. We tested different existing distillation objectives that were designed to distill standard performance or (empirical) adversarial robustness in terms of how effective they are in distilling certified robustness. Based on these results, we proposed a distillation objective (CRD) tailored for distilling certified robustness. However, CRD suffers from a network capacity limitation which makes it impractical to use with state-of-the-art certified training methods; further research is needed to address this shortcoming. We believe our preliminary investigation will serve as a useful starting point for future works on compressing certifiably robust machine learning models.

References

[1] Elahe Arani, Fahad Sarfraz, and Bahram Zonooz. Noise as a resource for learning in knowledge distillation. In *IEEE/CVF Winter Conference on Applications of Computer Vision*, 2021.

[2] Anish Athalye, Nicholas Carlini, and David A. Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International Conference on Machine Learning*, 2018.

[3] Lei Jimmy Ba and Rich Caruana. Do deep nets really need to be deep? In *Advances in Neural Information Processing Systems*, 2014.

[4] Sébastien Bubeck, Yin Tat Lee, Eric Price, and Ilya Razenshteyn. Adversarial examples from computational constraints. In *International Conference on Machine Learning*, 2019.

[5] Nicholas Carlini, Anish Athalye, Nicolas Papernot, Wieland Brendel, Jonas Rauber, Dimitris Tsipras, Ian J. Goodfellow, Aleksander Madry, and Alexey Kurakin. On evaluating adversarial robustness. *CoRR*, abs/1902.06705, 2019.

[6] Jeremy Cohen, Elan Rosenfeld, and Zico Kolter. Certified adversarial robustness via randomized smoothing. In *International Conference on Machine Learning*, 2019.

[7] Micah Goldblum, Liam Fowl, Soheil Feizi, and Tom Goldstein. Adversarially robust distillation. In *AAAI Conference on Artificial Intelligence*, 2020.

[8] Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2014.

[9] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network, 2015. arXiv:1503.02531.

[10] Jongheon Jeong, Sejun Park, Minkyu Kim, Heung-Chang Lee, Do-Guk Kim, and Jinwoo Shin. Smoothmix: Training confidence-calibrated smoothed classifiers for certified robustness. *Advances in Neural Information Processing Systems*, 2021.

[11] Jongheon Jeong and Jinwoo Shin. Consistency regularization for certified robustness of smoothed classifiers. *Advances in Neural Information Processing Systems*, 2020.

[12] Guy Katz, Clark Barrett, David L Dill, Kyle Julian, and Mykel J Kochenderfer. Reluplex: An efficient smt solver for verifying deep neural networks. In *International conference on computer aided verification*, pages 97–117. Springer, 2017.

[13] Mathias Lecuyer, Vaggelis Atlidakis, Roxana Geambasu, Daniel Hsu, and Suman Jana. Certified robustness to adversarial examples with differential privacy. In *IEEE Symposium on Security and Privacy*, 2019.

[14] Linyi Li, Xiangyu Qi, Tao Xie, and Bo Li. Sok: Certified robustness for deep neural networks. *CoRR*, abs/2009.04131, 2020.

[15] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018.

[16] Preetum Nakkiran. Adversarial robustness may be at odds with simplicity. *arXiv preprint arXiv:1901.00532*, 2019.

[17] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems (NIPS)*, 2019.

[18] Hadi Salman, Greg Yang, Jerry Li, Pengchuan Zhang, Huan Zhang, Ilya Razenshteyn, and Sébastien Bubeck. Provably robust deep learning via adversarially trained smoothed classifiers. In *Advances in Neural Information Processing Systems*, 2019.

[19] Lukas Schott, Jonas Rauber, Matthias Bethge, and Wieland Brendel. Towards the first adversarially robust neural network model on MNIST. In *International Conference on Learning Representations*, 2019.

[20] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *International Conference on Learning Representations*, 2014.

[21] Runtian Zhai, Chen Dan, Di He, Huan Zhang, Boqing Gong, Pradeep Ravikumar, Cho-Jui Hsieh, and Liwei Wang. Macer: Attack-free and scalable robust training via maximizing certified radius. In *International Conference on Learning Representations*, 2020.

[22] Jianing Zhu, Jiangchao Yao, Bo Han, Jingfeng Zhang, Tongliang Liu, Gang Niu, Jingren Zhou, Jianliang Xu, and Hongxia Yang. Reliable adversarial distillation with unreliable teachers. *arXiv preprint arXiv:2106.04928*, 2021.

[23] Bojia Zi, Shihao Zhao, Xingjun Ma, and Yu-Gang Jiang. Revisiting adversarial robustness distillation: Robust soft labels make student better. In *IEEE/CVF International Conference on Computer Vision*, 2021.