STABLE WEIGHT DECAY REGULARIZATION

ABSTRACT

Weight decay is a popular regularization technique for training of deep neural networks. Modern deep learning libraries mainly use L_2 regularization as the default implementation of weight decay. Loshchilov & Hutter (2018) demonstrated that L_2 regularization is not identical to weight decay for adaptive gradient methods, such as Adaptive Momentum Estimation (Adam), and proposed Adam with Decoupled Weight Decay (AdamW). However, we found that the popular implementations of weight decay, including L_2 regularization and decoupled weight decay, in modern deep learning libraries usually damage performance. First, the L_2 regularization is unstable weight decay for all optimizers that use Momentum, such as stochastic gradient descent (SGD). Second, decoupled weight decay is highly unstable for all adaptive gradient methods. We further propose the *Stable Weight Decay* (SWD) method to fix the unstable weight decay problem from a dynamical perspective. The proposed SWD method makes significant improvements over L_2 regularization and decoupled weight decay in our experiments. Simply fixing weight decay in Adam by SWD, with no extra hyperparameter, can outperform complex Adam variants, which have more hyperparameters.

1 INTRODUCTION

Weight decay is a popular and even necessary regularization technique for training deep neural networks that generalize well (Krogh & Hertz, 1992). People commonly use L_2 regularization as "weight decay" for training of deep neural networks and interpret it as a Gaussian prior over the model weights. This is true for vanilla SGD. However, Loshchilov & Hutter (2018) revealed that, when the learning rate is adaptive, the commonly used L_2 regularization is not identical to the original weight decay proposed by Hanson & Pratt (1989):

$$\theta_t = (1 - \lambda_0)\theta_{t-1} - \eta g_t, \tag{1}$$

where λ_0 is the weight decay hyperparameter, θ_t is the model parameters at t-th step , η is the learning rate, and g_t is the gradient of the minibatch loss function $L(\theta)$ at θ_{t-1}. Zhang et al. (2018) revealed three different roles of weight decay. However, the quantitative measures for weight decay are still missing.

Adaptive gradient methods that use Adaptive Learning Rate, such as AdaGrad (Duchi et al., 2011), RMSprop (Hinton et al., 2012), Adadelta (Zeiler, 2012) and Adam (Kingma & Ba, 2015), are a class of dominated methods to accelerate training of deep neural networks. Loshchilov & Hutter (2018) reported that, in adaptive gradient methods, the correct implementation of weight decay should be applied to the weights directly and decoupled with the gradients. We show the different implementations of decoupled weight decay and L_2 regularization for Adam in Algorithm 3.

It has been widely observed that adaptive gradient methods usually do not generalize as well as SGD (Wilson et al., 2017). A few Adam variants tried to fix the hidden problems in adaptive gradient methods, including AdamW Loshchilov & Hutter (2018), AMSGrad (Reddi et al., 2019) and Yogi (Zaheer et al., 2018). A recent research line, such as AdaBound (Luo et al., 2019), Padam (Chen & Gu, 2018), and RAdam (Liu et al., 2019), believes controlling the adaptivity of learning rates may improve generalization. This research line usually introduces extra hyperparameters to control the adaptivity, which requires more efforts in tuning hyperparameters.

Although popular optimizers have achieved great empirical success for training of deep neural networks, we discover that nonoptimal weight decay implementations have been widely used in

Table 1: Test performance comparison of optimizers. We report the mean and the standard deviations (as the subscripts) of the optimal test errors computed over three runs of each experiment. AdamS generalizes better than popular adaptive gradient methods significantly and often compares favorably with the baseline optimizer SGD.

DATASET	MODEL	SGD	ADAMS	ADAM	AMSGRAD	ADAMW	ADABOUND	PADAM	YOGI	RADAM
CIFAR-10	RESNET18	$5.01_{0.03}$	$\mathbf{4.91}_{0.04}$	$6.96_{0.02}$	$6.16_{0.18}$	$5.08_{0.07}$	$5.65_{0.08}$	$5.12_{0.04}$	$5.87_{0.12}$	$6.01_{0.10}$
	VGG16	$6.42_{0.02}$	$\mathbf{6.09}_{0.11}$	$7.31_{0.25}$	$7.14_{0.14}$	$6.59_{0.13}$	$6.76_{0.12}$	$6.15_{0.06}$	$6.90_{0.22}$	$6.56_{0.04}$
CIFAR-100	DENSENET121	$\mathbf{19.81}_{0.33}$	$20.52_{0.26}$	$25.11_{0.15}$	$24.43_{0.09}$	$21.55_{0.14}$	$22.69_{0.15}$	$21.10_{0.23}$	$22.15_{0.36}$	$22.27_{0.22}$
	GOOGLENET	$21.21_{0.29}$	$\mathbf{21.05}_{0.18}$	$26.12_{0.33}$	$25.53_{0.17}$	$21.29_{0.17}$	$23.18_{0.31}$	$21.82_{0.17}$	$24.24_{0.16}$	$22.23_{0.15}$

modern deep learning libraries, including PyTorch (Paszke et al., 2019), TensorFlow (Abadi et al., 2016), MXNet (Chen et al., 2015), and Chainer (Tokui et al., 2019). The nonoptimal implementations can lead to the unstable weight decay problem during training, which may harm performance seriously. We try to answer when the unstable weight decay problem happens and how to mitigate it. We organize our main findings as follows.

1. The effect of weight decay can be interpreted as iteration-wisely rescaling the loss landscape and the learning rate at the same time. We formulate the weight decay rate based on the rescaling ratio per unit stepsize. We call it *unstable weight decay* if the weight decay rate is not constant during training, seen in Definition 1. Our empirical analysis suggests that the unstable weight decay problem may undesirably damage performance of popular optimizers.

2. L_2 regularization is unstable weight decay in all optimizers that use Momentum. Most popular optimizers in modern deep learning libraries use Momentum and L_2 regularization at the same time, including SGD (with Momentum). Unfortunately, L_2 regularization often damages performance in the presence of Momentum.

3. Decoupled weight decay is unstable weight decay in adaptive gradient methods. All adaptive gradient methods used L_2 regularization as weight decay until Loshchilov & Hutter (2018) proposed decoupled weight decay. However, decoupled weight decay only solves part of the unstable weight decay problem. Decoupled weight decay is still unstable in the presence of Adaptive Learning Rate.

4. Always make weight decay rates stable. We proposed the *stable weight decay* (SWD) method which applies a bias correction factor on decoupled weight decay to make weight decay more stable during training. SWD makes significant improvements over L_2 regularization and decouple weight decay in our experiments. We display the test performance in Table 1. The Adam with SWD (AdamS) is displayed in Algorithm 4.

2 A DYNAMICAL PERSPECTIVE ON WEIGHT DECAY

In this section, we study how weight decay affects learning dynamics and how to measure the weight decay rate from a viewpoint of dynamics. We also analyze the hidden weight decay problem in the presence of Momentum.

We first take vanilla SGD as the studied example, where no Momentum is involved. The vanilla weight decay described by Hanson & Pratt (1989) is given by Equation 1. A more popular implementation in modern deep learning libraries is given by

$$\theta_t = (1 - \eta\lambda)\theta_{t-1} - \eta\frac{\partial L(\theta_{t-1})}{\partial \theta},$$

(2)

where we denote the training loss of a minibatch as $L(\theta)$. It is easy to see that vanilla SGD with L_2 regularization $\frac{\lambda}{2}\|\theta\|^2$ is also given by Equation 2. Suppose the learning rate is fixed in the whole training procedure, then Equation 2 will be identical to Equation 1 if we simply choose $\lambda_0 = \eta\lambda$. However, learning rate decay is quite important for training of deep neural networks. So Equation 2 is not identical to Equation 1 in practice. Which implementation is better?

A dynamical perspective on weight decay. We present a new tool for understanding the effect of weight decay. We define new coordinates $w_t \equiv \theta_t(1 - \eta\lambda)^{-t}$, which is an iteration-dependent

Figure 1: We compared Equation-1-based weight decay and Equation-2-based weight decay by training ResNet18 on CIFAR-10 via vanilla SGD. We divided the learning rate by 10 at the epoch of 80 and 160, which is a popular learning rate scheduler. No matter how we choose λ for Equation-1-based weight decay, Equation-2-based weight decay shows better test performance. It demonstrates that the form $-\eta\lambda\theta$ is a better weight decay implementation than $-\lambda\theta$ in the presence of learning rate schedulers.

Figure 2: We compare the generalization of Vanilla SGD, SGD, SGDW, and SGDS under various weight decay hyperparameters by training VGG16 on CIFAR-10. The optimal performance of SGDS/SGDW is better than the widely used Vanilla SGD and SGD. For Vanilla SGD, SGD, and SGDS, we may choose $\lambda_{L_2} = \lambda_S = 0.0005$ to maintain the optimal performance. But we have to re-tune $\lambda_W = 0.005$ for SGDW. Hyperparameter Setting: $\beta_1 = 0$ for Vanilla SGD; $\beta_1 = 0.9$ for SGD, SGDW, and SGDS. We repeat each simulation for three runs. A similar experimental result for ResNet18 is presented in Appendix B.

rescaled system of θ. In the system of w, we may define the loss function of w as $L^w(w_t) = L((1-\eta\lambda)^t w_t) = L(\theta_t)$. Then, we may rewrite Equation 2 as

$$w_t = w_{t-1} - (1-\eta\lambda)^{-t}\eta\frac{\partial L(\theta_{t-1})}{\partial\theta} = w_{t-1} - (1-\eta\lambda)^{-2t-1}\eta\frac{\partial L^w(w_{t-1})}{\partial w}. \qquad (3)$$

Equation 3 describes learning dynamics in the coordinates of w. The effect of weight decay can be interpreted as flattening the loss landscape of θ by a factor of $(1-\eta\lambda)$ per iteration and increase the learning rate by a factor of $(1-\eta\lambda)^{-2}$ per iteration.

In dynamics of SGD, the learning rate η may be interpreted as unit stepsize or unit time. The dynamical time of deep learning dynamics at t-th iteration can be defined as the cumulative sum of stepsizes: $\tau = t\eta$. Thus, for each time step as $d\tau = \eta$, the effect of weight decay can be measured by the rescaling factor of $(1-\lambda d\tau) \approx (1-\lambda)^{d\tau}$, where the approximation holds for small λ and η. Given the dynamical time τ, the total effect of weight decay after t iterations can be measured by the cumulative rescaling product $(1-\lambda)^\tau$. As it is $(1-\lambda)$ that decides the rescaling rate of the dynamical system w per unit (dynamical) time, we define the *weight decay rate* as $R = 1 - \lambda$, and the *total weight decay effect* after t iterations as $\rho_t = (1-\lambda)^{t\eta} = R^\tau$. The *total weight decay effect* indicates the flattened ratio of the coordinates w after t iterations.

Definition 1 (Stable Weight Decay). *The weight decay is stable if the weight decay rate is constant during training. Otherwise, we define it unstable weight decay.*

Statement 1. *Equation-1-based weight decay is unstable weight decay in the presence of learning rate schedulers.*

If we apply both Equation-1-based weight decay and learning rate decay at the same time, the weight decay rate $R_t = 1 - \frac{\lambda_0}{\eta_t}$ will change with the learning rate decay. We denote the learning rate and the weight decay rate at the iteration t as η_t and R_t, respectively. Thus, we have Statement 1. We hold that Equation 2 is better than Equation 1, because Equation 2 can make the weight decay rate more stable. In Figure 1, we empirically verify that the popular Equation-2-based implementation indeed outperforms the original Equation 1. The Equation-2-based implementation has been widely accepted by modern deep learning libraries.

Statement 2. L_2 *regularization is unstable weight decay in the presence of Momentum.*

We take Heavy Ball Method (HBM) (Zavriev & Kostyuk, 1993), which only uses fixed momentum inertia and dampening coefficients, as the studied example in the presence of Momentum, as HBM-

Figure 3: The test errors of ResNet18 on CIFAR-10. SGDS has a deeper blue basin near dark points ($\leq 4.83\%$). The optimal choices of η and λ are very close for SGDS and SGD.

style Momentum methods are widely used by many popular optimizers. SGD implemented in PyTorch (Paszke et al., 2019) is actually HBM with default hyperparameters. The SGD in TensorFlow (Abadi et al., 2016) follows a slightly different style of Momentum, which uses the learning rate inside the updating rule of Momentum. In this paper, we use the popular implementation of SGD in PyTorch, displayed in Algorithm 1, as the base implementation, as it follows the style of HBM. We leave the SGD implementation of TensorFlow in Appendix D. Our theoretical results can be very easily generalized to the SGD implementation in TensorFlow. We write HBM with L_2 regularization as

$$\begin{cases} m_t = \beta_1 m_{t-1} + \beta_3 (g_t + \lambda_{L_2} \theta_{t-1}) \\ \theta_t = \theta_{t-1} - \eta m_t, \end{cases} \tag{4}$$

where β_1 and β_3 are the hyperparameters. In the common setting of SGD with Momentum, $\beta_1 = 0.9$ and $\beta_3 = 0$. It is commonly believed that L_2 regularization is an optimal weight decay implementation when Adaptive Learning Rate is not involved. Almost all deep learning libraries directly use L_2 regularization as the default weight decay, but we will show L_2 regularization is unstable weight decay and often harms performance slightly when Momentum is involved.

It is easy to understand how L_2 regularization and weight decay are different in the presence of Momentum. We rewrite HBM with L_2 regularization as

$$\begin{cases} m_t = \beta_1 m_{t-1} + \beta_3 g_t \\ \theta_t = \theta_{t-1} - \eta m_t - \eta \lambda_{L_2} \beta_3 \prod_{k=1}^{t} \beta_1^{k-1} \theta_{t-k} = \theta_{t-1} - \eta m_t - \eta \lambda_{L_2} \beta_3 \frac{1-\beta_1^t}{1-\beta_1} \langle \theta_{t-1} \rangle, \end{cases} \tag{5}$$

where we denote the exponential moving average of past θ as $\langle \theta_{t-1} \rangle = \frac{1-\beta_1}{1-\beta_1^t} \prod_{k=1}^{t} \beta_1^{k-1} \theta_{t-k}$. Although $\langle \theta_{t-1} \rangle$ is an approximated value of θ_{t-1}, replacing θ_{t-1} by $\langle \theta_{t-1} \rangle$ still introduces undesirable noise into learning dynamics. Thus, we have Statement 2. We state the SWD correction for HBM as

$$\begin{cases} m_t = \beta_1 m_{t-1} + \beta_3 g_t \\ \theta_t = \left[1 - \frac{\beta_3(1-\beta_1^t)}{1-\beta_1} \eta \lambda \right] \theta_{t-1} - \eta m_t, \end{cases} \tag{6}$$

where $\frac{\beta_3(1-\beta_1^t)}{1-\beta_1} \eta$ is the effective learning rate in HBM, as $m_t \approx \frac{\beta_3(1-\beta_1^t)}{1-\beta_1} \mathbb{E}[g_t]$. As $(1-\beta_1^t)$ converges to 1 soon, we use the simplified $\frac{\beta_3}{1-\beta_1} \eta$ as the bias correction in practice, where a relatively large weight decay rate in the first dozen iterations can work like a model parameter initialization strategy. It is easy to see that the bias correction factor $\frac{\beta_3}{1-\beta_1}$ for weight decay is exactly the difference between our stable weight decay and decoupled weight decay suggested by Loshchilov & Hutter (2018). The pseudocode of SGD with SWD (SGDS) is displayed in Algorithm 2. It may also be called HBM with SWD (HBMS).

Algorithm 1: SGD/SGDW (HBM/HBMW)	**Algorithm 2:** SGDS (HBMS)
$g_t = \nabla L(\theta_{t-1}) + \lambda \theta_{t-1}$;
$m_t = \beta_1 m_{t-1} + \beta_3 g_t$;
$\theta_t = \theta_{t-1} - \eta m_t - \eta \lambda \theta_{t-1}$;	$g_t = \nabla L(\theta_{t-1})$;
$m_t = \beta_1 m_{t-1} + \beta_3 g_t$;
$\theta_t = \theta_{t-1} - \eta m_t - \frac{\beta_3}{1-\beta_1} \eta \lambda \theta_{t-1}$;

Now, we have three kinds of weight decay hyperparameters. We use λ_{L_2}, λ_W, and λ_S denote the L_2 regularization hyperparameter, the decoupled weight decay hyperparameter, and the stable weight decay hyperparameter, respectively. We note that SGDS is different from SGD with Decoupled Weight Decay (SGDW) only by the bias correction factor $\frac{\beta_3}{1-\beta_1}$.

Empirical Analysis on SGDS. We empirically verified that the optimal performance of SGDS/SGDW is often better than the widely used vanilla SGD and SGD, seen in Figures 2 and 9. We leave more empirical results of SGDS in Appendix B, such as Table 2. Particularly, we report the test performance of SGDS and SGD for ResNet18 on CIFAR-10 under various learning rates and weight decay in Figure 3. SGDS has a deeper blue basin than SGD.

It is not well-known that SGDW often outperforms SGD slightly. We believe it is mainly because people rarely know re-tuning λ_W based on $\frac{\beta_3}{1-\beta_1}$ is necessary for maintaining good performance when people switch from SGD to SGDW. As the effective learning rate of SGD is $\frac{\beta_3}{1-\beta_1}\eta$, the weight decay rate of SGDW is actually $R = \frac{1-\beta_1}{\beta_3}\lambda_W$ rather than λ_W. If we use different settings of β_1 and β_3 in decoupled weight decay, we will undesirably change the weight decay rate R unless we re-tune λ_W. However, people usually directly let $\lambda_W = \lambda_{L_2}$ for SGDW in practice. Figure 2 shows that, the optimal λ_{L_2} and λ_S in SGD with $\eta = 1$, $\beta_1 = 0.9$, and $\beta_3 = 0$, are both 0.0005, while the optimal λ_W is 0.005 instead. The optimal λ_{L_2} and λ_S are almost same, while the optimal λ_W is quite different. Thus, the advantage of SGDS over SGDW can save us from re-tuning the weight decay hyperparameter.

3 FIXING WEIGHT DECAY IN ADAPTIVE GRADIENT METHODS

In this section, we study weight decay in dynamics of adaptive gradient methods. Loshchilov & Hutter (2018) first pointed that, when the learning rate is adaptive, the commonly used L_2 regularization is not identical to weight decay. We display Adam and AdamW in Algorithm 3.

Algorithm 3: Adam/AdamW
$g_t = \nabla L(\theta_{t-1}) + \lambda\theta_{t-1}$;
$m_t = \beta_1 m_{t-1} + (1-\beta_1)g_t$;
$v_t = \beta_2 v_{t-1} + (1-\beta_2)g_t^2$;
$\hat{m}_t = \frac{m_t}{1-\beta_1^t}$;
$\hat{v}_t = \frac{v_t}{1-\beta_2^t}$;
$\theta_t = \theta_{t-1} - \frac{\eta}{\sqrt{\hat{v}_t}+\epsilon}\hat{m}_t - \eta\lambda\theta_{t-1}$;

Algorithm 4: AdamS
$g_t = \nabla L(\theta_{t-1})$;
$m_t = \beta_1 m_{t-1} + (1-\beta_1)g_t$;
$v_t = \beta_2 v_{t-1} + (1-\beta_2)g_t^2$;
$\hat{m}_t = \frac{m_t}{1-\beta_1^t}$;
$\hat{v}_t = \frac{v_t}{1-\beta_2^t}$;
$\bar{v}_t = mean(\hat{v}_t)$;
$\theta_t = \theta_{t-1} - \frac{\eta}{\sqrt{\hat{v}_t}+\epsilon}\hat{m}_t - \frac{\eta}{\sqrt{\bar{v}_t}}\lambda\theta_{t-1}$;

Statement 3. *Decoupled weight decay is unstable weight decay in adaptive gradient methods.*

In the following analysis, we ignore the effect of Momentum and focus on the effect of Adaptive Learning Rate. We will show that even decoupled weight decay is still unstable weight decay in the presence of Adaptive Learning Rate. Without losing generality, we first assume the dimensionality of θ is one. Thus, AdamW dynamics can be written as

$$\theta_t = (1 - \eta\lambda)\theta_{t-1} - \eta v_t^{-\frac{1}{2}}\frac{\partial L(\theta_{t-1})}{\partial\theta}, \tag{7}$$

where v_t is the exponential moving average of the squared gradient in Algorithm 3. We interpret $\eta v_t^{-\frac{1}{2}}$ as the effective learning rate of Adam. We clearly see that decoupled weight decay use the vanilla learning rate rather than the effective learning rate. As $v^{-\frac{1}{2}}$ is adaptive, the weight decay rate $R = 1 - \lambda v^{\frac{1}{2}}$ is highly unstable during training. Thus, we have Statement 3. However, a good property of decoupled weight decay is that, as the dynamical time step is $\eta v_t^{-\frac{1}{2}}$, the total weight decay effect after t iterations is

$$\rho_t = \prod_{k=1}^{t}(1 - v_k^{\frac{1}{2}}\lambda)^{\eta v_k^{-\frac{1}{2}}} \approx (1-\lambda)^{t\eta}, \tag{8}$$

where the approximation holds for small λ and η. In summary, the advantage of AdamW is that the total weight effect ρ after training does not depend on v, while the disadvantage of AdamW is that v makes the weight decay rate unstable during training. The analysis can be easily generalized to the multi-dimensional dynamics, where v becomes a vector.

Statement 4. *The bias corrected factor in Algorithm 4 make the weight decay rate more stable.*

It is easy to fix weight decay in one-dimensional dynamics by using the following bias-corrected weight to make the weight decay rate more stable:

$$\theta_t = (1 - \eta v_t^{-\frac{1}{2}} \lambda)\theta_{t-1} - \eta v_t^{-\frac{1}{2}} \frac{\partial L(\theta_{t-1})}{\partial \theta}, \tag{9}$$

where the weight decay rate $R = (1 - \lambda)$. The bias correction factor $v_t^{-\frac{1}{2}}$ make the weight decay rate stable during training in one-dimensional dynamics. However, if we still use the element-wise bias correction factor $v_t^{-\frac{1}{2}}$ in multi-dimensional dynamics, the total weight decay effect ρ will become highly different along different dimensions: $\rho_t = (1 - \lambda)^{\sum_{k=1}^{t} \eta v_k^{-\frac{1}{2}}}$. The anisotropic total weight decay effect is undesirable.

Unfortunately, there is no simple solution to achieving both an ideally stable weight decay rate and an isotropic total weight decay effect at the same time for adaptive gradient methods. This is an internal fault of all optimizers that use Adaptive Learning Rate. Although there is no ideal stable weight decay for Adam, it is possible to apply an isotropic bias correction term to implement relatively more stable weight decay. We propose the updating rule in presence of Adaptive Learning Rate as:

$$\theta_t = (1 - \eta \bar{v}_t^{-\frac{1}{2}} \lambda)\theta_{t-1} - \eta v_t^{-\frac{1}{2}} \frac{\partial L(\theta_{t-1})}{\partial \theta}, \tag{10}$$

where $\bar{v}_t$ is the mean of all elements of the vector v_t. Here $\eta \bar{v}_t^{-\frac{1}{2}}$ is for approximating the effective learning rate. As $\bar{v}_t^{-\frac{1}{2}}$ is isotropic, the total weight decay effect is still same along different dimensions. SWD is more stable than decoupled weight decay in the presence of Adaptive Learning Rate, and may maintain the isotropic total weight decay effect. We have Statement 4. We present AdamS in Algorithm 4. The source code is available to the public in Supplementary Materials.

4 EMPIRICAL ANALYSIS AND DISCUSSION

In this section, we empirically study how the SWD-corrected optimizers are compared with conventional optimizers. We choose Adam as the base optimizer, and train popular deep models, including ResNet18/ResNet34 (He et al., 2016), VGG16 (Simonyan & Zisserman, 2014), DenseNet121 (Huang et al., 2017), and GoogLeNet (Szegedy et al., 2015), on CIFAR-10 and CIFAR-100 (Krizhevsky et al., 2009). The hyperparameter settings can be found in Appendix A.

Empirical results. Figure 4 shows the learning curves of AdamS, AdamW, and Adam on several benchmarks. In our experiments, AdamS always leads to lower test errors, and sometimes leads to lower training losses. However, Figure 5 shows that, even if with similar or higher training losses, AdamS still generalizes significantly better than AdamW, Adam, and popular Adam variants. Figure 6 displays the learning curves of all adaptive gradient methods. The test performance of other models can be found in Table 1. Simply fixing weight decay in Adam by SWD even outperforms recent Adam variants. Figure 7 further demonstrates that AdamS consistently outperforms Adam and AdamW under various weight decay hyperparameters. According to Figure 7, we also notice that the optimal decoupled weight decay hyperparameter in AdamW can be very different from L_2 regularization and stable weight decay, but the corresponding optimal weight decay rates of three weight decay implementations are often similar. Finally, a supplementary experiment on language modeling is presented in Figure 16 of Appendix C.

Popular Adam variants often generalizes worse than SGD. Some papers (Luo et al., 2019; Chen & Gu, 2018) argued that their proposed Adam variants may generalize as well as SGD. However, we found that this argument is contracted with our comparative experimental results, such as Table 1. In our empirical analysis, these advanced Adam variants may narrow but not completely close the generalization gap between adaptive gradient methods and SGD. SGD with a fair weight decay

Figure 4: The learning curves of AdamS, AdamW, and Adam on CIFAR-10 and CIFAR-100. Top Row: Test curves. Bottom Row: Training curves. AdamS shows significantly better generalization than AdamW and Adam.

Figure 5: The scatter plot of training losses and test errors during final 40 epochs of training ResNet34 on CIFAR-100. Even with similar or higher training losses, AdamS still generalizes better than other Adam variants. We leave the scatter plot on CIFAR-10 in Appendix C.

Figure 6: The learning curves of all adaptive gradient methods by training ResNet34 on CIFAR-100. AdamS outperforms other Adam variants. The test performance of other models can be found in Table 1.

Figure 7: The test errors of VGG16 on CIFAR-10 with various weight decay rates. The displayed weight decay value of AdamW has been rescaled by the bias correction factor ≈ 0.001. A similar experimental result for ResNet34 is presented in Appendix C.

hyperparameter as the baseline performance usually generalizes better than recent adaptive gradient methods. The main problem may lie in weight decay. SGD with weight decay $\lambda = 0.0001$, a common setting in related papers, is often not a good baseline, as $\lambda = 0.0005$ often shows better generalization on CIFAR-10 and CIFAR-100, seen in Figures 2, 9 and 7. We also conduct comparative experiments with $\lambda = 0.0001$, seen in Table 3 of Appendix C. Under the setting $\lambda = 0.0001$, while some existing Adam variants may outperform SGD sometimes due to the lower baseline performance of SGD, AdamS shows superior test performance. For example, for ResNet18 on CIFAR-10, the test error of AdamS is lower than SGD by nearly one point and no other Adam variant may compare with AdamS.

Two metrics for weight decay. The main effect of weight decay for deep learning dynamics can be reflected by these two metrics: the weight decay rate R and the total weight decay effect ρ. We summary two principles about weight decay critically related to performance. First, we need to make the weight decay rate as stable as possible during training. Second, we need choose the optimal

Figure 8: The test errors of ResNet18 on CIFAR-10. AdamS has a much deeper and wider basin near dark points ($\leq 4.9\%$). The optimal test error of AdamS, AdamW, and Adam are 4.52%, 4.90%, and 5.49%, respectively. The displayed weight decay value of AdamW has been rescaled by the bias correction factor ≈ 0.001.

weight decay hyperparameter to maintain the optimal total weight decay effect. These two principles lead to two linear scaling rules.

Two linear scaling rules. We report two kinds of *linear scaling rules* of weight decay and learning rates for selecting the weight decay hyperparameter λ. First, as Statement 1 and Figure 1 indicate, the learning rate scheduler should be applied to both the learning rate and weight decay in the form of $-\eta_t \lambda \theta_{t-1}$ during training. Second, the initial learning rate and the weight decay hyperparameter λ are linearly coupled for the total weight decay effect. The expression of the total weight decay effect in Equation 8 mainly depends on the weight decay hyperparameter λ, the learning rate η, and the number of iterations t. Usually, people do not fine tune the number of iterations t. Given the fixed t and the optimal weight decay rate R, the total weight decay effect ρ approximately depends on $\eta\lambda$. The second linear scaling rule indicates that, in the procedure of fine-tuning hyperparameters, we should try larger λ for smaller initial learning rates to maintain the optimal total weight decay effect. We observe that the blue basin of AdamS and AdamW in Figure 8 both approximately reflect the linear scaling rule, which was also reported by Van Laarhoven (2017); Loshchilov & Hutter (2018). We point that its theoretical mechanism closely relates to the total weight decay effect.

A novel interpretation of weight decay. The effect of weight decay can be interpreted as iteration-wisely flattening the loss landscape and increasing the learning rate at the same time. Thus, it is not surprising that increasing weight decay and increasing learning rate have some similar influence on optimization performance (Van Laarhoven, 2017; Zhang et al., 2018; Hoffer et al., 2018). However, simply increasing learning rates cannot replace weight decay in practice. For weight decay, increasing the learning rate by a factor of $(1 - \eta\lambda)^{-2}$ is iteration-wise during training, and flattening the loss landscape by a factor of $(1 - \eta\lambda)$ per iteration must happen at the same time. This interpretation of weight decay actually controls the adaptivity of learning rates in learning dynamics, as the total weight decay effect ρ is isotropic along different dimensions. This may explain why stable weight decay can effectively fix the ill-conditioned flat minima selection of adaptive gradient methods revealed by Xie et al. (2020b) from a diffusion perspective (Xie et al., 2020a).

5 CONCLUSION

We proposed the SWD method which applies the bias correction on decoupled weight decay to make the weight decay rate more stable during training. The empirical results demonstrate that SWD makes significant improvements over L_2 regularization and decoupled weight decay (when they are different). Particularly, we observe that the advantage of existing Adam variants is very weak compared with the performance improvement by simply fixing weight decay. The standard Adam with SWD, with no extra hyperparameter, can outperform complex Adam variants, such as Padam and AdaBound, which have more hyperparameters. Although our analysis mainly focused on Adam, SWD can be easily combined with other Adam variants, too. The proposed principle and method of stable weight decay expands our understanding towards the role of weight decay in deep learning. It will be interesting to further investigate the theory for the weight decay rate in future.

REFERENCES

Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, et al. Tensorflow: A system for large-scale machine learning. In *12th {USENIX} symposium on operating systems design and implementation ({OSDI} 16)*, pp. 265–283, 2016.

Jinghui Chen and Quanquan Gu. Closing the generalization gap of adaptive gradient methods in training deep neural networks. *arXiv preprint arXiv:1806.06763*, 2018.

Tianqi Chen, Mu Li, Yutian Li, Min Lin, Naiyan Wang, Minjie Wang, Tianjun Xiao, Bing Xu, Chiyuan Zhang, and Zheng Zhang. Mxnet: A flexible and efficient machine learning library for heterogeneous distributed systems. *arXiv preprint arXiv:1512.01274*, 2015.

John Duchi, Elad Hazan, and Yoram Singer. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of machine learning research*, 12(Jul):2121–2159, 2011.

Stephen José Hanson and Lorien Y Pratt. Comparing biases for minimal network construction with back-propagation. In *Advances in neural information processing systems*, pp. 177–185, 1989.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Geoffrey Hinton, Nitish Srivastava, and Kevin Swersky. Neural networks for machine learning lecture 6a overview of mini-batch gradient descent. 2012.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Elad Hoffer, Ron Banner, Itay Golan, and Daniel Soudry. Norm matters: efficient and accurate normalization schemes in deep networks. In *Advances in Neural Information Processing Systems*, pp. 2160–2170, 2018.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *3rd International Conference on Learning Representations, ICLR 2015*, 2015.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Anders Krogh and John A Hertz. A simple weight decay can improve generalization. In *Advances in neural information processing systems*, pp. 950–957, 1992.

Liyuan Liu, Haoming Jiang, Pengcheng He, Weizhu Chen, Xiaodong Liu, Jianfeng Gao, and Jiawei Han. On the variance of the adaptive learning rate and beyond. In *International Conference on Learning Representations*, 2019.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2018.

Liangchen Luo, Yuanhao Xiong, Yan Liu, and Xu Sun. Adaptive gradient methods with dynamic bound of learning rate. *7th International Conference on Learning Representations, ICLR 2019*, 2019.

Mitchell Marcus, Beatrice Santorini, and Mary Ann Marcinkiewicz. Building a large annotated corpus of english: The penn treebank. 1993.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *Advances in neural information processing systems*, pp. 8026–8037, 2019.

Sashank J Reddi, Satyen Kale, and Sanjiv Kumar. On the convergence of adam and beyond. *6th International Conference on Learning Representations, ICLR 2018*, 2019.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1–9, 2015.

Seiya Tokui, Ryosuke Okuta, Takuya Akiba, Yusuke Niitani, Toru Ogawa, Shunta Saito, Shuji Suzuki, Kota Uenishi, Brian Vogel, and Hiroyuki Yamazaki Vincent. Chainer: A deep learning framework for accelerating the research cycle. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 2002–2011, 2019.

Twan Van Laarhoven. L2 regularization versus batch and weight normalization. *arXiv preprint arXiv:1706.05350*, 2017.

Ashia C Wilson, Rebecca Roelofs, Mitchell Stern, Nati Srebro, and Benjamin Recht. The marginal value of adaptive gradient methods in machine learning. In *Advances in Neural Information Processing Systems*, pp. 4148–4158, 2017.

Zeke Xie, Issei Sato, and Masashi Sugiyama. A diffusion theory for minima selection: Stochastic gradient descent escapes from sharp minima exponentially fast. *arXiv preprint arXiv:2002.03495*, 2020a.

Zeke Xie, Xinrui Wang, Huishuai Zhang, Issei Sato, and Masashi Sugiyama. Adai: Separating the effects of adaptive learning rate and momentum inertia. *arXiv preprint arXiv:2006.15815*, 2020b.

Manzil Zaheer, Sashank Reddi, Devendra Sachan, Satyen Kale, and Sanjiv Kumar. Adaptive methods for nonconvex optimization. In *Advances in neural information processing systems*, pp. 9793–9803, 2018.

SK Zavriev and FV Kostyuk. Heavy-ball method in nonconvex optimization problems. *Computational Mathematics and Modeling*, 4(4):336–341, 1993.

Matthew D Zeiler. Adadelta: an adaptive learning rate method. *arXiv preprint arXiv:1212.5701*, 2012.

Guodong Zhang, Chaoqi Wang, Bowen Xu, and Roger Grosse. Three mechanisms of weight decay regularization. In *International Conference on Learning Representations*, 2018.

A   EXPERIMENTAL DETAILS

Data Preprocessing: We perform the common per-pixel zero-mean unit-variance normalization, horizontal random flip, and 32×32 random crops after padding with 4 pixels on each side.

Hyperparameter Settings: We select the optimal learning rate for each experiment from $\{0.001, 0.01, 0.1, 1, 10\}$ for non-adaptive gradient methods and use the default learning rate for adaptive gradient methods. In the experiments on CIFAF-10 and CIFAR-100: $\eta = 1$ for Adai; $\eta = 0.1$ for AdaiS; $\eta = 0.1$ for SGD and SGDS; $\eta = 0.001$ for AdamS, Adam, AMSGrad, AdamW, and AdaBound; $\eta = 0.01$ for Padam. For the learning rate schedule, the learning rate is divided by 10 at the epoch of $\{80, 160\}$ for CIFAR-10 and $\{100, 150\}$ for CIFAR-100, respectively. The batch size is set to 128 for both CIFAR-10 and CIFAR-100.

The strength of L_2 regularization and SWD is default to 0.0005 as the baseline. Considering the linear scaling rule, we choose $\lambda_W = \frac{\lambda_{L_2}}{\eta}$. Thus, the weight decay of AdamW uses $\lambda_W = 0.5$ for CIFAR-10 and CIFAR-100. As for SWD in AdaiS, we choose $\lambda_S = 0.005$ for achieve a similar total weight decay effect as SGD. The basic principle of choosing weight decay strength is to let all optimizers have either a similar weight decay rate R or a similar total weight decay effect ρ to the baseline L_2 regularization.

Table 2: Test performance comparison of Adai, AdaiS, SGD, and SGDS. Stable/Decoupled Weight Decay often outperform L_2 regularization for optimizers involving in momentum. We report the mean and the standard deviations (as the subscripts) of the optimal test errors computed over three runs of each experiment.

DATASET	MODEL	ADAIS	ADAI	SGDS	SGD
CIFAR-10	RESNET18	$\mathbf{4.59}_{0.16}$	$4.74_{0.14}$	$4.69_{0.09}$	$5.01_{0.03}$
	VGG16	$\mathbf{5.81}_{0.07}$	$6.00_{0.09}$	$6.28_{0.07}$	$6.42_{0.02}$
CIFAR-100	DENSENET121	$\mathbf{19.44}_{0.21}$	$19.59_{0.38}$	$19.61_{0.26}$	$19.81_{0.33}$
	GOOGLENET	$\mathbf{20.50}_{0.25}$	$20.55_{0.32}$	$20.68_{0.03}$	$21.21_{0.29}$

Figure 9: We compare the generalization of Vanilla SGD, SGD, SGDW, and SGDS with various weight decay hyperparameters by training ResNet18 on CIFAR-10. The optimal weight decay rates are near 0.0005 for all three weight implementations. The optimal performance of SGDS/SGDW is better than Vanilla SGD and SGD. For Vanilla SGD, SGD, and SGDS, we may safely choose $\lambda_{L_2} = \lambda_S = 0.0005$. But we have to re-tune $\lambda_W = 0.005$ for SGDW. Hyperparameter Setting: $\beta_1 = 0$ for Vanilla SGD; $\beta_1 = 0.9$ for SGD, SGDW, and SGDS.

We set the momentum hyperparameter $\beta_1 = 0.9$ for SGD and SGDS. As for other optimizer hyperparameters, we apply the default hyperparameter settings directly.

We leave the empirical results with the weight decay setting $\lambda = 0.0001$ in Appendix C.

The source code of AdamS and SGDS in Supplementary Materials is available to the public.

B SUPPLEMENTARY FIGURES AND RESULTS OF SGD WITH MOMENTUM AND ADAI

We compare SGDS, SGDW, vanilla SGD and SGD under various weight decay hyperparameters by training ResNet18 on CIFAR-10. We observe that the optimal performance of SGDS/SGDW is better than vanilla SGD and SGD in Figure 9. The advantage of SGDS over SGDW is that we do not need to fine-tune the weight decay hyperparameters based on $\frac{\beta_3}{1-\beta_1}$.

We report the learning curves of SGD and SGDS in Figure 10. SGDS compares favorably with SGD.

Based on a diffusion theoretical framework (Xie et al., 2020a), Xie et al. (2020b) proposed Adaptive Inertia Estimation (Adai) that uses adaptive momentum inertia instead of Adaptive Learning Rate to help training. Adaptive inertia can be regarded as an inertia-adaptive variant of HBM. The previous analysis on HBM can be easily generalized to Adai. We display Adai with SWD (AdaiS) in Algorithm 6. We report the learning curves of Adai and AdaiS in Figure 11, which may verify the generalization advantage of AdaiS over Adai.

Figure 10: Generalization analysis on SGDS and SGD with L_2 regularization. Hyperparameter Setting: $\lambda_S = \lambda_{L_2} = 0.0005$ and $\beta_1 = 0.9$.

Figure 11: Generalization analysis on AdaiS and Adai with L_2 regularization. Hyperparameter Setting: $\lambda_S = \lambda_{L_2} = 0.0005$.

C SUPPLEMENTARY FIGURES AND RESULTS OF ADAPTIVE GRADIENT METHODS

We report the learning curves of all adaptive gradient methods in Figure 12. They shows that vanilla Adam with SWD can outperform other complex variants of Adam.

Figure 13 displays the scatter plot of training losses and test errors during final 40 epochs of training DenseNet121 on CIFAR-100.

Figure 14 displays the test performance of AdamS, AdamW, and Adam under various weight decay hyperparameters of ResNet34 on CIFAR-100.

We train ResNet18 on CIFAR-10 for 900 epochs to explore the performance limit of AdamS, AdamW, and Adam in Figure 15.

Table 3 displays the test performance with $\lambda = 0.0001$, which is a common weight decay setting in related papers.

Figure 12: The learning curves of adaptive gradient methods.

Figure 13: Even if with similar or higher training losses, AdamS still generalizes better than AdamW and Adam. The scatter plot of training losses and test errors during final 50 epochs of training VGG16 on CIFAR-10 and DenseNet121 on CIFAR-100.

Figure 14: We compare the generalization of Adam, AdamW, and AdamS with various weight decay rates by training ResNet34 on CIFAR-100. The displayed weight decay of AdamW in the figure has been rescaled by the bias correction factor ≈ 0.001. The optimal test performance of AdamS is significantly better than AdamW and Adam.

Figure 15: We train ResNet18 on CIFAR-10 for 900 epochs to explore the performance limit of AdamS, AdamW, and Adam. The learning rate is divided by 10 at the epoch of 300 and 600. AdamS achieves the most optimal test error, 4.70%.

(a) Test Perplexity   (b) Training Perplexity

Figure 16: Language Modeling. The learning curves of AdamS, AdamW, and Adam for LSTM on Penn TreeBank. AdamS has better test performance than AdamW and Adam for LSTM. The optimal test perplexity of AdamS, AdamW, and Adam are 69.90, 72.88, and 77.01, respectively.

Table 3: Test performance comparison of optimizers with $\lambda_{L_2} = \lambda_S = 0.0001$ and $\lambda_W = 0.1$. AdamS still show better test performance than popular adaptive gradient methods and SGD.

DATASET	MODEL	SGD	ADAMS	ADAM	AMSGRAD	ADAMW	ADABOUND	PADAM	YOGI	RADAM
CIFAR-10	RESNET18	5.58	**4.69**	6.08	5.72	5.33	6.87	5.83	5.43	5.81
	VGG16	6.92	**6.16**	7.04	6.68	6.45	7.33	6.74	6.69	6.73
CIFAR-100	DENSENET121	**20.98**	21.35	24.39	22.80	22.23	24.23	22.26	22.40	22.40
	GOOGLENET	21.89	**21.60**	24.60	24.05	21.71	25.03	26.69	22.56	22.35

Finally, we present the learning curves for language modeling experiments in Figure 16. As we expect, AdamS outperforms AdamW and Adam again. We use a classical language model, two-layer Long Short-Term Memory (LSTM) (Hochreiter & Schmidhuber, 1997) with 512 embedding dimensions and 512 hidden dimensions, which has 14 million model parameters. The benchmark task is the word-level Penn TreeBank (Marcus et al., 1993). Hyperparameter Setting: $\lambda = 0.00005$, $\eta = 0.001$, and the dropout probability is 0.5.

D   ADDITIONAL ALGORITHMS

Algorithm 5 is the TensorFlow implementation for SGD.

Algorithm 6 is the implementation of Adai, AdaiW, and AdaiS. As $\frac{\beta_3}{1-\beta_1}$ is always 1 in Adai, AdaiW is identical to AdaiS.

We note that the implementation of AMSGrad in Algorithm 7 is the popular implementation in PyTorch. We use the PyTorch implementation in our paper, as it is widely used in practice.

Algorithm 5: SGD in TensorFlow

$g_t = \nabla L(\theta_{t-1}) + \lambda \theta_{t-1}$;
$m_t = \beta_1 m_{t-1} - \eta g_t$;
$\theta_t = \theta_{t-1} + m_t$;

Algorithm 6: Adai /AdaiS=AdaiW

$g_t = \nabla L(\theta_{t-1}) + \lambda \theta_{t-1}$;
$v_t = \beta_2 v_{t-1} + (1 - \beta_2) g_t^2$;
$\hat{v}_t = \frac{v_t}{1 - \beta_2^t}$;
$\bar{v}_t = mean(\hat{v}_t)$;
$\beta_{1t} = (1 - \beta_0 \frac{\hat{v}_t}{\bar{v}_t}).Clip(0, 1 - \epsilon)$;
$m_t = \beta_{1t} m_{t-1} + (1 - \beta_{1t}) g_t$;
$\hat{m}_t = \frac{m_t}{1 - \prod_{k=1}^t \beta_{1k}}$;
$\theta_t = \theta_{t-1} - \eta \hat{m}_t - \eta \lambda \theta_{t-1}$;

Algorithm 7: AMSGrad/AMSGradW

$g_t = \nabla L(\theta_{t-1}) + \lambda \theta_{t-1}$;
$m_t = \beta_1 m_{t-1} + (1 - \beta_1) g_t$;
$v_t = \beta_2 v_{t-1} + (1 - \beta_2) g_t^2$;
$\hat{m}_t = \frac{m_t}{1 - \beta_1^t}$;
$v_{max} = max(v_t, v_{max})$;
$\hat{v}_t = \frac{v_{max}}{1 - \beta_2^t}$;
$\theta_t = \theta_{t-1} - \frac{\eta}{\sqrt{\hat{v}_t} + \epsilon} \hat{m}_t - \eta \lambda \theta_{t-1}$;

Algorithm 8: AMSGradS

$g_t = \nabla L(\theta_{t-1})$;
$m_t = \beta_1 m_{t-1} + (1 - \beta_1) g_t$;
$v_t = \beta_2 v_{t-1} + (1 - \beta_2) g_t^2$;
$\hat{m}_t = \frac{m_t}{1 - \beta_1^t}$;
$v_{max} = max(v_t, v_{max})$;
$\hat{v}_t = \frac{v_{max}}{1 - \beta_2^t}$;
$\bar{v}_t = mean(\hat{v}_t)$;
$\theta_t = \theta_{t-1} - \frac{\eta}{\sqrt{\hat{v}_t} + \epsilon} \hat{m}_t - \frac{\eta}{\sqrt{\bar{v}_t}} \lambda \theta_{t-1}$;