Energy-based Predictive Representations
for Partially Observed Reinforcement Learning

Abstract

In real world applications, it is usually common for a reinforcement learning algorithm to handle partial observability, which is not captured by a Markov decision process (MDP). Although partially observable Markov decision processes (POMDPs) have been precisely motivated by this requirement, they raise significant computational and statistical hardness challenges in learning and planning. In this work, we introduce the *Energy-based Predictive Representation (EPR)* to support a unified approach to practical reinforcement learning algorithm design for both the MDP and POMDP settings, which enables *learning, exploration, and planning* to be handled in a coherent way. The proposed framework relies on a powerful neural energy-based model to extract a sufficient representation, from which Q-functions can be efficiently approximated. With such a representation, confidence can be efficiently computed to allow optimism/pessimism in the face of uncertainty to be efficiently implemented in planning, enabling effective management of the exploration versus exploitation tradeoff. An experimental investigation shows that the proposed algorithm can achieve state-of-the-art performance in both MDP and POMDP settings.

1 INTRODUCTION

Reinforcement learning (RL) based on Markov Decision Processes (MDPs) has proved to be extremely effective in several real world decision-making problems [Levine et al., 2016, Jiang et al., 2021]. However, the success of most RL algorithms [Ren et al., 2022b, Zhang et al., 2022] relies heavily on the assumption that the environment state is fully observable to the agent. In practice, such an assumption can be easily violated in the presence of observational noise. To address this issue, Partially Observable Markov Decision

Processes (POMDPs) [Åström, 1965] have been proposed for capturing the inherent uncertainty about the state arising from partial observations.

However, the flexibility of POMDPs creates significant statistical and computational hardness in terms of planning, exploration and learning. In particular, the partial observability induces a non-Markovian dependence over the *entire history*, which expands the spaces of observation sequences or state space distributions, therefore, incurs significant representation challenges. In fact, due to the full history dependence, it has been proved that the planning for even finite-horizon tabular POMDPs is NP-hard without additional structural assumptions [Papadimitriou and Tsitsiklis, 1987] and the sample complexity for learning POMDPs can be exponential with respect to the horizon [Jin et al., 2020a]. These complexities only become more demanding in continuous state spaces and real-world scenarios.

On the other hand, despite the theoretical hardness in the worst cases, there is sufficient structures in real-world POMDPs that can be exploited to bypass the aforementioned complexities. Recently, observable POMDPs with invertible emissions have been investigated to justify the finite-length sliding window heuristic in tabular cases [Azizzadenesheli et al., 2016, Guo et al., 2016, Jin et al., 2020a, Golowich et al., 2022a], which has been further extended with function approximation for large and continuous state POMDPs [Wang et al., 2022, Uehara et al., 2022]. Although these algorithms can exploit particular structure efficiently in terms of the sample complexity, they rely on unrealistic computation oracles, and are thus not applicable in practice. In this paper, we consider the following natural question:

*How can one design **efficient** and **practical** algorithms for structured POMDPs?*

In particular, we would like to exploit special structures that allows approximation to bypass inherent worst-case difficulties. By "efficient" we mean considering **learning**, **planning** and **exploration** in a unified manner that can

Submitted to the 39th Conference on Uncertainty in Artificial Intelligence (UAI 2023). **To be used for reviewing only**.

balance errors in each component and reduce unnecessary computation, while by "practical" we mean the algorithm retains sufficient flexibility and can be easily implemented and deployed in real-world scenarios.

There have been many attempts to address this question. The most straightforward idea is to extend model-free RL methods, including policy gradient and Q-learning, with a memory-limited parametrization, *e.g.*, recurrent networks [Wierstra et al., 2007, Hausknecht and Stone, 2015, Zhu et al., 2017]. Alternatively, in model-based RL [Kaelbling et al., 1998], an approximation of the latent dynamics can be estimated and a posterior over latent states (*i.e.*, beliefs) maintained, in principle allowing an optimal policy to be extracted via dynamic programming upon beliefs. Following this idea, Deisenroth and Peters [2012] and Igl et al. [2018], Gregor et al. [2019], Zhang et al. [2019], Lee et al. [2020] consider Gaussian process or deep model parametrizations, respectively. Such methods are designed based on implicit assumptions about structure through the parameterization choices of the models. However, these approaches suffer from sub-optimal performance due to several compounding factors: **i),** approximation error from inaccurate parametrizations of the learnable components (policy, value function, model, belief), **ii),** a sub-optimal policy induced by approximated planning (through policy gradient or dynamic progamming), and **iii),** the neglect of exploration when interacting with the environment.

As an alternative, spectral representation approaches provide an alternative strategy based on extracting a sufficient representation that can support learning, planning and exploration. In this vein Azizzadenesheli et al. [2016] investigate spectral methods for latent variable model estimation in POMDPs, but only consider tabular scenarios with finite state and action cases. Predictive State Representations (PSR) [Littman and Sutton, 2001] also leverage spectral decomposition, but instead of recovering an underlying latent variable model, they learn an *equivalent sufficient* representation of belief. These methods have been extended to real-world settings with continuous observations and actions by exploiting kernel embeddings [Boots et al., 2013] or deep models [Downey et al., 2017, Venkatraman et al., 2017, Guo et al., 2018]. However, tractable planning and efficient exploration upon spectral representations has yet to be thoroughly developed [Zhan et al., 2022].

In this paper, we propose *Energy-based Predictive Representation (EPR)* to support efficient and tractable learning, planning, and exploration in POMDPs (and MDPs), as a solution to the aforementioned question. More specifically:

- We propose a flexible nonlinear energy-based model for induced belief-state MDPs *without explicit parameterization of beliefs*, providing a principled *linear sufficient* representation for the state-action value function.
- We reveal the connection between EPR and PSR, while

also illustrating the differences, to demonstrate the modeling ability of the proposed EPR.

- We provide *computationally-tractable* learning and planning algorithms for EPR that implement the principles of optimism and pessimism in the face of uncertainty for online and offline RL, balancing exploration and exploitation.
- We conduct a comprehensive comparison to existing state-of-the-art RL algorithms in both MDP and POMDP benchmarks, demonstrating superior empirical performance of the proposed EPR.

2 PRELIMINARIES

In this section, we introduce POMDPs and their degenerate case of MDPs, identifying the special structures that will be used to derive the proposed representation learning method.

Partially Observable Markov Decision Processes. Formally, we define a partially observable Markov decision process (POMDP) as a tuple $\mathcal{P} = (\mathcal{S}, \mathcal{A}, \mathcal{O}, r, H, \mu, P, O)$, where H is a positive integer denoting the length of horizon; μ is the initial distribution of state, $r : \mathcal{S} \times \mathcal{A} \rightarrow [0, 1]$, the reward function, and $\mathcal{S}, \mathcal{A}, \mathcal{O}$ denote the state, action and observation space, respectively. $P(\cdot|s, a) : \mathcal{S} \times \mathcal{A} \rightarrow \Delta(\mathcal{S})$ is the transition kernel, capturing the dynamics between states, and $O(\cdot|s) : \mathcal{S} \rightarrow \Delta(\mathcal{O})$ is the emission kernel, where $\Delta(\cdot)$ denotes the set of probability measures over the support.

Initially, given a state $s_1 \sim \mu(s)$ as a starting point, at each step $h \in [1, H]$, the agent takes an action $a \in \mathcal{A}$, a new state s_{h+1} is generated $s_{h+1} \sim P(\cdot|s_h, a_h)$, and the agent observes $o_{h+1} \sim O(\cdot|s_{h+1})$ and reward $r(s_{h+1}, a_{h+1})$. Due to partial observability, the dependence between observations is non-Markovian, hence, we define a policy $\pi = \{\pi_t\}$ where $\pi_t : \mathcal{O} \times (\mathcal{A} \times \mathcal{O})^t \rightarrow \Delta(\mathcal{A})$ to depend on the whole history, *i.e.*, $x_t = \{o_0, \{a_i, o_{i+1}\}_{i=0}^{t-1}\}$. The corresponding value for policy π can be defined as $V^\pi = \mathbb{E}_\pi \left[\sum_{h=1}^H r(s_h, a_h) \right]$, and the objective is to find the optimal policy $\pi^* = \text{argmax}_\pi V^\pi$.

Markov decision processes (MDPs) are a degenerate case of POMDPs, where $\mathcal{S} = \mathcal{O}$ and $O(o|s) = \delta(o = s)$, and can be specified as $\mathcal{M} = (\mathcal{S}, \mathcal{A}, r, H, \mu, P)$. One can also convert a POMDP to an MDP by treating the whole history $x_t = \{o_0, \{a_i, o_{i+1}\}_{i=0}^{t-1}\}$ as the state. Specifically, following [Kaelbling et al., 1998], we define the belief $b : \mathcal{O} \times (\mathcal{A} \times \mathcal{O})^t \rightarrow \Delta(\mathcal{S}), \forall t \in \mathbb{N}^+$, which can be recursively defined as: $b(s_1|o_1) = P(s_1|o_1)$, and

$$b(s_{t+1}|x_{t+1}) = \frac{b(s_t|x_t)P(s_{t+1}|s_t, a_t)O(o_{t+1}|s_{t+1})}{\int b(s_t|x_t)P(s_{t+1}|s_t, a_t)O(o_{t+1}|s_{t+1})\,\mathrm{d}s_t\,\mathrm{d}o_{t+1}}. \tag{1}$$

Each entry of the belief state describes the probability of the underlying state given the past history. Furthermore, with a slight abuse of notation, we use b_t to denote the belief

state at step t. Then, one can construct the equivalent belief MDP $\mathcal{M}_b = (\mathcal{X}, \mathcal{A}, R_h, H, \mu_b, T_b)$ with $\mathcal{X}$ denoting the set of possible histories, and

$$\mu_b := \int b(s|o_1)\mu(o_1)do_1, \tag{2}$$

$$R_t(b, a) = \int b_t(s_h)r(s_t, a)ds_h, \tag{3}$$

$$T_b(b_{t+1}|b_t, a_t) := \int_{\mathcal{O}} \mathbf{1}_{b_{t+1}=b(x_{t+1})} P(o_{t+1}|b_t, a_t)\, \mathrm{d}o_{t+1}. \tag{4}$$

Therefore, the corresponding value function $V_h^\pi(b_h)$ and $Q_h^\pi(b_h, a_h)$ for the belief MDP given a policy π can be defined as:

$$V_h^\pi(b_h) = \mathbb{E}\left[\sum_{t=h}^{H} R_t(b_t, a_t)|x_h\right], \tag{5}$$

$$Q_h^\pi(b_h, a_h) = \mathbb{E}\left[\sum_{t=h}^{H} R_t(b_t, a_t)|b_h, a_h\right]. \tag{6}$$

Following the MDP perspective, we also have the Bellman recursive equation:

$$V_h^\pi(b_h) = \mathbb{E}_\pi\left[Q_h^\pi(b_h, a_h)\right], \tag{7}$$

$$Q_h^\pi(b_h, a_h) = R_h(b_h, a_h) + \mathbb{E}_{T_b}\left[V_{h+1}^\pi(b_{h+1})\right]. \tag{8}$$

One can still apply a dynamic programming style approach to solve POMDPs according to (7), however since the belief depends on the entire history, the number of possible beliefs can still be infinite even the number of states is finite. To combat with these essential difficulties, we will leverage two particular structures, observability and linearity, as introduced below.

Observability in POMDPs. It has been shown [Golowich et al., 2022b, Uehara et al., 2022] that for POMDPs with an observability assumption, one can relax the history dependence with a short window, bypassing the exponential sample and planning complexity w.r.t. horizon length [Golowich et al., 2022a,b]. Specifically, the observability property for POMDPs is defined as follows.

Assumption 1 ([Golowich et al., 2022b]). *The POMDP with emission model O satisfies γ-observability if for arbitrary beliefs b and b' over states, $\|\langle O, b\rangle - \langle O, b'\rangle\|_1 \geqslant \gamma \|b - b'\|_1$, where $\langle O, b\rangle := \int O(o|s)b(s)ds$.*

A key consequence of observability is that, the belief can be well approximated with a short history window [Golowich et al., 2022b], and one can construct an approximate MDP based on a finite belief history, which eliminates the exponential complexity induced by full history dependence. Specifically, we denote L as the length of the window. Then, defining $x_t^L = \left\{o_{t-L}, \{a_i, o_{i+1}\}_{i=t-L}^{t}\right\} \in \mathcal{X}^L$, the approximated beliefs b^L follow the same recursive definition

as (1) but with only finite history x_t^L starting from the uniform belief. This immediately induces an approximate MDP $\mathcal{M}_b^L = \left(\mathcal{X}^L, \mathcal{A}, R_h^L, H, \mu_b, T_b^L\right)$ according to (4) with b^L, instead of b. Theorem 2.1 in Golowich et al. [2022a] proves that the approximation error of the finite-memory belief MDP is small for observable POMDPs. Hence, with slight abuse of notation, we still use b to represent b^L throughout the paper.

Linearity in MDPs. To handle the complexity induced by large state spaces, linear/low-rank structures have been introduced in MDPs [Jin et al., 2020b] for effective function approximation, which leverages spectral factorization of the transition dynamics and reward:

$$P(s'|s, a) = \langle \phi(s, a), \mu(s')\rangle,\ r(s, a) = \langle \phi(s, a), \theta\rangle, \tag{9}$$

where $\phi : \mathcal{S} \times \mathcal{A} \to \mathcal{H}$, $\mu : \mathcal{S} \to \mathcal{H}$ are two feature maps to a Hilbert space $\mathcal{H}$. Under such an assumption, we can represent the state-action value function Q^π for an arbitrary policy π by:

$$Q^\pi(s, a) = r(s, a) + \gamma \int V^\pi(s')P(s'|s, a)ds' \tag{10}$$

$$= \left\langle \phi(s, a), \theta + \gamma \int V^\pi(s')\mu(s')ds'\right\rangle, \tag{11}$$

which implies that instead of a complicated function space defined on the raw state space, one can design a computationally efficient planning and sample efficient exploration algorithm in the space linearly spanned by ϕ. In fact, from the correspondence between policy and Q-function as discussed in [Ren et al., 2022a], ϕ can be understood as representing primitives for skill set construction. Efficient and practical algorithms have been designed for exploiting linearity in MDPs [Zhang et al., 2022, Qiu et al., 2022], which inspires us to exploit similar properties in POMDPs.

Energy-based Models. Energy-based Models are one of the most flexible models to represent the conditional probability measure. It takes the form of $p(y|x) = \exp(-f(x, y))/Z(x)$ where $f(x, y)$, which can be parametrized by deep models, is the energy of (x, y) and $Z(x)$ is a partition function that only depends on x to guarantee $p(y|x)$ is a valid probability measure. When y is discrete, we have that $p(y|x) = \exp(-f(x, y))/\sum_y \exp(-f(x, y))$, which corresponds to the standard softmax probability where $-f(x, y)$ is the softmax logits. We refer the interested readers to Song and Kingma [2021] for the training methods of energy-based models.

3 ENERGY-BASED PREDICTIVE REPRESENTATION

We propose *Energy-based Predictive Representation (EPR)*, which introduces linear structure into finite-history approximated POMDPs, reducing the complexity induced by large

state spaces and long histories, and thus, yielding improved efficiency for learning, planning and exploration. We emphasize that the proposed method is also applicable to MDPs.

The approach builds upon recent progress in large-state MDPs [Zhang et al., 2022, Qiu et al., 2022] that leverages linear structure in the dynamics, $P(s'|s,a) = \langle \phi(s,a), \mu(s') \rangle$, to obtain an efficient and practical framework for learning, planning and exploration. Recall the construction of a finite-memory belief MDP to approximate a POMDP discussed in Section 2, which avoids full history dependence. For such a constructed belief MDP, a natural idea is to apply linear MDP algorithms, *i.e.*, extracting the linear decomposition for $T_b^L(b'|b,a) = \langle \phi(b,a), \mu(b') \rangle$, to handle the hardnesses of POMDPs mentioned in Section 1. However, there are several difficulties in such a straightforward extension:

i, the set of beliefs is proportional to the number of states, which could be infinite, which leads the difficulty in parametrization and calculation of the belief;

ii, the learning and factorization of the transition dynamics (4) in the equivalent belief MDP is difficult.

These difficulties hinder the extension of linear MDPs to observable POMDPs. However, note that we never explicitly require the beliefs and their dynamics, but only the representation $\phi(b,a)$. As beliefs are functions over finite-window histories, the representation can also be rewritten as $\phi(x_t, a_t)$, which suggests that one might bypass the inherent difficulties by a *reparameterization trick*. Consider the energy-based parametrization for $P(o_{t+1}|b(x_t), a_t)$ where $b(x_t)$ is the belief for history x_t:

$$P(o_{t+1}|b(x_t), a_t)$$
$$= p(o_{t+1}) \exp \left(f(x_t, a_t)^\top \left(g(o_{t+1}) + \lambda f(x_t, a_t) \right) \right),$$
$$\tag{12}$$
$$\mathbb{E}_{o_{t+1}} \left[\exp \left(f(x_t, a_t)^\top \left(g(o_{t+1}) + \lambda f(x_t, a_t) \right) \right) \right] = 1,$$
$$\tag{13}$$
$$\forall (x_t, a_t) \in \mathfrak{X}^L,$$
$$\tag{14}$$

where λ is a scalar, $p(o)$ is a fixed distribution and the normalization condition enforces that the energy-based model $P(o_{t+1}|b(x_t), a_t)$ is a valid distribution. We avoid any explicit parametrization and computation of beliefs b, while preserving dependence through f and g, which will be learned jointly. Compared to standard parametrizations, we do not need to specify unnecessary model parameters for the transition dynamics P and emmission O, and bypass any learning and approximation of beliefs that induce compounding errors. As a special case, we note that the observable Linear-Quadratic Gaussian (LQG) actually follows (12) with a specific λ and $p(o)$. See Appendix C for details.

Meanwhile, this approach also provides a linear factorization of $T(b_{t+1}|b_t, a_t)$ almost for free. By viewing the proposed parameterization (12) as a kernel and following the

random Fourier feature trick [Rahimi and Recht, 2007, Ren et al., 2022b], one can write

$$P(o_{t+1}|b_t, a_t) = \mathbb{E}_\omega \left[\phi_\omega(x_t, a_t) \psi_\omega(o_{t+1}) \right], \tag{15}$$

where $\omega_i \sim \mathcal{N}(0, I_d)$ and

$$\phi_\omega(x_t, a_t) = \left[\exp \left(\left(\lambda - \frac{1}{2} \right) \|f(x_t, a_t)\|^2 + \omega_i^\top f(x_t, a_t) \right) \right]_{i=1}^d, \tag{16}$$

$$\psi_\omega(x_{t+1}) = \left[p(o_{t+1}) \exp \left(\omega_i^\top g(o_{t+1}) - \frac{\|g(o_{t+1})\|^2}{2} \right) \right]_{i=1}^d. \tag{17}$$

We provide a detailed derivation in Appendix B. Substituting (15) into (4) yields the factorization of T_b as

$$T_b \left(b_{t+1}|b_t, a_t \right)$$
$$= \int_{\mathcal{O}} \mathbf{1}_{b(\cdot|x_{t+1})=b(\cdot|x_t, a_t, o_{t+1})} \mathbb{E}_\omega \left[\phi_\omega(x_t, a_t) \psi_\omega(o_{t+1}) \right] \mathrm{d}o_{t+1}$$
$$= \mathbb{E}_\omega \left[\phi_\omega(x_t, a_t) \mu(b_{t+1}) \right],$$

where $\mu(b_{t+1}) := \int_{\mathcal{O}} \mathbf{1}_{b(\cdot|x_{t+1})=b(\cdot|x_t, a_t, o_{t+1})} \psi_\omega(o_{t+1}) \mathrm{d}o_{t+1}$. With this formula, we obtain a valid linear representation $\phi(b_t, a_t) = \phi_\omega(x_t, a_t)$ with $\omega \sim \mathcal{N}(0, I_d)$ as Energy-based Predictive Representation (EPR) for a belief MDP without any explicit calculation of beliefs. Although the linear representation $\phi_\omega(x_t, a_t)$ is infinite dimensional, it can be approximated by Monte-Carlo approximation easily [Rahimi and Recht, 2007, Ren et al., 2022b].

To learn the EPR given data $\mathcal{D} := \{o_{t-1}, a_t, r_t\}_{t=1}^H$, we exploit maximum likelihood estimation (MLE) of (12),

$$\min_{f,g} - \widehat{\mathbb{E}}_{\mathcal{D}} \left[f(x_t, a_t)^\top \left(g(o_{t+1}) + \lambda f(x_t, a_t) \right) \right], \tag{18}$$
$$\text{s.t.} \mathbb{E}_{p(o_{t+1})} \left[\exp \left(f(x_t, a_t)^\top \left(g(o_{t+1}) + \lambda f(x_t, a_t) \right) \right) \right] = 1,$$
$$\forall (x_t, a_t) \in \mathfrak{X}^L.$$

To ensure the constraints, we add a regularization term

$$\left(\log \left(\mathbb{E}_o \left[\exp(f(x_t, a_t)^\top \left(g(o) + \lambda f(x_t, a_t) \right)) \right] \right) \right)^2$$
$$\approx \left(\log \left(\frac{1}{m} \sum_{i=1}^m \exp(f(x_t, a_t)^\top \left(g(o_i) + \lambda f(x_t, a_t) \right)) \right) \right)^2,$$

with $o_i \sim p$. The objective will be

$$\min_{f,g} \widehat{\mathbb{E}}_{\mathcal{D}} \Big[- f(x_t, a_t)^\top \left(g(o_{t+1}) + \lambda f(x_t, a_t) \right)$$
$$+ \alpha \left(\log \left(\frac{1}{m} \sum_{i=1}^m \exp(f(x_t, a_t)^\top \left(g(o_i) + \lambda f(x_t, a_t) \right)) \right) \right)^2 \Big].$$

In practice, we can further simplify the objective by normalizing the $\tilde{f}(x_t, a_t) = \frac{f(x_t, a_t)}{\|f(x_t, a_t)\|_2}$, obtaining the final

objective

$$\min_{\tilde{f},g} \widehat{\mathbb{E}}_{\mathcal{D}} \left[-\tilde{f}(x_t, a_t)^\top g(o_{t+1}) + \lambda + \right. \tag{19}$$

$$\left. \alpha \left(\log \left(\sum_{i=1}^m \exp(\tilde{f}(x_t, a_t)^\top g(o_i) + \lambda) \right) \right)^2 \right],$$

which reduces to a contrastive loss that can be optimized by stochastic gradient descent with a deep network parameterization of $\tilde{f}$ and g. We obtain negative samples $\{o_i\}_{i=1}^m \sim p(o)$ from a mixture of replay buffer and collected trajectories.

Before we introduce an exploration-exploitation mechanism with EPR in Section 3.1, we first discuss the relationship between the proposed EPR, predictive state representations (PSR) [Littman and Sutton, 2001, Singh et al., 2004], and spectral dynamics embedding (SPEDE) [Ren et al., 2022b].

Connection to PSR [Littman and Sutton, 2001, Singh et al., 2004]: The predictive state representation (PSR) was proposed to bypass belief calculation by factorizing transition dynamics operator. Specifically, given the history (x_t, a_t), the probability for observing a test, *i.e.*, the finite sequence of events $y = (a_{t+1}, o_{t+1}, \cdots, a_{t+k}, o_{t+k})$ with $k \in \mathbb{N}$, is $p(y|x) := p(o_{t+1}^{t+k}|x_t, a_t^{t+k})$. For time step t, one can construct a set of core tests $U = \{u_i, \ldots, u_k\}$ as sufficient statistics for history x_t, such that for any test τ, $p(\tau|x_t) = \langle p(U|x_t), w_\tau \rangle$ for some weights $w_{\tau,} \in \mathbb{R}^{|U_t|}$. The forward dynamics can be represented in a PSR by Bayes' rule: $p(\tau|x_t, a_t, o_{t+1}) = \frac{w_{(\tau, a_t, o_{t+1})}^\top p(U|x_t)}{w_{(a_t, o_{t+1})}^\top p(U|x_t)}$, which implies that a PSR updates with new observations and actions by repeating a calculation for each $u_i \in U$. Although originally defined for tabular cases, PSRs have been extended to continuous observations by introducing kernels [Boots et al., 2013] or neural networks [Guo et al., 2018, Downey et al., 2017, Hefny et al., 2018].

The proposed EPR shares similarities with PSR. Both factorize conditional distributions defined by the dynamics. However, these representations are designed for different purposes, and thus, with different usages and updates. Concretely, EPR is proposed for seeking a linear space that can represent the Q-function. The representation is designed to preserve linearity with successive observations without the need for Bayesian updates, which induce extra nonlinearity in PSRs. This linear property leads to efficient exploration and planning in EPR; while an efficient exploration and planning algorithm has not yet been discussed for PSR.

Connection to SPEDE [Ren et al., 2022b]: Linear random features have been proposed for solving planning in MDPs with nonlinear dynamics in [Ren et al., 2022b], where the transition operator is defined as $T(s'|s,a) \propto$

Algorithm 1 Energy-based Predictive Representation

1: **Input:** History Embedding $f(x, a)$, Observation Embedding $g(o)$, Random Feature $\{\omega_i\}_{i=1}^n$ where $\omega_i \sim \mathcal{N}(0, I_d)$, Initial Random Policy π_0, Initial Dataset $\mathcal{D} = \emptyset$ for online setting.
2: **for** Episode $i = 1, \cdots, K$ **do**
3:     Collect data $\{(x_{i,j}, a_{i,j}, o_{i,j}, r_{i,j})\}_{j=1}^H$ with $\tilde{\pi}_i = \xi\pi_i + (1-\xi)\pi_0$, and add the data to $\mathcal{D}$.
4:     Optimize f and g with (19) using the data from $\mathcal{D}$.
5:     Obtain the representation $\phi(x_t, a_t)$ via (16) using $\{\omega_i\}_{i=1}^n$.
6:     Add the bonus (20) to the reward and obtain the optimal policy π_{i+1} with the $Q(x_t, a_t)$ parameterize as $\phi(x_t, a_t)$ and optimize via FQI.
7:     *(Optional) Extract policy by soft-AC from learned Q.*
8: **end for**
9: **Return** π_K.

$\exp\left(-\|s' - f(s,a)\|_2^2 / (2\sigma^2)\right)$, corresponding to dynamics $s' = f(s,a) + \epsilon$ with Gaussian noise $\epsilon \sim \mathcal{N}(0, \sigma)$. In addition to the generalization of EPR for POMDPs, even in an MDP, EPR considers a general energy-based model, $T(s'|s,a) \propto p(s') \exp\left(f(s,a)^\top (g(s') + \lambda f(s,a))\right)$ for the dynamics, which is far more flexible than the Gaussian perturbation model considered in SPEDE.

3.1 ONLINE EXPLORATION AND OFFLINE POLICY OPTIMIZATION WITH EPR

With an EPR $\phi(x_t, a_t)$ learned for a POMDP, we can represent the Q-function linearly for the approximated belief MDP, and thus, achieve computationally efficient planning, while calculating confidence bounds for implementing the optimism/pessimism in the face of uncertainty.

Exploration and Exploitation with Elliptical Confidence Bound. Given the learned representation $\phi(x_t, a_t)$, the confidence bounds can be calculated efficiently, which allows efficient implementation of optimism/pessimism in the face of uncertainty via upper/lower confidence bound [Abbasi-Yadkori et al., 2011, Jin et al., 2020b, Uehara et al., 2021]. This is achieved simply by adding an additional elliptical bonus to the $R(x, a)$. Specifically, given the dataset we collect $\mathcal{D} = \{(x_i^L, a_i, R_i, o_{i+1})\}_{i=1}^n$, and calculate the confidence bound as the bonus,

$$b(x_t, a_t) = \sqrt{\phi(x_t, a_t)\Sigma_n^{-1}\phi(x_t, a_t)} \tag{20}$$

where λ is a pre-specified hyperparameter, and $\Sigma_n = \sum_{i=1}^n \lambda I + \phi(x_i^L, a_i)\phi(x_i^L, a_i)^\top$. One can then implement UCB/LCB by adding/subtracting the bonus to $R(x_t, a_t)$, and performing planning on the modified reward function.

Planning with Obtained Representation. Planning can be conducted by Bellman recursion within the linear space

spanned by $\phi(x_t^L, a_t)$ without a bonus. However, with an additional bonus term, the Q^π no longer lies in the linear space of ϕ, since

$$Q^\pi\left(x_t^L, a_t\right) = R(x_t^L, a_t) + b(x_t^L, a_t) + \mathbb{E}_{T_b^L \pi}\left[Q^\pi\left(x_{t+1}, a_{t+1}\right)\right]$$

As discussed in [Zhang et al., 2022], one can augment the feature space $\psi(x, a) := \{\phi(x, a), b(x, a)\}$ to ensure the Q-functions can still be linearly represented but with an extra $\mathcal{O}\left(d^2\right)$ memory cost. In practice, we perform fitted Q iteration with a nonlinear component extending the linear parameterization, *i.e.*, $Q(x, a) = \{w_1, w_2\}^\top\left[\phi(x, a), \sigma\left(w_3^\top \phi(x, a)\right)\right]$.

We provide an outline of our implementation of UCB in Algorithm 1. LCB for pessimistic offline RL is similar but using a pre-collected dataset $\hat{\mathcal{D}}$ without data collection in Step 2, and with the bonus subtracted in Step 6. Our algorithm follows the standard interaction paradigm between the agent and the environment, where the agent executes the policy and logs the data to the dataset. Then we perform representation learning and optimistic planning with the Q function parameterized upon the learned representation. Finally, we also extract a policy from the learned Q by soft actor-critic [Haarnoja et al., 2018].

We also remark that the representation learning part in our algorithm can easily exploit extra offline data as a warm start for free to the online improvement.

4 RELATED WORK

Partial Observability in Reinforcement Learning. Despite the essential hardness of POMDPs in terms of learning, planning and exploration [Papadimitriou and Tsitsiklis, 1987, Vlassis et al., 2012, Jin et al., 2020b], the study of reinforcement learning with partial observations, from both theoretical and empirical aspects, is still attractive due to its practical importance.

Algorithmically, model-based/-free algorithms have been extended to POMDPs, explicitly or implicitly exploiting structure information. Model-based RL algorithms parameterize and learn latent dynamics with an emission model explicitly, and planning through the simulation upon the learned models. A variety of deep models have been proposed recently for better modeling [Watter et al., 2015, Karl et al., 2016, Igl et al., 2018, Zhang et al., 2019, Lee et al., 2020, Hafner et al., 2019, 2020]. Although deep models indeed provide better approximation ability, they also bring new challenges in terms of planning and exploration, which has not been fully handled. On the other hand, model-free RL algorithms have been extended for POMDPs by learning history dependent value functions and/or policies, through temporal-difference algorithms or policy gradients. For example, deep Q-learning [Mnih et al., 2013] concatenates 4 consecutive frames as the input of a deep neural Q-net, which is then improved by recurrent neural networks for longer windows [Bakker, 2001, Hausknecht and Stone,

2015, Zhu et al., 2017]. Recurrent neural networks have also been exploited for history dependent policies [Schmidhuber, 1990, Bakker, 2001, Wierstra et al., 2007, Heess et al., 2015] with policy gradient as well as actor-critic approaches [Ni et al., 2021, Meng et al., 2021]. Model-free RL for POMDPs bypasses the planning complexity of model-based RL algorithms. However, the difficulty in exploration remains, which leads to suboptimal performance in practice. By contrast, the proposed EPR not only can be efficiently learned, but is also equipped with principled planning and exploration methods, which has not been previously achieved.

Representation Learning for RL. Successful vision-based representation learning methods have been extended to RL for extracting compact and invariant *state-only* information from raw-pixels, *e.g.*, [Kostrikov et al., 2021]. However, such vision-based features are not specially designed for capturing properties in POMDPs/MDPs essential for decision making. To reveal structure that is particularly helpful for RL, many representation learning methods have been designed for different purposes, such as bi-simulation [Ferns et al., 2004, Gelada et al., 2019, Zhang et al., 2020], successor features [Dayan, 1993, Barreto et al., 2017, Kulkarni et al., 2016], spectral decomposition of transition operators [Mahadevan and Maggioni, 2007, Wu et al., 2018, Duan et al., 2019], latent future prediction [Schwarzer et al., 2020] and contrastive learning [Oord et al., 2018, Mazoure et al., 2020, Nachum and Yang, 2021, Yang et al., 2021]. These representation methods ignore the requirement of planning tractability. Moreover, they are learning based on a pre-collected dataset, which ignores the exploration issue.

Features that are able to represent value functions are desirable for efficient planning and exploration. Based on the linear MDPs structure [Jin et al., 2020b], several theoretical algorithms [Agarwal et al., 2020, Uehara et al., 2021] have been developed. Ren et al. [2022b,a], Zhang et al. [2022], Qiu et al. [2022] bridge the gap between theory and practice and bypass computational intractability via different techniques, demonstrating advantages empirically. The proposed EPR is inspired from this class of representations, but extended to POMDPs, which is highly non-trivial.

5 EXPERIMENTS

Our experiments investigate how our algorithm performs in robotic lomocation simulation environments. We extensively evaluate the proposed approach on the Mojuco in OpenAI Gym and DeepMind Control Suites. We conduct experiments on both the fully observable MDP and partially observable POMDP settings.

5.1 FULLY OBSERVABLE MDP

Dense-Reward Mujoco Tasks. We first conduct experiments in the fully observable MDP setting in Mujoco locomotion tasks. This is a test suite commonly used for both model-free and model-based RL algorithms. We compare EPR with model-based RL baselines PETS [Chua

Table 1: Performance on various MuJoCo control tasks. All the results are averaged across 4 random seeds and a window size of 10K. Results marked with * is adopted from MBBL. EPR achieves strong performance compared with baselines.

		HalfCheetah	Reacher	Humanoid-ET	Pendulum	I-Pendulum
Model-Based RL	ME-TRPO*	2283.7±900.4	-13.4±5.2	72.9±8.9	**177.3±1.9**	-126.2±86.6
	PETS-RS*	966.9±471.6	-40.1±6.9	109.6±102.6	167.9±35.8	-12.1±25.1
	PETS-CEM*	2795.3±879.9	-12.3±5.2	110.8±90.1	167.4±53.0	-20.5±28.9
	Best MBBL	3639.0±1135.8	**-4.1±0.1**	1377.0±150.4	**177.3±1.9**	**0.0±0.0**
Model-Free RL	PPO*	17.2±84.4	-17.2±0.9	451.4±39.1	163.4±8.0	-40.8±21.0
	TRPO*	-12.0±85.5	-10.1±0.6	289.8±5.2	166.7±7.3	-27.6±15.8
	SAC* (3-layer)	4000.7±202.1	-6.4±0.5	**1794.4±458.3**	168.2±9.5	-0.2±0.1
Representation RL	DeepSF	4180.4±113.8	-16.8±3.6	168.6±5.1	168.6±5.1	-0.2±0.3
	SPEDE	4210.3±92.6	-7.2±1.1	886.9±95.2	169.5±0.6	0.0±0.0
	EPR	**5107.6±195.4**	**-5.6±0.3**	1494.6±131.3	169.4±4.1	**0.0±0.0**

		Ant-ET	Hopper-ET	S-Humanoid-ET	CartPole	Walker-ET
Model-Based RL	ME-TRPO*	42.6±21.1	1272.5±500.9	-154.9±534.3	160.1±69.1	-1609.3±657.5
	PETS-RS*	130.0±148.1	205.8±36.5	320.7±182.2	195.0±28.0	312.5±493.4
	PETS-CEM*	81.6±145.8	129.3±36.0	355.1±157.1	195.5±3.0	260.2±536.9
	Best MBBL	275.4±309.1	1272.5±500.9	**1084.3±77.0**	**200.0±0.0**	312.5±493.4
Model-Free RL	PPO*	80.1±17.3	758.0±62.0	454.3±36.7	86.5±7.8	306.1±17.2
	TRPO*	116.8±47.3	237.4±33.5	281.3±10.9	47.3±15.7	229.5±27.1
	SAC* (3-layer)	2012.7±571.3	1815.5±655.1	834.6±313.1	199.4±0.4	**2216.4±678.7**
Representation RL	DeepSF	768.1±44.1	548.9±253.3	533.8±154.9	194.5±5.8	165.6±127.9
	SPEDE	806.2±60.2	732.2±263.9	986.4±154.7	138.2±39.5	501.6±204.0
	EPR	**4081.3±973.9**	**2191.4±502.8**	**1326.3±20.8**	**200.8±0.1**	1975.4±751.3

et al., 2018] and ME-TRPO [Kurutach et al., 2018], and model-free RL baselines SAC [Haarnoja et al., 2018], TRPO [Schulman et al., 2015] and PPO [Schulman et al., 2017]. In addition, we also compare to the representation learning RL baselines Deep Successor Feature (DeepSF) [Kulkarni et al., 2016] and SPEDE [Ren et al., 2022b]. We list the best model-based RL results (except for iLQR [Li and Todorov, 2004]) in MBBL [Wang et al., 2019] for comparison. All algorithms are run for 200K environment steps. The results are averaged across four random seeds with a window size of 10K. We show that in Tab. 1, EPR significantly outperforms all the baselines including the strong previous SoTA model-free algorithm SAC.

In particular, we observe that most model-based algorithms have a hard time learning the walk and hop behavior in the Walker and Hopper environments respectively. We suspect that this is due to the fact that the quality of the data is bad at the initial data collection process (e.g., the agent often fall to the ground or has a hard time standing up). As a result, the behavior learned by most model-based algorithms can be suboptimal. For example, some model-based algorithms only learn to stand up without hopping in the Hopper environment. In contrast, EPR achieves SoTA performance in the Hopper task and Ant task, demonstrating the behavior of doing good exploration in the task domain.

Sparse-Reward DM Control Tasks. Manually-designed dense reward functions are extremely hard to obtain, while it is difficult to gain access to a good dense reward function in practical real-robot settings. Thus, exploration in the sparse-reward settings is a key consideration for the success of RL in robotics settings. We test our algorithm EPR with SAC and PPO in such cases. Here we compare with DeepSF as an additional representation RL baseline. Note that the critic network used in SAC and PPO is deeper than EPR.

From Tab. 2, we see that EPR achieves a particularly huge gain compared to SAC and PPO in sparse reward tasks `walker-run-sparse`.

5.2 PARTIAL OBSERVABLE MDP COVERING VELOCITY

Mujoco. Often in practice, it is hard to recover a full observation of the states. Thus, the ability to handle a partially-observed MDP (POMDP) is also important if we can only recover partial observations. To conduct experiments in this setting, we adopt a commonly used approach [Ni et al., 2021, Gangwani et al., 2020, Weigand et al., 2021] of masking the the velocities in the observations. We compare to algorithms with different embedding approaches that maps a given history sequence to a latent representation, which is used as the input for a SAC planner. We consider four embedding methods as baselines: Transformer (Trans), which uses causal encoding with one layer and one head, and positional encoding (details in Appendix D); GRU; PSR [Guo et al., 2018]; and a simple MLP baseline for sanity checking. The MLP baseline concatenates the history sequence and maps it to a latent feature using a MLP. We find that this setting is very challenging and the performance of all algorithms degrades compared to the fully-observable setting, as shown in Tab. 3. Nevertheless, the proposed algorithm still achieves SoTA performance in tasks like Halfcheetah, Ant, SlimHumanoid. This demonstrates the capability of handling partial observability in EPR which can have an important effect in practice.

DM Control Suite. Correspondingly, we conduct POMDP experiments in the DM Control Suite. However, we find that covering all the velocities is very challenging, leading to trivial performances for all the competitors. We cover the last 3 dimensions of the velocity. As shown in Tab. 4,

Table 2: Performance of on various Deepmind Suite Control tasks. All the results are averaged across four random seeds and a window size of 10K. Comparing with SAC, our method achieves even better performance on sparse-reward tasks.

		cheetah_run	cheetah_run_sparse	walker_run	walker_run_sparse	humanoid_run
Model-Based RL	Dreamer	542.0 ± 27.7	499.9±73.3	337.7±67.2	95.4±54.7	1.0±0.2
Model-Free RL	PPO	227.7±57.9	5.4±10.8	51.6±1.5	0.0±0.0	1.1±0.0
	SAC (2-layer)	222.2±41.0	32.4±27.8	183.0±23.4	53.5±69.3	1.3±0.1
	SAC (3-layer)	595.2±96.0	419.5±73.3	700.9±36.6	311.5±361.4	1.2±0.1
Representation RL	DeepSF	295.3±43.5	0.0±0.0	27.9±2.2	0.1±0.1	0.9±0.1
	Proto RL	305.5±37.9	0.0±0.0	433.5±56.8	46.9±34.1	0.3±0.6
	EPR	**611.6±53.5**	**469.8±30.6**	**792.8±35.7**	**701.8±30.4**	**11.5±5.4**

Table 3: Performance on various MuJoCo control tasks with partial observation. All the results are averaged across 4 random seeds and a window size of 10K. Results marked with $*$ is adopted from MBBL. EPR achieves strong performance compared with baselines.

		HalfCheetah	Humanoid-ET	Walker-ET
Representation RL	**EPR**	**3441.6 ± 993.0**	**865.6 ± 107.3**	416.6 ± 145.6
	PSR	2679.75 ± 386	534.4 ± 36.6	862.4 ± 355.3
Model-Free RL	MLP	1612.0 ± 223	614.15 ± 67.6	236.5 ± 65.6
	Trans	1443.5 ± 227.2	387.1 ± 8.4	388.7 ± 224.9
	GRU	1664.3 ± 431.2	467.7 ± 43.4	**1020.6 ± 364.9**
		Ant-ET	Hopper-ET	S-Humanoid-ET
Representation RL	**EPR**	**1508.1 ± 594.4**	**1059.4 ± 582.5**	**805.7 ± 65.9**
	PSR	1128.3 ± 166.6	818.8 ± 87.2	493.3 ± 65.2
Model-Free RL	MLP	1262.0 ± 68.7	260.6 ± 63.7	294.17 ± 49.4
	Trans	928.5 ± 44.2	470.8 ± 50.3	447.9 ± 112.6
	GRU	1190.8 ± 79.4	777.5 ± 113.3	485.9 ± 25.8

Table 4: Performance of on various Deepmind Suite Control tasks with partial observation. All the results are averaged across four random seeds and a window size of 10K. Comparing with SAC, our method achieves even better performance on sparse-reward tasks.

		cheetah_run	cheetah_run_sparse	walker_run	walker_run_sparse	humanoid_run
Explicit Model	SLAC	105.1 ± 30.1	0.0 ± 0.0	139.2 ± 3.4	0.0 ± 0.0	0.9 ± 0.1
Model-Free RL	MLP	**743.3 ± 7.2**	0.0 ± 0.0	279.8 ± 190.6	0.0 ± 0.0	1.2 ± 0.1
	Trans	379.6 ± 80	0.0 ± 0.0	68.06 ± 39.9	0.0 ± 0.0	0.92 ± 0.1
Representation RL	PSR	173.7 ± 25.7	0.0 ± 0.0	57.4 ± 7.4	0.0 ± 0.0	0.89 ± 0.1
	EPR	526.5±61.1	**411.0±51.6**	**509.8±24.4**	**460.3±51.6**	**6.1±2.5**

Figure 1: **EPR in image-based environment:** EPR gets a good performance compared to SPR and SAC+AE.

our EPR significantly dominant the other competitors.

5.3 IMAGE-BASED ENVIRONMENTS

To test our method on image-based environments, we conduct an additional experiment on MetaWorld [Yu et al., 2020]. We choose one of the `fetch-reach` tasks and compare against the model-free algorithm SAC+AE [Yarats et al., 2021] and a popular representation learning method SPR [Schwarzer et al., 2020]. We show the results in Fig. 1 and note that the minimum distance between the current state and the goal is used as the evaluation metric (the smaller distance means better performance). We can see that EPR manages to reach the distant goal within 100K

steps. Comparing to SAC+AE, EPR strictly dominate its performance. For SPR, although it learns faster at the beginning, EPR has better final performance.

6 CONCLUSION

We exploit Energy-based Predictive Representation (EPR) for linearly representing value functions for arbitrary policies and supporting reinforcement learning in partially observed environments with finite memories. The proposed EPR shows that planning and strategic exploration can be implemented efficiently. The coherent design of each component brings empirical advantages in RL benchmarks considering both the MDP and POMDP settings. Such superior performance makes the theoretical understanding of EPR more intriguing, which we leave as future work.

References

Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. *NeurIPS*, 2011.

Alekh Agarwal, Sham Kakade, Akshay Krishnamurthy, and Wen Sun. Flambe: Structural complexity and representation learning of low rank mdps. *NeurIPS*, 2020.

Karl Johan Åström. Optimal control of markov processes with incomplete state information. *Journal of mathematical analysis and applications*, 10(1):174–205, 1965.

Kamyar Azizzadenesheli, Alessandro Lazaric, and Animashree Anandkumar. Reinforcement learning of pomdps using spectral methods. In *COLT*, 2016.

Bram Bakker. Reinforcement learning with long short-term memory. *NeurIPS*, 2001.

André Barreto, Will Dabney, Rémi Munos, Jonathan J Hunt, Tom Schaul, Hado P van Hasselt, and David Silver. Successor features for transfer in reinforcement learning. *NeurIPS*, 2017.

Byron Boots, Geoffrey Gordon, and Arthur Gretton. Hilbert space embeddings of predictive state representations. *UAI*, 2013.

Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. *NeurIPS*, 31, 2018.

Peter Dayan. Improving generalization for temporal difference learning: The successor representation. *Neural computation*, 5 (4):613–624, 1993.

Marc Peter Deisenroth and Jan Peters. Solving nonlinear continuous state-action-observation pomdps for mechanical systems with gaussian noise. 2012.

Carlton Downey, Ahmed Hefny, Byron Boots, Geoffrey J Gordon, and Boyue Li. Predictive state recurrent neural networks. *NeurIPS*, 30, 2017.

Yaqi Duan, Tracy Ke, and Mengdi Wang. State aggregation learning from markov transition data. *NeurIPS*, 2019.

Norm Ferns, Prakash Panangaden, and Doina Precup. Metrics for finite markov decision processes. In *UAI*, 2004.

Tanmay Gangwani, Joel Lehman, Qiang Liu, and Jian Peng. Learning belief representations for imitation learning in pomdps. In *UAI*, 2020.

Carles Gelada, Saurabh Kumar, Jacob Buckman, Ofir Nachum, and Marc G Bellemare. Deepmdp: Learning continuous latent space models for representation learning. In *ICML*, 2019.

Noah Golowich, Ankur Moitra, and Dhruv Rohatgi. Learning in observable pomdps, without computationally intractable oracles. *arXiv:2206.03446*, 2022a.

Noah Golowich, Ankur Moitra, and Dhruv Rohatgi. Planning in observable pomdps in quasipolynomial time. *arXiv:2201.04735*, 2022b.

Karol Gregor, Danilo Jimenez Rezende, Frederic Besse, Yan Wu, Hamza Merzic, and Aaron van den Oord. Shaping belief states with generative environment models for rl. *NeurIPS*, 2019.

Zhaohan Guo, Shayan Doroudi, and Emma Brunskill. A pac rl algorithm for episodic pomdps. In *AISTATS*, 2016.

Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, Bilal Piot, Bernardo A Pires, and Rémi Munos. Neural predictive belief representations. *arXiv:1811.06407*, 2018.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *ICML*, 2018.

Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. *arXiv:1912.01603*, 2019.

Danijar Hafner, Timothy Lillicrap, Mohammad Norouzi, and

Jimmy Ba. Mastering atari with discrete world models. *arXiv:2010.02193*, 2020.

Matthew Hausknecht and Peter Stone. Deep recurrent q-learning for partially observable mdps. In *AAAI fall symposium series*, 2015.

Nicolas Heess, Jonathan J Hunt, Timothy P Lillicrap, and David Silver. Memory-based control with recurrent neural networks. *arXiv:1512.04455*, 2015.

Ahmed Hefny, Zita Marinho, Wen Sun, Siddhartha Srinivasa, and Geoffrey Gordon. Recurrent predictive state policy networks. In *ICML*, 2018.

Maximilian Igl, Luisa Zintgraf, Tuan Anh Le, Frank Wood, and Shimon Whiteson. Deep variational reinforcement learning for pomdps. In *ICML*, 2018.

Michael Janner, Qiyang Li, and Sergey Levine. Offline reinforcement learning as one big sequence modeling problem. *NeurIPS*, 2021.

Haoming Jiang, Bo Dai, Mengjiao Yang, Tuo Zhao, and Wei Wei. Towards automatic evaluation of dialog systems: A model-free off-policy evaluation approach. In *EMNLP*, 2021.

Chi Jin, Sham Kakade, Akshay Krishnamurthy, and Qinghua Liu. Sample-efficient reinforcement learning of undercomplete pomdps. *NeurIPS*, 2020a.

Chi Jin, Zhuoran Yang, Zhaoran Wang, and Michael I Jordan. Provably efficient reinforcement learning with linear function approximation. In *COLT*, 2020b.

Leslie Pack Kaelbling, Michael L Littman, and Anthony R Cassandra. Planning and acting in partially observable stochastic domains. *Artificial intelligence*, 101(1-2):99–134, 1998.

Maximilian Karl, Maximilian Soelch, Justin Bayer, and Patrick Van der Smagt. Deep variational bayes filters: Unsupervised learning of state space models from raw data. *arXiv:1605.06432*, 2016.

Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *ICLR*, 2021.

Akshay Krishnamurthy, Alekh Agarwal, and John Langford. Pac reinforcement learning with rich observations. *NeurIPS*, 2016.

Tejas D Kulkarni, Ardavan Saeedi, Simanta Gautam, and Samuel J Gershman. Deep successor reinforcement learning. *arXiv:1606.02396*, 2016.

Thanard Kurutach, Ignasi Clavera, Yan Duan, Aviv Tamar, and Pieter Abbeel. Model-ensemble trust-region policy optimization. *arXiv:1802.10592*, 2018.

Alex X Lee, Anusha Nagabandi, Pieter Abbeel, and Sergey Levine. Stochastic latent actor-critic: Deep reinforcement learning with a latent variable model. *NeurIPS*, 2020.

Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. *The JMLR*, 17 (1):1334–1373, 2016.

Weiwei Li and Emanuel Todorov. Iterative linear quadratic regulator design for nonlinear biological movement systems. In *ICINCO (1)*, pages 222–229. Citeseer, 2004.

Michael Littman and Richard S Sutton. Predictive representations of state. *NeurIPS*, 14, 2001.

Qinghua Liu, Alan Chung, Csaba Szepesvári, and Chi Jin.

When is partially observable reinforcement learning not scary? *arXiv:2204.08967*, 2022.

Sridhar Mahadevan and Mauro Maggioni. Proto-value functions: A laplacian framework for learning representation and control in markov decision processes. *JMLR*, 8(10), 2007.

Bogdan Mazoure, Remi Tachet des Combes, Thang Long Doan, Philip Bachman, and R Devon Hjelm. Deep reinforcement and infomax learning. *NeurIPS*, 2020.

Lingheng Meng, Rob Gorbet, and Dana Kulić. Memory-based deep reinforcement learning for pomdps. In *IROS*, 2021.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv:1312.5602*, 2013.

Ofir Nachum and Mengjiao Yang. Provable representation learning for imitation with contrastive fourier features. *NeurIPS*, 2021.

Tianwei Ni, Benjamin Eysenbach, and Ruslan Salakhutdinov. Recurrent model-free rl is a strong baseline for many pomdps. *arXiv:2110.05038*, 2021.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv:1807.03748*, 2018.

Christos H Papadimitriou and John N Tsitsiklis. The complexity of markov decision processes. *Mathematics of operations research*, 12(3):441–450, 1987.

Shuang Qiu, Lingxiao Wang, Chenjia Bai, Zhuoran Yang, and Zhaoran Wang. Contrastive ucb: Provably efficient contrastive self-supervised learning in online reinforcement learning. In *ICML*, 2022.

Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. *NeurIPS*, 20, 2007.

Tongzheng Ren, Tianjun Zhang, Lisa Lee, Joseph E Gonzalez, Dale Schuurmans, and Bo Dai. Spectral decomposition representation for reinforcement learning. *ICLR*, 2022a.

Tongzheng Ren, Tianjun Zhang, Csaba Szepesvári, and Bo Dai. A free lunch from the noise: Provable and practical exploration for representation learning. In *UAI*, 2022b.

Jürgen Schmidhuber. Reinforcement learning in markovian and non-markovian environments. *NeurIPS*, 3, 1990.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *ICML*, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv:1707.06347*, 2017.

Max Schwarzer, Ankesh Anand, Rishab Goel, R Devon Hjelm, Aaron Courville, and Philip Bachman. Data-efficient reinforcement learning with self-predictive representations. *arXiv:2007.05929*, 2020.

Satinder Singh, Michael R James, and Matthew R Rudary. Predictive state representations: a new theory for modeling dynamical systems. In *UAI*, 2004.

Yang Song and Diederik P Kingma. How to train your energy-based models. *arXiv:2101.03288*, 2021.

Masatoshi Uehara, Xuezhou Zhang, and Wen Sun. Representation learning for online and offline rl in low-rank mdps. *arXiv:2110.04652*, 2021.

Masatoshi Uehara, Ayush Sekhari, Jason D Lee, Nathan Kallus, and Wen Sun. Provably efficient reinforcement learning in partially observable dynamical systems. *arXiv:2206.12020*, 2022.

Arun Venkatraman, Nicholas Rhinehart, Wen Sun, Lerrel Pinto, Martial Hebert, Byron Boots, Kris Kitani, and J Bagnell. Predictive-state decoders: Encoding the future into recurrent networks. *NeurIPS*, 30, 2017.

Nikos Vlassis, Michael L Littman, and David Barber. On the computational complexity of stochastic controller optimization in pomdps. *ACM Transactions on Computation Theory (TOCT)*, 4(4):1–8, 2012.

Lingxiao Wang, Qi Cai, Zhuoran Yang, and Zhaoran Wang. Embed to control partially observed systems: Representation learning with provable sample efficiency. *arXiv:2205.13476*, 2022.

Tingwu Wang, Xuchan Bao, Ignasi Clavera, Jerrick Hoang, Yeming Wen, Eric Langlois, Shunshi Zhang, Guodong Zhang, Pieter Abbeel, and Jimmy Ba. Benchmarking model-based reinforcement learning. *arXiv:1907.02057*, 2019.

Manuel Watter, Jost Springenberg, Joschka Boedecker, and Martin Riedmiller. Embed to control: A locally linear latent dynamics model for control from raw images. *NeurIPS*, 2015.

Stephan Weigand, Pascal Klink, Jan Peters, and Joni Pajarinen. Reinforcement learning using guided observability. *arXiv:2104.10986*, 2021.

Daan Wierstra, Alexander Foerster, Jan Peters, and Juergen Schmidhuber. Solving deep memory pomdps with recurrent policy gradients. In *ICANN*, 2007.

Yifan Wu, George Tucker, and Ofir Nachum. The laplacian in rl: Learning representations with efficient approximations. *arXiv:1810.04586*, 2018.

Mengjiao Yang, Sergey Levine, and Ofir Nachum. Trail: Near-optimal imitation learning with suboptimal data. *arXiv:2110.14770*, 2021.

Denis Yarats, Amy Zhang, Ilya Kostrikov, Brandon Amos, Joelle Pineau, and Rob Fergus. Improving sample efficiency in model-free reinforcement learning from images. In *AAAI*, 2021.

Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Karol Hausman, Chelsea Finn, and Sergey Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *CORL*, 2020.

Wenhao Zhan, Masatoshi Uehara, Wen Sun, and Jason D Lee. Pac reinforcement learning for predictive state representations. *arXiv:2207.05738*, 2022.

Amy Zhang, Rowan McAllister, Roberto Calandra, Yarin Gal, and Sergey Levine. Learning invariant representations for reinforcement learning without reconstruction. *arXiv:2006.10742*, 2020.

Marvin Zhang, Sharad Vikram, Laura Smith, Pieter Abbeel, Matthew Johnson, and Sergey Levine. Solar: Deep structured representations for model-based reinforcement learning. In *ICML*, 2019.

Tianjun Zhang, Tongzheng Ren, Mengjiao Yang, Joseph Gonzalez, Dale Schuurmans, and Bo Dai. Making linear mdps practical via contrastive representation learning. In *ICML*, 2022.

Pengfei Zhu, Xin Li, Pascal Poupart, and Guanghui Miao. On improving deep reinforcement learning for pomdps. *arXiv:1704.07978*, 2017.