Temporal Difference Uncertainties as a Signal for Exploration

Abstract

An effective approach to exploration in reinforcement learning is to rely on an agent's uncertainty over the optimal policy, which can yield near-optimal exploration strategies in tabular settings. However, in non-tabular settings that involve function approximators, obtaining accurate uncertainty estimates is almost as challenging a problem. In this paper, we highlight that value estimates are easily biased and temporally inconsistent. In light of this, we propose a novel method for estimating uncertainty over the value function that relies on inducing a distribution over temporal difference errors. This exploration signal controls for state-action transitions so as to isolate uncertainty in value that is due to uncertainty over the agent's parameters. Because our measure of uncertainty conditions on state-action transitions, we cannot act on this measure directly. Instead, we incorporate it as an intrinsic reward and treat exploration as a separate learning problem, induced by the agent's temporal difference uncertainties. We introduce a distinct exploration policy that learns to collect data with high estimated uncertainty, which gives rise to a "curriculum" that smoothly changes throughout learning and vanishes in the limit of perfect value estimates. We evaluate our method on hard-exploration tasks, including Deep Sea and Atari 2600 environments and find that our proposed form of exploration facilitates both diverse and deep exploration.

1 Introduction

Striking the right balance between exploration and exploitation is fundamental to the reinforcement learning problem. A common approach is to derive exploration from the policy being learned. Dithering strategies, such as ϵ-greedy exploration, render a reward-maximising policy stochastic around its reward maximising behaviour (Williams & Peng, 1991). Other methods encourage higher entropy in the policy (Ziebart et al., 2008), introduce an intrinsic reward (Singh et al., 2005), or drive exploration by sampling from the agent's belief over the MDP (Strens, 2000).

While greedy or entropy-maximising policies cannot facilitate temporally extended exploration (Osband et al., 2013; 2016a), the efficacy of intrinsic rewards depends crucially on how they relate to the extrinsic reward that comes from the environment (Burda et al., 2018a). Typically, intrinsic rewards for exploration provide a bonus for visiting novel states (e.g Bellemare et al., 2016a) or visiting states where the agent cannot predict future transitions (e.g Pathak et al., 2017; Burda et al., 2018a). Such approaches can facilitate learning an optimal policy, but they can also fail entirely in large environments as they prioritise novelty over rewards (Burda et al., 2018b).

Methods based on the agent's uncertainty over the optimal policy explicitly trade off exploration and exploitation (Kearns & Singh, 2002). Posterior Sampling for Reinforcement Learning (PSRL; Strens, 2000; Osband et al., 2013) is one such approach, which models a distribution over Markov Decision Processes (MDPs). While PSRL is near-optimal in tabular settings (Osband et al., 2013; 2016b), it cannot be easily scaled to complex problems that require function approximators. Prior work has attempted to overcome this by instead directly estimating the agent's uncertainty over the policy's value function (Osband et al., 2016a; Moerland et al., 2017; Osband et al., 2019; O'Donoghue et al., 2018; Janz et al., 2019). While these approaches can scale posterior sampling to complex problems and nonlinear function approximators, estimating uncertainty over value functions introduces issues that can cause a bias in the posterior distribution (Janz et al., 2019).

In response to these challenges, we introduce *Temporal Difference Uncertainties* (TDU), which derives an intrinsic reward from the agent's uncertainty over the value function. Concretely, TDU relies on the Bootstrapped DQN (Osband et al., 2016a) and separates exploration and reward-maximising behaviour into two separate policies that bootstrap from a shared replay buffer. This separation allows us to derive an exploration signal for the exploratory policy from estimates of uncertainty of the reward-maximising policy. Thus, TDU encourages exploration to collect data with high model uncertainty over reward-maximising behaviour, which is made possible by treating exploration as a separate learning problem. In contrast to prior works that directly estimate value function uncertainty, we estimate uncertainty over *temporal difference (TD) errors*. By conditioning on observed state-action transitions, TDU controls for environment uncertainty and provides an exploration signal only insofar as there is model uncertainty. We demonstrate that TDU can facilitate efficient exploration in challenging exploration problems such as Deep Sea and Montezuma's Revenge.

2 ESTIMATING VALUE FUNCTION UNCERTAINTY IS HARD

We begin by highlighting that estimating uncertainty over the value function can suffer from bias that is very hard to overcome with typical approaches (see also Janz et al., 2019). Our analysis shows that biased estimates arise because uncertainty estimates require an integration over unknown future state visitations. This requires tremendous model capacity and is in general infeasible. As a solution to this problem, TDU estimates uncertainty over value-estimates by *conditioning* on an observed trajectory. This removes the issue of integrating over the future of a trajectory, but results in a metric that cannot be used directly for action selection in the sense of posterior sampling or as an upper confidence bound. Instead we incorporate TDU as an intrinsic reward, detailed in Sections 3 and 4.

We consider a Markov Decision Process $(\mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma)$ for some given state space $(\mathcal{S})$, action space $(\mathcal{A})$, transition dynamics $(\mathcal{P})$, reward function $(\mathcal{R})$ and discount factor (γ). For a given (deterministic) policy $\pi : \mathcal{S} \mapsto \mathcal{A}$, the action value function is defined as the expected cumulative reward under the policy starting from state s with action a:

$$Q_\pi(s, a) \coloneqq \mathbb{E}_\pi \left[\sum_{t=0}^\infty \gamma^t r_{t+1} \,\middle|\, s_0 = s, a_0 = a \right] = \mathbb{E}_{\substack{r \sim \mathcal{R}(s,a) \\ s' \sim \mathcal{P}(s,a)}} [r + \gamma Q_\pi(s', \pi(s'))], \quad (1)$$

where t index time and the expectation $\mathbb{E}_\pi$ is with respect to realised rewards r sampled under the policy π; the right-hand side characterises Q recursively under the Bellman equation. The action-value function Q_π is estimated under a function approximator Q_θ parameterised by θ. Uncertainty over Q_π is expressed by placing a distribution over the parameters of the function approximator, $p(\theta)$. We overload notation slightly and write $p(\theta)$ to denote the probability density function p_θ over a random variable θ. Further, we denote by $\theta \sim p(\theta)$ a random sample θ from the distribution defined by p_θ. Methods that rely on posterior sampling under function approximators assume that the induced distribution, $p(Q_\theta)$, is an accurate estimate of the agent's uncertainty over its value function, $p(Q_\pi)$, so that sampling $Q_\theta \sim p(Q_\theta)$ is approximately equivalent to sampling from $Q_\pi \sim p(Q_\pi)$.

For this to hold, the moments of $p(Q_\theta)$ at each state-action pair (s, a) must correspond to the expected moments in future states. In particular, moments of $p(Q_\pi)$ must satisfy a Bellman Equation akin to Eq. 1 (O'Donoghue et al., 2018). We focus on the mean ($\mathbb{E}$) and variance ($\mathbb{V}$):

$$\mathbb{E}_\theta[Q_\theta(s, a)] = \mathbb{E}_\theta[\mathbb{E}_{r,s'}[r + \gamma Q_\theta(s', \pi(s'))]], \quad (2)$$

$$\mathbb{V}_\theta[Q_\theta(s, a)] = \mathbb{V}_\theta[\mathbb{E}_{r,s'}[r + \gamma Q_\theta(s', \pi(s'))]]. \quad (3)$$

If $\mathbb{E}_\theta[Q_\theta]$ and $\mathbb{V}_\theta[Q_\theta]$ fail to satisfy these conditions, the estimates of $\mathbb{E}[Q_\pi]$ and $\mathbb{V}[Q_\pi]$ are biased, causing a bias in exploration under posterior sampling from $p(Q_\theta)$. Formally, the agent's uncertainty over $p(Q)$ implies uncertainty over the MDP (Strens, 2000). Given a belief over the MDP, i.e., a distribution $p(M)$, we can associate each $M \sim p(M)$ with a distinct value function Q_π^M. Lemma 1 below shows that, for $p(\theta)$ to be interpreted as representing some $p(M)$ by push-forward to $p(Q_\theta)$, the induced moments must match under the Bellman Equation.

Lemma 1. *If $\mathbb{E}_\theta[Q_\theta]$ and $\mathbb{V}_\theta[Q_\theta]$ fail to satisfy Eqs. 2 and 3, respectively, they are biased estimators of $\mathbb{E}_M[Q_\pi^M]$ and $\mathbb{V}_M[Q_\pi^M]$ for any choice of $p(M)$.*

All proofs are deferred to Appendix B. Lemma 1 highlights why estimating uncertainty over value functions is so challenging; while the left-hand sides of Eqs. 2 and 3 are stochastic in θ only, the right-hand sides depend on marginalising over the MDP. This requires the function approximator to generalise to unseen future trajectories. Lemma 1 is therefore a statement about scale; the harder it is to generalise, the more likely we are to observe a bias—even in deterministic environments.

This requirement of "strong generalisation" poses a particular problem for neural networks, which are prone to overfitting and tend to generalise through interpolation (e.g. Li et al., 2020; Liu et al., 2020; Belkin et al., 2019), but the issue is more general. In particular, we show that factorising the posterior $p(\theta)$ will typically cause estimation bias for all but tabular MDPs. This is problematic because it is often computationally infeasible to maintain a full posterior; previous work either maintains a full posterior over the final layer of the function approximator (Osband et al., 2016a; O'Donoghue et al., 2018; Janz et al., 2019) or maintains a diagonal posterior over all parameters (Fortunato et al., 2018; Plappert et al., 2018) of the neural network. Either method limits how expressive the function approximator can be with respect to future states, thereby causing an estimation bias. To establish this formally, let $Q_\theta := w \circ \phi_\vartheta$, where $\theta = (w_1, \ldots, w_n, \vartheta_1, \ldots, \vartheta_v)$, with $w \in \mathbb{R}^n$ a linear projection and $\phi : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^n$ a feature extractor with parameters $\vartheta \in \mathbb{R}^v$.

Proposition 1. *If the number of state-action pairs where $\mathbb{E}_\theta[Q_\theta(s,a)] \neq \mathbb{E}_\theta[Q_\theta(s',a')]$ is greater than n, where $w \in \mathbb{R}^n$, then $\mathbb{E}_\theta[Q_\theta]$ and $\mathbb{V}_\theta[Q_\theta]$ are biased estimators of $\mathbb{E}_M[Q_\pi^M]$ and $\mathbb{V}_M[Q_\pi^M]$ for any choice of $p(M)$.*

This result is a consequence of the feature extractor ψ mapping into a co-domain that is larger than the space spanned by w; a bias results from having more unique state-action representations $\psi(s,a)$ than degrees of freedom in w. The implication is that function approximators under factorised posteriors cannot generalise uncertainty estimates across states (a similar observation in tabular settings was made by Janz et al., 2019)—they can only produce temporally consistent uncertainty estimates if they have the capacity to memorise point-wise uncertainty estimates for each (s, a), which defeats the purpose of a function approximator. Thus, common approaches to uncertainty estimation with neural networks generally fail to provide unbiased uncertainty estimates over the value function in non-trivial MDPs. Proposition 1 shows that to accurately capture value function uncertainty, we need a full posterior over parameters, which is often infeasible. It also underscores that the main issue is the dependence on future state visitation. This motivates Temporal Difference Uncertainties as an estimate of uncertainty *conditioned* on observed state-action transitions.

3 ESTIMATING TEMPORAL DIFFERENCE UNCERTAINTIES IS EASY

Estimating value function uncertainty is made challenging by the inherent uncertainty over future state-action transitions. A direct solution to this problem is to instead *fix* a transition $\tau := (s, a, r, s')$ so that the *only* source of uncertainty over τ is due to $p(\theta)$. Fixing a transition, we induce a conditional distribution $p(\delta \mid \tau)$ over Temporal Difference (TD) errors, $\delta(\theta, \tau) := \gamma Q_\theta(s', \pi(s')) + r - Q_\theta(s, a)$, that we characterise by its mean and variance:

$$\mathbb{E}_\delta[\delta \mid \tau] = \mathbb{E}_\theta[\delta(\theta, \tau) \mid \tau] \qquad \text{and} \qquad \mathbb{V}_\delta[\delta \mid \tau] = \mathbb{V}_\theta[\delta(\theta, \tau) \mid \tau]. \qquad (4)$$

Following O'Donoghue et al. (2018), we derive an exploration signal from the variance; areas where variance over TD errors is high indicate that there are elements of the MDP the function approximator has yet to internalise. Because $p(\delta \mid \tau)$ is defined per transition, it cannot be used as-is for posterior sampling. Therefore, we incorporate TDU as a signal for exploration via an intrinsic reward. To obtain an exploration signal that is on approximately the same scale as the extrinsic reward, we use the standard deviation $\sigma(\tau) := \sqrt{\mathbb{V}_\theta[\delta(\theta, \tau) \mid \tau]}$ to define an augmented reward function

$$\tilde{\mathcal{R}}(\tau) := \mathcal{R}((s, a) \in \tau) + \beta\, \sigma(\tau), \qquad (5)$$

where $\beta \in [0, \infty)$ is a hyper-parameter that determines the emphasis on exploration. Another appealing property of σ is that it naturally decays as the agent converges on a solution (as model uncertainty diminishes); TDU defines a distinct MDP $(\mathcal{S}, \mathcal{A}, \mathcal{P}, \tilde{\mathcal{R}}, \gamma)$ under Eq. 5 that converges on the true MDP in the limit of no model uncertainty. For a given policy π and distribution $p(Q_\theta)$,

Algorithm 1 Bootstrapped DQN with TDU	**Algorithm 2** Bootstrapped TD-loss with TDU.
Require: $M, \mathcal{L}$: MDP to solve, TDU loss	**Require:** $\{\theta^k\}_1^K, \{\tilde{\theta}^k\}_1^N$: parameters
Require: β, K, N, ρ: hyper-parameters	**Require:** $\gamma, \beta, \mathcal{D}$: hyper-parameters, data
1: Initialise $\mathcal{B}$: replay buffer	1: Initialise $\ell \leftarrow 0$
2: Initialise $K + N$ value functions, $\mathcal{Q} \cup \tilde{\mathcal{Q}}$	2: **for** $s, a, r, s', m \in \mathcal{D}$ **do**
3: **while** not done **do**	3: $\tau \leftarrow (s, a, r, s', \gamma)$
4: Observe s and choose $Q_k \sim \mathcal{Q} \cup \tilde{\mathcal{Q}}$	4: Compute $\{\delta_i\}_{i=1}^K = \{\delta(\theta^i, \tau)\}_{i=1}^K$
5: **while** episode not done **do**	5: Compute σ from $\{\delta_k\}_{k=1}^K$ (Eq. 6)
6: Take action $a = \arg\max_{\hat{a}} Q_k(s, \hat{a})$	6: Update τ by $r \leftarrow r + \beta\,\sigma$
7: Sample mask $m, m_i \sim \mathrm{Bin}(n{=}1, p{=}\rho)$	7: Compute $\{\tilde{\delta}_j\}_{j=K+1}^N = \{\delta(\tilde{\theta}^j, \tau)\}_{j=K+1}^N$
8: Enqueue transition (s, a, r, s', m) to $\mathcal{B}$	8: $\ell \leftarrow \ell + \sum_{i=1}^K m_i \delta_i^2 + \sum_{j=1}^N m_{K+j} \tilde{\delta}_j^2$
9: Optimise $\mathcal{L}(\{\theta^k\}_1^K, \{\tilde{\theta}^k\}_1^N, \gamma, \beta, \mathcal{D} \sim \mathcal{B})$	9: **end for**
10: **end while**	10: **return:** $\ell \,/\, (2(N+K)|\mathcal{D}|)$
11: **end while**	

there exists an exploration policy μ that collects transitions over which $p(Q_\theta)$ exhibits maximal uncertainty, as measured by σ. In hard exploration problems, the exploration policy μ can behave fundamentally differently from π. To capture such distinct exploration behaviour, we treat μ as a separate exploration policy that we train to maximise the augmented reward $\tilde{\mathcal{R}}$, along-side training a policy π that maximises the extrinsic reward $\mathcal{R}$. This gives rise to a natural separation of exploitation and exploration in the form of a cooperative multi-agent game, where the exploration policy is tasked with finding experiences where the agent is uncertain of its value estimate for the greedy policy π. As π is trained on this data, we expect uncertainty to vanish (up to noise). As this happens, the exploration policy μ is incentivised to find new experiences with higher estimated uncertainty. This induces a particular pattern where exploration will reinforce experiences until the agent's uncertainty vanishes, at which point the exploration policy expands its state visitation further. This process can allow TDU to overcome estimation bias in the posterior—since it is in effect exploiting it—in contrast to previous methods that do not maintain a distinct exploration policy. We demonstrate this empirically both on Montezuma's Revenge and on Deep Sea (Osband et al., 2020).

4 IMPLEMENTING TDU WITH BOOTSTRAPPING

The distribution over TD-errors that underlies TDU can be estimated using standard techniques for probability density estimation. In this paper, we leverage the statistical bootstrap as it is both easy to implement and provides a robust approximation without requiring distributional assumptions. TDU is easy to implement under the statistical bootstrap—it requires only a few lines of extra code. It can be implemented with value-based as well as actor-critic algorithms (we provide generic pseudo code in Appendix A); in this paper, we focus on Q-learning. Q-learning alternates between policy evaluation (Eq. 1) and policy improvement under a greedy policy $\pi_\theta(s) = \arg\max_a Q_\theta(s, a)$. Deep Q-learning (Mnih et al., 2015) learns Q_θ by minimising its TD-error by stochastic gradient descent on transitions sampled from a replay buffer. Unless otherwise stated, in practice we adopt a common approach of evaluating the action taken by the learned network through a target network with separate parameters that are updated periodically (Van Hasselt et al., 2016).

Our implementation starts from the bootstrapped DQN (Osband et al., 2016a), which maintains a set of K function approximators $\mathcal{Q} = \{Q_{\theta^k}\}_{k=1}^K$, each parameterised by θ^k and regressed towards a unique target function using bootstrapped sampling of data from a shared replay memory. The Bootstrapped DQN derives a policy π_θ by sampling θ uniformly from $\mathcal{Q}$ at the start of each episode. We provide an overview of the Bootstrapped DQN in Algorithm 1 for reference. To implement TDU in this setting, we make a change to the loss function (Algorithm 2, changes highlighted in green).

First, we estimate the TDU signal σ using bootstrapped value estimation. We estimate σ through observed TD-errors $\{\delta_k\}_{k=1}^K$ incurred by the ensemble $\mathcal{Q}$ on a given transition:

$$\sigma(\tau) \approx \sqrt{\frac{1}{K-1} \sum_{k=1}^K \left(\delta(\theta_k, \tau) - \bar{\delta}(\tau)\right)^2}, \tag{6}$$

where $\bar{\delta} = \gamma \bar{Q}' + r - \bar{Q}$, with $\bar{x} := \frac{1}{K} \sum_{i=1}^K x_i$ and $Q' := Q(s', \pi(s'))$. An important assumption underpinning the bootstrapped estimation is that of stochastic optimism (Osband et al., 2016b), which requires the distribution over $\mathcal{Q}$ to be approximately as wide as the true distribution over value estimates. If not, uncertainty over $\mathcal{Q}$ can collapse, which would cause σ to also collapse. To prevent this, $\mathcal{Q}$ can be endowed with a prior (Osband et al., 2018) that maintains diversity in the ensemble by defining each value function as $Q_{\theta^k} + \lambda P_k$, $\lambda \in [0, \infty)$, where P_k is a random prior function.

Rather than feeding this exploration signal back into the value functions in $\mathcal{Q}$, which would create a positive feedback loop (uncertainty begets higher reward, which begets higher uncertainty ad-infinitum), we introduce a separate ensemble of exploration value functions $\tilde{\mathcal{Q}} = \{Q_{\tilde{\theta}^k}\}_{k=1}^N$ that we train over the augmented reward (Eqs. 5 and 6). We derive an exploration policy $\mu_{\tilde{\theta}}$ by sampling exploration parameters $\tilde{\theta}$ uniformly from $\tilde{\mathcal{Q}}$, as in the standard bootstrapped DQN.

In summary, our implementation of TDU maintains $K + N$ value functions. The first K defines a standard Bootstrapped DQN. From these, we derive an exploration signal σ, which we use to train the last N value functions. At the start of each episode, we proceed as in the standard Bootstrapped DQN and randomly sample a parameterisation θ from $\mathcal{Q} \cup \tilde{\mathcal{Q}}$ that we act under for the duration of the episode. All value functions are trained by bootstrapping from a single shared replay memory (Algorithm 1); see Appendix A for a complete JAX (Bradbury et al., 2018) implementation. Consequently, we execute the (extrinsic) reward-maximising policy $\pi_{\theta \sim \mathcal{Q}}$ with probability $K/(K+N)$ and the exploration policy $\mu_{\tilde{\theta} \sim \tilde{\mathcal{Q}}}$ with probability $N/(K+N)$. While π visits states around current reward-maximising behaviour, μ searches for data with high model uncertainty.

There are several equally valid implementations of TDU (see Appendix A for generic implementations for value-based learning and policy-gradient methods). In our case, it would be equally valid to define only a single exploration policy (i.e. $N = 1$) and specify the probability of sampling this policy. While this can result in faster learning, a potential drawback is that it restricts the exploratory behaviour that μ can exhibit at any given time. Using a full bootstrapped ensemble for the exploration policy leverages the behavioural diversity of bootstrapping.

5 EMPIRICAL EVALUATION

5.1 BEHAVIOUR SUITE

Bsuite (Osband et al., 2020) was introduced as a benchmark for characterising core cognitive capabilities of RL agents. We focus on a Deep Sea, which is explicitly designed to test for deep exploration. It is a challenging exploration problem where only one out of 2^N policies yields any positive reward. Performance is compared on instances of the environment with grid sizes $N \in \{10, 12, \ldots, 50\}$, with an overall "score" that is the percentage of N for which average regret goes to below 0.9 faster than 2^N.

For all experiments, we use a standard MLP with Q-learning, off-policy replay and a separate target network. See Appendix C for details and TDU results on the full suite. We compare TDU on Deep Sea to a battery of exploration methods, broadly divided into methods that facilitate exploration by (a) sampling from a posterior (Bootstrapped DQN, Noisy Nets (Fortunato et al., 2018), Successor Uncertainties (Janz et al., 2019)) or (b) use an intrinsic reward (Random Network Distillation (RND; Burda et al., 2018b), CTS (Bellemare et al., 2016a), and Q-Explore (QEX; Simmons-Edler et al., 2019)). We report best scores obtained from a hyper-parameter sweep for each method. Overall, performance varies substantially between methods; only TDU performs (near-)optimally on both the deterministic and stochastic version. Methods that rely on posterior sampling do well on the deterministic version, but suffer a substantial drop in performance on the stochastic version. As the stochastic version serves to increase the complexity of modelling future state visitation, this

Figure 1: Deep Sea Benchmark. QEX, CTS, and RND use intrinsic rewards; BDQN, SU, and NNS use posterior sampling (Section 5.1). Posterior sampling does well on the deterministic version, but struggles on the stochastic version, suggesting an estimation bias (Section 2). Only TDU performs (near-)optimally on both the deterministic and the stochastic version of Deep Sea.

Figure 2: Deep Sea results. All models solve the deterministic version for prior scale $\lambda = 3$ (dashed line). TDU also solves it for $\lambda = 1$. *Left:* introducing stochasticity substantially deteriorates baseline performance; including TDU ($\beta > 0$) recovers close to full performance. *Center left:* effect of varying λ, TDU benefits from diversity in Q estimates. *Center right*: effect of removing prior ($\lambda = 0$). Increasing β improves exploration, but does not reach full performance. *Right:* Qa replaces $\sigma(\delta)$ with $\sigma(\mathcal{Q})$, Qb acts by $\mathrm{argmax}_a(Q + \sigma(\mathcal{Q}))(s, a)$. Estimating uncertainty over Q fails to match TDU.

is clear evidence that these methods suffer from the estimation bias identified in Section 2. We could not make Q-explore and NoisyNets perform well in the default Bsuite setup, while Successor Uncertainties suffers a catastrophic loss of performance on the stochastic version of DeepSea.

Examining TDU, we find that it facilitates exploration while retaining overall performance except on Mountain Car where $\beta > 0$ hurts performance (Appendix C). For Deep Sea (Figure 2), prior functions are instrumental, even for large exploration bonuses ($\beta >> 0$). However, for a given prior strength, TDU does better than the BDQN ($\beta = 0$). In the stochastic version of Deep Sea, BDQN suffers a significant loss of performance (Figure 2). As this is a ceteris paribus comparison, this performance difference can be directly attributed to an estimation bias in the BDQN that TDU circumvents through its intrinsic reward. That TDU is able to facilitate efficient exploration despite environment stochasticity demonstrates that it can correct for such estimation errors.

Finally, we compare TDU to alternative versions that construct an intrinsic reward directly from value estimates, as opposed to TD-errors. We compare TDU to (a) a version where σ is defined as standard deviation over $\mathcal{Q}$ and (b) where $\sigma(\mathcal{Q})$ is used as an upper confidence bound in the policy, instead of as an intrinsic reward (Figure 2). Neither matches TDU's performance across Bsuite and in particular on the Deep Sea exploration problem, suggesting that the key to TDU's success is that the intrinsic reward relies on a distribution of TD-errors to control for environment uncertainty.

Figure 3: Atari results with distributed training. We compare TDU with and without additive prior functions to R2D2 and Bootstrapped R2D2 (B-R2D2). *Left*: Results for `montezuma_revenge`. *Center*: Results for `tennis`. *Right*: Mean HNS for the hard exploration games in the Atari2600 suite (including `tennis`). TDU achieves a higher performance than baselines.

5.2 ATARI

Proposition 1 shows that estimation bias is particularly likely in complex environments that require neural networks to generalise across states. Such domains also require advanced learning algorithms to scale well. Therefore, we study whether TDU can scale to sophisticated off-policy learning setups in the context of the R2D2 algorithm (Kapturowski et al., 2018).

In recent years, significant improvements in deep RL systems have been achieved by running on distributed training platforms that can process large amounts of experience obtained through agent parallelism. It is thus important to develop exploration algorithms that scale gracefully and can leverage the benefits of distributed training. In this section we evaluate whether TDU can have a positive impact when combined with the Recurrent Replay Distributed DQN (R2D2) (Kapturowski et al., 2018), which achieves state-of-the-art results on the Atari2600 suite by carefully combining a set of key components: a recurrent state, experience replay, off-policy value learning and distributed training. As a baseline we implemented a distributed version of the bootstrapped DQN with additive prior functions. We present full implementation details, hyper-parameter choices, and results on all games in Appendix D. Here, we focus on games that are well-known to pose challenging exploration problems (Machado et al., 2018): `montezuma_revenge`, `pitfall`, `private_eye`, `solaris`, `venture`, `gravitar`, and `tennis`. Following standard practice, Figure 3 reports Human Normalized Score (HNS), HNS $= \frac{\text{Agent}_{\text{score}} - \text{Random}_{\text{score}}}{\text{Human}_{\text{score}} - \text{Random}_{\text{score}}}$, as an aggregate result across exploration games as well as results on `montezuma_revenge` and `tennis`, which are both known the be particularly hard exploration games (Machado et al., 2018).

TDU is instrumental in achieving high rewards on `tennis` and results in a significant improvement on `montezuma_revenge` within 10 billion environment steps. More generally, we find that TDU facilitates exploration substantially, improving the mean HNS score across exploration games by 30% compared to baselines. We observe no significant gains from including prior functions with TDU in this experiment and find that bootstrapping alone produces relatively marginal gains. Beyond exploration games, TDU can match or improve upon the baseline, but exhibits greater sensitivity to hyper-parameter choices that dictate the degree of exploration (β, number of explorers (N); see Appendix D for details). This finding is in line with observations made by (Puigdomènech Badia et al., 2020); combining TDU with adaptive policy sampling (Schaul et al., 2019) or online hyper-parameter tuning (Xu et al., 2018; Zahavy et al., 2020) are exciting avenues for future research. See Appendix D for further comparisons.

6 RELATED WORK

Fundamentally, TDU relies on quantifying uncertainty in terms of value estimates of a policy. Bayesian approaches to exploration typically use uncertainty as the mechanism for balancing ex-

ploitation and exploration (Strens, 2000). A popular instance of this form of exploration is the PILCO algorithm (Deisenroth & Rasmussen, 2011). Recent work places the posterior distribution directly over the value function (Osband et al., 2016a;b) to avoid modelling the full MDP. In this paper, we use bootstrapped DQN (Osband et al., 2016a) to obtain uncertainty estimates over the value function, but several other approaches have been proposed in the literature; such as by placing a parameterised distribution over model parameters (Fortunato et al., 2018; Plappert et al., 2018) or by modeling a distribution over both the value and the returns (Moerland et al., 2017), using Bayesian linear regression on the value function (Azizzadenesheli et al., 2018; Janz et al., 2019), or by modelling the variance over value estimates as a Bellman operation (O'Donoghue et al., 2018). The underlying exploration mechanism in these works is posterior sampling from the agent's current beliefs (Thompson, 1933; Dearden et al., 1998); our work suggests that estimating this posterior is significantly more challenging that previously thought.

An alternative to posterior sampling is to facilitate exploration via learning by introducing an intrinsic reward function. Previous works typically formulate intrinsic rewards in terms of state visitation (Lopes et al., 2012; Bellemare et al., 2016a; Puigdomènech Badia et al., 2020), state novelty (Schmidhuber, 1991; Oudeyer & Kaplan, 2009; Pathak et al., 2017), or state predictability (Florensa et al., 2017; Burda et al., 2018b; Gregor et al., 2016; Hausman et al., 2018). Most of these works rely on properties of the state space to drive exploration while ignoring rewards. While this can be effective in sparse reward settings (e.g. Burda et al., 2018b; Puigdomènech Badia et al., 2020), it can also lead to arbitrarily bad as the exploration (see analysis in Osband et al., 2019).

A smaller body of work uses statistics derived from observed rewards (Nachum et al., 2016) or TD-errors to design intrinsic reward functions; our work is particularly related to the latter. Tokic (2010) proposes an extension of ϵ-greedy exploration, where the TD-error modulates ϵ to be higher in states with higher TD-error. Gehring & Precup (2013) use the mean absolute TD-error, accumulated over time, to measure controllability of a state and reward the agent for visiting states with low mean absolute TD-error. In contrast to our work, this method integrates the TD-error over time to obtain a measure of irreducibility. Simmons-Edler et al. (2019) propose to use two Q-networks, where one is trained on data collected under both networks and the other obtains an intrinsic reward equal to the absolute TD-error of the first network on a given transition. In contrast to our work, this method does not have a probabilistic interpretation and thus does not control for uncertainty over the environment. TD-errors have also been used in White et al. (2015), where surprise is defined in terms of the moving average of the TD-error over the full variance of the TD-error. Finally, using the TD-error as an exploration signal is related to the notion of "learnability" or curiosity as a signal for exploration, which is often modelled in terms of the prediction error in a dynamics model (e.g. Schmidhuber, 1991; Oudeyer et al., 2007; Gordon & Ahissar, 2011; Pathak et al., 2017).

7 CONCLUSION

We present Temporal Difference Uncertainties (TDU), a method for estimating uncertainty over an agent's value function. Obtaining well-calibrated uncertainty estimates under function approximation is non-trivial and we show that popular approaches, while in principle valid, can fail to accurately represent uncertainty over the value function because they must represent an unknown future.

This motivates TDU as an estimate of uncertainty conditioned on observed state-action transitions, so that the only source of uncertainty for a given transition is due to uncertainty over the agent's parameters. This gives rise to an intrinsic reward that encodes the agent's model uncertainty, and we capitalise on this signal by introducing a distinct exploration policy. This policy is incentivised to collect data over which the agent has high model uncertainty and we highlight how this separation gives rise to a form of cooperative multi-agent game. We demonstrate empirically that TDU can facilitate efficient exploration in hard exploration games such as Deep Sea and Montezuma's Revenge.

REFERENCES

Azizzadenesheli, K., Brunskill, E., and Anandkumar, A. Efficient exploration through bayesian deep q-networks. *arXiv preprint arXiv:1802.04412*, 2018.

Belkin, M., Hsu, D., and Xu, J. Two models of double descent for weak features. *arXiv preprint arXiv:1903.07571*, 2019.

Bellemare, M., Srinivasan, S., Ostrovski, G., Schaul, T., Saxton, D., and Munos, R. Unifying count-based exploration and intrinsic motivation. In *Advances in Neural Information Processing Systems*, 2016a.

Bellemare, M., Srinivasan, S., Ostrovski, G., Schaul, T., Saxton, D., and Munos, R. Unifying count-based exploration and intrinsic motivation. In *Advances in Neural Information Processing Systems*, pp. 1471–1479, 2016b.

Bradbury, J., Frostig, R., Hawkins, P., Johnson, M. J., Leary, C., Maclaurin, D., and Wanderman-Milne, S. JAX: composable transformations of Python+NumPy programs, 2018. URL http://github.com/google/jax.

Burda, Y., Edwards, H., Pathak, D., Storkey, A. J., Darrell, T., and Efros, A. A. Large-scale study of curiosity-driven learning. *CoRR*, abs/1808.04355, 2018a.

Burda, Y., Edwards, H., Storkey, A. J., and Klimov, O. Exploration by random network distillation. *arXiv preprint arXiv:1810.12894*, 2018b.

Choi, J., Guo, Y., Moczulski, M., Oh, J., Wu, N., Norouzi, M., and Lee, H. Contingency-aware exploration in reinforcement learning. *arXiv preprint arXiv:1811.01483*, 2018.

Dearden, R., Friedman, N., and Russell, S. Bayesian q-learning. In *Association for the Advancement of Artificial Intelligence*, 1998.

Deisenroth, M. and Rasmussen, C. E. Pilco: A model-based and data-efficient approach to policy search. In *International Conference on Machine Learning*, 2011.

Florensa, C., Duan, Y., and Abbeel, P. Stochastic neural networks for hierarchical reinforcement learning. In *International Conference on Learning Representations*, 2017.

Fortunato, M., Azar, M. G., Piot, B., Menick, J., Osband, I., Graves, A., Mnih, V., Munos, R., Hassabis, D., Pietquin, O., et al. Noisy networks for exploration. In *International Conference on Learning Representations*, 2018.

Gehring, C. and Precup, D. Smart exploration in reinforcement learning using absolute temporal difference errors. In *Proceedings of the International Conference on Autonomous Agents and Multi-Agent Systems*, 2013.

Gordon, G. and Ahissar, E. Reinforcement active learning hierarchical loops. In *International Joint Conference on Neural Networks*, pp. 3008–3015, 2011.

Gregor, K., Rezende, D. J., and Wierstra, D. Variational intrinsic control. *CoRR*, abs/1611.07507, 2016.

Hausman, K., Springenberg, J. T., Wang, Z., Heess, N., and Riedmiller, M. Learning an embedding space for transferable robot skills. In *International Conference on Learning Representations*, 2018.

Janz, D., Hron, J., Hernández-Lobato, J. M., Hofmann, K., and Tschiatschek, S. Successor uncertainties: exploration and uncertainty in temporal difference learning. In *Advances in Neural Information Processing Systems*, 2019.

Kapturowski, S., Ostrovski, G., Quan, J., Munos, R., and Dabney, W. Recurrent experience replay in distributed reinforcement learning. In *International Conference on Learning Representations*, 2018.

Kearns, M. and Singh, S. Near-optimal reinforcement learning in polynomial time. *Machine learning*, 49(2-3):209–232, 2002.

Kingma, D. P. and Ba, J. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

Li, Y., Gimeno, F., Kohli, P., and Vinyals, O. Strong generalization and efficiency in neural programs. *arXiv preprint arXiv:2007.03629*, 2020.

Liu, C., Zhu, L., and Belkin, M. Toward a theory of optimization for over-parameterized systems of non-linear equations: the lessons of deep learning. *CoRR*, abs/2003.00307, 2020.

Lopes, M., Lang, T., Toussaint, M., and Oudeyer, P.-Y. Exploration in model-based reinforcement learning by empirically estimating learning progress. In *Advances in Neural Information Processing Systems*, 2012.

Machado, M. C., Bellemare, M. G., Talvitie, E., Veness, J., Hausknecht, M., and Bowling, M. Revisiting the arcade learning environment: Evaluation protocols and open problems for general agents. *Journal of Artificial Intelligence Research*, 61:523–562, 2018.

Mnih, V., Kavukcuoglu, K., Silver, D., Rusu, A. A., Veness, J., Bellemare, M. G., Graves, A., Riedmiller, M., Fidjeland, A. K., Ostrovski, G., et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Moerland, T. M., Broekens, J., and Jonker, C. M. Efficient exploration with double uncertain value networks. In *Advances in Neural Information Processing Systems*, 2017.

Nachum, O., Norouzi, M., and Schuurmans, D. Improving policy gradient by exploring underappreciated rewards. In *International Conference on Learning Representations*, 2016.

Osband, I., Russo, D., and Van Roy, B. (more) efficient reinforcement learning via posterior sampling. In *Advances in Neural Information Processing Systems*, 2013.

Osband, I., Blundell, C., Pritzel, A., and Van Roy, B. Deep exploration via bootstrapped dqn. In *Advances in Neural Information Processing Systems*, 2016a.

Osband, I., Van Roy, B., and Wen, Z. Generalization and exploration via randomized value functions. In *International Conference on Machine Learning*, 2016b.

Osband, I., Aslanides, J., and Cassirer, A. Randomized prior functions for deep reinforcement learning. In *Advances in Neural Information Processing Systems*, 2018.

Osband, I., Van Roy, B., Russo, D. J., and Wen, Z. Deep exploration via randomized value functions. *Journal of Machine Learning Research*, 20:1–62, 2019.

Osband, I., Doron, Y., Hessel, M., Aslanides, J., Sezener, E., Saraiva, A., McKinney, K., Lattimore, T., Szepezvari, C., Singh, S., and Benjamin Van Roy, Richard Sutton, D. S. H. V. H. Behaviour suite for reinforcement learning. In *International Conference on Learning Representations*, 2020.

Ostrovski, G., Bellemare, M. G., van den Oord, A., and Munos, R. Count-based exploration with neural density models. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 2721–2730. JMLR. org, 2017.

Oudeyer, P.-Y. and Kaplan, F. What is intrinsic motivation? a typology of computational approaches. *Frontiers in neurorobotics*, 1:6, 2009.

Oudeyer, P.-Y., Kaplan, F., and Hafner, V. V. Intrinsic motivation systems for autonomous mental development. *IEEE transactions on evolutionary computation*, 11(2):265–286, 2007.

O'Donoghue, B., Osband, I., Munos, R., and Mnih, V. The uncertainty bellman equation and exploration. In *International Conference on Machine Learning*, 2018.

Pathak, D., Agrawal, P., Efros, A. A., and Darrell, T. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning*, 2017.

Plappert, M., Houthooft, R., Dhariwal, P., Sidor, S., Chen, R. Y., Chen, X., Asfour, T., Abbeel, P., and Andrychowicz, M. Parameter space noise for exploration. In *International Conference on Learning Representations*, 2018.

Puigdomènech Badia, A., Sprechmann, P., Vitvitskyi, A., Guo, D., Piot, B., Kapturowski, S., Tieleman, O., Arjovsky, M., Pritzel, A., Bolt, A., and Blundell, C. Never give up: Learning directed exploration strategies. In *International Conference on Learning Representations*, 2020.

Schaul, T., Borsa, D., Ding, D., Szepesvari, D., Ostrovski, G., Dabney, W., and Osindero, S. Adapting behaviour for learning progress. *arXiv preprint arXiv:1912.06910*, 2019.

Schmidhuber, J. Curious model-building control systems. In *Proceedings of the International Joint Conference on Neural Networks*, 1991.

Simmons-Edler, R., Eisner, B., Mitchell, E., Seung, H. S., and Lee, D. D. Qxplore: Q-learning exploration by maximizing temporal difference error. *arXiv preprint arXiv:1906.08189*, 2019.

Singh, S. P., Barto, A. G., and Chentanez, N. Intrinsically motivated reinforcement learning. In *Advances in Neural Information Processing Systems*, 2005.

Strens, M. A bayesian framework for reinforcement learning. In *International Conference on Machine Learning*, 2000.

Thompson, W. R. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3/4):285–294, 1933.

Tokic, M. Adaptive ε-greedy exploration in reinforcement learning based on value differences. In *Annual Conference on Artificial Intelligence*, pp. 203–210. Springer, 2010.

Van Hasselt, H., Guez, A., and Silver, D. Deep reinforcement learning with double Q-learning. In *Association for the Advancement of Artificial Intelligence*, 2016.

White, A. et al. *Developing a predictive approach to knowledge*. PhD thesis, University of Alberta, 2015.

Williams, R. J. and Peng, J. Function optimization using connectionist reinforcement learning algorithms. *Connection Science*, 3(3):241–268, 1991.

Xu, T., Liu, Q., Zhao, L., and Peng, J. Learning to explore via meta-policy gradient. In *International Conference on Machine Learning*, 2018.

Zahavy, T., Xu, Z., Veeriah, V., Hessel, M., Oh, J., van Hasselt, H., Silver, D., and Singh, S. Self-tuning deep reinforcement learning. *arXiv preprint arXiv:2002.12928*, 2020.

Ziebart, B. D., Maas, A., Bagnell, J. A., and Dey, A. K. Maximum entropy inverse reinforcement learning. In *Association for the Advancement of Artificial Intelligence*, 2008.

A IMPLEMENTATION AND CODE

In this section, we provide code for implementing TDU in a general policy-agnostic setting and in the specific case of bootstrapped Q-learning. Algorithm 3 presents TDU in a policy-agnostic framework. TDU can be implemented as a pre-processing step (Line 9) that augments the reward with the exploration signal before computing the policy loss. If Algorithm 3 is used to learn a single policy, it benefits from the TDU exploration signal but cannot learn distinct exploration policies for it. In particular, on-policy learning does not admit such a separation. To learn a distinct exploration policy, we can use Algorithm 3 to train the *exploration* policy, while the another policy is trained to maximise extrinsic rewards only using both its own data and data from the exploration policy. In case of multiple policies, we need a mechanism for sampling behavioural policies. In our experiments we settled on uniform sampling; more sophisticated methods can potentially yield better performance.

In the case of value-based learning, TDU takes a special form that can be implemented efficiently as a staggered computation of TD-errors (Algorithm 4). Concretely, we compute an estimate of the distribution of TD-errors from some given distribution over the value function parameters (Algorithm 4, Line 3). These TD-errors are used to compute the TDU signal σ, which then modulates the reward used to train a Q function (Algorithm 4, Line 7). Because the only quantities being computed are TD-errors, this can be combined into a single error signal (Algorithm 4, Line 11). When implemented under bootstrapping, `Qparams` denotes the ensemble $\mathcal{Q}$ and `Qtilde_distribution_params` denotes the ensemble $\tilde{\mathcal{Q}}$; we compute the loss as in Algorithm 2.

Finally, Algorithm 5 presents a complete JAX (Bradbury et al., 2018) implementation that can be used along with the Bsuite (Osband et al., 2020) codebase.[1] We present the corresponding TDU agent class (Algorithm 4), which is a modified version of the `BootstrappedDqn` class in `bsuite/baselines/jax/boot_dqn/agent.py` and can be used by direct swap-in.

Algorithm 3 Pseudo-code for generic TDU loss

```
1  def loss(transitions, pi_params, Qtilde_distribution_params, beta):
2    # Estimate TD-error distribution.
3    td = array([td_error(p, transitions) for p in sample(Qtilde_distribution_params)])
4
5    # Compute critic loss.
6    td_loss = mean(0.5 * (td ** 2))
7
8    # Compute exploration bonus.
9    transitions.r_t += beta * stop_gradient(std(td, axis=1))
10
11   # Compute policy loss on transition with augmented reward.
12   pi_loss = pi_loss_fn(pi_params, transitions)
13
14   return pi_loss, td_loss
```

Algorithm 4 Pseudo-code for Q-learning TDU loss

```
1  def loss(transitions, Q_params, Qtilde_distribution_params, beta):
2    # Estimate TD-error distribution.
3    td_K = array([td_error(p, transitions) for p in sample(Qtilde_distribution_params)])
4
5    # Compute exploration bonus and Q-function reward.
6    transitions.reward_t += beta * stop_gradient(std(td_K, axis=1))
7    td_N = td_error(Q_params, transitions)
8
9    # Combine for overall TD-loss.
10   td_errors = concatenate((td_ex, td_in), axis=1)
11   td_loss = mean(0.5 * (td_errors) ** 2))
12   return td_loss
```

---

[1] Available at: https://github.com/deepmind/bsuite.

Algorithm 5 JAX implementation of TDU Agent under Bootstrapped DQN

```
1  # Copyright 2020 the Temporal Difference Uncertainties as a Signal for Exploration authors.  Licensed under
2  # the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with
3  # the License.  You may obtain a copy of the License at https://www.apache.org/licenses/LICENSE-2.0.
4  # Unless required by applicable law or agreed to in writing, software distributed under the License is
5  # distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
6  # See the License for the specific language governing permissions and limitations under the License.
7
8  class TDU(bsuite.baselines.jax.boot_dqn.BootstrappedDqn):
9
10   def __init__(self, K: int, beta: float, **kwargs: Any):
11     """TDU under Bootstrapped DQN with randomized prior functions."""
12     super(TDU, self).__init__(**kwargs)
13     network, optimizer, N = kwargs['network'], kwargs['optimizer'], kwargs['num_ensemble']
14     noise_scale, discount = kwargs['noise_scale'], kwargs['discount']
15
16     def td(params: hk.Params, target_params: hk.Params,
17            transitions: Sequence[jnp.ndarray]) -> jnp.ndarray:
18       """TD-error with added reward noise + half-in bootstrap."""
19       o_tm1, a_tm1, r_t, d_t, o_t, z_t = transitions
20       q_tm1 = network.apply(params, o_tm1)
21       q_t = network.apply(target_params, o_t)
22       r_t += noise_scale * z_t
23       return jax.vmap(rlax.q_learning)(q_tm1, a_tm1, r_t, discount * d_t, q_t)
24
25     def loss(params: Sequence[hk.Params], target_params: Sequence[hk.Params],
26            transitions: Sequence[jnp.ndarray]) -> jnp.ndarray:
27       """Q-learning loss with TDU."""
28       # Compute TD-errors for first K members.
29       o_tm1, a_tm1, r_t, d_t, o_t, m_t, z_t = transitions
30       td_K = [td(params[k], target_params[k],
31              [o_tm1, a_tm1, r_t, d_t, o_t, z_t[:, k]]) for k in range(K)]
32
33       # TDU signal on first K TD-errors.
34       r_t += beta * jax.lax.stop_gradient(jnp.std(jnp.stack(td_K, axis=0), axis=0))
35
36       # Compute TD-errors on augmented reward for last K members.
37       td_N = [td(params[k], target_params[k],
38              [o_tm1, a_tm1, r_t, d_t, o_t, z_t[:, k]]) for k in range(K, N)]
39
40       return jnp.mean(m_t.T * jnp.stack(td_K + td_N)  ** 2)
41
42     def update(state: TrainingState, gradient: Sequence[jnp.ndarray]) -> TrainingState:
43       """Gradient update on ensemble member."""
44       updates, new_opt_state = optimizer.update(gradient, state.opt_state)
45       new_params = optix.apply_updates(state.params, updates)
46       return TrainingState(params=new_params, target_params=state.target_params,
47                            opt_state=new_opt_state, step=state.step + 1)
48
49     @jax.jit
50     def sgd_step(states: Sequence[TrainingState],
51                  transitions: Sequence[jnp.ndarray]) -> Sequence[TrainingState]:
52       """Does a step of SGD for the whole ensemble over 'transitions'."""
53       params, target_params = zip(*[(state.params, state.target_params) for state in states])
54       gradients = jax.grad(loss)(params, target_params, transitions)
55       return [update(state, gradient) for state, gradient in zip(states, gradients)]
56
57     self._sgd_step = sgd_step  # patch BootDQN sgd_step with TDU sgd_step.
58
59   def update(self, timestep: dm_env.TimeStep, action: base.Action,
60              new_timestep: dm_env.TimeStep):
61     """Update the agent: add transition to replay and periodically do SGD."""
62     if new_timestep.last():
63       self._active_head = self._ensemble[np.random.randint(0, self._num_ensemble)]
64
65     mask = np.random.binomial(1, self._mask_prob, self._num_ensemble)
66     noise = np.random.randn(self._num_ensemble)
67     transition = [timestep.observation, action, np.float32(new_timestep.reward),
68                   np.float32(new_timestep.discount), new_timestep.observation, mask, noise]
69     self._replay.add(transition)
70     if self._replay.size < self._min_replay_size:
71       return
72
73     if self._total_steps % self._sgd_period == 0:
74       transitions = self._replay.sample(self._batch_size)
75       self._ensemble = self._sgd_step(self._ensemble, transitions)
76
77     for k, state in enumerate(self._ensemble):
78       if state.step % self._target_update_period == 0:
79         self._ensemble[k] = state._replace(target_params=state.params)
```

B   PROOFS

We begin with the proof of Lemma 1. First, we show that if Eq. 2 and Eq. 3 fail, $p(\theta)$ induce a distribution $p(Q_\theta)$ whose first two moments are biased estimators of the moments of the distribution of interest $p(Q_\pi)$, for *any* choice of belief over the MDP, $p(M)$. We restate it here for convenience.

Lemma 1. *If $\mathbb{E}_\theta[Q_\theta]$ and $\mathbb{V}_\theta[Q_\theta]$ fail to satisfy Eqs. 2 and 3, respectively, they are biased estimators of $\mathbb{E}_M\big[Q_\pi^M\big]$ and $\mathbb{V}_M\big[Q_\pi^M\big]$ for any choice of $p(M)$.*

Proof. Assume the contrary, that $\mathbb{E}_M\big[Q_\pi^M(s, \pi(s))\big] = \mathbb{E}_\theta[Q_\theta(s, \pi(s))]$ for all $(s, a) \in \mathcal{S} \times \mathcal{A}$. If Eqs. 2 and 3 do not hold, then for any $\mathbb{M} \in \{\mathbb{E}, \mathbb{V}\}$,

$$\mathbb{M}_M\big[Q_\pi^M(s, \pi(s))\big] = \mathbb{M}_\theta[Q_\theta(s, \pi(s))] \tag{7}$$

$$\neq \mathbb{M}_\theta\left[\mathbb{E}_{\substack{s' \sim \mathcal{P}(s, \pi(s)) \\ r \sim \mathcal{R}(s, \pi(s))}}[r + \gamma Q_\theta(s', \pi(s'))]\right] \tag{8}$$

$$= \mathbb{E}_{\substack{s' \sim \mathcal{P}(s, \pi(s)) \\ r \sim \mathcal{R}(s, \pi(s))}}[r + \gamma \mathbb{M}_\theta[Q_\theta(s', \pi(s'))]] \tag{9}$$

$$= \mathbb{E}_{\substack{s' \sim \mathcal{P}(s, \pi(s)) \\ r \sim \mathcal{R}(s, \pi(s))}}[r + \gamma \mathbb{M}_M\big[Q_\pi^M(s', \pi(s'))\big]] \tag{10}$$

$$= \mathbb{M}_M\left[\mathbb{E}_{\substack{s' \sim \mathcal{P}(s, \pi(s)) \\ r \sim \mathcal{R}(s, \pi(s))}}\big[r + \gamma Q_\pi^M(s', \pi(s'))\big]\right] \tag{11}$$

$$= \mathbb{M}_M\big[Q_\pi^M(s, \pi(s))\big], \tag{12}$$

a contradiction; conclude that $\mathbb{M}_M\big[Q_\pi^M(s, \pi(s))\big] \neq \mathbb{M}_\theta[Q_\theta(s, \pi(s))]$. Eqs. 8 and 12 use Eqs. 2 and 3; Eqs. 7, 8 and 10 follow by assumption; Eqs. 9 and 11 use linearity of the expectation operator $\mathbb{E}_{r, s'}$ by virtue of $\mathbb{M}$ being defined over θ. As (s, a, r, s') and $p(M)$ are arbitrary, the conclusion follows. ∎

Methods that take inspiration from by PSRL but rely on neural networks typically approximate $p(M)$ by a parameter distribution $p(\theta)$ over the value function. Lemma 1 establishes that the induced distribution $p(Q_\theta)$ under push-forward of $p(\theta)$ must propagate the moments of the distribution $p(Q_\theta)$ consistently over the state-space to be unbiased estimate of $p(Q_\pi^M)$, for any $p(M)$.

With this in mind, we now turn to neural networks and their ability to estimate value function uncertainty in MDPs. To prove our main result, we establish two intermediate results. Recall that we define a function approximator $Q_\theta = w \circ \phi_\vartheta$, where $\theta = (w_1, \ldots, w_n, \vartheta_1, \ldots, \vartheta_v)$; $w \in \mathbb{R}^n$ is a linear layer and $\phi : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^n$ is a feature extractor with parameters $\vartheta \in \mathbb{R}^v$.

As before, let M be an MDP $(\mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma)$ with discrete state and action spaces. We denote by N the number of states and actions with $\mathbb{E}_\theta[Q_\theta(s, a)] \neq \mathbb{E}_\theta[Q_\theta(s', a')]$ with $\mathcal{N} \subset \mathcal{S} \times \mathcal{A} \times \mathcal{S} \times \mathcal{A}$ the set of all such pairs (s, a, s', a'). This set can be thought of as a minimal MDP—the set of states within a larger MDP where the function approximator generates unique predictions. It arises in an MDP through dense rewards, stochastic rewards, or irrevocable decisions, such as in Deep Sea. Our first result is concerned with a very common approach, where ϑ is taken to be a point estimate so that $p(\theta) = p(w)$. This approach is often used for large neural networks, where placing a posterior over the full network would be too costly (Osband et al., 2016a; O'Donoghue et al., 2018; Azizzadenesheli et al., 2018; Janz et al., 2019).

Lemma 2. *Let $p(\theta) = p(w)$. If $N > n$, with $w \in \mathbb{R}^n$, then $\mathbb{E}_\theta[Q_\theta]$ fail to satisfy the first moment Bellman equation (Eq. 2). Further, if $N > n^2$, then $\mathbb{V}_\theta[Q_\theta]$ fail to satisfy the second moment Bellman equation (Eq. 3).*

Proof. Write the first condition of Eq. 2 as

$$\mathbb{E}_\theta\big[w^T \phi_\vartheta(s, a)\big] = \mathbb{E}_\theta\big[\mathbb{E}_{r, s'}\big[r + \gamma w^T \phi_\vartheta(s', \pi(s'))\big]\big]. \tag{13}$$

Using linearity of the expectation operator along with $p(\theta) = p(w)$, we have

$$\mathbb{E}_w[w]^T \phi_\vartheta(s, a) = \mu(s, a) + \gamma \mathbb{E}_w[w]^T \mathbb{E}_{s'}[\phi_\vartheta(s', \pi(s'))], \tag{14}$$

where $\mu(s, a) = \mathbb{E}_{r \sim \mathcal{R}(s,a)}[r]$. Rearrange to get

$$\mu(s, a) = \mathbb{E}_w[w]^T \left(\phi_\vartheta(s, a) - \gamma \mathbb{E}_{s'}[\phi_\vartheta(s', \pi(s'))] \right). \tag{15}$$

By assumption $\mathbb{E}_\theta[Q_\theta(s, a)] \neq \mathbb{E}_\theta[Q_\theta(s', a')]$, which implies $\phi_\vartheta(s, a) \neq \phi_\vartheta(s', \pi(s'))$ by linearity in w. Hence $\phi_\vartheta(s, a) - \gamma \mathbb{E}_{s'}[\phi_\vartheta(s', \pi(s'))]$ is non-zero and unique for each (s, a). Thus, Eq. 15 forms a system of linear equations over $\mathcal{S} \times \mathcal{A}$, which can be reduced to a full-rank system over $\mathcal{N}$: $\mu = \Phi \mathbb{E}_w[w]$, where $\mu \in \mathbb{R}^N$ stacks expected reward $\mu(s, a)$ and $\Phi \in \mathbb{R}^{N \times n}$ stacks vectors $\phi_\vartheta(s, a) - \gamma \mathbb{E}_{s'}[\phi_\vartheta(s', \pi(s'))]$ row-wise. Because Φ is full rank, if $N > n$, this system has no solution. The conclusion follows for $\mathbb{E}_\theta[Q_\theta]$. If the estimator of the mean is used to estimate the variance, then the estimator of the variance is biased. For an unbiased mean, using linearity in w, write the condition of Eq. 3 as

$$\mathbb{E}_\theta \left[\left[(w - \mathbb{E}_w[w])^T \phi_\vartheta(s, a) \right]^2 \right] = \mathbb{E}_\theta \left[\left[\gamma(w - \mathbb{E}_w[w])^T \mathbb{E}_{s'}[\phi_\vartheta(s', \pi(s'))] \right]^2 \right]. \tag{16}$$

Let $\tilde{w} = (w^T - \mathbb{E}_w[w])$, $x = \tilde{w}^T \phi_\vartheta(s, a)$, $y = \gamma \tilde{w}^T \mathbb{E}_{s'}[\phi_\vartheta(s', a')]$. Rearrange to get

$$\mathbb{E}_\theta[x^2 - y^2] = \mathbb{E}_w[(x - y)(x + y)] = 0. \tag{17}$$

Expanding terms, we find

$$0 = \mathbb{E}_\theta \left[\left(\tilde{w}^T[\phi_\vartheta(s, a) - \gamma \mathbb{E}_{s'}[\phi_\vartheta(s', a')]] \right) \left(\tilde{w}^T[\phi_\vartheta(s, a) + \gamma \mathbb{E}_{s'}[\phi_\vartheta(s', a')]] \right) \right] \tag{18}$$

$$= \sum_{i=1}^n \sum_{j=1}^n \mathbb{E}_w[\tilde{w}_i \tilde{w}_j] d_i^- d_j^+ = \sum_{i=1}^n \sum_{j=1}^n \text{Cov}(w_i, w_j) d_i^- d_j^+. \tag{19}$$

where we define $d^- = \phi_\vartheta(s, a) - \gamma \mathbb{E}_{s'}[\phi_\vartheta(s', a')]$ and $d^+ = \phi_\vartheta(s, a) + \gamma \mathbb{E}_{s'}[\phi_\vartheta(s', a')]$. As before, d^- and d^+ are non-zero by assumption of unique Q-values. Perform a change of variables $\omega_{\alpha(i,j)} = \text{Cov}(w_i, w_j)$, $\lambda_{\alpha(i,j)} = d_i^- d_j^+$ to write Eq. 19 as $0 = \lambda^T \omega$. Repeating the above process for every state and action we have a system $\mathbf{0} = \Lambda \omega$, where $\mathbf{0} \in \mathbb{R}^N$ and $\Lambda \in \mathbb{R}^{N \times n^2}$ are defined by stacking vectors λ row-wise. This is a system of linear equations and if $N > n^2$ no solution exists; thus, the conclusion follows for $\mathbb{V}_\theta[Q_\theta]$, concluding the proof. ∎

Note that if $\mathbb{E}_\theta[Q_\theta]$ is biased and used to construct the estimator $\mathbb{E}_\theta[Q_\theta]$, then this estimator is also biased; hence if $N > n$, $p(\theta)$ induce biased estimators $\mathbb{E}_\theta[Q_\theta]$ and $\mathbb{V}_\theta[Q_\theta]$ of $\mathbb{E}_M[Q_\pi^M]$ and $\mathbb{V}_M[Q_\pi^M]$, respectively.

Lemma 2 can be seen as a statement about linear uncertainty. While the result is not too surprising from this point of view, it is nonetheless a frequently used approach to uncertainty estimation. We may hope then that by placing uncertainty over the feature extractor as well, we can benefit from its nonlinearity to obtain greater representational capacity with respect to uncertainty propagation. Such posteriors come at a price. Placing a full posterior over a neural network is often computationally infeasible, instead a common approach is to use a diagonal posterior, i.e. $\text{Cov}(\theta_i, \theta_j) = 0$ (Fortunato et al., 2018; Plappert et al., 2018). Our next result shows that any posterior of this form suffers from the same limitations as placing a posterior only over the final layer. We establish something stronger: any posterior of the form $p(\theta) = p(w)p(\vartheta)$ suffers from the limitations described in Lemma 2.

Lemma 3. *Let $p(\theta) = p(w)p(\vartheta)$; if $N > n$, with $w \in \mathbb{R}^n$, then $\mathbb{E}_\theta[Q_\theta]$ fail to satisfy the first moment Bellman equation (Eq. 2). Further, if $N > n^2$, then $\mathbb{V}_\theta[Q_\theta]$ fail to satisfy the second moment Bellman equation (Eq. 3).*

Proof. The proof largely proceeds as in the proof of Lemma 2. Re-write Eq. 14 as

$$\mathbb{E}_w[w]^T \mathbb{E}_\vartheta[\phi_\vartheta(s,a)] = \mu(s,a) + \gamma \mathbb{E}_w[w]^T \mathbb{E}_{s'}[\mathbb{E}_\vartheta[\phi_\vartheta(s',\pi(s'))]]. \tag{20}$$

Perform a change of variables $\tilde{\phi} = \mathbb{E}_\vartheta[\phi_\vartheta]$ to obtain

$$\mu(s,a) = \mathbb{E}_w[w]^T \left(\tilde{\phi}(s,a) - \gamma \mathbb{E}_{s'}\left[\tilde{\phi}(s',\pi(s')) \right] \right). \tag{21}$$

Because $\mathbb{E}_\theta[Q_\theta(s,a)] \neq \mathbb{E}_\theta[Q_\theta(s',a')]$, by linearity in w we have that $\tilde{\phi}(s,a) - \tilde{\phi}(s',a')$ is non-zero for any (s',a') and hence Eq. 21 has no trivial solutions. Proceeding as in the proof of Lemma 2 obtains $\mu = \tilde{\Phi}\mathbb{E}_w[w]$, where $\tilde{\Phi}$ is analogously defined. Note that if $N > n$ there is no solution $\mathbb{E}_w[w]$ for *any* admissible (full-rank) choice of $\tilde{\Phi}$, and hence the conclusion follows for the first part. For the second part, using that $\mathbb{E}_\theta = \mathbb{E}_w\mathbb{E}_\vartheta$ in Eq. 19 yields

$$0 = \sum_{i=1}^{n}\sum_{j=1}^{n} \mathbb{E}_w[\tilde{w}_i\tilde{w}_j]\,\mathbb{E}_\vartheta\left[d_i^- d_j^+\right] = \sum_{i=1}^{n}\sum_{j=1}^{n} \text{Cov}\,(w_i,w_j)\,\mathbb{E}_\vartheta\left[d_i^- d_j^+\right]. \tag{22}$$

Perform a change of variables $\tilde{\lambda}_{\alpha(i,j)} = \mathbb{E}_\vartheta\left[d_i^- d_j^+\right]$. Again, by $\mathbb{E}_\theta[Q_\theta(s,a)] \neq \mathbb{E}_\theta[Q_\theta(s',a')]$ we have that $\tilde{\lambda}$ is non-zero; proceed as before to complete to proof. ∎

We are now ready to prove our main result. We restate it here for convenience:

Proposition 1. *If the number of state-action pairs where $\mathbb{E}_\theta[Q_\theta(s,a)] \neq \mathbb{E}_\theta[Q_\theta(s',a')]$ is greater than n, where $w \in \mathbb{R}^n$, then $\mathbb{E}_\theta[Q_\theta]$ and $\mathbb{V}_\theta[Q_\theta]$ are biased estimators of $\mathbb{E}_M\left[Q_\pi^M\right]$ and $\mathbb{V}_M\left[Q_\pi^M\right]$ for any choice of $p(M)$.*

Proof. Let $p(\theta)$ be of the form $p(\theta) = p(w)$ or $p(\theta) = p(w)p(\vartheta)$. By Lemmas 2 and 3, $p(\theta)$ fail to satisfy Eq. 2. By Lemma 1, this causes $\mathbb{E}_\theta[Q_\theta]$ to be a biased estimator of $\mathbb{E}_M\left[Q_\pi^M\right]$. This in turn implies that $\mathbb{V}_\theta[Q_\theta]$ is a biased estimator of $\mathbb{V}_M\left[Q_\pi^M\right]$. Further, if $N > n^2$, $\mathbb{V}_\theta[Q_\theta]$ is biased independently of $\mathbb{E}_\theta[Q_\theta]$. ∎

Figure 4: Overall performance scores on Bsuite. *Left:* Effect of varying β. *Right:* comparison of TDU to exploration under $\sigma = \sigma(\mathcal{Q})$ as intrinsic reward (QU) or as an immediate bonus (Q+UCB).

C BEHAVIOUR SUITE

From Osband et al. (2020): "The Behaviour Suite for Reinforcement Learning (Bsuite) is a collection of carefully-designed experiments that investigate core capabilities of a reinforcement learning agent . The aim of the Bsuite project is to collect clear, informative and scalable problems that capture key issues in the design of efficient and general learning algorithms and study agent behaviour through their performance on these shared benchmarks."

C.1 AGENTS AND HYPER-PARAMETERS

All baselines use the default Bsuite DQN implementation[2]. We use the default architecture and hyper-parameters from the published baseline, reported in Table 1, and sweep over algorithm-specific hyper-parameters, reported in Table 2. The agent is composed of a two-layer MLP with RELU activations that approximate $Q(s, a)$ and is trained using experience replay. In the case of the bootstrapped DQN, all ensemble members learn from a shared replay buffer with bootstrapped data sampling, where each member Q_{θ^k} is a separate MLP (no parameter sharing) that is regressed towards separate target networks. We use Adam (Kingma & Ba, 2015) and update target networks periodically (Table 1).

Table 1: Hyper-parameters for Bsuite.

discount factor (γ)	0.99
batch size	32
num hidden layers	2
hidden layer sizes	[64, 64]
ensemble size	20
learning rate	0.001
mask prob	1.0
replay size	10000
env steps per gradient step	1
env steps per target update	4

QEX Uses two networks Q_θ and Q_ϑ, where Q_θ is trained to maximise the extrinsic reward, while Q_ϑ is trained to maximise the absolute TD-error of Q_θ (Simmons-Edler et al., 2019). In contrast to TDU, the intrinsic reward is given as a point estimate of the TD-error for a given transition, and thus cannot be interpreted as measuring uncertainty as such.

CTS Implements a count-based reward defined by $i(s, a, \mathcal{H}) = (N(s, a, \mathcal{H}) + 0.01)^{-1/2}$, where $\mathcal{H}$ is the history and $N(s, a, \mathcal{H}) = \sum_{\tau \in \mathcal{H}} \mathbf{1}_{(s,a) \in \tau}$ is the number of times (s, a) has appeared in a transition $\tau := (s, a, r, s')$. This intrinsic reward is added to the extrinsic reward to form an augmented reward $\tilde{r} = r + \beta i$ used to train a DQN agent (Bellemare et al., 2016a).

RND Uses two auxiliary networks f_ϑ and $f_{\tilde{\vartheta}}$ that map a state into vectors $x = f_\vartheta(s)$ and $\tilde{x} = f_{\tilde{\vartheta}}(s)$, $x, \tilde{x} \in \mathbb{R}^m$. While $\tilde{\vartheta}$ is a random parameter vector that is fixed throughout, ϑ is trained to minimise the mean squared error $i(s) = \|x - \tilde{x}\|$. This error is simultaneously used as an intrinsic reward in the augmented reward function $\tilde{r}(s, a) = r(s, a) + \beta i(s)$ and is used to train a DQN agent. Following

---

[2]https://github.com/deepmind/bsuite/tree/master/bsuite/baselines/jax/dqn.

Table 2: Hyper-parameter grid searches for Bsuite. Best values in bold.

Algorithm	Hyper-parameter	Sweep set
Q-Explore	Intrinsic reward scale (β)	$\{10^{-4}, 10^{-3}, 10^{-2}, 10^{-1}, 10^0, 5 \cdot 10^0, \mathbf{10^1}, 10^2, 10^3\}$
CTS	Intrinsic reward scale (β)	$\{10^{-4}, 10^{-3}, 10^{-2}, \mathbf{10^{-1}}, 5 \cdot 10^0, 10^0, 10^1, 10^2, 10^3\}$
RND	Intrinsic reward scale (β)	$\{10^{-2}, 5 \cdot 10^{-1}, 10^{-1}, 10^0, 5 \times 10^0, \mathbf{10^1}, 10^2\}$
	x-dim (m)	$\{\mathbf{10}, 64, 128\}$
	Moving average decay (α)	$\{0.9, 0.99, \mathbf{0.999}\}$
	Normalise intrinsic reward	$\{\mathbf{True}, False\}$
BDQN	Prior scale (λ)	$\{0, 1, \mathbf{3}, 5, 10, 50, 100\}$
SU	Hidden size	$\{20, \mathbf{64}\}$
	Likelihood variance (β)	$\{10^{-2}, 10^{-1}, 10^0, \mathbf{10^1}, 10^2\}$
	Prior variance (θ)	$\{\mathbf{10^{-3}}, 10^{-1}, 10^0, 10^1, 10^3\}$
NNS	Noise scale (β)	$\{10^{-2}, 10^{-1}, 10^0, \mathbf{10^1}, 10^2\}$
TDU	Prior scale (λ)	$\{0, 10^0, \mathbf{3 \cdot 10^0}\}$
	Intrinsic reward scale (β)	$\{10^{-3}, 10^{-2}, 10^{-1}, \mathbf{10^0}, 5 \cdot 10^0, 10^1\}$

Burda et al. (2018b), we normalise intrinsic rewards by an exponential moving average of the mean and the standard deviation that are being updated with batch statistics (with decay α).

BDQN   Trains an ensemble $\mathcal{Q} = \{Q_{\theta^k}\}_{k=1}^K$ of DQNs (Osband et al., 2016a). At the start of each episode, one DQN is randomly chosen from which a greedy policy is derived. Data collected is placed in a shared replay memory, and all ensemble members have some probability ρ of training on any transition in the replay. Each ensemble member has its own target network. In addition, each DQN is augmented with a random prior function f_ϑ, where $\tilde{\vartheta}$ is a fixed parameter vector that is randomly sampled at the start of training. Each DQN is defined by $Q_{\theta^k} + \lambda f_{\vartheta^k}$, where λ is a hyper-parameter regulating the scale of the prior. Note that the target network uses a distinct prior function.

SU   Decomposes the DQN as $Q_\theta(s, a) = w^T \psi_\vartheta(s, a)$. The parameters ϑ are trained to satisfy the Success Feature identity while w is learned using Bayesian linear regression; at the start of each episode, a new w is sampled from the posterior $p(w \mid \text{history})$ (Janz et al., 2019).[3]

NNS   NoisyNets replace feed-forward layers $Wx + b$ by a noisy equivalent $(W + \Sigma \odot \epsilon^W)x + (b + \sigma \odot \epsilon^b)$, where $\odot$ is element-wise multiplication; $\epsilon_{ij}^W \sim \mathcal{N}(0, \beta)$ and $\epsilon_i^b \sim \mathcal{N}(0, \beta)$ are white noise of the same size as W and b, respectively. The set (W, Σ, b, σ) are learnable parameters that are trained on the normal TD-error, but with the noise vector re-sampled after every optimisation step. Following Fortunato et al. (2018), sample noise separately for the target and the online network.

TDU   We fix the number of explorers to 10 (half of the number of value functions in the ensemble), which roughly corresponds to randomly sampling between a reward-maximising policy and an exploration policy. Our experiments can be replicated by running the `TDU` agent implemented in Algorithm 5 in the Bsuite GitHub repository.[4]

C.2   TDU Experiments

Effect of TDU   Our main experiment sweeps over β to study the effect of increasing the TDU exploration bonus, with $\beta \in \{0, 0.01, 0.1, 0.5, 1, 2, 3, 5\}$; $\beta = 0$ corresponds to default bootstrapped DQN. We find that β reflects the exploitation-exploration trade-off: increasing β leads to better performance on exploration tasks (see main paper) but typically leads to worse performance on

---

[3]See https://github.com/DavidJanz/successor_uncertainties_tabular.
[4]https://github.com/deepmind/bsuite/blob/master/bsuite/baselines/jax.

tasks that do not require further exploration beyond ϵ-greedy (Figure 4). In particular, we find that $\beta > 0$ prevents the agent from learning on Mountain Car, but otherwise retains performance on non-exploration tasks. Figure 5 provides an in-depth comparison per game.

Because σ is a principled measure of concentration in the distribution $p(\delta \mid s, a, r, s')$, β can be interpreted as specifying how much of the tail of the distribution the agent should care about. The higher we set β, the greater the agent's sensitivity to the tail-end of its uncertainty estimate. Thus, there is no reason in general to believe that a single β should fit all environments, and recent advances in multi-policy learning (Schaul et al., 2019; Zahavy et al., 2020; Puigdomènech Badia et al., 2020) suggests that a promising avenue for further research is to incorporate mechanisms that allow either β to dynamically adapt or the sampling probability over policies. To provide concrete evidence to that effect, we conduct an ablation study that uses bandit policy sampling below.

Effect of prior functions We study the inter-relationship between additive prior functions (Osband et al., 2019) and TDU. We sweep over $\lambda \in [0, 1, 3]$, where prior functions define value function estimates by $Q^k = Q_{\theta^k} + \lambda P^k$ for some random network P^k. Thus, $\lambda = 0$ implies no prior function. We find a general synergistic relationship; increasing λ improves performance (both with and without TDU), and for a given level of λ, performance on exploration tasks improve for any $\beta > 0$. It should be noted that these effects do no materialise as clearly in our Atari settings, where we find no conclusive evidence to support $\lambda > 0$ under TDU.

Ablation: exploration under non-TD signals To empirically support theoretical underpinnings of TDU, we conduct an ablation study where σ is re-defined as the standard deviation over value estimates:

$$\sigma(\mathcal{Q}) := \sqrt{\frac{1}{K-1} \sum_{k=1}^{K} Q^k - \bar{Q}}. \tag{23}$$

In contrast to TDU, this signal does not condition on the future and consequently is a biased estimate of epistemic uncertainty. We apply this signal both as in intrinsic reward (QU), as in TDU, and as an UCB-style exploration bonus (Q+UCB), where σ is instead applied while acting by defining a policy by $\pi(\cdot) = \arg\max_a Q(\cdot, a) + \beta\sigma(\mathcal{Q}; \cdot, a)$. Note that TDU cannot be applied in this way because the TDU exploration signal depends on r and s'. We tune each baseline over the same set of β values as above (incidentally, these coincide to $\beta = 1$) and report best results in Figure 4. We find that either alternative is strictly worse than TDU. They suffer a significant drop in performance on exploration tasks, but are also less able to handle noise and reward scaling. These findings are in line with theory, as noise makes bias more likely in uncertainty estimates over $\mathcal{Q}$. Moreover, biased uncertainty estimates will negatively impact the agent's ability to explore.

Ablation: bandit policy sampling Our main results indicate, unsurprisingly, that different environments require different emphasis on exploration. To test this more concretely, in this experiment we replace uniform policy sampling with the UCB1 bandit algorithm. However, in contrast to that example, where UCB1 is used to take actions, here it is used to select a policy for the next episode. We treat each $N + K$ value function as an "arm" and estimate its mean reward $V^k \approx \mathbb{E}_{\pi^k}[r]$, where the expectation is with respect to rewards r collected under policy $\pi^k(\cdot) = \arg\max_a Q^k(\cdot, a)$. The mean reward is estimated as the running average

$$V^k(n) = \frac{1}{n(k)} \sum_{i=1}^{n(k)} r_i, \tag{24}$$

where $n(k)$ is the number of environment steps for which policy π^k has been used and r_i are the observed rewards under policy π^k. Prior to an episode, we choose a policy to act under according to: $\arg\max_{k=1,\dots,N+K} V^k(n) + \eta\sqrt{\log n / n(k)}$, where n is the total number of environment steps taken so far and η is a hyper-parameter that we tune. As in the bandit example, this sampling strategy biases selection towards policies that currently collect higher reward, but balances sampling by a count-based exploration bonus that encourages the agent to eventually try all policies. This bandit mechanism is very simple as our purpose is to test whether some form of adaptive sampling can provide benefits; more sophisticated methods (e.g. Schaul et al., 2019) can yield further gains.

Figure 5: Bsuite per-task results. Results reported for different values of β with prior $\lambda = 3$. We also report results under UCB1 policy sampling ("bandit") for $\beta = 1, \lambda = 3, \eta = 8$.

We report full results in Figure 5; we use $\beta = 1$ and tune $\eta \in \{0.1, 1, 2, 4, 6, 8\}$. We report results for the hyper-parameter that performed best overall, $\eta = 8$, though differences with $\eta > 4$ are marginal. While TDU does not impact performance negatively in general, in the one case where it does—Mountain Car—introducing a bandit to adapt exploration can largely recover performance. The bandit yields further gains in dense reward settings, such as in Cartpole and Catch, with an outlying exception in the bandit setting with scaled rewards.

D ATARI WITH R2D2

D.1 BOOTSTRAPPED R2D2

We augment the R2D2 agent with an ensemble of dueling action-value heads Q_i. The behavior policy followed by the actors is an ϵ-greedy policy as before, but where the greedy action is determined according to a single Q_i for a fixed length of time (100 actor steps in all of our experiments), before sampling a new Q_i uniformly at random. The evaluation policy is also ϵ-greedy with $\epsilon = 0.001$, where the Q-values are averaged only over the exploiter heads.

Each trajectory inserted into the replay buffer is associated with a binary mask indicating which Q_i will be trained from this data, ensuring that the same mask is used every time the trajectory is sampled. Priorities are computed as in R2D2, except that TD-errors are now averaged over all heads.

Instead of using reward clipping, R2D2 estimates a transformed version of the state-action value function to make it easier to approximate for a neural network. One can define a transformed Bellman operator given any squashing function $h : \mathbb{R} \to \mathbb{R}$ that is monotonically increasing and invertible. We use the function $h : \mathbb{R} \mapsto \mathbb{R}$ defined by

$$h(z) = \text{sign}(z)(\sqrt{|z| + 1} - 1) + \epsilon z, \tag{25}$$

$$h^{-1}(z) = \text{sign}(z)\left(\left(\frac{\sqrt{1 + 4\epsilon(|z| + 1 + \epsilon)} - 1}{2\epsilon}\right) - 1\right), \tag{26}$$

for ϵ small. In order to compute the TD errors accurately we need to account for the transformation,

$$\delta(\theta, s, a, r, s') := \gamma h^{-1}(Q_\theta(s', \pi(s'))) + r - h^{-1}(Q_\theta(s, a)). \tag{27}$$

Similarly, at evaluation time we need to apply h^{-1} to the output of each head before averaging.

When making use of a prior we use the form $Q^k = Q_\theta^k + \lambda P^k$, where P^k utilizes the same general architecture as the Q_θ^k network, but with the widths of all layers cut in half in order to improve computational efficiency. Finally, instead of n-step returns we utilize Peng's $Q(\lambda)$ as was done in (Value-driven Hindsight Modelling: citation needed). In all variants we used the hyper-parameters listed in Table 3.

D.2 PRE-PROCESSING

We used the standard pre-process of the frames received from the Arcade Learning Environment.[5] See Table 4 for details.

D.3 HYPER PARAMETER SELECTION

In the distributed setting we have three TDU-specific hyper-parameters to tune namely: β, N and the prior weight λ. We ran a set of shorter experiments (collecting 5 billion environment steps) using a subset of 8 games: `frostbite`,`gravitar`, `hero`, `montezuma_revenge`, `ms_pacman`, `seaquest`, `space_invaders`, `venture`. We ran three seeds for each setting. This subset presents quite a bit of diversity including dense-reward games as well as three hard exploration games: `gravitar`, `montezuma_revenge` and `venture`. To minimise the computational

Table 4: Atari pre-processing hyperparameters.

Max episode length	30 min
Num. action repeats	4
Num. stacked frames	4
Zero discount on life loss	$false$
Random noops range	30
Sticky actions	$false$
Frames max pooled	3 and 4
Grayscaled/RGB	Grayscaled
Action set	Full

cost, we started by setting λ and N while maintaining $\beta = 1$. We employed a coarse grid of $\lambda \in \{0., 0.05, 0.1\}$ and $N \in \{2, 3, 5\}$. Figure 6 summarises the results in terms of the mean Human Normalised Scores (HNS) across the set. We see that the performance depends on the type of games being evaluated. Specifically, hard exploration games achieve a significantly lower score. Performance does not significantly change with the number of explorers. The largest differences are observed for the exploration games when $N = 5$. We selected the best performing sets of hyper parameters for both, with and without the use of additive priors. We chose to use $(N = 2, \lambda = 0.1)$ and $(N = 5, \lambda = 0.)$ to run the main results reported in Section 5.2.

We evaluate the influence of the exploration bonus strength by fixing $(N = 5, \lambda = 0.)$ and choosing $\beta \in \{0.1, 1., 2.\}$. Figure 7 summarises the results. The set of dense rewards is composed of the games in the ablation set that are not considered hard exploration games. We observe that larger values of β help on exploration but affect performance on dense reward games. We plot jointly the performance in mean HNS acting when averaging the Q-values for both, the exploiter heads (solid lines) and the explorer heads (dotted lines). We can see that higher strengths for the exploration bonus (higher β) renders the explorers "uninterested" in the extrinsic rewards, preventing them

---

[5]Publicly available at https://github.com/mgbellemare/Arcade-Learning-Environment.

Figure 6: Ablation for prior scale, λ and the number of explorers, N, on the distributed setting. We fix $\beta = 1$. Refer to the text for details on the ablation and exploration set of games.

Figure 7: Ablation for the exploration bonus strength, β, on the distributed setting. We fix ($N = 5, \lambda = 0$.). We report the mean HNS for the ensemble of exploiter (solid lines) and the ensemble of explorers (dotted lines). All runs are average over three seeds per game. Refer to the text for details on ablation and exploration set of games.

to converge to exploitative behaviours. This effect is less strong for the hard exploration games. Figure 8 we show how this effect manifests itself on the performance on three games: gravitar, space_invaders, and hero. This finding also applies to the evaluation performed on our evaluation using all 57 games in the Atari suite, as shown below. We conjecture that controlling for the strength of the exploration bonus on a per game manner would significantly improve the results. This finding is in line with observations made by (Puigdomènech Badia et al., 2020); combining TDU with adaptive policy sampling (Schaul et al., 2019) or online hyper-parameter tuning (Xu et al., 2018; Zahavy et al., 2020) are exciting avenues for future research.

Figure 8: Ablation for the exploration bonus strength, β, on the distributed setting. We fix ($N = 5, \lambda = 0.$). We report the score on three different games for the ensemble of exploiter (solid lines) and the ensemble of explorers (dotted lines). All runs are average over three seeds per game.

D.4 HARD EXPLORATION GAMES

In this section we provide more details regarding the results presented in Figure 4 of Section 5.2 of the main text. We concentrated our attention on the subset of games that are well-known to pose challenging exploration problems (Machado et al., 2018): `montezuma_revenge`, `pitfall`, `private_eye`, `solaris`, `venture`, `gravitar`, and `tennis`. Figure 9 shows the performance for each game. We can see that TDU always performs on par or better than each of the baselines, leading to significant improvments in data efficiency and final score in games such as `montezuma_revenge`, `gravitar`, and `tennis`. In the case of `gravitar`, the baseline R2D2 can eventually match the end performance (as reported in the original paper) but it requires significantly more interactions with the environment.

In our experiments we only included comparisons with respect to our base agent (R2D2) and it's bootstrapped version. The main reason behind our choice was that these comparisons are very meaningful: we used the same amount of training data, infrastructure and architecture in all cases. The only differences between these methods is due to the algorithmic choices. In Table 5, we compare TDU to recently proposed state-of-the-art exploration methods. While comparisons must be made with care due to different training regimes, computational budgets, and architectures, we note a general trend that no method is uniformly superior. Further, methods that are good on extremely sparse exploration games, such as Montezuma's Revenge and Pitfall!, tend to do poorly on dense rewards, and vice versa. TDU is generally performant, being among the top 2 algorithms all cases but on Montezuma's Revenge and Pitfall!, where some form of state-based exploration is needed to achieve sufficient coverage of the MDP. In particular, we note that TDU generally outperforms both Pixel-CNN (Ostrovski et al., 2017), CTS (Bellemare et al., 2016b), and RND (except on Montezuma's Revenge Burda et al., 2018b). It is on par with state-of-the-art agent NGU (Puigdomènech Badia et al., 2020) in all cases except Montezuma's Revenge and Pitfall!, and even outperforms it on three out of six games considered, while being a considerably simpler algorithm.

D.5 FULL ATARI SUITE

In this section we report the performance on all 57 games of the Atari suite. In addition to the two configurations used to obtain the results presented in the main text (reported in Section 5.2), in this section we included a variant of each of them with lower exploration bonus strength of $\lambda = 0.1$. In all figures we refer to these variants by adding an L (for lower λ) at the end of the name, e.g. TDU-R2D2-L. In Figure 10 we report a summary of the results in terms of mean HNS and meadian HNS for the suite as well as mean HNS restricted to the hard exploration games only. We show the performance on each game in Figure 11. Reducing the value of β significantly improves the mean HNS without strongly degrading the performance on the games that are challenging from an exploration standpoint. The difference in performance in terms of mean HNS can be explained by looking at a few high scoring games, for instance: `assault`, `asterix`, `demon_attack` and

gopher (see Figure 11). We can see that incorporating priors to TDU is not crucial for achieving high performance in the distributed setting.

Figure 9: Performance on each hard exploration game and for of the different algorithms compared in Figure 4 of the main text.

Figure 10: Performance over the 57 atari games. We reprt mean and median HNS over the full suite, and mean HNS over the exploration games.

Figure 11: Results for each individual game.

Table 3: R2D2 hyperparameters.

Ensemble size	10
Optimizer	Adam (Kingma & Ba, 2015)
Learning rate	0.0002
Adam epsilon	0.001
Adam beta1	0.9
Adam beta2	0.999
Adam global clip norm	40
Discount	0.997
Batch size	64
Trace length	80
Replay period	40
Burn in length	20
λ for RL loss	0.97
R2D2 reward transformation	$\text{sign}(x) \cdot (\sqrt{|x| + 1} - 1) + 0.001 \cdot x$
Replay capacity (num of sequences)	$1e5$
Replay priority exponent	0.9
Importance sampling exponent	0.6
Minimum sequences to start replay	5000
Actor update period	100
Target Q-network update period	400
Evaluation ϵ	0.001

Table 5: Results comparison with exploration algorithm baselines.[†]Ostrovski et al. (2017), [‡]Bellemare et al. (2016b), [◇]Burda et al. (2018b), [⋆]Choi et al. (2018), [⊙]Puigdomènech Badia et al. (2020).

Algorithm	Gravitar	Montezuma's Revenge	Pitfall!	Private Eye	Solaris	Venture
Avg. Human	3,351	4,753	6,464	69,571	12,327	1,188
R2D2	15,680	2,061	0.0	5,322.7	3,787.2	1,970.7
DQN + PixelCNN[†]	859.1	2,514	0.0	15,806.5	5,501.5	1,356.3
DQN + CTS[‡]	498.3	3,706	0.0	8,358.7	82.2	
RND[◇]	3,906	10,070	-3	8,666	3,282	1,859
CoEx[⋆]	-	11,618	-	11,000	-	1,916
NGU[⊙]	14,100	10,400	8,400	100,000	4,900	1,700
TDU-R2D2	13,000	5,233	0	40,544	14,712	2,000
TDU-R2D2-PRIOR	10,916	2,833	0	61,168	15,230	1,977