Automatic renal perfusion estimation on postoperative PCASL MRI based on deep learning image analysis and segmentation

Abstract

Non-invasive arterial spin labeling is an MRI technique that can be used for kidney transplant evaluation and perfusion estimation. This work proposes an automatic workflow for renal segmentation and perfusion estimation, based on deep learning approach and image analysis. Similarity coefficients above 90% are achieved for kidney, cortex, and medulla segmentation results and perfusion values within the acceptable ranges are obtained.

Keywords: Renal perfusion, PCASL MRI, segmentation.

1. Introduction

Renal transplant is the treatment of choice in patients suffering from chronic kidney disease, characterized by a progressive and irreversible loss of kidney function (Jiang and Lerman, 2019). Renal blood flow (RBF) has a great value for clinicians as it enables the identification of perfusion impairment as an emerging biomarker of transplanted renal dysfunction. The overall RBF is determined by the vasoconstriction of renal arterial tree and changes in the intrarenal vascular resistance (Field et al., 2010). Pseudo-continuous arterial spin labeling (PCASL) is a non-invasive MRI technique that allows the characterization of RBF using magnetically labelled arterial blood water spins as endogenous tracer with a combination of a train of radiofrequency pulses and slice-selective gradients (Nery et al., 2018). It is considered an appropriate imaging technique for patients with renal dysfunction for whom the administration of contrast agents could be contraindicated (Odudu et al., 2018). RBF estimation derived from PCASL entails extra segmentation work, which is tedious and prone to error. To date, the applications of machine and deep learning models in renal MRI are scarce compared to those found for computerized tomography (CT) (Zhang et al., 2020) and contrasted MRI (Klepaczko et al., 2021). We propose a fully-automated pipeline that; first performs a preliminary whole kidney segmentation by Mask R-CNN; secondly classifies the pixels within the kidney region into cortex and medulla classes; and finally estimates RBF for quantitative assessment (see Figure 1).

2. Experimental setup and results

The dataset used consists of PCASL and T_1-weighted (w) images from 16 transplanted patients with the following readout: acquisition matrix, 96 x 96; number of slices, 3; and slice orientation, coronal oblique or coronal-sagittal. Each dataset contains a M_0 reference image, 25 control and labels PCASL pairs, and 14 T_1-w images. Binary masks encompassing the kidney, the cortex, and the medulla are used in the training and testing steps. Data augmentation and intensity normalization is used in the training process.

Figure 1: Automatic renal perfusion estimation pipeline.

SEGMENTATION OF THE KIDNEY

We implement the Mask R-CNN for the segmentation of the kidney on PCASL images. It consists of a two stage (Feature Pyramid Network (FPN) and a ResNet101 backbone) convolutional neural network (CNN) that generates bounding boxes and segmentation masks for each instance of an object in the image (He et al., 2018). The model is trained for 150 epochs, using supervised gradient descent optimizer, learning rate of 10^{-4}, and pre-trained weights for MS COCO (Abdulla, 2017). We use Python 3.8 and Tensorflow on GPU NVIDIA GeForce RTX 3090. Training takes $\approx$ 120 min. We compare the performance of the Mask R-CNN against the U-Net (Ronneberger et al., 2015) and Supervised Descent Method (Xiong and De la Torre, 2013). The method proposed achieves a Dice similarity coefficient (DSC) score (mean $\pm$ standard deviation, SD) of 93.90 $\pm$ 2.00, whereas the U-Net and SDM achieve DSC values of 87.87 $\pm$ 1.30 and 84.40 $\pm$ 11.89, respectively.

SEGMENTATION OF RENAL COMPARTMENTS

The multiclass segmentation method proposed is based on temporal information thresholding of T_1-w images. Based on ground truth (GT) cortex and medulla annotations, we construct time-intensity curves for each tissue along the inversion times (TI) and analyse the temporal distribution of the null points for each pixel. We note that cortical tissue attains its null point before the medulla does. Pixels within kidney masks resulted from Mask R-CNN are classified as cortex if its null point is found at $5 \leq k \leq 8$ TIs and as medulla if found at $10 \leq k \leq 13$. Unclassified pixels are designated the uncertain class. In a second stage, pixels are reclassified according to GT T_1 values. Instance segmentation is evaluated using a set of standard metrics: DSC, precision (PC), recall (RC), and F-measure (FM) with β value of 2. In order to counteract the class imbalance between cortex and medulla, metrics are weighted according to the number of pixels for each class. Thus, attained RC is 89.66 $\pm$ 9.99%, PC is 91.85 $\pm$ 4.89%, FM is 89.47 $\pm$ 10.61% and DSC is 89.70 $\pm$ 10.23%.

RBF ESTIMATION

Mean cortical and medullary signals are calculated over respective tissues of subtracted control and label pairs. RBF maps are computed using the single compartment model (Nery et al., 2020). For evaluation purposes, the relative error (%) between GT and estimated cortical and medullary perfusion values are calculated. Figure 2 contains scatter plots of pairwise comparisons between predicted and GT perfusion values. All comparisons show

positive association, as the GT perfusion values increases, so does the predicted values. Lower correlation coefficient (r) is shown for medullary perfusion values. Obtained cortical perfusion values for proposed and GT values are: 153 ± 87 mL/min/100 g and 162 ± 70 mL/min/100 g, respectively; and medullary perfusion values of 69 ± 74 mL/min/100 g, and 67 ± 62 mL/min/100 g, respectively. Moreover, the cortical perfusion value discrepancy is 6.78% and the medullary discrepancy is 18.31%.

Figure 2: Scatter plot of pairwise comparison between perfusion values (median ± SD) of GT and the method proposed, for cortex and medulla.

3. Discussion

The approach proposed leads to a reliable renal perfusion estimation. Segmentation results based on Mask R-CNN presents outstanding results, obtaining averaged DSC values above 93%, outperforming the current state-of-the-art. The segmentation performance highly depends on the intensity range of the images. Even if intensity rescale is applied, the heterogeneity of image intensity should be considered when testing with new data. As expected, the results obtained for the cortex are better than the ones extracted for the medulla compartment. The segmentation performance of medullary tissue shows higher dissimilarities between manually drawn labels and automatically achieved ones. This discrepancy is mainly caused by the mislabelling or under-segmentation of the medulla region, which tends to be less precise than the segmentation of the cortex due to the low-contrasted interface between the tissues and the partial volume effects in MRI images. The method proposed also generates an uncertain class mask in areas where the differentiation between cortex and medulla pixels is not clear, that could be processed in further steps to complete cortical and medullary masks, and indeed, the estimation of perfusion values. Regarding the estimation of renal perfusion, our work demonstrates that multiclass segmentations do have an effect on cortical and medullary RBF estimation.

Acknowledgments

Acknowledgments withheld.

References

Waleed Abdulla. Mask r-cnn for object detection and instance segmentation on keras and tensorflow. https://github.com/matterport/Mask_RCNN, 2017.

Michael J. Field, David C. Harris, and Carol A. Pollock. Glomerular Filtration and Acute Kidney Injury. In Michael J. Field, David C. Harris, and Carol A. Pollock, editors, *The Renal System (Second Edition)*, pages 57–67. Churchill Livingstone, January 2010. ISBN 978-0-7020-3371-1. doi: 10.1016/B978-0-7020-3371-1.00005-1.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask R-CNN, January 2018.

Kai Jiang and Lilach O. Lerman. Prediction of Chronic Kidney Disease Progression by Magnetic Resonance Imaging: Where Are We? *American journal of nephrology*, 49(2): 111–113, 2019. ISSN 0250-8095. doi: 10.1159/000496160.

Artur Klepaczko, Eli Eikefjord, and Arvid Lundervold. Healthy Kidney Segmentation in the Dce-Mr Images Using a Convolutional Neural Network and Temporal Signal Characteristics. *Sensors (Basel, Switzerland)*, 21(20):6714, October 2021. ISSN 1424-8220. doi: 10.3390/s21206714.

Fabio Nery, Isky Gordon, and David L. Thomas. Non-Invasive Renal Perfusion Imaging Using Arterial Spin Labeling MRI: Challenges and Opportunities. *Diagnostics*, 8(1):2, March 2018. ISSN 2075-4418. doi: 10.3390/diagnostics8010002.

Fabio Nery, Charlotte E. Buchanan, Anita A. Harteveld, Aghogho Odudu, Octavia Bane, Eleanor F. Cox, Katja Derlin, H. Michael Gach, Xavier Golay, Marcel Gutberlet, Christoffer Laustsen, Alexandra Ljimani, Ananth J. Madhuranthakam, Ivan Pedrosa, Pottumarthi V. Prasad, Philip M. Robson, Kanishka Sharma, Steven Sourbron, Manuel Taso, David L. Thomas, Danny J. J. Wang, Jeff L. Zhang, David C. Alsop, Sean B. Fain, Susan T. Francis, and María A. Fernández-Seara. Consensus-based technical recommendations for clinical translation of renal ASL MRI. *Magma (New York, N.Y.)*, 33 (1):141–161, February 2020. ISSN 1352-8661. doi: 10.1007/s10334-019-00800-z.

Aghogho Odudu, Fabio Nery, Anita A. Harteveld, Roger G. Evans, Douglas Pendse, Charlotte E. Buchanan, Susan T. Francis, and María A. Fernández-Seara. Arterial spin labelling MRI to measure renal perfusion: A systematic review and statement paper. *Nephrology, Dialysis, Transplantation: Official Publication of the European Dialysis and Transplant Association - European Renal Association*, 33(suppl_2):ii15–ii21, September 2018. ISSN 1460-2385. doi: 10.1093/ndt/gfy180.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-Net: Convolutional Networks for Biomedical Image Segmentation, May 2015.

Xuehan Xiong and Fernando De la Torre. Supervised Descent Method and Its Applications to Face Alignment. In *2013 IEEE Conference on Computer Vision and Pattern Recognition*, pages 532–539, Portland, OR, USA, June 2013. IEEE. ISBN 978-0-7695-4989-7. doi: 10.1109/CVPR.2013.75.

Yao Zhang, Yixin Wang, Feng Hou, Jiawei Yang, Guangwei Xiong, Jiang Tian, and Cheng Zhong. Cascaded Volumetric Convolutional Network for Kidney Tumor Segmentation from CT volumes, May 2020.