# The Scaling Laws of Classification Networks: Insights from Adaptive Exact Average Density Approximation

## Abstract

Our main goal is to establish a theoretical foundation for the scaling laws that aligns with the empirical scaling laws observed in deep neural networks (DNNs). Under the assumption that the boundary of the target classification function is a semi-algebraic set, we show that the generalization error bound follows scaling laws for large networks. The rate of scaling with respect to sample size is intrinsically linked to the effective dimension of the data manifold, independent of the specific network model or learning algorithm. The scaling law with respect to the number of parameters, however, varies across learning methods and architectures — a variability captured by the *box-model dimension*, which measures how the number of model parameters grows as the radius of covering balls decreases. As a secondary contribution, we show that modular network architectures exhibit a discrete scale-invariance property that enables the prediction of generalization error for larger models from smaller ones, and we empirically demonstrate this on ResNet, VGG, and Inception models trained on ImageNet, CIFAR-100, and Udacity.

## 1 Introduction

Scaling laws in deep neural networks (DNNs) indicate that, across a wide range of architectures and tasks, the generalization error is primarily driven by scale. The generalization error typically decreases according to predictable power-law relationships associated with variables such as the number of parameters, the amount of training data, and the computational resources used for training. This observation suggests that larger models, trained on larger datasets, generally perform better in a smooth, quantifiable manner when properly optimized and regularized during training. Such regularities have been instrumental in guiding the design of large-scale models, such as GPT and PaLM, which use scaling curves to forecast performance before full-scale training.

Our main goal is to provide a theoretical explanation of scaling laws, with a secondary goal of identifying conditions under which a scaling law manifests itself as a smooth, predictable curve. To this end, we study the geometry of the partition regions of a classification function induced by dense samples, emphasizing that increasing the depth of DNNs enhances their ability to capture finer local structures and thereby reduces generalization error. The analysis rests on two key conditions: first, sample points must densely cover the input domain, ensuring each decision region contains at least one training point; second, the histogram over decision regions must accurately represent the average density within those regions. Together, these allow us to express generalization error in terms of the smallest enclosing ball radius, and to demonstrate a scaling law showing that greater network depth and larger sample size reduce this radius.

Under these conditions, we establish the following theoretical results. First, we prove that the relationship between generalization error and sample size follows a scaling law, where the slope is inversely proportional to the intrinsic dimension of the data manifold — a result consistent with earlier studies by Cortes et al. (1993), Bahri et al. (2024), and Bisla et al. (2021). Second, we identify a scaling law relating generalization error to network size. To characterize the rate of this scaling law, we introduce the *box-model dimension* — a measure of how the parameter count of a model family grows as the box size decreases, capturing the shape

of a set across scales. We show that both network architecture and optimization method can significantly influence this dimension.

The prevailing view holds that scaling laws operate exclusively within the interpolating zone, where the training error is zero. We stress, however, that this is not the only source of such laws: they can also emerge when sample points densely cover the input domain, provided that the histogram over decision regions accurately approximates the underlying average density. We extend our analysis to the interpolating zone in Appendix I.

As a secondary and exploratory contribution, we show that large networks built from modular design blocks exhibit a discrete scale-invariance property, which manifests as a log-periodic pattern around a power-law trend in the log-log plot of generalization error against parameter count. This enables reliable prediction of generalization error for larger models. To illustrate this, we provide preliminary numerical results on ResNet, VGG, and Inception models trained on ImageNet, CIFAR-100, and Udacity. We also discuss the limitations of our theory and experiments.

Section 2 surveys prior work. Section 3 establishes the connection between generalization error and geometry via the covering radius. The first two subsections of Section 4 derive scaling laws in both sample size and model size; the third shows that the generalization error of a large modular-architecture model can be predicted from smaller models using published data. The final subsection discusses limitations, and Section 5 concludes with directions for future work.

## 2 Related works

Empirically, the generalization error of deep neural networks has been observed to follow a smooth power-law scaling of the form $aN^{-\alpha} + b$ with respect to dataset size $N$ (Hestness et al., 2017; Hutter, 2021), and analogous smooth power-law relationships have been identified with respect to model size and training steps (Rosenfeld et al., 2019; 2021; Xiong et al., 2024). Under the assumption that these scaling laws are smooth and continuous, recent work has further shown that they can be used to reliably predict generalization error for larger models from observations on smaller ones (Choshen et al., 2024; Li et al., 2025). Extensive empirical evidence by Caballero et al. (2022) demonstrates that scaling laws can be piecewise continuous and can be predicted using a broken neural scaling law.

Some analysis aims to explain the scaling laws theoretically. Sharma and Kaplan (2022) propose a model explaining scaling laws in terms of training set size $D$ and parameter count $P$. Bahri et al. (2024) analyzes generalization error with respect to $D$ and $P$ across two regimes: one where both can grow unboundedly, and one where one is held fixed. Bisla et al. (2021) derives a closed-form expression for generalization error by approximating local density as uniform within hypercubes, obtaining results consistent with empirical scaling laws. Park et al. (2025) further shows that benign overfitting can occur in the classical regime for large $D$.

From studying tractable shallow networks, it is possible to derive the factors governing the underlying dynamic behaviour at different scales. Bartlett et al. (2020) shows that effective generalization requires the number of "unimportant" parameter directions to significantly exceed the sample size. Cui et al. (2021) bounds the generalization error of kernel ridge regression, showing that eigenvalue decay governs learning rates. Maloney et al. (2022) analyzes a solvable one-hidden-layer model in the limit of large data and many parameters, deriving analytical formulas linking spectral properties of the data to power-law scaling of test loss, and explaining why scaling laws can eventually plateau.

## 3 Geometry, sample density, and generalization error

### 3.1 Assumptions and simplifications

We outline the simplifications needed to keep our analysis tractable. We focus on the unit $d$-ball $B_d(\mathbf{0}, 1)$ as the input domain, which can be readily adapted to any compact domain encountered in practice. Boundary effects are omitted due to compact support, yielding cleaner results. We also do not distinguish between the ambient dimension $d$ and the effective (intrinsic) dimension $d_e$, defined as the minimum number of

independent parameters needed to represent a density function without substantial loss of information Levina and Bickel (2004); Ansuini et al. (2019). Since $d_e \ll d$ in practice, replacing $d$ with $d_e$ yields substantially more favorable scaling and mitigates the curse of dimensionality. All results stated in terms of $d$ carry over to $d_e$ directly, and we use the two interchangeably where appropriate.

The generalization error measures the difference between the expected test error and the expected training error, while the generalization bound represents an upper bound of that error. Our analysis makes two assumptions about training data distribution.

**Assumption of densely covering**: We assume that the data is sufficiently densely distributed, allowing spheres centered at a selected subset to cover the input domain within a defined radius.

To access the density of training data in the input domain, we use the $\beta_l$-covering of the input domain, which means that for any $\mathbf{x}$ in the input domain, there is a training point $\mathbf{x}_i$ such as $\|\mathbf{x} - \mathbf{x}_i\|_2 \leq \beta_l$. The $\beta_l$-covering distribution in training points emphasizes that the input domain can be covered using balls with radius $\beta_l$, and each ball contains at least one training point.

The classification network $\mathcal{M}$ is responsible for learning the classifier function $f$ by utilizing $N$ training data pairs $(\mathbf{x}_i, f(\mathbf{x}_i))$. $\mathcal{M}$ is a piecewise constant function, dividing the input domain into non-overlapping decision regions and assigning each region a specific class.

**Assumption of histogram approximation**: We assume that sufficient training data are available for each decision region to allow an accurate approximation of the average probability mass within the region using a histogram over bins defined by the regions. Note that this assumption concerns the average density function within regions, not the actual density function.

### 3.2 Generalization bound for covering with fixed radius balls

To understand the local geometry of the input of a neural network's function, we use covering balls in the input domain, focusing on two parameters: $\gamma_s$, the radius of the smallest enclosing ball for a set of regions, and $\beta_l$, the radius of the largest inscribed ball within that set. These regions relate to the arrangement of training points in the decision areas in classification networks. In Figure 1(a), $\gamma_s$ is the radius of the ball encompassing both regions, while $\beta_l$ represents the largest inscribed ball.

Our study utilizes specified balls to analyze local geometry, linking this analysis to generalization error and sample complexity. We demonstrate that the parameter $\gamma_s$ effectively characterizes generalization errors. However, a higher sample density is essential to ensure that each decision region contains at least one training point. This necessary density is determined by the maximum radius of the balls, $\beta_l$, within the decision regions.

The lemma below shows that the sample density defined by $\beta_l$ ensures that each region formed by the classification network has at least one training point (proof in Appendix A).

**Lemma 1.** *Let $\beta_l$ be the radius of the largest inscribed balls in the finest decision regions of the one-hot classification network $\mathcal{M}$. If samples cover the input domain with a $\beta_l$-covering, then each region of $\mathcal{M}$ contains at least one training point.* ∎

The following lemma shows that, for sufficiently large networks, the generalization error in classification tasks exhibits a linear behavior with respect to $\gamma_s$. The analysis is applicable to classification networks that define piecewise-constant functions over the input domain, with at least one training point assigned to each decision region of a specific class.

Let $f$ be the target classification function. For generalization error, we use the volume of enclosing balls near the actual classification boundary, $\partial f$, based on the observation that when $\partial f$ intersects with the network's decision regions, potential errors arise. Specifically, points within $2\gamma_s$ of $\partial f$ are likely to belong to a region that could contribute to errors. This relationship emphasizes $\gamma_s$'s significance in determining the network's generalization error, as shown in Figure 1(b). In addition, to measure the volume of balls proximity to $\partial f$, denoted by $2\gamma_s$, we need to characterize the boundary over the input domain. Here, we assume $\partial f$ is a semi-algebraic set because a semi-algebraic set can realize an arbitrarily complicated shape.

(a)                                                      (b)

Figure 1: (a) Each polygon can be enclosed by a ball of radius $\gamma_s$ (blue) and inscribed in a ball of radius $\beta_l$ (red). (b) Polygons represent decision regions, each assigned a class. Any point $\mathbf{x}$ within the $2\gamma_s$-tube of $\partial f$ (i.e., $\eta_f(\mathbf{x}) \leq 2\gamma_s$) may cause a classification error, bounding the generalization error. The red polygon intersects $\partial f$, with its two subregions belonging to different classes under $f$ but the same class under the network. Points farther than $2\gamma_s$ from $\partial f$ cannot intersect the boundary, like the blue polygon.

The process of stratification involves decomposing a semi-algebraic set into a finite union of disjoint semi-algebraic subsets, known as strata, which are locally closed submanifolds (Benedetti et al., 1991). In a stratification, the boundary of the entire set $S$ is the union of all strata of lower dimension than the "top-level" interior strata. If $S$ is a closed semi-algebraic set, then $\partial S = \bigcup_{X_j \cap \text{int}(S)=\emptyset} X_j$, where $X_j$ is a stratum of $S$ and it does not touch the interior of $S$.

The target function $f$ partitions the input domain into a finite union of disjoint sets, denoted as $\bigcup g(i)$ where $i \in [l]$. The set $g(i) = \{\mathbf{x} \in B_d(\mathbf{0}, 1)|f(\mathbf{x}) = \mathbf{e}_i\}$ corresponds to class $i$ and is assumed to be a semi-algebraic set, meaning that its representation is a finite union of disjoint subsets, each defined by a finite combination of polynomial equations and inequalities. Formally, we can represent a stratification of $\bigcup g(i)$ by a finite collection of semi-algebraic subsets $\{f_k = \bigcup_j f_k^j\}$, where the dimension of $f_k^j$ is $k$ and $f_k^j$ are disjoint semi-algebraic sets. We refer to the volume of $f_k^j$ as $|f_k^j|$. The concept of volume measures the size of an object: a 1-volume corresponds to length, while a 2-volume corresponds to area, and so on.

Hence, considering the boundary of the involved sets leads to the following relationship:

$$\partial f = \bigcup_{i=1}^{l} \partial g(i) = \bigcup_{k=0}^{d-1} f_k = \bigcup_{k=0}^{d-1} \bigcup_{j} f_k^j, \tag{1}$$

with $f_k = \bigcup_j f_k^j$ and

$$|f_k| = \sum_j |f_k^j|. \tag{2}$$

For example, consider the stratification of $g(1) = \{(x, y) \in \mathbb{R}^2 \mid |x| + |y| < 1\} \bigcup \{(x, y) \in \mathbb{R}^2 \mid |x| + |y| = 1\}$ with dimension 2. The first subset of that stratification is the interior of $g(1)$; therefore, that set does not contribute to the boundary of $g(1)$. We can decompose the second subset into four 1-dimensional semi-algebraic sets: $f_1^1 = \{x + y = 1|x, y > 0\}$, $f_1^2 = \{-x + y = 1|x < 0, y > 0\}$, $f_1^3 = \{-x - y = 1|x, y < 0\}$, and $f_1^4 = \{x - y = 1|x > 0, y < 0\}$, and four 0-dimensional vertices: $f_0^1 = \{(1, 0)\}$, $f_0^2 = \{(0, 1)\}$, $f_0^3 = \{(-1, 0)\}$, and $f_0^4 = \{(0, -1)\}$. The boundaries of their stratification of $g(1)$ are as follows:

$$\partial g(1) = f_1 \cup f_0 = (\cup_i f_1^i) \cup (\cup_j f_0^j). \tag{3}$$

The following lemma demonstrates that assuming the decision boundary is a semi-algebraic set leads to its decomposition into a combination of polynomial functions of varying degrees (proof in Appendix B). This lemma connects the generalization error to the network's granularity, represented by $\gamma_s$ and $\beta_l$, in approximating the classification boundary. For networks with a small $\gamma_s$, the decision boundary that intersects a given region can be considered a curved $(d-1)$-dimensional surface, homeomorphic to a hyperplane. The $2\gamma_s$-neighborhood of the union of the "hyperplanes" represents the region in the input domain that can contribute to a bound of generalization error.

**Lemma 2.** *Let $f$ be the function $B_d(\mathbf{0}, 1) \to \{\mathbf{e}_1, \cdots, \mathbf{e}_l\}$, defined as $f = \bigcup_{i=1}^l g(i)$, where $g(i) = \{\mathbf{x}|f(\mathbf{x}) = \mathbf{e}_i\}$ is a semi-algebraic set with decision boundary $\partial f$ adhering to the stratification equations (1) and (2). Let $\gamma_s$ and $\beta_l$ represent the smallest enclosing radius and largest inscribed radius of the decision regions in $B_d(\mathbf{0}, 1)$ of the one-hot classification network $\mathcal{M}$. Assume the training data satisfies the conditions for $\beta_l$-covering the unit $d$-ball and the histogram approximation. We use the notation $|S|$ to denote the volume of the set $S$.*
*(i) For an arbitrary density function $\mathcal{P}$ on $B_d(\mathbf{0}, 1)$, the error is given by:*

$$\int_{B_d(\mathbf{0},1)} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))\mathcal{P}(\mathbf{x})\, d\mathbf{x} \leq \frac{1}{N}\sum_{i=1}^N g(f(\mathbf{x}_i), \mathcal{M}(\mathbf{x}_i))$$
$$+ c_\mathcal{P} \sum_{k=0}^{d-1} (2\gamma_s)^{d-k}|B_{d-k}(\mathbf{0},1)||f_k|, \tag{4}$$

*where $g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))$ is the 0/1 error, and $c_\mathcal{P} \in (0,1)$ depends on the density supported over the $2\gamma_s$-neighborhood of $\partial f$.*
*(ii) We further suppose the volume of $f_{d-1}$ is not zero. For small value of $\gamma_s$, we can approximate the above expression as follows:*

$$\int_{B_d(\mathbf{0},1)} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))\mathcal{P}(\mathbf{x})\, d\mathbf{x} \leq \frac{1}{N}\sum_{i=1}^N g(f(\mathbf{x}_i), \mathcal{M}(\mathbf{x}_i)) + c_\mathcal{P}(4\gamma_s)|f_{d-1}|. \tag{5}$$

∎

**Remark.** While our analysis focuses on histogram approximation of the average density in decision regions, all results extend — with minor modifications to Lemma 2 — to the interpolating zone, where training error is zero. We relegate this extension to Appendix I to keep the exposition focused. Notably, both approaches yield similar results, revealing that scaling-law behavior can be achieved via two distinct pathways: histogram approximation or interpolation.

## 4 Connecting geometry to scaling laws

### 4.1 Scaling laws with respect to sample size

The early work on learning curve theory by Cortes et al. (1993) illustrates how a binary classification network's performance changes as the amount of training data increases. This study reveals a scaling law related to data size: the log-log plot of generalization error versus the number of training samples, with nonzero training error, forms a straight line with a negative slope. For the MNIST dataset, the absolute value of slope ranges from $\frac{1}{2}$ to 1 (see Figures 5 and 6 of the paper).

By imposing $\mathcal{P} \geq k > 0$ over $B_{d_e}(\mathbf{0}, 1)$ where $d_e$ is the effective dimension of $\mathcal{P}$, the probability mass of $\mathcal{P}$ over the ball $B_{d_e}(\mathbf{a}, \beta_l)$, denoted as $P(\mathbf{a}, B_{d_e}(\mathbf{a}, \beta_l))$, can be uniformly bounded below as follows:

$$P(\mathbf{a}, B_{d_e}(\mathbf{a}, \beta_l)) = \int_{B_{d_e}(\mathbf{a},\beta_l)} \mathcal{P}(\mathbf{x})\, d\mathbf{x} \geq |B_{d_e}(\mathbf{0}, \beta_l)| \cdot \min_{\mathbf{x} \in B_{d_e}(\mathbf{a},\beta_l)} \mathcal{P}(\mathbf{x}) \geq |B_{d_e}(\mathbf{0}, \beta_l)|k = c\beta_l^{d_e}, \tag{6}$$

where $c = |B_{d_e}(\mathbf{0}, 1)|k$.

We substitute the input domain dimension with the effective dimension in Lemma 2. The findings presented below indicating that the generalization error bound for a large network and sample size follow a scaling law with a slope of $1/d_e$ (proof in Appendix C).

**Theorem 1.** *The assumptions related to Lemma 2(ii) hold. Suppose the density function $\mathcal{P} \geq k > 0$. The generalization error with respect to sample size for a one-hot classification $\mathcal{M}$ is bounded by $\frac{|\partial f_d|}{(cN)^{1/d_e}}$.* ∎

## 4.2 Box-model dimension and scaling laws with respect to network size

Having bounded the generalization error in terms of ball radii capturing the local geometry of a network function, we now investigate how these radii relate to the number of network parameters.

### 4.2.1 Box-model dimension

The box-counting dimension is a way to measure the "ruggedness" or complexity of a shape by examining how it occupies space at different scales. To calculate the box-counting dimension of a specific shape, we examine the relationship between the scaling factor and the number of boxes needed to cover it. The dimension $D$ is the logarithmic power law relationship between the number of boxes and their size: $D = \lim_{s \to 0} \frac{\log \# B(s)}{\log(1/s)}$, where $\# B$ is the number of boxes (a grid of squares) with side length $s$ over the object. This dimension is found by overlaying a grid of boxes with side length $s$ over the object, counting the number of boxes, then making the boxes smaller and counting again, and observing how the count increases as $s$ decreases. In practice, since the box-counting dimension may not exist or may be numerically difficult to calculate, the upper box-counting dimension is used to indicate that this set has a dimension at least $\bar{D}$ by considering $\bar{D} = \limsup_{s \to 0} \frac{\log \# B(s)}{\log(1/s)}$.

The box-counting dimension measures the complexity of a set by quantifying how many boxes are needed to describe its shape at various scales of box size. In contrast, the box-model dimension measures the number of parameters $\# W$ in a model $\mathcal{M}$ required to construct the box-coverage of a target shape when one zooms into the shape. We define the box-model dimension as follows:

$$D_{\mathcal{M}} = \lim_{s \to 0} \frac{\log \# W(s)}{\log(1/s)}. \tag{7}$$

By this definition, we focus on how the radii decrease with depth as the number of parameters in a neural network increases. We express the relationship between the number of parameters $\# W$ in network $\mathcal{M}$ and the radius $\gamma_s$ as follows:

$$\gamma_s \leq \frac{1}{\# W^{1/\log_2(1 + \alpha(\# W, \gamma_s))}}. \tag{8}$$

In our analysis of classification tasks, the radius $\gamma_s$ is derived from the decision regions of model $\mathcal{M}$. Increasing the number of network parameters $\# W$ generates more decision regions, potentially reducing the radius. As a result, $\gamma_s$ is a non-increasing function of $\# W$. The condition in Eq. (8) states that the growth rate of $\# W^{1/\log_2(1+\alpha)}$ must be slower than the decrease in $\gamma_s$, as characterized by the value of $\alpha$. This condition provides an upper bound of parameters, preventing the network from overfitting or over-approximating the training points. Taking the logarithm on both sides and then dividing by $\log_2 1/\gamma_s$, we obtain:

$$\frac{\log_2 \# W}{\log_2 1/\gamma_s} \leq \log_2(1 + \alpha(\# W, \gamma_s)). \tag{9}$$

As $\gamma_s \to 0$, we obtain the upper box-model dimension:

$$\limsup_{\gamma_s \to 0} \frac{\log_2 \# W}{\log_2 1/\gamma_s} = \bar{D}_{\mathcal{M}} \to \log_2(1 + \alpha_{\mathcal{M}}). \tag{10}$$

Here, the parameter $\alpha_{\mathcal{M}} > 0$ is model-dependent and influenced by factors such as the network architecture and the specific training method used. Due to this model dependence, networks with the same input domain can produce different box-model dimensions depending on their architecture and training method. In Appendix D, we demonstrate that the exact configuration of the input domain, generated by shallow and deep network structures, can produce different box-model dimensions in the scaling laws.

The logarithmic function in Eq. (8) arises from constructing a base network $\mathcal{M}_0$ and expanding its depth to create $\mathcal{M}_1$. The goal was to ensure that $\gamma_1$ of $\mathcal{M}_1$ was reduced to less than half the value of $\gamma_0$ of $\mathcal{M}_0$, while increasing the parameter count by a factor of at most $1 + \alpha$, where $\gamma_0$ and $\alpha$ are held constant throughout the construction. We then apply the process recursively to decrease the enclosing radius to a desired value

$\gamma_s$. Setting $\gamma_0 = 1$, reducing the radius to $\gamma_s$ requires $L = -\log_2 \gamma_s$ iterations. Let the resulting network be $\mathcal{M}_L$. Using $\#W_{l_k} \leq (1+\alpha)\#W_{l_{k-1}}$ with initial condition $\#W_0 = 1$, the parameter count of $\mathcal{M}_L$ satisfies $\#W \leq (1+\alpha)^L$, and hence

$$\log_2 \#W \leq (-\log_2(1+\alpha))(\log_2 \gamma_s). \tag{11}$$

This gives the relation $\gamma_s \cdot \#W^{\frac{1}{\log_2(1+\alpha)}} \leq 1$ with $\alpha > 0$, as depicted in Eq. (8). We note that $\alpha$ need not be uniform across sub-networks or depths; the construction readily accommodates depth-varying $\alpha$.

We consider the network $\mathcal{M}_L^0 = [I + \rho M_L] \circ [I + \rho M_{L-1}] \circ \cdots \circ [I + \rho M_1]$, where $I$ denotes the identity mapping (serving as a skip connection within each layer), $\rho$ denotes the Rectified Linear Unit (ReLU) activation function, and $M_l$ represents an affine linear mapping. We show that it is possible to arrange the hyperplanes and the training points such that the scaling law is satisfied with a constant exponent for any depth $l$ in $\mathcal{M}_l^0$. The arrangement of the hyperplanes and training points required here is not generally achievable by gradient-based training methods. Furthermore, our construction halves the covering radius at each successive layer. Since the number of covering balls scales exponentially with each such reduction, this halving condition leads to an exponential increase in network width from one layer to the next. This contrasts with practical architectures such as ResNets and VGGs, where network width grows only moderately (e.g., polynomially) across layers. Therefore, the exponential parameter requirement is a property of our theoretical construction, introduced to establish the existence of scaling laws, and should not be interpreted as a constraint on practical architectures. A detailed derivation of this proposition can be found in Appendix E.

**Proposition 1.** *Let $\#W_l$ denote the number of parameters and $\gamma_l$ denote the radius of the smallest enclosing balls of the regions induced by $\mathcal{P}_l^0$ in network $\mathcal{M}_l^0$. There exists a configuration of hyperplanes in layer $\rho M_{l+1}$ and a choice of training points such that the finest partition $\mathcal{P}_{l+1}^0$ of network $\mathcal{M}_{l+1}^0$ with $l \leq L-1$ is a refinement of $\mathcal{P}_l^0$ that satisfies $\gamma_{l+1} \leq \frac{\gamma_l}{2}$. Additionally, the number of parameters in $\mathcal{M}_{l+1}$ and $\mathcal{M}_l$ can be constrained by the inequality $\#W_{l+1} \leq (1+\alpha)\#W_l$, where $\alpha \geq 1$ when $l$ is large (as the covering radius becomes smaller).* ∎

The construction in this proposition focuses on how to achieve the desired covering radius by increasing network width at each layer. Once the desired covering radius of $\mathcal{M}_L^0$ is achieved, we align the output dimension with that of the target network by appending a series of layers of gradually decreasing width. This width-decreasing composition preserves the covering radius achieved by $\mathcal{M}_L^0$.

### 4.2.2 Scaling laws with respect to network size

We now examine the implications of the condition on Eq. (8) for generalization bounds. Given $\gamma$ and $\#W$, the value of $\alpha$ satisfying the condition has a minimal value. We denote the minimal value $\alpha^*(\#W, \gamma)$ that satisfies the condition with equality. By substituting the equality condition into Lemma 2 for $\gamma_s$, the generalization bounds become inversely proportional to the number of parameters in a network.

**Theorem 2.** *Suppose the classification boundary $\partial f$ of target classification function $f : B_d(\mathbf{0}, 1) \to \{\mathbf{e}_1, \cdots, \mathbf{e}_l\}$ is a semi-algebraic set satisfying the stratification equations (1) and (2). Let $\gamma_s$ and $\beta_l$ denote the smallest enclosing radius and the largest inscribed radius of input domain partition regions derived by a one-hot classification network $\mathcal{M} : B_d(\mathbf{0}, 1) \to \{\mathbf{e}_1, \cdots, \mathbf{e}_l\}$. We assume that the training data $\{(\mathbf{x}_i, f(\mathbf{x}_i))\}$ from $\mathcal{P}$ satisfies the $\beta_l$-covering assumption for the unit d-ball and the histogram approximation. Let $\#W$ represent the number of parameters in $\mathcal{M}$. Let $\alpha^*(\#W, \gamma_s)$ satisfy $\gamma_s = \frac{1}{\#W^{1/\log_2(1+\alpha^*(\#W, \gamma_s))}}$.*

*(i) Substituting the equality condition for $\gamma_s$, we can bound the error between classification functions $f$ and $\mathcal{M}$ as follows:*

$$\int_{B_d(\mathbf{0},1)} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))\mathcal{P}(\mathbf{x}) \, d\mathbf{x} \leq \frac{1}{N} \sum_{i=1}^{N} g(f(\mathbf{x}_i), \mathcal{M}(\mathbf{x}_i))$$
$$+ c_\mathcal{P} \sum_{k=0}^{d-1} \left( \frac{2}{\#W^{1/\log_2(1+\alpha^*(\#W, \gamma_s))}} \right)^{d-k} |B_{d-k}(\mathbf{0}, 1)||f_k|, \tag{12}$$

where $g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))$ is the 0/1 error and $c_{\mathcal{P}} \in (0, 1)$ depends on the density $\mathcal{P}$ restricted to the $2\gamma_s$-neighborhood of $\partial f$.

*(ii) We further suppose the volume of $f_{d-1}$ is not zero. For a small value of $\gamma_s$, we can approximate the above expression as follows:*

$$\int_{B_d(\mathbf{0}, 1)} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x})) \mathcal{P}(\mathbf{x}) \, d\mathbf{x} \leq \frac{1}{N} \sum_{i=1}^{N} g(f(\mathbf{x}_i), \mathcal{M}(\mathbf{x}_i)) + \frac{4 c_{\mathcal{P}} |f_{d-1}|}{\#W^{1/\log_2(1 + \alpha^*(\#W, \gamma_s))}}. \tag{13}$$

■

We denote the generalization error as a function of $(\#W, \gamma)$ as $g(\#W, \gamma_s) = \frac{4 c_{\mathcal{P}} |f_{d-1}|}{\#W^{1/\log_2(1 + \alpha^*(\#W, \gamma_s))}}$. Taking the logarithm of both sides of the equation, we obtain

$$\ln g(\#W, \gamma_s) + \frac{1}{\log_2(1 + \alpha^*(\#W, \gamma_s))} \ln \#W = k, \tag{14}$$

for some constant $k$. This curve on the $(\#W, \varepsilon)$ plane underlies the prediction problem: points on the curve are sampled from smaller models, the curve is fitted, and the fitted curve is used to extrapolate the performance of larger models. However, the curve is generally not smooth or continuous, as reported by Caballero et al. (2022). Consequently, the prediction problem is nontrivial, as the complexity of the curve depends on $\alpha(\#W, \gamma_s)$, which is determined by the architecture and learning method. We therefore seek a special case, motivated by architecture design, in which the curve is smooth and predictable. This is the subject of the following subsections.

## 4.3 Discrete scale invariance

If we approximate the generalization error with the bound, we can apply the framework of discrete scale invariance to show that the log-log plot of generalization error against parameter count forms a straight line decorated with a highly regular oscillation Sornette (1998). From this line, we can extrapolate the test performance of larger models from that of smaller ones.

The discrete scale invariance studies the behavior of $f(\lambda \mathbf{x}) = \lambda^p f(\mathbf{x})$ for some discrete $\lambda$. The general solution to this equation is not a pure power law. Instead, it is the power law modified by a periodic function: $f(\mathbf{x}) = \mathbf{x}^p F\left(\frac{\ln \mathbf{x}}{\ln \lambda}\right)$, where $F(\mathbf{y})$ is a periodic function of period 1 (meaning that $F(\mathbf{y} + 1) = F(\mathbf{y})$). Since $F$ is a bounded, taking the logarithmic slope, we have

$$\frac{\ln f(\mathbf{x})}{\ln 1/\mathbf{x}} = -p + \frac{\ln F\left(\frac{\ln \mathbf{x}}{\ln \lambda}\right)}{\ln 1/\mathbf{x}}, \tag{15}$$

which shows that discrete scale invariance manifests as log-periodic oscillations superimposed on a leading power law. Taking the limit $\mathbf{x} \to 0$, the oscillatory term vanishes since $F$ is bounded, giving

$$\lim_{\mathbf{x} \to 0} \frac{\ln f(\mathbf{x})}{\ln 1/\mathbf{x}} = -p. \tag{16}$$

The network constructed in Proposition 1 satisfies the discrete scale invariance equation: $\#W(\gamma/2) = (1 + \alpha) \#W(\gamma)$ with $\lambda = 1/2$ and $p = -\log_2(1 + \alpha)$. Then, $\lim_{\gamma \to 0} \frac{\ln \#W(\gamma)}{\ln 1/\gamma} = -p = \log_2(1 + \alpha)$, the box-model dimension.

From the perspective of both software and hardware, deep learning is built from modular design blocks, such as standard transformer blocks or ResNet blocks. When we scale a model, we do not arbitrarily add individual parameters throughout the computation graph. Instead, we stack these self-contained modules. Each additional block contributes a discrete unit of function-fitting capability, and their recursive stacking gives rise to discrete self-similarity and scale invariance.

Following this perspective, let $\#W(\gamma)$ represent the number of parameters in a network, where $\gamma$ denotes the smallest enclosing radius of its partition of the input domain. Suppose we construct a larger network

by adding $\alpha \# W(\gamma)$ parameters to the original network while simultaneously reducing the smallest enclosing radius to $\lambda_0 \gamma$, where $\lambda_0 < 1$ is a constant. We can express this construction using the following equation for discrete scale invariance:

$$\# W(\lambda_0 \gamma) = (1 + \alpha) \# W(\gamma) = \lambda_0^{\frac{\log_2(1+\alpha)}{\log_2 \lambda_0}} \# W(\gamma), \tag{17}$$

which identifies $p = -\frac{\log_2(1+\alpha)}{\log_2 \lambda_0}$ in the general framework. Hence, the solution to the above equation is

$$\frac{\ln \# W(\gamma)}{\ln 1/\gamma} = -\frac{\log_2(1 + \alpha)}{\log_2 \lambda_0} + \frac{\ln F\left(\frac{\ln \gamma}{\ln \lambda_0}\right)}{\ln 1/\gamma}. \tag{18}$$

Taking the limit $\gamma \to 0$, we define the box-model dimension as

$$\lim_{\gamma \to 0} \frac{\ln \# W(\gamma)}{\ln 1/\gamma} = -\frac{\log_2(1 + \alpha)}{\log_2 \lambda_0} = \log_2(1 + \alpha_{\mathcal{M}}). \tag{19}$$

### 4.3.1 Empirical validation

We design our experiments to demonstrate that the discrete architectural choices for large networks such as ResNets, VGGs, and Inceptions impose the discrete scale invariance property. We leverage this property to predict the test performance of a large network from that of smaller networks, using the solution to the discrete scale invariance equation. We demonstrate that test performance prediction can be carried out accurately using a simpler prediction method for networks whose architecture satisfies the discrete scale invariance property.

We let $\# W_i$ be the number of parameters of $\mathcal{M}_i$, and $\gamma_i$ be the smallest enclosing radius of the input domain partition regions derived by $\mathcal{M}_i$. We further suppose that $\gamma_j < \gamma_i$ and $\# W_j > \# W_i$ for $j > i$. Suppose that there exists a constant $\alpha$ such that $\gamma_i \approx \frac{k}{\# W_i^{1/\log_2(1+\alpha)}}$ for some constant $k$, for $\gamma_i \leq \gamma_0$ and $\# W_i \geq \# W_0$. Then, the pairs $(\# W_i, \gamma_i)$ lie approximately on the line in the $(\# W, \gamma)$ plane, given by $\ln \gamma + \frac{1}{\log_2(1+\alpha)} \ln \# W = \ln k$, so that in the log-log plots of the generalization bound against the number of parameters, the slope is $-1/\log_2(1 + \alpha)$, a constant.

By Lemma 2(ii), the generalization error bound is proportional to the radius of the smallest enclosing balls of the input domain partition regions. Combining with Part (ii) of Theorem 2, we use the following formulation to estimate $\alpha$ from smaller models with known generalization errors and numbers of parameters:

$$\left(\frac{g_1}{g_2}\right)^{\log_2(1+\alpha)} \approx \frac{\# W_2}{\# W_1}, \tag{20}$$

where $g_i$ and $\# W_i$ represent the generalization error and the number of parameters for model $i$, respectively. This approximation does not necessarily require operating in the interpolation zone, where the training error is zero or nearly zero. However, within the interpolation zone, the generalization error can be approximated by the expected test error. Let $\hat{\alpha}$ represent the estimated value of $\alpha$ from the two smallest models. We assess accuracy using two methods:

**Method A** uses this estimated value to predict the generalization error $\hat{g}_{i+1}$ for model $i + 1$ using model $i$: $\left(\frac{g_i}{\hat{g}e_{i+1}}\right)^{\log_2(1+\hat{\alpha})} \approx \frac{\# W_{i+1}}{\# W_i}$, and **Method B** uses this estimated value to predict the generalization error $\hat{g}e_{i+1}$ with a fixed reference model (model 2): $\left(\frac{g_2}{\hat{g}_{i+1}}\right)^{\log_2(1+\hat{\alpha})} \approx \frac{\# W_{i+1}}{\# W_2}$. To evaluate the accuracy of this prediction, in both methods, we calculate the relative error (RE) using the formula: $\frac{|\hat{g}_{i+1} - g_{i+1}|}{g_{i+1}} \times 100\%$.

We evaluate the extrapolation performance of our approach using large models built on a modular design, incorporating numerous training points. This design is more likely to align with our assumptions and is less likely to impose limitations on the required depth increment for prediction. We conduct two sets of experiments: one for classification tasks (reported in sections I-III) and another for a regression task (reported in section IV).

For the first set, we illustrate these scaling laws using experimental results from ResNet and VGG models on the ImageNet and CIFAR-100 datasets, drawn from various benchmark implementations, related papers, and reports. The absolute value of the slope measures the rate of change in test errors with respect to the number of model parameters on the log-log scale. In our analysis of VGGs and ResNets on ImageNet, we found that the absolute value of the slope for VGGs $\approx 1.5$ is larger than that for ResNets $\approx 0.2$. This result suggests that VGGs achieve approximately a 7-fold greater reduction in test error per unit increase in parameters compared to ResNets on a log-log scale. Nevertheless, this efficiency comes at the expense of increased parameter redundancy, as the VGG model has over 100M parameters.

**I. ResNets on ImageNet:** Table 1 and Figure 2 illustrate the predicted Top-1 Error for the ResNet model on this dataset. As shown in Figure 2, the scaling law indicates that the generalization error bound, which is the difference between the expected test error and the expected training error, behaves as a line in the log-log plot of generalization error and the number of parameters. In the log-log plane of generalization error versus the number of parameters, Equation (14) represents a line with slope $-1/\log_2(1 + \alpha)$. The estimated value of $\alpha$ from ResNet-18 and ResNet-34 is $35.14$. This results in $\log_2(1 + \hat{\alpha}) = 5.188$ and a slope of $-\frac{1}{\log_2(1+\hat{\alpha})} = -0.19$. This slope suggests, according to Equation (20), that for the test error of a ResNet to be reduced to half its original value, the number of parameters would have to increase to thirty-two times its original size. We use this slope value to derive the predicted Top-1 error presented in the table and figure.

Figure 2: Log-log plot of Table 1. Axes show raw parameter counts and top-1 test errors for ease of interpretation. The line through the two smallest models (ResNet-18, ResNet-34) is used to predict performance of larger models (ResNet-50, ResNet-101, ResNet-152). Solid circles denote actual values; empty circles denote predictions from Method A.

| Model-Depth | Size (M) | Error (%) | A: Pred. Err. (%) | A: RE (%) | B: Pred. Err. | B: RE |
|---|---|---|---|---|---|---|
| ResNet-18 | 11.7 | 30.1 | x | x | x | x |
| ResNet-34 | 21.8 | 26.7 | x | x | x | x |
| ResNet-50 | 25.6 | 23.8 | 25.9 | 8.82 | 25.9 | 8.82 |
| ResNet-101 | 44.5 | 22.6 | 21.4 | 5.31 | 23.3 | 3.1 |
| ResNet-152 | 60.2 | 21.7 | 21.3 | 1.84 | 21.9 | 0.88 |

Table 1: Prediction of the top-1 test error for ResNet models on ImageNet, whose validation set contains approximately 6% label errors (Northcutt et al., 2021). Parameter counts and error rates are taken from He et al. (2016) and benchmark re-implementations (Wightman et al., 2021; PyTorch Development Team, 2025); slight variations may arise from differences in training setup. Predictions from smaller models achieve a relative error below 10%, enabling reliable resource assessment for larger models.

**II. ResNets on CIFAR-100:** The Top-1 Error, as shown in Table 2, was obtained from the implementation of ResNet models on the CIFAR-100 dataset, as reported by Jafar and Lee (2023). The slope derived from the ResNet-20 and ResNet-34 models is -0.15, with an estimated value of $\alpha$ being 93.2.

| Model-Depth | Size (M) | Error (%) | A: Pred. Err. (%) | A: RE (%) | B: Pred. Err. | B: RE |
|---|---|---|---|---|---|---|
| ResNet-20 | 0.27 | 30.31 | x | x | x | x |
| ResNet-34 | 0.46 | 27.95 | x | x | x | x |
| ResNet-44 | 0.66 | 27.02 | 26.44 | 2.14 | 26.44 | 2.14 |
| ResNet-101 | 1.7 | 23.86 | 23.39 | 1.96 | 22.91 | 3.98 |

Table 2: Prediction of the top-1 test error for ResNet models on CIFAR-100, whose validation set contains approximately 5.85% label errors (Northcutt et al., 2021). Parameter counts and error rates are taken from Jafar and Lee (2023); note that parameter counts differ from Table 1 due to variations in layer width. Relative errors for ResNet-44 and ResNet-101 are both below 5%.

**III. VGGs on ImageNet:** In our analysis of the VGG family of models tested on ImageNet, we first examine the least-squares regression lines presented on a log-log scale. The regression lines adhere to scaling laws, displaying slopes of -1.21 for models that utilize Batch Normalization (BN) and -1.11 for those that do not. This difference in slope values indicates that the BN model is slightly more efficient with its parameters than the one without BN, suggesting a faster rate of decrease in test error.

The VGG implementations on ImageNet exhibit a non-negligible training error. However, as long as the training error is comparably small to the test error, we can still apply Eq. (20) to obtain an estimate of the slope for smaller models. The values of $\alpha$ were found to be 0.551 for models without BN and 0.478 for those with BN. The slope for models without BN is -1.581, while the slope for models utilizing BN is -1.784. The values are slightly lower but qualitatively consistent with those obtained using the least-squares method for three observations. Tables 3 and 4 present the prediction performance results, and the performance differences shown in the tables primarily result from the implementation of BN. Since there are only three observations, both methods yield identical predictions.

| Model-Depth | Size (M) | Test Error (%) | Pred. Test Error (%) | Relative Error (%) |
|---|---|---|---|---|
| VGG-13 | 133 | 30.1 | x | x |
| VGG-16 | 138 | 28.4 | x | x |
| VGG-19 | 144 | 27.6 | 26.55 | 3.8 |

Table 3: Prediction of the top-1 test error for VGG models (without Batch Normalization) on ImageNet. Parameter counts and error rates are taken from Simonyan and Zisserman (2014) and benchmark re-implementations (Paszke et al., 2019; PyTorch Development Team, 2025); slight variations may arise from differences in training setup.

| Model-Depth | Size (M) | Test Error (%) | Pred. Test Error (%) | Relative Error (%) |
|---|---|---|---|---|
| VGG-13-BN | 133 | 28.4 | x | x |
| VGG-16-BN | 138 | 26.6 | x | x |
| VGG-19-BN | 144 | 25.8 | 24.66 | 4.4 |

Table 4: Prediction of the top-1 test error for VGG models with Batch Normalization (Ioffe and Szegedy, 2015) on ImageNet (Paszke et al., 2019; PyTorch Development Team, 2025). Slight variations may arise from differences in training setup.

**IV. InceptionNets on Udacity:** Nadella et al. (2024) measures the performance of Inception architectures on the Kaggle SAP dataset of approximately 97,330 road images with corresponding steering angles, predicting continuous-valued steering angles from road images. While our analysis is primarily designed for classification, we apply our method to this regression task to demonstrate its generalizability. The MSE, computed over all test images, serves as the prediction error reported in the following table.

| Model | Size (M) | MSE | A: Pred. MSE | A: RE (%) | B: Pred. MSE | B: RE |
|---|---|---|---|---|---|---|
| InceptionNet | 13 | 0.06044 | x | x | x | x |
| InceptionNet a | 14.5 | 0.05945 | x | x | x | x |
| InceptionNet b | 15.5 | 0.05849 | 0.05885 | 0.62 | 0.05885 | 0.62 |
| InceptionNet c | 17 | 0.05846 | 0.057649 | 1.39 | 0.05805 | 0.7 |
| InceptionNet d | 17.6 | 0.05961 | 0.05815 | 2.5 | 0.05775 | 3.12 |
| InceptionNet e | 20.7 | 0.05802 | 0.05817 | 0.26 | 0.05636 | 2.86 |
| InceptionNet f | 21.7 | 0.05907 | 0.05761 | 2.47 | 0.05602 | 5.16 |

Table 5: Predicted MSE for the InceptionNet family of models on the Udacity dataset. The box-model dimension $\log_2(1 + \alpha)$, estimated from the first two models, is 6.612.

### 4.3.2 Limitations

First, our theorem assumes that the boundary set $\partial f$ is a semi-algebraic set, excluding sets with non-tame or pathological structure. While scaling laws for semi-algebraic sets suggest similar principles may extend to o-minimal structures, the analysis shows that scaling laws can fail for target classification functions with irregular decision boundaries. Second, the box-counting method measures $\mathcal{N}(\gamma) \sim \gamma^D$ boxes needed to cover $\partial f$ at scale $\gamma$, a number that may vary across implementation methods. The box-model approach additionally imposes $\gamma \cdot \#W^{\frac{1}{\log_2(1+\alpha)}} \leq 1$, where $\#W$ and $\alpha$ depend on the architecture and learning algorithm. When $\partial f$ exhibits multi-fractal characteristics, $D$ varies with $\gamma$, and the log-log line method cannot provide reliable predictions. Third, the log-log linear relationship between $\gamma$ and $\#W$ holds only within a specific range depending on $\partial f$; predictions are valid only for networks operating within that range.

Beyond the geometry of $\partial f$, if a network's hypothesis class does not satisfy the discrete scale-invariance property, we cannot in theory guarantee log-log linearity, and our prediction method does not apply. Moreover, the method requires the network to be sufficiently large so that Theorem 2(ii) holds. Finally, our theoretical results assume that training and testing points are drawn i.i.d. from the same distribution, with labels generated by the same function $f$. Consequently, our framework does not apply to the classification noise correction setting (Wei et al., 2021), where training labels are generated by $f$ while test labels are generated by a different function $\tilde{f}$. Specifically, the training sets consist of noisy labels $(\mathbf{X}_{train}, f(\mathbf{X}_{train}))$, while the testing sets maintain their original ground-truth labels $(\mathbf{X}_{test}, \tilde{f}(\mathbf{X}_{test}))$. However, if the dataset contains mislabeled data but the same distribution is used for both training and testing, our framework remains applicable.

## 5 Conclusions

In this paper, we have analyzed the scaling laws for deep neural networks and contributed theoretically by linking the geometric properties of a network's decision boundaries to empirical scaling laws. We have introduced the *box-model dimension* to quantify the number of parameters needed to describe a shape at different scales, adapting fractal geometry's box-counting dimension to neural network architecture. Our results establish that scaling laws can be decoupled: sample size scaling is intrinsically related to the effective dimension of the data manifold, while network size scaling is connected to the learning method and architecture. As a secondary contribution, we have shown that networks constructed with modular design blocks exhibit a discrete scale-invariance property that enables reliable prediction of generalization error for larger models from smaller ones, and we have provided preliminary empirical results on ResNet, VGG, and Inception models to support this hypothesis. We hope this work provides a foundation for future research, including relaxing the semi-algebraic assumption, pursuing larger-scale empirical validation, and extending the analysis to a more general PAC setting.

## References

Alessio Ansuini, Alessandro Laio, Jakob H Macke, and Davide Zoccolan. Intrinsic dimension of data representations in deep neural networks. *Advances in Neural Information Processing Systems*, 32, 2019.

Yasaman Bahri, Ethan Dyer, Jared Kaplan, Jaehoon Lee, and Utkarsh Sharma. Explaining neural scaling laws. *Proceedings of the National Academy of Sciences*, 121(27):e2311878121, 2024.

Peter L Bartlett, Philip M Long, Gábor Lugosi, and Alexander Tsigler. Benign overfitting in linear regression. *Proceedings of the National Academy of Sciences*, 117(48):30063–30070, 2020.

Riccardo Benedetti, Jean-Jacques Risler, et al. *Real algebraic and semialgebraic sets.* Hermann, 1991.

Devansh Bisla, Apoorva Nandini Saridena, and Anna Choromanska. A theoretical-empirical approach to estimating sample complexity of dnns. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3270–3280, 2021.

Stephen P Boyd and Lieven Vandenberghe. *Convex optimization.* Cambridge university press, 2004.

Ethan Caballero, Kshitij Gupta, Irina Rish, and David Krueger. Broken neural scaling laws. *arXiv preprint arXiv:2210.14891*, 2022.

Leshem Choshen, Yang Zhang, and Jacob Andreas. A hitchhiker's guide to scaling law estimation, 2024. *URL https://arxiv. org/abs/2410.11840*, 2024.

Corinna Cortes, Lawrence D Jackel, Sara Solla, Vladimir Vapnik, and John Denker. Learning curves: Asymptotic values and rate of convergence. *Advances in neural information processing systems*, 6, 1993.

Hugo Cui, Bruno Loureiro, Florent Krzakala, and Lenka Zdeborová. Generalization error rates in kernel regression: The crossover from the noiseless to noisy regime. *Advances in Neural Information Processing Systems*, 34:10131–10143, 2021.

Alan M Frieze and Shang-Hua Teng. On the complexity of computing the diameter of a polytope. *computational complexity*, 4(3):207–219, 1994.

Martin Grötschel, László Lovász, and Alexander Schrijver. *Geometric algorithms and combinatorial optimization*, volume 2. Springer Science & Business Media, 2012.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Joel Hestness, Sharan Narang, Newsha Ardalani, Gregory Diamos, Heewoo Jun, Hassan Kianinejad, Md Mostofa Ali Patwary, Yang Yang, and Yanqi Zhou. Deep learning scaling is predictable, empirically. *arXiv preprint arXiv:1712.00409*, 2017.

Marcus Hutter. Learning curve theory. *arXiv preprint arXiv:2102.04074*, 2021.

Wen-Liang Hwang and Shih-Shuo Tung. Analysis of function approximation and stability of general dnns in directed acyclic graphs using un-rectifying analysis. *Electronics (Invited paper)*, 12(18):3858, 2023.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pages 448–456. pmlr, 2015.

Abbas Jafar and Myungho Lee. High-speed hyperparameter optimization for deep resnet models in image recognition. *Cluster Computing*, 26(5):2605–2613, 2023.

Elizaveta Levina and Peter Bickel. Maximum likelihood estimation of intrinsic dimension. *Advances in neural information processing systems*, 17, 2004.

Houyi Li, Wenzhen Zheng, Qiufeng Wang, Hanshan Zhang, Zili Wang, Shijie Xuyang, Yuantao Fan, Zhenyu Ding, Haoying Wang, Ning Ding, et al. Predictable scale: Part i, step law–optimal hyperparameter scaling law in large language model pretraining, 2025. *URL https://arxiv. org/abs/2503.04715*, 2025.

Alexander Maloney, Daniel A Roberts, and James Sully. A solvable model of neural scaling laws. *arXiv preprint arXiv:2210.16859*, 2022.

Swetha Nadella, Pramiti Barua, Jeremy C Hagler, David J Lamb, and Qing Tian. Enhancing accuracy and robustness of steering angle prediction with attention mechanism. In *2024 IEEE Intelligent Vehicles Symposium (IV)*, pages 2339–2344. IEEE, 2024.

Curtis G Northcutt, Anish Athalye, and Jonas Mueller. Pervasive label errors in test sets destabilize machine learning benchmarks. *arXiv preprint arXiv:2103.14749*, 2021.

Junhyung Park, Patrick Bloebaum, and Shiva Prasad Kasiviswanathan. A classical view on benign overfitting: The role of sample size. *arXiv preprint arXiv:2505.11621*, 2025.

Razvan Pascanu, Guido Montufar, and Yoshua Bengio. On the number of response regions of deep feed forward networks with piece-wise linear activations. *arXiv preprint arXiv:1312.6098*, 2013.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chillemi, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Fowler, et al. PyTorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems*, pages 8024–8035, 2019.

PyTorch Development Team. TorchVision models and pre-trained weights. `https://pytorch.org/vision/stable/models.html`, 2025. Accessed: 21 Oct. 2025.

Jonathan S Rosenfeld, Amir Rosenfeld, Yonatan Belinkov, and Nir Shavit. A constructive prediction of the generalization error across scales. *arXiv preprint arXiv:1909.12673*, 2019.

Jonathan S Rosenfeld, Jonathan Frankle, Michael Carbin, and Nir Shavit. On the predictability of pruning across scales. In *International conference on machine learning*, pages 9075–9083. PMLR, 2021.

Utkarsh Sharma and Jared Kaplan. Scaling laws from the data manifold dimension. *Journal of Machine Learning Research*, 23(9):1–34, 2022.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Didier Sornette. Discrete-scale invariance and complex dimensions. *Physics reports*, 297(5):239–270, 1998.

Jiaheng Wei, Zhaowei Zhu, Hao Cheng, Tongliang Liu, Gang Niu, and Yang Liu. Learning with noisy labels revisited: A study using real-world human annotations. *arXiv preprint arXiv:2110.12088*, 2021.

Ross Wightman, Hugo Touvron, and Hervé Jégou. Resnet strikes back: An improved training procedure in timm. *arXiv preprint arXiv:2110.00476*, 2021.

Yizhe Xiong, Xiansheng Chen, Xin Ye, Hui Chen, Zijia Lin, Haoran Lian, Zhenpeng Su, Wei Huang, Jianwei Niu, Jungong Han, et al. Temporal scaling law for large language models. *arXiv preprint arXiv:2404.17785*, 2024.

## A   Proof of Lemma 1

Given that $\beta_l$ is the radius of the largest inscribed ball within all decision regions in the input domain derived by network $\mathcal{M}$, it follows that for any region, there exists a ball with a radius of $\beta_l$ contained within that region.

To reach a contradiction, let's assume there exists a region containing no training points. In this case, the center of the inscribed ball with a radius of $\beta_l$ in that region would be devoid of training points within a distance of $\beta_l$. This situation contradicts the assumption that the input domain is $\beta_l$-covering.

## B  Proof of Lemma 2

One-hot classifiers are piecewise constant functions, assigning inputs to a single class $i$ within the range of $\{1, \cdots, l\}$. The standard coordinate basis $\mathbf{e}_i$ represents class $i$ in a one-hot coding system. To compute the $0/1$ error function, we can use the formula below: for any $f(\mathbf{y}), f(\mathbf{z}) \in \{\mathbf{e}_1, \cdots, \mathbf{e}_l\}$,

$$g(f(\mathbf{y}), f(\mathbf{z})) = \frac{1}{\sqrt{2}} \|f(\mathbf{y}) - f(\mathbf{z})\|_2 = \begin{cases} 1 \text{ if } f(\mathbf{y}) \neq f(\mathbf{z}) \\ 0 \text{ otherwise.} \end{cases} \tag{21}$$

For a given classifier $f$, a ball exists around any point $\mathbf{x}$ in the input domain, where all the points inside this ball have the same class as that of $\mathbf{x}$. If $\mathbf{x}$ lies on the classification boundary of $f$, the radius of the ball is zero. We use the notation $\eta_f(\mathbf{x}) \geq 0$ to denote the maximum radius of the ball centered at $\mathbf{x}$ such that $f(\mathbf{y}) = f(\mathbf{x})$ for all $\mathbf{y}$ belonging to $B_d(\mathbf{x}, \eta_f(\mathbf{x}))$. Therefore, the class of $f$ at any point $\mathbf{y}$ is the same as that of $\mathbf{x}$ when the distance between $\mathbf{x}$ and $\mathbf{y}$ is less than or equal to $\eta_f(\mathbf{x})$. Hence, we have

$$h_f(\mathbf{x}; \|\mathbf{x} - \mathbf{y}\|_2) = g(f(\mathbf{x}), f(\mathbf{y})) = 0 \text{ if } \|\mathbf{x} - \mathbf{y}\|_2 \leq \eta_f(\mathbf{x}). \tag{22}$$

We can bound $h_f$ with the following radius function:

$$\hat{h}_f(\mathbf{x}; \|\mathbf{x} - \mathbf{y}\|_2) = \begin{cases} 1 \text{ if } \|\mathbf{x} - \mathbf{y}\|_2 > \eta_f(\mathbf{x}) \\ 0 \text{ otherwise.} \end{cases} \geq h_f(\mathbf{x}; \|\mathbf{x} - \mathbf{y}\|_2). \tag{23}$$

$\hat{h}_f(\mathbf{x}; \|\mathbf{x} - \mathbf{y}\|_2)$ is a non-decreasing function of $\|\mathbf{x} - \mathbf{y}\|_2$ for any function $f$. In the case where $\mathbf{x}$ is on the classification boundary, $\hat{h}_f(\mathbf{x}; \|\mathbf{x} - \mathbf{y}\|_2)$ will always be equal to 1 for any value of $\mathbf{y} \neq \mathbf{x}$.

The classification network $\mathcal{M}$ is responsible for learning the classifier function $f$ by utilizing $N$ training data pairs $(\mathbf{x}_i, f(\mathbf{x}_i))$. The function of $\mathcal{M}$ is piece-wise constant, dividing the input domain into non-overlapping regions and assigning each region a specific class. The collection of all these regions is referred to as $R_s$. Each region in $R_s$ is associated with two geometric parameters related to balls: the smallest enclosing radius and the largest inscribed radius. The smallest enclosing radius that encompasses all regions in $R_s$ and the largest inscribed radius for all regions in $R_s$ are denoted as $\gamma_s$ and $\beta_l$, respectively.

The training points are $\beta_l$-covering distributed means that every region of $R_s$ must have at least one training point (see Lemma 1). For any input point $\mathbf{x}$ located in region $p$, let $\mathbf{x}_p$ represent a training point within that region. The distance between $\mathbf{x}$ and $\mathbf{x}_p$ will always be less than or equal to $2\gamma_s$, since the radius of the enclosing ball for the region is $\gamma_s$. To calculate the error between $f(\mathbf{x})$ and $\mathcal{M}(\mathbf{x})$ with respect to $\mathbf{x}_p$, we can use the following equation:

$$\begin{aligned} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x})) &= \frac{1}{\sqrt{2}} (\|f(\mathbf{x}) - \mathcal{M}(\mathbf{x}) + f(\mathbf{x}_p) - f(\mathbf{x}_p) + \mathcal{M}(\mathbf{x}_p) - \mathcal{M}(\mathbf{x}_p)\|_2) \\ &\leq \frac{1}{\sqrt{2}} (\|f(\mathbf{x}) - f(\mathbf{x}_p)\|_2 + \|f(\mathbf{x}_p) - \mathcal{M}(\mathbf{x}_p)\|_2 + \|\mathcal{M}(\mathbf{x}_p) - \mathcal{M}(\mathbf{x})\|_2) \\ &\leq g(f(\mathbf{x}), f(\mathbf{x}_p)) + \varepsilon_p. \end{aligned} \tag{24}$$

Here, we define $\frac{1}{\sqrt{2}} \|f(\mathbf{x}_p) - \mathcal{M}(\mathbf{x}_p)\|_2$ as $g(f(\mathbf{x}_p), \mathcal{M}(\mathbf{x}_p)) = \varepsilon_p$. As points in the same region of $R_s$ of $\mathcal{M}$ have the same class, the term $\|\mathcal{M}(\mathbf{x}_p) - \mathcal{M}(\mathbf{x})\|_2$ is zero.

Denote $\{\mathbf{x}_{p,i}\}_{i=1}^{n_p}$ as the set of $n_p$ training points in region $p$. By applying Eq. (24) to each training point in the region and then computing the average, we can obtain the following result:

$$\begin{aligned} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x})) &\leq \frac{1}{n_p} \sum_{i=1}^{n_p} g(f(\mathbf{x}), f(\mathbf{x}_{p,i})) + \bar{\varepsilon}_p \\ &\leq \max_i g(f(\mathbf{x}), f(\mathbf{x}_{p,i})) + \bar{\varepsilon}_p. \end{aligned} \tag{25}$$

To assess the expected error for probability distribution $\mathcal{P}$, we use Eq. (25) for each point $\mathbf{x}$ in a region $p$, and then sum over all regions of $R_s$ to obtain:

$$
\begin{aligned}
\int_{B_d(\mathbf{0},1)} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))\mathcal{P}(\mathbf{x})\, d\mathbf{x} &= \sum_{p \in R_s} \int_p g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))\mathcal{P}(\mathbf{x})\, d\mathbf{x} \\
&\leq \sum_{p \in R_s} \int_p \max_i g(f(\mathbf{x}), f(\mathbf{x}_{p,i}))\mathcal{P}(\mathbf{x})d\mathbf{x} \\
&+ \sum_{p \in R_s} \bar{\varepsilon}_p \int_p \mathcal{P}(\mathbf{x})\, d\mathbf{x}.
\end{aligned}
\tag{26}
$$

In the equation, $\bar{\varepsilon}_p$ represents the mean of the prediction error, which is a constant in region $p$, and the equality holds because $R_s$ partitions the input domain. The left side indicates the generalization error, while the right comprises two integrals. The first integral is the maximum value of the function g calculated with respect to all training points $\mathbf{x}_{p,i}$ in region $p$. The second term in Eq. (26) can be further derived using the assumption of histogram approximation to relate this term to the average of all training points:

$$
\begin{aligned}
\sum_{p \in P_s} \bar{\varepsilon}_p \int_p \mathcal{P}(\mathbf{x})\, d\mathbf{x} &= \sum_{p \in P_s} \bar{\varepsilon}_p \frac{n_p}{N} = \frac{1}{N} \sum_{p \in P_s} \sum_{i=1}^{n_p} \|f(\mathbf{x}_{p,i}) - \mathcal{M}(\mathbf{x}_{p,i})\|_2 \\
&= \frac{1}{N} \sum_{i=1}^N \|f(\mathbf{x}_i) - \mathcal{M}(\mathbf{x}_i)\|_2.
\end{aligned}
\tag{27}
$$

Thus, Eq. (26) can be expressed as:

$$
\begin{aligned}
\int_{B_d(\mathbf{0},1)} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))\mathcal{P}(\mathbf{x})\, d\mathbf{x} &\leq \sum_{p \in R_s} \int_p \max_i g(f(\mathbf{x}), f(\mathbf{x}_{p,i}))\mathcal{P}(\mathbf{x})d\mathbf{x} \\
&+ \frac{1}{N\sqrt{2}} \sum_i \|f(\mathbf{x}_i) - \mathcal{M}(\mathbf{x}_i)\|_2 \\
&= \sum_{p \in R_s} \int_p \max_i g(f(\mathbf{x}), f(\mathbf{x}_{p,i}))\mathcal{P}(\mathbf{x})d\mathbf{x} \\
&+ \frac{1}{N\sqrt{2}} \sum_i g(f(\mathbf{x}_i), \mathcal{M}(\mathbf{x}_i)).
\end{aligned}
\tag{28}
$$

We can utilize two facts to calculate an upper bound for the first term in Eq. (28). The first is that $\|\mathbf{x} - \mathbf{x}_{p,i}\|_2 \leq 2\gamma_s$, and the second is that $\hat{h}_f$ is a non-decreasing function, as per Eqs. (23) and (22). By using these facts, we obtain the following inequality:

$$
\begin{aligned}
\sum_{p \in R_s} \int_p \max_i g(f(\mathbf{x}), f(\mathbf{x}_{p,i}))\mathcal{P}(\mathbf{x})d\mathbf{x} &\leq \sum_{p \in R_s} \int_p \max_i \hat{h}_f(\mathbf{x}; \|\mathbf{x} - \mathbf{x}_{p,i}\|_2)\mathcal{P}(\mathbf{x})d\mathbf{x} \\
&\leq \int \hat{h}_f(\mathbf{x}; 2\gamma_s)\mathcal{P}(\mathbf{x})d\mathbf{x} \\
&\leq \int 1([2\gamma_s \geq \eta_f(\mathbf{x})])\mathcal{P}(\mathbf{x})d\mathbf{x}.
\end{aligned}
\tag{29}
$$

Here, $1([2\gamma_s \geq \eta_f(\mathbf{x})])$ is an indicator function for $2\gamma_s \geq \eta_f(\mathbf{x})$, and the last inequality is a result of Eq. (23). For function $f$, the value of $\eta_f(\mathbf{x})$ remains fixed. Moreover, the function $1([2\gamma_s \geq \eta_f(\mathbf{x})])$ is an increasing function of $\gamma_s$. Therefore, a network $\mathcal{M}$ with a lower value of $\gamma_s$ can lead to a reduced generalization bound.

(i) The probability mass that contributes to $\int 1([2\gamma_s \geq \eta_f(\mathbf{x})])\mathcal{P}(\mathbf{x})d\mathbf{x}$, which can generate generalization error, can be bounded. The points satisfying $2\gamma_s \geq \eta_f(\mathbf{x})$ are within a distance no greater than $2\gamma_s$ from the classification boundary of $f$, denoted by $\partial f$, as the schematic diagram illustrated in Figure 1(b). The

Figure 3: The boundary of closed surface $f_2$ consists of four sub-components under stratification, and its dimension is 2. The central axis (represented as a dashed line segment) of the cylinder in $\mathbb{R}^3$ is the first part of the boundary of $f_2$, denoted as $\partial f_2^1$. This axis has a dimension of 1, while the radius of the cylinder is $2\gamma_s$. The volume of the cylinder can be expressed as $|\partial f_2^1|(2\gamma_s)^2\pi$.

boundary can be decomposed as the union of semi-algebraic subsets as follows:

$$\partial f = \bigcup_{k=0}^{d-1} f_k = \bigcup_{k=0}^{d-1} \bigcup_i f_k^i,$$

where $f_k^i$ is a $k$-dimensional semi-algebraic set. We define the $2\gamma_s$-neighborhood of $\partial f$ in $\ell_2$-norm as

$$A(2\gamma_s, \partial f) = \{\mathbf{x} \in B_d(\mathbf{0}, 1) \mid \text{dist}(\mathbf{x}, \partial f) \leq 2\gamma_s\} = \bigcup_{k=0}^{d-1} A(2\gamma_s, f_k) \tag{30}$$

and the $2\gamma_s$-neighborhood of $f_k = \bigcup_i f_k^i$ is defined as

$$A(2\gamma_s, f_k) = \bigcup_i A(2\gamma_s, f_k^i) = \bigcup_i \{\mathbf{x} \in B_d(\mathbf{0}, 1) \mid \text{dist}(\mathbf{x}, f_k^i) \leq 2\gamma_s\}.$$

The volume of $A(2\gamma_s, f_k)$ can be bounded in accordance with the union bound and $\dim f_k^j = k$ as

$$|A(2\gamma_s, f_k)| \leq \sum_i |A(2\gamma_s, f_k^i)| \leq (2\gamma_s)^{d-k}|B_{d-k}(\mathbf{0}, 1)| \sum_i |f_k^i|$$
$$= (2\gamma_s)^{d-k}|B_{d-k}(\mathbf{0}, 1)||f_k|. \tag{31}$$

See the illustrative example on calculating $|A(2\gamma_s, f_2)|$ in Figure 3. In the above, we utilize the fact that $|A(2\gamma_s, f_k^i)|$ equals $|B_{d-k}(\mathbf{0}, 2\gamma_s)||f_k^i|$, where $|B_{d-k}(\mathbf{0}, 2\gamma_s)| = (2\gamma_s)^{d-k}|B_{d-k}(\mathbf{0}, 1)|$.

By applying the union bound to Eq. (30) and then to Eq. (31), we derive a bound for the volume of the $2\gamma_s$-neighborhood of $\partial f$:

$$|A(2\gamma_s, \partial f)| \leq \sum_{k=0}^{d-1} |A(2\gamma_s, f_k)| \leq \sum_{k=0}^{d-1} (2\gamma_s)^{d-k}|B_{d-k}(\mathbf{0}, 1)||f_k|.$$

Consequently,

$$\int \mathbb{1}([2\gamma_s \geq \eta_f(\mathbf{x})])\mathcal{P}(\mathbf{x})d\mathbf{x} = c_\mathcal{P}|A(2\gamma_s, \partial f)| \leq c_\mathcal{P} \sum_{k=0}^{d-1} (2\gamma_s)^{d-k}|B_{d-k}(\mathbf{0}, 1)||f_k|. \tag{32}$$

The first equality bounds the probability mass by the volume of the points over the $2\gamma_s$-neighborhood of $\partial f$, where $c_p \in (0, 1)$ represents the average density of $\mathcal{P}$ distributed across the neighborhood.

(ii) When $\gamma_s$ is small and $|f_{d-1}| \neq 0$, the sum $\sum_{k=0}^{d-1}(2\gamma_s)^{d-k}|B_{d-k}(\mathbf{0}, 1)||f_k|$ in equation (32) can be approximated by the leading term $(2\gamma_s)|B_1(\mathbf{0}, 1)||f_{d-1}| = 4\gamma_s|f_{d-1}|$ with $|B_1(\mathbf{0}, 1)| = 2$ (the length of a segment).

## C  Proof of Theorem 1

Let $N$ be the number of training points that forms a $\beta_l$-covering. Then, the expected number of training points within a distance $\beta_l$ at $\mathbf{x}$ is given by

$$\sum_{k=1}^{N} k \binom{N}{k} P(\mathbf{x}, B_{d_e}(\mathbf{x}, \beta_l))^k (1 - P(\mathbf{x}, B_{d_e}(\mathbf{x}, \beta_l)))^{N-k} = NP(\mathbf{x}, B_{d_e}(\mathbf{x}, \beta_l)) \geq 1 \tag{33}$$

By the assumption $\mathcal{P} \geq k > 0$ and Eq. (6), there exists a point $\mathbf{x}_0$ and integer $t$ such that $NP(\mathbf{x}_0, B_{d_e}(\mathbf{x}_0, \beta_l)) = t \geq cN\beta_l^{d_e}$. Taking $t = 1$ as the minimal case, we derive the inequality $\frac{1}{(cN)^{1/d_e}} \geq \beta_l$. Applying this inequality, $|f_{d-1}| \leq |\partial f_d|$, and $K\beta_l \geq \gamma_s$ for some $K \geq 1$ (since $\gamma_s$ and $\beta_l$ are both bounded and bounded away from zero, their ratio $\gamma_s/\beta_l$ is bounded above by some fixed constant $K \geq 1$) to Lemma 2(ii) yields the generalization error bound $c_{\mathcal{P}}(4\gamma_s)|f_{d-1}| \leq c_{\mathcal{P}}(4K\beta_l)|f_{d-1}| \leq \frac{4Kc_{\mathcal{P}}|f_{d-1}|}{(cN)^{1/d_e}} \leq \frac{4Kc_{\mathcal{P}}|\partial f_d|}{(cN)^{1/d_e}}$. This establishes the scaling law for the generalization error bound of a sufficiently large one-hot network: the bound scales as $\frac{|\partial f_d|}{(cN)^{1/d_e}}$ with respect to sample size.

## D  Box-model dimensions of shallow and deep networks

We develop DNNs by increasing depth, in contrast to the wider configurations discussed by Sharma and Kaplan (2022).

Assume that the training points are distributed within a unit cube $[0,1]^{d_e}$, where $d_e$ denotes the effective dimension. The unit cube can be structured as a grid composed of hypercubes, each with a side length of $s < 1$. The number of hypercubes, denoted as $N_s$, is given by $(s)^{-d_e}$. Sharma and Kaplan (2022) suggest that the number of parameters $\#S_s$ of a network $\mathcal{S}_s$ required to realize this grid is proportional to $N_s$.

Analogously, if the side length of hypercubes in the grid becomes $2s < 1$, the number of hypercubes is $N_{2s} = (2s)^{-d_e}$, and the number of parameters $\#S_{2s}$ of a network to realize this grid is proportional to $N_{2s}$.

Following this reasoning, when reducing the side length from $2s$ to $s$, the number of parameters required for the network $\mathcal{S}_s$ is given by $\#S_s = c(s)^{-d_e} = 2^{d_e}\#S_{2s}$, where $c$ is the proportionality constant. Thus, halving the side length increases the required number of parameters by a factor of $2^{d_e}$.

This exponential increase in parameter counts results from widening the network while keeping the depth fixed. However, we argue that the parameters used to realize the grid with side length $2s$ can be reused to construct the finer grid with side length $s$, which the approach of Sharma and Kaplan (2022) does not consider.

Alternatively, the grid configuration with side length $s$ can be constructed from two grids with side length $2s$, where the second is obtained by translating the first by $s$ units along each axis. If a network realizing a grid of side length $2s$ can be reused and augmented with this translation, the number of parameters required for the finer grid with side length $s$ can be substantially reduced compared to training a new network from scratch.

Suppose we have a sub-network $\mathcal{N}_{2s}^1$ that consists of $\frac{1}{2s}$ parallel and equally spaced hyperplanes with respect to the first component of the coordinate system of $d_e$ components. From those hyperplanes, we can generate $\frac{1}{s}$ parallel and equally spaced hyperplanes by adding a layer to $\mathcal{N}_{2s}^1$ as follows:

$$\mathcal{N}_s^1 = \text{ReLU}\left[\begin{matrix} \mathcal{N}_{2s}^1 \\ \mathcal{N}_{2s}^1 + \begin{bmatrix} -s \\ 0 \\ \vdots \\ 0 \end{bmatrix} \end{matrix}\right] = \text{ReLU } \mathbf{A}_s \mathcal{N}_{2s}^1. \tag{34}$$

The upper component in $\mathbf{A}_s$ is the identity matrix $\mathbf{I}$, which generates the same hyperplanes as those in $\mathcal{N}_{2s}^1$. The bottom mapping involves translating by $-s$ along the first coordinate axis, resulting in another set of

hyperplanes, each of which is shifted by $s$ units toward the origin relative to the corresponding hyperplane in $\mathcal{N}_{2s}^1$. The ReLU layer clips the output to $[0,1]^{d_e}$.

By concatenating the outputs of $\mathcal{N}_{2s}^i$ for $i = 1, \cdots, d_e$, we obtain the network that generates the grid configuration of side length $s$:

$$\mathcal{N}_s = \begin{bmatrix} \mathcal{N}_{2s}^1 \\ \vdots \\ \mathcal{N}_{2s}^{d_e} \end{bmatrix} = \mathrm{ReLU}\left(\mathrm{diag}(\mathbf{A}_s, \cdots, \mathbf{A}_s)\right)\mathcal{N}_{2s}, \tag{35}$$

where $\mathrm{diag}(\mathbf{A}_s, \cdots, \mathbf{A}_s)$ is the block diagonal matrix with each block $\mathbf{A}_s$. $\mathcal{N}_s$ produces a grid partition of side length $s$ over the input domain $[0,1]^{d_e}$. Figure 4 shows how the network $\mathcal{N}_s$ is constructed within the domain $[0,1]^2$, as described in Eqs. (34) and (35).

This construction shows that adding a layer increases the number of parameters linearly with respect to $d_e$. This is captured by $\#W_s = \#W_{2s} + d_e c \le (1+\alpha)\#W_{2s}$, where $c$ denotes the number of parameters for $\mathbf{A}_s$, $\alpha > 0$, and $\#W_s$ and $\#W_{2s}$ denote the number of parameters of $\mathcal{N}_s$ and $\mathcal{N}_{2s}$, respectively. This linear increase in parameter counts stands in sharp contrast to the exponential growth observed in the network of Sharma and Kaplan (2022).

(a)                                     (b)

Figure 4: Schematic diagrams in (a) and (b) illustrate how the network $\mathcal{N}_s$ is formed by adding an additional layer to $\mathcal{N}_{2s}$, with its domain in $[0,1]^2$. Subfigure (a) depicts the configurations along the first coordinate, transitioning from $\mathcal{N}_{2s}^1$ to $\mathcal{N}_s^1$. Here, the distance between the parallel hyperplanes in $\mathcal{N}_{2s}^1$ is $2s$, while the distance for the hyperplanes in $\mathcal{N}_s^1$ is $s$. The middle top subfigure corresponds to $\mathcal{N}_{2s}^1$, whereas the middle bottom subfigure shows the configuration of $\mathcal{N}_{2s}^1 + [-s\ 0]^\top$. The configuration of $\mathcal{N}_s^1$ is obtained by concatenating those in $\mathcal{N}_{2s}^1$ and $\mathcal{N}_{2s}^1 + [-s\ 0]^\top$, as defined by Eq. (34). Subfigure (b) illustrates how the configurations of $\mathcal{N}_s^1$ and $\mathcal{N}_s^2$ are concatenated to obtain the configuration of $\mathcal{N}_s$, as defined by Eq. (35). The domain partition of $\mathcal{N}_s$ corresponds to the Cartesian product of the domain partitions of $\mathcal{N}_s^1$ and $\mathcal{N}_s^2$, as stated by Hwang and Tung (2023).

Next, we compare the mean absolute test errors. Assume that each partition region of $\mathcal{N}_s$ in $[0,1]^{d_e}$ contains at least one training point. Let $\mathbf{x}$ and $\mathbf{x}_i$ be two points within a hypercube of side length $s$, with $\|\mathbf{x} - \mathbf{x}_i\| \le \sqrt{d_e}$. By the geometry of the hypercube, $\sqrt{d_e}s$ represents the maximum distance between two points inside a hypercube of side length $s$.

Define $f : \mathbb{R}^{d_e} \to \mathbb{R}$ as the target function with Lipschitz constant $K_f$, where $|f(\mathbf{x}) - f(\mathbf{y})| \le K_f \|\mathbf{x} - \mathbf{y}\|_2$. We suppose $\mathcal{N}_s$ interpolates $f$ at the training points; i.e., $\mathcal{N}_s(\mathbf{x}_i) = f(\mathbf{x}_i)$. Since $\mathcal{N}_s$ is a piecewise constant function over a partition of hypercubes and each hypercube contains at least one training point, if $\mathbf{x}$ and $\mathbf{x}_i$ are in the same hypercube, then $\mathcal{N}_s(\mathbf{x}) = \mathcal{N}_s(\mathbf{x}_i)$. This leads us to the bound:

$$|\mathcal{N}_s(\mathbf{x}) - f(\mathbf{x})| = |\mathcal{N}_s(\mathbf{x}_i) - f(\mathbf{x})| = |f(\mathbf{x}_i) - f(\mathbf{x})| \le K_f \|\mathbf{x}_i - \mathbf{x}\|_2 \le K_f \sqrt{d_e}s.$$

Consequently, if we let $2^l s = 1$ , where $l$ denotes the number of refinement levels, the test error can be bounded by:

$$\int_{[0,1]^{d_e}} |f(\mathbf{x}) - \mathcal{N}_s(\mathbf{x})| d\mathbf{x} \le K_f \sqrt{d_e} s = K_f \sqrt{d_e}(1/2^l). \tag{36}$$

By unfolding the recurrence equation $\#W_s \le (1 + \alpha)\#W_{2s}$ $l$ times and using the boundary condition $\#W_1 = 1$, corresponding to a single hypercube over $[0, 1]^{d_e}$, we can determine the number of parameters for network $\mathcal{N}_s$ as follows:

$$\#W_s \le (1+\alpha)^l \#W_1 \le (1+\alpha)^l. \tag{37}$$

If we substitute $2^l = (1+\alpha)^{l/\log_2(1+\alpha)}$ into Eq. (37), we obtain: $2^l \ge \#W_s^{1/\log_2(1+\alpha)}$. Then, if we substitute this expression for $2^l$ into Eq. (36), the test error for the network $\mathcal{N}_s$ is bounded by:

$$\frac{K_f \sqrt{d_e}}{\#W_s^{1/\log_2(1+\alpha)}}. \tag{38}$$

The absolute value of the slope in the log-log plot is $1/\log_2(1 + \alpha)$.

In contrast, using the recurrence for the network of Sharma and Kaplan (2022): $\#S_s = 2^{d_e}\#S_{2s}$, with boundary condition $\#S_1 = 1$, we obtain $\#S_s = 2^{l d_e}\#S_1 = 2^{l d_e}$. Substituting $2^l = (\#S_s)^{1/d_e}$ into Eq. (36), the test error for the network $\mathcal{S}_s$ is bounded by

$$\frac{K_f \sqrt{d_e}}{\#S_s^{1/d_e}}. \tag{39}$$

The slope's absolute value is $1/d_e$, as noted in Sharma and Kaplan (2022).

Additionally, we argue that $\#S_s \ge \#W_s$ because the wide network includes additional parameters without accounting for the values of the existing ones in previous depths. Consequently, based on Eqs. (38) and (39), we establish a comparison between box-model dimensions, resulting in the inequality:

$$\log_2(1 + \alpha) \le d_e.$$

**Remark.** A bound that requires neither interpolation at training points nor a $\gamma_s$-covering of the input domain, in contrast to Eq. (36), is given in Eq. (2.2) of Sharma and Kaplan (2022), where $L = \int_{[0,1]^{d_e}} (f(\mathbf{x}) - \mathcal{N}_s(\mathbf{x}))^2 d\mathbf{x} \lesssim K_f^2 s^2 d_e$. Intuitively, the error comes entirely from how much $f$ can vary within a single hypercube. The Lipschitz condition bounds that variation by the diameter of the hypercube, $\sqrt{d_e}s$. The integral then averages this worst-case error over the whole domain, and since the domain has unit volume, the average equals the pointwise worst-case bound.

# E   Proof of Proposition 1

Because the two networks $[I + \rho M_L] \circ [I + \rho M_{L-1}] \circ \cdots \circ [I + \rho M_1]$ and $[\rho M_L] \circ [\rho M_{L-1}] \circ \cdots \circ [\rho M_1]$ share the same input domain partition Hwang and Tung (2023), we can simplify our notation for convenience. If our focus is on the input domain partition, we define:

$$\mathcal{M}_L^0 = [\rho M_L] \circ [\rho M_{L-1}] \circ \cdots \circ [\rho M_1].$$

We will construct $\mathcal{M}_l^0 = [\rho M_l] \cdots [\rho M_1]$ layer by layer, ensuring that it satisfies the condition in Eq. (8) with a constant value of $\alpha$ maintained throughout the network's depth.

The function of $\mathcal{M}_L^0$ is piece-wise continuous. Pascanu et al. (2013) previously discussed the machine's capability for function approximations, focusing on the number of regions generated for function approximation. If $P_l^0$ is the finest input domain partition of $\mathcal{M}_l^0$, where each partitioning region of $P_l^0$ contains no sub-regions, then $|P_l^0|$ represents the size of $P_l^0$. When considering $P_l^0$, each partitioning region is a polytope,

an affine linear mapping domain. Additionally, we note that $P_{l+1}^0$ is a refined partition of $P_l^0$, meaning that every region in $P_{l+1}^0$ is within a region in $P_l^0$. This refinement of partitioning regions in $P_l^0$ sets up a tree-like partitioning of $P_l^0$, where each region in $P_{l+1}^0$ has a unique parent region in $P_l^0$.

Within $P_L^0$, every partitioning region forms a polytope, essentially the intersection of half-planes. The "diameter" of a region denotes the longest distance between two points within the region. The maximum diameter among all polytopes in a partition is equivalent to the diameter of the smallest enclosing ball of the partition. Calculating the diameter of a polytope according to Frieze and Teng (1994) can be intricate for polytopes of arbitrary dimension and facet number. Here, we are developing a tractable algorithm to partition a polytope and reduce the diameters of the resulting sub-polytopes to a constant fraction of the original value.

The algorithm begins by dividing a polytope $p$ in $P_L^0$ via a cutting hyperplane passing through an anchor point in $p$ into two sub-polytopes. This method is then applied recursively to each sub-polytope. As a result, polytope $p$ is the root of a tree-like structure, with intermediate and leaf nodes representing the sub-polytopes. The sub-polytopes at the leaf nodes that refine $p$ will have a diameter smaller than half that of the root polytope. Consequently, the collection of sub-polytopes at the leaf nodes of all trees forms the partition $P_{L+1}^0$, with the diameter to be less than half that of $P_L^0$.

Figure 5: The dashed ellipsoid represents the maximum inscribed ellipsoid of polygon $p$. As per Eq. (41), the primary axis of the ellipsoid has a radius of $\eta$, while the minor axis has a radius of $\tilde{\eta}$, and their ratio is given by $\tilde{\eta}/\eta \geq \zeta > 0$. The center of the ellipsoid corresponds to the highlighted anchor point $\mathbf{a}^p$ of the polygon. The outer ellipsoid, shown in red and expanded by a factor of two at the boundary of the maximum inscribed ellipsoid, encloses the polygon. Enclosed within the polygon is a blue inner circle with a radius of $\tilde{\eta}$, and the polygon itself is enclosed by a blue outer circle with a radius of $2\eta$; hence, $B_2(\mathbf{a}^p, \tilde{\eta}) \subseteq p \subseteq B_2(\mathbf{a}^p, 2\eta)$.

The anchor point is the center of the maximum inscribed ellipsoid within the polytope. By Boyd and Vandenberghe (2004), we can determine this point using convex optimization methods. Additionally, we can utilize properties that approximate the volume of a polytope from both inside and outside at the anchor point, as described in Grötschel et al. (2012) to bound the radius of the smallest enclosing ball of a polytope in $P_{L+1}^0$. Let $\mathbf{a}^p \in \mathbb{R}^d$ be the anchor point of the polytope $p$. Any hyperplane passing through $\mathbf{a}^p$ divides the polytope into two sub-polytopes, with $q$ being one of them. The volume-reduction property shows a reduction in volume between $p$ and $q$, as demonstrated by the inequality

$$\mathrm{vol}(q) \leq \left(1 - \frac{1}{d}\right) \mathrm{vol}(p). \tag{40}$$

Additionally, if polytope $p$ is convex (or its convex hull if it's not), then the volume of $p$ can be effectively approximated from the outside by an ellipsoid enlarging a constant factor of the inner maximum inscribed ball of $p$; specifically, the outer ellipsoid of $p$ represents the boundary of the inner ellipsoid, expanded by a factor $d$ around the anchor point.

Let $\eta > 0$ represent the radius of the principal axis of the inner maximum volume inscribed ellipsoid of $p$, and $\tilde{\eta} > 0$ denote the smallest radius of this ellipsoid. Assume the relationship $\tilde{\eta}/\eta \geq \zeta > 0$ holds, where $\zeta$ is

a predetermined value. Then, we can express the approximation of polytope volume from inside and outside by balls in the following inequality:

$$\zeta^d \eta^d \operatorname{vol} B_d(\mathbf{0}, 1) \leq \tilde{\eta}^d \operatorname{vol} B_d(\mathbf{0}, 1) \leq \operatorname{vol}(p) \leq (d\eta)^d \operatorname{vol} B_d(\mathbf{0}, 1). \tag{41}$$

The first inequality follows the condition $\tilde{\eta}/\eta \geq \zeta$. The second inequality approximates the volume of $p$ from the inside using a ball of radius $\tilde{\eta}$, applying the formula $\operatorname{vol} B_d(\mathbf{0}, r) = r^d \operatorname{vol} B_d(\mathbf{0}, 1)$. The final inequality provides an approximation from the outside, where $d\eta$ represents the radius of an enclosing ball around $p$. Figure 5 offers a schematic illustration of Eq. (41).

Let's consider sub-polytopes formed by cutting $p \in P_L^0$ with a hyperplane passing the anchor point of $p$. These sub-polytopes are children of the root polytope $p$ in a binary branch. This process can be repeated for each sub-polytope, creating a binary tree of depth $k$, with at most $2^k$ leaves, each leaf sub-polytope connected to a path rooted at $p$. We can label the sub-polytope in a path at depth one as $q_1$, the sub-polytope in the path at depth two as $q_2$, and so on, as shown in Figure 6, which provides a schematic description of a path of sub-polytopes in the tree and their hyperplane cuttings. To ensure a child's sub-polytope has a non-empty volume, we assume that all eigenvalues of the largest inscribed ellipsoids of any sub-polytope $q_i$ are greater than zero, and the ratio of the smallest radius to the largest radius of a maximum inscribed ellipsoid is not less than $\zeta$. Let's denote $\eta_k$ and $\tilde{\eta}_k$ as the largest and smallest radii of the principal axes of the maximum volume inscribed ellipsoid of $q_k$. Using Eqs. (40) and (41), we obtain the inequality

$$\zeta^d \eta_k^d \operatorname{vol} B_d(\mathbf{0}, 1) \leq \operatorname{vol}(q_k) \leq (1 - \frac{1}{d})^k \operatorname{vol}(p). \tag{42}$$

As we increase the depth $k$, the volume of $q_k$ decreases to zero. This implies that the sequence $\{\eta_k\}$ decreases to zero as $k$ increases, satisfying the inequality

$$\eta_k \leq \left[ \frac{(1 - \frac{1}{d})^k \operatorname{vol}(p)}{\zeta^d \operatorname{vol} B_d(\mathbf{0}, 1)} \right]^{\frac{1}{d}}. \tag{43}$$

Thus, for each path from root polytope $p$ to leaf sub-polytope $q_k$ of the binary tree, we can find a sufficiently large $k$ such that $(d\eta_k) \leq \frac{\gamma_p}{2}$, where $\gamma_p$ is the radius of the smallest enclosing ball of $p$, and $q_k$ is enclosed by a ball of radius $d\eta_k$. The number of hyperplane cuts required to create the path from $p$ to $q_k$ is equal to $k$, the depth of the path, with each hyperplane cut requiring $d+1$ parameters.

For a binary tree of depth $k-1$, the number of nodes in the tree is fewer than $2k$. Based on the construction, each node contains one hyperplane with $d+1$ parameters that divides the polytope associated with the node into two sub-polytopes. Although the number of paths grows exponentially as $2^k$, the number of hyperplane cuts — and hence the parameter count — is determined solely by the number of nodes in the tree, which grows only exponentially as $2k$. Thus, despite the exponential number of paths, few than $2k(d+1)$ parameters are needed to reduce the enclosing radius of $p$ to half its value for all paths in the tree.

Note that each region in $P_l^0$ has a specific depth for its own binary tree. We define $\omega \in \mathbb{N} \cup \{0\}$ as the maximum depth of the binary tree corresponding to any polytope in $P_l^0$ for $l \leq L$ (thus, $\omega \geq k$). Hence, the parameter bound $2k(d+1)$ from the previous argument extends to $2\omega(d+1)$, where $\omega$ serves as the uniform depth bound across all regions in $P_l^0$. Using $\omega$, the number of polytopes in $P_{l+1}^0$ is at most $|P_{l+1}^0| \leq 2^\omega |P_l^0| \leq 2^{l\omega}$ with $|P_0^0| = 1$. Since the subdivision of a polytope requires at most $2\omega(d+1)$ parameters and there are at most $2^\omega$ polytopes, the number of parameters needed to generate $P_{l+1}^0$ from $P_l^0$ is bounded by $2\omega(d+1)2^{l\omega}$.

The number of parameters in $\mathcal{M}_{l+1}^0$, denoted by $\#W_{l+1}$, is equal to the number of parameters in $\mathcal{M}_l^0$, denoted by $\#W_l$, plus the number of parameters required to obtain $P_{l+1}^0$ from $P_l^0$, which is bounded by $2\omega(d+1)2^{l\omega}$. With the base case $\#W_0 \leq 2\omega(d+1)$, we obtain

$$\#W_{l+1} \leq \#W_l + 2\omega(d+1)2^{l\omega} \leq (1+\alpha)\#W_l. \tag{44}$$

Recursively expanding $\#W_l$ in the above inequality for $\omega \in \mathbb{N}$, we obtain

$$\#W_l \le 2\omega(d+1)\sum_{i=0}^{l-1} 2^{i\omega} = 2\omega(d+1)\frac{2^{l\omega}-1}{2^\omega-1}. \tag{45}$$

Since $1 + \alpha \ge \frac{\#W_{l+1}}{\#W_l}$, taking the ratio of consecutive terms gives

$$1 + \alpha \ge \frac{2^{(l+1)\omega}-1}{2^{l\omega}-1}. \tag{46}$$

For large $l$, $\frac{2^{(l+1)\omega}-1}{2^{l\omega}-1} \approx 2^\omega$, and hence $\alpha \gtrsim 2^\omega - 1$. Since $\omega \ge 1$, $\alpha \ge 1$ at large $l$.

Figure 6: The convex polygon $p$ can be partitioned into sub-polytopes using sequences of hyperplane cuttings, leading to a binary tree structure with $p$ at the root. The root $p$ is divided into two sub-polygons by a hyperplane passing through the anchor point $\mathbf{a}_1$, the center of the maximal inscribed ball of $p$. The sub-polygon $q_1$, colored in blue, is further divided using anchor points $\mathbf{a}_2$, $\mathbf{a}_3$, and $\mathbf{a}_4$, corresponding to the centers of the maximal inscribed balls for sub-polygons $q_2$, $q_3$, and $q_4$, respectively. It is worth noting that the volume of any sub-polygon retains a constant fraction of its parent polygon, as defined by Eq. (40).

To complete the construction, we need to translate all cutting hyperplanes of the trees into a new layer. By induction, suppose we obtain $\mathcal{M}_l^0$. We denote the restriction of $\mathcal{M}_l^0$ on the polytope $p \in \mathcal{P}_l^0$ as $\mathcal{M}_l^0|p$. Let $q \in \mathcal{P}_{l+1}^0$ represent a sub-polytope of $p$. We denote $\mathcal{M}_{l+1}^0|q = \rho\mathbf{A}_{q,p}\mathcal{M}_l^0|p$ the equations define polytope $q$, where $\rho\mathbf{A}_{q,p}$ is the affine mapping derived from the sequence of cutting hyperplanes used to construct $q$ from $p$. In the derivation, we can replace $\rho$ by a diagonal matrix containing entries 0 or 1. The values in this matrix are determined by the values of $\mathcal{M}_l^0|p$. The overall affine linear mapping $M_{l+1}$ is then constructed by stacking the arrays of $\mathbf{A}_{q,p}$ generated from each polytope $p$ in $\mathcal{P}_l^0$.

## F  Proof of Lemma 3

If the center of a ball $b$ with radius $\beta_l$ is located outside the ball $B_{d_e}(\mathbf{x}, \beta_l)$, then the point $\mathbf{x}$ cannot be contained within the ball $b$. We can conclude that the probability of a randomly chosen ball not containing $\mathbf{x}$ is given by $1 - P(\mathbf{x}; B_{d_e}(\mathbf{x}, \beta_l))$, where $P(\mathbf{x}; B_{d_e}(\mathbf{x}, \beta_l))$ represents the probability of $\mathbf{x}$ being located inside the ball $B_{d_e}(\mathbf{x}, \beta_l)$.

The probability of $\mathbf{x}$ being covered by the $l$-th random ball but not by the first $l-1$ balls by process $X(\beta_l)$ is given by $P(\mathbf{x}; B_{d_e}(\mathbf{x}, \beta_l))(1 - P(\mathbf{x}; B_{d_e}(\mathbf{x}, \beta_l)))^{l-1}$. Hence, the expected number of random balls required

to cover $\mathbf{x}$ for the first time is

$$\begin{aligned}
\bar{l}(\mathbf{x}) &= \sum_{l=1}^{\infty} l P(\mathbf{x}; B_{d_e}(\mathbf{x}, \beta_l))(1 - P(\mathbf{x}; B_{d_e}(\mathbf{x}, \beta_l)))^{l-1} \\
&= P(\mathbf{x}; B_{d_e}(\mathbf{x}, \beta_l)) \frac{\mathrm{d} \sum_{l=1}^{\infty} [1 - P(\mathbf{x}; B_{d_e}(\mathbf{x}, \beta_l))]^l}{\mathrm{d}[1 - P(\mathbf{x}; B_{d_e}(\mathbf{x}, \beta_l))]} \\
&= \frac{1}{P(\mathbf{x}; B_{d_e}(\mathbf{x}, \beta_l))} \leq \frac{1}{c\beta_l^d}.
\end{aligned} \tag{47}$$

In the above calculation, we utilized the formula $\sum_{i=0}^{\infty} x^i = \frac{1}{1-x}$ for $x \in (0, 1)$, and $P(\mathbf{x}, B_{d_e}(\mathbf{x}, \beta_l)) \geq c\beta_l^d$ for all $\mathbf{x} \in B_{d_e}(\mathbf{0}, 1)$, which is a consequence of $\mathcal{P} \geq k > 0$ over $B_{d_e}(\mathbf{0}, 1)$.

The mean of the first time to cover the unit $d$-ball by random balls is the integral of the product of $\bar{l}(\mathbf{x})$ and $\mathcal{P}(\mathbf{x})$ over the unit $d$-ball, i.e.,

$$\mathcal{E}(|X_{min}|) = \int \bar{l}(\mathbf{x})\mathcal{P}(\mathbf{x})d\mathbf{x} \leq \frac{1}{c\beta_l^{d_e}}. \tag{48}$$

We now estimate the average number of samples drawn independently according to $\mathcal{P}$ and the process $X(\beta_l)$ needed to cover the unit $d_e$-ball for the first time. Leveraging the Markov inequality, we can derive an upper bound for the probability that the initial $N$ samples generated by $X(\beta_l)$ cannot cover the unit $d_e$-ball as follows:

$$P(|X_{min}| > N) \leq \frac{\mathcal{E}(|X_{min}|)}{N} \leq \frac{1}{cN\beta_l^{d_e}}. \tag{49}$$

Hence, the probability of the initial $N$ samples forming a covering is $P(|X_{min}| \leq N) \geq 1 - \frac{1}{cN\beta_l^{d_e}}$.

## G  Proof of Lemma 4

The empirical frequency of bin $p$ in the sequence $S$ is given by

$$Z_p^m(S) = \frac{1}{N} \sum_{i=1}^{N} \mathcal{I}(X_i \in p) = \frac{n_p(S)}{N}, \tag{50}$$

where $\mathcal{I}$ is the indicator function and $n_p(S)$ is the number of points in bin $p$. Applying Hoeffding's inequality to $Z_p^m(S)$ yields

$$P(|\int_p \mathcal{P}(\mathbf{x})d\mathbf{x} - \frac{n_p(S)}{N}| \geq t_p) \leq 2\exp(-2Nt_p^2). \tag{51}$$

Equivalently,

$$P(|\int_p \mathcal{P}(\mathbf{x})d\mathbf{x} - \frac{n_p(S)}{N}| < t_p) > 1 - 2\exp(-2Nt_p^2), \tag{52}$$

where the right-hand side approaches 1 as $N \to \infty$ for any fixed $t_p > 0$. More generally, the same conclusion holds for any sequence $t_p \to 0$ slower than $N \to \infty$. Hence, $\int_p \mathcal{P}(\mathbf{x})\, d\mathbf{x} = \frac{n_p(S)}{N}$ in probability as $N \to \infty$.

## H  Analysis of primary assumptions with random balls

Our earlier analysis in Lemma 2 relies on two primary assumptions. We carefully assess the conditions needed to validate these assumptions and explore their connections to the concentration results that underpin the generalization error bounds. In particular, we address the probability that random balls of a fixed radius

cover the unit $d_e$-ball densely, where $d_e$ is the effective dimension adopted here to address the curse of dimensionality in data sampling. Furthermore, we derive the concentration bound necessary for the histogram approximation assumption.

We use the random process $X(\beta_l)$ to generate centers for balls of radius $\beta_l$, one at a time. These centers are drawn independently based on the density function $\mathcal{P}$. We denote $S$ as the set of centers generated by this process, and $X_{min}(S)$ as the smallest subset of $S$ that forms a covering of the input domain with balls of radius $\beta_l$.

The first lemma below discusses the probability of a sequence covering the unit $d_e$-ball randomly for the first time, while the following lemma focuses on a concentration inequality to approximate the unknown density function using histogram approximation. The proofs of the first lemma and the second lemma are provided in Appendices F and G, respectively.

**Lemma 3.** *Assume the density function $\mathcal{P} \geq k > 0$ for some $k$ over $B_{d_e}(\mathbf{0}, 1)$. The probability of the initial $N \geq 1/(c\beta_l^{d_e})$ samples in $X(\beta_l)$ forming a cover of the unit $d_e$-ball is*

$$P(|X_{\min}| \leq N) \geq 1 - \frac{1}{cN\beta_l^{d_e}}, \tag{53}$$

*for some constant $c$ satisfying $P(\mathbf{x}, B_{d_e}(\mathbf{x}, \beta_l)) \geq c\beta_l^{d_e}$ for any $\mathbf{x} \in B_{d_e}(\mathbf{0}, 1)$ (see Eq. (6)).* ∎

The classification network $\mathcal{M}$ divides the input domain into non-overlapping regions and assigns each region a specific class. The collection of all these regions is referred to as $R_s$. We next address the concentration inequality to approximate the following term with the histogram for region $p \in R_s$:

$$\int_p P(\mathbf{x}) \, d\mathbf{x}. \tag{54}$$

In histogram approximation, $\int_p P(\mathbf{x})d\mathbf{x}$ is replaced with $\frac{n_p}{N}$, where $n_p$ is the number of training points assigned to region $p$ among $N$ total, and is a random variable determined by the sampling sequence.

**Lemma 4.** *Recall the process $X(\beta_l)$. Let $S$ be a sequence of $N$ points that forms a $\beta_l$-covering of the input domain, with $|X_{min}(S)| \leq N$. Then the following concentration inequality holds for the histogram approximation of $\int_p \mathcal{P}(\mathbf{x})d\mathbf{x}$ over any bin $p$:*

$$P(|\int_p \mathcal{P}(\mathbf{x})d\mathbf{x} - \frac{n_p(S)}{N}| \geq t_p) \leq 2\exp(-2Nt_p^2). \tag{55}$$

*If $t_p$ goes to zero at a rate slower than $N$ goes to infinity, then in the limit as $N \to \infty$, we have $\int_p \mathcal{P}(\mathbf{x}) \, d\mathbf{x} = \frac{n_p(S)}{N}$.* ∎

**Proposition 2.** *Assume $\mathcal{P} \geq k > 0$ for some $k$ over $B_d(\mathbf{0}, 1)$. Consider the random ball model $X(\beta_l)$, the assumptions of $\beta_l$-covering and the histogram approximation hold for any $\beta_l > 0$, when $N \to \infty$.* ∎

**Proof.** Using $P(A, B) = P(A)P(B|A)$ where $A = |X_{min}| \leq N$ denotes the $\beta_l$-covering of the input domain and $B = |\int_p \mathcal{P}(\mathbf{x})d\mathbf{x} - \frac{n_p}{N}| < t_p$ for any $t_p > 0$.

According to Lemma 3, $P(|X_{min}| \leq N) \geq 1$, as $N \to \infty$. Hence, the assumption of $\beta_l$-covering is affirmative. In addition, Lemma 4 asserts that the Hoeffding's inequality as described in Eq. (55) indicates that for any region and any $t_p > 0$ and $N \to \infty$,

$$P(|\int_p \mathcal{I}(\mathbf{x} \in p)\mathcal{P}(\mathbf{x})d\mathbf{x} - \frac{n_p}{N}| < t_p| \, |X_{min}| \leq N) > 1. \tag{56}$$

This means that $\int_p \mathcal{P}(\mathbf{x})d\mathbf{x} = \frac{n_p}{N}$. Hence $P(A, B) = 1$ as $N \to \infty$. Q.E.D.

**Remark.** In practice, it is useful to estimate the sample size required for the two primary assumptions to hold with high probability. We thus provide an $(\epsilon, \delta)$ PAC-type analysis to characterize this sample size requirement.

Suppose $N$ training points form a $\beta_l$-covering of $B_{d_e}(\mathbf{0}, 1)$. We let $R_s$ denote the decision regions of a network $\mathcal{M}$. Then, by a volume argument using balls of radius $\beta_l$ to cover the input domain, we obtain $N\beta_l^{d_e} \geq 1$. Combining this equation with Eq. (8), where $\frac{1}{\#W^{1/\log_2(1+\alpha(\gamma_s))}} \geq \gamma_s$, and letting $\nu = \beta_l/\gamma_s \leq 1$ denote the scaling factor of the decision partition of the network $\mathcal{M}$, we obtain

$$\frac{1}{\#W^{1/\log_2(1+\alpha(\gamma_s))}} \geq \gamma_s = \frac{\beta_l}{\nu} \geq \frac{1}{\nu}\left(\frac{1}{N}\right)^{1/d_e}. \tag{57}$$

Hence,

$$N \geq \frac{1}{\nu^{d_e}}\#W^{d_e/\log_2(1+\alpha)} \geq |R_s|. \tag{58}$$

The last inequality is a necessary condition for at least one training point in each decision region.

For a single decision region $p \in R_s$, the probability $\int_p \mathcal{P}(\mathbf{x})d\mathbf{x} \approx \frac{n_p}{N}$ can be estimated using Hoeffding's inequality,

$$P(|\int_p \mathcal{P}(\mathbf{x})d\mathbf{x} - \frac{n_p}{N}| > \epsilon) \leq 2e^{-2N\epsilon^2}. \tag{59}$$

The probability estimate is only "accurate" if all decision regions are approximated accurately simultaneously. Applying the union bound and substituting the single-bin bound, with failure probability at most $\delta$, we obtain

$$\delta = P\left(\exists q \in R_s : |\int_q \mathcal{P}(\mathbf{x})d\mathbf{x} - \frac{n_q}{N}| > \epsilon\right) \leq \sum_{p \in R_s} P(|\int_p \mathcal{P}(\mathbf{x})d\mathbf{x} - \frac{n_p}{N}| > \epsilon) \leq 2|R_s|e^{-2N\epsilon^2}. \tag{60}$$

Now, we apply Eq. (58) to bound $|R_s|$ in the above failure probability:

$$\delta \leq \frac{2}{\nu^{d_e}}\#W^{d_e/\log_2(1+\alpha)}e^{-2N\epsilon^2}. \tag{61}$$

Consequently, under the assumptions that the training points form a $\beta_l$-covering of $B_{d_e}(\mathbf{0}, 1)$ and each decision region contains at least one training point, we obtain

$$N \leq \frac{1}{2\epsilon^2}\left(\ln\left(\#W^{d_e/\log_2(1+\alpha)}\right) + \ln\frac{2}{\delta} + \ln\frac{1}{\nu^{d_e}}\right). \tag{62}$$

## I  Generalization bounds via the interpolation zone

When a network $\mathcal{M}$ operates in the interpolation zone where the training error is zero, the histogram-approximation assumption is not required to reach a result analogous to Lemma 2.

**Lemma 5.** *Let $f$ be the function $B_d(\mathbf{0}, 1) \to \{\mathbf{e}_1, \cdots, \mathbf{e}_l\}$, defined as $f = \bigcup_{i=1}^l g(i)$, where $g(i) = \{\mathbf{x}|f(\mathbf{x}) = \mathbf{e}_i\}$ is a semi-algebraic set with decision boundary $\partial f$ adhering to the stratification equations (1) and (2). Let $\gamma_s$ and $\beta_l$ represent the smallest enclosing radius and largest inscribed radius of the decision regions in $B_d(\mathbf{0}, 1)$ of the one-hot classification network $\mathcal{M}$. Assume the training data satisfies the conditions for $\beta_l$-covering the unit d-ball and there is no training error. We use the notation $|S|$ to denote the volume of the set $S$.*
*(i) For an arbitrary density function $\mathcal{P}$ on $B_d(\mathbf{0}, 1)$, the error is given by:*

$$\int_{B_d(\mathbf{0},1)} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))\mathcal{P}(\mathbf{x})\,d\mathbf{x} \leq c_{\mathcal{P}}\sum_{k=0}^{d-1}(2\gamma_s)^{d-k}|B_{d-k}(\mathbf{0}, 1)||f_k|, \tag{63}$$

*where $g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))$ is the 0/1 error, and $c_{\mathcal{P}} \in (0, 1)$ depends on the density distributed over the $2\gamma_s$-neighborhood of $\partial f$.*
*(ii) We further suppose the volume of $f_{d-1}$ is not zero. For a small value of $\gamma_s$, we can approximate the above expression as follows:*

$$\int_{B_d(\mathbf{0},1)} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x}))\mathcal{P}(\mathbf{x})\,d\mathbf{x} \leq c_{\mathcal{P}}(4\gamma_s)|f_{d-1}|. \tag{64}$$

∎

**Proof**.

The notation and deduction steps follow those in the proof of Lemma 2. The major deviation is in Eq. (24), in which calculating the error between $f(\mathbf{x})$ and $\mathcal{M}(\mathbf{x})$ with respect to training point $\mathbf{x}_p$, we can use the following equation:

$$
\begin{aligned}
g(f(\mathbf{x}), \mathcal{M}(\mathbf{x})) &= \frac{1}{\sqrt{2}} (\|f(\mathbf{x}) - \mathcal{M}(\mathbf{x}) + f(\mathbf{x}_p) - f(\mathbf{x}_p) + \mathcal{M}(\mathbf{x}_p) - \mathcal{M}(\mathbf{x}_p)\|_2) \\
&\leq \frac{1}{\sqrt{2}} (\|f(\mathbf{x}) - f(\mathbf{x}_p)\|_2 + \|f(\mathbf{x}_p) - \mathcal{M}(\mathbf{x}_p)\|_2 + \|\mathcal{M}(\mathbf{x}_p) - \mathcal{M}(\mathbf{x})\|_2) \\
&\leq g(f(\mathbf{x}), f(\mathbf{x}_p)).
\end{aligned}
\tag{65}
$$

As points in the same decision region of network $\mathcal{M}$ have the same class, the term $\|\mathcal{M}(\mathbf{x}_p) - \mathcal{M}(\mathbf{x})\|_2$ is zero. Meanwhile, $\|f(\mathbf{x}_p) - \mathcal{M}(\mathbf{x}_p)\|_2$ vanishes due to the interpolation condition, where $f(\mathbf{x}_p) = \mathcal{M}(\mathbf{x}_p)$.

Denote $\{\mathbf{x}_{p,i}\}_{i=1}^{n_p}$ as the set of $n_p$ training points in decision region $p$. By applying Eq. (65) to each training point in the region and then taking the maximum, we obtain

$$
g(f(\mathbf{x}), \mathcal{M}(\mathbf{x})) \leq \max_i g(f(\mathbf{x}), f(\mathbf{x}_{p,i})).
\tag{66}
$$

To assess the expected error for a probability distribution $\mathcal{P}$, we apply Eq. (66) to each point $\mathbf{x}$ in region $p$, and then sum over all decision regions to obtain:

$$
\begin{aligned}
\int_{B_d(\mathbf{0},1)} g(f(\mathbf{x}), \mathcal{M}(\mathbf{x})) \mathcal{P}(\mathbf{x})\, d\mathbf{x} &= \sum_p \int_p g(f(\mathbf{x}), \mathcal{M}(\mathbf{x})) \mathcal{P}(\mathbf{x})\, d\mathbf{x} \\
&\leq \sum_p \int_p \max_i g(f(\mathbf{x}), f(\mathbf{x}_{p,i})) \mathcal{P}(\mathbf{x}) d\mathbf{x} \\
&\leq \sum_p \int_p \max_i \hat{h}_f(\mathbf{x}; \|\mathbf{x} - \mathbf{x}_{p,i}\|_2) \mathcal{P}(\mathbf{x}) d\mathbf{x} \\
&\leq \int 1([2\gamma_s \geq \eta_f(\mathbf{x})]) \mathcal{P}(\mathbf{x}) d\mathbf{x}.
\end{aligned}
\tag{67}
$$

The last inequality arises from the fact that the distance between any two points within the same decision region will always be less than or equal to $2\gamma_s$. Additionally, $\hat{h}_f$ is defined in Eq. (23).

The rest of the derivations follow those of parts (i) and (ii) in the proof of Lemma 2, which we omit. Q.E.D.

This lemma is the principal mechanism underlying the scaling laws with respect to sample size and network size, as given in Theorems 1 and 2. We can thus immediately obtain analogous results by replacing the histogram-approximation assumption with the interpolation condition where the training error is zero. Consequently, the training errors in Eqs. (12) and (13) vanish. To avoid redundancy, we do not restate those results here.