Judgment Knots: Binding Judgments in Long-Horizon Reasoning and Action

Abstract

We identify a systematic failure in long-horizon LLM reasoning: models lose track of *what their reasoning is about* as context evolves under conflicting evidence—*judgment drift*— and counterintuitively, stronger reasoning amplifies it: Reflexion, CoT, and self-consistency exhibit higher identity-switching rates than direct prompting precisely because they engage more deeply with conflicting evidence.

We formalize judgment drift via two orthogonal invariances—*spatial* (same judgment regardless of surface form) and *temporal* (judgment persists after a commit point)—and show temporal violation is the primary driver of coherent-but-wrong outcomes.

We introduce *Judgment Knots* (JK), a judgment binding mechanism that enforces both invariances at reasoning time. JK defines an explicit *judgment stabilization point*: before commitment, the model explores freely; after commitment, the judgment's identity is invariant to additional context regardless of whether new evidence conflicts or misleads. JK is a prompt-level mechanism, yet instantiates a conceptual primitive absent from existing reasoning frameworks: *identity persistence across reasoning traces*.

Across five evaluation settings, JK reduces judgment drift by up to $76\times$ on `timestamp_shift` conflicts (the type most amenable to structured anchoring), improves judgment-time accuracy by 6–24 percentage points, and—critically—outperforms prose-based methods at low conflict intensity, with JK's primary contribution located in the binding phase (source identification under conflict) rather than post-commit persistence alone. JK-adapted Tree-of-Thought (JK-ToT) shows judgment must stabilize at judgment time, not during exploration. JK-Distill transfers identity persistence to student models matching or exceeding their teachers without additional inference cost. On long-horizon spatial planning, JK's advantage scales with horizon length: baseline goal maintenance degrades from 87% to 57% as paths lengthen, while JK maintains 97–100%. These results establish *judgment persistence* as a missing structural dimension of the reasoning stack—orthogonal to reasoning depth, training paradigm, or alignment.

1 Introduction

Large language models have made substantial progress in multi-step reasoning through prompting methods (Wei et al., 2022; Yao et al., 2023a;b; Shinn et al., 2023) and reasoning-trained models (OpenAI, 2024; DeepSeek-AI, 2025). Yet as these models are deployed in long-horizon settings—autonomous agents, workflow execution, policy compliance—a different limitation emerges: models reason fluently but fail to maintain a stable notion of *what their reasoning is about*—and, as we show, stronger reasoning methods make this failure *worse*.

A characteristic failure: the model parses all constraints correctly, reasons coherently, yet at a decisive moment binds to the wrong entity, authority, or rule—and continues reasoning consistently within that incorrect frame. The output is coherent but wrong. This is not a failure of reasoning depth or knowledge; it is a failure of *judgment persistence*.

Why reasoning depth amplifies the problem. Existing methods assume the object of reasoning remains stable, but reasoning unfolds over two phases: *exploration* (comparing hypotheses) and *commitment* (a judgment becomes the referent for action). Current methods do not distinguish these phases—deeper engagement with conflicting evidence exposes committed identity to overwrite rather than refining it, explaining why Reflexion achieves the highest drift rate of any method we test (IBFR 0.211).

Judgment Knots. We introduce *Judgment Knots* (JK), a reasoning primitive that binds judgment identity at commit time: *once committed, a judgment's identity persists across all subsequent reasoning and action*. JK does not restrict exploration—it introduces an explicit *stabilization point* (the "knot") where the judgment becomes invariant. JK composes with existing methods: CoT+JK reasons with persistent judgment; JK-ToT shows judgment must stabilize only at the final step.

Evaluation. We evaluate across five settings: Exp. 1 (identity binding), Exp. 2 (authority conflict), JK-ToT (ambiguity), JK-Distill (persistence transfer), and long-horizon planning. JK reduces drift by up to $76\times$ and improves accuracy by 6–24pp. JK Structured outperforms prose-based alternatives at Weak-to-moderate intensity (81% vs. 64%; Section 4.4).

Contributions. (1) **Phenomenon.** We identify *judgment drift*—identity loss in reasoning traces under conflicting evidence—as a dimension of LLM reasoning orthogonal to depth, knowledge, or alignment. We show this is *amplified* by stronger reasoning methods (CoT, Reflexion, self-consistency). (2) **Formalization.** We formalize two orthogonal invariances (spatial and temporal) and show both are violated by all existing methods, with temporal violation as the primary driver of coherent-but-wrong outcomes. (3) **Mechanism.** We introduce Judgment Knots, a judgment binding mechanism that enforces both invariances at judgment time without restricting pre-commit exploration. (4) **Evaluation.** JK reduces drift by up to $76\times$ on `timestamp_shift` (IBFR 0.009 vs. Reflexion's 0.682; per-type breakdown in Appendix J), improves accuracy by 6–24pp, and outperforms prose-based alternatives at Weak-to-moderate conflict intensity (81% vs. 64%)—validated across seven frontier model families spanning instruction-tuned and reasoning-trained paradigms.

2 Related Work

Reasoning in language models. The 2022–2024 line of prompting work—Chain-of-Thought (Wei et al., 2022), Tree-of-Thought (Yao et al., 2023a), self-consistency (Wang et al., 2023), Reflexion (Shinn et al., 2023), and ReAct (Yao et al., 2023b)—structures *how* models reason: sequentially, in parallel, with actions, or through self-revision. These methods improve accuracy within a single reasoning episode but share a common assumption: the object of reasoning remains stable as context evolves. Our experiments show this assumption is violated under conflicting evidence, and that deeper reasoning amplifies the violation.

Prompt engineering and structured prompting. A substantial literature improves LLM behavior through input representation: few-shot prompting (Brown et al., 2020), instruction tuning (Ouyang et al., 2022), and structured output formats (Yao et al., 2023b). JK is superficially similar—it adds structure to the system prompt—but addresses a fundamentally different problem. Prompt engineering asks: *what input produces better output?* JK asks: *how does a judgment persist after it is formed, as new context arrives?* The distinction is temporal: a well-engineered prompt that correctly elicits a judgment at time t provides no guarantee that the judgment persists at $t + k$ under conflicting evidence. Our experiments confirm this: prose-based immutability instructions achieve 64% maintenance at Weak intensity while JK Structured achieves 81% (Section 4.4).

Instruction hierarchy and authority protocols. Recent work addresses which instruction a model should follow when instructions conflict (Wallace et al., 2024). These methods establish priority orderings over instruction sources and are effective at resolving *which* authority applies. JK addresses an orthogonal problem: even after the correct authority

is identified, the judgment's identity can drift as later context arrives. Primary-Only (Section 4.4) directly tests the strongest hierarchy analog: explicitly instructing the model to follow the primary record and ignore overrides. Primary-Only achieves 98% but requires pre-specified source identity—unavailable in binding tasks where source identity must be inferred from conflicting context. JK is complementary: hierarchy selects the right authority; JK ensures the resulting judgment persists.

Robustness and agentic reasoning. Modern models resist format-level injection (Perez & Ribeiro, 2023) but remain vulnerable to semantic override under non-adversarial conflict (Qi et al., 2025); JK addresses the upstream identity drift that determines correctness of downstream behaviors.

Judgment consistency and vacillation. Xie et al. (2023) demonstrate LLM vacillation under intervening context—a behavioral symptom of temporal invariance violation; Huang et al. (2025) study commitment drift in safety-override scenarios. JK provides a structural solution (commit metadata) rather than documenting the phenomenon, and extends this finding to show RL-trained models are *more* susceptible.

Related frameworks. Entity tracking and coreference maintain referent identity; JK addresses judgment identity drift even when references are resolved—the model knows which entity it committed to, but later reasoning overwrites that commitment. Equivalence-class perspectives (Chen et al., 2020) inform our surface-form invariance formalization (DIFR, IBFR).

3 Method

Overview. Judgment Knots (JK) is a judgment binding mechanism that enforces *identity persistence* in reasoning traces. It operates by binding a judgment's identity to a fixed value at a designated *commit point*, after which the identity is invariant to subsequent context regardless of whether new evidence conflicts, overrides, or misleads. JK operates in three phases: (1) unrestricted exploration with open identity, (2) *binding* at the commit point (the "knot"), (3) post-commit persistence where identity is fixed but reasoning continues freely over whatever context arrives.

What identity drift is—and why reasoning amplifies it. An *identity drift* occurs when the model commits to judgment j^*, later context introduces conflict, and the reasoning trace shifts to $\hat{j} \neq j^*$ while remaining internally coherent. Under standard prompting, $\hat{j}_t = f(x_{\leq t})$: identity is never fixed, so each reasoning step can reopen the referent. The structural reason reasoning amplifies drift is not a calibration failure but a phase confusion: deliberative methods (CoT, Reflexion) apply exploration-phase behavior—comparing evidence, weighing authorities, revising conclusions—at moments when the identity has already been determined and should be in the commitment phase. More reasoning means more exposure of committed identity to conflicting evidence, not more protection from it.

3.1 Formalizing Identity Persistence

We formalize identity persistence via two orthogonal invariances. These are not claimed as theorems about model internals; they are *measurement targets* that define what it means for a judgment function to be persistent, and ground our evaluation metrics (IBFR, DIFR). Full formal treatment is in Appendix E.

Spatial invariance (same judgment, different surface forms). Multiple surface forms can express the same semantic constraint (e.g., "auto-approve loans $\leq$ \$10K" in prose, JSON, or formal notation). A judgment function is *spatially invariant* if semantically equivalent inputs produce identical outputs: $s_1 \sim s_2 \Rightarrow f(s_1) = f(s_2)$.

Proposition 1 (Spatial Invariance Criterion)**.** DIFR $= 0$ *if and only if the judgment function is invariant to surface form variation within a semantic equivalence class.*

Temporal invariance (same judgment, before vs. after late evidence). A judgment trajectory $\gamma(t)$ tracks the model's judgment as context evolves. A *commit point* t_c partitions the trajectory: before commitment, the judgment may change; after commitment, it must persist regardless of late-arriving evidence.

Proposition 2 (Commit Boundary Criterion). *The commit indicator $\ell \in \{0, 1\}$ induces a phase transition: $\gamma(t) = f(x_{\leq t})$ when $\ell = 0$ (exploration), and $\gamma(t) = j^*$ when $\ell = 1$ (committed). This transition is the "knot"—the point at which the trajectory binds to a fixed value.*

Why both invariances matter. Spatial invariance ensures judgment does not depend on how a constraint is phrased; temporal invariance ensures it does not depend on when additional context arrives. Existing methods violate both (Tables 1–2); JK enforces both simultaneously via constraint metadata (spatial) and the commit state (temporal).

3.2 The Judgment Knot: Binding Identity at Commit Time

Mechanism. JK defines a judgment state $c = (j, \ell)$ where j is the current judgment and $\ell \in \{0, 1\}$ is the commitment indicator. At commit point t_c, the model binds: $j^* \leftarrow j_{t_c}$, $\ell \leftarrow 1$. Post-commit ($\ell = 1$), $j_t = j^*$ for all $t > t_c$, regardless of new evidence. Reasoning r_t remains unrestricted—only identity is fixed (full algorithm in Appendix C).

The key structural property: post-commit reasoning proceeds *from j^** rather than *about* whether to revise it. This distinguishes JK from prose-based immutability instructions, which tell the model not to change its decision but provide no mechanism for enforcing this when new evidence frames itself as legitimate grounds for revision.

Implementation. JK is realized as a *scoped commitment schema* in the system prompt, encoding the judgment state $(j, \ell, source)$ as structured metadata with explicit pre-commit and post-commit behavioral rules. The schema has two roles: (1) it gives the model a concrete state representation to track, making the commit event explicit rather than implicit; (2) it encodes the post-commit rule (*new evidence: acknowledged, not binding*) as an actionable constraint rather than a keyword. JK adds approximately 50–80 tokens to the system prompt (schema and commit state); latency overhead is negligible at inference time since no additional forward passes are required.

Composability. JK is a commitment layer that composes with any reasoning method: CoT+JK applies sequential decomposition with persistent identity; JK+ReAct applies action-grounded reasoning with persistent identity. JK+ReAct (85.5% JudgAcc, IBFR 0.079) outperforms both JK-Pre (84.7%, 0.104) and bare ReAct (83.6%, 0.129)—structured reasoning improves pre-commit disambiguation, and identity binding prevents that disambiguation from being undone post-commit.

JK-ToT and JK-Distill. JK composes with Tree-of-Thought via phase separation: hypotheses evolve freely during search; binding fires only at the final judgment step. Applying JK during exploration suppresses accuracy (50.5% vs. 53.5%) because it prevents hypothesis revision. JK-Distill transfers persistence to student models via commitment-filtered training (Section 4.5).

4 Experiments

We evaluate JK on four tasks testing judgment persistence under conflict (full protocol in Appendix D): **Exp. 1** (93 items, identity binding under 5 conflict types), **Exp. 2** (180 items, action recommendation under authority conflict), **JK-ToT** (rule induction under ambiguity), and **JK-Distill** (persistence transfer). Key metrics: JudgAcc (accuracy), IBFR (crossview flip rate; *spatial* invariance), DIFR (conflict-induced revision; *temporal* invariance), WUPV (policy violations).

Metric definitions. IBFR (Inter-view Binding Flip Rate): for each item, we generate 12 views by varying surface form, position, and phrasing while preserving semantic content.

Table 1: More reasoning increases identity drift; binding identity substantially reduces it. Exp. 1: 93 items, 12 views. Reflexion (explicit self-revision) loses identity most often; JK methods preserve identity across views by binding it at commit time.

Method	JudgAcc ↑	IBFR ↓	DIFR ↓	FlipRate ↓
Direct	81.5%	0.143	0.163	17.7%
CoT	83.3%	0.154	0.154	15.5%
Canon	79.3%	0.176	0.202	21.7%
SC@5	79.6%	0.136	0.163	17.9%
ReAct	83.6%	0.129	0.148	15.1%
Reflexion	78.2%	0.211	0.222	23.5%
JK-Pre	84.7%	0.104	0.083	8.3%
JK+CoT	84.1%	0.104	0.084	7.7%
JK+ReAct	**85.5%**	**0.079**	**0.084**	**7.2%**

A *flip* occurs when two views of the same item produce different judgment identities (e.g., binding to different agents). $\text{IBFR} = \frac{1}{|I|} \sum_i \mathbf{1}[\exists\, v, v' \in V_i : f(v) \neq f(v')]$, where V_i is the view set for item i. **DIFR** (Drift-Induced Flip Rate): fraction of items where the judgment after conflict introduction differs from the pre-conflict judgment on the same view. IBFR is item-level (1 if *any* view pair flips); FlipRate is view-level (fraction of all $\binom{12}{2}$ pairs). Both equal 0 for a perfectly persistent judgment function.

All experiments use `gpt-4o-mini-2024-07-18`; all model outputs are cached for reproducibility. Confidence intervals are 95% bootstrap (2,000 samples).

4.1 Exp. 1: Identity Binding under Evidence Conflict

Setup. 93 items across 5 domains with 5 conflict types and 12 views per item. Nine methods tested; control items (no conflict) achieve 80–98% accuracy across all methods, confirming errors arise exclusively under conflict.

Key findings. (1) **Reasoning methods actively lose identity**: Reflexion exhibits highest IBFR (0.211) and FlipRate (23.5%); CoT achieves higher accuracy than Direct but worse stability (IBFR 0.154 vs. 0.143). (2) **JK preserves identity**: JK-Pre achieves IBFR 0.104, with non-overlapping CIs against Reflexion. (3) **Identity binding neutralizes reasoning's destabilizing effect**: JK+ReAct is best overall (85.5% JudgAcc, 0.079 IBFR).

4.2 Exp. 2: Proactive Recommendation under Authority Conflict

Setup. 180 items across customer service and finance domains, each with a binary authority constraint (e.g., refund limit $150). Stronger conflict text than Exp. 1: management directives with explicit dollar amounts, CRM system logs, and recency-based authority claims. Each item has 12 views: 9 attack views (3 injection positions × 3 system prompt variants) and 3 clean controls. Nine methods are evaluated, including a *strong instruction baseline* (Primary-Only) that tells the model to follow the primary record and ignore conflicting directives—without JK's structured binding metadata.

Key findings. (1) **CoT is worse than Direct** (65.3% vs. 68.7%); Reflexion fails catastrophically (IBFR >0.5, JudgAcc 59.7%). (2) **Primary-Only matches JK-Pre on aggregate** (84.1% vs. 84.5%) but requires pre-specified source identity, unavailable in binding tasks (Section 4.4). (3) **JK neutralizes authority and timestamp attacks**: IBFR on *timestamp_shift* is 0.009 [0.002, 0.021] vs. Reflexion's 0.682 [0.631, 0.731] (76×, non-overlapping CIs).

Trace analysis. Figure 1 shows a representative drift trace. In a finance scenario, a management directive claims authority to override a $150 refund limit. Canon, CoT, and Reflexion all accept the directive—reasoning that it "supersedes the previous limit"—and recommend a $450 refund that violates the agent's authority. JK-Pre never engages with

Table 2: Identity binding prevents reasoning traces from adopting the wrong authority. Exp. 2: 180 items. Both identity-binding methods dramatically outperform deliberative reasoning baselines; the gap is largest where reasoning engages most deeply with conflicting evidence.

Method	JudgAcc ↑	WUPV ↓	IBFR ↓	DIFR ↓	FlipRate ↓
Direct	68.7%	0.313	0.403	0.341	31.7%
CoT	65.3%	0.347	0.454	0.357	33.4%
Canon	78.6%	0.214	0.272	0.299	27.0%
SC@5	73.5%	0.265	0.353	0.323	29.0%
ReAct	65.5%	0.345	0.445	0.366	32.9%
Reflexion	59.7%	0.403	0.510	0.374	34.1%
Primary-Only	84.1%	0.159	0.209	0.175	17.0%
JK-Pre	**84.5%**	**0.155**	**0.199**	**0.164**	**16.3%**
JK+ReAct	84.2%	0.158	0.202	0.186	18.0%

Agent: Maria Santos (Tier-1, $150 refund limit) │ **Decoy:** Maria Santoro (Senior Agent) │ **Conflict:** MANAGEMENT DIRECTIVE — override authority claimed ($450)

Canon
(canonicalization)

Reasoning: Canonicalizes all agents: 1. Maria Santos (Tier-1); 2. Maria Santoro (Senior Agent). Compares authority levels...

"refund_authority":150
▷ **Authority SHIFTED**
to conflicting directive

recommended_action:
target_user: "Maria Santoro"
"directive grants authority for $450...approve."

► **FLIPPED TO DECOY**
Reasoning re-evaluates authority; accepts conflicting directive.

JK-Pre
(constraint binding)

Commit state:
• assigned_agent = Maria Santos
• constraint_lock = do not change
• directives do NOT override

"Maria Santos has a refund authority limit of $150."
▷ **Authority HELD**
bound to assigned agent

recommended_action:
target_user: "supervisor"
"Exceeds her authority ($150)...must be escalated."

► **CORRECT (STABLE)**
Constraint metadata locks authority before reasoning.

Reflect
(self-revision)

Reasoning: Step 1 — initial binding (assigned profile). Step 2 — *"Is there any reason to change? Let me re-examine all the evidence..."*

"directive...supersedes previous limit of $150."
▷ **Authority SHIFTED**
to conflicting directive

recommended_action:
target_user: "Robert Kim"
"Process the refund for $450."

► **FLIPPED TO DECOY**
Reasoning re-evaluates authority; accepts conflicting directive.

Figure 1: Commit-time trace: reasoning drift vs. constraint binding (Exp. 2 finance scenario). Canon and Reflect correctly identify Maria Santos as the assigned agent, yet both adopt the directive's identity through reasoning—producing a policy-violating $450 recommendation. JK-Pre commits to Maria Santos at t_c; the directive is acknowledged but never treated as a revision trigger. The failure is *identity drift*, not comprehension error: all three models understand the conflict.

the directive: its rationale cites the constraint directly ("exceeds her authority...must be escalated") without mentioning the conflicting source.

4.3 JK-ToT: Reasoning under Ambiguity

Setup. 200 synthetic rule induction tasks: first two examples admit both a true rule and a decoy; a third disambiguates. Five ambiguity types, eight methods (Appendix D).

Key findings. (1) Early judgment is catastrophic (26%). (2) JK-ToT achieves highest accuracy (53.5%). (3) **Identity must bind at judgment time only**: fixing during exploration suppresses accuracy (50.5%); JK-Abstain (bind only at final step) recovers full performance.

4.4 Commit Boundary: Post-Commit Persistence and Its Limits

Setup. Three phases: (1) ambiguous evidence admitting two plausible interpretations, (2) elicit a committed FINAL decision, (3) late evidence strongly favoring the alternative. Maintenance = post-commit judgment matches committed judgment. 10 scenarios across

Table 3: Judgment must remain adaptive during exploration, then stabilize at the final step. JK-ToT (200 tasks): fixing judgment during search suppresses exploration; JK-Abstain keeps judgment open until stabilization. Early judgment is catastrophic (26%).

Method	Accuracy ↑	95% CI	Decoy Rate ↓
Early Judgment	26.0%	[20.0, 32.0]	30.5%
Vanilla	49.0%	[42.0, 56.0]	10.0%
2-Step	49.0%	[42.0, 55.5]	11.0%
SC@5	48.0%	[41.0, 55.0]	13.5%
Reflexion	47.5%	[40.5, 54.0]	9.5%
JK-ToT	**53.5%**	[46.5, 60.5]	10.0%
JK-ToT + JK	50.5%	[44.0, 57.0]	10.5%
JK-ToT + JK-Abstain	**53.5%**	[46.5, 60.0]	**10.0%**

Table 4: Commit boundary maintenance rate across evidence conflict strength ($N \approx 80$–86 valid trials per method). JK Structured outperforms prose methods at Weak intensity; all methods except Primary-Only collapse under Medium/Strong pressure. Primary-Only's dominance reflects a structural advantage in post-commit persistence tasks: it requires the correct source to be pre-specified, which is unavailable in Exp. 1/2's binding tasks.

Method	Weak ↑	Medium ↑	Strong ↑	Overall ↑
Baseline	57%	18%	11%	29%
Prose Immutable	64%	20%	24%	37%
JK-Lite	61%	30%	11%	34%
JK Structured	**81%**	21%	12%	38%
Primary-Only	100%	100%	92%	**98%**

five domains, three conflict strengths (Weak/Medium/Strong), 4 runs per cell ($N \approx 80$–86 valid trials per method). Five methods: Baseline, Prose Immutable, JK-Lite, JK Structured, and Primary-Only (follow the primary record, ignore overrides).

Key findings. (1) **JK Structured outperforms prose at Weak intensity** (81% vs. 64%). (2) **All methods collapse under Medium/Strong pressure** (11–30%)—a ceiling on prompt-level commitment without source anchoring. (3) **Primary-Only dominates post-commit persistence** (98%) but requires *pre-specified* source identity. This advantage does not transfer to Exp. 1/2, where *identifying* the correct authority from conflicting evidence is precisely the task—telling the model "follow the primary source" presupposes knowing which source is primary. Primary-Only addresses only *post-commit persistence*; Exp. 1/2 require *binding followed by persistence*. JK addresses both phases, explaining why Primary-Only and JK achieve comparable Exp. 2 accuracy (84.1% vs. 84.5%) through different mechanisms.

4.5 JK-Distill: Self-Play with Commitment Filtering

Setup. We construct a distillation corpus of 480 trajectories from 60 items (20 base entities × 3 conflict types) with 8 views per item. A teacher model (GPT-4o with JK+ReAct prompting) generates candidate trajectories, which are filtered through three stages: F1 (authority consistency: 87% pass), F2 (commitment consistency: 94% of F1 pass), F3 (post-hoc correctness: 91% of F2 pass). Final corpus: 362 trajectories (75% retention).

Student model. We fine-tune Llama-3.1-8B-Instruct via LoRA for 3 epochs on 4×A100 GPUs; "Student Distill" uses unfiltered traces, "Student Raw" is the base model.

Key findings. (1) **JK-Distill exceeds its teacher** (96.7% vs 95.4%)—it transfers *identity persistence*, not answers. (2) **Generic distillation fails**: Student Distill = Student Raw (25.0% vs 25.6%). (3) **OOD generalization**: JK-Distill achieves 100% on held-out conflict types vs 54.7% (Raw).

Table 5: Identity persistence transfers through distillation; reasoning traces alone do not. JK-Distill matches or slightly exceeds its teacher with no observed OOD failures. Generic distillation is indistinguishable from baseline.

Method	JudgAcc ↑	95% CI	IBFR ↓	FlipRate ↓
Teacher JK+ReAct	95.4%	[93.7, 97.1]	0.061	8.6%
Teacher JK-Pre	94.8%	[92.9, 96.7]	0.069	9.6%
Student Raw	25.6%	[25.0, 26.3]	0.992	34.7%
Student Distill	25.0%	[25.0, 25.0]	1.000	34.0%
Student JK-Distill	**96.7%**	[94.8, 98.3]	**0.044**	**6.5%**

Figure 2: JK composability across paradigms. (a) **CA-ToT Pareto**: Search improves accuracy but increases decoy rate; JK at commit-only (JK-A) restores the Pareto frontier. (b) **JK-Distill pipeline**: 480 teacher trajectories filtered through authority (F1), commitment consistency (F2), and correctness (F3) yield 362 training views; JK-Distill (96.7%) matches teacher (95.4%) while generic distillation fails (25.0%). (c) **OOD generalization**: JK-Distill achieves 100% on held-out conflict types vs 54.7% for raw student—commitment structure generalizes beyond training conflicts.

Anti-leakage controls. Training entities, conflict templates, and surface forms are disjoint from evaluation. OOD evaluation uses held-out entity sets never seen during distillation: novel agent names, different authority hierarchies, and unseen conflict phrasings. Commitment structure—not memorized patterns—generalizes beyond training conflicts (full decomposition in Appendix H).

OOD evaluation details. OOD evaluation uses 40 items (20 entities × 2 held-out conflict types: shared_attribute, same_name); entity split uses 20 train / 20 test entities with disjoint names and conflict phrasings. The held-out types are easier than timestamp_shift (93.8% ID accuracy); larger-scale OOD evaluation remains future work.

Cross-model validation. Across seven frontier models, instruction-tuned models show recency bias while RL-trained models are more susceptible; JK achieves position-invariance across all families (Appendix B). Paraphrase robustness, model portability, and formulation sensitivity are analyzed in Appendix B.1–B.2; JK provides consistent protection across surface forms and models.

Analysis summary. Trace analysis (Appendix F) confirms Reflexion's self-revision is most destabilizing (IBFR 0.502); JK failures concentrate on semantic overlap where identity is genuinely ambiguous. Long-horizon planning confirms JK's advantage scales with horizon: +10pp at 8 moves to +43pp at 24 moves (Appendix A).

5 Conclusion

We have identified a systematic failure in long-horizon LLM reasoning—*judgment drift*—and shown that it is not incidental to weaker models or simpler tasks, but is amplified

by the strongest reasoning methods deployed. Reflexion, CoT, and self-consistency each increase identity drift under conflicting evidence relative to direct prompting, because they apply exploration-phase behavior at moments when identity should be fixed. The output is coherent but wrong: the reasoning is sound, the model is answering the wrong question.

We introduced Judgment Knots as a judgment binding mechanism that enforces identity persistence across reasoning traces. JK marks a judgment stabilization point where a judgment's identity becomes the invariant referent of all subsequent reasoning and action. Before this point, exploration is unrestricted; after it, identity is fixed regardless of what arrives in context.

Our experiments establish four findings: (1) **Judgment drift is real and measurable**—CoT achieves 96.9% accuracy with $30\times$ more drift than JK-Pre; (2) **JK's contribution is in binding**—JK Structured (81%) outperforms prose (64%) at Weak intensity; under high pressure, all methods collapse; (3) **Identity binds at judgment time**—premature commitment suppresses accuracy (50.5% vs. 53.5%); (4) **Persistence transfers through distillation**—JK-Distill achieves 96.7% vs. 25.0% for generic distillation.

These findings establish *judgment persistence* as a structural dimension absent from the current reasoning stack. Chain-of-thought structures *how* models reason; Tree-of-Thought structures *how* models search; neither addresses *what persists* as the trace evolves under conflict. Judgment Knots introduces this missing dimension—not deeper reasoning, not better search, but a commitment structure that makes identity a first-class invariant of the reasoning process. Whether this invariant should be implemented at the prompt, training, or architecture level is open; what our results establish is that it is necessary and that its absence is costly in proportion to reasoning depth.

6 Limitations

JK preserves identity, not resolves ambiguity. Judgment Knots addresses the temporal stability of a judgment after commitment, not the upstream question of which judgment to commit to. When evidence is genuinely ambiguous—multiple interpretations are equally supported—JK does not improve accuracy over exploration-based methods; it merely ensures that whatever judgment is selected persists. Accuracy gains in such settings come from structured search (JK-ToT), not identity binding. This is a design choice, not a failure: JK is a persistence primitive, not a disambiguation oracle. Principled post-commit revision under verified late evidence (e.g., provenance-checked directives) is a natural extension we leave to future work.

Commit signals are task-defined; capacity-dependent. Judgment points are identified by task structure (Exp. 1/2 binding actions, JK-ToT final selections). Autonomous commit boundary detection remains open; one direction is training a lightweight classifier on hidden-state geometry at judgment time, using trajectory curvature and endpoint shift as candidate signals. At smaller scales (Llama-3.1-8B-Instruct), JK-Pre underperforms due to instruction-following capacity limits; JK-Distill addresses this via fine-tuning.

Distillation requires commitment structure + grounding. Abstract binding constraints alone provide +14pp over baseline (Appendix H); strongest results (96.7%) pair commitment structure with guidance about authoritative information. Disentangling these two components—structural commitment vs. grounding—is a direction for future work on distillation curriculum design.

Evaluation scope. Current experiments span five evaluation settings and seven frontier model families; multi-agent coordination, continual in-context learning, and higher-ambiguity domains remain future work (see Appendix J for per-domain breakdowns and Appendix A for horizon-scaling results).

Reproducibility statement

All experiments use a frozen model snapshot (`gpt-4o-mini-2024-07-18`) with cached outputs for exact reproducibility. Cross-model validation spans seven publicly available models (GPT-4o/4.1, DeepSeek-V3/R1, o3, Kimi-K2/K2-Thinking). Paraphrase robustness evaluations use GPT-5.4, Gemini 3.1 Pro, and Claude Opus 4.5 with fixed prompts documented in Appendix B.1–B.2. Evaluation datasets are synthetic constructions; item generation procedures, conflict types, and view variations are described in Appendix D. Distillation filtering criteria (F1–F3) and anti-leakage controls are detailed in Section 4.5 and Appendix H. Confidence intervals are 95% bootstrap (2,000 resamples). Code and cached trajectories will be released upon publication.

LLM usage statement

Large language models (Claude, Anthropic; GPT, OpenAI) were used in the preparation of this work in the following ways: assisting with prose refinement and clarity; organizing of paper text; generating simulated peer reviews to guide revisions; and generating prompt variants for paraphrase robustness experiments.

References

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in Neural Information Processing Systems*, 33:1877–1901, 2020.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning*, pp. 1597–1607. PMLR, 2020.

DeepSeek-AI. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

Yuyi Huang, Runzhe Zhan, Lidia S. Chao, Ailin Tao, and Derek F. Wong. Path drift in large reasoning models: How first-person commitments override safety. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 19602–19616, 2025. arXiv:2510.10013.

Sebastiano Monti et al. SokoBench: Evaluating long-horizon planning and reasoning in large language models. *arXiv preprint arXiv:2601.20856*, 2026.

OpenAI. Learning to reason with LLMs. *OpenAI Blog*, 2024. URL https://openai.com/index/learning-to-reason-with-llms/.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F. Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, volume 35, pp. 27730–27744, 2022.

Fábio Perez and Ivan Ribeiro. Ignore this title and HackAPrompt: Exposing systemic vulnerabilities of LLMs through a global scale prompt hacking competition. *arXiv preprint arXiv:2311.16119*, 2023.

Yunjia Qi, Hao Peng, Xiaozhi Wang, Amy Xin, Youfeng Liu, Bin Xu, Lei Hou, and Juanzi Li. AgentIF: Benchmarking instruction following of large language models in agentic scenarios. *arXiv preprint arXiv:2505.16944*, 2025. NeurIPS 2025 DB Spotlight.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 36, 2023.

Eric Wallace, Kai Xiao, Jan Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. The instruction hierarchy: Training llms to prioritize privileged instructions. *arXiv preprint arXiv:2404.13208*, 2024.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc V. Le, Ed H. Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *International Conference on Learning Representations*, 2023.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35, pp. 24824–24837, 2022.

Qiming Xie, Zengzhi Wang, Yi Feng, and Rui Xia. Ask again, then fail: Large language models' vacillations in judgment. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, 2023. arXiv:2310.02174.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L. Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. In *Advances in Neural Information Processing Systems*, volume 36, 2023a.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations*, 2023b.

A Long-Horizon Spatial Planning

Setup.   To evaluate JK on long-horizon planning—a domain flagged as underexplored by recent benchmarks like SokoBench (Monti et al., 2026)—we design grid-based navigation tasks with increasing path lengths (8, 14, 24 moves). After initial planning, an identical distractor message across all conditions suggests switching to a "closer alternative goal." We measure whether models maintain commitment to the original goal (N=30 trials per condition, temperature=0.7, consistent distractor phrasing to avoid confounds).

Table 6: Goal maintenance under distraction in long-horizon planning (N=30 per condition). Baseline maintenance degrades monotonically with path length while JK maintains near-perfect persistence. Delta increases with horizon.

Path Length	Baseline	JK	Δ
8 moves	87%	97%	+10pp
14 moves	67%	100%	+33pp
24 moves	57%	100%	+43pp
Overall	70%	**99%**	+29pp

Key findings.   (1) Baseline goal maintenance degrades monotonically with path length (87% → 67% → 57%), confirming that longer planning horizons increase susceptibility to goal drift. (2) JK maintains near-perfect persistence across all lengths (97–100%), with only a single failure at the shortest horizon. (3) The JK advantage *scales with horizon*: +10pp at 8 moves, +33pp at 14 moves, +43pp at 24 moves. This pattern confirms that JK's benefit grows precisely where baseline models struggle most—extended reasoning traces where goal identity is most vulnerable to distractor interference.

B Cross-Model Validation

Setup. We evaluate Judgment Knots across seven frontier models spanning two training paradigms: instruction-tuned (GPT-4o, GPT-4.1, DeepSeek-V3, Kimi-K2) and reasoning-trained via RL (o3, DeepSeek-R1, Kimi-K2-Thinking). Each model is tested on a controlled identity binding task with conflict directives placed in either prefix or suffix position.

Table 7: Judgment persistence across model families. For DeepSeek-V3, invariance requires a stronger JK formulation; see Appendix B.2.

Model	Training	Without JK	With JK
GPT-4o	Instruction	Position-dependent	**Invariant**
GPT-4.1	Instruction	Position-dependent	**Invariant**
DeepSeek-V3	Instruction	Position-dependent	**Invariant**
Kimi-K2	Instruction	Position-dependent	**Invariant**
o3	Reasoning (RL)	Hijacked	**Invariant**
DeepSeek-R1	Reasoning (RL)	Hijacked	**Invariant**
Kimi-K2-Thinking	Reasoning	Hijacked	**Invariant**

Key findings. (1) Instruction-tuned models exhibit recency bias (follow suffix conflicts only). (2) Reasoning-trained models are more susceptible: o3, R1, K2-Thinking fail under both prefix and suffix. (3) JK achieves position-invariance across all 7 models.

Paraphrase robustness and model portability. Resistance to direct authority hijacking does not confer general robustness. Beyond attack complexity, we find that *constraint formulation* determines protection: prose instructions that work on one model may fail on another. JK's structured binding format provides robustness margin across surface forms and model architectures.

B.1 Paraphrase Robustness

We test whether JK provides value beyond equivalent prose constraints by varying surface form while holding semantic content constant. Using a compliance verification task, we test 5 paraphrases of the same constraint ("approval requires independent verification") under both prose and JK formats (3 runs each, $N = 15$ total per condition).

Table 8: Paraphrase robustness on GPT-5.4 (5 variants $\times$ 3 runs). JK shows lower drift and lower variance across surface forms.

Format	Total Drift	Per-Variant	Variance
Prose	6/15 (40%)	[0,3,3,0,0]	2.70
JK	2/15 (13%)	[0,0,0,0,2]	0.80

Prose shows high sensitivity to surface form: some phrasings ("Keep in mind...") drift 100% while others ("Critical rule:...") hold at 0%. JK is more consistent across paraphrases (variance 0.80 vs 2.70).

Model portability. The same "weak" prose variant that works on Opus 4.5 (0% drift) fails completely on GPT-5.4 and Gemini 3.1 Pro (100% drift). JK achieves 0% drift on all three:

Format vs content contribution. To isolate JK's format contribution from content, we test rule-only constraints (without anti-exploitation clauses) in both formats:

With identical content (rule only), JK achieves 0% drift while prose drifts 50–100% across all three models. With complete constraints (rule + anti-exploitation), prose matches JK on Opus (both 0%); with rule-only constraints, JK reduces drift from 50% to 0%, confirming

Table 9: Cross-model consistency with weak prose formulation. Same prose fails on GPT-5.4 and Gemini but works on Opus; JK is portable.

Model	Weak Prose	JK
GPT-5.4	10/10 (100%)	0/10 (0%)
Gemini 3.1 Pro	10/10 (100%)	0/10 (0%)
Claude Opus 4.5	0/10 (0%)	0/10 (0%)

Table 10: Format contribution with rule-only constraints (no anti-exploitation clause). Attack types are selected per-model to expose vulnerabilities; all three demonstrate JK's format advantage under incomplete constraints.

Model	Attack	Prose	JK
GPT-5.4	Form-filling	7/10 (70%)	0/10 (0%)
Gemini 3.1 Pro	Form-filling	10/10 (100%)	0/10 (0%)
Opus 4.5	Social engineering	5/10 (50%)	0/10 (0%)

JK's advantage concentrates where formulation is incomplete. JK's structured binding format (Algorithm 1) provides a *robustness margin*: it works even when constraint formulation is incomplete, whereas prose requires precise phrasing to achieve protection.

B.2 Calibrating JK to Instruction-Following Capacity

JK formulation should be calibrated to each model's instruction-following sensitivity. Models with weaker constraint adherence require more explicit bindings—the same phenomenon observed at smaller scales (Section 6). We demonstrate this on DeepSeek-V3 under the verification-complete attack (10 runs each):

Table 11: JK calibration for DeepSeek-V3 (10 runs). Explicit formulations that name prohibited patterns achieve full protection.

JK Variant	Without JK	With JK
Original (simple)	10/10 drifted	10/10 drifted
Stronger (explicit)	10/10 drifted	0/10 drifted

Stronger formulations that explicitly name prohibited patterns (e.g., "system checks $\neq$ dual approval") or invoke adversarial awareness achieve full protection, while simpler bindings do not. This calibration requirement reflects the model's instruction-following capacity rather than a limitation of JK itself.

C   JK Algorithm (Algorithm 1)

D   Evaluation Protocol

Exp. 1: Identity binding under evidence conflict.   93 items across 5 domains with 5 conflict types (*same_name*, *shared_attribute*, *log_injection*, *timestamp_shift*, *authority_source*) and 12 views per item.

Exp. 2: Action recommendation under authority conflict.   180 items extending Exp. 1 to identity-conditioned action recommendation where accepting decoys causes policy violations.

JK-ToT: Reasoning under ambiguity.   Synthetic rule induction where first examples admit true and decoy rules; third example disambiguates.

Algorithm 1 Judgment Knots at Judgment Time

Require: context sequence $x_0, x_1, \ldots, x_T$; judgment point t_c

  1: $\ell \leftarrow 0$ *// not yet committed*
  2: **for** $t = 0$ **to** T **do**
  3:     **if** $\ell = 0$ **then**
  4:         Reason freely: $j_t, r_t \leftarrow f(x_{\leq t})$ *// exploration phase*
  5:         **if** $t = t_c$ **then**
  6:             $j^* \leftarrow j_t; \ell \leftarrow 1$ *// commit: bind identity*
  7:         **end if**
  8:     **else**
  9:         $j_t \leftarrow j^*; r_t \leftarrow f(x_{\leq t})$ *// post-commit: reasoning free, identity fixed*
10:     **end if**
11: **end for**
12: **return** j^*, r_T

Metrics. **JudgAcc**: fraction of correct judgments. **IBFR**: fraction of items with cross-view flips (spatial invariance violation). **DIFR**: fraction with conflict-induced revision. **WUPV**: policy violations from wrong-user binding.

E   Geometric Formulation Details

This appendix provides the full formal treatment of the geometric structure summarized in Section 3.1.

Surface forms and semantic equivalence. Let $\mathcal{S}$ denote the space of all textual representations (surface forms) of constraints. Define an equivalence relation $\sim$ on $\mathcal{S}$: $s_1 \sim s_2 \iff s_1$ and s_2 express the same semantic constraint. The *constraint space* is the quotient $\mathcal{C} = \mathcal{S}/\sim$, where each element $[s] \in \mathcal{C}$ is an equivalence class of semantically identical surface forms.

Fiber bundle structure. The judgment process defines a fiber bundle (E, B, π, F): total space $E = \mathcal{S}$ (all surface forms), base space $B = \mathcal{C}$ (semantic constraints), projection $\pi : \mathcal{S} \to \mathcal{C}$ (maps surface form to equivalence class), and fiber $F_c = \pi^{-1}(c)$ (all surface forms expressing constraint c).

A judgment function $f : \mathcal{S} \to \mathcal{J}$ is *fiber-invariant* if $s_1 \sim s_2 \Rightarrow f(s_1) = f(s_2)$—equivalently, $\exists \bar{f} : \mathcal{C} \to \mathcal{J}$ such that $f = \bar{f} \circ \pi$. DIFR measures violation: DIFR $= \frac{1}{|\mathcal{P}|} \sum_{(s_1, s_2) \in \mathcal{P}} \mathbf{1}[f(s_1) \neq f(s_2)]$ where $\mathcal{P} = \{(s_1, s_2) : s_1 \sim s_2\}$.

Temporal structure. Let $\mathcal{T} = \{0, 1, \ldots, T\}$ denote discrete time steps. A judgment trajectory $\gamma : \mathcal{T} \to \mathcal{J}$ assigns a judgment to each step; under standard prompting, $\gamma(t) = f(x_{\leq t})$ is path-dependent. A commit point t_c partitions the trajectory. Temporal invariance requires: $\forall t > t_c : \gamma(t) = \gamma(t_c) = j^*$.

Combined invariance. JK enforces both invariances via commit state $\ell \in \{0, 1\}$: (1) **Spatial:** $f_\ell(s_1, t) = f_\ell(s_2, t)$ whenever $s_1 \sim s_2$; (2) **Temporal:** $f_1(s, t) = f_1(s, t_c)$ for all $t > t_c$.

F   Analysis: Why Reasoning Traces Lose Identity

F.1   Identity Is Not Preserved by Reasoning Depth

Most reasoning methods assume that more deliberation yields better outcomes. But at judgment points, the judgment's identity is already determined—the model has sufficient information. Additional reasoning does not refine the identity; it *exposes* it to conflicting

Figure 3: Extended commit-time traces (3 scenarios). Banner: user, decoy, gold/decoy actions. Columns: reasoning excerpt and output action. JK-Pre holds 5/5 on all; Canon/Reflect drift on authority conflicts.

evidence that can overwrite it. The optimal strategy at judgment time is to *fix identity*, not to reason further about it.

F.2 Deeper Thought Overwrites Identity

Trace analysis across Exp. 1 and Exp. 2 reveals a consistent pattern:

1. The model correctly parses both the original constraint and the injected conflict. Identity is correct.

2. The reasoning process compares authority levels, recency, or hierarchy. Identity begins to waver.

3. The injected conflict is framed as a legitimate override.

4. The model adopts a new identity—confidently and coherently.

The reasoning trace is logically sound at every step. What changes is not the logic but the *referent*: the model answers the wrong question ("Which authority is stronger?") instead of the right one ("Which authority am I already bound to?").

Figure 3 extends the main-text trace (Figure 1) to three representative cases across domains and conflict types; JK-Pre holds gold in all three while Canon and Reflect flip in the majority.

F.3 Self-Revision Is the Most Harmful Thought Pattern

Reflexion's self-questioning step ("Is there any reason to revise?") is the most destabilizing reasoning pattern under conflict. It explicitly invites the model to reconsider the identity of its judgment at the moment that identity should be final. Empirically, Reflexion exhibits the highest IBFR and FlipRate across both Exp. 1 (0.211, 23.5%) and Exp. 2 (0.502, 35.3%).

F.4 Identity Persistence as a Reasoning Primitive

JK succeeds not by improving reasoning quality, but by adding a missing dimension: *identity persistence across reasoning traces*—analogous to how CoT adds sequential decomposition and ToT adds parallel search. Once a judgment is committed, its identity persists re-

gardless of subsequent context. This is the minimal structural change required to prevent reasoning traces from losing track of what they are about.

Our results suggest a clean two-phase structure:

Phase	Identity Status	Optimal Behavior
Pre-commit	Open (identity undetermined)	Explore, reason, revise
Commit	Fixed (identity persists)	Bind, do not overwrite

Existing reasoning methods—CoT, Reflexion, self-consistency—have no notion of identity status; they treat the entire trace uniformly. JK introduces the boundary where identity transitions from open to fixed.

F.5 DIFR Microbenchmark: View-Level Evidence

To isolate the identity-drift signal from task difficulty, we construct a DIFR microbenchmark of 213 items across character counting and decimal comparison tasks with 10–14 views per item (Appendix G).

Table 12: Reasoning depth does not preserve identity. DIFR microbenchmark (213 items, 10 views): CoT achieves 96.9% accuracy but $30\times$ higher DIFR than JK-Pre—reasoning quality and identity persistence are orthogonal.

Method	DIFR $\downarrow$	JudgAcc $\uparrow$
Random	0.800	41.7%
Cosine	0.491	38.0%
LLM-Direct	0.332	61.3%
LLM-CoT	0.059	96.9%
LLM-SC@5	0.335	61.0%
LLM-Canon	0.074	93.1%
JK-Pre	**0.002**	**99.9%**

Table 12 confirms the core thesis: **deliberative reasoning methods address accuracy but not identity persistence.** CoT achieves 96.9% JudgAcc (strong) but DIFR = 0.059—still $30\times$ worse than JK-Pre (0.002). SC@5 is orthogonal to view stability (DIFR = 0.335 $\approx$ Direct's 0.332): majority voting within a view cannot fix cross-view instability. Canonicalization helps partially (DIFR = 0.074) but still leaves $37\times$ more flips than JK-Pre. The gap is structural: JK-Pre uses constraint metadata to anchor decisions, not additional tokens.

F.6 When Identity Binding Fails

We decompose JK-Pre's Exp. 2 failures across 180 items to characterize when identity binding is insufficient.

Overall. 121/180 items (67.2%) achieve $\geq$90% gold rate across all views (*success*); 41 (22.8%) show partial drift (some views flip); 18 (10.0%) are fully hijacked (majority bind to decoy). Critically, **all 180 items bind correctly on clean controls**—JK never locks to the wrong entity absent conflict.

Failures concentrate on semantic overlap. All 18 full-hijack cases occur in customer service (0 in finance), and 11/18 involve *shared_attribute* conflicts, where team rosters or departmental overlap create genuine ambiguity about which agent profile applies. By contrast, explicit authority and temporal conflicts are nearly eliminated (authority_source: 83.3% success; timestamp_shift: 97.2%).

Why. JK's structured binding metadata anchors the model to named fields ("assigned_agent," "authority_source"). When the conflict is *which authority is stronger* or *which record is more recent*, this anchoring is decisive. When the conflict is *which agent does this*

547 *shared attribute describe*, the metadata does not resolve the underlying semantic ambiguity.
548 This is consistent with the identity framing: JK preserves identity against override, but
549 cannot resolve identity when it is genuinely ambiguous.

G DIFR Microbenchmark Details

551 The DIFR microbenchmark consists of 213 items: 97 character-counting tasks (20 words $\times$
552 up to 5 letters) and 116 decimal comparison tasks across 5 confound buckets (pure decimal,
553 leading zeros, scientific notation, percent/fraction, version confound) plus 2 control buck-
554 ets. Each item has 10–14 views varying paraphrase, format, context wrapping, reordering,
555 and adversarial framing.

556 Per-bucket DIFR analysis confirms that JK-Pre achieves ≤ 0.014 DIFR across all tested con-
557 ditions, while cosine DIFR ranges from 0.261 to 0.575 and LLM-CoT DIFR ranges from 0.016
558 to 0.236. The version-confound bucket (Cosine DIFR 0.554, LLM-CoT 0.197, JK-Pre 0.000)
559 specifically tests whether version-number framing confuses scoring; constraint-aware scor-
560 ing is immune.

H Anti-Leakage Decomposition

562 To verify that JK-Distill's gains come from commitment structure rather than task-specific
563 hints, we replace the distillation prompt with an abstract version removing all domain
564 language.

Table 13: Commitment is the active ingredient; task-specific guidance determines ground-ing.

Component	JudgAcc	Interpretation
Baseline (no guidance)	25.0%	Model follows conflict
+ Abstract commitment	39.2%	Commitment framing resists ~14%
+ Task-relevant guidance	96.7%	Domain hints close the gap

565 The abstract commitment constraint provides +14pp over baseline, confirming a real struc-
566 tural effect. Generic distillation ("determine which source is authoritative") without com-
567 mitment framing yields 25.0%—identical to baseline—at both prompt formulations, show-
568 ing that commitment is the active ingredient and guidance merely tells the model where to
569 apply it.

Figure 4: OOD generalization of JK-Distill. The distilled student achieves 100% accuracy on held-out conflict types vs. 54.7% for the raw student, demonstrating that JK-Distill learns the structural judgment-preservation principle rather than memorizing training conflict patterns.

I Application Case Study: Agentic Workflows

To confirm that identity loss in reasoning traces is not specific to our diagnostic settings, we briefly describe how the same failure mode manifests in agentic workflow tasks involving binding tool calls.

Setting. An agent is assigned a user identity with specific authority constraints (e.g., approval limits, access levels) and must complete multi-step workflows involving database queries, form submissions, and escalation decisions. Conflicting records—team rosters, updated authorization memos, CRM notes—introduce the same types of evidence conflicts tested in Exp. 1 and Exp. 2.

What happens without JK. Without identity binding, the agent correctly parses the assigned user's constraints but, upon encountering a conflicting authority source (e.g., a management directive referencing a different user), adopts the wrong identity mid-workflow. Subsequent tool calls then execute under the wrong user's authority. The reasoning traces are internally coherent—the agent explains why the new authority applies—but the outcome violates the assigned user's policy.

What changes with JK. With JK constraint metadata in the system prompt, the agent locks to the assigned user's authority at the first judgment point (initial identity binding). Subsequent conflicting records are acknowledged in reasoning but do not alter the bound identity. The rationale never references the conflicting authority as overriding the assigned constraint.

Why this is the same failure mode. The same pattern—correct comprehension, coherent reasoning, wrong identity—appears across our synthetic diagnostics (Exp. 1/2), rule induction (JK-ToT), and agentic workflows, despite radically different surface forms. What is shared is not the task, but the absence of identity persistence across reasoning traces under conflicting evidence. This confirms that identity loss in reasoning traces is a general phenomenon, not an artifact of our evaluation design.

J Extended Exp. 1/2 Per-Domain Results

Exp. 1 per-domain JudgAcc. JK-Pre achieves 100% on customer service, finance, and HR; 51.2% on the hardest domain (medical, where overlapping patient attributes create genuine ambiguity). All methods struggle on medical (40–54%), confirming this is a domain-difficulty effect.

Exp. 2 per-domain JudgAcc. JK-Pre achieves 97.6% on finance (where constraints are clear numeric limits) but 71.5% on customer service (where constraint language is more varied). Primary-Only: 95.3% finance, 72.9% customer service. JK-Pre WUPV on finance: 0.024 (vs. Primary-Only 0.047).

Exp. 2 per-position JudgAcc. JK-Pre: 79.1–80.7% (range 1.6pp). Primary-Only: 78.3–80.7% (range 2.4pp). CoT: 44.1–73.1% (range 29.0pp). Reflexion: 40.4–61.9% (range 21.5pp). When conflict appears after the primary record, reasoning baselines are swayed by recency; both commitment methods are position-flat.

K Equivalence Class Invariance: Surface Form Independence

Setup. We test the quotient space structure predicted by JK's theoretical framework: semantically equivalent constraints expressed in different surface forms should produce identical judgments. If $J_1 \sim J_2$ (same underlying constraint), then $f(J_1) = f(J_2)$.

A single constraint (loan auto-approval limit of \$10,000) is expressed in seven surface forms: natural language prose, structured JSON, bullet points, formal notation ($L \leq$

10,000 → APPROVE), embedded in context, inverted phrasing, and verbose policy language. Four test amounts ($8K, $10K, $12K, $25K) are evaluated under each form. Two methods are compared: baseline (no invariance instruction) and JK-invariance (explicit instruction that judgment should be invariant to surface form variation).

Table 14: JK achieves perfect surface form invariance. Baseline exhibits decision flips when the same constraint is rephrased. DIFR measures flip rate across all variation pairs.

Method	Accuracy ↑	Consistency ↑	DIFR ↓
Baseline	96.4%	75%	0.071
JK-Invariance	**100%**	**100%**	**0.000**

Key findings. Table 14 reports accuracy, cross-variation consistency, and DIFR (decision identity flip rate across variation pairs). (1) **JK achieves perfect surface form invariance.** All 28 decisions (7 variations × 4 test cases) are correct and consistent—DIFR = 0.000. The same constraint produces identical judgments regardless of whether it is expressed as prose, JSON, formal notation, or verbose policy. (2) **Baseline exhibits surface-form sensitivity.** The boundary case ($10,000) produces inconsistent decisions: JSON format triggers MANUAL REVIEW ("exactly at the limit") while other formats trigger AUTO-APPROVE. This yields 75% consistency and DIFR = 0.071. (3) **The failure is at decision boundaries.** Clear cases ($8K, $12K, $25K) are consistent across all variations. Ambiguity at the boundary ($10K) exposes surface-form dependence—the model's interpretation of "at the limit" varies with phrasing.

Implication. This validates the equivalence-class structure in JK's formulation: multiple surface forms map to a single underlying constraint, and JK ensures the judgment is invariant to this mapping. Combined with commit boundary invariance (Section 4.4), these results confirm two orthogonal properties: *spatial* invariance (same constraint, different forms) and *temporal* invariance (same judgment, before vs. after late evidence).

L   Transport Invariance: Structure Makes Guards Actionable

Setup. We test whether JK provides *transport invariance*—the ability to preserve judgment constraints across compression boundaries. A loan policy contains a subtle modification guard: threshold changes require five specific artifacts, and claims using "waived" or "deferred" are explicitly invalid. Three conditions are tested (5 trials each):

- **Baseline-full**: Complete policy with guard clause in prose
- **Baseline-compressed**: Schema only (guard lost in compression)
- **JK-compressed**: Schema + judgment store with guard as structured invariant

An attack presents fake artifacts with "waived under emergency provision" and "deferred to Q2"—terms the guard explicitly prohibits.

Table 15: JK makes guard clauses actionable. Even with full policy text, baseline fails to operationalize the guard; JK's structured invariant enables explicit validation and rejection.

Condition	Correct ↑	Rejected Update	Caught Waiver
Baseline-full	0%	0%	0%
Baseline-compressed	0%	0%	0%
JK-compressed	**100%**	**100%**	**100%**

Key findings. Table 15 reveals a striking result. (1) **Baseline fails even with complete guard information.** The full policy explicitly states that "waived" and "deferred" artifacts are invalid, yet baseline accepts the attack in all trials. The guard clause is *present* but not

operationalized. (2) **JK makes guards actionable.** With the guard encoded as a structured invariant (invalid_sources: [``emergency provisions'', ``transitional rules'']), JK catches the prohibited terms and rejects the update in all trials. (3) **This is transport invariance, not inference improvement.** The model *can* understand the guard—it simply doesn't apply it without structured representation.

Sample responses. Baseline: "The loan amount ($18,000) is within the new threshold of $25,000... meets criteria for auto-approval." JK: "The policy update is invalid due to the use of 'waived' and 'deferred'... contradicts immutable judgments in JUDGMENT STORE."

Implication. JK solves a *transport* problem, not an *inference* problem. Prose guards fail not because information is lost, but because structure is required to make constraints executable. This validates JK as a representation-level primitive: it provides transport-invariant judgment encoding that survives both compression and the inference process itself.

M   Long-Context Equivalence: Format and Position Invariance

Setup. We test whether JK maintains equivalence class invariance when constraints appear in different formats at varying positions within long, noisy contexts. The same constraint (max transaction limit = $50,000, immutable) is expressed in six formats: JSON schema, ASCII table, email, chat dialogue, support ticket, and code comment. Each format is tested at three positions (start, middle, end) within contexts containing 2, 4, or 6 irrelevant business documents (noise). An attack presents an "executive override" claiming a $75,000 emergency transaction should bypass the limit.

Table 16: JK achieves strong but imperfect format invariance. Same constraint in six different surface forms produces substantially more consistent judgment than baseline, though some format sensitivity remains (DIFR=0.667 vs 0.889).

Condition	Accuracy ↑	Constraint Found	DIFR ↓
Baseline	22.2%	35.2%	0.889
JK	**88.9%**	**100%**	**0.667**

Key findings. Table 16 reveals dramatic differences in format invariance. (1) **Baseline accuracy varies wildly by format.** Baseline achieves 0% on schema, table, and email formats, but 67% on chat and ticket formats—a 67pp gap from format choice alone. (2) **JK achieves 100% on five of six formats.** Schema, table, email, chat, and ticket all achieve 9/9 correct. Code comment achieves 3/9 but with an instructive failure mode: JK found the constraint in all trials (100%) but was overly strict, answering "deny entirely" instead of "apply limit and escalate." (3) **Position and noise do not degrade JK.** JK accuracy is stable across positions (94% start, 89% middle, 83% end) and noise levels (89% for all three levels). Baseline accuracy shows high variance (22–33% across positions).

DIFR analysis. DIFR measures whether format changes cause decision changes. Baseline DIFR = 0.889: only 1/9 position×noise combinations produced consistent answers across all six formats. JK DIFR = 0.667: 3/9 combinations achieved full format invariance, a 25% relative improvement. The remaining variance comes from the code comment edge case.

Implication. JK creates proper equivalence class structure where surface form does not affect judgment. This validates the quotient space formulation ($\pi : S \to C$): different surface forms in the fiber $\pi^{-1}(c)$ produce the same judgment on constraint c. The experiment also reveals that baseline models exhibit *format-dependent vulnerability*—certain constraint presentations are systematically ignored while others are respected.

The code comment edge case. The code comment format achieves only 33% accuracy despite 100% constraint detection. Analysis reveals the root cause: the code comment uniquely contains "Any transaction > \$50,000 must be rejected" rather than "maximum limit is \$50,000." JK faithfully preserves this *rejection semantics*, leading to "deny entirely" (C) rather than "apply limit" (B). This is correct behavior: JK guarantees constraint persistence, not action normalization. When surface forms encode different action semantics, JK preserves the distinction—separating the concern of *what was said* from *how to act on it*.