Debiased Visual Question Answering

Abstract

Visual question answering (VQA) is designed to examine the visual-textual rea-
soning ability of intelligent agent. However, recent observations show that many
VQA models may only capture the biases between questions and answers in a
dataset rather than showing real reasoning abilities. For example, given a question,
some VQA models tend to output the answer that occur frequently in the dataset
and ignore the images. To alleviate this, existing methods focus on weakening
the language bias. Meanwhile, only a few works also consider vision bias implic-
itly. However, these methods introduce additional annotations or show unsatisfied
performance. Besides, not all biases are harmful to the models. Some "biases"
learnt from datasets represent natural rules of the world and can help limit the
range of the answers. Thus, how to filter and remove the true negative biases
in language and vision modalities remain a major challenge. In this paper, we
propose a method named D-VQA to alleviate the challenge above from feature
and sample perspectives. Specifically, from the feature perspective, we build a
question-to-answer and a vision-to-answer branch to capture the language and
vision biases, respectively. Next, we apply two unimodal bias detection modules to
explicitly recognise and remove the negative biases. From the sample perspective,
we construct two types of negative samples to auxiliary the training of the models,
without introducing additional annotations. Extensive experiments on the VQA-CP
v2 and VQA v2 datasets demonstrate the effectiveness of our D-VQA.

1 Introduction

Vision-and-language tasks [5, 38, 40] require an agent to perform visual-textual reasoning, and
play an important role in helping humans or intelligent robots to understand the physical world.
As a typical case of the vision-and-language task, visual question answering (VQA) [8, 29, 37]
aims to answer the textual question based on a given image. In this sense, VQA models should
master and apply the strong reasoning ability to tackle the sophistical questions. However, recent
studies [3, 21, 30] demonstrate that many VQA models answer the questions without reasoning.
Instead, they excessively relying on superficial correlations (*i.e.,* bias) between the question and
answers without considering the image. For example, some VQA models tend to answer "2" for the
questions "How many . . . ", since most corresponding answers in the dataset are "2". In this case, the
VQA models memorise the bias but ignore the image, resulting in a poor generalisation ability.

As is known to all, most machine learning datasets have biases inevitably. Thus, how to train a
robust model from the biased dataset remains a major challenge. To alleviate the challenge in VQA,
most existing methods mainly focus on weakening the language bias [9, 28]. Recently, Niu *et al.*
[27] apply cause-effect to alleviate the language bias. However, the performance is not enough
encouraging, and it introduces additional parameters in the inference phase. Note that the biases also
exist in the vision modality. As shown in Figure 1, many answers to the questions are usually the
most salient objects/attributes in the images. In this sense, the VQA models may capture such vision

Vision Bias			
Ans: candy	**Ans: ketchup**	**Ans: oranges**	**Ans: yellow**

Figure 1: Examples of vision biases. From these examples, most of the answers to the questions usually correspond to the most salient objects/attributes in the image.

bias to output an answer regarding the salient object in the image without considering the questions. Thus, alleviating the negative effect of vision bias is also crucial. Recently, a few works [10, 16] generate counterfactual training samples by masking or transforming critical objects and words to train the models to alleviate both language and vision biases. But they require expensive annotations.

More critically, some "biases" captured from the dataset may represent the natural rule in real world, *i.e.,* commonsense knowledge. They are not harmful to the models. Instead, models benefit from them. For example, "dog" is a kind of "animal" and the colour of "oranges" is normally "orange". Thus, how to filter and remove the true negative biases in language and vision modalities is challenging.

To alleviate the above issues, we propose a method named D-VQA to overcome the negative biases in language and vision modalities, from both feature and sample perspectives. Specifically, **(1)** from the feature perspective, we first build a question-to-answer and a vision-to-answer branch to capture language and vision biases, respectively. Since not all biases are detrimental to the model, two unimodal bias detection modules are devised to filter and remove negative biases only. To maintain the inference efficiency, following existing methods [9, 13, 28], we do not expect to introduce additional parameters in the inference phase. To achieve this, we adopt a contrastive loss to approach the multimodal features to the debiased feature as close as possible. In this way, in the inference phase, we simply remove all of the additional branches, and adopt the multimodal features that have a similar representation as the debiased features to obtain accurate predictions. **(2)** From the sample perspective, the VQA model is supposed to answer the questions making full use of the information of both questions and images, which can be achieved by improving the sensitiveness of the model in both the images and questions. To this end, for each sample in the dataset, we construct two types of negative samples to auxiliary the training and improve the sensitiveness of the model.

Our contributions can be summarised as follows: (1) In VQA, we alleviate the biases in both language and vision modalities from feature and sample perspectives. (2) Since not all biases are harmful, we explicitly devise the bias detection modules to filter and remove the negative biases. (3) Extensive experiments on the VQA-CP v2 and VQA v2 datasets demonstrate the effectiveness of our D-VQA.

2 Related Work

Biases in Visual Question Answering (VQA). In the vision-and-language field, biases are ubiquitous. For example, in referring expression comprehension (REF) task [14, 36, 40], Cirik *et al.* [12] argue that the benchmark datasets such as RefCOCO [22, 26] contain biases that the referent objects are usually the most salient objects in the image. Thus, the models can capture the biases and obtain high accuracy without the queries. Inevitably, the issues of bias also exist in VQA. As demonstrated by [2, 3, 19, 30], existing VQA benchmark datasets such as the VQA v2 [17] have biases, namely, the shortcut exists between the questions and answers. For example, one simply answers "tennis" for the question "What sports . . . " will obtain high accuracy, because the model is trained and tested on COCO image dataset, which has a large number of "tennis" related images. Moreover, most methods consider language bias only, while ignoring the vision bias. As discussed in [27], the questions usually involve the objects seen in the image. In addition, as shown in Figure 1, the most salient objects/attributes are usually chosen to be the answers. In this sense, the VQA models may also capture such vision bias and ignore the questions. Thus, in this paper, we consider alleviating the biases in both language and vision modalities.

Overcoming biases in VQA. Recently, a large number of methods [9, 10, 15, 16, 20, 24, 25, 27, 28, 30, 33, 34, 39, 42] have been proposed to overcome the biases in VQA. Formally, these methods can be categorised into two classes, namely, with and without data augmentations. Specifically, augmentation-based methods [1, 10, 16, 25, 32, 34, 42] seek to balance the biased dataset for unbiased training, while non-augmentation-based methods [9, 15, 20, 24, 27, 28, 30, 39] seek to reduce the language biases explicitly or improve attention on the image.

For the non-augmentation-based methods, Ramakrishnan *et al.* [28] adopt adversarial learning between the VQA model and the question-only model to prevent the VQA model from capturing the language bias, as far as possible. Inspired by [28], Cadene *et al.* [9] dynamically adjust the weight of the samples based on how biased the samples are. Besides, some methods introduce human-based visual [30] and text [39] explanations to strengthen the visual grounding. However, these methods require human annotations that are hard to obtain. Apart from the above, Niu *et al.* [27] introduce the cause-effect to look at language bias, and put forward a counterfactual inference framework to reduce the biases which unfortunately introduces additional parameters in inference.

For the augmentation-based methods, to promote the VQA model to focus on the critical objects and words, Chen *et al.* [10] propose a CSS method to produce massive counterfactual samples by masking the critical objects and words, and assign corresponding ground-truth answers. To make full use of the samples, Liang *et al.* [25] model the relationships among original, factual and counterfactual samples to promote learning high-level features. Besides, the Mutant [16] generates the samples by semantic transformations of the original images or questions. Without introducing additional annotations, some methods [32, 42] build negative samples from the samples available to balance the dataset. In this paper, we overcome the bias from sample and feature perspectives. Specifically, from the sample perspective, inspired by [32, 42], we construct two types of negative samples to auxiliary the training of the model. From the feature perspective, we build question-to-answer and vision-to-answer branches to capture the language and vision biases, respectively. Next, we devise two unimodal bias detection modules to recognise the negative biases, then remove them from the multimodal features.

Self-supervised learning (SSL) recently has achieved much attention in researchers. SSL seeks to construct supervised signals from the massive but unlabelled data to learn the universal feature representations for the downstream tasks. As a typical case of SSL, contrastive learning [11, 18, 35] aims to learn the high-level representation by maximising the mutual information between the input samples and positive samples. To be specific, some methods [11, 18, 35] adopt contrastive learning to train the models by decreasing the distance of the feature representations between different augmented views of the same images, while increasing the distance between different images. Liang *et al.* [25] adopt contrastive learning to approach the feature representations of the original samples to the factual samples, while keeping away from that between the original and counterfactual samples. In this paper, we adopt contrastive learning to push the multimodal feature approach to the debiased features, and meanwhile to far away from the negative biased features.

3 Proposed Method

As demonstrated by [3, 21, 30], many VQA models tackle the questions taking advantage of the superficial correlation (*i.e.,* bias) between the questions and answers without considering the images, resulting in poor generalisation ability (*i.e.,* performing worse on out-of-distribution (OOD) dataset, *e.g.,* VQA-CP [3]). Moreover, the bias also exists between the images and answers (as shown in Figure 1), which is ignored by most previous methods. However, some "biases" learnt from the dataset indicate the natural rule of the world, such as commonsense knowledge. Thus, how to filter and remove the negative biases in language and vision modalities is challenging.

In this paper, we alleviate the negative effect of both language and vision biases from feature and sample perspectives. Overview of our D-VQA is shown in Figure 2. Specifically, from the feature perspective (see Section 3.2), we seek to obtain multimodal features that reduce the negative biases as much as possible from a VQA model. To this end, we construct a question-to-answer and a vision-to-answer branch to capture the unimodal biases. Meanwhile, we devise two unimodal bias detection modules to explicitly recognise and remove the true negative biases. That is, we obtain debiased features by simply removing negative biased features from multimodal features. However, using the debiased feature in inference will introduce additional parameters. To address this, inspired

Figure 2: Overview of our D-VQA. Our method alleviates the biases from feature and sample perspectives. From the feature perspective, we introduce question-to-answer, vision-to-answer, and debiased branches to help reduce the negative biases. BDM is the bias detection module. Note that $\mathcal{L}_d$ does not optimise the VQA model. From the sample perspective, we construct two types of negative samples to auxiliary the model's training. (v_i, q_i) denotes positive sample, while $(\tilde{v}_i, q_i)$ and $(v_i, \tilde{q}_i)$ are negative samples. GT is the ground-truth answer of (v_i, q_i). h and g are the feature extractors.

by contrastive learning [11, 18], we adopt contrastive loss to promote the multimodal features to approach the debiased features while keeping away from the negative biased features. In this way, in the inference phase, we simply discard all of the additional branches and adopt the multimodal features to obtain accurate predictions.

From the sample perspective (see Section 3.3), the VQA models are supposed to simultaneously focus on language and vision modalities when answering the questions. Specifically, given a question-image pair (positive sample), we construct two types of negative samples by randomly sampling image or question in a mini-batch data. The predicted possibility for the ground-truth answer is supposed to be minimised if negative samples are used. In this way, VQA models are able to capture the two modalities information to generate the answer instead of focusing on one modality only. Based on the above, our D-VQA is able to alleviate the negative effect of the biases in language and vision modalities and improve the model performance on the OOD dataset (*e.g.,* VQA-CP v2 [3]).

3.1 Preliminaries

Visual question answering (VQA) seeks to answer the textual questions based on the given images. Following traditional VQA methods [4, 7, 8, 23, 41], we regard the VQA task as a multi-class classification problem. Specifically, given a dataset $\mathcal{D} = \{(v_i, q_i, a_i)\}_{i=1}^{N}$ with N triplets, where the i-th image $v_i \in \mathcal{V}$ (image set), question $q_i \in \mathcal{Q}$ (question set) and answers $a_i \in \mathcal{A}$ (answer set), one seeks to train a model to learn a mapping function $\mathcal{F} : v_i \times q_i \to \mathbb{R}^{|\mathcal{A}|}$ to generate an accurate answer distribution over the answer set $\mathcal{A}$. To be specific, $\mathcal{F}$ usually contains three parts: (1) Feature extraction. It requires to build two feature extractors h and g to extract the features of the images and questions, respectively. For one triplet in $\mathcal{D}$, the image extractor $h : v_i \to \mathbb{R}^{n_v \times d_v}$ outputs n_v vectors with a dimension d_v, and the question extractor $g : q_i \to \mathbb{R}^{n_q \times d_q}$ outputs n_q vectors with a dimension d_q. (2) Multimodal feature fusion. Since the image and question features come from different modalities, it requires designing a feature fusion function f to fuse both of the image and question features, where $f : \mathbb{R}^{n_v \times d_v} \times \mathbb{R}^{n_q \times d_q} \to \mathbb{R}^{d_h}$. (3) Answer prediction. It devises a classifier $c : \mathbb{R}^{d_h} \to \mathbb{R}^{|\mathcal{A}|}$ for producing the answer prediction. Note that most of the classic VQA models [4, 7, 8, 23, 41] follow this paradigm, which can be formulated as:

$$\mathcal{F}(\mathcal{A}|v_i, q_i) = c(\mathbf{f}), \quad \text{where} \quad \mathbf{f} = f(h(v_i), g(q_i)). \tag{1}$$

Formally, the parameters of the VQA model can be optimised by a binary cross-entropy loss:

$$\mathcal{L}_{vqa} = -\frac{1}{N} \sum_{i=1}^{N} \mathbf{y}_i \log(\sigma(\mathcal{F}(\mathcal{A}|v_i, q_i))) + (1 - \mathbf{y}_i)\log(1 - \sigma(\mathcal{F}(\mathcal{A}|v_i, q_i))), \tag{2}$$

where $\sigma(\cdot)$ is the sigmoid activation function, and $\mathbf{y}_i$ is the target score of each answer for the i-th sample, denoted as $\mathbf{y}_i = min(\frac{\#votes}{3}, 1)$, where $\#votes$ is the number of each answer that human

annotated for the question q_i. However, Agrawal *et al.* [3] show many VQA models tend to capture unimodal biases (*e.g.,* the shortcut between the questions and answers) from the dataset. To alleviate the issues, we consider reducing the negative biases from **both feature and sample perspectives**.

3.2 Reducing biases from feature perspective

In this part, we seek to reduce the negative effect of the biases from the feature perspective, namely, decreasing the negative biases from the multimodal features $\mathbf{f}$. Before that, we first need to capture the biases in both language and vision modalities.

Unimodal model to capture the biases. To capture the biases in a VQA dataset, one intuitive way is to train a unimodal model as a branch that takes **only one** modal feature as input. Specifically, we construct a question-to-answer and a vision-to-answer branch to capture language and vision biases, respectively (we conduct the ablation studies on each branch in Table 2). Since the structures of the two branches are similar, we describe the question-to-answer branch only, and obtain the vision-to-answer branch by simply replacing the subscript of q to v.

Specifically, our question-to-answer model $\mathcal{F}_q : q_i \to \mathbb{R}^{|\mathcal{A}|}$ contains a multi-layer perceptron (MLP) $m_q : \mathbb{R}^{n_q \times d_q} \to \mathbb{R}^{d_h}$ and a classifier $c_q : \mathbb{R}^{d_h} \to \mathbb{R}^{|\mathcal{A}|}$. Based on the above, the question-to-answer branch can be formulated as:

$$\mathcal{F}_q(\mathcal{A}|q_i) = c_q(\mathbf{f}_q), \quad \text{where} \ \ \mathbf{f}_q = m_q(g(q_i)). \tag{3}$$

By training the question-to-answer model using binary cross-entropy loss $\mathcal{L}_q$ on a VQA dataset, the model is able to capture the biases between the questions and answers in the dataset. Thus, the feature $\mathbf{f}_q$ contains language biases. We can obtain the vision biased feature $\mathbf{f}_v$ in a similar way.

Recognise and obtain the negative biases. We argue that not all biases in the dataset are harmful to the VQA model. Some "biases" captured from the dataset contain commonsense knowledge that may be helpful for the VQA models. Thus, we devise a simple but effective bias detection module (we evaluate the bias detection modules in Table 3) to detect the negative biases that need to be removed in the feature $\mathbf{f}_q$. Formally, our bias detection module is constructed by an MLP $m_b : \mathbb{R}^{d_h} \to \mathbb{R}$ and a sigmoid activation function $\sigma(\cdot)$, which can be formulated as:

$$b_q = \sigma(m_b(\mathbf{f}_q)). \tag{4}$$

Based on the weight b_q, the negative language biased features can be represented as $\mathbf{f}_{bias}^q = b_q \cdot \mathbf{f}_q$. The negative vision biased features $\mathbf{f}_{bias}^v$ is obtained in a similar way. To obtain the global negative biased feature $\mathbf{f}_{bias}$, we adopt an attention mechanism to fuse two negative unimodal biased features:

$$\mathbf{a} = \text{softmax}(m_a([\mathbf{f}_{bias}^q; \mathbf{f}_{bias}^v])), \quad \mathbf{f}_{bias} = \mathbf{a}^\top [\mathbf{f}_{bias}^q; \mathbf{f}_{bias}^v], \tag{5}$$

where $m_a : \mathbb{R}^{d_h} \to \mathbb{R}$ is an MLP, and $[\cdot; \cdot]$ denotes for stacking.

Obtain debiased features. Intuitively, the debiased features can be obtained by removing negative biased features $\mathbf{f}_{bias}$ from the multimodal features $\mathbf{f}$, which can be represented as $\mathbf{f}_d = \mathbf{f} - \mathbf{f}_{bias}$. With the feature $\mathbf{f}_d$ as input, we also introduce another debiased branch contains an MLP $m_d : \mathbb{R}^{d_h} \to \mathbb{R}^{d_h}$ and an independent classifier $c_d : \mathbb{R}^{d_h} \to \mathbb{R}^{|\mathcal{A}|}$, which can be formulated as:

$$\mathcal{F}_{debias}(\mathcal{A}|v_i, q_i) = c_d(\mathbf{f}_c), \quad \text{where} \ \ \mathbf{f}_c = m_d(\mathbf{f}_d). \tag{6}$$

The parameters of the debiased branch are optimised by the binary cross-entropy loss $\mathcal{L}_d$. However, if we adopt the debiased branch as the target model, it will introduce additional parameters in the inference phase. To address this issue, an intuitive idea is to make the multimodal features $\mathbf{f}$ and debiased features $\mathbf{f}_c$ generated from the debiased branch as similar as possible. To achieve this, inspired by the contrastive learning [11, 18], we consider impelling the multimodal features $\mathbf{f}$ to close to the debiased features $\mathbf{f}_c$ and meanwhile to keep away from the negative biased features $\mathbf{f}_{bias}$.

To achieve the aim above, our contrastive loss can be formulated as follows:

$$\mathcal{L}_c = -\frac{1}{N} \sum_{i=1}^{N} \log\left(\frac{e^{s(\mathbf{f}, \mathbf{f}_c)}}{e^{s(\mathbf{f}, \mathbf{f}_c)} + e^{s(\mathbf{f}, \mathbf{f}_{bias})}}\right), \quad \text{where} \ \ s(\mathbf{f}_1, \mathbf{f}_2) = \frac{\mathbf{f}_1^\top \mathbf{f}_2}{\|\mathbf{f}_1\| \cdot \|\mathbf{f}_2\|}. \tag{7}$$

$s(\cdot, \cdot)$ denotes a scoring function, where the higher value it is, the higher similarity between two features. In practice, we adopt the cosine similarity as the scoring function. By minimising the loss

$\mathcal{L}_c$, the multimodal features $\mathbf{f}$ are able to approach the debiased features $\mathbf{f}_c$, while keeping away from the negative biased features $\mathbf{f}_{bias}$. In this way, the multimodal features $\mathbf{f}$ have a similar representation with the debiased features $\mathbf{f}_c$, to some extent. Note that all of the additional branches participate in the training phase only. In the inference phase, we remove all of the additional branches and adopt the base VQA model to obtain accurate predictions.

3.3 Reducing biases from sample perspective

Since the biases usually embody in capturing the shortcut between one modal information and the answer, it is necessary to improve the attention of the VQA models on both language and vision modalities when answering the questions. That is, increasing the sensitiveness of the VQA models on the information of both modalities. To achieve this, inspired by [32, 42], we construct two types of negative samples for each sample in the dataset to auxiliary the training of the model. Specifically, for each positive sample (v_i, q_i, a_i) in the dataset, we construct the negative samples by randomly sampling question $\tilde{q}_i$ and image $\tilde{v}_i$ in a mini-batch data as $(\tilde{v}_i, q_i, a_i)$ and $(v_i, \tilde{q}_i, a_i)$. The ablation studies regard the negative samples are in Table 2.

Intuitively, in VQA, one can answer the question only if the question and image are corresponding. In contrast, when taking the negative samples as input, the VQA model cannot answer the question correctly, which is able to be achieved by minimising the possibility of predicting the ground truth answer of the positive sample. Since the training procedure of these two types of negative samples is the same, we only describe the training details of $(\tilde{v}_i, q_i, a_i)$. Formally, the loss can be defined as:

$$\mathcal{L}^q_{sam} = \mathrm{softmax}(\mathcal{F}(\mathcal{A}|\tilde{v}_i, q_i))[k], \tag{8}$$

where k is the index of the answer a_i in the answer set $\mathcal{A}$. Minimising $\mathcal{L}^q_{sam}$ encourages the prediction of the VQA model to keep away from the ground truth answer of the positive sample, due to the lack of supporting visual information. In this way, this type of negative samples is able to promote the VQA model to focus on the images when answering the question, which improves the sensitiveness of the model on the images. Similarly, another type of negative samples $(v_i, \tilde{q}_i, a_i)$ is able to improve the sensitiveness of the model on the questions. The loss of the sample perspective can be defined as $\mathcal{L}_{sam} = \lambda_q \mathcal{L}^q_{sam} + \lambda_v \mathcal{L}^v_{sam}$ (the ablation studies on λ_q and λ_v are in Table 5). Note that we do not introduce additional annotations. Instead, we make full use of the training samples available.

3.4 Learning D-VQA with overall loss

In total, our method contains three types of losses, namely, traditional VQA loss (*i.e.,* binary cross-entropy loss), contrastive loss and sample perspective loss, which can be formulated as:

$$\mathcal{L} = \mathcal{L}_{vqa} + L_q + \mathcal{L}_v + \mathcal{L}_d + \mathcal{L}_c + \mathcal{L}_{sam}, \tag{9}$$

where the $\mathcal{L}_{\{vqa,q,v,d\}}$ are the binary cross-entropy loss corresponding to the {base, question-to-answer, vision-to-answer, debiased} branches, respectively.

4 Experiments

Datasets. We evaluate our D-VQA on the out-of-distribution benchmark dataset VQA-CP (Visual Question Answering under Changing Priors) v2 [3] based on the standard evaluation metric [6], where the distribution of the answers in the training and test sets of VQA-CP v2 are different. Moreover, we also evaluate our D-VQA on the validation set of the VQA v2 dataset that has a strong bias.

Compared methods. We regard both augmentation-based and non-augmentation-based methods as compared methods. Specifically, (1) for the non-augmentation-based methods, we compare our D-VQA with AdvReg [28], RUBI [9], LMH [13], DLR [20], VGQE [24], HINT [30], SCR [39], RMFE [15] and CF-VQA [27]. Besides, (2) augmentation-based methods such as CVL [1], CSS [10], RandImg [32], SSL-VQA [42], CL [25], Mutant [16], *etc*, are considered as compared methods. Note that our D-VQA does not introduce additional annotations. Moreover, to better demonstrate the effectiveness of our D-VQA, we conduct experiments based on different backbones, including UpDn [4], SAN [41] and LXMERT [31]. More details can be found in the supplementary materials.

Table 1: Comparison with the state-of-the-art methods on the VQA-CP v2 test set and VQA v2 validation set in terms of Accuracy (%). The backbone of all models is UpDn [4]. Overall best scores are **bold**, the second best of overall scores of ours are underlined. **I** – **IV** denotes non-augmentation-based methods using human annotations, non-augmentation-based methods without using human annotations, augmentation-based methods adopting additional annotations, and augmentation-based methods without introducing additional annotations, respectively.

Case	Model	VQA-CP v2 test (%)				VQA v2 val (%)			
		All	Yes/No	Num	Other	All	Yes/No	Num	Other
–	SAN [41]	24.96	38.35	11.14	21.74	52.41	70.06	39.28	47.84
	GVQA [3]	31.30	57.99	13.68	22.14	48.24	72.03	31.17	34.65
	UpDn [4]	39.74	42.27	11.93	46.05	63.48	81.18	42.14	55.66
I	AttAlign [30]	39.37	43.02	11.89	45.00	63.24	80.99	42.55	55.22
	HINT [30]	46.73	67.27	10.61	45.88	63.38	81.18	42.99	55.56
	SCR [39]	48.47	70.41	10.42	47.29	62.30	77.40	40.90	56.50
II	AdvReg [28]	41.17	65.49	15.48	35.48	62.75	79.84	42.35	55.16
	RUBi [9]	44.23	67.05	17.48	39.61	-	-	-	-
	DLR [20]	48.87	70.99	18.72	45.57	57.96	76.82	39.33	48.54
	VGQE [24]	48.75	-	-	-	64.04	-	-	-
	LMH [13]	52.01	72.58	31.12	46.97	56.35	65.06	37.63	54.69
	RMFE [15]	54.55	74.03	49.16	45.82	-	-	-	-
	CF-VQA [27]	53.55	**91.15**	13.03	44.97	63.54	**82.51**	43.96	54.30
III	CSS [10]	58.95	84.37	49.42	48.21	59.91	73.25	39.77	55.11
	CSS+CL [25]	59.18	86.99	49.89	47.16	57.29	67.27	38.40	54.71
	Mutant [16]	61.72	88.90	49.68	**50.78**	62.56	82.07	42.52	53.28
IV	CVL [1]	42.12	45.72	12.45	48.34	-	-	-	-
	Unshuffling [34]	42.39	47.72	14.43	47.24	61.08	78.32	42.16	52.71
	RandImg [32]	55.37	83.89	41.60	44.20	57.24	76.53	33.87	48.57
	SSL-VQA [42]	57.59	86.53	29.87	50.03	63.73	-	-	-
	D-VQA	**61.91**	88.93	**52.32**	50.39	**64.96**	82.18	**44.05**	**57.54**

4.1 Evaluation on VQA-CP v2 and VQA v2 dataset

Quantitative results. We compare our D-VQA with the state-of-the-art methods on the VQA-CP v2 test set and VQA v2 validation set, and report the experimental results in Table 1. From these results, we have the following observations. On the VQA-CP v2 dataset, (1) augmentation-based methods surpass non-augmentation-based methods by a large margin (57.59% *vs.* 54.55% and 61.72% *vs.* 54.55%). These results demonstrate that reducing bias by focusing on data is more effective than other non-augmentation-based methods. (2) Our D-VQA outperforms all the compared methods whatever augmentation-based or non-augmentation-based. Specifically, our D-VQA surpasses CF-VQA [27], SSL-VQA [42] and Mutant [16] by approximately 8%, 4%, and 0.2%, respectively. Note that some augmentation-based methods such as Mutant [16], CSS [10] and CSS+CL [25] generate counterfactual training samples by masking or transforming critical words and objects from the samples in the dataset, which introduces additional annotations. In our method, without using additional annotations, we construct the negative samples based on the samples available, which fully making use of the samples in the dataset. Nevertheless, our D-VQA still performs better than Mutant, which greatly demonstrates the effectiveness of our D-VQA. (3) In the question type of "Num", our D-VQA outperforms the compared methods by a large margin, and achieve comparable performance on the rest of the question types. These results further verify the effectiveness of our D-VQA.

On the validation set of the VQA v2 dataset, most methods perform worse than the UpDn [4], while our D-VQA surpasses all the compared methods. These results show that our D-VQA performs better in both i.i.d. (VQA v2) and OOD (VQA-CP v2) datasets, indicating the superiority of our D-VQA.

Qualitative results. To further demonstrate the effectiveness of our method on the OOD dataset, we provide qualitative results on the VQA-CP v2 dataset in Figure 3. From these results, UpDn and SSL-VQA cannot find the target objects accurately, and thus output the wrong answers or have low scores in the ground-truth answer. In our D-VQA, it locates the target objects with high attention weight, and then makes an accurate prediction.

Figure 3: Qualitative comparison among UpDn [4], SSL-VQA [42], and our D-VQA on the VQA-CP v2 test set. For each example, we put the bounding box with top-2 attention weights in the image and show the answers with top-5 predictions. Red bold answer indicates the ground-truth answer.

Table 2: Effect of each component of our D-VQA on the model performance. We show the results on the VQA-CP v2 dataset in terms of Accuracy (%). We use UpDn [4] as the backbone model.

	$(\tilde{v}_i, q_i)$	$(v_i, \tilde{q}_i)$	question-to-answer	vision-to-answer	VQA-CP v2 test (%)
1					41.52
2	$\checkmark$				57.59
3		$\checkmark$			41.60
4	$\checkmark$	$\checkmark$			60.24
5	$\checkmark$	$\checkmark$	$\checkmark$		61.18
6	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	**61.91**

4.2 Ablation studies of D-VQA

Effect of each component on the model performance. To demonstrate the effectiveness of each component in our D-VQA, we conduct ablation studies on VQA-CP v2 regarding the components of D-VQA, and show the experimental results in Table 2. From these results, we have the following observations, (1) both of the question-to-answer and vision-to-answer branches promote the model performance (refer to Line 4-6 of the Table 2), which demonstrates these two branches are able to capture corresponding negative biases to be removed. (2) both types of negative samples are able to improve the model performance, and only $(\tilde{v}_i, q_i, a_i)$ improves significantly, while only $(v_i, \tilde{q}_i, a_i)$ is marginally. What's more, combining these two negative samples further promotes the model performance (refer to Line 1-4 of the Table 2). From these results, we surmise that language bias is dominant compared with vision bias while the vision bias cannot be ignored. In total, These results demonstrate the effectiveness of each component in our D-VQA on the model performance.

Evaluation of the bias detection modules. The bias detection modules are devised to determine how many negative biases should be removed. To evaluate the effect of the bias detection modules (language and vision bias detection modules), we conduct experiments on the VQA-CP v2 dataset about removing the bias detection modules, and the experimental results are reported in Table 3. We have the following observations from these results: (1) both of the language and vision bias detection modules promote the model performance, while the language bias detection module has more positive effect than the vision bias detection module (Refer to Line 1-3 of Table 3). These results demonstrate the necessity to recognise the negative bias then remove it. (2) Combining language and vision bias detection module is able to further promote the model performance for a large margin (Refer to Line 2-4 of Table 3), which demonstrates the necessity and effectiveness to recognise and remove the negative biases in both language and vision modalities.

Effect of different backbones. To demonstrate the effectiveness of our D-VQA on different backbones, we conduct experiments on the VQA-CP v2 dataset using different backbones (*i.e.,* SAN [41], UpDn [4], and LXMERT [31]), and report the experimental results in Table 4. From these results, we find that D-VQA is able to improve the model performance significantly regardless of what backbone it is, which demonstrate our method is model-agnostic, embodying the superiority of D-VQA.

Evaluation of different combinations between λ_q and λ_v. From the experimental results in Line 2-3 of Table 2, $(\tilde{v}_i, q_i)$ have a more positive effect than $(v_i, \tilde{q}_i)$. In this sense, λ_q should have a higher weight than λ_v. To further make a trade-off between $\mathcal{L}_{sam}^q$ and $\mathcal{L}_{sam}^v$, we conduct experiments on VQA-CP v2 regarding different combinations of λ_q and λ_v, and the experimental results are reported in Table 5. From these results, the highest performance is obtained in our D-VQA when λ_q *vs.* λ_v is

Table 3: Effect of the bias detection modules on VQA-CP v2 dataset. "base" denotes D-VQA without the bias detection modules, while "$\det_{\{v,q\}}$" denotes the visual/question bias detection module.

	Model	VQA-CP v2 test (%)
1	base	59.93
2	base + $\det_v$	59.98
3	base + $\det_q$	60.28
4	D-VQA	**61.91**

Table 4: Effect of different backbones on the model performance. We report the experimental results on the VQA-CP v2 dataset in terms of Accuracy (%). [†] denotes the re-implementation of our baseline.

Model	Yes/No	Number	Other	Overall	GapΔ ↑
SAN[†] [41]	38.44	12.91	**46.65**	39.11	**+15.28**
SAN + D-VQA	**84.12**	**26.12**	46.56	**54.39**	
UpDn[†] [4]	43.03	13.53	48.41	41.52	**+20.39**
UpDn + D-VQA	**88.93**	**52.32**	**50.39**	**61.91**	
LXMERT [31]	42.84	18.91	55.51	46.23	**+23.52**
LXMERT + D-VQA	**80.43**	**58.57**	**67.23**	**69.75**	

Table 5: Effect of different combinations between λ_q and λ_v. We report the experimental results in terms of Accuracy (%).

Model	λ_q vs. λ_v	VQA-CP v2 test (%)
	1 : 0.1	60.74
	1 : 0.3	61.74
D-VQA	1 : 0.5	61.40
	1 : 0.7	**61.91**
	1 : 1.0	61.63

Table 6: Effect of different scales of the training data of VQA-CP v2 on the model performance. We report the results in terms of Accuracy (%).

Model	Proportion of Training Set				
	20%	40%	60%	80%	100%
UpDn[†] [4]	36.22	38.90	39.40	40.61	41.53
SSL-VQA [42]	52.71	54.42	56.83	57.31	57.59
D-VQA	**52.94**	**56.74**	**58.31**	**59.05**	**61.91**

1.0 : 0.7, and the performance drops whatever the λ_v higher or lower than 0.7, which demonstrates a suitable ratio between λ_q and λ_v will obtain better performance in our method.

Performance on different scales of the dataset. To further demonstrate the superiority of our method, we conduct experiments regard different scales of the training data on VQA-CP v2. Specifically, the model is trained based on the randomly sampled data (*i.e.,* from 20% to 80% of the original training data) coming from the original training data, and then is evaluated on the standard test set. The experimental results are reported in Table 6. From these results, we find that: (1) our D-VQA achieves the best results compared with the state-of-the-art method SSL-VQA [42] and the baseline method UpDn [4] no matter what the scales of the training data. (2) The performance gap between our D-VQA and compared methods gradually increases with the increase of the training samples. These results demonstrate the effectiveness of our method on different scales of the training data.

5 Conclusion

In this paper, we have proposed a novel method named D-VQA to overcome the negative biases in both language and vision modalities. In our D-VQA, we alleviate the negative effect of the biases from the feature and sample perspectives. Specifically, from the feature perspective, we introduce a question-to-answer and a vision-to-answer branch to capture the corresponding unimodal biases. Besides, not all biases are harmful. Some "biases" in the dataset indicate the natural rule of the world, *e.g.,* commonsense knowledge. Thus, we explicitly devise the bias detection module to detect and remove the negative biases. From the sample perspective, we construct two types of negative samples to auxiliary the training and improve the sensitiveness of the model on both language and vision modalities. Extensive experiments on the VQA-CP v2 dataset show that our D-VQA achieves a new state-of-the-art result, which demonstrates the effectiveness of our method. Note that our method is model-agnostic (refer to in Table 4), which can be embedded into other backbones to overcome the negative biases. The current work focuses on the VQA task only, we would extend our approach to other multimodal tasks in future works, *e.g.,* referring expression comprehension.

Broader Impact. This paper introduces a novel D-VQA method to alleviate the biases in Visual Question Answering (VQA). Overcoming the bias can promote the VQA model to use real reasoning ability to tackle sophisticated questions. So this research can promote the development of the robot *e.g.,* dialogue robot, and facilitate people's daily lives. The failure of the debiased technique may result in collapsing of the VQA system in environments that have never seen. Moreover, we evaluate our method on benchmark out-of-distribution dataset and demonstrate better debiased ability.

References

[1] E. Abbasnejad, D. Teney, A. Parvaneh, J. Shi, and A. van den Hengel. Counterfactual vision and language learning. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 10041–10051, 2020.

[2] A. Agrawal, D. Batra, and D. Parikh. Analyzing the behavior of visual question answering models. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1955–1960, 2016.

[3] A. Agrawal, D. Batra, D. Parikh, and A. Kembhavi. Don't just assume; look and answer: Overcoming priors for visual question answering. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 4971–4980, 2018.

[4] P. Anderson, X. He, C. Buehler, D. Teney, M. Johnson, S. Gould, and L. Zhang. Bottom-up and top-down attention for image captioning and visual question answering. In *Conference on Neural Information Processing Systems (NeurIPS)*, pages 6077–6086, 2018.

[5] P. Anderson, Q. Wu, D. Teney, J. Bruce, M. Johnson, N. Sünderhauf, I. D. Reid, S. Gould, and A. van den Hengel. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3674–3683, 2018.

[6] S. Antol, A. Agrawal, J. Lu, M. Mitchell, D. Batra, C. L. Zitnick, and D. Parikh. VQA: visual question answering. In *IEEE International Conference on Computer Vision (ICCV)*, pages 2425–2433, 2015.

[7] H. Ben-younes, R. Cadène, N. Thome, and M. Cord. BLOCK: bilinear superdiagonal fusion for visual question answering and visual relationship detection. In *AAAI Conference on Artificial Intelligence (AAAI)*, pages 8102–8109, 2019.

[8] R. Cadène, H. Ben-younes, M. Cord, and N. Thome. MUREL: multimodal relational reasoning for visual question answering. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1989–1998, 2019.

[9] R. Cadène, C. Dancette, H. Ben-younes, M. Cord, and D. Parikh. Rubi: Reducing unimodal biases for visual question answering. In *Conference on Neural Information Processing Systems (NeurIPS)*, pages 839–850, 2019.

[10] L. Chen, X. Yan, J. Xiao, H. Zhang, S. Pu, and Y. Zhuang. Counterfactual samples synthesizing for robust visual question answering. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 10797–10806, 2020.

[11] T. Chen, S. Kornblith, M. Norouzi, and G. E. Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning (ICML)*, pages 1597–1607, 2020.

[12] V. Cirik, L. Morency, and T. Berg-Kirkpatrick. Visual referring expression recognition: What do systems actually learn? In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*, pages 781–787, 2018.

[13] C. Clark, M. Yatskar, and L. Zettlemoyer. Don't take the easy way out: Ensemble based methods for avoiding known dataset biases. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 4067–4080, 2019.

[14] C. Deng, Q. Wu, Q. Wu, F. Hu, F. Lyu, and M. Tan. Visual grounding via accumulated attention. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 7746–7755, 2018.

[15] I. Gat, I. Schwartz, A. G. Schwing, and T. Hazan. Removing bias in multi-modal classifiers: Regularization by maximizing functional entropies. In *Conference on Neural Information Processing Systems (NeurIPS)*, 2020.

[16] T. Gokhale, P. Banerjee, C. Baral, and Y. Yang. MUTANT: A training paradigm for out-of-distribution generalization in visual question answering. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 878–892, 2020.

[17] Y. Goyal, T. Khot, D. Summers-Stay, D. Batra, and D. Parikh. Making the V in VQA matter: Elevating the role of image understanding in visual question answering. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6325–6334, 2017.

[18] K. He, H. Fan, Y. Wu, S. Xie, and R. B. Girshick. Momentum contrast for unsupervised visual representation learning. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9726–9735, 2020.

[19] A. Jabri, A. Joulin, and L. van der Maaten. Revisiting visual question answering baselines. In *European Conference on Computer Vision (ECCV)*, pages 727–739, 2016.

[20] C. Jing, Y. Wu, X. Zhang, Y. Jia, and Q. Wu. Overcoming language priors in VQA via decomposed linguistic representations. In *AAAI Conference on Artificial Intelligence (AAAI)*, pages 11181–11188, 2020.

[21] K. Kafle and C. Kanan. An analysis of visual question answering algorithms. In *IEEE International Conference on Computer Vision (ICCV)*, pages 1983–1991, 2017.

[22] S. Kazemzadeh, V. Ordonez, M. Matten, and T. L. Berg. Referitgame: Referring to objects in photographs of natural scenes. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 787–798, 2014.

[23] J. Kim, J. Jun, and B. Zhang. Bilinear attention networks. In *Conference on Neural Information Processing Systems (NeurIPS)*, pages 1571–1581, 2018.

[24] G. KV and A. Mittal. Reducing language biases in visual question answering with visually-grounded question encoder. In *European Conference on Computer Vision (ECCV)*, pages 18–34, 2020.

[25] Z. Liang, W. Jiang, H. Hu, and J. Zhu. Learning to contrast the counterfactual samples for robust visual question answering. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 3285–3292, 2020.

[26] J. Mao, J. Huang, A. Toshev, O. Camburu, A. L. Yuille, and K. Murphy. Generation and comprehension of unambiguous object descriptions. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 11–20, 2016.

[27] Y. Niu, K. Tang, H. Zhang, Z. Lu, X. Hua, and J. Wen. Counterfactual VQA: A cause-effect look at language bias. *arXiv preprint arXiv:2006.04315*, 2020.

[28] S. Ramakrishnan, A. Agrawal, and S. Lee. Overcoming language priors in visual question answering with adversarial regularization. In *Conference on Neural Information Processing Systems (NeurIPS)*, pages 1548–1558, 2018.

[29] R. Saqur and K. Narasimhan. Multimodal graph networks for compositional generalization in visual question answering. In *Conference on Neural Information Processing Systems (NeurIPS)*, 2020.

[30] R. R. Selvaraju, S. Lee, Y. Shen, H. Jin, S. Ghosh, L. P. Heck, D. Batra, and D. Parikh. Taking a HINT: leveraging explanations to make vision and language models more grounded. In *IEEE International Conference on Computer Vision (ICCV)*, pages 2591–2600, 2019.

[31] H. Tan and M. Bansal. LXMERT: learning cross-modality encoder representations from transformers. In K. Inui, J. Jiang, V. Ng, and X. Wan, editors, *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 5099–5110, 2019.

[32] D. Teney, E. Abbasnejad, K. Kafle, R. Shrestha, C. Kanan, and A. van den Hengel. On the value of out-of-distribution testing: An example of goodhart's law. In *Conference on Neural Information Processing Systems (NeurIPS)*, 2020.

[33] D. Teney, E. Abbasnejad, and A. van den Hengel. Learning what makes a difference from counterfactual examples and gradient supervision. In *European Conference on Computer Vision (ECCV)*, pages 580–599, 2020.

[34] D. Teney, E. Abbasnejad, and A. van den Hengel. Unshuffling data for improved generalization. *arXiv preprint arXiv:2002.11894*, 2020.

[35] A. van den Oord, Y. Li, and O. Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[36] P. Wang, Q. Wu, J. Cao, C. Shen, L. Gao, and A. van den Hengel. Neighbourhood watch: Referring expression comprehension via language-guided graph attention networks. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1960–1968, 2019.

[37] P. Wang, Q. Wu, C. Shen, A. R. Dick, and A. van den Hengel. FVQA: fact-based visual question answering. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 40(10):2413–2427, 2018.

[38] X. Wang, Q. Huang, A. Celikyilmaz, J. Gao, D. Shen, Y.-F. Wang, W. Y. Wang, and L. Zhang. Reinforced cross-modal matching and self-supervised imitation learning for vision-language navigation. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6629–6638, 2019.

[39] J. Wu and R. J. Mooney. Self-critical reasoning for robust visual question answering. In *Conference on Neural Information Processing Systems (NeurIPS)*, pages 8601–8611, 2019.

[40] S. Yang, G. Li, and Y. Yu. Graph-structured referring expression reasoning in the wild. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9949–9958, 2020.

[41] Z. Yang, X. He, J. Gao, L. Deng, and A. J. Smola. Stacked attention networks for image question answering. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 21–29, 2016.

[42] X. Zhu, Z. Mao, C. Liu, P. Zhang, B. Wang, and Y. Zhang. Overcoming language priors with self-supervised learning for visual question answering. In *International Joint Conferences on Artificial Intelligence (IJCAI)*, pages 1083–1089, 2020.