TopicNet: Semantic Graph-Guided Topic Discovery

Abstract

Existing deep hierarchical topic models are able to extract semantically meaningful topics from a text corpus in an unsupervised manner and automatically organize them into a topic hierarchy. However, it is unclear how to incorporate prior belief such as knowledge graph to guide the learning of the topic hierarchy. To address this issue, we introduce TopicNet as a deep hierarchical topic model that can inject prior structural knowledge as inductive bias to influence the learning. TopicNet represents each topic as a Gaussian-distributed embedding vector, projects the topics of all layers into a shared embedding space, and explores both the symmetric and asymmetric similarities between Gaussian embedding vectors to incorporate prior semantic hierarchies. With a variational auto-encoding inference network, the model parameters are optimized by minimizing the evidence lower bound and regularization term via stochastic gradient descent. Experiments on widely used benchmarks show that TopicNet outperforms related deep topic models on discovering deeper interpretable topics and mining better document representations.

1 Introduction

Topic models, which have the ability to uncover the hidden semantic structure in a text corpus, have been widely applied to text analysis. Generally, a topic model is designed to discover a set of semantically-meaningful latent topics from a collection of documents, each of which captures word co-occurrence patterns commonly observed in a document. While vanilla topic models, such as Latent Dirichlet Allocation (LDA) [1] and Poisson factor analysis (PFA) [2], are able to achieve this goal, a series of their hierarchical extensions [3–8] have been developed in the hope of exploring multi-layer document representations and mining meaningful topic taxonomies. Commonly, these hierarchical topic models aim to learn a hierarchy, in which the latent topics exhibit an increasing level of abstraction when moving towards a deeper hidden layer, as shown in Fig. 1 (a). Consequently, it provides users with an intuitive and interpretable way to better understand textual data.

Despite their attractive performance, many existing hierarchical topic models are purely data-driven and incorporate no prior domain knowledge, which may result in some learned topics failing to describe a semantically coherent concept [9], especially for those at a deeper hidden layer [10]. Furthermore, the inflexibility of adding prior knowledge also somewhat limits the applicability of hierarchical topic models, since it is common that a user is interested in a specific topic structure and only focused on information related to it [11]. To address this issue, we assume a structured prior in the form of a predefined topic hierarchy, where each topic is described by a semantic concept, with the concepts between two adjacent layers following the hypernym relation, as illustrated in Fig. 1 (b). Such a hierarchy can be easily constructed, either according to the user's customization or some generic knowledge graph like WordNet [12]. However, there are two main challenges: one is how to model this semantic hierarchy, and the other is how to combine it with topic models.

For the first challenge, a general and powerful approach [13] is to learn a distance-preserving mapping, which maps semantically similar topics to nearby points in the embedding space, with a symmetric distance measure (e.g., Euclidean or cosine distance) typically being used. However, the embeddings

Figure 1: Illustration of (a) topics discovered by a hierarchical topic model, (b) semantic graph constructed by prior knowledge, and (c) topics learned by TopicNet, the proposed knowledge-based hierarchical topic model.

learned by such a scheme can not perfectly reflect the entailment between concepts. To mitigate this issue, Vendrov et al. [14] exploit the partial order structure of the semantic hierarchy to learn order embeddings that respect this partial order structure. On the other hand, considering that probability distributions are better at capturing uncertainties of concepts than point vectors, Athiwaratkun and Wilson [15] introduce density order embeddings as an improvement to order embeddings. Density order embeddings allows the entailment relationship to be expressed naturally, with general words such as "entity" corresponding to broad distributions that encompass more specific words such as "animal". Through encapsulation of probability densities, it can intuitively reflect the hierarchical structure of semantic concepts, thus offering us an effective way to model the topic hierarchy.

As for the second challenge of combining the constructed topic hierarchy with topic models, there are two major difficulties. For one thing, the structured priori requires modeling the relationship between topics across different layers directly, while hierarchical topic models often assume that the topics at different layers are independent [6], which makes the fusion of the two a bit far-fetched. For another, since the constructed topic hierarchy can be very deep for large-scale text corpora, an equally deep topic model with multiple latent layers is needed to incorporate with it. However, most existing deep neural topic models are hard to go very deep due to the problem of model collapse [10, 16]. Fortunately, SawETM [10], a recently proposed neural topic model, not only builds the dependencies between topics at different layers in a shared embedding space, but also alleviates the issue of model collapse to some extent through a novel network module referred to as Sawtooth Connection (SC), and hence overcoming both difficulties.

This paper introduces a novel knowledge-based hierarchical topic model, the core idea of which is to represent each topic as a Gaussian embedding, and then project the topics of all layers into a shared embedding space to facilitate the injection of structured prior knowledge into the model. In particular, we first introduce the Gaussian-distributed embeddings to the SawETM, resulting in a variant of SawETM with a stochastic decoder called Gaussian SawETM. To incorporate prior belief into Gaussian SawETM, we then constrain the topics between two adjacent layers to encourage them to capture the concepts satisfying the predefined hypernym relation. With the variational inference technique, the entire model is learned in an end-to-end manner by minimizing the evidence lower bound and a regularization term. Extensive experiments demonstrate our model has competitive performance and better interpretability against most of hierarchical topic models.

The main contributions of the paper can be summarized as follows.

- To capture semantic uncertainties of words and topics, we propose a novel probabilistic generative model with a stochastic decoder, referred to as Sawtooth Factorial Gaussian Topic Embeddings guided gamma belief network (Gaussian SawETM).
- To incorporate the structured prior knowledge from the real world, we propose TopicNet, a novel knowledge-based hierarchical topic model based on Gaussian SawETM.
- In addition to detailed theoretical analysis, we conduct extensive experiments to verify the effectiveness of the above two models. One of the most appealing properties of TopicNet is its interpretability. We conduct extensive qualitative evaluation on the quality of the topics discovered by TopicNet, including word embedding, topic embedding, and topic hierarchies.

2   Models and inference

In this section, we elaborate on the construction and inference of Gaussian SawETM, a deep hierarchical topic model that represents words and topics as Gaussian-distributed embeddings [17].

2.1 Symmetric similarity: expected likelihood kernel

The distance measure plays a key role in quantifying the similarities between embeddings. A simple choice is taking the inner product between the means of two Gaussians, which, however, does not take the advantage of the semantic uncertainties brought by Gaussian-distributed embeddings. In this paper, we employ the expected likelihood kernel [18] as our similarity measure, which is defined as

$$\mathrm{E}^{(\mathrm{s})}\left(\boldsymbol{\alpha}_i, \boldsymbol{\alpha}_j\right) = \int_{\boldsymbol{x} \in \mathbb{R}^n} N\left(\boldsymbol{x}; \boldsymbol{\mu}_i, \boldsymbol{\Sigma}_i\right) N\left(\boldsymbol{x}; \boldsymbol{\mu}_j, \boldsymbol{\Sigma}_j\right) d\boldsymbol{x} = N\left(\boldsymbol{0}; \boldsymbol{\mu}_i - \boldsymbol{\mu}_j, \boldsymbol{\Sigma}_i + \boldsymbol{\Sigma}_j\right), \quad (1)$$

where $\boldsymbol{\alpha}_i$ is a Gaussian distribution with mean $\boldsymbol{\mu}_i$ and diagonal covariance matrix $\boldsymbol{\Sigma}_i$. As a symmetric similarity function, this kernel incorporates both the means and covariances of two Gaussians, adding the impact of semantic uncertainties.

2.2 Document decoder with sawtooth factorization and Gaussian embeddings

The generative network (also known as decoder) is one of the core components of topic models. As discussed in Section 1, to build dependencies between topics at two adjacent layers and learn a deep topic hierarchy, we draw experience from the Sawtooth Connection (SC) in SawETM. We develop a stochastic decoder by introducing Gaussian-distributed embeddings to better represent the topics in SawETM. Formally, the generative model with T latent layers can be expressed as

$$\boldsymbol{x}_j^{(1)} \sim \mathrm{Pois}(\boldsymbol{\Phi}^{(1)}\boldsymbol{\theta}_j^{(1)}), \left\{\boldsymbol{\theta}_j^{(t)} \sim \mathrm{Gam}(\boldsymbol{\Phi}^{(t+1)}\boldsymbol{\theta}_j^{(t+1)}, 1/c_j^{(t+1)})\right\}_{t=1}^{T-1}, \boldsymbol{\theta}_j^{(T)} \sim \mathrm{Gam}(\boldsymbol{\gamma}, 1/c_j^{(T+1)}),$$

$$\left\{\boldsymbol{\Phi}_k^{(t)} = \mathrm{Softmax}\left(\log\left(\mathrm{E}^{(\mathrm{s})}\left(\boldsymbol{\alpha}^{(t-1)}, \boldsymbol{\alpha}_k^{(t)}\right)\right)\right)\right\}_{t=1}^{T}, \left\{\boldsymbol{\alpha}_k^{(t)} \sim \boldsymbol{N}\left(\boldsymbol{x}; \boldsymbol{\mu}_k^{(t)}, \boldsymbol{\Sigma}_k^{(t)}\right)\right\}_{t=0}^{T}, \quad (2)$$

In the above formula, $\boldsymbol{x}_j \in \mathbb{Z}^V$ denotes the word count vector of the j^{th} document, which is factorized as the product of the factor loading matrix $\boldsymbol{\Phi}^{(1)} \in \mathbb{R}_+^{V \times K_1}$ and gamma distributed factor score $\boldsymbol{\theta}_j^{(1)}$ under the Poisson likelihood; and to obtain a multi-layer document representation, the hidden units $\boldsymbol{\theta}_j^{(t)} \in \mathbb{R}_+^{K_t}$ of the t^{th} layer are further factorized into the product of the factor loading $\boldsymbol{\Phi}^{(t+1)} \in \mathbb{R}_+^{K_t \times K_{t+1}}$ and hidden units of the next layer, until to the top layer, hidden units $\boldsymbol{\theta}_j^{(T)}$ are sampled from a prior distribution. In addition, the k^{th} topic $\boldsymbol{\alpha}_k^{(t)}$ at layer t follows a Gaussian distribution with mean $\boldsymbol{\mu}_k^{(t)}$ and covariance $\boldsymbol{\Sigma}_k^{(t)}$, where the mean vector describes a semantic concept and the covariance matrix reflects its level of abstraction. Note that in the bottom layer $\boldsymbol{\alpha}^{(0)}$ represents the distributed embeddings of words. And $\boldsymbol{\Phi}_k^{(t)}$, used to capture the relationships between topics at two adjacent layers, is calculated based on the topic representations in the shared embedding space, instead of being sampled from a Dirichlet distribution. In particular, in the equation $\mathrm{E}^{(\mathrm{s})}(\cdot)$ refers to the symmetric similarity function defined in (1).

2.3 Document encoder: Weibull upward and downward encoder networks

As presented in Section 2.2, instead of using Gaussian latent variables like most of neural topic models [19], our generative model employs the gamma distributed latent variables that are more suitable for modeling sparse and non-negative document representations. While in sampling based inference, the gamma distribution is commonly used to represent the conditional posterior of these latent variables, the difficulty of reparameterizing a gamma distributed random variable makes it difficult to apply it to an inference network. For this reason, we utilize a Weibull upward-downward variational encoder inspired by the work in Zhang et al. [16]. We let

$$q(\boldsymbol{\theta}_j^{(t)}|-) = \mathrm{Weibull}(\boldsymbol{k}_j^{(t)}, \boldsymbol{\lambda}_j^{(t)}), \quad (3)$$

where, the parameters $\boldsymbol{k}_j^{(t)}, \boldsymbol{\lambda}_j^{(t)} \in \mathbb{R}^{K_t}$ are deterministically transformed from both the observed document features and the information from the stochastic up-down path $\boldsymbol{\theta}_j^{(t+1)}$. In detail, the inference network can be expressed as

$$\boldsymbol{h}_j'^{(0)} = \mathrm{Relu}(\mathbf{W}_1^{(0)}\boldsymbol{x}_j + \boldsymbol{b}_1^{(0)})) \quad \boldsymbol{h}_j'^{(t)} = \boldsymbol{h}_j'^{(t-1)} + \mathrm{Relu}(\mathbf{W}_1^{(t)}\boldsymbol{h}_j'^{(t-1)} + \boldsymbol{b}_1^{(t)}), \quad t = 1, \cdots, T,$$

$$\boldsymbol{h}_j^{(t)} = \boldsymbol{h}_j'^{(t)} \oplus \boldsymbol{\Phi}^{(t+1)}\boldsymbol{\theta}_j^{(t+1)}, \qquad t = 0, \cdots, T-1, \qquad \boldsymbol{h}_j^{(T)} = \boldsymbol{h}_j'^{(T)},$$

$$\boldsymbol{k}_j^{(t)} = \mathrm{Softplus}(\mathbf{W}_2^{(t)}\boldsymbol{h}_j^{(t)} + \boldsymbol{b}_2^{(t)}), \quad \boldsymbol{\lambda}_j^{(t)} = \mathrm{Softplus}(\mathbf{W}_3^{(t)}\boldsymbol{h}_j^{(t)} + \boldsymbol{b}_3^{(t)}), \quad t = 0, \cdots, T, \qquad (4)$$

Figure 2: Overviews of (a) generative model of Gaussian SawETM, (b) TopicTree constructed by WordNet, and (c) Density order embeddings where specific entities correspond to concentrated distributions encapsulated in broader distributions of general entities.

where $\{\boldsymbol{b}_i^{(t)}\}_{i=1,t=1}^{3,T} \in \mathbb{R}^{K_t}$, $\{\mathbf{W}_i^{(t)}\}_{i=1,t=1}^{3,T} \in \mathbb{R}^{K_t \times K_{t-1}}$, and $\{\boldsymbol{h}_j^{(t)}\}_{j=1,t=1}^{N,T} \in \mathbb{R}^{K_t}$, $\oplus$ denotes the concatenation in feature dimension, $\text{Relu}(\cdot) = \max(0, \cdot)$ is the nonlinear activation function, and $\text{Softplus}(\cdot)$ applies $\ln[1 + \exp(\cdot)]$ to each element to ensure positive shape and scale parameters of the Weibull distribution. To avoid mode collapse, a skip-connected deterministic upward path [10] is used to obtain the hidden representations $\{\boldsymbol{h}_j'^{(t)}\}_{j=1,t=1}^{N,T}$ of the input $\boldsymbol{x}_j$.

2.4 Inference and estimation

Similar to VAEs [20, 21], the training objective of Gaussian SawETM is to maximize the Evidence Lower BOund (ELBO):

$$L_{\text{ELBO}} = \sum_{j=1}^{N} \mathbb{E}\left[\ln p(\boldsymbol{x}_j | \boldsymbol{\Phi}^{(1)}, \boldsymbol{\theta}_j^{(1)})\right] - \sum_{j=1}^{N}\sum_{t=1}^{T} \mathbb{E}\left[\ln \frac{q(\boldsymbol{\theta}_j^{(t)}|-)}{p(\boldsymbol{\theta}_j^{(t)}|\boldsymbol{\Phi}^{(t+1)}, \boldsymbol{\theta}_j^{(t+1)})}\right], \qquad (5)$$

where, $q(\boldsymbol{\theta}_j^{(t)}|-)$ is the variational weibull distribution in Eq. (3), and $p(\boldsymbol{\theta}_j^{(l)})$ is the prior gamma distribution in Eq. (2). The first term is the expected log-likelihood or reconstruction error, while the second term is the Kullback–Leibler (KL) divergence that constrains $q(\boldsymbol{\theta}_j^{(l)})$ to be close to its prior $p(\boldsymbol{\theta}_j^{(l)})$ in the generative model. The analytic KL expression and simple reparameterization of the Weibull distribution make it simple to estimate the gradient of the ELBO, with respect to $\{\boldsymbol{\mu}_k^{(t)}\}_{t=0}^{T}$ and $\{\boldsymbol{\Sigma}_k^{(t)}\}_{t=0}^{T}$ of Gaussian embeddings and other parameters in the inference network.

3 TopicNet: Semantic graph-guided topic discovery

In Section 2, a novel hierarchical topic model called Gaussian SawETM is proposed to discover meaningful topics that are organized into a hierarchy. Below we describe our solution to incorporate prior belief, e.g., knowledge graph, into Gaussian SawETM to guide the learning of the topic hierarchy.

3.1 TopicTree: Semantic graph constructed by prior knowledge

Finding an appropriate way to encode prior knowledge is especially important for realizing the incorporation of prior belief into topic models. Due to the hierarchical structure of deep topic models, correspondingly, we represent prior knowledge in the form of a hierarchical semantic graph and we call it TopicTree. Particularly, in the TopicTree each node is described by a semantic concept and the concepts of nodes at two adjacent layers follow the entailment relations, which results in a bottom-up process of gradual abstraction, as displayed in Fig. 2(b). Besides, it is worth mentioning that some generic knowledge graphs such as WordNet [12] provide us a convenient way to build the TopicTree, since the hypernyms or hyponyms of any given word can be easily found in them.

3.2 Partial order: Asymmetric entailment relationship

As described in Section 3.1, we organize prior knowledge into a hierarchical semantic graph so that it can be incorporated into our Gaussian SawETM naturally. Specifically, for a constructed TopicTree with depth T, we build a Gaussian SawETM with T latent layers corresponding to it, then we match the topics of each layer in the Gaussian SawETM with the semantic concepts of the corresponding layer in the TopicTree, i.e., each topic has a corresponding semantic concept to describe it. Most

significantly, the relationships between semantic concepts in the TopicTree should also be injected to guide the learning of the topic hierarchy. Since the Gaussian SawETM projects the topics of all layers to a shared embedding space, such a goal can be achieved by imposing constraints on the topic representations in the shared embedding space.

Inspired by Vendrov et al. [14], the semantic hierarchy (akin to the hypernym relation between words) of the TopicTree can be seen as a special case of the partial order structure. In detail, a partial order over a set of points X is a binary relation $\preceq$ such that for $a, b, c \in X$, the following properties hold: 1) $a \preceq a$ (reflexively); 2) if $a \preceq b$ and $b \preceq a$ then $a = b$ (anti-symmetry); 3) if $a \preceq b$ and $b \preceq c$ then $a \preceq c$ (transitivity). Thereupon, Vendrov et al. [14] propose learning such asymmetric relationships with order embeddings: they represent semantic concepts as vectors of non-negative coordinates, and stipulate that smaller coordinates imply higher position in the partial order and correspond to a more general concept. E.g., the following expression defines an ordered pair (x, y) of vectors in $\mathbb{R}_+^N$.

$$x \preceq y \text{ if and only if } \bigwedge_{i=1}^{N} x_i \geq y_i \tag{6}$$

Since the order embedding condition defined by Eq.(6) is too restrictive to satisfy by imposing a hard constraint, Vendrov et al. [14] relax the condition and turn to seek an approximate order-embedding. In particular, for an ordered pair of points, they apply a penalty that is formulated as:

$$E(x, y) = \|\max(0, y - x)\|^2 \tag{7}$$

Note that this imposes a strong prior on the embeddings, which could encourage the learned relations to satisfy the partial order properties of transitivity and antisymmetry.

Although Gaussian-distributed embeddings are used to represent topics in our Gaussian SawETM, we find that they are also natural at capturing the partial order structure (or the semantic hierarchy of the TopicTree) [15, 22]. For instance, for two topics following the hypernym relation, their Gaussian-distributed embeddings $\boldsymbol{\alpha}_i$ and $\boldsymbol{\alpha}_j$ form an ordered pair. Assuming that $\boldsymbol{\alpha}_i$ represents the specific topic and $\boldsymbol{\alpha}_j$ represents the general one, then we have $\boldsymbol{\alpha}_i \preceq \boldsymbol{\alpha}_j$, meanwhile we expect that $\boldsymbol{\alpha}_j$ corresponds to a broad distribution that encompasses $\boldsymbol{\alpha}_i$. To meet this expectation, the KL divergence between $\boldsymbol{\alpha}_i$ and $\boldsymbol{\alpha}_j$ provides us a ready-made tool:

$$\mathrm{E}^{(\mathrm{a})}\left(\boldsymbol{\alpha}_i, \boldsymbol{\alpha}_j\right) = D_{KL}\left(N_i \parallel N_j\right) = \int_{\boldsymbol{x} \in \mathbb{R}^n} N\left(\boldsymbol{x}; \boldsymbol{\mu}_i, \boldsymbol{\Sigma}_i\right) \log\left(N\left(\boldsymbol{x}; \boldsymbol{\mu}_i, \boldsymbol{\Sigma}_i\right)/N\left(\boldsymbol{x}; \boldsymbol{\mu}_j, \boldsymbol{\Sigma}_j\right)\right) d\boldsymbol{x}$$

$$= \frac{1}{2}\left(\mathrm{tr}\left(\boldsymbol{\Sigma}_j^{-1}\boldsymbol{\Sigma}_i\right) + (\boldsymbol{\mu}_i - \boldsymbol{\mu}_j)^{\mathrm{T}}\boldsymbol{\Sigma}_j^{-1}\left(\boldsymbol{\mu}_i - \boldsymbol{\mu}_j\right) - d + \log\left(\det\left(\boldsymbol{\Sigma}_j\right)/\det\left(\boldsymbol{\Sigma}_i\right)\right)\right) \tag{8}$$

However, using $\mathrm{E}^{(\mathrm{a})}(\boldsymbol{\alpha}_i, \boldsymbol{\alpha}_j)$ directly as a penalty for violating the partial order is undesirable. Since the KL divergence has a property that $\mathrm{E}(\boldsymbol{\alpha}_i, \boldsymbol{\alpha}_j) = 0$ if and only if $\boldsymbol{\alpha}_i = \boldsymbol{\alpha}_j$, which means the penalty is zero only if $\boldsymbol{\alpha}_i = \boldsymbol{\alpha}_j$, but we expect the penalty should also be zero when $\boldsymbol{\alpha}_i \neq \boldsymbol{\alpha}_j$ and $\boldsymbol{\alpha}_i \preceq \boldsymbol{\alpha}_j$. For this reason, following Athiwaratkun and Wilson [15], we consider using a thresholded divergence as our penalty for order violation:

$$d_\gamma\left(\boldsymbol{\alpha}_i, \boldsymbol{\alpha}_j\right) = \max\left(0, \mathrm{E}^{(\mathrm{a})}(\boldsymbol{\alpha}_i, \boldsymbol{\alpha}_j) - \gamma\right) \tag{9}$$

So this penalty can be zero if $\boldsymbol{\alpha}_i$ is properly encapsulated in $\boldsymbol{\alpha}_j$. Nevertheless, note that we no longer have the strict partial order with such a penalty. In other words, the transitivity and anti-symmetry are not guaranteed. Therefore, actually our learned relations also respect an approximate order structure.

3.3 Objective: ELBO with a prior regularity

Essentially, TopicNet is a topic model, so the Evidence Lower BOund (ELBO) still plays a leading role in the training objective. At the same time, a regularization term is also necessary for injecting hierarchical prior knowledge to guide the topic discovery. Therefore, the final objective of TopicNet can be written as:

$$L_{\mathrm{TopicNet}} = L_{\mathrm{ELBO}} + \beta L_{\mathrm{prior}} \tag{10}$$

where β is a hyper-parameter used to imbalance the impact of the two terms. Particularly, for the ELBO term L_{ELBO}, it is the same as defined by Eq. (5). As for the regularization term L_{prior}, we cannot only constrain topics that follow the hypernym relation between two adjacent layers, but the topics that do not follow the hypernym relation should also be considered. This is consistent with the notion of positive and negative sample pairs in contrastive learning. Based on this idea, we use

a max-margin loss to encourage the largest penalty between positive sample pairs to be below the smallest penalty between negative sample pairs, which is defined as:

$$L_j^{(t+1)} = \max(0, m - \max\left\{d_\gamma(i,j)\right\}_{i \in D} + \min\left\{d_\gamma(i,j)\right\}_{i \notin D}) \tag{11}$$

This represents the penalty for the j^{th} topic at $(t+1)^{th}$ layer, and D is the set of hyponym topics of topic j. For $i \in D$, (i,j) forms an positive pair, for $i \notin D$, (i,j) forms an negetive pair. m is the margin that determines the degree to which the positive and negative pairs are separated. Considering the penalties for all topics in each layer, we obtain the prior regularization term.

$$L_{\text{prior}} = \sum_{t=0}^{T-1} \sum_{j=0}^{K^{(t+1)}} L_j^{(t+1)} \tag{12}$$

With the final objective, TopicNet learns the topics influenced by both the word co-occurrence information and prior semantic knowledge, thus discovering more interpretable topics. Note that, in our experiments, the hyper-parameters are set as $m = 10.0$ and $\beta = 1.0$.

3.4 Model Properties

In this part, we recap several good properties of TopicNet: uncertainty, interpretablility and flexibility.

Effectiveness of Gaussian-distributed embeddings: Mapping a topic to a distribution instead of a vector brings many advantages, including: on the one hand, better capturing uncertainty about a representation, where the mean indicates the semantics of a topic and the covariance matrix reflects its level of abstraction; on the other hand, expressing asymmetric relationships more naturally than point vectors, which is beneficial to modeling the partial order structure of semantic hierarchy [15, 17].

Hierarchical interpretable topics: In conventional hierarchical topic models, the semantics of a topic is reflected by its distributed words, and we have to summarize a semantically coherent concept manually by post-hoc visualization. In some cases, the topic is too abstract to get a semantically coherent concept, which makes it hard to interpret. Such cases are common in deeper hidden layers. While in TopicNet, we know in advance what semantic concept a certain topic corresponds to, since it is encoded from prior knowledge and used to guide the topic discovery process of the model as a kind of supervision information. Therefore, once the model is trained, the words distributed under each topic are semantically related to the concept that describes it, as shown in Figure. 5. From this perspective, our TopicNet has better interpretability.

Flexibility to incorporate prior belief: Traditional topic models learn topics only by capturing word co-occurrence information from data, which do not consider the possible prior domain knowledge (e.g. Knowledge Graph like WordNet [23]). However, TopicNet provides a flexible framework to incorporate the structured prior knowledge into hierarchical topic models.

4 Experiments

We conducted extensive experiments to verify the effectiveness of Gaussian SawETM and TopicNet.

Baseline methods and their settings: We compare Gaussian SawETM with the state-of-the-art topic models: 1. LDA Group, including: Latent Dirichlet Allocation(**LDA**) [1], which is a basic probability topic model and closely related to a single-hidden layer version of DLDA; LDA with Products of Experts (**AVITM**) [19], which replaces the mixture model in LDA with a product of experts and uses the AVI for training; Embedding Topic Model (**ETM**) [24], a generative model that incorporates word embeddings into traditional topic model. 2. DLDA Group, including: Deep latent allocation inferred by Gibbs sampling (**DLDA-Gibbs**) [25] and by TLASGR-MCMC (**DLDA-TLASGR**) [7]. 3. Deep Neural Topic Model (DNTM) Group, including Weibull Hybrid Autoencoding Inference model (**WHAI**) [16], which employs deep variational encoder to infer hierarchical document representations, and Sawtooth Factorial Embedded Topic Model (**SawETM**) [10], where topics are modeled as learnable deterministic vectors. For all baselines, we use their official default parameters with best reported settings.

Datasets Our experiments are conducted on four widely-used textual data, including 20Newsgroups (20NG), Reuters Corpus Volume I (RCV1), Wikipedia (Wiki), and a subset of the Reuters-21578 dataset (R8), varying in scales and document length. 20NG, with a vocabulary of 2,000 words, has 20 classes and was split into 11,314 training and 7,532 test documents. RCV1 consists of 804,414 documents with a vocabulary size of 8,000. Wiki, with a vocabulary size of 10,000, consists of 3

Table 1: Comparison of per-heldout-word perplexity on three different datasets.

Method	Depth	20NG	RCV1	Wiki	Method	Depth	20NG	RCV1	Wiki
LDA [1]	1	735	942	1553	DNTM-WHAI [16]	1	762	952	1657
AVITM [27]	1	784	968	1703	DNTM-WHAI [16]	5	726	906	1595
ETM [24]	1	742	951	1581	DNTM-WHAI [16]	15	724	902	1592
DLDA-Gibbs [25]	1	702	-	-	DNTM-SawETM [10]	1	718	908	1536
DLDA-Gibbs [25]	5	678	-	-	DNTM-SawETM [10]	5	688	873	1503
DLDA-Gibbs [25]	15	670	-	-	DNTM-SawETM [10]	15	684	864	1492
DLDA-TLASGR [7]	1	714	912	1455	DNTM-GaussSawETM	1	714	904	1529
DLDA-TLASGR [7]	5	684	877	1432	DNTM-GaussSawETM	5	685	866	1477
DLDA-TLASGR [7]	15	673	842	1421	DNTM-GaussSawETM	15	678	857	1452

million documents randomly downloaded from Wikipedia using the script provided by Hoffman et al. [26]. R8, with a vocabulary size of 10,000, has 8 classes and was split into 5,485 training and 2,189 test documents. The summary statistics of these datasets and other implementation details (such as dataset preprocess and length statistics etc.) are described in Appendix.

4.1 Unsupervised learning for document representation

Per-heldout-word perplexity: To measure predictive quality of the proposed model, we calculate the per-heldout-word perplexity (PPL) [25], on three regular document datasets, e.g., 20NG, RCV1, and Wiki. For deep topic models in DLDA and DNTM groups, we report the PPL with 3 different stochastic layers T, $\mathbf{T} \in \{1, 5, 15\}$. Specifically, for a 15-layer model, the topic size from bottom to top is set as $\mathbf{K} = [256, 224, 192, 160, 128, 112, 96, 80, 64, 56, 48, 40, 32, 16, 8]$, and the detailed description can be found in the Appendix. For each corpus, we randomly select 80% of the word tokens from each document to form a training matrix X, holding out the remaining 20% to form a testing matrix Y. We use X to train the model and calculate the per-held-word perplexity as

$$\exp\left\{ -\frac{1}{y_{..}} \sum_{v=1}^{V} \sum_{n=1}^{N} y_{vn} \ln \frac{\sum_{s=1}^{S} \sum_{k=1}^{K^1} \phi_{vk}^{(1)s} \theta_{kn}^{(1)s}}{\sum_{s=1}^{S} \sum_{v=1}^{V} \sum_{k=1}^{K^1} \phi_{vk}^{(1)s} \theta_{kn}^{(1)s}} \right\},$$

where S is the total number of collected samples and $y_{..} = \sum_{v=1}^{V} \sum_{n=1}^{N} y_{vn}$. As shown in Table. 1, overall, DLDA-Gipps perform best in terms of PPL, which is not supervising as they from the true posteriors given a sufficiently large number of Gibbs sampling iterations. DLDA-TLASGR is a mini-batch algorithm that is much more scalable in training than DLDA-Gibbs, at the expense of slightly degraded performance in out-of-sample prediction. Apart from these deep probabilistic topic models, Gaussian SawETM outperforms other neural topic models in all datasets. In particular, compared with Gaussian based single layer neural topic model, WHAI performs better, which can be attributed to two aspects, the first is the effectiveness of Weibull distribution in modeling sparse and non-negative document latent representations, and the second is aggregating the information in both the higher (prior) layer and that upward propagated to the current layer via inference network. Benefit from the embedding decoder and the Sawtooth Connection that builds the dependencies of hierarchical topics, SawETM performs better than WHAI, especially at deeper layers. However, modeling topics with point vectors, SawETM cannot capture the uncertainties of topics. Gaussian SawETM represents the topics with Gaussian-distributed embeddings to capture the uncertainties, and achieves promising improvements compared with SawETM, especially for modeling complex and big corpora such as Wiki. Note that although the methods in DLDA group get better performance, they require iteratively sampling to infer latent document representations in the test stage, which limits their application [16]. While Gaussian SawETM can infer latent representations via direct projection, which makes it both salable to large corpora and fast in out-of-sample prediction.

Document Classification & **Clustering** Document-topic distributions can be viewed as unsupervised document representations, to evaluate their quality, we perform document classification and clustering tasks. In detail, we first use the trained topic models to extract the latent representations of the testing documents and then use logistic regression to predict the label while use k-means to predict the clusters. we measure the classification performance by classification accuracy, and clustering performance by accuracy (ACC) and normalized mutual information (NMI), both of which are the higher the better. we test the model performance on 20NG and R8, where the document labels are considered. And different from the perplexity experiments, a larger vocabulary of 20,000 words is used for 20News to achieve better performance. The network structure is defined by TopicTree, which is introduced in Section. 3.1, and details will be described in the appendix. The comparison

Table 2: Comparison of document classification and clustering performance.

| Methods | Depth | Classification | | Clustering | | | |
| | | 20NG | R8 | 20NG | | R8 | |
				ACC	NMI	ACC	NMI
LDA [1]	1	72.6±0.3	88.4±0.5	46.5±0.2	45.1±0.4	51.4±0.4	40.5±0.3
NVITM [27]	1	71.5±0.4	87.3±0.2	48.3±0.5	46.4±0.3	52.5±0.2	41.2±0.4
ETM [24]	1	71.9±0.2	87.9±0.4	49.8±0.6	48.4±0.5	55.3±0.4	42.3±0.2
PGBN [6]	1	74.2±0.5	90.8±0.5	46.6±0.5	45.4±0.6	51.7±0.4	40.7±0.4
PGBN [6]	4	76.0±0.3	91.6±0.4	48.2±0.2	46.5±0.5	54.4±0.4	41.2±0.3
WHAI [16]	1	72.8±0.3	85.3±0.2	49.4±0.5	46.5±0.4	57.9±0.5	42.3±0.4
WHAI [16]	4	73.7±0.5	88.4±0.3	49.5±0.4	47.0±0.3	60.4±0.4	44.1±0.2
SawETM [10]	1	70.5±0.3	88.6±0.2	50.2±0.2	48.7±0.3	61.2±0.4	43.4±0.4
SawETM [10]	4	71.1±0.2	90.5±0.3	51.2±0.3	50.7±0.2	63.8±0.3	45.9±0.5
Gaussian SawETM	1	72.8±0.3	89.8±0.4	51.3±0.4	50.6±0.2	61.5±0.3	44.1±0.2
Gaussian SawETM	4	75.2±0.4	91.0±0.3	53.0±0.3	51.3±0.2	65.2±0.4	47.0±0.3
TopicNet	1	71.6±0.2	88.6±0.3	49.5±0.3	46.3±0.4	61.0±0.2	43.2±0.3
TopicNet	4	74.3±0.5	89.5±0.4	50.8± 0.3	47.8±0.4	64.2±0.3	46.5±0.2

results are summarized in Table 2. Benefit from the Gaussian distribution of topic, Gaussian SawETM outperforms the other neural topic models not only on document classification task but also clustering task, which proves the effectiveness of extracting document latent representations. Note that, Gaussian SawETM acquire promising improvement compared with SawETM in 20NG dataset shows the potential for modeling complex data, while the SawETM is a special case of Gaussian SawETM. Besides, with the predefined knowledge prior, TopicNet does not perform better maybe because the prior information is irrelevant with the document classification and clustering tasks, and we will explore how to build a task-related prior to improve the TopicNet's performance on special tasks.

4.2 Explainable topic discovery

Apart from excelling at document representation learning, another appealing characteristic of TopicNet is that it can discover interpretable hierarchical topics. In this section, We perform the topic discovery experiment with a 7-ayer TopicNet trained on 20NG. The network structure is constructed according to the structure of TopicTree, which is set as [411, 316, 231, 130, 46, 11, 2].

Topic quality: Two metrics are considered to evaluate the topic quality. The first metric is topic coherence, which is computed by taking the average Normalized Pointwise Mutual Information (NPMI) of the top 10 words of each topic [28]. It provides a quantitative measure of the interpretability of a topic. The second metric is topic diversity [24], which suggests the percentage of unique words in the top 25 words of all topics. Diversity close to 1 means more sundry topics. Following [24], we define topic quality as the product of topic coherence and topic diversity. As shown in Figure. 3, Gaussian SawETM gets a better score compared with SawETM, which can be attributed to the Gaussian-distributed embeddings that capture uncertainties of topics. Incorporating the hierarchical prior knowledge, TopicNet gets a better score compared with Gaussian SawETM, but obtains a worse score compared with DLDA-Gibbs in the first two layers. As layer goes deeper, it performs better, this is easy to understand since information from data reduces slightly in the shallow layers but severely in the deep layers.

Figure 3: Topic quality as measured by normalized product of topic coherence and topic diversity (the higher the better) with the varied number of layers.

Visualisation of embedding space: First of all, we use a 3-layer Gaussian SawETM with 2-dim embedding trained on 20NG for the Gaussian-distribution embedding visualization. The top 4 words from the 16^{th} topic at 1^{th} layer are visualized in Fig. 4(a). As we can see, the words under the same topic are closer in embedding space, which demonstrates the learned embeddings are semantically similar. Apart from the semantics of words and topics, the shadow range describes the uncertainties and reflects the abstraction levels. Secondly, we visualize the means of Gaussian-

(a) Words Embedding   (b) Topic Embedding

Figure 4: (a) 2-dim Gaussian embedding in Gaussian SawETM, which we choose the top four words for the topic and (b) T-SNE visualisation of the mean of Gaussian distribution embedding in TopicNet. (The Topic: t-j : xx denotes the j^{th} topic at t^{th} layer and xx represent the concept about the topic.)

Figure 5: An example of hierarchical topics learned by a 7-layer TopicNet, we only show example topics at the top two layers and bottom two layers. Boldface indicates the concept of each topic.

distributed embeddings learned by TopicNet with T-SNE[29]. As is shown in Fig.4.2, in the shared embedding space, the words with similar semantics are close to each other, meanwhile they all locate near the topic that has similar semantics to them, which means the TopicNet effectively captures the prior semantic information and discovers more interpretable topics.

Hierarchical structure of TopicNet: Distinct from many existing topic models that understanding topics by post-hoc visualization, we can easily understand the semantic of whole stochastic network via the predefined TopicTree. Specially, the hierarchical structure of TopicNet is shown in Figure. 5. The semantic of each topic can be represented by the concept in the TopicTree, which is more interpretable compared with traditional topic models. And this result can support our motivation which is shown in Figure. 1.

5   Conclusion

To equip topic models with the flexibility to incorporate prior knowledge, this paper makes a useful attempt, and proposes a novel knowledge-based hierarchical topic model - TopicNet. In detail, TopicNet first explores the effectiveness of Gaussian distributions to represent topics, then develops a regularization term that encourages the model to discover topics guided by hierarchical prior knowledge. Compared with other neural topic models, TopicNet achieves promising results on various tasks, which provides a possible direction for the future development of tpoic models in terms of practicability.

References

[1] David M Blei, Andrew Y Ng, and Michael I Jordan. Latent dirichlet allocation. *Journal of machine Learning research*, 3(Jan):993–1022, 2003.

[2] Mingyuan Zhou, Lauren Hannah, David Dunson, and Lawrence Carin. Beta-negative binomial process and poisson factor analysis. In *Artificial Intelligence and Statistics*, pages 1462–1471, 2012.

[3] David M Blei, Thomas L Griffiths, and Michael I Jordan. The nested chinese restaurant process and bayesian nonparametric inference of topic hierarchies. *Journal of the ACM (JACM)*, 57(2): 1–30, 2010.

[4] John Paisley, Chong Wang, David M Blei, and Michael I Jordan. Nested hierarchical dirichlet processes. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 37(2):256–270, 2014.

[5] Zhe Gan, Changyou Chen, Ricardo Henao, David Carlson, and Lawrence Carin. Scalable deep poisson factor analysis for topic modeling. In *International Conference on Machine Learning*, pages 1823–1832, 2015.

[6] Mingyuan Zhou, Yulai Cong, and Bo Chen. Augmentable gamma belief networks. *The Journal of Machine Learning Research*, 17(1):5656–5699, 2016.

[7] Yulai Cong, Bo Chen, Hongwei Liu, and Mingyuan Zhou. Deep latent dirichlet allocation with topic-layer-adaptive stochastic gradient riemannian mcmc. *arXiv preprint arXiv:1706.01724*, 2017.

[8] He Zhao, Lan Du, Wray Buntine, and Mingyuan Zhou. Dirichlet belief networks for topic structure learning. *arXiv preprint arXiv:1811.00717*, 2018.

[9] Jonathan Chang, Jordan Boyd-Graber, Chong Wang, Sean Gerrish, and David M Blei. Reading tea leaves: How humans interpret topic models. In *Neural information processing systems*, volume 22, pages 288–296. Citeseer, 2009.

[10] Zhibin Duan, Dongsheng Wang, Bo Chen, Chaojie Wang, Wenchao Chen, Yewen Li, Jie Ren, and Mingyuan Zhou. Sawtooth factorial topic embeddings guided gamma belief network. In *ICML 2021: International Conference on Machine Learning*, July 2021.

[11] Yu Meng, Yunyi Zhang, Jiaxin Huang, Yu Zhang, Chao Zhang, and Jiawei Han. Hierarchical topic mining via joint spherical tree and text embedding. In *Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 1908–1917, 2020.

[12] George A Miller. Wordnet: a lexical database for english. *Communications of the ACM*, 38(11): 39–41, 1995.

[13] Sumit Chopra, Raia Hadsell, and Yann LeCun. Learning a similarity metric discriminatively, with application to face verification. In *2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05)*, volume 1, pages 539–546. IEEE, 2005.

[14] Ivan Vendrov, Ryan Kiros, Sanja Fidler, and Raquel Urtasun. Order-embeddings of images and language. *arXiv preprint arXiv:1511.06361*, 2015.

[15] Ben Athiwaratkun and Andrew Gordon Wilson. Hierarchical density order embeddings. *arXiv preprint arXiv:1804.09843*, 2018.

[16] Hao Zhang, Bo Chen, Dandan Guo, and Mingyuan Zhou. Whai: Weibull hybrid autoencoding inference for deep topic modeling. *arXiv preprint arXiv:1803.01328*, 2018.

[17] Luke Vilnis and Andrew McCallum. Word representations via gaussian embedding. *arXiv preprint arXiv:1412.6623*, 2014.

[18] Tony Jebara, Risi Kondor, and Andrew Howard. Probability product kernels. *The Journal of Machine Learning Research*, 5:819–844, 2004.

[19] Akash Srivastava and Charles Sutton. Autoencoding variational inference for topic models. *arXiv preprint arXiv:1703.01488*, 2017.

[20] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[21] Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and variational inference in deep latent gaussian models. In *International Conference on Machine Learning*, volume 2, 2014.

[22] Rajarshi Das, Manzil Zaheer, and Chris Dyer. Gaussian lda for topic models with word embeddings. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 795–804, 2015.

[23] Christiane Fellbaum. Wordnet. In *Theory and applications of ontology: computer applications*, pages 231–243. Springer, 2010.

[24] Adji B Dieng, Francisco JR Ruiz, and David M Blei. Topic modeling in embedding spaces. *Transactions of the Association for Computational Linguistics*, 8:439–453, 2020.

[25] Mingyuan Zhou, Yulai Cong, and Bo Chen. The poisson gamma belief network. *Advances in Neural Information Processing Systems*, 28:3043–3051, 2015.

[26] Matthew Hoffman, Francis R Bach, and David M Blei. Online learning for latent dirichlet allocation. In *advances in neural information processing systems*, pages 856–864. Citeseer, 2010.

[27] Guangxu Xun, Vishrawas Gopalakrishnan, Fenglong Ma, Yaliang Li, Jing Gao, and Aidong Zhang. Topic discovery for short texts using word embeddings. In *2016 IEEE 16th international conference on data mining (ICDM)*, pages 1299–1304. IEEE, 2016.

[28] Nikolaos Aletras and Mark Stevenson. Evaluating topic coherence using distributional semantics. In *Proceedings of the 10th International Conference on Computational Semantics (IWCS 2013)– Long Papers*, pages 13–22, 2013.

[29] Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.