Associative Memory augmented Asynchronous spatiotemporal Representation learning for Event-based perception

Abstract

We propose *EventFormer*– a computationally efficient event-based representation learning framework for asynchronously processing event camera data. Event-Former treats sparse input events as a spatially unordered set and models their spatial interactions using self-attention mechanism. An associative memory-augmented recurrent module is used to correlate with the stored representation computed from past events. A memory addressing mechanism is proposed to store and retrieve the latent states only *where* these events occur and update them only *when* they occur. The representation learning shift from input space to the latent memory space resulting in reduced computation cost for processing each event. We show that EventFormer achieves 0.5% and 9% better accuracy with $30000\times$ and $200\times$ less computation compared to the state-of-the-art dense and event-based method, respectively, on event-based object recognition datasets.

1 Introduction

Ultra-low power, high dynamic range ($> 120dB$), high temporal resolution, and low latency makes event-based cameras (Brandli et al., 2014; Suh et al., 2020; Son et al., 2017; Finateu et al., 2020) attractive for real-time machine vision applications such as robotics and autonomous driving (Falanga et al., 2020; Hagenaars et al., 2020; Sun et al., 2021; Zhu et al., 2018; Gehrig et al., 2021). Convolutional and recurrent neural network-based methods, originally developed for frame-based cameras, have demonstrated good perception accuracy on event camera (Gehrig et al., 2019; Baldwin et al., 2022; Cannici et al., 2020b). But they rely on temporal aggregation of the events to create a frame-like dense representation as input thereby discarding the inherent sparsity of event data and resulting in high computational cost (Figure 2). Recent works have explored event-based processing methods for object recognition to exploit data sparsity. Examples of such methods include Time-surface based representation relying on hand-crafted features (Lagorce et al., 2016; Sironi et al., 2018; Ramesh et al., 2019), 3D space-time event-cloud (Wang et al., 2019), and Graph-based methods (Li et al., 2021c; Schaefer et al., 2022). These methods adopt event-based processing to achieve lower computational costs but do not achieve similar performance compared to the dense-representation based methods (Figure 2). This necessitates computationally efficient algorithms that exploit sparsity and achieve high accuracy.

We propose an associative memory-augmented asynchronous representation learning framework for event-based perception, hereafter referred to as *EventFormer*, that enables computationally efficient event-based processing with high performance (Figure 1). As events are triggered asynchronously, an event-based processing algorithm must generate and maintain a higher-order representation from the events, and efficiently update that representation to correlate a new event with the past events across space and time. One way to address this is to include a recurrent module at each pixel to track history of past events (Cannici et al., 2020a). However, the associated processing and memory requirement of such a method increases exponentially with the number of pixels. Motivated by recent works in memory augmented neural networks(Kumar et al., 2016; Ma et al., 2018; Karunaratne et al., 2021), we address the preceding challenge by maintaining a spatiotemporal representation associated with past events, occurring at various pixels, as the hidden states of an Associative Memory. As learning spatiotemporal correlation is shifted from the high-dimension input (pixel) space to a compact latent memory space, EventFormer requires an order of magni-

Figure 1: **Comparison with existing works.** **(a)** Event-based perception algorithms where perception latency $k\Delta$ is proportional to the event-generation rate(Δ). **(b)** Existing works include (left) *dense processing* that aggregate events into a frame and use CNN (Gehrig et al., 2019), *event-based processing* including (mid) GNN on spatiotemporal event-graph (Li et al., 2021c), or (right) PointNet like architectures treating events as point-cloud (Wang et al., 2019). These methods either re-process (frame and point cloud) or store the past events (graph) to perform spatiotemporal correlation with new events. **(c)** The proposed EventFormer encodes the spatiotemporal interaction of the past events into a compact latent memory space to efficiently retrieve and correlate with the new events without requiring to store or re-process the past events.

tude lower floating point operation (FLOPs) per event to update the memory. To the best of our knowledge, EventFormer is the first associative memory-augmented spatiotemporal representation learning method for event-based perception. The key contributions of this paper are:

- EventFormer maps the spatiotemporal representation of the incoming event stream into the hidden states of an associative memory and uses a lightweight perception head directly operating on these states to generate perception decisions.

- Spatiotemporal representation update mechanism activates only 'when' and only 'where' there is a new event using unstructured set-based processing without requiring to store and re-process the past events.

- We propose a novel query-key association-based memory access mechanism that enables us spatial location-aware memory content access to retrieve the past states associated with the new event locations.

Given a new event (or a set of events), our model generates a spatial representation by computing their spatial interaction through self-attention mechanism (Vaswani et al., 2017)and retrieves the past spatiotemporal states related to that pixel location(s) from the memory. The retrieval process exploits a novel location-based query and content-based key-value association mechanism to extract correlations among the past events at neighboring pixels. Once we get the past states, along with our present spatial representation, a recurrent module takes them as input and generates the *refined* state information. The associated hidden states of the memory are updated with the new information. We evaluate EventFormer on object recognition task from event-camera data. In our experiments on existing benchmark datasets, N-Caltech101 (Orchard et al., 2015) and N-Cars (Sironi et al., 2018), EventFormer shows an excellent computational advantage over the existing methods (both dense and event-based) while achieving performance comparable to the dense methods (Figure 2).

Related Work *.Dense methods* convert events to dense frame-like representation and process them with standard deep learning models such as CNNs (Maqueda et al., 2018; Gehrig et al., 2019; Cannici et al., 2020a). These methods are synchronous in nature as they generate dense inputs by binning and aggregating events in time and generate output only when the entire bin is processed. *Event-based methods* update their representations with a new event and generate new output. Methods such as (Lagorce et al., 2016; Sironi et al., 2018; Ramesh et al., 2019) compute time-ordered representation (also known as time-surface) in an event-based manner with fewer computations. However, their reliance on fixed, hand-tuned representation results in sub-optimal performance compared to the data-driven methods (Gehrig et al., 2019). Recently, graph-based methods (Messikommer et al., 2020; Li et al., 2021b; Schaefer et al., 2022) have been considered that gen-

erate a spatiotemporal event graph and process them with GNN. For a new event, the graph is updated by removing nodes associated with past events and adding new ones. As these methods require subsampling the events to reduce the size of the graph (and hence, computation), performance is reduced as well. Also, they need to store the past events inside the graph to correlate with the new event causing additional computation and memory overhead. *Point cloud*-based methods can natively process unstructured event camera data in a permutation invariant manner (Wang et al., 2019; Vemprala et al., 2021). However, they process over a sliding window of time τ and need to re-process the past events for every new event to establish correlations leading to redundant computations. *Memory Augmented Neural Networks* typically combine an external associative memory with a recurrent controller (Kumar et al., 2016; Ma et al., 2018; Karunaratne et al., 2021) resulting in enhanced memory capacity compared to the vanilla recurrent module (Cho et al., 2014). Cannici et al. (2020) propose a pixel-wise memory-based representation learning for event-camera data that stores states at each pixel location (Cannici et al., 2020a). However, it requires a computationally expensive feature extractor as spatiotemporal correlations among these states are not considered.

2 METHOD

Preliminaries and Problem Formulation
An event-based camera consists of sensors at every pixel location that can respond to the change of brightness asynchronously and independently (Gallego et al., 2020). Mathematically, a set of events produced at pixel locations $(x, y)_i$ $(0 \leq x \leq W, 0 \leq y \leq H)$ during a time interval τ can be defined as a time-ordered sequence, $\mathcal{E}_\tau = \{(x_i, y_i, t_i, p_i) \mid t_i \in \tau, T = \sup_i t_i\}$ where t_i denotes the event triggering timestamps, $p_i \in \{-1, 1\}$ as the polarity (relative change in brightness), and T as the total time of observation. In this work, we consider the spatial locations of the events as the input, that is: $\mathcal{E}_\tau = \{(x_i, y_i)\}$. Our goal is to learn a compute efficient parametric mapping $\mathcal{F} : \mathcal{E}_\tau \to \mathcal{M}_{\mathcal{E}_\tau}$ that can convert the raw event sequence $\mathcal{E}_\tau$ into a suitable representation $\mathcal{M}_{\mathcal{E}_\tau} \in \mathbb{R}^{m \times d}$ (where $m \times d$ defines the dimension of the feature space) with event-based processing capability. This implies that $\mathcal{F}$ needs to have the capability to update its representation as soon as a new event(or a new event sequence) arrives without storing or recomputing the past events.

Figure 2: **Recognition performance vs computation.** On N-Caltech101 dataset, EventFormer has about $30000\times$ lower compute cost than the SoTA dense method (Cannici et al., 2020b) with 9% improvement in accuracy compared to the best performing event-based method (Li et al., 2021c).

Overview of the Framework Eventformer consists of a positional encoder (Li et al., 2021a) followed by a pairwise interaction module to compute the spatial interactions among the events (Figure 3). A recurrent module takes this output, $\mathcal{Z}_t$ as the current input state, and computes the spatiotemporal representation $\mathcal{X}_t$ by retrieving the past hidden states $\mathcal{H}_{t-1}$ stored in an associative memory, $\mathcal{M}$. The output of this recurrent module is used to update the memory representation $\mathcal{M}_t$, which is used by a classification head for the recognition task. To facilitate these operations, EventFormer has three unique `Operators`: `Read` to retrieve the past representation, `Write/Erase` to update the memory with new representation, and, `Refine` to compute the spatial correlation among the events. Both `Read` and `Write/Erase` operators use multihead residual attention (Vaswani et al., 2017) as a building block. The `Refine` operator adopts an efficient version of this building block (Shen et al., 2021) to address the quadratic memory and compute requirement (that can become computationally prohibitive for a very fast-moving object generating a large number of events at a given time) of the traditional dot-product attention mechanism (Vaswani et al., 2017). Algorithm 1 shows an implementation of the overall Eventformer architecture.

Figure 3: **EventFormer architecture.** EventFormer generates positional embedding π_t from a list of new events x_t at time t, and calculates their pairwise interaction, $\mathcal{Z}_t$ using self-attention. A recurrent unit extracts the past states $\mathcal{H}_{t-1}$ associated with x_t from an associative memory and computes $\mathcal{X}_t$ as the current states. This is further encoded into the latent memory space, $\mathcal{M}_t$ to process future events. A linear layer uses $\mathcal{M}_t$ to predict the target class.

Algorithm 1: Compute the event-based representation through EventFormer

Input: A list of n 2-dimensional pixel coordinates of the events at time t:
$$x_t = \{(x_i, y_i) \mid i \leq n\}$$
Output: Prediction vector $Y_t \in \mathbb{R}^c$ where c denotes the number of class.
Hyperparameter: The dimension of the event-representation vector d, row size of the memory m, number of stacks for the $\texttt{Refine}(.,.)$ operator R.
Initialize the memory representation with the learned initializer, $\mathcal{M}_0 \in \mathbb{R}^{m \times d}$

1   $\pi_t \leftarrow \Pi(x_t) := \frac{1}{\sqrt{d}} \left(\cos(x_t W_p^T) \parallel \sin(x_t W_p^T) \right);$

2   $\mathcal{H}_{t-1} \leftarrow \texttt{Read}(\pi_t, \mathcal{M}_{t-1});$ ▷ *Read the past memory-representation*

3   **foreach** $r \in R$ **do**

4      $\pi_t \leftarrow \texttt{Refine}_r(\pi_t, \pi_t);$ ▷ *Compute interactions among the events*

5      $\mathcal{Z}_t \leftarrow \pi_t;$

6   $\mathcal{X}_t \leftarrow \mathcal{R}(\mathcal{Z}_t, \mathcal{H}_{t-1});$ ▷ *Compute the current states*

7   $\mathcal{M}'_t \leftarrow \texttt{Write}(\mathcal{M}_{t-1}, \mathcal{X}_t);$ ▷ *Compute new memory representation*

8   $\alpha_t \leftarrow \texttt{sigmoid}(\texttt{Erase}(\mathcal{M}_{t-1}, \mathcal{X}_t));$ ▷ *Compute the update factor*

9   $\mathcal{M}_t = \alpha_t \mathcal{M}_{t-1} + (1 - \alpha_t)\mathcal{M}'_t;$ ▷ *Update the memory*

10   $\mathcal{M}_t^{flat} \leftarrow$ Reshape $\mathcal{M}_t$ into a 1-dimensional vector;

11   $Y_t \leftarrow \texttt{FF}_{\texttt{pred}}(\mathcal{M}_t^{flat});$ ▷ *Prediction at time t*

12   **return** Y_t.

Operator details: An $\texttt{Operator}(\mathcal{A}, \mathcal{B})$ takes $\mathcal{A} \in \mathbb{R}^{n \times d}$ and $\mathcal{B} \in \mathbb{R}^{m \times d}$ as input and maps them into the Q (query), K (key), and V (value) space using a linear transformation. The attention mechanism maps the Q to outputs as follows:

$$\texttt{Attn}(Q, K, V; a) = a(QK^\top)V \tag{1}$$

$QK^\top \in \mathbb{R}^{n \times m}$ measures the pairwise similarity of the query and key vectors. $a(QK^\top)V \in \mathbb{R}^{n \times d}$ is a weighted sum of the value vectors where the weights are computed using scaled softmax activation $a(.) = \texttt{softmax}(./\sqrt{d})$. The multihead residual attention computes multiple attention by projecting Q, K, and V onto h separate d/h dimensional space, respectively. The output is a linear combination of h-different attentions ($\texttt{Attn}(.,.,.;a)$) applied to each of these h projections:

$$\texttt{MultiHead}(Q, K, V; w, a) = \texttt{concatenate}(O^1, ..., O^h)W^o \tag{2}$$

$$\text{where} \quad O^i = \texttt{Attn}(QW_i^q, KW_i^k, VW_i^v; a_i) \tag{3}$$

$w = \{W_i^q, W_i^k, W_i^v\}_{i=1}^h \in \mathbb{R}^{d \times \frac{d}{h}}$ and $W^o \in \mathbb{R}^{hd_v \times d}$ are learnable parameters. A following residual block completes the operation and generates output, O as follows:

$$O = \texttt{Operator}(\mathcal{A}, \mathcal{B}) := \texttt{LayerNorm}(O_h + \texttt{FF}^o(O_h)) \tag{4}$$

Figure 4: **Details of the memory operations. (a)** block diagram of the multihead residual attention, **(b)** composition of an $\texttt{Operator}(\mathcal{A}, \mathcal{B})$, **(c)** $\texttt{Read}$ operator calculates query from positional embedding π_t and key-value pair from past memory representation, $\mathcal{M}_{t-1}$. The $\texttt{Write}$ and $\texttt{Erase}$ operator computes query from $\mathcal{M}_{t-1}$ and key-value pair from $\mathcal{X}_t$, and, **(d)** An update to the associative memory occurs with a linear combination of the new value to be added $\mathcal{M}'_t$ and past representation $\mathcal{M}_{t-1}$ weighted by an elementwise scaling factor generated by the $\texttt{Erase}$ operator.

$$\text{where} \quad O_h = \texttt{LayerNorm}(\mathcal{A} + \texttt{MultiHead}(Q, K, V; w, a)) \tag{5}$$

$\texttt{LayerNorm}$ is layer normalization function (Ba et al., 2016). Figure 4 illustrates these operations.

Positional encoder: EventFormer generates positional embedding by mapping the event sequence from a low-dimensional (2D) space to a higher-dimensional feature space. This is done by a learnable Fourier feature-based positional encoder. At any given time t, the positional encoder, $\Pi : x_t \in \mathbb{R}^{n \times 2} \to \pi_t \in \mathbb{R}^{n \times d}$ parameterized by $W_p \in \mathbb{R}^{\frac{d}{2} \times 2}$ maps a list of n 2-dimensional events, x_t to a d-dimensional feature space, π_t using the following equation:

$$\pi_t = \Pi(x_t) := \frac{1}{\sqrt{d}} \left(\texttt{concatenate} \left(\cos(x_t W_p^T), \sin(x_t W_p^T) \right) \right) \tag{6}$$

Spatial correlation: To compute a refined representation that considers spatial correlation among the events, we compute self-attention among the positional embedding π_t by using the $\texttt{Refine}$ operator. The efficient attention mechanism modifies the Equation 1 as follows:

$$\texttt{EfficientAttn}(Q, K, V; a_q, a_k) = a_q(Q) \left(a_k \left(K^\top \right) V \right) \tag{7}$$

where a_q and a_k denotes the row-wise and column-wise scaled softmax activation, $a(.)$. A closer look at Equation 7 reveals that the memory and computation complexity now has been reduced to $\mathcal{O}(dn + d^2)$ and $\mathcal{O}(d^2 n)$ respectively, which is now linear with respect to the number of events, n. Finally, we stack multiple $\texttt{Refine}$ operators to compute $\mathcal{Z}_t \in \mathbb{R}^{n \times d}$ as their higher-order interactions.

Associative memory augmented recurrent module: The proposed associative memory has a *query-key* association-based memory access architecture with a separate association mechanism for state retrieval and update operation (Figure 4). We define $\mathcal{M}_t \in \mathbb{R}^{m \times d}$ as the stored memory representation at time t. The $\texttt{Read}$ operator retrieves the past representation $\mathcal{H}_{t-1} \in \mathbb{R}^{n \times d}$ using the current event locations π_t. It computes the query vectors from π_t and key, value vectors using the past stored representation $\mathcal{M}_{t-1}$. The final retrieved state is a weighted sum of the projected $\mathcal{M}_{t-1}$ where the weights are computed through the association between event-location (π_t) and the abstract 'memory-address' (keys projected from $\mathcal{M}_{t-1}$). This implies that a particular memory representation gets more weight if its corresponding address (key) has a higher similarity with the query (i.e., positional embedding). The retrieved $\mathcal{H}_{t-1}$ is used as the past hidden state of the recurrent module, $\mathcal{R}$, to compute the current spatiotemporal representation, $\mathcal{X}_t \in \mathbb{R}^{n \times d}$. We use gated recurrent unit (GRU) as the recurrent module. The $\texttt{Write}$ and $\texttt{Erase}$ operator jointly update $\mathcal{M}_t$ with new information. The $\texttt{Write}$ operator computes the query vectors from $\mathcal{M}_{t-1}$ and the key-value pair from $\mathcal{X}_t$ to query the location of the memory that needs to be updated and generate the new representation, $\mathcal{M}'_t \in \mathbb{R}^{m \times d}$. The purpose of $\texttt{Erase}$ operator is to calculate a set of element-wise scaling factor,

Figure 5: **Temporal evolution of memory representation. (a)** and **(b)** Change in memory representation over time for samples from two different classes. **(c)** tSNE plot of the memory representation for 10 randomly selected classes from N-Caltech101 dataset.

$\alpha_t \in \{\mathbb{R}^{m \times d} \mid 0 \leq \alpha_t \leq 1\}$ to control the update strength at each memory location. Finally, we update the memory using:

$$\mathcal{M}_t = \alpha_t \mathcal{M}_{t-1} + (1 - \alpha_t)\mathcal{M}'_t \tag{8}$$

Classification head: A single feedforward layer $\texttt{FF}_{pred}(.)$ that maps the flattened memory representation, $\mathcal{M}_t^{flat} \in \mathbb{R}^{md}$ to the prediction vector, $Y_t \in \mathbb{R}^c$ where c is the number of class.

3 EXPERIMENTS AND RESULTS

Datasets and metrics: We evaluate the performance of our method on standard event-based object recognition benchmarks: N-Caltech101 and N-Cars (see Appendix D for details). We consider two metrics: recognition accuracy and the number of floating point operations required to update the representation for each new event (MFLOPs/ev).

Implementation: EventFormer follows an end-to-end feed-forward layer-based implementation. We use 32×32 and 16×16 as memory dimensions ($\mathbb{R}^{m \times d}$) for N-Caltech101 and N-Cars dataset, respectively. Unless otherwise specified, all the multihead residual attention blocks use h (number of heads) = 4, and the number of stacks for the Refine operator, $R = 2$. Additional details including training hyperparameters and time intervals can be found in Appendix E.

Representation Learning in Associative Memory: We first visualize the evolution of the learned representation in the associative memory for different classes of N-Caltech101 (Figure 5). Initially, the memory representation starts from the same initial state for all classes. As events are observed over time, the memory states start to form unique patterns for different classes. The tSNE plot in Figure 5(c) shows that the learned representations for various classes form a distinct cluster enabling separation of the class boundaries even with a relatively simple classifier head.

Temporal Update of Learned Representations with Class Updates We study the temporal updates of the memory states over time when samples from two different classes are passed to EventFormer in a streaming manner (Figure 6). We observe that the memory representation is updated as the object class changes, enabling accurate classification results over time. We randomly take 3000 samples from the N-Caltech101 dataset consisting of sequential class change (3000 unique class combinations). We plot the distribution of the number of events required for the target class output

Figure 6: **Memory representation dynamics over sequential class update**. **(a)** Change in prediction probability of the target class over time. **(b)** change in memory representation when class changes occur. **(c)** Average memory update activity for a large-scale experiment similar to (a) and (b), and **(d)** their corresponding perception latency distribution.

Figure 7: **Memory representation dynamics over sequential input transformation**. **(a)** Change in prediction probability of the target class over time. **(b)** change in memory representation when transformed input appears. **(c)** Average memory update activity for a large-scale experiment similar to (a) and (b), and **(d)** their corresponding perception latency distribution.

to reach a 0.6 confidence, hereafter referred to as the perception latency (Figure 6 (d)). The median perception latency is ~ 120 and ~ 60 events for the initial and new class, respectively. The perception latency for the initial class (red) has a wider distribution since the memory has to adapt its representation from the initial state. We also plot the mean and standard deviation of the Frobenius norm of the difference between two successive memory representations $\|\mathcal{M}_{t+1} - \mathcal{M}_t\|_2$, hereafter referred to as the memory update activity, for the same experiment (Figure 6 (c)). Higher memory update activity, observed when developing the representation of the initial class, stabilizes with more events of the same class. The change in the class also results in increased memory update activity but less than the initial case. This shows that EventFormer can adapt to new representations in real-time and re-use important features already computed in the past thereby reducing perception latency.

Temporal Update of Learned Representations with Input Transformations We study the temporal update of the memory states over time while objects from the same class but with different transformations (rotation) are passed to EventFormer in a streaming manner (Figure 7). With the incoming events from the rotated sample, we observe degradation in prediction probability due to representation update, which stabilizes over time. We consider 3000 random samples from N-Caltech101 with combinations of two random rotations between 10 to 30 degrees. We observe that the memory update activity is less for input transformation of the same example (Figure 7 (c)), compared to a completely new example (Figure 6 (c)). This shows that EventFormer can preserve learned representation for a class even under input transformation enabling less memory update activity.

Computational complexity: We analytically derive the computational complexity model of EventFormer (details in the Appendix C). We study the FLOP contributions from the key components in

Figure 8: **FLOP analysis.** (a) Normalized FLOP contribution from the key components of Event-Former (for n=1). (b) Change in relative compute cost for the `Operators` with increasing n.

Experiment	Associative memory	Separate write and erase operator	Refine operator	Accuracy ↑	MFLOPs/ev ↓
(a)	✗	✗	✓	0.670	0.014
(b)	✓	✗	✓	0.752	0.041
(c)	✓	✓	✗	0.703	0.035
(d)	✓	✓	✓	**0.848**	**0.048**

Table 1: Ablation study of the effectiveness of various key-components of EventFormer. Performances are evaluated on the N-Caltech101 dataset.

Figure 8. For a single event (n=1), most of the FLOP costs are from the memory update blocks due to their $\mathcal{O}(md^2 + md + d^2)$ compute complexity. With larger n the cost of memory update diminishes and `Read` and `Refine` operator start to dominate (Figure 8 (b)).

Ablation study on the components: We consider the experiments where EventFormer is implemented without *(a):* the associative memory, *(b):* separate `Write` and `Erase` operator, and *(c):* `Refine` operator and compare the results with *(d):* the complete EventFormer to analyze the impact of different components. For experiment (a), we pool the $\mathcal{X}_t$ to a 1-dimensional vector (Vemprala et al., 2021) to deal with the variable-sized sequence. Also, we make the hidden size of the recurrent module $m \times d$ so that the `FF`$_{\tt pred}$ receives the same sized input. In experiment (b), we linearly project the output of the `Write` operator into a $\mathbb{R}^{m \times 2d}$

Hyperparameter		Accuracy ↑	MFLOPs/ev ↓
	1	0.759	0.042
R	2	0.848	0.048
	4	0.864	0.061
	16	0.550	0.012
$m(= d)$	32	0.848	0.048
	48	0.882	0.108

Table 2: Performance of EventFormer on N-Caltech101 with different hyperparameters.

space and split it into two equal sized vectors to get $\mathcal{M}'_t$ and α_t. The results are shown in Table 1. Merging the write and erase operation marginally reduces the MFLOPs/ev, but at the expense of less flexibility during memory updates and hence, lower accuracy. On the other hand, when the `Refine` operator is eliminated, the model saves more computation but lacks the higher order interaction modeling among the events, causing marginal accuracy loss. Finally, we observe that eliminating the associative memory reduces maximum computation but also causes the model to lose spatial information (due to the pooling operation) resulting in minimum performance.

Effect of Hyperparameters: We study the impact of hyperparameters R and $m(= d)$ (Table 2). We observe that increasing their values result in better performance but at the cost of higher MFLOPs/ev. Therefore, we follow our initial setting (R=2 and $m(= d)$=32) to have a better balance between accuracy and compute cost while comparing with the state-of-the-art methods.

Methods	Representation	Async.	N-Caltech101		N-Cars	
			Accuracy ↑	MFLOPs/ev ↓	Accuracy ↑	MFLOPs/ev ↓
H-First	Spike	✓	0.054	-	0.561	-
Gabor-SNN	Spike	✓	0.284	-	0.789	-
HOTS	Time-Surface	✓	0.210	54.0	0.624	14.0
HATS	Time-Surface	✓	0.642	4.3	0.902	0.03
DART	Time-Surface	✓	0.664	-	-	-
EST	Event-Histogram	✗	0.817	4150	0.925	1050
Matrix-LSTM	Event-Histogram	✗	0.843	1580	0.926	1250
YOLE	Voxel-Grid	✓	0.702	3659	0.927	328.16
AsyNet	Voxel-Grid	✓	0.745	202	0.944	21.5
EvS-S	Graph	✓	0.761	11.5	0.931	6.1
AEGNN	Graph	✓	0.668	0.369	0.945	0.03
Ours	Unstructured Set	✓	**0.848**	**0.048**	**0.943**	**0.013**

Table 3: Performance comparison with state-of-the-art event-based and dense methods.

Comparison with the state-of-the-art: We compare the performance of EventFormer with state-of-the-art dense and event-based methods on the test set of these two datasets (Table 3). Following the previous work (Schaefer et al., 2022), we report the MFLOPs/ev on an average window of 25000 events. Methods that employ hand-crafted features: H-First (Orchard et al., 2015), Gabor-SNN (Bovik et al., 1990), HOTS (Lagorce et al., 2016), HATS (Sironi et al., 2018), DART (Ramesh et al., 2019), typically require fewer MFLOPs/ev, however, they lack behind the data-driven approaches in terms of accuracy. EST (Gehrig et al., 2019) and Matrix-LSTM (Cannici et al., 2020b) are synchronous methods that jointly learn the optimal representation in an end-to-end manner and achieve higher accuracy. However, they require compute-intensive feature extractors (such as ResNet) to work on these learned representations. Whereas EventFormer does not require any such complex feature extractors since the learned representation in the memory captures both the spatial and temporal information. Therefore, it can achieve similar performance with $30000\times$ less computation. YOLE (Cannici et al., 2019) and AsyNet (Messikommer et al., 2020) modify the existing CNN architectures to enable asynchronous and sparse processing to reduce the compute cost. However, they do not account for the temporal information present in the events. EvS-S (Li et al., 2021c) and AEGNN(Schaefer et al., 2022) are graph-based methods that employ an asynchronous formulation for updating the graph nodes in a compute-efficient manner. However, these methods require subsampling the events to restrict the graph size from growing prohibitively large, leading to suboptimal performance due to the information loss. Our method, on the other hand, inherently learns to leverage useful events to update the memory representation without requiring any redundant computation (such as radius search). Also, the memory mechanism enables learning better temporal correlation compared to the graph-based methods. As a result, our method achieves 9% better accuracy on complex dataset like N-Caltech101 while being $200\times$ more efficient compared to (Li et al., 2021c).

Computation Latency: The computation latency of EventFormer implemented with PyTorch (Paszke et al., 2019) on an Nvidia RTX3090 is 4.5ms per event on N-Caltech101 dataset. Our method is $10\times$ faster than the existing most computationally efficient method (Schaefer et al., 2022) which takes 52ms for processing one event. Unlike this existing method, we do not require searching over a large graph to update the representation which reduces computational latency.

4   CONCLUSION AND FUTURE WORK

We propose a novel memory-augmented representation learning framework–EventFormer, for asynchronous and efficient event-based perception. EventFormer learns to store, retrieve and update its memory representation in the latent form of higher order spatiotemporal dynamics of the events that allow it to achieve high performance with minimal compute cost. Our experiments show that it can be an order of magnitude efficient and faster compared to the existing methods while achieving excellent performance on the event-based object recognition tasks. This opens up future research directions for memory-augmented networks on more challenging event-based tasks including high-speed object detection, vision-based control, and navigation.

REFERENCES

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

Raymond Baldwin, Ruixu Liu, Mohammed Mutlaq Almatrafi, Vijayan K Asari, and Keigo Hirakawa. Time-ordered recent event (tore) volumes for event cameras. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2022.

Alan C. Bovik, Marianna Clark, and Wilson S. Geisler. Multichannel texture analysis using localized spatial filters. *IEEE transactions on pattern analysis and machine intelligence*, 12(1):55–73, 1990.

Christian Brandli, Raphael Berner, Minhao Yang, Shih-Chii Liu, and Tobi Delbruck. A 240 × 180 130 db 3 μs latency global shutter spatiotemporal vision sensor. *IEEE Journal of Solid-State Circuits*, 49(10):2333–2341, 2014. doi: 10.1109/JSSC.2014.2342715.

Marco Cannici, Marco Ciccone, Andrea Romanoni, and Matteo Matteucci. Asynchronous convolutional networks for object detection in neuromorphic cameras. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 0–0, 2019.

Marco Cannici, Marco Ciccone, Andrea Romanoni, and Matteo Matteucci. A differentiable recurrent surface for asynchronous event-based data. In *European Conference on Computer Vision*, pp. 136–152. Springer, 2020a.

Marco Cannici, Marco Ciccone, Andrea Romanoni, and Matteo Matteucci. Matrix-lstm: a differentiable recurrent surface for asynchronous event-based data. In *Proceedings of the European Conference on Computer Vision (ECCV), Glasgow, UK*, pp. 23–28, 2020b.

Kyunghyun Cho, Bart Van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*, 2014.

Davide Falanga, Kevin Kleber, and Davide Scaramuzza. Dynamic obstacle avoidance for quadrotors with event cameras. *Science Robotics*, 5(40):eaaz9712, 2020.

Thomas Finateu, Atsumi Niwa, Daniel Matolin, Koya Tsuchimoto, Andrea Mascheroni, Etienne Reynaud, Pooria Mostafalu, Frederick Brady, Ludovic Chotard, Florian LeGoff, Hirotsugu Takahashi, Hayato Wakabayashi, Yusuke Oike, and Christoph Posch. 5.10 a 1280×720 back-illuminated stacked temporal contrast event-based vision sensor with 4.86μm pixels, 1.066geps readout, programmable event-rate controller and compressive data-formatting pipeline. In *2020 IEEE International Solid- State Circuits Conference - (ISSCC)*, pp. 112–114, 2020. doi: 10.1109/ISSCC19947.2020.9063149.

Guillermo Gallego, Tobi Delbrück, Garrick Orchard, Chiara Bartolozzi, Brian Taba, Andrea Censi, Stefan Leutenegger, Andrew J Davison, Jörg Conradt, Kostas Daniilidis, et al. Event-based vision: A survey. *IEEE transactions on pattern analysis and machine intelligence*, 44(1):154–180, 2020.

Daniel Gehrig, Antonio Loquercio, Konstantinos G Derpanis, and Davide Scaramuzza. End-to-end learning of representations for asynchronous event-based data. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 5633–5643, 2019.

Mathias Gehrig, Willem Aarents, Daniel Gehrig, and Davide Scaramuzza. Dsec: A stereo event camera dataset for driving scenarios. *IEEE Robotics and Automation Letters*, 6(3):4947–4954, 2021.

Jesse J Hagenaars, Federico Paredes-Vallés, Sander M Bohté, and Guido CHE De Croon. Evolved neuromorphic control for high speed divergence-based landings of mavs. *IEEE Robotics and Automation Letters*, 5(4):6239–6246, 2020.

Geethan Karunaratne, Manuel Schmuck, Manuel Le Gallo, Giovanni Cherubini, Luca Benini, Abu Sebastian, and Abbas Rahimi. Robust high-dimensional memory-augmented neural networks. *Nature communications*, 12(1):1–12, 2021.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Ankit Kumar, Ozan Irsoy, Peter Ondruska, Mohit Iyyer, James Bradbury, Ishaan Gulrajani, Victor Zhong, Romain Paulus, and Richard Socher. Ask me anything: Dynamic memory networks for natural language processing. In *International conference on machine learning*, pp. 1378–1387. PMLR, 2016.

Xavier Lagorce, Garrick Orchard, Francesco Galluppi, Bertram E Shi, and Ryad B Benosman. Hots: a hierarchy of event-based time-surfaces for pattern recognition. *IEEE transactions on pattern analysis and machine intelligence*, 39(7):1346–1359, 2016.

Yang Li, Si Si, Gang Li, Cho-Jui Hsieh, and Samy Bengio. Learnable fourier features for multi-dimensional spatial positional encoding. *Advances in Neural Information Processing Systems*, 34:15816–15829, 2021a.

Yijin Li, Han Zhou, Bangbang Yang, Ye Zhang, Zhaopeng Cui, Hujun Bao, and Guofeng Zhang. Graph-based asynchronous event processing for rapid object recognition. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 934–943, October 2021b.

Yijin Li, Han Zhou, Bangbang Yang, Ye Zhang, Zhaopeng Cui, Hujun Bao, and Guofeng Zhang. Graph-based asynchronous event processing for rapid object recognition. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 934–943, 2021c.

Chao Ma, Chunhua Shen, Anthony Dick, Qi Wu, Peng Wang, Anton van den Hengel, and Ian Reid. Visual question answering with memory-augmented networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 6975–6984, 2018.

Ana I Maqueda, Antonio Loquercio, Guillermo Gallego, Narciso García, and Davide Scaramuzza. Event-based vision meets deep learning on steering prediction for self-driving cars. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5419–5427, 2018.

Nico Messikommer, Daniel Gehrig, Antonio Loquercio, and Davide Scaramuzza. Event-based asynchronous sparse convolutional networks. In *European Conference on Computer Vision*, pp. 415–431. Springer, 2020.

Garrick Orchard, Cedric Meyer, Ralph Etienne-Cummings, Christoph Posch, Nitish Thakor, and Ryad Benosman. Hfirst: A temporal approach to object recognition. *IEEE transactions on pattern analysis and machine intelligence*, 37(10):2028–2040, 2015.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.

Bharath Ramesh, Hong Yang, Garrick Orchard, Ngoc Anh Le Thi, Shihao Zhang, and Cheng Xiang. Dart: distribution aware retinal transform for event-based cameras. *IEEE transactions on pattern analysis and machine intelligence*, 42(11):2767–2780, 2019.

Simon Schaefer, Daniel Gehrig, and Davide Scaramuzza. Aegnn: Asynchronous event-based graph neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12371–12381, 2022.

Zhuoran Shen, Mingyuan Zhang, Haiyu Zhao, Shuai Yi, and Hongsheng Li. Efficient attention: Attention with linear complexities. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pp. 3531–3539, 2021.

Amos Sironi, Manuele Brambilla, Nicolas Bourdis, Xavier Lagorce, and Ryad Benosman. Hats: Histograms of averaged time surfaces for robust event-based object classification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1731–1740, 2018.

Bongki Son, Yunjae Suh, Sungho Kim, Heejae Jung, Jun-Seok Kim, Changwoo Shin, Keunju Park, Kyoobin Lee, Jinman Park, Jooyeon Woo, Yohan Roh, Hyunku Lee, Yibing Wang, Ilia Ovsiannikov, and Hyunsurk Ryu. 4.1 a 640×480 dynamic vision sensor with a 9μm pixel and 300meps address-event representation. In *2017 IEEE International Solid-State Circuits Conference (ISSCC)*, pp. 66–67, 2017. doi: 10.1109/ISSCC.2017.7870263.

Yunjae Suh, Seungnam Choi, Masamichi Ito, Jeongseok Kim, Youngho Lee, Jongseok Seo, Heejae Jung, Dong-Hee Yeo, Seol Namgung, Jongwoo Bong, Sehoon Yoo, Seung-Hun Shin, Doowon Kwon, Pilkyu Kang, Seokho Kim, Hoonjoo Na, Kihyun Hwang, Changwoo Shin, Jun-Seok Kim, Paul K. J. Park, Joonseok Kim, Hyunsurk Ryu, and Yongin Park. A 1280×960 dynamic vision sensor with a 4.95-μm pixel pitch and motion artifact minimization. In *2020 IEEE International Symposium on Circuits and Systems (ISCAS)*, pp. 1–5, 2020. doi: 10.1109/ISCAS45731.2020. 9180436.

Sihao Sun, Giovanni Cioffi, Coen De Visser, and Davide Scaramuzza. Autonomous quadrotor flight despite rotor failure with onboard vision sensors: Frames vs. events. *IEEE Robotics and Automation Letters*, 6(2):580–587, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Sai Vemprala, Sami Mian, and Ashish Kapoor. Representation learning for event-based visuomotor policies. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 4712–4724. Curran Associates, Inc., 2021.

Qinyi Wang, Yexin Zhang, Junsong Yuan, and Yilong Lu. Space-time event clouds for gesture recognition: From rgb cameras to event cameras. In *2019 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pp. 1826–1835. IEEE, 2019.

Alex Zihao Zhu, Dinesh Thakur, Tolga Özaslan, Bernd Pfrommer, Vijay Kumar, and Kostas Daniilidis. The multivehicle stereo event camera dataset: An event camera dataset for 3d perception. *IEEE Robotics and Automation Letters*, 3(3):2032–2039, 2018.

Supplement to "Associative Memory Augmented Asynchronous Spatiotemporal Representation Learning for Event-based Perception"

A   APPENDIX

In this supplementary material, we provide experimental and additional details on EventFormer.

B   DETAILS OF THE NOTATION USED IN THIS WORK

Type	Description	Notation	Dimension
Scaler parameters	number of events	n	-
	dimension of event-representation	d	-
	row size of the memory	m	-
	number of classes	c	-
Functions	positional encoder	$\Pi(.)$	-
	recurrent module	$\mathcal{R}(.,.)$	-
	classifier head	$\text{FF}_{\text{pred}}(.)$	-
Vector/Matrix	sequence of events at time t	x_t	$n \times 2$
	positional embedding	π_t	$n \times d$
	associative memory representation at t	$\mathcal{M}_t$	$m \times d$
	retrieved state from the memory (past hidden state for the recurrent module)	$\mathcal{H}_{t-1}$	$n \times d$
	representation with higher order interaction among the events	$\mathcal{Z}_t$	$n \times d$
	current spatiotemporal representation	$\mathcal{X}_t$	$n \times d$
	new memory representation at t	$\mathcal{M}'_t$	$m \times d$
	scaling factors to control memory update	α_t	$m \times d$
	prediction at time t	Y_t	$1 \times c$

Table 4: Different notations used to describe the operations of EventFormer

C   DERIVATION OF COMPUTATIONAL COMPLEXITY MODEL OF EVENTFORMER

Here we derive the computational complexity model of the proposed EventFormer architecture. Let us define n as the number of events to be processed within time-interval τ, d as the dimension of the representation, m as the number of rows in the memory, h be the number of heads in the residual attention blocks (we use the same h in all the blocks), r as the number of stacks for the `Refine` operator, and c be the number of class for the recognition task.

(i) Positional Encoder: Our positional encoder block consists of single matrix multiplication with the input, that is to compute $x_t W_p^T$, we need $2nd$ multiplications and $nd(2-1)$ additions, so in total $3nd$ FLOPs.

(ii) Read Operator: Read operator consists of a residual multihead attention block with h heads. To begin with, calculating the query matrix for each head, we need $n(\frac{d}{h})^2$ multiplication and $n\frac{d}{h}(\frac{d}{h}-1)$ additions, so in total $n\frac{d}{h}(2\frac{d}{h}-1)$ FLOPs. Similarly for the key and value matrix, we need total $2m\frac{d}{h}(2\frac{d}{h}-1)$ FLOPs. Then, to compute $QK^\top$, we need an additional $mn(2\frac{d}{h}-1)$ computation. Similarly the product $(QK^\top)V$ requires $n\frac{d}{h}(2m-1)$ FLOPs. Upto now for each head, we require total FLOPs:

$$n\frac{d}{h}(2\frac{d}{h} - 1) + 2m\frac{d}{h}(2\frac{d}{h} - 1) + mn(2\frac{d}{h} - 1) + n\frac{d}{h}(2m - 1),$$

Therefore, for h heads, it becomes:

$$nd(2\frac{d}{h} - 1) + 2md(2\frac{d}{h} - 1) + hmn(2\frac{d}{h} - 1) + nd(2m - 1)$$

The following 2 residual connection involves pointwise addition of a $n \times d$ dimensional matrix and the out-projection involves an additional $nd(2d - 1)$ FLOPs. Finally, total FLOPs count for the $\texttt{Read}(\pi_\texttt{t}, \mathcal{M}_\texttt{t-1})$ becomes:

$$nd(2\frac{d}{h} - 1) + 2md(2\frac{d}{h} - 1) + hmn(2\frac{d}{h} - 1) + nd(2m - 1) + 2nd + 2nd(2d - 1)$$

(iii) Recurrent Module: Our recurrent module is a GRU that involves 3 matrix multiplication (update, reset, hidden) for the current input, π_t and hidden state H_{t-1} each. Therefore 6 matrix multiplication in total followed by 5 elementwise addition and 2 elementwise multiplication. Therefore, the total computation becomes:

$$6nd(2d - 1) + 7nd$$

(iv) Refine Operator: Unlike the $\texttt{Read}(.,.)$ operator, it projects the same input, X_t to query, key and value space. Therefore, total computation for such project becomes $3n\frac{d}{h}(2\frac{d}{h} - 1)$, followed by additional $(\frac{d}{h})^2(2n - 1)$ and $n\frac{d}{h}(2\frac{d}{h} - 1)$ FLOPs for $K^\top V$, and $Q(K^\top V)$ computation. Therefore, for h heads and considering the additional cost for residual operations and out-projections, the final cost becomes:

$$r\left(3nd(2\frac{d}{h} - 1) + (\frac{d^2}{h})(2n - 1) + nd(2\frac{d}{h} - 1) + 2nd + 2nd(2d - 1)\right)$$

here r accounts for the number of stacks.

(iv) Write and Erase Operator: Similar to the $\texttt{Read}(.,.)$ operator, we can calculate the total FLOPs required for the $\texttt{Write}(\mathcal{M}_{t-1}, Z_t)$ and $\texttt{Erase}(\mathcal{M}_{t-1}, Z_t)$ operation combined as follows:

$$2\left(md(2\frac{d}{h} - 1) + 2nd(2\frac{d}{h} - 1) + hmn(2\frac{d}{h} - 1) + md(2n - 1) + 2md + 2md(2d - 1)\right) + 3md$$

here, the additional $3md$ accounts for the 2 pointwise addition and 1 multiplication in Equation 8.

(iv) Perception Output: The final output is calculated by a vector($\in \mathbb{R}^{md}$)-matrix($\in \mathbb{R}^{md \times c}$) multiplication, which requires an additional $c(2md - 1)$ FLOPs.

Total FLOPs: The total FLOPs accounting all the above computation becomes:

$$
\underbrace{3nd}_{\text{Positional Encoder}} + \underbrace{nd(2\frac{d}{h} - 1) + 2md(2\frac{d}{h} - 1) + hmn(2\frac{d}{h} - 1) + nd(2m - 1) + 2nd + 2nd(2d - 1) +}_{\text{Read Operation}}
$$

$$
\underbrace{6nd(2d - 1) + 7nd}_{\text{Recurrent Module}} + \underbrace{r\left(3nd(2\frac{d}{h} - 1) + (\frac{d^2}{h})(2n - 1) + nd(2\frac{d}{h} - 1) + 2nd + 2nd(2d - 1)\right)}_{\text{Refine Operator}}
$$

$$
+ \underbrace{2\left(md(2\frac{d}{h} - 1) + 2nd(2\frac{d}{h} - 1) + hmn(2\frac{d}{h} - 1) + md(2n - 1) + 2md + 2md(2d - 1)\right) + 3md}_{\text{Memory Update (includes both Write and Erase operation)}}
$$

$$
+ \underbrace{c(2md - 1)}_{\text{Output}}
$$

$$(9)$$

D   DETAILS OF THE DATASETS

N-Caltech101 (Orchard et al., 2015) is converted to event-space from standard frame-based dataset (Caltech101). It has 8246 event-sequences from 101 class categories following the original Caltech101 dataset. N-Caltech101 uses an event-based camera to record event streams generated by moving images displayed on a monitor.

N-Cars (Sironi et al., 2018) is a real-world event-camera dataset with 24039 event sequence from 2-class instances (car or background). N-Cars utilizes an event camera mounted on a moving car recording its surroundings in a real-world setting.

E   TRAINING DETAILS

Data Preparation: For both of the dataset, we use the official test set portion to report the result and split the remaining into 90% and 10% ratios for training and validation purposes. The event coordinates are normalized by dividing them by the height and width (180×260 for N-Caltech101 and 100×120 for N-Cars) of the frame resolution. We use 50 ms long sequence for each sample to reduce training complexity. Each sample is chunked by a 1ms window, resulting in 50-sequences for each sample.

Optimization: We use the standard categorical cross-entropy as the loss function to train the network with Adam (Kingma & Ba, 2014) with batch size 128 for N-Cars and 64 for N-Caltech101 with an initial learning rate of $1e^{-3}$ that decreases by a factor of 5 after every 25 epochs. The memory representation is initialized by a set of learnable parameters $\mathcal{M}_I \in \mathbb{R}^{m \times d}$. We also use a dropout of 0.2 on the memory representation before passing them to the final classification layer. To avoid gradient explosion during training, we use gradient clipping with a maximum gradient norm of 100.