Case-based Reasoning for Better Generalization in Text-Adventure Games

Abstract

Text-based games (TBG) have emerged as promising environments for driving research in grounded language understanding and studying problems like generalization and sample efficiency. Several deep reinforcement learning (RL) methods with varying architectures and learning schemes have been proposed for TBGs. However, these methods fail to generalize efficiently, especially under distributional shifts. In a departure from deep RL approaches, in this paper, we propose a general method inspired by case-based reasoning to train agents and generalize out of the training distribution. The case-based reasoner collects instances of positive experiences from the agent's interaction with the world and later reuses the collected experiences to act efficiently. The method can be used in conjunction with any existing on-policy neural agent introduced in the literature for TBGs. Our experiments show that the proposed approach consistently improves existing methods, obtains good out-of-distribution generalization and achieves new state-of-the-art results on widely used environments.

1 Introduction

Text-based games (TBGs) have emerged as key benchmarks for studying how reinforcement learning (RL) agents can tackle the challenges of grounded language understanding, partial observability, large action spaces, and out-of-distribution generalization (Hausknecht et al., 2020; Bahdanau et al., 2019; Ammanabrolu & Riedl, 2019). While we have indeed made some progress on these fronts in recent years and several new RL agent architectures have been proposed (Ammanabrolu & Hausknecht, 2020; Adhikari et al., 2020; Murugesan et al., 2021b;a), these agents are still very inefficient and suffer from insufficient generalization to novel environments. As an example, state-of-the-art agents require 5 to 10 times more steps than a human to accomplish even simple household tasks (Murugesan et al., 2021b). As the agents are purely neural architectures requiring significant training experience and compute, they fail to efficiently adapt to new environments and use their past experiences to reason in novel situations. This is in stark contrast to human learning which is much more robust, efficient and generalizable (Lake et al., 2017).

Motivated by this fundamental difference in learning, we propose new agents for TBGs that rely on case-based reasoning (CBR) (Aamodt & Plaza, 1994) to efficiently act in the world. CBR draws its foundations in cognitive science (Schank, 1983; Kolodner, 1983) and mimics the process of solving new tasks based on solutions to previously encountered similar tasks. Concretely, we design a general CBR framework that enables an agent to collect instances of past situations which led to a positive reward (known as cases) while interacting with the world. During decision making, the agent retrieves a case most similar to the current situation and then applies it after appropriately mapping the case to the current context.

The CBR agent stores past experiences, along with the actions it performed, in a repository called its memory. To efficiently use this information, the agent should be able to represent relevant information from the state of the game in a compact way, while retaining the property that contexts that require similar actions receive similar representations. We represent the state of the game as a knowledge graph (Ammanabrolu & Hausknecht, 2020) and we address these challenges by *(a)* introducing a seeded message propagation scheme that focuses only on the relevant subset of nodes and *(b)* using vector quantization (Ballard, 2000) to efficiently map similar contexts to similar discrete representations. Vector quantization allows the model to significantly compress the context

Figure 1: Overview of the proposed approach and architecture of the CBR agent. A memory stores actions that have been used successfully in previous experience. The context of the game is represented by a graph attention mechanism focused on a subset of the entities. Actions are retrieved based on the context and mapped to the current state. If no valid action is obtained, a neural agent selects the most likely action.

representations while retaining their semantics; thereby, allowing for a scalable implementation of CBR in RL settings. An illustration of the approach is shown in Figure 1.

Our experiments show that CBR can be used to consistently boost the performance of various on-policy RL agents proposed in literature for TBGs. We obtain a new state of the art on the *TextWorld Commonsense* (Murugesan et al., 2021b) dataset and we achieve better or comparable scores on 24 of the 33 games in the *Jericho* suite (Hausknecht et al., 2020). We further demonstrate that CBR agents are resilient to domain shifts and suffer only marginal drops in performance (**6%**) on out-of-distribution settings when compared to their counterparts (**35%**).

2 PRELIMINARIES

Text-based games. A text-based game (TBG) is an environment where an agent can observe the current state of the game and act in the world using only the modality of text. The state of the game is hidden, so a TBG can be modeled as a Partially Observable Markov Decision Process (POMDP) $(\mathcal{S}, \mathcal{A}, \mathcal{O}, \mathcal{T}, \mathcal{E}, r)$, where $\mathcal{S}$ is the set of states of the environment of the game, $\mathcal{A}$ is the natural language action space, $\mathcal{O}$ is the set of observations or sequences of words describing the current state, $\mathcal{T}$ are the conditional transition probabilities from one state to another, $\mathcal{E}$ are the conditional observation probabilities, r is the reward function, which maps a state and action to a scalar reward that the agent receives, $r : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$.

Case-based reasoning. Case-based Reasoning (CBR) is the process of solving new problems based on the solution of previously seen similar problems. Generally, CBR assumes access to a memory which stores past problems (known as cases) and their solutions. When a new problem is encountered, CBR will *(i)* **retrieve** a similar problem and its solution from memory; *(ii)* **reuse** the solution by mapping it to the current problem; *(iii)* **revise** the solution by testing it and checking whether it is viable way to address the new problem; and *(iv)* **retain** the solution in memory if the adaptation to the new problem was successful.

3 CASE-BASED REASONING IN REINFORCEMENT LEARNING

This section introduces our approach inspired by CBR for improving generalization in TBGs. Even though we situate our work in TBGs, it serves as a good starting point for applying CBR in more general RL settings. We consider an *on-policy* RL agent that, at any given time step t, has access to a memory $\mathcal{M}_t$, that can be used to retrieve previous experiences. The memory contains key-value pairs, where values are actions that were taken by the agent and the keys are a representation of the context where those actions were taken. As mentioned in Section 2, case-based reasoning can be formalized as a four-step process. We describe our proposal for each step below. Algorithm 1 provides a detailed formalization of our approach.

Retrieve. Given the state of the game s_t and the valid actions $\mathcal{A}_t$, we want to retrieve from the memory $\mathcal{M}_t$ previous experiences that might be useful in decision-making at the current state. To this end, for each admissible action $a_t \in \mathcal{A}_t$, we define a context selector $c_t = context(s_t, a_t)$. The context selector is an action-specific representation of the state, namely the portion of the state that is relevant to the execution of an action. We will explain later how the context selector is defined in our implementation. Next, for each context c_t, we retrieve from the memory the context-action pair $(c_t^{\mathcal{M}}, a_t^{\mathcal{M}})$, such that $c_t^{\mathcal{M}}$ has maximum similarity with c_t. We denote as $\delta = sim(c_t, c_t^{\mathcal{M}}) \in [0,1]$ the relevance score given to the retrieved action. Only actions $a_t^{\mathcal{M}}$ with a relevance score above a *retriever threshold* τ are retrieved from $\mathcal{M}_t$. We denote as $\mathcal{A}_t^{\mathcal{M}}$ the final set of all the retrieved actions and the corresponding relevance.

Reuse. The goal of the reuse step is to adapt the actions retrieved from the memory based on the current state. This is accomplished by a *reuse* function, that is applied to each retrieved action to construct a set $\tilde{\mathcal{A}}_t$ of candidate actions that should be applicable to the current state, each paired with a confidence level.

Revise. If any of the action candidates $\tilde{\mathcal{A}}_t$ is a valid action, then the one with the highest relevance δ is executed, otherwise a neural agent π is used to select the best action $a_t^\star$. We denote with $r_t = r(s_t, a_t^\star)$ the obtained reward obtained. Note that π can be an existing agent for TBGs (Murugesan et al., 2021c;b; Ammanabrolu & Hausknecht, 2020).

Algorithm 1: CBR in Text-based RL

● **Retrieve**

Let $\mathcal{C}_t = \{context(s_t, a_t) \mid a_t \in \mathcal{A}_t\}$ be a set of context selectors for state s_t at time step t

$\mathcal{A}_t^{\mathcal{M}} \leftarrow \emptyset$

for $c_t \in \mathcal{C}_t$ **do**

  Let $(c_t^{\mathcal{M}}, a_t^{\mathcal{M}}) = \arg\max_{(c_t^{\mathcal{M}}, a_t^{\mathcal{M}}) \in \mathcal{M}_t} sim(c_t, c_t^{\mathcal{M}})$

  Let $\delta = sim(c_t, c_t^{\mathcal{M}})$

  if $\delta > \tau$ **then**

    | $\mathcal{A}_t^{\mathcal{M}} \leftarrow \mathcal{A}_t^{\mathcal{M}} \cup \{(a_t^{\mathcal{M}}, \delta)\}$

  end

end

● **Reuse**

Build a set of action candidates:

$$\tilde{\mathcal{A}}_t = \{reuse(a_t^{\mathcal{M}}, s_t, \delta) \mid (a_t^{\mathcal{M}}, \delta) \in \mathcal{A}_t^{\mathcal{M}}\}$$

● **Revise**

if $\mathcal{A}_t \cap \tilde{\mathcal{A}}_t \neq \emptyset$ **then**

  | Let $a_t^\star, \delta^\star = \arg\max_{\tilde{a}_t, \delta \in \tilde{\mathcal{A}}_t} \delta$

else

  | $a_t^\star = \arg\max_{a_t \in \mathcal{A}_t} \pi(a_t | s_t)$

end

Let $r_t = r(s_t, a_t^\star)$ be the reward obtained at time step t by executing action $a_t^\star$

● **Retain**

Let $c_t^\star = context(s_t, a_t^\star)$ be the context of action $a_t^\star$

Let $B = \{(c_t^\star, a_t^\star), (c_{t-1}^\star, a_{t-1}^\star), \ldots, (c_{t-m+1}^\star, a_{t-m+1}^\star)\}$

if $r_t > 0$ **then**

  | $\mathcal{M}_{t+1} \leftarrow \mathcal{M}_t \cup B$

end

Retain. Finally, the retain step stores successful experiences as new cases in the memory, so that they can be retrieved in the future. In principle, this can be accomplished by storing actions for which the agent obtained positive reward. However, we found that storing previous actions as well can result in improved performance. Therefore, each action $a_t^\star$ is stored in a buffer B containing the $m \in \mathbb{N}^+$ most recent executed actions and their context. Whenever $r_t > 0$, the whole buffer B is stored in the memory, so that the actions in B can be retrieved in future time steps.

4 A CBR POLICY AGENT TO GENERALIZE IN TEXT-BASED GAMES

Designing an agent that can act efficiently in TBGs using the described approach poses several challenges. Above all, efficient memory use is crucial to making the approach practical and scalable. Since the context selectors are used as keys for accessing values in the memory, their representation needs to be such that contexts where similar actions were taken receive similar representations. At the same time, as the state space is exponential, context representations need to be focused only on relevant portions of the state and they need to be compressed and compact.

4.1 REPRESENTING THE CONTEXT THROUGH SEEDED GRAPH ATTENTION

State space as a knowledge graph. Following previous work (Ammanabrolu & Riedl, 2019; Ammanabrolu & Hausknecht, 2020; Murugesan et al., 2021c), we represent the state of the game as a dynamic knowledge graph $\mathcal{G}_t = (\mathcal{V}_t, \mathcal{R}_t, \mathcal{E}_t)$, where a node $v \in \mathcal{V}_t$ represents an entity in the game, $r \in \mathcal{R}_t$ is a relation type, and an edge $v \xrightarrow{r} v' \in \mathcal{E}_t$ represents a relation of type $r \in \mathcal{R}_t$ between entities $v, v' \in \mathcal{V}_t$. In TBGs, the space of valid actions $\mathcal{A}_t$ can be modeled as a template-based action space, where actions a_t are instances of a finite set of templates with a given set of entities, denoted as $\mathcal{V}_{a_t} \subseteq \mathcal{V}_t$. As an example, the action "*kill orc with sword*" can be seen as an instance of the template "*kill v_1 with v_2*", where v_1 and v_2 are "*orc*" and "*sword*" respectively.

Seeded graph attention. The state graph $\mathcal{G}_t$ and the entities $\mathcal{V}_{a_t}$ are provided as input to the agent for each action $a_t \in \mathcal{A}_t$, in order to build an action-specific contextualized representation of the state. A pre-trained BERT model (Devlin et al., 2019) is used to get a representation $\mathbf{h}_v^{(0)} \in \mathbb{R}^d$ for each node $v \in \mathcal{V}_t$. Inspired by Sun et al. (2018), we propose a seeded graph attention mechanism (GAT), so that the propagation of messages is weighted more for nodes close to the entities $\mathcal{V}_{a_t}$. Let $\alpha_{vu}^{(l)}$ denote the attention coefficients given by a graph attention network (Velickovic et al., 2018) at layer l for nodes $v, u \in \mathcal{V}_t$. Then, for each node $v \in \mathcal{V}_t$, we introduce a coefficient $\beta_v^{(l)}$ that scales the amount of messages received by node v at layer l:

$$\beta_v^{(1)} = \begin{cases} \frac{1}{|\mathcal{V}_{a_t}|} & \text{if } v \in \mathcal{V}_{a_t} \\ 0 & \text{otherwise} \end{cases}, \qquad \beta_v^{(l+1)} = (1-\lambda)\beta_v^{(l)} + \lambda \sum_{u \in \mathcal{N}_v} \alpha_{vu}^{(l)} \beta_u^{(l)},$$

where $\mathcal{N}_v$ denotes the neighbors of v, considering the graph as undirected. Note that, at layer $l = 1$, only the nodes in $\mathcal{V}_{a_t}$ receive messages, whereas for increasing values of l, $\beta_v^{(l)}$ will be non-zero for their $(l-1)$-hop neighbors as well. The representation of each $v \in \mathcal{V}_t$ is then updated as:

$$\mathbf{h}_v^{(l)} = \text{FFN}^{(l)}\left(\mathbf{h}_v^{(l-1)} + \beta_v^{(l)} \sum_{u \in \mathcal{N}_v} \alpha_{vu}^{(l)} \mathbf{W}^{(l)} \mathbf{h}_u^{(l-1)}\right),$$

where $\text{FFN}^{(l+1)}$ is a 2-layer feed-forward network with ReLU non-linearity and $\mathbf{W}^{(l)} \in \mathbb{R}^{d \times d}$ are learnable parameters. Finally, denoting with n_l the number of layers of seed graph attention, we compute a final continuous contextualized representation $\mathbf{c}_{a_t}$ of the state by summing the projected representations $\mathbf{h}_v^{(n_l)}$ of each $v \in \mathcal{V}_{a_t}$ and passing the result through a further feed-forward network.

4.2 MEMORY ACCESS THROUGH CONTEXT QUANTIZATION

Given a continuous representation $\mathbf{c}_{a_t}$ of the context, we need an efficient way to access the memory $\mathcal{M}_t$ in order to retrieve or store actions based on such a context selector. Storing and retrieving based on the continuous representation $\mathbf{c}_{a_t}$ would be impractical for scalability reasons. Additionally, since the parameters of the agent change over training, the same context would result in several duplicated entries in the memory even with a pre-trained agent over different episodes.

Discretization of the context. In order to address these problems, we propose to use vector quantization (Ballard, 2000) before reading or writing to memory. Following previous work (Chen et al., 2018; Sachan, 2020), we learn a discretization function $\phi : \mathbb{R}^d \rightarrow \mathbb{Z}_K^D$, that maps the continuous representation $\mathbf{c}_{a_t}$ into a K-way D-dimensional code $c_t \in \mathbb{Z}_K^D$, with $|\mathbb{Z}_K| = K$ (we refer to c_t as a KD code). With reference to Section 3, then we will use $c_t = context(s_t, a_t) = \phi(\mathbf{c}_{a_t})$ as the context selector used to access the memory $\mathcal{M}_t$. In order to implement the discretization function, we define a set of K key vectors $\mathbf{k}_i \in \mathbb{R}^d, i = 1, \ldots, K$, and we divide each vector in D partitions $\mathbf{k}_i^j \in \mathbb{R}^{d/D}, j = 1, \ldots, D$. Similarly, we divide $\mathbf{c}_{a_t}$ in D partitions $\mathbf{c}_{a_t}^j \in \mathbb{R}^{d/D}, j = 1, \ldots, D$. Then, we compute the j-th code z^j of c_t by nearest neighbor search, as $z^j = \arg\min_i \|\mathbf{c}_{a_t}^j - \mathbf{k}_i^j\|_2^2$. We use the straight-through estimator (Bengio et al., 2013) to address the non differentialbility of the *argmin* operator.

Memory access. The KD codes introduced above are used to provide a memory-efficient representation of the keys in the memory. Then, given the KD code representing the current context selector c_t, we query the memory by computing a similarity measure $sim(c_t, c_t^{\mathcal{M}})$ between c_t and each $c_t^{\mathcal{M}}$ in $\mathcal{M}_t$. The similarity function is defined as the fraction of codes shared by c_t and $c_t^{\mathcal{M}}$. The context-action pair with the highest similarity is returned as a result of the memory access, together with a relevance score δ representing the value of the similarity measure.

4.3 Symbolic action reuse and revise policy

We use a simple purely symbolic *reuse* function to adapt the actions retrieved from the memory to the current state. Let c_t be the context selector computed based on state s_t and the entities $\mathcal{V}_{a_t}$, as explained in Sections 4.1 and 4.2. Denote with $(c_t^{\mathcal{M}}, a_t^{\mathcal{M}})$ the context-action pair retrieved from $\mathcal{M}_t$ with confidence δ. Then, the reuse function $reuse(a_t^{\mathcal{M}}, s_t, \delta)$ constructs the action candidate $\tilde{a}_t$ as the action with the same template as $a_t^{\mathcal{M}}$ applied to the entities $\mathcal{V}_{a_t}$. If the reuse step cannot generate a valid action, we fallback to a neural policy agent π that outputs a probability distribution of the current admissible actions $\mathcal{A}_t$.

5 Training

In Section 3, we have introduced an on-policy RL agent that relies on case-based reasoning to act in the world efficiently. This agent can be trained in principle using any online RL method. This section discusses the training strategies and learning objectives used in our implementation.

Objective. In our implementation, two main portions of the model need to be trained: *(a)* the *retriever*, namely the neural network that computes the context representation and accesses the memory through its discretization, and *(b)* the main neural agent π which is used in the revise step. All agents π used in our experiments are trained with an Advantage Actor Critic (A2C) method (Mnih et al., 2016). For optimizing the parameters of π, we use the same learning objectives defined by Adolphs & Hofmann (2019). Whenever the executed action $a_t^\star$ is not chosen by the model π but it comes from the symbolic reuse step, then we optimize instead an additional objective for the retriever, namely the following contrastive loss (Hadsell et al., 2006):

$$\mathcal{L}_r^{(t)} = \frac{1}{2}(1 - y_t)(1 - sim(c_t, c_t^{\mathcal{M}}))^2 + \frac{1}{2}y_t \max\{0, \mu - 1 + sim(c_t, c_t^{\mathcal{M}})\}^2,$$

where c_t denotes the context selector of the action executed at time step t, $c_t^{\mathcal{M}}$ is the corresponding key entry retrieved from $\mathcal{M}_t$, μ is the margin parameter of the contrastive loss, and $y_t = 1$ if $r_t > 0$, $y_t = 0$ otherwise. This objective encourages the retriever to produce similar representations for two contexts where reusing an action yielded a positive reward.

Pretraining. To make learning more stable and allow the agent to act more efficiently, we found it beneficial to pretrain the retriever. This minimizes large shifts in the context representations over training. We run a baseline agent (Ammanabrolu & Hausknecht, 2020) to collect instances of the state graph and actions that yielded positive reward. Then we train the retriever to encode to similar representations contexts for which similar actions (i.e., actions with the same template) were used. This is achieved using the same contrastive loss defined above.

6 Experiments

This section provides a detailed evaluation of our approach. We assess quantitatively the performance of CBR combined with existing RL approaches and we demonstrate its capability to improve sample efficieny and generalize out of the training distribution. Next, we provide qualitative insights and examples of the behavior of the model and we perform an ablation study to understand the role played by the different components of the architecture.

6.1 Experimental setup

Agents. We consider several agents obtained by plugging existing RL methods in the revise step. We first define two simple approaches: **CBR-only**, where we augment a random policy with the

	Easy		Medium		Hard	
	#Steps	Norm. Score	#Steps	Norm. Score	#Steps	Norm. Score
Text	23.83 ± 2.16	0.88 ± 0.04	44.08 ± 0.93	0.60 ± 0.02	49.84 ± 0.38	0.30 ± 0.02
TPC	20.59 ± 5.01	0.89 ± 0.06	42.61 ± 0.65	0.62 ± 0.03	48.45 ± 1.13	0.32 ± 0.04
KG-A2C	22.10 ± 2.91	0.86 ± 0.06	41.61 ± 0.37	0.62 ± 0.03	48.00 ± 0.61	0.32 ± 0.00
BiKE	18.27 ± 1.13	0.94 ± 0.02	39.34 ± 0.72	0.64 ± 0.02	47.19 ± 0.64	0.34 ± 0.02
CBR-only	22.13 ± 1.98	0.80 ± 0.05	43.76 ± 1.23	0.62 ± 0.03	48.12 ± 1.30	0.33 ± 0.06
Text + CBR	17.53 ± 3.36	0.93 ± 0.04	39.10 ± 1.77	0.66 ± 0.04	47.11 ± 1.21	0.34 ± 0.02
TPC + CBR	16.81 ± 3.12	0.94 ± 0.03	37.05 ± 1.61	0.67 ± 0.03	47.25 ± 1.56	0.37 ± 0.03
KG-A2C + CBR	15.91 ± 2.52	0.95 ± 0.03	36.13 ± 1.65	0.66 ± 0.05	46.11 ± 1.13	0.40 ± 0.04
BiKE + CBR	15.72 ± 1.15	0.95 ± 0.04	35.24 ± 1.22	0.67 ± 0.03	45.21 ± 0.87	0.42 ± 0.04

Table 1: Test-set performance for *TWC in-distribution* games

	Easy		Medium		Hard	
	#Steps	Norm. Score	#Steps	Norm. Score	#Steps	Norm. Score
Text	29.90 ± 2.92	0.78 ± 0.02	45.90 ± 0.22	0.55 ± 0.01	50.00 ± 0.00	0.20 ± 0.02
TPC	27.74 ± 4.46	0.78 ± 0.07	44.89 ± 1.52	0.58 ± 0.01	50.00 ± 0.00	0.19 ± 0.03
KG-A2C	28.34 ± 3.63	0.80 ± 0.07	43.05 ± 2.52	0.59 ± 0.01	50.00 ± 0.00	0.21 ± 0.00
BiKE	25.59 ± 1.92	0.83 ± 0.01	41.01 ± 1.61	0.61 ± 0.01	50.00 ± 0.00	0.23 ± 0.02
CBR-only	23.43 ± 2.09	0.80 ± 0.04	44.03 ± 1.75	0.63 ± 0.04	48.71 ± 1.15	0.31 ± 0.03
Text + CBR	20.91 ± 1.72	0.89 ± 0.02	40.32 ± 1.27	0.66 ± 0.04	47.89 ± 0.87	0.32 ± 0.06
TPC + CBR	18.90 ± 1.91	0.92 ± 0.01	37.30 ± 1.00	0.66 ± 0.02	47.54 ± 1.67	0.34 ± 0.03
KG-A2C + CBR	18.21 ± 1.32	0.90 ± 0.02	37.02 ± 1.22	0.68 ± 0.03	47.10 ± 1.12	0.38 ± 0.02
BiKE + CBR	17.15 ± 1.45	0.93 ± 0.03	35.45 ± 1.40	0.67 ± 0.03	45.91 ± 1.32	0.40 ± 0.03

Table 2: Test-set performance for *TWC out-of-distribution* games

CBR approach, and **Text + CBR**, which relies on the CBR method combined with a simple GRU-based policy network that consumes as input the textual observation from the game. Next, we select three recently proposed TBG approaches: **Text+Commonsense** (**TPC**) (Murugesan et al., 2021b), **KG-A2C** (Ammanabrolu & Hausknecht, 2020), and **BiKE** (Murugesan et al., 2021c), to create the **TPC + CBR**, **KG-A2C + CBR** and **BiKE + CBR** agents. We treat the original agents as baselines.

Datasets. We empirically verify the efficacy of our approach on **TextWorld Commonsense** (*TWC*) (Murugesan et al., 2021b) and **Jericho** (Hausknecht et al., 2020). *Jericho* is a well-known and challenging learning environment including 33 interactive fiction games. *TWC* is an environment which builds on *TextWorld* (Côté et al., 2018) and provides a suite of games requiring commonsense knowledge. *TWC* allows agents to be tested on two settings: the *in-distribution games*, where the objects that the agent encounters in the test set are the same as the objects in the training set, and the *out-of-distribution games* which have no entity in common with the training set. For each of these settings, *TWC* provides three difficulty levels: *easy*, *medium*, and *hard*.

Evaluation metrics. Following Murugesan et al. (2021b), we evaluate the agents on *TWC* based on the number of steps (**#Steps**) required to achieve the goal (lower is better) and the normalized cumulative reward (**Norm. Score**) obtained by the agent (larger is better). On Jericho, we follow previous work (Hausknecht et al., 2020; Guo et al., 2020; Ammanabrolu & Hausknecht, 2020) and we report the average score achieved over the last 100 training episodes.

6.2 RESULTS ON TEXTWORLD COMMONSENSE

Table 1 reports the results on *TWC* for the *in-distribution* set of games. Overall, we observe that CBR consistently improves the performance of all the baselines. The performance boost is large enough that even a simple method as **Text + CBR** outperforms all considered baselines except **BiKE**.

Out-of-distribution generalization. CBR's ability to retrieve similar cases should allow our method to better generalize to new and unseen problems. In our next set of experiments, we test

Figure 2: Performance on *TWC* (showing mean and standard deviation averaged over 5 runs) for the three difficulty levels: *easy* (left), *medium* (middle), *Hard* (right) using normalized score and number of steps.

this hypothesis on the *out-of-distribution* games in TWC. The results of this experiment are reported in Table 2. We notice that all existing approaches fail to generalize out of the training distribution and suffer a substantial drop in performance in this setting. However, when coupled with CBR, the drop is minor (on average **6%** with CBR *vs* **35%** without on the hard level). Interestingly, even the **CBR-only** agent achieves competitive results with respect to the top-performing baselines.

Sample Efficiency. Another key benefit of our approach comes as better sample efficiency. With its ability to explicitly store prior solutions effectively, CBR allows existing algorithms to learn faster. Figure 2 shows the learning curves for our best agents and the corresponding baselines. The plots report the performance of the agent over the training episodes, both in terms of the number of steps and the normalized score. Overall, we observe that the CBR agents obtain faster convergence with respect to their counterparts on all difficulty levels.

6.3 PERFORMANCE ON THE JERICHO GAMES

We evaluate our best performing variant from the experiments on *TWC* (**BiKE + CBR**) against existing approaches on the 33 games in the Jericho environment. We compare our approach against strong baselines, including **TDQN** (Hausknecht et al., 2020), **DRRN** (He et al., 2016), **KG-A2C** (Ammanabrolu & Hausknecht, 2020), **MPRC-DQN** (Guo et al., 2020), and **RC-DQN** (Guo et al., 2020). The same experimental setting and handicaps as the baselines is used, as we train for $100\,000$ steps and we assume access to valid actions. Table 3 summarizes the results on the Jericho games. We observe that our CBR agent achieves comparable or better performance than any baseline on 24 (73%) of the games, strictly outperforming all the other agents in 18 the games.

6.4 QUALITATIVE ANALYSIS AND ABLATION STUDIES

Insights on the model. Figure 3 provides two examples showing the **BiKE + CBR** agent interacting with the zork1 game. In the example on top, the agent retrieves an experience that can be successfully reused and turned into a valid action at the current time step. The heat maps visualize the value of the context similarity function defined in Section 4 for the top entries in the memory. In the negative example at the bottom instead, the agent retrieves an action that is not useful and it needs to fallback to the neural policy π. Figure 4 shows the fraction of times that actions retrieved from the memory are reused successfully in the *TWC* games. We observe that, both for *in-distribution* and *out-of-distribution* games, the trained agent relies on CBR from 60% to approximately 70% of the times. This supports the hypothesis that the agent has learnt to map new problems to previous cases and that the CBR is actually useful in decision-making in TBGs.

Game	Human (max)	Human (Walkthrough-100)	TDQN	DRRN	KG-A2C	MPRC-DQN	RC-DQN	BiKE + CBR
905	1	1	**0**	**0**	**0**	**0**	**0**	**0**
acorncourt	30	30	1.6	10	0.3	10	10	**12.2**
adventureland	100	42	0	20.6	0	24.2	21.7	**27.3**
afflicted	75	75	1.3	2.6	–	**8**	**8**	3.2
awaken	50	50	**0**	**0**	**0**	**0**	**0**	**0**
detective	360	350	169	197.8	207.9	317.7	291.3	**326.1**
dragon	25	25	-5.3	-3.5	0	0.04	4.84	**8.3**
inhumane	90	70	0.7	0	3	0	0	**24.2**
library	30	30	6.3	17	14.3	17.7	18.1	**22.3**
moonlit	1	1	**0**	**0**	**0**	**0**	**0**	**0**
omniquest	50	50	16.8	10	3	10	10	**17.2**
pentari	70	60	17.4	27.2	50.7	44.4	43.8	**52.1**
reverb	50	50	0.3	**8.2**	–	2	2	6.5
snacktime	50	50	9.7	0	0	0	0	**22.1**
temple	35	20	**7.9**	7.4	7.6	8	8	7.8
ztuu	100	100	4.9	21.6	9.2	85.4	79.1	**87.2**
advent	350	113	36	36	36	**63.9**	36	62.1
balances	51	30	4.8	10	10	10	10	**11.9**
deephome	300	83	**1**	**1**	**1**	**1**	**1**	**1**
gold	100	30	**4.1**	0	–	0	0	2.1
jewel	90	24	0	1.6	1.8	4.46	2	**6.4**
karn	170	40	0.7	2.1	0	**10**	**10**	0
ludicorp	150	37	6	13.8	17.8	19.7	17	**23.8**
yomomma	35	34	0	0.4	–	**1**	**1**	**1**
zenon	20	20	0	0	3.9	0	0	**4.1**
zork1	350	102	9.9	32.6	34	38.3	38.8	**44.3**
zork3	7	3	0	0.5	0.1	**3.63**	2.83	3.2
anchor	100	11	**0**	**0**	**0**	**0**	**0**	**0**
enchanter	400	125	8.6	20	12.1	20	20	**36.3**
sorcerer	400	150	5	20.8	5.8	**38.6**	38.3	24.5
spellbrkr	600	160	18.7	37.8	21.3	25	25	**41.2**
spirit	250	8	0.6	0.8	1.3	3.8	**5.2**	4.2
tryst205	350	50	0	9.6	–	10	10	**13.4**
(Win rate/Win count)			21% / 7	18% / 6	15% / 5	30% / 10	24% / 8	**73% / 24**

Table 3: Average raw score on the Jericho games. We denote with colors the difficulty of the games (green for *possible* games, yellow for difficult games and red for extreme games). The last row reports the fraction and the absolute number of games where an agent achieves the best score. We additionally report human performance (**Human – max**) and the 100-step results from a human-written walkthrough (**Human – Walkthrough 100**). Results are taken from the original papers or "−" is used if a result was not reported.

Figure 3: Examples from the zork1 game, showing the content of the memory and the context similarities, in a situation where the agent is able to reuse a previous experience and in a case where the revise step is needed.

Figure 4: Fraction of times that a retrieved action is reused successfully on *TWC* for *in-distribution* (**IN**) and *out-of-distribution* (**OUT**) games.

Ablation studies. In order to understand the role of the main modules of our CBR agent, we design two ablation studies. First, instead of using the seeded GAT mechanism, we define the context of a state-action pair $context(s_t, a_t)$ as just one of the entities that a_t is applied to. This definition suits well the *TWC* games because rewarded actions are always applied to one target object and a location for that object (see Appendix A for details). Note that, since the set of entities is discrete, no context quantization is needed. We report the performance of the resulting **BiKE + CBR (w/o GAT)** agent in Table 4. The results show that CBR on *TWC* is effective even with this simple

		Easy	Medium	Hard
IN	**BiKE + CBR (w/o GAT)**	16.32 ± 1.10	36.13 ± 1.40	45.72 ± 0.63
	BiKE + CBR (w/o VQ)	22.67 ± 1.23	43.18 ± 2.10	49.21 ± 0.55
OUT	**BiKE + CBR (w/o GAT)**	18.15 ± 1.51	37.10 ± 1.41	46.70 ± 0.71
	BiKE + CBR (w/o VQ)	27.75 ± 2.11	44.55 ± 1.67	50.00 ± 0.00

Table 4: Results of the ablation study on TWC, evaluated based on the number of steps (**#Steps**) to solve the games.

Figure 5: Number of entries in the memory over training.

context definition, but the lower performance with respect to our proposed agent demonstrates the advantage of incorporating additional context information. Finally, we investigate the role played by vector quantization, by experimenting with an agent (**BiKE + CBR w/o VQ**) that stores the continuous context representations. In general, this poses scalability challenges, but since *TWC* has only 5 games per difficulty level, each with a small number of objects, we were able to evaluate the performance of this agent on the three levels separately. The results, reported in Table 4, show that this agent performs much worse than the other CBR implementations. This happens because storing continuous representations over training results in duplicated entries in the memory and makes it harder to retrieve meaningful experiences. Figure 5 demonstrates how the size (number of entries) in the memory grows over training. In this experiment, we trained the agent on all difficulty levels at the same time, resulting in the implementation running out of memory (OOM) on the GPU.

7 RELATED WORK

Text-based reinforcement learning. TBGs are a rich domain for studying grounded language and how information from text can be utilized in control. Prior work has explored text-based RL to learn strategies for multi-user dungeon games (Narasimhan et al., 2015) and other environments like Civilization II (Branavan et al., 2012). Zahavy et al. (2018) proposed the Action-Elimination Deep Q-Network (AE-DQN), which learns to predict invalid actions in the text-adventure game *Zork*. Recently, Côté et al. (2018) introduced `TextWorld`, a sandbox learning environment for training and evaluating RL agents on text-based games. On the same line, Murugesan et al. (2021b) introduced *TWC* that requires agents with commonsense knowledge. The *LeDeepChef* system (Adolphs & Hofmann, 2019) achieved good results on the *First TextWord Problems* (Trischler et al., 2019) by supervising the model with entities from `FreeBase`, allowing the agent to generalize to unseen objects. A recent line of work on TBGs learns symbolic (typically graph-structured) representations of the agent's belief. Notably, Ammanabrolu & Riedl (2019) proposed *KG-DQN* and Adhikari et al. (2020) proposed *GATA*; both represent the game state as a belief graph. We also use these belief graphs to model game context in our work.

Case-based reasoning in RL. In the context of RL, CBR has been used to speed up and improve transfer learning in heuristic-based RL. Celiberto Jr et al. (2011) and Bianchi et al. (2018) have shown that cases collected from one domain can be used as heuristics to speed up learning of an RL algorithm on a different domain. In contrast to these works, we present a scalable way of using CBR alongside deep RL methods in settings with very large state spaces. More recently, CBR has been successfully applied in the field of knowledge base (KB) reasoning. Das et al. (2020) and Das et al. (2021) show that CBR can effectively learn to generate new logical reasoning chains from prior cases, to answer questions on KBs.

8 CONCLUSION AND FUTURE WORK

In this work, we proposed new agents for TBGs using case-based reasoning. In contrast to expensive deep RL approaches, CBR simply builds a collection of its past experiences in the TBG and uses the ones relevant to the current situation to decide upon its next action in the game. Our experiments on two prominent TBG datasets showed that CBR when combined with existing RL agents can make them more efficient and aid generalization in out-of-distribution settings. Even though CBR was quite successful in the TBGs explored in our work, future work is needed to understand the limitations of CBR in such settings.

REPRODUCIBILITY STATEMENT

We will publish our code after the review process. The implementation details and the hyperparameters can be found in Appendix C. Details about how the model is trained are given in Section 5 and Appendix B. We include a link to allow reviewers to download the source code in Appendix C.

ETHICS STATEMENT

While our models are not tuned for any specific real-world application, our methods could be used in sensitive contexts such as legal or health-care settings; and it is essential that any work that builds on our approaches undertake extensive quality-assurance and robustness testing before using it in their setting. The datasets used in our work do not contain sensitive information to the best of our knowledge.

REFERENCES

Agnar Aamodt and Enric Plaza. Case-based reasoning: Foundational issues, methodological variations, and system approaches. *AI communications*, 7(1):39–59, 1994.

Ashutosh Adhikari, Xingdi Yuan, Marc-Alexandre Côté, Mikuláš Zelinka, Marc-Antoine Rondeau, Romain Laroche, Pascal Poupart, Jian Tang, Adam Trischler, and William L Hamilton. Learning dynamic knowledge graphs to generalize on text-based games. *arXiv preprint arXiv:2002.09127*, 2020.

Leonard Adolphs and Thomas Hofmann. Ledeepchef: Deep reinforcement learning agent for families of text-based games. *ArXiv*, abs/1909.01646, 2019.

Prithviraj Ammanabrolu and Matthew Hausknecht. Graph constrained reinforcement learning for natural language action spaces. *arXiv preprint arXiv:2001.08837*, 2020.

Prithviraj Ammanabrolu and Mark Riedl. Playing text-adventure games with graph-based deep reinforcement learning. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 3557–3565, 2019.

Dzmitry Bahdanau, Shikhar Murty, Michael Noukhovitch, Thien Huu Nguyen, Harm de Vries, and Aaron C. Courville. Systematic generalization: What is required and can it be learned? In *ICLR 2019*, 2019.

Dana H. Ballard. *An introduction to natural computation*. Complex adaptive systems. MIT Press, 2000. ISBN 978-0-262-52258-8.

Yoshua Bengio, Nicholas Léonard, and Aaron C. Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *CoRR*, abs/1308.3432, 2013. URL http://arxiv.org/abs/1308.3432.

Reinaldo AC Bianchi, Paulo E Santos, Isaac J Da Silva, Luiz A Celiberto, and Ramon Lopez de Mantaras. Heuristically accelerated reinforcement learning by means of case-based reasoning and transfer learning. *Journal of Intelligent & Robotic Systems*, 91(2):301–312, 2018.

SRK Branavan, David Silver, and Regina Barzilay. Learning to win by reading manuals in a monte-carlo framework. *Journal of Artificial Intelligence Research*, 43:661–704, 2012.

Luiz A Celiberto Jr, Jackson P Matsuura, Ramon Lopez De Mantaras, and Reinaldo AC Bianchi. Using cases as heuristics in reinforcement learning: a transfer learning application. In *Twenty-Second International Joint Conference on Artificial Intelligence*, 2011.

Ting Chen, Martin Renqiang Min, and Yizhou Sun. Learning k-way d-dimensional discrete codes for compact embedding representations. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan,*

Stockholm, Sweden, July 10-15, 2018, volume 80 of *Proceedings of Machine Learning Research*, pp. 853–862. PMLR, 2018. URL `http://proceedings.mlr.press/v80/chen18g.html`.

Marc-Alexandre Côté, Ákos Kádár, Xingdi Yuan, Ben Kybartas, Tavian Barnes, Emery Fine, James Moore, Matthew Hausknecht, Layla El Asri, Mahmoud Adada, Wendy Tay, and Adam Trischler. Textworld: A learning environment for text-based games. *CoRR*, abs/1806.11532, 2018.

Rajarshi Das, Ameya Godbole, Shehzaad Dhuliawala, Manzil Zaheer, and Andrew McCallum. A simple approach to case-based reasoning in knowledge bases. *arXiv preprint arXiv:2006.14198*, 2020.

Rajarshi Das, Manzil Zaheer, Dung Thai, Ameya Godbole, Ethan Perez, Jay-Yoon Lee, Lizhen Tan, Lazaros Polymenakos, and Andrew McCallum. Case-based reasoning for natural language queries over knowledge bases. *arXiv preprint arXiv:2104.08762*, 2021.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In Jill Burstein, Christy Doran, and Thamar Solorio (eds.), *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, pp. 4171–4186. Association for Computational Linguistics, 2019. URL `https://www.aclweb.org/anthology/N19-1423/`.

Xiaoxiao Guo, Mo Yu, Yupeng Gao, Chuang Gan, Murray Campbell, and Shiyu Chang. Interactive fiction game playing as multi-paragraph reading comprehension with reinforcement learning. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 7755–7765, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.624. URL `https://aclanthology.org/2020.emnlp-main.624`.

Raia Hadsell, Sumit Chopra, and Yann LeCun. Dimensionality reduction by learning an invariant mapping. In *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR 2006), 17-22 June 2006, New York, NY, USA*, pp. 1735–1742. IEEE Computer Society, 2006. doi: 10.1109/CVPR.2006.100. URL `https://doi.org/10.1109/CVPR.2006.100`.

Matthew Hausknecht, Prithviraj Ammanabrolu, Marc-Alexandre Côté, and Xingdi Yuan. Interactive fiction games: A colossal adventure. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 7903–7910, 2020.

Ji He, Jianshu Chen, Xiaodong He, Jianfeng Gao, Lihong Li, Li Deng, and Mari Ostendorf. Deep reinforcement learning with a natural language action space. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics, ACL 2016, August 7-12, 2016, Berlin, Germany, Volume 1: Long Papers*. The Association for Computer Linguistics, 2016. doi: 10.18653/v1/p16-1153. URL `https://doi.org/10.18653/v1/p16-1153`.

Janet L Kolodner. Reconstructive memory: A computer model. *Cognitive science*, 7(4):281–328, 1983.

Brenden M. Lake, Tomer D. Ullman, Joshua B. Tenenbaum, and Samuel J. Gershman. Building machines that learn and think like people. *Behavioral and Brain Sciences*, 40:e253, 2017. doi: 10.1017/S0140525X16001837.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pp. 1928–1937, 2016.

K. Murugesan, Subhajit Chaudhury, and Kartik Talamadupula. Eye of the beholder: Improved relation generalization for text-based reinforcement learning agents. *ArXiv*, abs/2106.05387, 2021a.

Keerthiram Murugesan, Mattia Atzeni, Pavan Kapanipathi, Pushkar Shukla, Sadhana Kumaravel, Gerald Tesauro, Kartik Talamadupula, Mrinmaya Sachan, and Murray Campbell. Text-based rl agents with commonsense knowledge: New challenges, environments and baselines. In *Thirty Fifth AAAI Conference on Artificial Intelligence*, 2021b.

Keerthiram Murugesan, Mattia Atzeni, Pavan Kapanipathi, Kartik Talamadupula, Mrinmaya Sachan, and Murray Campbell. Efficient text-based reinforcement learning by jointly leveraging state and commonsense graph representations. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pp. 719–725, 2021c.

Karthik Narasimhan, Tejas Kulkarni, and Regina Barzilay. Language understanding for text-based games using deep reinforcement learning. *arXiv preprint arXiv:1506.08941*, 2015.

Mrinmaya Sachan. Knowledge graph embedding compression. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel R. Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pp. 2681–2691. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.acl-main.238. URL `https://doi.org/10.18653/v1/2020.acl-main.238`.

Roger C Schank. *Dynamic memory: A theory of reminding and learning in computers and people*. cambridge university press, 1983.

Haitian Sun, Bhuwan Dhingra, Manzil Zaheer, Kathryn Mazaitis, Ruslan Salakhutdinov, and William Cohen. Open domain question answering using early fusion of knowledge bases and text. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 4231–4242, 2018.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. A Bradford Book, Cambridge, MA, USA, 2018. ISBN 0262039249.

Adam Trischler, Marc-Alexandre Côté, and Pedro Lima. First TextWorld Problems, the competition: Using text-based games to advance capabilities of AI agents, 2019.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-SNE. *Journal of Machine Learning Research*, 9:2579–2605, 2008. URL `http://www.jmlr.org/papers/v9/vandermaaten08a.html`.

Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL `https://openreview.net/forum?id=rJXMpikCZ`.

Tom Zahavy, Matan Haroush, Nadav Merlis, Daniel J Mankowitz, and Shie Mannor. Learn what not to learn: Action elimination with deep reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 3562–3573, 2018.

A   ADDITIONAL RESULTS USING ENTITIES AS CONTEXT SELECTORS

As mentioned in Section 6.4, we performed an ablation study where the seeded graph attention and the state graph where not used in the retriever. Instead, we represent the context as just a single focus entity. This choice suits very well the *TWC* games, as the goal of each game is to tidy up a house by putting objects in their commonsensical locations. Hence, each rewarded action in *TWC* is of the form "*put o on s*" or "*insert o in c*", where o is an entity of type *object*, s is a *supporter*, and c is a *container* (Murugesan et al., 2021c; Côté et al., 2018). As an example, a rewarded action could be "*insert dirty singlet in washing machine*", where *dirty singlet* is the *object* and *washing machine* is the container.

Representing the context as just single entities of type *object*, means that the memory of the CBR agent is storing what action to apply to each object in the game, and therefore the agent is in practice constructing a registry where each object is paired with its commonsensical location. Let c_v, c_u be two context entities. The *retriever* then computes the similarity between the contexts as:

$$sim(c_v, c_u) = cosine(FFN(\mathbf{h}_v), FFN(\mathbf{h}_u)),$$

where *cosine* denotes the cosine similarity, *FFN* is a 2-layer feed-forward network and $\mathbf{h}_v, \mathbf{h}_u$ are the BERT encodings of the [CLS] token for objects v and u respectively. The retriever is therefore encouraged to map objects that should be placed in the same location (either a *supporter* or a *container*) to similar representations.

Figure 6 depicts a t-SNE (van der Maaten & Hinton, 2008) visualization of the representations $FFN(\mathbf{h}_v)$ learned by the retriever of the **BiKE + CBR (w/o GAT)** agent. The plot shows that entities that belong to the same location are mapped to similar representations. This holds both for objects in the *in-distribution* games and for objects in the *out-of-distribution* games.

Figure 6: Visualization of the entity representations learned by the retriever. Colors denote the target location of each object.

We evaluated all the CBR agents with the simple retriever defined above. Table 5 and 6 report the results for the *in-distribution* and *out-of-distribution* games. The results confirm that the entity-based context selection performs well and achieves good out-of-distribution generalization. However, we remark that the complete retriever described in Section 4 consistently achieves better results, showing the importance of incorporating additional structured information.

	Easy		Medium		Hard	
	#Steps	**Norm. Score**	**#Steps**	**Norm. Score**	**#Steps**	**Norm. Score**
CBR (w/o GAT)	22.70 ± 2.05	0.81 ± 0.07	44.13 ± 1.15	0.62 ± 0.04	48.05 ± 1.30	0.33 ± 0.05
Text + CBR (w/o GAT)	19.01 ± 3.99	0.89 ± 0.05	40.10 ± 1.52	0.67 ± 0.05	47.80 ± 1.32	0.33 ± 0.02
TWC + CBR (w/o GAT)	17.15 ± 2.91	0.94 ± 0.04	38.32 ± 1.76	0.66 ± 0.03	47.22 ± 1.35	0.36 ± 0.03
KG-A2C + CBR (w/o GAT)	16.67 ± 2.30	0.96 ± 0.03	38.05 ± 1.84	0.66 ± 0.03	46.45 ± 1.02	0.38 ± 0.02
BiKE + CBR (w/o GAT)	16.32 ± 1.10	0.95 ± 0.03	36.13 ± 1.40	0.67 ± 0.04	45.72 ± 0.63	0.41 ± 0.03

Table 5: Test-set performance for *TWC in-distribution* games.

	Easy		Medium		Hard	
	#Steps	Norm. Score	#Steps	Norm. Score	#Steps	Norm. Score
CBR (w/o GAT)	23.90 ± 2.17	0.79 ± 0.05	44.71 ± 1.50	0.61 ± 0.04	48.87 ± 1.89	0.31 ± 0.03
Text + CBR (w/o GAT)	21.64 ± 2.52	0.88 ± 0.02	41.12 ± 1.21	0.66 ± 0.05	48.00 ± 1.10	0.32 ± 0.06
TWC + CBR (w/o GAT)	19.82 ± 2.13	0.92 ± 0.03	39.34 ± 1.01	0.67 ± 0.02	47.33 ± 1.30	0.36 ± 0.04
KG-A2C + CBR (w/o GAT)	19.07 ± 2.50	0.92 ± 0.02	38.41 ± 1.94	0.65 ± 0.04	46.89 ± 2.21	0.37 ± 0.03
BiKE + CBR (w/o GAT)	18.15 ± 1.51	0.92 ± 0.03	37.10 ± 1.41	0.67 ± 0.03	46.70 ± 0.71	0.39 ± 0.03

Table 6: Test-set performance for *TWC out-of-distribution* games.

B TRAINING DETAILS

All agents used in our experiments are trained with an Advantage Actor Critic (A2C) method (Mnih et al., 2016) according to the general scheme defined below. We use the n-step temporal difference method (Sutton & Barto, 2018) to compute the return $R(s_t, a_t)$ of a single time step t in a session of length T as:

$$R(s_t, a_t) = \gamma^{T-t} V(s_T) + \sum_{i=0}^{T-t} \gamma^i r(s_{t+i}, a_{t+i}),$$

where $V(s_T)$ denotes the value of s_T computed by the critic network, γ is the discount factor, and r is the reward function. We then compute the advantage $A(s_t, a_t) = R(s_t, a_t) - V(s_t)$. The final objective term consists of four separate objectives. First, we have $\mathcal{L}_\pi^{(t)}$ that denotes the objective of the policy, which tries to maximize the the advantage A:

$$\mathcal{L}_\pi^{(t)} = -A(s_t, a_t^\star) \log \pi(a_t^\star | s_t).$$

We then add the objective of the critic as:

$$\mathcal{L}_v^{(t)} = \frac{1}{2} \left(R(s_t, a_t^\star) - V(s_t) \right)^2.$$

$\mathcal{L}_v^{(t)}$ encourages the value of the critic V to better estimate the reward R by reducing the mean squared error between them. To prevent the policy from assigning a large weight on a single action, we perform entropy regularization by introducing an additonal term:

$$\mathcal{L}_e^{(t)} = \eta \times \sum_{a_t \in \mathcal{A}_t} \pi(a_t | s_t) \cdot \log \pi(a_t | s_t).$$

The η parameter helps balance the exploration-exploitation trade-off for the policy. The sum of the above objectives defines the loss when the neural agent π is used to select the action $a_t^\star$. In case actions are reused from the memory, then we use the contrastive loss as discussed in Section 5, namely we compute the loss as:

$$\mathcal{L}_r^{(t)} = \frac{1}{2}(1 - y_t)(1 - sim(c_t, c_t^\mathcal{M}))^2 + \frac{1}{2} y_t \max\{0, \mu - 1 + sim(c_t, c_t^\mathcal{M})\}^2.$$

C HYPERPARAMETERS AND REPRODUCIBILITY

All CBR agents are trained using the same hyperparameter settings and the same hardware/software configuration. As mentioned in Section 4, we use a pre-trained BERT model (Devlin et al., 2019) to represent initial node features in the state graph. BERT is only used to compute the initial representations of the entities and is not fine-tuned. We use the following hyperparameters for our experiments.

- We set the hidden dimensionality of the model to $d = 768$ and we use 12 attention heads for the graph attention network, each applied to 64-dimensional inputs.
- We use $n_l = 2$ seeded GAT layers for *TWC* and $n_l = 3$ for Jericho.
- On both datasets, we apply a dropout regularization on the seeded GAT with probability of 0.1 at each layer.

- Similarly, for the experiments on *TWC*, we set the size of the buffer B to $m = 1$, whereas we set $m = 3$ for Jericho. We used a buffer size of $m = 2$ for the scalability analysis depicted in Figure 5.

- The retriever threshold is kept constant to $\tau = 0.7$ across all experiments.

- On *TWC*, we train the agents for 100 episodes and a maximum of 50 steps for each episode. On Jericho, as mentioned, we follow previous work and we train for $100\,000$ valid steps, starting a new episode every 100 steps or whenever the games ends.

- We set the discount factor γ to 0.9 on all experiments.

Experiments were parallelized on a cluster where each node was dedicated to a separate run. The configuration of the execution nodes is as reported in Table 7. The source code is available for download at: `https://bit.ly/3myaebo`.

Resource	Setting
CPU	Intel(R) Xeon(R) CPU E5-2690 v4 @ 2.60GHz
Memory	128GB
GPUs	1 x NVIDIA Tesla k80 12 GB
Disk1	100GB
Disk2	600GB
OS	Ubuntu 18.04-64 Minimal for VSI

Table 7: Hardware and software configuration used to train the agents