Learning Multi-Objective Curricula for Robotic Policy Learning

Abstract: Various automatic curriculum learning (ACL) methods have been proposed to improve the sample efficiency and final performance of robots' policies learning. They are designed to control how a robotic agent collects data, which is inspired by how humans gradually adapt their learning processes to their capabilities. In this paper, we propose a unified automatic curriculum learning framework to create multi-objective but coherent curricula that are generated by a set of parametric curriculum modules. Each curriculum module is instantiated as a neural network and is responsible for generating a particular curriculum. In order to coordinate those potentially conflicting modules in unified parameter space, we propose a multi-task hyper-net learning framework that uses a single hyper-net to parameterize all those curriculum modules. We evaluate our method on a series of robotic manipulation tasks and demonstrate its superiority over other state-of-the-art ACL methods in terms of sample efficiency and final performance.

Keywords: ACL, Hyper-net, Multi-objective Curricula

1 Introduction

The concept that humans frequently organize their learning into a curriculum of interdependent processes according to their capabilities was first introduced to machine learning in [1]. Over time, curriculum learning has become more widely used in machine learning to control the stream of examples provided to training algorithms [2], to adapt model capacity [3], and to organize exploration [4]. Automatic curriculum learning (ACL) for deep reinforcement learning (DRL) [5] has recently emerged as a promising tool to learn how to adapt a robot's learning tasks to its capabilities during training. ACL can be applied to robotics' policies learning in various ways, including adapting initial states [6], shaping reward functions [7], and generating goals [8].

Oftentimes, only a single ACL paradigm (*e.g.*, generating subgoals) is considered. It remains an open question whether different paradigms are complementary to each other and if yes, how to combine them in a more effective manner similar to how the "rainbow" approach of [9] has greatly improve DRL performance in Atari games. Multi-task learning is notoriously difficult Yu et al. [10] hypothesize that the optimization difficulties might be due to the gradients from different tasks conflicting with each other thus hurting the learning process. In this work, we propose a multi-task bilevel learning framework for more effective multi-objective curricula robotics' policy learning. Concretely, inspired by neural modular systems [11] and multi-task RL [12], we utilize a set of neural modules and train each of them to output a curriculum. In order to coordinate potentially conflicting gradients from modules in a unified parameter space, we use a single hyper-net [13] to parameterize neural modules so that these modules generate a diverse and cooperative set of curricula. *Multi-task learning provides a natural curriculum for the hyper-net itself* since learning easier curriculum modules can be beneficial for learning of more difficult curriculum modules with parameters generated by the hyper-net.

Submitted to the 6th Conference on Robot Learning (CoRL 2022). Do not distribute.

Furthermore, existing ACL methods usually rely on manually-designed paradigms of which the target and mechanism have to be clearly defined and it is therefore challenging to create a very diverse set of curriculum paradigms. Consider goal-based ACL for example, where the algorithm is tasked with learning how to rank goals to form the curriculum [14]. Many of these curriculum paradigms are based on simple intuitions inspired by learning in humans, but they usually take too simple forms (*e.g.*, generating subgoals) to apply to neural models. Instead, we propose to augment the hand-designed curricula introduced above with an *abstract* curriculum of which paradigm is learned from scratch. More concretely, we take the idea from memory-augmented meta-DRL [15] and equip the hyper-net with a non-parametric memory module, which is also directly connected to the DRL agent. The hyper-net can write entries to and update items in the memory, through which the DRL agent can interact with the environment under the guidance of the abstract curriculum maintained in the memory. The *write-only*[1] permission given to the hyper-net over the memory is distinct from the common use of memory modules in meta-DRL literature, where the memories are both readable and writable. We point out that the hyper-net is instantiated as a recurrent neural network [16] which has its own internal memory mechanism and thus a write-only extra memory module is enough. Another key perspective is that *such a write-only memory module suffices to capture the essences of many curriculum paradigms*. For instance, the subgoal-based curriculum can take the form of a sequence of coordinates in a game which can be easily generated a hyper-net and stored in the memory module.

In summary, our proposed framework helps in learning coordinated curricula rather than naïvely combining multiple curricula that are otherwise trained independently. The combination of the curriculum modules and the memory module further boosts the performance in terms of sample-efficiency and unifies memory-augmented meta-DRL and ACL. We demonstrate our approach in a rich robotic manipulation environment, and show that it substantially outperforms state-of-the-art baselines and naïve ACL ensemble methods.

2   Preliminaries

Reinforcement learning (RL) is used to train an agent policy with the goal of maximizing the (discounted) cumulative rewards through trial and error. A basic RL setting is modeled as a Markov decision process (MDP) with the following elements: $\mathcal{S}$ is the set of environment states; $\mathcal{A}$ is the set of actions; δ is the state transition probability function, where $\delta(s^{t+1}|s^t, a^t)$ maps a state–action pair at time-step t to a probability distribution over states at time $t+1$; R is the immediate reward after a transition from s to s'; $\pi(\cdot; \phi_\pi)$ is the policy function parameterized by ϕ_π, and $\pi(a|s; \phi_\pi)$ denotes the probability of choosing action a given an observation s.

Automatic curriculum learning (ACL) is a learning paradigm where an agent is trained iteratively following a curriculum to ease learning and exploration in a multi-task problem. Since it is not feasible to manually design a curriculum for each and every task, recent work has proposed to create an implicit curriculum directly from the task objective. Concretely, it aims to maximize a metric P computed over a set of target tasks $T \sim \mathcal{T}_{target}$ after some episodes t'. Following the notation in [5], the objective is set to: $\max_{\mathcal{D}} \int_{T \sim \mathcal{T}_{target}} P_T^{t'} dT$, where $\mathcal{D} : \mathcal{H} \to \mathcal{T}_{target}$ is a task selection function. The input of $\mathcal{D}$ is $\mathcal{H}$ the history, and the output of $\mathcal{D}$ is a curriculum such as an initial state.

Hyper-networks were proposed in [13] where one network (hyper-net) is used to generate the weights of another network. All the parameters of both networks are trained end-to-end using backpropagation. We follow the notation in [17] and suppose that we aim to model a target function $y : \mathcal{X} \times \mathcal{I} \to \mathbb{R}$, where $x \in \mathcal{X}$ is independent of the task and $I \in \mathcal{I}$ depends on the task. A **base** neural network $f_b(x; f_h(I; \theta_h))$ can be seen as a composite function, where $f_b : \mathcal{X} \to \mathbb{R}$ and $f_h : \mathcal{I} \to \Theta_b$. Conditioned on the task information I, the small **hyper**-net $f_h(I; \theta_h)$ generates the parameters θ_b of base-net f_b. Note that θ_b is never updated using loss gradients directly.

---

[1]To the DRL agent, the memory module is *read-only*.

3 Learning Multi-Objective Curricula

We use a single hyper-net to dynamically parameterize all the curriculum modules over time and modify the memory module shared with the DRL agent. We call this framework a Multi-Objective Curricula (MOC). This novel design encourages different curriculum modules to merge and exchange information through the shared hyper-net.

Following the design of hyper-networks with recurrence [13], this hyper-net is instantiated as a recurrent neural network (RNN), which we refer to as the **Hyper-RNN**, denoted as $f_h(I; \theta_h)$, in the rest of this paper to emphasize its dynamic nature. Our motivation for the adoption of an RNN design is its capability for producing a distinct set of curricula for every episode, which strikes a better trade-off between the number of model parameters and its expressiveness. On the other hand, each manually designed curriculum module is also instantiated as an RNN, which is referred as a **Base-RNN** $f_b(x; \theta_b)$ parameterized by $\theta_b = f_h(I; \theta_h)$. Each Base-RNN is responsible for producing a specific curriculum, *e.g.*, a series of sub-goals.

Figure 1: Illustration of MOC-DRL with two loops. Curricula generation corresponds to the outer-level loop. The DRL agent interacts with the environment in the inner-level loop.

Algorithm 1: Multi-Objective Curricula Deep Reinforcement Learning (MOC-DRL).

1 **for** *Episode t' in* 1 *to* T_{outer} **do**
2   · Sample a new environment from the distribution of environments;
3   · Hyper-RNN generates parameters for each curriculum module;
4   **for** *Base-RNN in* 1 *to* 3 **do**
5   · Generate a curriculum;
6   · Hyper-RNN updates the abstract curriculum in the memory;
7   **for** *Training step t in* 1 *to* T_{inner} **do**
8   · DRL agent reads memory;
9   · Train DRL agent following curricula;
10   · Update Hyper-RNN based on outer-level objective;

The architecture of MOC-DRL is depicted in Fig. 1, and its corresponding pseudo-code is given in Alg. 1. We formulate the training procedure as a bilevel optimization problem [18] where we minimize an outer-level objective that depends on the solution of the inner-level tasks.

In our case, the *outer*-level optimization comes from the curriculum generation loop where each step is an episode denoted as t'. On the other hand, the *inner*-level optimization involves a common DRL agent training loop on the interactions between the environment and the DRL agent, where each time-step at this level is denoted as t. We defer the discussion on the details to Sec. 3.3.

Inputs, I, of the Hyper-RNN, f_h, consist of: (1) the final state of the last episode, and (2) role identifier for each curriculum module (*e.g.*, for initial states generation) represented as a one-hot encoding. Ideally, we expect each Base-RNN to have its own particular role, which is specific to each curriculum. When generating the parameters for each Base-RNN, we additionally feed the role identifier representation to the Hyper-RNN.

Outputs of the Hyper-RNN at episode t' include: (1) parameters $\theta_b^{t'}$ for each Base-RNN, and (2) the abstract curriculum, $\mathbf{h}_h^{t'}$, maintained in the memory module. Here $\mathbf{h}_h^{t'}$ corresponds to the hidden states of the Hyper-RNN such that $[\theta_b^{t'}, \mathbf{h}_h^{t'}] = f_h(I^{t'}; \theta_h)$.

3.1 Manually Designed Curricula

In Sec. 3.1, we describe the details of generating manually designed curricula while the process of updating the abstract curriculum is described in Sec. 3.2. We describe how to train them in Sec. 3.3.

In this work, we use three curriculum modules responsible for generating pre-defined curricula [5]: *initial state generator, sub-goal state generator,* and *reward shaping generator.*Our approach can be easily extended to include other forms of curricula (*e.g.,* selecting environments from a discrete set [19]) by adding another curriculum generator to the shared hyper-net. These Base-RNNs simultaneously output the actual curricula for the DRL agent in a synergistic manner. It should be noted that these Base-RNNs are not directly updated by loss gradients, as their *pseudo-parameters* are generated by the Hyper-RNN.

Generating subgoal state γ^t as curriculum $\mathbf{c}_{goal}$ with Base-RNN $\dot{f}_b$. As one popular choice in ACL for DRL, the subgoals can be selected from discrete sets [8] or a continuous goal space [14]. A suitable subgoal state γ^t can ease the learning procedures by guiding the agent how to achieve subgoals step by step and ultimately solving the final task. To incorporate the subgoal state in the overall computation graph, in this paper, we adopt the idea from universal value functions [20] and modify the action-value function, $Q(\cdot; \phi_q)$, to combine the generated subgoal state with other information $Q :=$ $Q(s^t, a^t, \gamma^t; \phi_q) = Q(s^t, a^t, \mathbf{c}_{goal}; \phi_q)$, where s^t is the state, a^t is the action, and γ^t is the generated subgoal state. The loss is defined as $\mathcal{J}_{goal} = \mathbb{E}_{(s^t, a^t, r^t, s^{t+1}, \gamma^t) \sim H_{buf}}[(Q(s^t, a^t, \mathbf{c}_{goal}; \phi_q) - \dot{y})^2]$, where $\dot{y}$ is the one-step look-ahead:

$$\dot{y} = r^t + \lambda \mathbb{E}_{a^{t+1} \sim \pi_\theta(s^{t+1})}[Q(s^t, a^t, \mathbf{c}_{goal}; \phi_q) \quad - \log(\pi(a^{t+1}|s^{t+1}; \phi_\pi))], \tag{1}$$

H_{buf} is the replay buffer and λ is the discount factor.

Generating initial state $\mathbf{s}_0$ as curriculum $\mathbf{c}_{init}$ with Base-RNN $\ddot{f}_b$. Intuitively, if the starting state $\mathbf{s_0}$ for the agent is close to the end-goal state, the training would become easier, which forms a natural curriculum for training tasks whose difficulty depends on a proper distance between initial state and the end-goal state. This method has been shown effective in control tasks with sparse rewards [6, 21]. To simplify implementation, even though we only need a single initial state $\mathbf{s}_0$ which is independent of time, we still use a Base-RNN,$\ddot{f}_b$, to output it.

To evaluate the generated initial states, we incorporate it into the action-value (Q) function and estimate the expect return. The loss for this module is: $\mathcal{J}_{init} = \mathbb{E}_{(s^t, a^t) \sim H_{buf}}[(Q(s^t, a^t, c_{init}; \phi_q) - \dot{y})^2]$, where $\dot{y}$ is defined in Eqn. 1.

Generating potential-based shaping function as curriculum $\mathbf{c}_{rew}$ with Base-RNN $\dddot{f}_b$. Motivated by success of using reward shaping for scaling RL methods to handle complex domains [22], we introduce the reward shaping as the third manually selected curriculum. The reward shaping function can take the form of: $\dddot{f'}_b(s^t, a^t, s^{t+1}) = \mu \cdot \dddot{f}_b(s^{t+1}) - \dddot{f}_b(s^t)$, where μ is a hyper-parameter and $\dddot{f}_b()$ is base-RNN that maps the current state with a reward. In this paper, we add the shaping reward $\dddot{f'}_b(s^t, a^t, s^{t+1})$ to the original environment reward r. We further normalize the shaping reward between 0 and 1 to deal with wide ranges.

Following the optimal policy invariant theorem [22], we modify the look-ahead function: $\dddot{y} = r^t + \dddot{f}_b(s^t, a^t, s^{t+1} + \lambda \mathbb{E}_{a^{t+1} \sim \pi_\theta(s^{t+1})}[Q(s^t, a^t, \mathbf{c}_{rew}; \phi_q) - \log(\pi(a^{t+1}|s^{t+1}; \phi_\pi))]$. Thus the loss is defined as: $\mathcal{J}_{reward} = \mathbb{E}_{s^t, a^t, s^{t+1}, a^{t+1} \sim H_{buf}}[(Q(s^t, a^t, \mathbf{c}_{rew}; \phi_q) - \dddot{y})^2]$.

3.2 Abstract Curriculum with Memory Mechanism

Although the aforementioned hand-designed curricula are generic enough to be applied in any environment/task, it is still limited by the number of such predefined curricula. It is reasonable to conjecture that there exist other curriculum paradigms, which might be difficult to hand-design based on human intuition. As a result, instead of solely asking the hyper-net to generate human-engineered curricula, we equip the hyper-nets with an external memory, in which the hyper-nets could read and update the memory's entries.

By design, the content in the memory can serve as abstract curricula for the DRL agent, which is generated and adapted according to the task distribution and the agent's dynamic capacity during training. Even though there is no constraint on how exactly the hyper-net learns to use the memory, we observe that (see Sec. 4.3): 1) The hyper-net can receive reliable training signals from the manually

163 designed curriculum learning objectives[2]; 2) Using the memory module alone would result in unstable
164 training; 3) Utilizing both the memory and manually curricula achieves the best performance and
165 stable training. Thus, training this memory module with other manually designed curriculum modules
166 contributes to the shaping of the content that can be stored in the memory and is beneficial for the
167 overall performance.

168 Specifically, an external memory is updated by the Hyper-RNN. To capture the latent curriculum
169 information, we design a neural memory mechanism similar to [23]. The form of memory is
170 defined as a matrix M. At each episode t', the Hyper-RNN emits two vectors $\mathbf{m}_e^{t'}$, and $\mathbf{m}_a^{t'}$ as
171 $[\mathbf{m}_e^{t'}, \mathbf{m}_a^{t'}]^T = [\sigma, \mathtt{tanh}]^T(\mathbf{W}_h^{t'}\mathbf{h}_h^{t'})$: where $\mathbf{W}_h^{t'}$ is the weight matrix of Hyper-RNN to transform
172 its internal state $\mathbf{h}_h^{t'}$ and $^t[\cdot]$ denotes matrix transpose. Note that $\mathbf{W}_h$ are part of the Hyper-LSTM
173 parameters θ_h.

174 The Hyper-RNN *writes* the abstract curriculum into the memory, and the DRL agent can *read* the
175 abstract curriculum information freely.

176 **Reading.** The DRL agent can read the abstract curriculum $\mathbf{c}_{abs}$ from the memory $\mathbf{M}$. The read
177 operation is defined as: $\mathbf{c}_{abs}^{t'} = \alpha^{t'}\mathbf{M}^{t'-1}$, where $\alpha^{t'} \in \mathbb{R}^K$ represents an attention distribution over
178 the set of entries of memory $\mathbf{M}^{t'-1}$. Each scalar element $\alpha^{t',k}$ in an attention distribution $\alpha^{t'}$ can
179 be calculated as: $\alpha^{t',k} = \mathtt{softmax}(\mathtt{cosine}(\mathbf{M}^{t'-1,k}, \mathbf{m}_a^{t'-1}))$, where we choose $\mathtt{cosine}(\cdot, \cdot)$ as
180 the align function, $\mathbf{M}^{t'-1,k}$ represents the k-th row memory vector, and $\mathbf{m}_a^{t'} \in \mathbb{R}^M$ is a add vector
181 emitted by Hyper-RNN.

182 **Updating.** The Hyper-RNN can write and update abstract curriculum in the memory module. The
183 write operation is performed as: $\mathbf{M}^{t'} = \mathbf{M}^{t'-1}(1 - \alpha^{t'}\mathbf{m}_e^{t'}) + \alpha^{t'}\mathbf{m}_a^{t'}$, where $\mathbf{m}_e^{t'} \in \mathbb{R}^M$ corresponds
184 to the extent to which the current contents in the memory should be deleted.

185 Equipped with the above memory mechanism, the DRL learning algorithm can read the memory
186 and utilize the retrieved information for the policy learning. We incorporate the abstract curriculum
187 into the value function by $Q(s^t, a^t, \gamma^t, c_{abs}^{t'}; \phi_q)$. Similar to manually designed currricula, we
188 minimize the Bellman error and define the loss function for the abstract curriculum as: $\mathcal{J}_{abstract} =$
189 $\mathbb{E}_{(s^t, a^t, r^t, s^{t+1}, c_{abs}^{t'}) \sim H_{buf}}[(Q(s^t, a^t, c_{abs}^{t'}; \phi_q) - \dot{y})^2]$, where $\dot{y}$ is defined in Eqn. 1.

3.3   Bilevel Training of Hyper-RNN

191 After introducing the manually designed curricula in Sec. 3.1 and the abstract curriculum in Sec. 3.2,
192 here we describe how we update the Hyper-RNN's parameters θ_h, the parameters associated with
193 the DRL agent ϕ_q and ϕ_π. Since the Hyper-RNN's objective is to serve the DRL agent, we naturally
194 formulate this task as a bilevel problem [18] of optimizing the parameters associated with multi-
195 objective curricula generation by nesting one inner-level loop in an outer-level training loop.

196 **Outer-level training of Hyper-RNN.** Specifically, the inner-level loop for the DRL agent learning
197 and the outer-level loop for training Hyper-RNN with hyper-gradients. The outer-level loss is defined
198 as : $\mathcal{J}_{outer} = \mathcal{J}_{initial} + \mathcal{J}_{goal} + \mathcal{J}_{reward} + \mathcal{J}_{abs}$.

199 Since the manually designed curricula and abstract curricula are all defined in terms
200 of Q-function, for the implementation simplicity, we combine them together $\mathcal{J}_{outer} =$
201 $\mathbb{E}_{s^t, a^t, s^{t+1}, a^{t+1} \sim H_{buf}}[(Q(s^t, a^t, \mathbf{c}_{goal}, \mathbf{c}_{rew}, \mathbf{c}_{init}, \mathbf{c}_{abs}; \phi_q) - \dddot{y})^2]$. Following the formulation and
202 implementation in [18], we obtain $\theta_h^* = \mathrm{argmin}\,(\theta_h; \mathcal{J}_{outer}\,(\mathrm{argmin}\,(\phi; \mathcal{J}_{inner}(\theta_h, \phi))))$.

203 **Inner-level training of DRL agent.** The parameters associated with the inner-level training, ϕ_q and
204 ϕ_π, can be updated based on any RL algorithm. In this paper, we use Proximal Policy Optimization
205 (PPO) [24] which is a popular policy gradient algorithm that learns a stochastic policy.

---

[2]To some extent, tasking the hyper-net to train manually designed curriculum modules can be seen as an
curriculum itself for training the abstract curriculum memory module.

4 Experiments

We evaluate and analyze our proposed MOC DRL on the CausalWorld [25], as this environment enables us to easily design and test different types of curricula in a fine-grained manner. This environment also provides wrapper makes the environment to execute actions on the real robot, which can be used in sim2real experiments. It should be noted that we do not utilize any causal elements of the environment. It is straightforward to apply our method to other DRL environments without major modification. Moreover, the training and evaluation task distributions are handled by CausalWorld. Take task "Pushing" as an example: for each outer loop, we use CausalWorld to generate a task with randomly sampled new goal shapes from a goal shape family.

Figure 2: Comparisons with state-of-the-art ACL algorithms. Each learning curve is computed in three runs with different random seeds.

4.1 Settings

We choose five out of the nine tasks introduced in CausalWorld since the other four tasks have limited support for configuring the initial and goal states. Specifically, we enumerate these five tasks here: (1) `Reaching` requires moving a robotic arm to a goal position and reach a goal block; (2) `Pushing` requires pushing one block towards a goal position with a specific orientation (restricted to goals on the floor level); (3) `Picking` requires picking one block at a goal height above the center of the arena (restricted to goals above the floor level); (4) `Pick And Place` is an arena is divided by a fixed long block and the goal is to pick one block from one side of the arena to a goal position with a variable orientation on the other side of the fixed block; (5) `Stacking` requires stacking two blocks above each other in a specific goal position and orientation.

The total number of training steps is 10 million steps. Similar to [26], we unroll the inner loop for one step to compute the approximate hyper-gradients to update the Hyper-RNN.

4.2 Comparing MOC with state-of-the-art ACL methods

We compare our proposed approach with the other state-of-the-art ACL methods: (1) GoalGAN [27], which uses a generative adversarial neural network (GAN) to propose tasks for the agent to finish; (2) ALP-GMM [5], which models the agent absolute learning progress with Gaussian mixture models. None of these baselines utilize multiple curricula.

Fig. 2 shows that MOC outperforms other ACL approaches in terms of mean episode reward, ractional success, and sample efficiency. Especially, MOC increases fractional success by up to 56.2% in all of three tasks, which illustrates the effectiveness of combining multiple curricula in a synergistic manner.

4.3 Ablation Study

Our proposed MOC framework consists of three key parts: the Hyper-RNN trained with hyper-gradients, multi-objective curriculum modules, and the abstract memory module. To get a better insight into MOC, we conduct an in-depth ablation study on probing these components. We first describe the MOC variants used in this section for comparison as follows: (1) $\mathbf{MOC}_{Base^-}$: MOC has the Hyper-RNN and the memory module but does not have the Base-RNNs for manually designed curricula. (2) $\mathbf{MOC}_{Memory^-}$: MOC has the Hyper-RNN to generate three curriculum modules but does not have the memory module. (3) $\mathbf{MOC}_{Memory^-,Hyper^-}$: MOC has Base-RNNs but does not have memory and Hyper-RNN components. It independently generates manually designed curricula. (4) $\mathbf{MOC}_{Memory^-,Goal^+}$: MOC with Hyper-RNN and one Base-RNN, but without the memory module. It only generates the subgoal curriculum as our pilot experiments show that it is consistently better than the other two manually designed curricula and is easier to analyze its behavior by visualizing the state visitation.

Figure 3: Comparison of algorithms with and without memory component on all four tasks. Each learning curve is obtained by three independent runs with different random seeds.

Ablations of Hyper-RNN. By comparing MOC_{Memory^-} with $\mathrm{MOC}_{Memory^-,Hyper^-}$ as shown in Fig. 3, we can observe that letting a Hyper-RNN generate the parameters of different curriculum modules indeed helps in improving the sample efficiency and final performance. The advantage is even more obvious in the harder tasks `pick and place` and `stacking`. The poor performance of $\mathrm{MOC}_{Memory^-,Hyper^-}$ may be caused by the potential conflicts among the designed curricula. For example, without coordination between the initial state curriculum and the goal curriculum, the initial state generator may set an initial state close to the goal state, which is easy to achieve by an agent but too trivial to provide useful training information to achieve the final goal. In sharp contrast, the Hyper-RNN can solve the potential conflicts from different curricula. All the curriculum modules are dynamically generated by the same hyper-net, and there exists an implicit information sharing between the initial state and the goal state curriculum generator. We put extra experimental results in Appendix Sec. A.3, Fig. 4.

Ablations of the memory module. We aim to provide an empirical justification for the use of the memory module and its associated abstract curriculum. By comparing MOC with MOC_{Memory^-} as shown in Fig. 3, we can see that the memory module is crucial for MOC to improve sample efficiency and final performance. Noticeably, in `pick and place` and `stacking`, we see that MOC gains a significant improvement due to the incorporation of the abstract curriculum. We expect that the abstract curriculum could provide the agent with an extra implicit curriculum that is complementary to the manually designed curricula. We also find that it is better for the Hyper-RNN to learn the abstract curriculum while generating other manually designed curricula. Learning multiple manually designed curricula provides a natural curriculum for the Hyper-RNN itself since learning

easier curriculum modules can be beneficial for learning of more difficult curriculum modules with parameters generated by the Hyper-RNN.

Ablations of individual curricula. We now investigate how gradually adding more curricula affects the training of DRL agent. By comparing $MOC_{Memory^-, Goal^+}$ and MOC_{Memory^-} as shown in Fig. 3, we observe that training an agent with a single curriculum receives less environmental rewards as compared to the ones based on multiple curricula. This suggests that the set of generated curricula indeed helps the agent to reach intermediate states that are aligned with each other and also guides the agent to the final goal state.

	Mean Episode Reward	Success Ratio		Mean Episode Reward	Success Ratio
$MOC_{RandInitState}$	936.9 ($\pm$35)	91% ($\pm$0.5%)	GoalGAN	609 ($\pm$23)	56% ($\pm$18%)
$MOC_{FixInitState}$	879.3 ($\pm$9)	89% ($\pm$1.1%)	ALP-GMM	568 ($\pm$26)	39% ($\pm$28%)
$MOC_{RandGoalState}$	921.0 ($\pm$46)	91% ($\pm$0.5%)	MOC (Goal State)	714 ($\pm$14)	68% ($\pm$15%)
MOC (Initial State)	1273 ($\pm$11)	100% ($\pm$0%)			

(a) Analysis of initial state curriculum   (b) Analysis of subgoal curriculum

Table 1: Analysis of initial state curriculum and subgoal state curriculum.

4.4 Curricula Analysis and Visualization

In this section, we analyze the initial state curriculum and goal state curriculum. First, we replace the initial state curriculum with two different alternatives: (1) $MOC_{RandInitState}$, in which we replace the initial state curriculum in MOC with a uniformly chosen state. Other MOC components remains the same; (2) $MOC_{FixInitState}$, in which we replace the initial state curriculum in MOC with a fixed initial state. The other MOC components remains the same. (3) $MOC_{RandGoalState}$, in which we replace the goal state curriculum in MOC with a uniformly chosen state. The other MOC components remains the same. The evaluations are conducted on the `reaching` task and the results are shown in Table 1a. From this table, we observe that MOC with initial state curriculum outperforms other two baseline schemes in terms of mean episode rewards and success ratio. This demonstrates the effectiveness of providing initial state curriculum. Besides, since "random sampling" outperforms "fixed initial state", we conjecture that it is better to provide different initial states, which might be beneficial for exploration.

In Sec. 4.2, we show that providing multi-objective curricula can improve the training of DRL agents. To further evaluate the advantages of hyper-RNN base-RNN framework, we conduct an experiment with GoalGAN, ALP-GMM and MOC with goal curriculum only. We evaluate on `reaching` task and the results are shown in Tab. 1b. In this table, we see that MOC Goal State ($MOC_{Memory^-, Goal^+}$), which is MOC has goal curriculum but doesn't have memory component, slightly outperform other two baseline schemes.

5 Limitations

This paper presents a multi-objective curricula learning approach for solving challenging deep robotics tasks. Our method trains a hyper-network for parameterizing multiple curriculum modules, which control the generation of initial states, subgoals, and shaping rewards. However, it may be interesting to improve the sample efficiency of policy learning. Our method utilizes bi-level optimization, which elongates the training efficiency in terms of interactions between robots and environments. We argue that this limitation could be largely alleviated by replacing the model-free policy learning method with the model-based policy learning method. Besides, the MOC method shows more advantages in goal-oriented tasks thanks to the subgoal curriculum module. In the future, we would like to extend this work to non-goal-oriented tasks.

References

[1] O. G. Selfridge, R. S. Sutton, and A. G. Barto. Training and tracking in robotics. In *Ijcai*, pages 670–672, 1985.

[2] Y. Bengio, J. Louradour, R. Collobert, and J. Weston. Curriculum learning. In *ICML*, volume 382 of *ACM International Conference Proceeding Series*, pages 41–48. ACM, 2009.

[3] K. A. Krueger and P. Dayan. Flexible shaping: How learning in small steps helps. *Cognition*, 110(3):380–394, 2009.

[4] J. Schmidhuber. Curious model-building control systems. In *Proc. international joint conference on neural networks*, pages 1458–1463, 1991.

[5] R. Portelas, C. Colas, L. Weng, K. Hofmann, and P.-Y. Oudeyer. Automatic curriculum learning for deep rl: A short survey. *arXiv preprint arXiv:2003.04664*, 2020.

[6] C. Florensa, D. Held, M. Wulfmeier, M. Zhang, and P. Abbeel. Reverse curriculum generation for reinforcement learning. *arXiv preprint arXiv:1707.05300*, 2017.

[7] M. G. Bellemare, S. Srinivasan, G. Ostrovski, T. Schaul, D. Saxton, and R. Munos. Unifying count-based exploration and intrinsic motivation. In *NIPS*, pages 1471–1479, 2016.

[8] N. Lair, C. Colas, R. Portelas, J.-M. Dussoux, P. F. Dominey, and P.-Y. Oudeyer. Language grounding through social interactions and curiosity-driven multi-goal learning. *arXiv preprint arXiv:1911.03219*, 2019.

[9] M. Hessel, J. Modayil, H. van Hasselt, T. Schaul, G. Ostrovski, W. Dabney, D. Horgan, B. Piot, M. G. Azar, and D. Silver. Rainbow: Combining improvements in deep reinforcement learning. In *AAAI*, pages 3215–3222. AAAI Press, 2018.

[10] T. Yu, S. Kumar, A. Gupta, S. Levine, K. Hausman, and C. Finn. Gradient surgery for multi-task learning. *arXiv preprint arXiv:2001.06782*, 2020.

[11] R. Yang, H. Xu, Y. Wu, and X. Wang. Multi-task reinforcement learning with soft modularization. *arXiv preprint arXiv:2003.13661*, 2020.

[12] T. Wang, H. Dong, V. Lesser, and C. Zhang. Multi-agent reinforcement learning with emergent roles. *arXiv preprint arXiv:2003.08039*, 2020.

[13] D. Ha, A. M. Dai, and Q. V. Le. Hypernetworks. In *ICLR (Poster)*. OpenReview.net, 2017.

[14] S. Sukhbaatar, Z. Lin, I. Kostrikov, G. Synnaeve, A. Szlam, and R. Fergus. Intrinsic motivation and automatic curricula via asymmetric self-play. *arXiv preprint arXiv:1703.05407*, 2017.

[15] C. Blundell, B. Uria, A. Pritzel, Y. Li, A. Ruderman, J. Z. Leibo, J. Rae, D. Wierstra, and D. Hassabis. Model-free episodic control. *arXiv preprint arXiv:1606.04460*, 2016.

[16] K. Cho, B. Van Merriënboer, C. Gulcehre, D. Bahdanau, F. Bougares, H. Schwenk, and Y. Bengio. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*, 2014.

[17] T. Galanti and L. Wolf. On the modularity of hypernetworks. *arXiv preprint arXiv:2002.10006*, 2020.

[18] E. Grefenstette, B. Amos, D. Yarats, P. M. Htut, A. Molchanov, F. Meier, D. Kiela, K. Cho, and S. Chintala. Generalized inner loop meta-learning. *arXiv preprint arXiv:1910.01727*, 2019.

[19] T. Matiisen, A. Oliver, T. Cohen, and J. Schulman. Teacher–student curriculum learning. *IEEE transactions on neural networks and learning systems*, 31(9):3732–3740, 2019.

[20] T. Schaul, D. Horgan, K. Gregor, and D. Silver. Universal value function approximators. In *ICML*, volume 37 of *JMLR Workshop and Conference Proceedings*, pages 1312–1320. JMLR.org, 2015.

[21] B. Ivanovic, J. Harrison, A. Sharma, M. Chen, and M. Pavone. Barc: Backward reachability curriculum for robotic reinforcement learning. In *ICRA*, pages 15–21. IEEE, 2019.

[22] A. Y. Ng, D. Harada, and S. J. Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *ICML*, pages 278–287. Morgan Kaufmann, 1999.

[23] S. Sukhbaatar, A. Szlam, J. Weston, and R. Fergus. End-to-end memory networks. *arXiv preprint arXiv:1503.08895*, 2015.

[24] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017.

[25] O. Ahmed, F. Träuble, A. Goyal, A. Neitz, M. Wuthrich, Y. Bengio, B. Schölkopf, and S. Bauer. Causalworld: A robotic manipulation benchmark for causal structure and transfer learning. In *ICLR*. OpenReview.net, 2021.

[26] I. Clavera, J. Rothfuss, J. Schulman, Y. Fujita, T. Asfour, and P. Abbeel. Model-based reinforcement learning via meta-policy optimization. In *Conference on Robot Learning*, pages 617–629. PMLR, 2018.

[27] C. Florensa, D. Held, X. Geng, and P. Abbeel. Automatic goal generation for reinforcement learning agents. In *International conference on machine learning*, pages 1515–1528, 2018.

[28] S. Narvekar, J. Sinapov, and P. Stone. Autonomous task sequencing for customized curriculum design in reinforcement learning. In *IJCAI*, pages 2536–2542, 2017.

[29] M. Svetlik, M. Leonetti, J. Sinapov, R. Shah, N. Walker, and P. Stone. Automatic curriculum graph generation for reinforcement learning agents. In *AAAI*, pages 2590–2596. AAAI Press, 2017.

[30] S. Narvekar and P. Stone. Learning curriculum policies for reinforcement learning. *arXiv preprint arXiv:1812.00285*, 2018.

[31] A. Campero, R. Raileanu, H. Küttler, J. B. Tenenbaum, T. Rocktäschel, and E. Grefenstette. Learning with amigo: Adversarially motivated intrinsic goals. *arXiv preprint arXiv:2006.12122*, 2020.

[32] A. Graves, M. G. Bellemare, J. Menick, R. Munos, and K. Kavukcuoglu. Automated curriculum learning for neural networks. In *international conference on machine learning*, pages 1311–1320. PMLR, 2017.

[33] T. Salimans and R. Chen. Learning montezuma's revenge from a single demonstration. *arXiv preprint arXiv:1812.03381*, 2018.

[34] D. Pathak, P. Agrawal, A. A. Efros, and T. Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning*, pages 2778–2787. PMLR, 2017.

[35] P. Shyam, W. Jaśkowski, and F. Gomez. Model-based active exploration. In *International Conference on Machine Learning*, pages 5779–5788. PMLR, 2019.

[36] Q. Long, Z. Zhou, A. Gupta, F. Fang, Y. Wu, and X. Wang. Evolutionary population curriculum for scaling multi-agent reinforcement learning. *arXiv preprint arXiv:2003.10423*, 2020.

[37] R. Portelas, C. Romac, K. Hofmann, and P.-Y. Oudeyer. Meta automatic curriculum learning. *arXiv preprint arXiv:2011.08463*, 2020.

[38] A. Wilson, A. Fern, S. Ray, and P. Tadepalli. Multi-task reinforcement learning: a hierarchical bayesian approach. In *Proceedings of the 24th international conference on Machine learning*, pages 1015–1022, 2007.

[39] L. Pinto and A. Gupta. Learning to push by grasping: Using multiple tasks for effective learning. In *2017 IEEE international conference on robotics and automation (ICRA)*, pages 2161–2168. IEEE, 2017.

[40] M. Riedmiller, R. Hafner, T. Lampe, M. Neunert, J. Degrave, T. Wiele, V. Mnih, N. Heess, and J. T. Springenberg. Learning by playing solving sparse reward tasks from scratch. In *International Conference on Machine Learning*, pages 4344–4353. PMLR, 2018.

[41] K. Hausman, J. T. Springenberg, Z. Wang, N. Heess, and M. Riedmiller. Learning an embedding space for transferable robot skills. In *International Conference on Learning Representations*, 2018.

[42] E. Parisotto, J. L. Ba, and R. Salakhutdinov. Actor-mimic: Deep multitask and transfer reinforcement learning. *arXiv preprint arXiv:1511.06342*, 2015.

[43] A. A. Rusu, S. G. Colmenarejo, C. Gulcehre, G. Desjardins, J. Kirkpatrick, R. Pascanu, V. Mnih, K. Kavukcuoglu, and R. Hadsell. Policy distillation. *arXiv preprint arXiv:1511.06295*, 2015.

[44] Y. W. Teh, V. Bapst, W. M. Czarnecki, J. Quan, J. Kirkpatrick, R. Hadsell, N. Heess, and R. Pascanu. Distral: Robust multitask reinforcement learning. *arXiv preprint arXiv:1707.04175*, 2017.

[45] Y. Zhang and D.-Y. Yeung. A regularization approach to learning task relationships in multitask learning. *ACM Transactions on Knowledge Discovery from Data (TKDD)*, 8(3):1–31, 2014.

[46] Z. Chen, V. Badrinarayanan, C.-Y. Lee, and A. Rabinovich. Gradnorm: Gradient normalization for adaptive loss balancing in deep multitask networks. In *International Conference on Machine Learning*, pages 794–803. PMLR, 2018.

[47] A. Kendall, Y. Gal, and R. Cipolla. Multi-task learning using uncertainty to weigh losses for scene geometry and semantics. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 7482–7491, 2018.

[48] X. Lin, H. S. Baweja, G. Kantor, and D. Held. Adaptive auxiliary task weighting for reinforcement learning. *Advances in neural information processing systems*, 32, 2019.

[49] O. Sener and V. Koltun. Multi-task learning as multi-objective optimization. *arXiv preprint arXiv:1810.04650*, 2018.

[50] Y. Du, W. M. Czarnecki, S. M. Jayakumar, M. Farajtabar, R. Pascanu, and B. Lakshminarayanan. Adapting auxiliary losses using gradient similarity. *arXiv preprint arXiv:1812.02224*, 2018.

[51] S. P. Singh. Transfer of learning by composing solutions of elemental sequential tasks. *Machine Learning*, 8(3):323–339, 1992.

[52] J. Andreas, D. Klein, and S. Levine. Modular multitask reinforcement learning with policy sketches. In *International Conference on Machine Learning*, pages 166–175. PMLR, 2017.

[53] A. A. Rusu, N. C. Rabinowitz, G. Desjardins, H. Soyer, J. Kirkpatrick, K. Kavukcuoglu, R. Pascanu, and R. Hadsell. Progressive neural networks. *arXiv preprint arXiv:1606.04671*, 2016.

[54] A. H. Qureshi, J. J. Johnson, Y. Qin, T. Henderson, B. Boots, and M. C. Yip. Composing task-agnostic policies with deep reinforcement learning. *arXiv preprint arXiv:1905.10681*, 2019.

[55] X. B. Peng, M. Chang, G. Zhang, P. Abbeel, and S. Levine. Mcp: Learning composable hierarchical control with multiplicative compositional policies. *arXiv preprint arXiv:1905.09808*, 2019.

[56] T. Haarnoja, V. Pong, A. Zhou, M. Dalal, P. Abbeel, and S. Levine. Composable deep reinforcement learning for robotic manipulation. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6244–6251. IEEE, 2018.

[57] H. Sahni, S. Kumar, F. Tejani, and C. Isbell. Learning to compose skills. *arXiv preprint arXiv:1711.11289*, 2017.

[58] M. Lengyel and P. Dayan. Hippocampal contributions to control: the third way. *Advances in neural information processing systems*, 20:889–896, 2007.

[59] O. Vinyals, C. Blundell, T. Lillicrap, K. Kavukcuoglu, and D. Wierstra. Matching networks for one shot learning. *arXiv preprint arXiv:1606.04080*, 2016.

[60] A. Pritzel, B. Uria, S. Srinivasan, A. P. Badia, O. Vinyals, D. Hassabis, D. Wierstra, and C. Blundell. Neural episodic control. In *International Conference on Machine Learning*, pages 2827–2836. PMLR, 2017.

[61] Y. Han, G. Huang, S. Song, L. Yang, H. Wang, and Y. Wang. Dynamic neural networks: A survey. *arXiv preprint arXiv:2102.04906*, 2021.

[62] X. Jia, B. De Brabandere, T. Tuytelaars, and L. Van Gool. Dynamic filter networks. In *NIPS*, 2016.

[63] O. Chang, L. Flokas, and H. Lipson. Principled weight initialization for hypernetworks. In *International Conference on Learning Representations*, 2019.