RS-FAIRFRS: COMMUNICATION EFFICIENT FAIR FEDERATED RECOMMENDER SYSTEM

ABSTRACT

Federated Recommender Systems (FRSs) aim to provide recommendations to clients in a distributed manner with privacy preservation. FRSs suffer from high communication costs due to the communication between the server and many clients. Some past literature on federated supervised learning shows that sampling clients randomly improve communication efficiency without jeopardizing accuracy. However, each user is considered a separate client in FRS and clients communicate only item gradients. Thus, incorporating random sampling and determining the number of clients to be sampled in each communication round to retain the model's accuracy in FRS becomes challenging. This paper provides sample complexity bounds on the number of clients that must be sampled in an FRS to preserve accuracy. Next, we consider the issue of demographic bias in FRS, quantified as the difference in the average error rates across different groups. Supervised learning algorithms mitigate the group bias by adding the fairness constraint in the training loss, which requires sharing protected attributes with the server. This is prohibited in a federated setting to ensure clients' privacy. We design RS-FAIRFRS, a Random Sampling based Fair Federated Recommender System, which trains to achieve a fair global model. In addition, it also trains local clients towards a fair global model to reduce demographic bias at the client level without the need to share their protected attributes. We empirically demonstrate all our results across the two most popular real-world datasets (ML1M, ML100k) and different sensitive features (age and gender) to prove that RS-FAIRFRS helps reduce communication cost and demographic bias with improved model accuracy.

1 INTRODUCTION

Recommender systems (RSs) have a wide variety of applications in online platforms like e-business, e-commerce, e-learning, e-tourism, music and movie recommendation engines (Lu et al. (2015)). Traditional RSs require gathering clients' private information at the central *server*, leading to serious privacy and security risks. ML models can train locally due to edge devices' increased storage and processing power. This has led to *Federated learning* (FL) (McMahan et al. (2017)), which allows clients to share their updates with the server without any data transfer. The server proposes a common model which is communicated with all clients. Using their data and the global model, clients train locally and communicate the updated model to the server. FL has found many applications in the past few years, e.g., Google keyboard query suggestion (Yang et al. (2018)), smartphone voice assistant, mobile edge computing, and visual object detection (Aledhari et al. (2020)). These applications face numerous challenges including communication efficiency (Smith et al. (2018)), statistical heterogeneity (Smith et al. (2017)), systems heterogeneity (Bonawitz et al. (2019)), privacy, personalization, fairness (Kairouz et al. (2021)), and many more. This paper focuses on two primary issues: communication efficiency and demographic bias in FRSs.

Unlike other applications of FL, where one client has data of many users, in FRS, each user acts as one client constituting a user's profile. FedRec (Lin et al. (2021)), an FRS, expects all the clients to parallelly train the model using *matrix factorization* (MF). In each communication round, the server aggregates the model updates from a huge number of local clients to obtain a global model, and this global model is then sent back to all the clients. This whole procedure increases the communication cost. We show that random sampling of clients in each communication round reduces the communication cost even when only item gradients of sampled users are communicated. Theoretically, we

provide bounds on an ideal fraction of clients to be sampled to maintain the model's accuracy. Proving sample complexity bounds is non-trivial as the clients may possess non-IID data. To circumvent this issue, we assume an underlying clustering structure on the clients such that clients within a cluster contain homogeneous data. The main novelty lies in proving that the random sampling will fetch enough representation from each cluster and the predicted ratings obtained after sampling small number of clients will not be far (with high probability) from that of predicted ratings obtained after communicating with all clients in all the rounds.

Fairness in FRSs is a critical yet under-investigated area. Empirically, we prove that FedRec offers more accurate recommendations to a particular group of clients. This unfair treatment can fortify the social stereotypes based on gender, race, or age, resulting in significant repercussions. So far, researchers have studied fairness in the domain of centralized RSs (Li et al. (2022)). Many past works (Islam et al. (2019); Yao & Huang (2017); Li et al. (2021); Yang et al. (2020a)) develop bias mitigation strategies in traditional RSs, which require sharing sensitive attributes with the server, causing privacy leakage in the federated setting. In FL framework, Yue et al. (2021); Kanaparthy et al. (2021); Du et al. (2020); Zhang et al. (2020) ameliorate bias in classification setting where each client possesses data of many users and thus can train for fairness in each communication round. As opposed to this, in FRS, each user acts as one client that sends its item gradients to the server after updating the user vectors and item gradients locally. We propose a dual-fair vector update technique with two phases. In Phase 1, the server aggregates the received item vectors and trains them towards fairness on a small fraction of data. Even if the server is training a fair model, local client updates may result in a heavily biased model. Thus in Phase 2, the clients minimize local error and learn item vectors closer to the globally fair item vectors.

In summary, our work aims at mitigating the issues of reducing the communication bottleneck and group bias in *Federated Recommendation system* (FedRec) (Yang et al. (2020b)) for the first time. We list down our main contributions below:

1. We provide sample complexity bounds on the fraction of clients required for maintaining accuracy within the desirable limit in Theorem1. Our experiments prove that sampling these many clients improve communication costs in FRS without affecting accuracy even when the clients do not disclose their user vectors and share only updated item gradients.

2. We show the existence of group bias in FRS quantified by evaluating discrepancies in the average group losses for each sensitive attribute. To mitigate this issue, we propose a novel *dual-fairness vector update* technique that tackles the issue of group fairness at local as well as global level.

3. Combining the ideas of random-sampling and dual-fairness vector update, we propose RS-FAIRFRS, a novel FRS model which provides communication efficiency and improved fairness as well as accuracy .

4. We show that RS-FAIRFRS mitigates demographic bias and improves accuracy via extensive experimentation on the two most popular datasets of ML1M, and ML100K, with different demographics (age and gender).

2 RELATED WORK

We divide the literature review into four sections: (i) federated recommender systems (FRS), (ii) client sampling in federated learning, (iii) fairness in centralized RSs, and (iv) fair federated learning models. We emphasize that there does not exist any work which targets fairness in FRS.

Federated Recommender Systems (FRS): *Federated Collaborative Filtering* (FCF) (ud din et al. (2019)) is the first FRS to use implicit feedback for providing personalized recommendations. Lin et al. (2021) identifies the need for an FRS that uses explicit ratings and proposes FedRec that deploys two techniques- *Hybrid Filling* (HF) and *User Averaging* (UA) for privacy preservation. Researchers have been actively exploring many areas of research in FRS like denoising (Liang et al. (2021)), personalization (Jalalirad et al. (2019); Anelli et al. (2021)), privacy enhancement (Wang et al. (2021); Hu et al. (2021); Ali et al. (2021)), building robust FRS (Wu et al. (2022); Zhang et al. (2022); Rong et al. (2022)),mitigating cold-start issue (Wahab et al. (2022)), and improving accuracy of FRS (Perifanis & Efraimidis (2022)). FedFast (Muhammad et al. (2020)) speeds up training in FRS by using an active sampling technique based on the clustering of the user vectors. However, Lin

et al. (2021) argues that only item vectors of clients should be shared with the server while retaining client vectors to preserve clients' privacy. Further, Saito et al. (2019) argues that though RSs widely use implicit feedback, it further leads to the positive-unlabeled problem. Thus, we aim to analyze FedRec (Lin et al. (2021)) as our base model. It uses explicit feedback, unlike the other existing models like FCF (ud din et al. (2019)), NCF (Perifanis & Efraimidis (2022)), and Federank (Anelli et al. (2021)), which either user implicit feedback or convert explicit ratings to implicit feedback. Moreover, none of the aforementioned works investigates fairness in federated recommendations. We identify two major challenges of high communication costs and demographic bias, which remain uninvestigated. Since client sampling methods can significantly reduce communication costs, we now discuss some existing papers that use random sampling in FL.

Client Sampling in Federated Learning: Malinovsky et al. (2022) terms the selection of a batch of clients by the server for participation in the training process as *partial participation* and demonstrate that local steps can help to overcome the communication bottleneck. Charles et al. (2021) conducted extensive experiments to elicit significant challenges such as generalization issues, diminishing returns, training failures, and fairness concerns due to using large cohorts in FL models. Authors in (Balakrishnan et al. (2022)) adopt a greedy strategy to select clients to represent the overall population and provide convergence guarantees for the same. Fraboni et al. (2021a) used clustered sampling for better client representation and reduced variance of stochastic aggregation weight, and Chen et al. (2020) restricted the number of clients allowed to communicate their updates to the server. Finally, Fraboni et al. (2021b) studies the impact of client sampling on the convergence of FL models. While all the above methods assume unbiased client selection, another line of work by Cho et al. (2020) offers the first federated optimization convergence study for biased client selection techniques. Compared to classification settings, FRSs are different as out of the user, only item gradients are communicated to the server. None of the above papers provide bounds on the ideal number of samples required during communication even in federated learning setting. This paper, for the first time provides the sample complexity bounds with respect to FRSs.

Group Fairness in RSs: Xiao et al. (2017) study group fairness by maximizing the satisfaction of each group while minimizing the unfairness between them. Fu et al. (2020) propose a fairness constrained approach via heuristic re-ranking to mitigate group bias in explainable RSs. Li et al. (2021) categorizes clients into advantaged and disadvantaged groups according to their activity level and provides a re-ranking approach to debias the recommendations. Beutel et al. (2019) introduce novel metrics using pairwise comparisons to provide reasoning to bias and offer a regularizer to encourage improving the corresponding metric. Yao & Huang (2017) formalizes four novel metrics to quantify demographic bias and introduce a regularizer term in the objective function to mitigate demographic bias; this approach is somewhat similar to Padala & Gujar (2020). All these methods require the availability of sensitive features of clients to get fair recommendations, leading to privacy leakage in federated settings. A few fair approaches like (Edizel et al. (2020); Bobadilla et al. (2020)) do not require sensitive attributes for mitigating bias but learn disparity from data while training to get unbiased recommendations for the clients whose demographics are unknown. However, FedRec only permits sharing item vector updates with the server, thus making these techniques inapplicable to building fair FRS. Unlike all these approaches, our model RS-FAIRFRS uses an in-processing method that neither disturbs the original data nor requires information leakage to the server.

Group Fairness in Federated Learning: Papadaki et al. (2022) provides an optimization algorithm to improve group fairness with similar performance guarantees to centralized ML models. Kanaparthy et al. (2021) proposes four heuristics by considering balanced and heterogeneous data cases separately for fair federated classification models. Yue et al. (2021) propose GI-Fair to tackle group and individual fairness in FLSs by using a regularization term to penalize the spread in the aggregated loss. Recent work by Hu et al. (2022) uses the concept of bounded group loss to provide theoretical guarantees in group fairness. All these works were proposed to solve the issue of demographic fairness in a federated classification setting. They can not be applied to FRS as in FRS each user acts as one client, unlike classification, where one client can have data of many users. Unique from all other methods, RS-FAIRFRS is the first algorithm to provide dual-fairness vector updation in FRS by learning locally towards the global fair model for local fairness and achieving global fairness by training aggregated vectors towards fairness.

3 PRELIMINARIES

FedRec: In a typical FRS with explicit feedback, we have n users (or clients), $u \in \{1, 2, 3, ..., n\}$ and m items, $i \in \{1, 2, 3, ..., m\}$. Each client u has it's rating vector $[r_{ui}]_{i=1}^{m}$ that depicts the rating given by a client u to an item i. The true ratings given by the user and predicted ratings are denoted using r_{ui} and $\hat{r}_{ui}$, respectively. We assume that $r_{ui} = 0$ if the client has not rated an item. $p_{ui} \in \{0, 1\}$ acts as an indicator variable for rated and unrated items. FedRec uses matrix factorization that identifies the latent structure behind the data to generate two matrices $U \in \mathbb{R}^{n \times k}$ and $V \in \mathbb{R}^{m \times k}$ in a way that each client u is associated with a vector $U_u \in \mathbb{R}^{1 \times k}$, called as *user vector* and each item i is associated with a vector $V_i \in \mathbb{R}^{1 \times k}$, termed as *item vector*. The predicted rating of i^{th} item by u^{th} user can be computed as $\hat{r}_{ui} = U_u.V_i^T$. The goal of FedRec is then to learn the user vectors (locally) and item vectors globally to minimize the loss function:

$$\mathcal{L}^{\mathcal{MF}} = \sum_{u \in [n]} \sum_{i \in [m]} p_{ui}(r_{ui} - U_u.V_i^T)^2 + \lambda^r(\| V_i \|^2 + \| U_u \|^2) \tag{1}$$

FedRec aims at predicting the rating of a client u for each item i without sharing their rating behaviors or records. For this, some unrated items are randomly sampled using sampling parameter ρ and assigned virtual rating. Then, item gradients $\nabla V(u, i)$ for both truly as well as virtually rated items are shared with the server. The server than aggregates these gradients and sends back the aggregated item vectors to all the clients. Additionally, each client also computes the user gradient ∇U_u locally and is not shared with the server. Next section proposes RS-FAIRFRS that solves the issue of communication inefficiency in FRS and mitigates demographic bias.

4 PROPOSED METHODOLOGY

To reduce the communication cost, we randomly sample clients in each communication round who communicate $\nabla V(u, i)$ with the server. Randomly sampling the clients has been proposed in literature under supervised federated learning (Charles et al. (2021); Fraboni et al. (2021b); Cho et al. (2020)). However, since each client is a separate user in FRS and user only shares the item gradients with the server, it is not clear if random sampling will aid the recommender system to reduce communication cost without affecting its accuracy in a federated setting. More importantly, the main question is that how many clients should we sample in each communication round. To answer this question, next section provides sample complexity bounds on the number of clients required to be sampled to obtained the desired accuracy.

4.1 RANDOM SAMPLING WITHOUT REPLACEMENT

Unlike FedRec (Lin et al. (2021)), where the server aggregates item vectors after all the clients have sent their updates, in RS-FAIRFRS, the server uniformly samples a τ fraction of n clients without replacement. It is well known that the users in Federated Learning are non-IID. However, users who provide ratings to items tend to possess an underlying clustered structure. Various algorithms (Koren et al. (2009); Gupta et al. (2020)) work by identifying the latent patterns of users to provide recommendations and within the cluster, users are IID and possess homogeneity. We aim to utilize this homogeneity within the same clusters without the knowledge of the K clusters and the users belonging to each cluster. For random sampling to work efficiently, it is important that the sampled set of clients C^τ must represent the entire population in each communication round. In the first result, we show that when certain number of clients are sampled randomly at uniform, they represent each cluster equally to ensure that this sampled set is enough to represent the entire population.

Lemma 1 *Suppose n clients are uniformly distributed amongst K clusters. Then, a subset $S \subseteq [n]$ sampled uniformly at random (without replacement) will contain an approximately equal number of clients from each cluster.*

We use Hoeffding's bound (Serfling (1974)), which holds for sampling without replacement but provides a very loose bound. Let $X_i^j \in \{0, 1\}$ denote the random variable taking the value 1 when i^{th} sample belong to cluster j and 0 othersise. Then using Hoeffding's bound, we get $\mathbb{P}\left(|\sum_i X_i^j - \frac{|S|}{K}| \geq \epsilon\right) \leq 2\exp\left\{\frac{-2\epsilon^2}{|S|}\right\}$. Substituting ϵ to be $\frac{|S|}{5K}$ (i.e. 20% error), we get, the

probability that the sum is within 20% error is as high as $1 - 2\exp\left\{\frac{-2|S|}{25K^2}\right\}$. If we take $|C^\tau| = 2100$, i.e. 35% of the total number of clients (6000), then we get this probability to be roughly around 0.62, which is obtained at $K = 10$. Hoeffding's inequality provides a very loose bound but actually this probability is very high which is evident from some basic experiments provided in the Appendix.

Lemma 2 *Given n clients during the training, τ represents the fraction of clients sampled for each communication round. If $\bar{V}_i^\tau = \frac{1}{n\tau} \sum_{i \in C^\tau} V_i$ denote the average of item vectors over some C^τ clients and $\bar{V}_i^n = \frac{1}{n} \sum_{i=1}^{n} V_i$ represent the average of item vectors over total n clients. Then, $\mathbb{E}[U_u^T \bar{V}_i^\tau] = \mathbb{E}[U_u^T \bar{V}_i^n]$*

Here, $U_u^T \bar{V}_i^\tau$ and $U_u^T \bar{V}_i^n$ denotes the predicted rating of any user u when aggregated item vectors are obtained only via the sampled users and all the clients in the training set respectively. This lemma holds inherently true if the underlying clients are homogeneous which is not true in FL. Thus we use the latent clustering assumption and Lemma 1 to prove that the expected values of predicted ratings of sampled as well as the entire population are equal.

Proof: Let S_j denote the set of clients in cluster j, and C_j denote the set of clients sampled from cluster j. Since in each cluster, the item vectors are coming from identical distribution, we have $\mathbb{E}[U_u^T \bar{V}_i^{S_i}] = \mathbb{E}[U_u^T \bar{V}_i^{C_i}]$. Here, $\bar{V}_i^{S_i}, \bar{V}_i^{C_i}$ represent the average of item vectors V_i's from sets S_i and C_i respectively. From Lemma 2, if τ fraction of clients are selected from n clients uniformly at random without repetition, then we have $C_j \approx \tau S_j$ with high probability. Then,
$\mathbb{E}[U_u^T \bar{V}_i^\tau] = \frac{1}{\sum_{j=1}^{l} |C_i|} \sum_{j=1}^{l} |C_i| \mathbb{E}[U_u^T \bar{V}_i^{C_i}] = \frac{1}{\sum_{j=1}^{l} \tau |S_i|} \sum_{j=1}^{l} \tau |S_i| \mathbb{E}[U_u^T \bar{V}_i^{S_i}] = \mathbb{E}[U_u^T \bar{V}_i^n]$

Now, we state and prove our main theorem below:

Theorem 1 *Random Sampling of Clients: Given a rating matrix R, let $< \{U_u\}_{u=1}^n, \{V_i\}_{i=1}^m >$ denotes a Federated Recommendation Model with predicted ratings lying within a range of $[a, b]$. If $\bar{V}_i^\tau = \frac{1}{n\tau} \sum_{i \in C^\tau} V_i$ denote the average of item vectors over some τ fraction of clients and $\bar{V}_i^n = \frac{1}{n} \sum_{i=1}^{n} V_i$ represent the average of item vectors over total n clients, then*

$$\mathbb{P}(|U_u^T \bar{V}_i^\tau - U_u^T \bar{V}_i^n| \geq \epsilon) \leq 2\exp\left\{\frac{-n\tau\epsilon^2}{2(b-a)^2}\right\}$$

.

Proof of Theorem 1: From Hoeffding's inequality, we have,
$\mathbb{P}(|U_u^T \bar{V}_i^\tau - \mathbb{E}[U_u^T \bar{V}_i^\tau]| \geq \epsilon) \leq 2\exp\{\frac{-2n\tau\epsilon^2}{(b-a)^2}\}$ and $\mathbb{P}(|U_u^T \bar{V}_i^n - \mathbb{E}[U_u^T \bar{V}_i^n]| \geq \epsilon) \leq 2\exp\{\frac{-2n\epsilon^2}{(b-a)^2}\}$

Thus with probability atleast $1 - 2\exp\{\frac{-2n\tau\epsilon^2}{(b-a)^2}\}$, we have,

$$\mathbb{E}[U_u^T \bar{V}_i^\tau] - \epsilon \leq U_u^T \bar{V}_i^\tau \leq \mathbb{E}[U_u^T \bar{V}_i^\tau] + \epsilon \implies \mathbb{E}[U_u^T \bar{V}_i^n] - \epsilon \leq U_u^T \bar{V}_i^\tau \leq \mathbb{E}[U_u^T \bar{V}_i^n] + \epsilon$$
$$\text{(From Lemma 2)}$$

$$\implies U_u^T \bar{V}_i^n - 2\epsilon \leq U_u^T \bar{V}_i^\tau \leq U_u^T \bar{V}_i^n + 2\epsilon$$

Thus, we get $\mathbb{P}(|U_u^T \bar{V}_i^\tau - U_u^T \bar{V}_i^n| \geq \epsilon) \leq 2\exp\{\frac{-n\tau\epsilon^2}{2(b-a)^2}\}$.

According to the above theorem, if the ratings lie between $[1, 5]$, then the probability that the error in predicted rating is more than 10% is less than 1% with just 35% clients from the pool of 6000 clients.

4.2 DUAL-FAIR UPDATE

This technique involves training towards fairness in two phases. We first explain the inability of existing fairness notions in RS to be able to measure group bias and propose fairness metric which when added as a constraint in optimization function at server helps achieve a fair global model. Existing fairness notions in RS, namely value unfairness, absolute unfairness, and non-parity fairness (Yao & Huang (2017)) consider the difference in average loss on a specific item i concerning users belonging to advantaged and disadvantaged groups. It is not feasible in FL as each client is distinct and prohibited from sharing its ratings with the server and other clients. Moreover, Mansoury et al.

(2020) mentions profile size as an important factor in group bias as more active clients receive better recommendations. We define *user activeness* as the number of items rated by a user, i.e. a user is more active if he or she has rated more items I_u out of all the items in the item set I. Thus, with an assumption of a binary attribute, our metric *accuracy parity* ($\mathcal{L}^{ap}$) normalizes the sum of squared loss over all the items rated by a client and is given as:

$$\mathcal{L}^{ap} = \frac{1}{|g|} \sum_{u \in g} \frac{1}{|I_u|} \sum_{I \in I_u} (\hat{r}_{ui} - r_{ui})^2 - \frac{1}{|\neg g|} \sum_{u \in \neg g} \frac{1}{|I_u|} \sum_{I \in I_u} (\hat{r}_{ui} - r_{ui})^2 \qquad (2)$$

Here, g and $\neg g$ denote the disadvantaged and advantaged groups, respectively. I_u is the set of items rated by u and $\hat{r}_{ui}$, r_{ui} depict the predicted and true ratings, respectively. For models θ and $\bar{\theta}$, we say that θ is a demographically fairer model if $\mathcal{L}^{ap}(\theta) < \mathcal{L}^{ap}(\bar{\theta})$. Designing a fair FRS involves tackling three significant challenges that any FRS as discussed below:

1. Designing debiasing techniques for local clients becomes challenging if they are reluctant to share their sensitive attributes (Ezzeldin et al. (2021)).

2. Considering the settings where each user is not one client, local fairness does not ensure global fairness in FL. The non-IID data in FL makes it impossible for the entire distribution to be represented by one standard distribution.

3. To achieve fairness, simple federated models usually do weighted aggregation; however, it becomes infeasible to assign weights to the updates sent to the server without knowing the group to which they belong.

FairMF: We assume the availability of data of very few (20%) clients D_{server} at the server for evaluating the fairness loss. This assumption was also considered by Kanaparthy et al. (2021) for building a fair federated model for face classification. This assumption helps achieve fairness without expecting clients to reveal their private sensitive attributes to the server even during training. Therefore, unlike a simple FRS, the server in RS-FAIRFRS not only aggregates but also helps achieve fairness. We denote each client at the server as $s \in \{1, ..., S\}$ such that $S << n$, i.e. the number of clients at the server will always be much less than the number of local clients. FairMF trains the data at server D_{server} for obtaining global fairness objective. The goal of FairMF is to optimize the loss function defined as the combination of regularized MF (equation 1) and fairness penalty (equation 2). The final loss function is

$$\min_{U,V} \mathcal{L}^{MF} + \lambda^f \mathcal{L}^{ap} \qquad (3)$$

The hyperparameter λ^f acts as a fairness penalizer. The update equations for client vector U_u and item vector V_i are obtained by taking derivatives of the fairness loss function with respect to client and item vectors respectively. Server runs FairMF for some iterations t_s and obtains final U_{fair} and V_{fair}. Finally, V_{fair} and $[V_i]_{i=1}^m$ (aggregated item vectors) are communicated to all the clients.

FO-ClientBatch: *Fairness Oriented Client Batch* ensures local fairness in FRS by learning locally towards fair global model. Each client downloads both V_{fair} and V_i from the server. While V_{fair} contributes towards fairness, communication of aggregated V_i provide each user with the benefit of other users' participation. Since in FL models global fairness does not ensure local fairness, it is important that each local client also trains towards the fair model. Then, each user vector is updated locally, followed by an updation in the V_i towards V_{fair}. Thus the local objective function changes to

$$\min_{U,V} \mathcal{L}^{MF} + \eta(||V_{fair} - V_i||^2) \qquad (4)$$

Clients keep ∇U_u with themselves and communicate only ∇V to the server. The section below describes the detailed algorithm and communication details.

4.3 RS-FAIRFRS

Algorithm1 describes RS-FAIRFRS in whole. With the assumption of the availability of a small dataset (D_{server}) corresponding to s users at the server, the procedure begins by initializing $V = [V_i]_{i=1}^m$ and $U = [U_u]_{u=1}^s$ which represent the item and user vectors respectively. Then, some τ

Algorithm 1 RS-FairFedRec Communication Efficient and Fairness Aware Federated Recommender System

---

1: Initialize $V = [V_i]_{i=1}^m$ and $U = [U_u]_{u=1}^s$
2: **for** $t = 1, 2, ..., T$ **do**
3:      $C^\tau \leftarrow$ {Randomly sub-sample τ fraction of clients from all the users in D_{train}}
4:      $U_{fair}, V_{fair} \leftarrow$ FairMF(D_{server}, V, U_{fair})
5:      **for** each client $u \in U$ in parallel **do**
6:          Sample I'_u from $I \setminus I_u$ with $|I'_u| = \rho |I_u|$
7:          ClientFilling($V_i, i = 1, 2, ..., m; U_u; u, t$)
8:          Calculate the gradients ∇U_u and $\nabla V(u, i)$ by differentiating equation 3
9:          Update U_u via $U_u \leftarrow U_u - \gamma \nabla U_u$
10:      **end for**
11:      **for** i = 1,.....,m **do**
12:          Calculate the aggregated gradient ∇V_i for clients in C^τ
13:          Update $V_i = V_i - \gamma \nabla V_i$
14:      **end for**
15:      Decrease the learning rate $\gamma \leftarrow 0.9\gamma$
16: **end for**

---

percentage of total clients present in the *training dataset* (D_{train}) are randomly sampled by the server and the set of these sampled clients is denoted by C^τ. Server assumes the availability of D_{server} to run FairMF for obtaining fair item vectors V_{fair} which are further communicated to all the clients for local fairness. Alongwith these, V is also sent to each client to retain the federated properties of FedRec and allow benefits of the participation of other clients. For initial round, the initialized item vectors are communicated, however as the training preoceeds, V gets updated by the aggregated item vectors. Further, the server aggregates item vectors sent by C^τ clients only. The fair item vectors V_{fair} and aggregated item vectors communicated by the server are received by each client u and local training happen at all the clients. Similar to FedRec, using UA, every client will receive some (ρ) virtual ratings. This procedure is called Client Filling (Lin et al. (2021)) and we describe the detailed algorithm in Appendix. The user gradients and item gradients are evaluated simply by differentiating the equation 4. The proposed local objective minimizes the squared loss between the global item vectors and local ones. The updated item gradients are uploaded to the server to train FairMF on the dataset available at the server D_{server} and obtains U_{fair} and V_{fair}. This procedure is repeated till convergence.

5 EXPERIMENTS

We empirically show that (i) random sub-sampling of clients reduces communication costs without any slump in accuracy of an FRS , (ii) FedRec suffers heavily from demographic bias, and (iii) RS-FAIRFRS significantly reduces bias without any leakage of client's privacy and improves accuracy.

5.1 EXPERIMENTAL SET-UP

Datasets: We use two benchmark datasets *ML1M* [1] and *ML100K* [2] with explicit ratings ranging from 1 to 5. *ML1M* dataset consists of $1,000,209$ ratings of $3,706$ movies by $6,040$ users and *ML100K* consists of 943 users with $100,000$ ratings for $1,682$ items. ML1M has $4,331$ males and $1,709$ females; also, there are $5,818$ people with age > 18 and 212 users with age < 18. Similarly, in ML100k, users with age above 18 (889) are much more than ones with under 18 (54). Furthermore, ML100k has only 273 females as compared to 670 males.
Metrics: All our experiments use RMSE (Root Mean Square Error) as used by Lin et al. (2021) to provide a fair comparison of the accuracy of our model with the FedRec. We also provide an analysis of Group Losses, calculated using the average sum of the RMSE score of all clients belonging to a certain group. Finally, we use $\mathcal{L}^{ap}$ [equation 2] to evaluate demographic bias in all the experiments. We split each dataset randomly by keeping 20% of the data for the test set and the rest for training.

---

[1] https://grouplens.org/datasets/movielens/1m/
[2] https://grouplens.org/datasets/movielens/100k/

(a) RMSE   (b) Time(in sec)

Figure 1: Comparison plots for accuracy and average time per communication round on different values of τ in RS-FedRec on two datasets of ML1M and ML100k

(a) ML1M   (b) ML100k

Figure 2: Difference in RMSE scores for different sensitive attributes by FedRec over two datasets.

Hyperparameters: Similar to Lin et al. (2021), we use $k = 20$ latent features and set the value of sampling parameter to $\rho = 2$. We run all the models till convergence ($T = 20$) and the FairMF procedure is executed to $t_s = 15$ runs. We report all our results over an average of 10 runs. The final tuned hyperparameter values and other details are provided in the Appendix.

Baselines: While it can be apparent that more data on the server will yield better performance, we run all our experiments on RS-FAIRFRS with 100% and RS-FAIRFRS with 20% data on the server to show that even with all the data on the server, RS-FAIRFRS with only a 20% data can provide much better accuracy as well as fairness. For exact numbers of the training and testing results, refer Appendix. Now we provide interesting results via various graphical representations.

5.2 EMPIRICAL EVALUATION

Random Sampling of Clients without Replacement: Out of all the clients available during training, we randomly sample τ fraction of clients. The model's accuracy is analyzed for a wide range of τ values in Figure 1a. It is evident that for minimal values of τ, the model has a very high error which indicates the failure to converge and with around 35% of clients, the model performs nearly the same as with 100% for both the datasets. From Theorem1, it can be shown that the predicted rating of each client with sampled item vectors will be within 5% error with a probability of at least 0.96. An interesting fact can be observed that by increasing τ, training loss too rises as stated by Charles et al. (2021). Further, Figure 1b presents the average time taken (in sec) for one communication round by FedRec with different values of τ. From these inferences, for all our experiments we select $\tau = 35$ as an ideal value which provides reasonable accuracy in very less time.

Disparate treatment of FedRec for certain sensitive attributes: To demonstrate the biased treatment of FedRec towards certain sensitive groups, we compute average losses on each sensitive attribute. Figure 2 shows that the groups with more number of clients *(advantaged groups)* enjoy more accurate recommendations where as the groups with lesser number of clients *(disadvantaged groups)* receive more erroneous recommendations. In both the datasets of ML1M and ML100k, clients with age > 18 enjoy recommendations with lesser RMSE as compared to the ones with age < 18. Similarly, females of both the datasets obtain recommendations with much higher error scores as compared to the males. This shows that the existing class imbalance affects the recommendations

| (a) ML1M[Age] | (b) ML1M[Gender] | (c) ML100k[Age] | (d) ML100k[Gender] |

Figure 3: $\mathcal{L}^{ap}$ on two datasets and two different demographics for different algorithms.

| (a) ML1M[Age] | (b) ML1M[Gender] | (c) ML100k[Age] | (d) ML100k[Gender] |

Figure 4: Fairness vs Accuracy plots

provided by FedRec which motivates us to develop a fair FedRec that trains towards mitigating this disparate treatment of FedRec.

Fairness of RS-FAIRFRS: To analyze the demographic fairness of our algorithm, we compare our results with those of the FedRec, RS-FedRec (FedRec with sampling) and RS-FAIRFRS with (100%) data at the server as baselines. We also provide bias results on MF to show that although FedRec has similar accuracy as MF (Lin et al. (2021)), it amplifies the bias due to aggregation of vectors. In Figure 3, we show that a minimal amount of data of the clients (20%) on the server helps in achieving better fairness instead of all the data on the server as demonstrated by RS-FAIRFRS(100%). It is evident from all the four figures (Figure3a, 3b, 3c, and 3d) that RS-FAIRFRS with 20% data on the server manages to acquire least bias on both the datasets for all the sensitive attributes respectively. Thus, RS-FAIRFRS(20%) manages to significantly reduce the bias in FedRec without leaking any sensitive information to the server during training.

Fairness vs Accuracy in RS-FAIRFRS: It is interesting to note that RS-FAIRFRS not only improves group bias but also generates more accurate recommendations. We compute RMSE as well as $\mathcal{L}^{ap}$ to depict the excellence of our model in both the aspects. Figures 4a and 4b shows that RS-FAIRFRS(20%) provides more fair and accurate recommendations to the clients in ML1M dataset for both the genders as well as users with age above and under 18. It can be easily inferred that a lower value in both Demographic bias and RMSE accounts for better model. Users belonging to both the age groups in ML100k dataset enjoy fair recommendations with RS-FAIRFRS(20%). Though, MF performs slightly better in terms of accuracy as well as fairness for users in ML100k for gender attribute due to the efficiency of centralized settings for smaller datasets, overall, RS-FAIRFRS(20%) outperforms all the existing federated algorithms.

6 CONCLUSION AND FUTURE WORK

We propose RS-FAIRFRS which incorporates two key ideas (i) random sampling of clients at each communication round to reduce the communication cost, and (ii) dual-fair updation to mitigate group bias. We are first to theoretically bound the sample complexity on the number of clients to be sampled to participate in each round so that the model accuracy is perpetuated. We empirically demonstrate our theoretical results and provide extensive experimentation to show that we can achieve much-reduced bias and improved model accuracy only with a small amount of data at the server. Exploring various other types of biases in FRSs can be an interesting research direction. We would also like to extend our analysis to provide theoretical fairness guarantees of RS-FAIRFRS and explore the usage of dual-fair updation-like techniques in many other FL domains in future.

REFERENCES

Mohammed Aledhari, Rehma Razzak, Reza M. Parizi, and Fahad Saeed. Federated learning: A survey on enabling technologies, protocols, and applications. *IEEE Access*, 8:140699–140725, 2020. doi: 10.1109/ACCESS.2020.3013541.

Waqar Ali, Rajesh Kumar, Zhiyi Deng, Yansong Wang, and Jie Shao. A federated learning approach for privacy protection in context-aware recommender systems. *The Computer Journal*, 64(7): 1016–1027, 2021.

Vito Walter Anelli, Yashar Deldjoo, Tommaso Di Noia, Antonio Ferrara, and Fedelucio Narducci. Federank: User controlled feedback with federated recommender systems. In *European Conference on Information Retrieval*, pp. 32–47. Springer, 2021.

Ravikumar Balakrishnan, Tian Li, Tianyi Zhou, Nageen Himayat, Virginia Smith, and Jeff Bilmes. Diverse client selection for federated learning via submodular maximization. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=nwKXyFvaUm.

Alex Beutel, Jilin Chen, Tulsee Doshi, Hai Qian, Li Wei, Yi Wu, Lukasz Heldt, Zhe Zhao, Lichan Hong, Ed H Chi, et al. Fairness in recommendation ranking through pairwise comparisons. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 2212–2220, 2019.

Jesús Bobadilla, Raúl Lara-Cabrera, Ángel González-Prieto, and Fernando Ortega. Deepfair: deep learning for improving fairness in recommender systems. *arXiv preprint arXiv:2006.05255*, 2020.

Hans-Hermann Bock. Clustering methods: a history of k-means algorithms. *Selected contributions in data analysis and classification*, pp. 161–172, 2007.

Keith Bonawitz, Hubert Eichner, Wolfgang Grieskamp, Dzmitry Huba, Alex Ingerman, Vladimir Ivanov, Chloe Kiddon, Jakub Konečný, Stefano Mazzocchi, Brendan McMahan, et al. Towards federated learning at scale: System design. *Proceedings of Machine Learning and Systems*, 1: 374–388, 2019.

Zachary Charles, Zachary Garrett, Zhouyuan Huo, Sergei Shmulyian, and Virginia Smith. On large-cohort training for federated learning. *CoRR*, abs/2106.07820, 2021. URL https://arxiv.org/abs/2106.07820.

Wenlin Chen, Samuel Horváth, and Peter Richtárik. Optimal client sampling for federated learning. *CoRR*, abs/2010.13723, 2020. URL https://arxiv.org/abs/2010.13723.

Yae Jee Cho, Jianyu Wang, and Gauri Joshi. Client selection in federated learning: Convergence analysis and power-of-choice selection strategies. *CoRR*, abs/2010.01243, 2020. URL https://arxiv.org/abs/2010.01243.

Wei Du, Depeng Xu, Xintao Wu, and Hanghang Tong. Fairness-aware agnostic federated learning, 2020.

Bora Edizel, Francesco Bonchi, Sara Hajian, André Panisson, and Tamir Tassa. Fairecsys: mitigating algorithmic bias in recommender systems. *International Journal of Data Science and Analytics*, 9(2):197–213, 2020.

Yahya H Ezzeldin, Shen Yan, Chaoyang He, Emilio Ferrara, and Salman Avestimehr. Fairfed: Enabling group fairness in federated learning. *arXiv preprint arXiv:2110.00857*, 2021.

Yann Fraboni, Richard Vidal, Laetitia Kameni, and Marco Lorenzi. Clustered sampling: Low-variance and improved representativity for clients selsection in federated learning. *CoRR*, abs/2105.05883, 2021a. URL https://arxiv.org/abs/2105.05883.

Yann Fraboni, Richard Vidal, Laetitia Kameni, and Marco Lorenzi. On the impact of client sampling on federated learning convergence. *CoRR*, abs/2107.12211, 2021b. URL https://arxiv.org/abs/2107.12211.

Zuohui Fu, Yikun Xian, Ruoyuan Gao, Jieyu Zhao, Qiaoying Huang, Yingqiang Ge, Shuyuan Xu, Shijie Geng, Chirag Shah, Yongfeng Zhang, et al. Fairness-aware explainable recommendation over knowledge graphs. In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*, pp. 69–78, 2020.

Meenu Gupta, Aditya Thakkar, Vishal Gupta, Dhruv Pratap Singh Rathore, et al. Movie recommender system using collaborative filtering. In *2020 International Conference on Electronics and Sustainable Communication Systems (ICESC)*, pp. 415–420. IEEE, 2020.

Nils Olof Hedman, Roine Johansson, and Urban Rosenqvist. Clustering and inertia: structural integration of home care in swedish elderly care. *International Journal of Integrated Care*, 7, 2007.

Hongsheng Hu, Gillian Dobbie, Zoran Salcic, Meng Liu, Jianbing Zhang, Lingjuan Lyu, and Xuyun Zhang. Differentially private locality sensitive hashing based federated recommender system. *Concurrency and Computation: Practice and Experience*, pp. e6233, 2021.

Shengyuan Hu, Zhiwei Steven Wu, and Virginia Smith. Fair federated learning via bounded group loss, 2022. URL https://arxiv.org/abs/2203.10190.

Rashidul Islam, Kamrun Naher Keya, Shimei Pan, and James Foulds. Mitigating demographic biases in social media-based recommender systems. *KDD (Social Impact Track)*, 2019.

Amir Jalalirad, Marco Scavuzzo, Catalin Capota, and Michael Sprague. A simple and efficient federated recommender system. In *Proceedings of the 6th IEEE/ACM International Conference on Big Data Computing, Applications and Technologies*, BDCAT '19, pp. 53–58, New York, NY, USA, 2019. Association for Computing Machinery. ISBN 9781450370165. doi: 10.1145/3365109.3368788. URL https://doi.org/10.1145/3365109.3368788.

Peter Kairouz, H Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Kallista Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, et al. Advances and open problems in federated learning. *Foundations and Trends® in Machine Learning*, 14(1–2):1–210, 2021.

Samhita Kanaparthy, Manisha Padala, Sankarshan Damle, and Sujit Gujar. Fair federated learning for heterogeneous face data, 2021.

Yehuda Koren, Robert Bell, and Chris Volinsky. Matrix factorization techniques for recommender systems. *Computer*, 42(8):30–37, 2009.

Yunqi Li, Hanxiong Chen, Zuohui Fu, Yingqiang Ge, and Yongfeng Zhang. User-oriented fairness in recommendation. In *Proceedings of the Web Conference 2021*, pp. 624–632, 2021.

Yunqi Li, Hanxiong Chen, Shuyuan Xu, Yingqiang Ge, Juntao Tan, Shuchang Liu, and Yongfeng Zhang. Fairness in recommendation: A survey, 2022. URL https://arxiv.org/abs/2205.13619.

Feng Liang, Weike Pan, and Zhong Ming. Fedrec++: Lossless federated recommendation with explicit feedback. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(5):4224–4231, May 2021. URL https://ojs.aaai.org/index.php/AAAI/article/view/16546.

Guanyu Lin, Feng Liang, Weike Pan, and Zhong Ming. Fedrec: Federated recommendation with explicit feedback. *IEEE Intelligent Systems*, 36(5):21–30, 2021. doi: 10.1109/MIS.2020.3017205.

Jie Lu, Dianshuang Wu, Mingsong Mao, Wei Wang, and Guangquan Zhang. Recommender system application developments: a survey. *Decision Support Systems*, 74:12–32, 2015.

Grigory Malinovsky, Konstantin Mishchenko, and Peter Richtárik. Server-side stepsizes and sampling without replacement provably help in federated optimization. *CoRR*, abs/2201.11066, 2022. URL https://arxiv.org/abs/2201.11066.

Masoud Mansoury, Himan Abdollahpouri, Jessie Smith, Arman Dehpanah, Mykola Pechenizkiy, and Bamshad Mobasher. Investigating potential factors associated with gender discrimination in collaborative recommender systems. In *The Thirty-Third International Flairs Conference*, 2020.

H. Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Agüera y Arcas. Communication-efficient learning of deep networks from decentralized data, 2017.

Khalil Muhammad, Qinqin Wang, Diarmuid O'Reilly-Morgan, Elias Tragos, Barry Smyth, Neil Hurley, James Geraci, and Aonghus Lawlor. Fedfast: Going beyond average for faster training of federated recommender systems. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 1234–1242, 2020.

Manisha Padala and Sujit Gujar. Fnnc: Achieving fairness through neural networks. In *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence,{IJCAI-20}, International Joint Conferences on Artificial Intelligence Organization*, 2020.

Afroditi Papadaki, Natalia Martinez, Martin Bertran, Guillermo Sapiro, and Miguel Rodrigues. Minimax demographic group fairness in federated learning. *arXiv preprint arXiv:2201.08304*, 2022.

Vasileios Perifanis and Pavlos S Efraimidis. Federated neural collaborative filtering. *Knowledge-Based Systems*, 242:108441, 2022.

Dazhong Rong, Shuai Ye, Ruoyan Zhao, Hon Ning Yuen, Jianhai Chen, and Qinming He. Fedrecattack: Model poisoning attack to federated recommendation. *arXiv preprint arXiv:2204.01499*, 2022.

Yuta Saito, Suguru Yaginuma, Yuta Nishino, Hayato Sakata, and Kazuhide Nakata. Unbiased recommender learning from missing-not-at-random implicit feedback, 2019. URL https://arxiv.org/abs/1909.03601.

Robert J Serfling. Probability inequalities for the sum in sampling without replacement. *The Annals of Statistics*, pp. 39–48, 1974.

Virginia Smith, Chao-Kai Chiang, Maziar Sanjabi, and Ameet S Talwalkar. Federated multi-task learning. *Advances in neural information processing systems*, 30, 2017.

Virginia Smith, Simone Forte, Ma Chenxin, Martin Takáč, Michael I Jordan, and Martin Jaggi. Cocoa: A general framework for communication-efficient distributed optimization. *Journal of Machine Learning Research*, 18:230, 2018.

Muhammad Ammad ud din, Elena Ivannikova, Suleiman A. Khan, Were Oyomno, Qiang Fu, Kuan Eeik Tan, and Adrian Flanagan. Federated collaborative filtering for privacy-preserving personalized recommendation system, 2019.

Omar Abdel Wahab, Gaith Rjoub, Jamal Bentahar, and Robin Cohen. Federated against the cold: A trust-based federated learning approach to counter the cold start problem in recommendation systems. *Information Sciences*, 2022.

Qinyong Wang, Hongzhi Yin, Tong Chen, Junliang Yu, Alexander Zhou, and Xiangliang Zhang. Fast-adapting and privacy-preserving federated recommender system. *The VLDB Journal*, pp. 1–20, 2021.

Chuhan Wu, Fangzhao Wu, Tao Qi, Yongfeng Huang, and Xing Xie. Fedattack: Effective and covert poisoning attack on federated recommendation via hard sampling. *arXiv preprint arXiv:2202.04975*, 2022.

Lin Xiao, Zhang Min, Zhang Yongfeng, Gu Zhaoquan, Liu Yiqun, and Ma Shaoping. Fairness-aware group recommendation with pareto-efficiency. In *Proceedings of the Eleventh ACM Conference on Recommender Systems*, pp. 107–115, 2017.

Ke Yang, Joshua R Loftus, and Julia Stoyanovich. Causal intersectionality for fair ranking. *arXiv preprint arXiv:2006.08688*, 2020a.

Liu Yang, Ben Tan, Vincent W Zheng, Kai Chen, and Qiang Yang. Federated recommendation systems. In *Federated Learning*, pp. 225–239. Springer, 2020b.

Timothy Yang, Galen Andrew, Hubert Eichner, Haicheng Sun, Wei Li, Nicholas Kong, Daniel Ramage, and Françoise Beaufays. Applied federated learning: Improving google keyboard query suggestions, 2018.

Sirui Yao and Bert Huang. Beyond parity: Fairness objectives for collaborative filtering. *Advances in neural information processing systems*, 30, 2017.

Xubo Yue, Maher Nouiehed, and Raed Al Kontar. Gifair-fl: An approach for group and individual fairness in federated learning, 2021.

Daniel Yue Zhang, Ziyi Kou, and Dong Wang. Fairfl: A fair federated learning approach to reducing demographic bias in privacy-sensitive classification models. In *2020 IEEE International Conference on Big Data (Big Data)*, pp. 1051–1060, 2020. doi: 10.1109/BigData50022.2020.9378043.

Shijie Zhang, Hongzhi Yin, Tong Chen, Zi Huang, Quoc Viet Hung Nguyen, and Lizhen Cui. Pi-pattack: Poisoning federated recommender systems for manipulating item promotion. In *Proceedings of the Fifteenth ACM International Conference on Web Search and Data Mining*, pp. 1415–1423, 2022.

A   APPENDIX

A.1   NOTATIONS

We list down all the important and frequently used notations in Table 1.

Symbol	Meaning
n	Number of clients in training set
m	Number of items in training set
K	Number of Latent factors
$R = \{1, ...5\}$	Rating range
r_{ui}	True rating
$\hat{r}_{ui}$	Predicted rating
r'_{ui}	Virtual rating
p_{ui}	Indiactor variable
u	client
i	item
I	Set of all items
U_i	Set of clients who rated item i
U'_i	Set of all clients who rated an item i virtually
I_u	Set of items rated by u
I'_u	Set of items rated virtually by u
U	client vectors matrix
V	Item vectors matrix
U_u	client vector for client u
V_i	Item vector for an item i
$\nabla V(u, i)$	Item gradient for i^{th} item which was rated by a user u
R	Rating Dataset
D_{train}	Training set
D_{server}	Dataset at server
g	Disadvantaged Group
$\neg g$	Advantaged Group
ρ	Sampling parameter
λ^r	Regularizer to prevent overfitting in FairMF
λ^f	Fairness regularizer in FairMF
α	Learning rate in FairMF
τ	Fraction of clients sampled for one communication round
γ	Learning Rate for clients
η	Fairness Penalizer for clients
T	Number of communication rounds
T_s	Number of epochs in FairMF
T_{local}	Number of iterations required to obtain prediction in Client Filling

Table 1: Notations and their meaning

A.2   EXPERIMENTAL PROOF FOR LEMMA 1

We provide the experimental proof for Lemma 1. FedRec generates item vectors at each communication round. We cluster these item vectors generated by FedRec by using K-means clustering

(Bock (2007)).Figure 5 shows the elbow curve obtained after plotting clustering loss *Inertia* (Hedman et al. (2007))corresponding to the number of clusters. Inertia is one of the most populalr metrics to evaluated clustering results. It is calculated as the sum of distances to each cluster center. A high value of total distance implies that the points are far from each other which is a clear indication that they are less similar to each other. It can be seen that for both the datasets we get $K = 20$ as the ideal number of clusters.

(a) ML1M (b) ML100k

Figure 5: Ideal number of clusters for item vectors in both datasets

Considering $K = 20$ and asssuming that we have total number of clients $n = 6000$, we randomly assign each client to one out of 20 clusters. Then, we randomly sample some of the clients and observe some interesting observations depicted in Figure 6. Figure 6a shows that after sampling some clients randomly at uniform, the average number of clients from each cluster are almost same. Further, Figure 6b clearly shows that the probability of getting $> 15\%$ error in above experiment is as small as 7.5% when averaged over 500 runs. Finally, Figure 6c demonstrates that minimum number of samples in each cluster is also same. Thus all the three experiments support our Lemma 1.

(a) (b) (c)

Figure 6: Experimental Analysis of Random Sampling of Clients and Clustering

A.3 CLIENTFILLING AT CLIENTS

The main goal of FedRec is to predict the rating of a user u to each item i without sharing the rating behaviors or rating records. For this, FedRec proposes two techniques, *User Averaging* (UA) and *Hybrid Filling* (HF) to add noise to the user's rating for privacy preservation. In UA, some unrated items are sampled and then a virtual rating r'_{ui} is assigned to these items. In HF, after a certain amount of time $T_{predict}$ the virtual rating is replaced by the predicted rating. To acquire predicted rating each client evaluates its user gradients and then updates its user vector *(line 4)*. The virtual rating r'_{ui} is given as:

$$r'_{ui} = \frac{\sum_{i=1}^{m} p_{ui}r_{ui}}{\sum_{i=1}^{m} p_{ui}} \tag{5}$$

The complete procedure is given in Algorithm 2

Algorithm 2 ClientFilling($V_i, i = 1, 2, ..., m; U_u; u; t$)

1: **if** strategy == HF **then**
2:     **for** $t_{local} = 1, 2, ..., T_{local}$ **do**
3:         Calculate the gradient ∇U_u
4:         $U_u \leftarrow U_u - \gamma \nabla U_u$
5:     **end for**
6:     Assign r'_{ui} to each item $i \in I'_u$ via HF
7: **else**
8:     Assign r'_{ui} to each item $i \in I'_u$ via UA
9: **end if**

Algorithm		Hyper-parameter	Tuned Values	
			ML1M	ML100k
FedRec		Learning Rate (γ)	0.1	0.08
		Regularizer (λ^r)	0.02	0.01
RS-FedRec		Learning Rate (γ)	0.1	0.08
		Regularizer (λ^r)	0.02	0.01
RS-FairFRS[20%]	Server	Learning Rate (α)	0.012	0.009
		Regularizer (λ^r)	0.05	0.02
		Fairness Regularizer (λ^f)	1.5	1.25
	Clients	Learning Rate (γ)	0.5	0.2
		Regularizer (λ^r)	0.01	0.02
		Fairness Regularizer (η)	1.75	1.55
RS-FairFRS[100%]	Server	Learning Rate (α)	0.04	0.15
		Regularizer (λ^r)	0.05	0.01
		Fairness Regularizer (λ^f)	2.5	2.0
	Clients	Learning Rate (γ)	0.65	0.22
		Regularizer (λ^r)	0.01	0.02
		Fairness Regularizer (η)	1.75	1.55

Table 2: Hyperparameter Values

A.4 HYPERPARAMETER TUNING

We carefully tune all the hyper-parameters and list down the final tuned values in Table 2. It is important to note that server in FedRec and RS-FedRec acts as an aggregator. Thus, the server does not require any tuning and the final tuned values for both the algorithms account for client side parameters. Opposite to this, server in RS-FAIRFRS[100%] as well as RS-FAIRFRS[20%] require fairness oriented training. Therefore, we present separate hyper-parameter values for client side and server side. Since, regularizers at server as well as client side prevents overfitting, we use λ^r to denote them, but fairness regularizer at server λ^f trains aggregated item vectors towards fairness using $D_s erver$ and fairness regularizer η at client side trains local models towards globally fair item vectors. Experimentally, we observe that all the models converge well at $T = 20$, thus we use $T = 20$ in all our experiments. However, while executing FairMF at the server, we train FairMF for $T_s = 15$ after each communication round. We obtain better fairness when we train FairMF for some epochs instead of letting it converge fully over each communication round which can be time consuming and it increases the load at server too. Thus FairMF executes for only 15 epochs and provides the updated item vectors to be communicated to all the local clients.

A.5 TRAINING AND TESTING RESULTS

We report the train as well as test results of all the four federated algorithms on two real-world datasets of ML1M and ML100k with two different sensitive attributes in Tables 3 and 4. It is noted that similar to training results, RS-FAIRFRS[20%] performs the best in terms of accuracy

as well as fairness. From the tables, it is evident that FedRec and RS-FedRec performs nearly the same which shows that random sampling retains the model accuracy. Then, our results (rows for RS-FAIRFRS[20%] and RS-FAIRFRS[100%]) provide an empirical proof to the claim we made in the main paper which states that we do not need huge amount of data at the server. With a minimal amount, we can acquire much better accuracy and demographic fairness too. Further, our results emphasize an important and interesting reasoning to improved accuracy as RS-FAIRFRS[20%] not only reduces the loss on advantaged group but also on the disadvantaged group. Our model is able to achieve this due to the uniqueness of the metric l_{ap} which when added to optimization function of MF, reduces loss as well as the difference between the loss on the various attributes over each stochastic gradient descent step.

Datasets	Attribute	Algorithms	RMSE	RMSE on Advantaged Group	RMSE on Disadvantaged Group	Demographic Bias
ML1M	Age	FedRec	0.89890 ± 0.00024	1.00784 ± 0.00212	0.89476 ± 0.00026	0.22409 ± 0.00432
		RS-FedRec	0.89922 ± 0.00040	1.00855 ± 0.00181	0.89506 ± 0.00042	0.22479 ± 0.00405
		RS-FairFRS [20%]	**0.80581 ± 0.00165**	**0.86298 ± 0.00441**	**0.80364 ± 0.00161**	**0.10244 ± 0.00660**
		RS-FairFRS [100%]	0.90466 ± 0.00080	1.00881 ± 0.00084	0.90071 ± 0.00085	0.21397 ± 0.00285
	Gender	FedRec	0.89890 ± 0.00024	0.91902 ± 0.00101	0.89112 ± 0.00047	0.05446 ± 0.00218
		RS-FedRec	0.89922 ± 0.00040	0.91923 ± 0.00045	0.89134 ± 0.00047	0.05448 ± 0.00171
		RS-FairFRS [20%]	**0.80695 ± 0.00104**	**0.81883 ± 0.00404**	**0.80365 ± 0.00652**	**0.03354 ± 0.00282**
		RS-FairFRS [100%]	0.90443 ± 0.00062	0.92200 ± 0.00095	0.89750 ± 0.00079	0.04826 ± 0.00271
ML100k	Age	FedRec	0.88866 ± 0.00159	0.95684 ± 0.00537	0.88452 ± 0.00156	0.15253 ± 0.00980
		RS-FedRec	0.88985 ± 0.00114	0.95893 ± 0.00475	0.88565 ± 0.00116	0.15483 ± 0.00937
		RS-FairFRS [20%]	**0.87343 ± 0.00316**	**0.90889 ± 0.00422**	**0.87127 ± 0.00321**	**0.07833 ± 0.00596**
		RS-FairFRS [100%]	0.90292 ± 0.00188	0.953335 ± 0.01394	0.90092 ± 0.00199	0.11760 ± 0.00325
	Gender	FedRec	0.88866± 0.00159	0.93465 ± 0.00214	0.89249 ± 0.00098	0.08380 ± 0.00370
		RS-FedRec	0.88985 ± 0.00114	0.93512 ± 0.00147	0.89315 ± 0.00094	0.08389 ± 0.00387
		RS-FairFRS [20%]	**0.88824 ± 0.00275**	**0.91282 ± 0.00510**	**0.87958 ± 0.00272**	**0.06503 ± 0.01114**
		RS-FairFRS [100%]	0.90241±0.00179	0.93135±0.00231	0.89062±0.00219	0.079656±0.00600

Table 3: Training results of 4 different algorithms on real-world datasets.

Datasets	Attribute	Algorithms	RMSE	RMSE on Advantaged Group	RMSE on Disadvantaged Group	Demographic Bias
ML1M	Age	FedRec	1.28992 ± 0.0009	1.34240 ± 0.00050	1.26220± 0.00050	0.45860 ± 0.00021
		RS-FedRec	1.30870 ± 0.00844	1.41004 ± 0.00085	1.28991 ± 0.00122	0.47445 ± 0.00311
		RS-FairFRS [20%]	**1.07941 ± 0.00355**	**0.90014 ± 0.00233**	**0.88700± 0.00220**	**0.20124 ± 0.00876**
		RS-FairFRS [100%]	1.50866 ± 0.00070	1.55281 ± 0.00081	1.10155 ± 0.00080	0.30369 ± 0.00549
	Gender	FedRec	1.27881 ± 0.00012	1.29940 ± 0.00120	1.25531± 0.000131	0.09971 ± 0.00880
		RS-FedRec	1.28808 ± 0.00043	1.30001 ± 0.00032	1.26101 ± 0.00014	0.09818 ± 0.00160
		RS-FairFRS [20%]	**1.00121 ± 0.00812**	**0.90144 ± 0.00555**	**0.86652 ± 0.00853**	**0.06164 ± 0.00372**
		RS-FairFRS [100%]	1.44441 ± 0.00022	1.29909 ± 0.00099	1.27713 ± 0.00069	0.08929 ± 0.00221
ML100k	Age	FedRec	1.33451± 0.00331	1.45421 ± 0.00549	1.38331 ± 0.00106	0.30133 ± 0.00860
		RS-FedRec	1.32320 ± 0.00450	1.42773 ± 0.00220	1.37877± 0.00545	0.30311 ± 0.00568
		RS-FairFRS [20%]	**1.12250 ± 0.00113**	**0.98182 ± 0.00661**	**0.90973 ± 0.00435**	**0.21243 ± 0.00601**
		RS-FairFRS [100%]	1.38915 ± 0.00087	1.43470 ± 0.00995	1.38001 ± 0.00221	0.28823 ± 0.00221
	Gender	FedRec	1.323112 ± 0.00229	1.37360 ± 0.00189	1.31004 ± 0.00022	0.10119 ± 0.00283
		RS-FedRec	1.329914 ± 0.00654	1.36915 ± 0.00441	1.30899 ± 0.00107	0.11218 ± 0.00471
		RS-FairFRS [20%]	**1.01877 ± 0.00334**	**0.80817 ± 0.00190**	**0.77521 ± 0.00162**	**0.08225 ± 0.00188**
		RS-FairFRS [100%]	1.39592 ± 0.00227	1.29280 ± 0.00779	1.12118 ± 0.00911	0.90718 ± 0.00901

Table 4: Testing Results of 4 different algorithms on real-world datasets