Model Zoo: A Growing "Brain" That Learns Continually

Abstract

This paper argues that continual learning methods can benefit by splitting the capacity of the learner across multiple models. We use statistical learning theory and experimental analysis to show how multiple tasks can interact with each other in a highly non-trivial fashion when trained on a single model. The generalization error on a particular task can improve when it is trained with synergistic tasks, but can just as easily deteriorate when trained with competing tasks. This phenomenon motivates our method named Model Zoo which, inspired from the boosting literature, grows an ensemble of small models, each of which is trained during one episode of continual learning. We demonstrate gains in accuracy on a variety of continual learning benchmarks.

1   Introduction

A continual learner seeks to leverage data from past tasks to learn new tasks shown to it in the future, and in turn, leverage data from these new tasks to improve its accuracy on past tasks. It stands to reason that the performance of such a learner would depend upon the relatedness of these tasks. If the two sets of tasks are dissimilar, learning on past tasks is unlikely to benefit future tasks—it may even be detrimental. And similarly, new tasks may cause the learner to "forget" and result in deteriorated accuracy on past tasks. Our goal in this paper is to model the relatedness between tasks and develop new methods for continual learning that result in good forward-backward transfer by accounting for such similarities and dissimilarities between tasks. Our contributions are as follows.

1. Theoretical analysis: We characterize when multiple tasks can be learned using a single model and, likewise, when doing so is detrimental to the accuracy of a particular task. **2. Algorithm development:** We develop such a continual learner called Model Zoo that splits the learning capacity amongst synergistic tasks using an algorithm loosely inspired from AdaBoost. **3. Empirical results:** We evaluate Model Zoo on benchmarks from task-incremental continual learning. There is a wide variety of problem settings and we find that in a number of these settings, Model Zoo obtains better accuracy than existing methods (improvement in average per-task accuracy is as large as 30% on Split-miniImagenet). **4. A critical look at continual learning:** We find that even an Isolated learner, i.e., one which trains a (small) model on tasks from each episode and does not perform any continual learning, *all* most continual learning methods on the evaluated benchmark problems, e.g., by more than 8% in Fig. 1. This strong performance is surprising because it is a very simple learner that has better training/inference time, no data replay, and a comparable number of weights to that of existing methods.

2   A theoretical analysis of how to learn from multiple tasks

2.1   Problem Formulation

A supervised learning task is defined as a joint probability distribution $P(x, y)$ of inputs $x \in X$ and labels $y \in Y$. The learner has access to m i.i.d samples $S = \{x_i, y_i\}_{i=1,\ldots,m}$ from the task. A hypothesis is a function $h : X \to Y$ with $h \in H$ being the hypothesis space. The learner may select a hypothesis that minimizes the empirical risk $\hat{e}_S(h) = \frac{1}{m} \sum_{i=1}^{m} \mathbf{1}_{\{h(x_i) \neq y_i\}}$ with the hope of achieving a small population risk $e_P(h) = \mathbb{P}(h(x) \neq y)$.

Let $D = \mathrm{VC}(H)$, refer to the VC-dimension of the hypothesis space H. We define the "excess risk" of a hypothesis as $\mathcal{E}_P(h) = e_P(h) - \inf_{h \in H} e_P(h)$. In the continual learning setting, a new task is shown to the learner at each episode (or round). Hence after n episodes, the learner is presented with n tasks $\bar{P} := (P_1, \ldots, P_n)$, with the corresponding training sets $\bar{S} := (S_1, \ldots, S_n)$, each with

Figure 1: Left: How well do existing continual learning methods work? We track the average accuracy (over all tasks seen until the current episode) on the Split-miniImagenet dataset and compare our method Model Zoo and its variants (all in bold) to existing continual learning methods (faint lines, see Table A1 for references). All methods in this plot (except red/orange lines) use the single epoch setting, i.e., each new task is allowed only 1 epoch of training. Isolated refers to a simplistic realization of Model Zoo where a separate model is fitted at each episode without any continual learning, or data sharing between tasks; Isolated-small or Model Zoo-small refer to using a small deep network with 0.12M weights. A number of surprising findings are seen here. (i) Isolated-small (black) outperforms existing methods by more than 10% margin, while having a faster training time, inference time, comparable model size and without performing any data replay. This indicates that **existing methods do not sufficiently leverage data from multiple tasks**. (ii) While the larger model with 3.6M weights per round, Isolated-Single Epoch (royal blue), performs poorly, its accuracy is better than the compared methods (Isolated-Multi Epoch) upon being trained for multiple epochs. This indicates that **existing methods may be severely under-trained in the single-epoch setting**. (iii) Model Zoo and Model Zoo-small which replay all data from past tasks (A-GEM also replays 10% of the data), achieves around 10% improvement over its Isolated counterparts in both the single-epoch and multi-epoch setting; This indicates that replaying data from past tasks is beneficial (Robins, 1995), even if replay may not conform to certain stylistic formulations of continual learning in the literature.

Right: Does the single-epoch setting show forward-backward transfer? The evolution of individual task accuracy of Model Zoo (the multi-epoch setting in bold and single-epoch setting in dotted), on the Split-miniImagenet dataset (only 5 tasks are plotted here, see Fig. A6 for the full version). The X markers denote the accuracy of Isolated. Accuracy of tasks improves with each episode which indicates backward transfer. Also, the X markers are often below the initial accuracy of the task during continual learning, which indicates forward transfer. While both single-epoch and multi-epoch Model Zoo show good forward-backward transfer, the accuracy of tasks for the former is about 25% worse than the latter; corresponding plots for other methods are in Appendix B.7. This indicates that we should also pay attention to under-training and per-task accuracy in continual learning.

m samples, and the learner selects n hypotheses $\bar{h} = (h_1, \ldots, h_n) \in H^n$, each $h_i \in H$. If it seeks a small average population risk $e_{\bar{P}}(\bar{h}) = \frac{1}{n} \sum_{i=1}^n e_{P_i}(h_i)$, it may do so by minimizing the average empirical risk $\hat{e}_{\bar{S}}(\bar{h}) = \frac{1}{n} \sum_{i=1}^n \hat{e}_{S_i}(h_i)$.

2.2 Task competition in hypothesis spaces with limited capacity

There could be settings under which fitting one model on multiple tasks may not suffice. To study this, we consider a weaker notion of relatedness. We say that two tasks P_i, P_j are ρ_{ij}-related if

$$c \, \mathcal{E}_{P_i}^{1/\rho_{ij}}(h) \geq \mathcal{E}_{P_j}(h, h_i^*), \text{ for all } h \in H. \tag{1}$$

Here $\mathcal{E}_P(h, h') := e_P(h) - e_P(h')$ and $h_i^* = \operatorname{argmin}_{h \in H} e_{P_i}(h)$ is the best hypothesis for task P_i; we set $c \geq 1$ to be a coefficient independent of i, j. Smaller the ρ_{ij}, more useful the samples from P_i to learn P_j. The definition suggests that all hypotheses h which have low excess risk on P_i also have low excess risk on P_j up to an additive term $e_{P_j}(h^*)$ and this effect becomes stronger as $\rho_{ij} \to 1_+$. Hanneke and Kpotufe (2020) call this the transfer exponent. We can now show the following theorem bounds the excess risk $\mathcal{E}_{P_1}(h)$ for a hypothesis h trained using data from multiple tasks. See Appendix C for the proof.

Theorem 1 (Task competition). Say we wish to find a good hypothesis for task P_1 and have access to n tasks $P_1, \ldots, P_n$ where each pair P_i, P_j are ρ_{ij}-related. Arrange tasks in an increasing order of ρ_{i1}, i.e., their relatedness to P_1. Let this ordering be $P_{(1)}, P_{(2)}, \ldots, P_{(n)}$ with $\rho_{(1)} \leq \rho_{(2)} \leq \ldots \leq \rho_{(n)}$ and $P_{(1)} \equiv P_1$ and $\rho_{(1)} = 1$. Let $\hat{h}^k$ be the hypothesis that minimizes the average empirical risk of

the first $k \leq n$ tasks. Then, with probability at least $1 - \delta$ over draws of the training data,

$$\mathcal{E}_{P_1}(\hat{h}^k) \leq \frac{1}{k} \sum_{i=1}^k \mathcal{E}_{P_1}(h^*_{(i)}) + \frac{c}{k} \left(e_{\bar{S}}(h) + c' \left(\frac{D - \log \delta}{km} \right)^{1/2} \right)^{1/\rho_{\max}} \tag{2}$$

where $\rho_{\max}(k) = \max \left\{ \rho_{(1)}, \ldots, \rho_{(k)} \right\}$ and c, c' are constants.

The first term can be understood as quantifying the competition between multiple tasks and the second term can be understood to capture the benefit of learning multiple tasks together. Notice that the first term grows with the number of tasks k because we pick tasks with lower ρ_{i1} that are more and more dissimilar to P_1. The second term typically decreases with an increasing the number of tasks k.

The generalization error of task P_1 is minimized when trained alongside the k most related tasks (not necessarily all available tasks) where k minimizes the upper-bound from equation (2). Next, we note that different tasks have different orderings for the most related tasks and it is harder to do well on all tasks using a single model. Inspired by Equation (2) we design Model Zoo, which splits the capacity of the model amongst different groups of tasks.

3 Model Zoo: A continual learner that grows its learning capacity

Theorem 1 indicates that ones should not always expect improved excess risk by combining data from different tasks. This theorem also suggests a way to work around the problem. If we learn small models on synergistic tasks, we can hope to have each task benefit from the synergies without deterioration of accuracy due to task competition with dissonant tasks. Model Zoo is a simple method that is designed for this purpose.

Let us assume that tasks $P_1, \ldots, P_n$ are shown sequentially to the continual learner. We assume that all tasks have the same input domain X but may have different output domains $Y_1, \ldots, Y_n$. At each "episode" k, Model Zoo is designed to train using the current task P_k and a subset of the past tasks. Let the set of tasks considered at episode k be denoted by $\bar{P}_k = \{P_{\omega_k^1}, \ldots, P_{\omega_k^b}\}$ where $b \leq k$ is a hyper-parameter and $\omega_k^i \in \{1, \ldots, k\}$. Training on $\bar{P}_k$ will involve, training one model with a feature generator h_k and task-specific classifiers g_{k,ω_k^i} for each task selected in that round. Such models, one trained in each round, together form the "Model Zoo". After k rounds, data from, say, P_i with $i \leq k$ can be predicted using the average of class probabilities output by all models that were fitted on that task, i.e.,

Figure 2: Ideally, we want to train synergistic tasks together, e.g., Model 1 for P_1 using P_3, P_6 and Model 3 for P_3 using P_1, P_4, P_5. Model Zoo is a simple, scalable instantiation of this idea. Discovering noncompeting tasks is difficult, so it selects tasks that have high training loss under the current ensemble.

$$p_{k,i}(y \mid x) \propto \sum_{l=1}^k \mathbf{1}_{\{P_i \in \bar{P}_l\}} g_{l,i} \circ h_l(x). \tag{3}$$

This expression is also used to predict at test time.

Selecting tasks to train with for each round using boosting. In principle, we could use the transfer exponents ρ_{ij} to select synergistic tasks, but computing the transfer exponents is essentially as difficult as training on all tasks. We therefore develop an automatic way to select tasks in each round. We draw inspiration from boosting (Schapire and Freund, 2013) for this purpose. Recall the AdaBoost algorithm which builds an ensemble of weak learners, each of which is fitted upon iteratively re-weighted training data (Breiman, 1998).

We think of the models learned at each episode of continual learning in Model Zoo as the "weak learners" and each round of boosting as the equivalent of each episode of continual learning. Let $\bar{w}_k \in \mathbb{R}^n$ be a normalized vector of task-specific weights. After episode k

$$\bar{w}_{k,i} \propto \exp\left(-1/m \sum_{(x,y) \in S_i} \log p_{k,i}(y \mid x) \right). \tag{4}$$

for each task P_i with $i \leq k$; for $i > k$, $\bar{w}_{k,i} = 0$. Tasks for the next round $\bar{P}_{k+1}$ are drawn from a multinomial distribution with weights $\bar{w}_k$. Therefore, tasks with a low empirical risk under the current Model Zoo get a low weight for the next boosting round. Just like AdaBoost drives down the training error on *all* samples to zero exponentially (Schapire and Freund, 2013) by iteratively focusing upon difficult-to-classify samples, Model Zoo achieves a low empirical risk on *all* tasks as more models are added.

Method	Rotated-MNIST	Permuted-MNIST	Split-MNIST	Split-CIFAR10	Split-CIFAR100	Coarse-CIFAR100	Split-miniImagenet
EWC (Kirkpatrick et al., 2017)	•84	•96.9	-	-	•42.40	-	46.69
GEM (Lopez-Paz and Ranzato, 2017)	86.07	82.60	-	-	*67.8	-	51.86
RWalk (Chaudhry et al., 2018) †	-	•93.5	99.3	-	*,•40.9	-	-
A-GEM (Chaudhry et al., 2019a) †	-	89.1	-	-	*62.3	-	61.13
Stable-SGD (Mirzadeh et al., 2020b) †	70.8	80.1	-	-	*59.9	-	57.79
ER-Reservoir (Chaudhry et al., 2019b) †	-	79.8	-	-	*68.5	-	64.03
MEGA-II (Guo et al., 2020a)	-	91.20	-	-	66.12	-	-
RMN (Kaushik et al., 2021) (strict)	-	97.73	99.5	-	80.01	-	-
Our methods							
Isolated-small	-	-	-	96.88	90.18	69.07	82.48
Model Zoo-small	-	-	-	96.85	92.06	73.72	94.27
Model Zoo-small (10% replay)	-	-	-	96.58	89.76	77.18	84.6
Isolated	99.64	98.03	99.98	97.46	91.90	80.72	86.28
Model Zoo	99.66	97.71	99.97	98.68	94.99	84.27	96.84
Multi-Head (multi-task)	99.66	98.16	99.98	98.11	95.38	83.19	90.83

Table 1: Average per-task accuracy (%) at the end of all episodes. MNIST, Permuted-MNIST and Rotated-MNIST are not informative benchmarks for judging forward and backward transfer because even Isolated achieves 99%+ accuracy. Model Zoo outperforms, by significant margins, all existing continual learning methods on all datasets. Accuracy of existing methods is worse than Isolated which suggests little to no forward or backward transfer. Model Zoo-small and Isolated-have comparable number of weights as that of existing methods, **Note:** * indicates that the evaluation was on Split-CIFAR100 with each task containing randomly sampled labels and is hence it is not directly comparable to other methods. † train for 1 epoch per episode. * denotes that accuracy is reported from other publications,

4 Experiments

Table 1 shows the validation accuracy of different continual learning methods on standard benchmark problems. Isolated can be thought of as the simplest possible continual learner—one that unfreezes new capacity at each episode and does not replay data. We also evaluate on the "small" variant of models, consisting of far fewer parameters (0.12M weights for each learner). We also evaluate with a limited experience replay. For more details and experiments, see Appendix B.

(i) **Accuracy of all existing methods** in Table 1, regardless of their specific setting, **is much poorer than Isolated** (more than 10% for both the small and standard versions). This indicates that existing methods may be failing to achieve forward or backward transfer compared to simply training the task in isolation; Table A2 investigates this further.

(ii) In comparison, **Model Zoo (all three variants**: small, small with 10% data replay and the standard method) **has dramatically better accuracy (more than 10% better than existing methods)** both compared to existing methods as well as compared to Isolated. This shows the utility of splitting the capacity of the learner across multiple tasks.

(iii) **Model Zoo matches the accuracy of the multi-task learner** in the last row of Table 1 which has access to all tasks beforehand. Surprisingly, **Model Zoo performs better than Multi-Head in spite of being trained in continual fashion**, especially on harder problems like Coarse-CIFAR100 and Split-miniImagenet. This is a direct demonstration of the effectiveness of Model Zoo in mitigating task competition: the capacity splitting mechanism not only avoids catastrophic forgetting, but it can also leverage data from other tasks even if they are shown sequentially.

5 Discussion

Continual learning is an important problem as deep learning systems transition from the traditional paradigm of having a fixed model that makes inferences on user queries to settings where we would like to update the model to handle new types of queries. The key desiderata of such a system are clear: it must display high per-task accuracy and strong forward-backward transfer. This paper seeks to develop such a continual learner and investigates the problem using the lens of task relatedness. It argues that the learner must split its capacity across sets of tasks to mitigate competition between tasks and benefit from synergies among them. We develop Model Zoo, which is a continual learning algorithm inspired by AdaBoost, that grows an ensemble of models, each of which is trained on data from the current episode along with a subset of past tasks. **We show that across a wide variety of datasets, problem formulations, and evaluation criteria, Model Zoo and its variants significantly outperform all existing continual learning methods**.

Our goal is to provide grounding to the practice of continual learning. We believe that there is merit in studying problem settings such as no data replay, or single epoch training. But if even a simple "baseline" method, where a separate, small model is trained independently in each episode, handily outperforms existing methods, or if even a small amount of data replay can obtain so much better accuracy and forward-backward transfer, then we need to consider whether the problem formulations

may be holding us back from building effective algorithms. We advocate that these desiderata should be the focus of future investigations. Also see some more discussion in Appendix D.

References

Baxter, J. (2000). A model of inductive bias learning. *Journal of artificial intelligence research*, 12:149–198.

Ben-David, S. and Borbely, R. S. (2008). A notion of task relatedness yielding provable multiple-task learning guarantees. *Machine learning*, 73(3):273–287.

Ben-David, S. and Schuller, R. (2003). Exploiting task relatedness for learning multiple tasks. In *Proceedings of the 16th Annual Conference on Learning Theory*.

Breiman, L. (1998). Arcing classifier (with discussion and a rejoinder by the author). *Annals of Statistics*, 26(3):801–849.

Chaudhry, A., Dokania, P. K., Ajanthan, T., and Torr, P. H. (2018). Riemannian walk for incremental learning: Understanding forgetting and intransigence. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 532–547.

Chaudhry, A., Ranzato, M., Rohrbach, M., and Elhoseiny, M. (2019a). Efficient lifelong learning with a-gem. In *ICLR*.

Chaudhry, A., Rohrbach, M., Elhoseiny, M., Ajanthan, T., Dokania, P. K., Torr, P. H., and Ranzato, M. (2019b). On tiny episodic memories in continual learning. *arXiv preprint arXiv:1902.10486*.

Crammer, K., Kearns, M., and Wortman, J. (2008). Learning from multiple sources. *Journal of Machine Learning Research*, 9(8).

Farajtabar, M., Azizan, N., Mott, A., and Li, A. (2020). Orthogonal gradient descent for continual learning. In *International Conference on Artificial Intelligence and Statistics*, pages 3762–3773. PMLR.

Farquhar, S. and Gal, Y. (2019). Towards Robust Evaluations of Continual Learning. *arXiv:1805.09733 [cs, stat]*.

Guo, Y., Liu, M., Yang, T., and Rosing, T. (2020a). Improved schemes for episodic memory-based lifelong learning. In *Advances in Neural Information Processing Systems*.

Guo, Y., Liu, M., Yang, T., and Rosing, T. (2020b). Improved schemes for episodic memory based lifelong learning algorithm. In *NeurIPS*.

Hanneke, S. and Kpotufe, S. (2020). A no-free-lunch theorem for multitask learning. *arXiv preprint arXiv:2006.15785*.

Kaushik, P., Gain, A., Kortylewski, A., and Yuille, A. (2021). Understanding catastrophic forgetting and remembering in continual learning with optimal relevance mapping. *arXiv preprint arXiv:2102.11343*.

Kietzmann, T. C., Spoerer, C. J., Sörensen, L. K., Cichy, R. M., Hauk, O., and Kriegeskorte, N. (2019). Recurrence is required to capture the representational dynamics of the human visual system. *Proceedings of the National Academy of Sciences*, 116(43):21854–21863.

Kirkpatrick, J., Pascanu, R., Rabinowitz, N., Veness, J., Desjardins, G., Rusu, A. A., Milan, K., Quan, J., Ramalho, T., Grabska-Barwinska, A., et al. (2017). Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526.

Li, L., Jamieson, K., Rostamizadeh, A., Gonina, E., Hardt, M., Recht, B., and Talwalkar, A. (2018). A system for massively parallel hyperparameter tuning. *arXiv preprint arXiv:1810.05934*.

Liaw, R., Liang, E., Nishihara, R., Moritz, P., Gonzalez, J. E., and Stoica, I. (2018). Tune: A research platform for distributed model selection and training. *arXiv preprint arXiv:1807.05118*.

Lopez-Paz, D. and Ranzato, M. (2017). Gradient episodic memory for continual learning. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 6470–6479.

Malviya, P., Ravindran, B., and Chandar, S. (2021). Tag: Task-based accumulated gradients for lifelong learning. *arXiv preprint arXiv:2105.05155*.

Mirzadeh, S. I., Farajtabar, M., Gorur, D., Pascanu, R., and Ghasemzadeh, H. (2020a). Linear mode connectivity in multitask and continual learning. *arXiv preprint arXiv:2010.04495*.

Mirzadeh, S. I., Farajtabar, M., Pascanu, R., and Ghasemzadeh, H. (2020b). Understanding the role of training regimes in continual learning. *arXiv preprint arXiv:2006.06958*.

Nguyen, C. V., Li, Y., Bui, T. D., and Turner, R. E. (2017). Variational continual learning. *arXiv preprint arXiv:1710.10628*.

Pan, P., Swaroop, S., Immer, A., Eschenhagen, R., Turner, R., and Khan, M. E. E. (2020). Continual deep learning by functional regularisation of memorable past. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M. F., and Lin, H., editors, *Advances in Neural Information Processing Systems*, volume 33, pages 4453–4464. Curran Associates, Inc.

Prabhu, A., Torr, P. H., and Dokania, P. K. (2020). Gdumb: A simple approach that questions our progress in continual learning. In *European conference on computer vision*, pages 524–540. Springer.

Rapin, J. and Teytaud, O. (2018). Nevergrad - A gradient-free optimization platform. `https://GitHub.com/FacebookResearch/Nevergrad`.

Rebuffi, S.-A., Bilen, H., and Vedaldi, A. (2017a). Learning multiple visual domains with residual adapters. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 506–516.

Rebuffi, S.-A., Kolesnikov, A., Sperl, G., and Lampert, C. H. (2017b). iCARL: Incremental classifier and representation learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2001–2010.

Robins, A. (1995). Catastrophic forgetting, rehearsal and pseudorehearsal. *Connection Science*, 7(2):123–146.

Rosenbaum, C., Klinger, T., and Riemer, M. (2017). Routing networks: Adaptive selection of non-linear functions for multi-task learning. *arXiv preprint arXiv:1711.01239*.

Rusu, A. A., Rabinowitz, N. C., Desjardins, G., Soyer, H., Kirkpatrick, J., Kavukcuoglu, K., Pascanu, R., and Hadsell, R. (2016). Progressive neural networks. *arXiv preprint arXiv:1606.04671*.

Schapire, R. E. and Freund, Y. (2013). *Boosting: Foundations and Algorithms*. Emerald Group Publishing Limited.

Serra, J., Suris, D., Miron, M., and Karatzoglou, A. (2018). Overcoming catastrophic forgetting with hard attention to the task. In *International Conference on Machine Learning*, pages 4548–4557. PMLR.

Thrun, S. and Pratt, L. (2012). *Learning to Learn*. Springer Science & Business Media.

Titsias, M. K., Schwarz, J., de G. Matthews, A. G., Pascanu, R., and Teh, Y. W. (2020). Functional regularisation for continual learning with gaussian processes. In *International Conference on Learning Representations*.

Van de Ven, G. M. and Tolias, A. S. (2019). Three scenarios for continual learning. *arXiv preprint arXiv:1904.07734*.

Vapnik, V. (1998). *Statistical Learning Theory*. John Wiley & Sons.

Vinyals, O., Blundell, C., Lillicrap, T., Wierstra, D., et al. (2016). Matching networks for one shot learning. *Advances in Neural Information Processing Systems*, 29:3630–3638.

Vogelstein, J. T., Dey, J., Helm, H. S., LeVine, W., Mehta, R. D., Geisa, A., van de Ven, G. M., Chang, E., Gao, C., Yang, W., et al. (2020). Omnidirectional transfer for quasilinear lifelong learning. *arXiv preprint arXiv:2004.12908*.

Zagoruyko, S. and Komodakis, N. (2016). Wide residual networks. *arXiv preprint arXiv:1605.07146*.

Zenke, F., Poole, B., and Ganguli, S. (2017). Continual learning through synaptic intelligence. In *International Conference on Machine Learning*, pages 3987–3995. PMLR.

A A theoretical analysis of how to learn from multiple tasks

In this section, we (i) formulate the problem of learning from multiple tasks, (ii) discuss a simple model that highlights when training one model on multiple tasks is beneficial, and (iii) show new results on how the fixed capacity of the model causes competition between tasks.

A.1 Problem Formulation

A supervised learning task is defined as a joint probability distribution $P(x, y)$ of inputs $x \in X$ and labels $y \in Y$. The learner has access to m i.i.d samples $S = \{x_i, y_i\}_{i=1,\ldots,m}$ from the task. A hypothesis is a function $h : X \to Y$ with $h \in H$ being the hypothesis space. The learner may select a hypothesis that minimizes the empirical risk $\hat{e}_S(h) = \frac{1}{m} \sum_{i=1}^{m} \mathbf{1}_{\{h(x_i) \neq y_i\}}$ with the hope of achieving a small population risk $e_P(h) = \mathbb{P}(h(x) \neq y)$. Classical PAC-learning results (Vapnik, 1998) suggest that with probability at least $1 - \delta$ over draws of the data S, uniformly for any $h \in H$, we have $e_P(h) \leq \hat{e}_S(h) + \epsilon$ if

$$m = \mathcal{O}\big((D - \log \delta) / \epsilon^2\big) \tag{5}$$

where $D = \text{VC}(H)$ is the VC-dimension of the hypothesis space H. We define the "excess risk" of a hypothesis as $\mathcal{E}_P(h) = e_P(h) - \inf_{h \in H} e_P(h)$. In the continual learning setting, a new task is shown to the learner at each episode (or round). Hence after n episodes, the learner is presented with n tasks $\bar{P} := (P_1, \ldots, P_n)$, with the corresponding training sets $\bar{S} := (S_1, \ldots, S_n)$, each with m samples, and the learner selects n hypotheses $\bar{h} = (h_1, \ldots, h_n) \in H^n$, each $h_i \in H$. If it seeks a small average population risk $e_{\bar{P}}(\bar{h}) = \frac{1}{n} \sum_{i=1}^{n} e_{P_i}(h_i)$, it may do so by minimizing the average empirical risk $\hat{e}_{\bar{S}}(\bar{h}) = \frac{1}{n} \sum_{i=1}^{n} \hat{e}_{S_i}(h_i)$. As Baxter (2000) shows, under very general conditions, if

$$m = \mathcal{O}\big(\epsilon^{-2} \left(d_H(n) - 1/n \log \delta\right)\big), \tag{6}$$

then we have $e_{\bar{P}}(\bar{h}) \leq e_{\bar{S}}(\bar{h}) + \epsilon$ for any $\bar{h} \in H^n$. The quantity $d_H(n)$ here is a generalized VC-dimension for the family of hypothesis spaces H^n, which depends on the joint distribution of tasks. Larger the number of tasks n, smaller the $d_H(n)$ (Ben-David and Borbely, 2008). Whether (6) is an improvement upon training the task in isolation as in (5) depends upon the hypothesis class H and the relatedness of tasks $P_1, \ldots, P_n$ through the quantity $d_H(n)$. The most important thing to note here is that according to these calculations, if one wishes to obtain a small *average* population risk across tasks, training multiple tasks together cannot be worse: $d_H(n) \leq \text{VC}(H)$.

A.2 Controlling the excess risk of a specific task for synergistic tasks

An important goal of continual learning is to have low risk on *all tasks*. This is a stronger requirement than for (6) which bounds the *average* population risk on all tasks.

Suppose there exists a family F of functions $f_i : X \to X$ that map the inputs of one task to those of another, i.e., any task can be written as

$$P_j(A) = f[P_i](A) = \mathbb{P}_i(\{(f(x), y) : (x, y) \in A\})$$

for some function $f \in F$ for any set A. We can assume without loss of generality that F acts as a group over the hypothesis space and H is closed under its action. In simple words, this entails that given $h \in H$ suitable for task P, we can obtain a new hypothesis $h \circ f$ that is suitable for another task $f[P]$. Instead of searching over the entire space H^n like in Appendix A.1, we now only need to find a hypothesis $h \in H$ such that its orbit

$$[h]_F = \{h' : \exists f \in F \text{ with } h' = h \circ f\}$$

contains hypotheses that have low empirical risk on each of the n tasks. Conceptually, this step learns the inductive bias (Baxter, 2000; Thrun and Pratt, 2012). The sample complexity of doing so is exactly (6). From within this orbit, we can select a hypothesis that has low empirical risk for a chosen task P_1. The sample complexity of this second step is

$$|S_1| = \mathcal{O}\big(\epsilon^{-2} \left(d_{\max} - \log \delta\right)\big) \tag{7}$$

where $d_{\max} = \sup_{h \in H} \text{VC}([h]_F)$. By uniform convergence, as Ben-David and Schuller (2003) show, this two-step procedure assures low excess risk for *every* task $P_1, \ldots, P_n$. We have

$$\sup_{h \in H} \text{VC}([h]_F) = d_{\max} \leq d_H(n+1) \leq d_H(n) \leq D = \text{VC}(H). \tag{8}$$

The total sample complexity is favorable to that of learning the task in isolation if both $d_H(n)$ and $d_{\max}$ are small. For instance, if F is finite and $n/\log n \geq D$, we have $d_H(n) \leq 2\log|F|$ which indicates that we get a statistical benefit of learning with multiple tasks if $D \gg \log|F|$.

Remark 2 (Data from other tasks may not improve accuracy even if they are synergistic). Let us make a few observations using the above analysis. (i) From (8), number of samples per task m decreases with n; this is the benefit of the strong relatedness among tasks and as we see next, this is *not* the case in general. (ii) The number of tasks scales essentially linearly with D, which indicates that one should use a small model if we have few tasks. (iii) But we cannot always use a small model. If tasks are diverse and related by complex transformations with a large $|F|$, we need a large hypothesis space to learn them together. If $|F|$ is large and H is not appropriately so, the VC-dimension $d_{\max}$ is as large as D itself; in this case there is *again no statistical benefit* of training with multiple tasks together, but there is no deterioration either.

A.3 Task competition occurs for hypothesis spaces with limited capacity

There could be settings under which fitting one model on multiple tasks may not suffice. To study this, we consider a weaker notion of relatedness. We say that two tasks P_i, P_j are ρ_{ij}-related if

$$c\,\mathcal{E}_{P_i}^{1/\rho_{ij}}(h) \geq \mathcal{E}_{P_j}(h, h_i^*), \text{ for all } h \in H. \tag{9}$$

Here $\mathcal{E}_P(h, h') := e_P(h) - e_P(h')$ and $h_i^* = \operatorname{argmin}_{h \in H} e_{P_i}(h)$ is the best hypothesis for task P_i; we set $c \geq 1$ to be a coefficient independent of i, j. Smaller the ρ_{ij}, more useful the samples from P_i to learn P_j. The definition suggests that all hypotheses h which have low excess risk on P_i also have low excess risk on P_j up to an additive term $e_{P_j}(h^*)$ and this effect becomes stronger as $\rho_{ij} \to 1_+$. Note that the definition of relatedness is not symmetric. Hanneke and Kpotufe (2020) call this the transfer exponent. To gain some intuition, we can connect this definition to a certain triangle inequality between the tasks developed by Crammer et al. (2008): in the realizable setting where $e_{P_i}(h_i^*) = 0$, for $c, \rho_{ij} = 1$, we can write (9) as

$$e_{P_i}(h) + e_{P_j}(h_i^*) \geq e_{P_j}(h)$$

which is akin to a triangle with vertices at h, h_i^* and h_j^* with terms like $e_{P_i}(h)$ representing the length of the side between h and h_i^*. This definition therefore models a set of tasks and hypothesis space that is not unduly pathological, $e_{P_j}(h)$ cannot be much worse than the sum of the other two sides. We can now show the following theorem bounds the excess risk $\mathcal{E}_{P_1}(h)$ for a hypothesis h trained using data from multiple tasks. See Appendix C for the proof.

Theorem 3 (Task competition). Say we wish to find a good hypothesis for task P_1 and have access to n tasks $P_1, \ldots, P_n$ where each pair P_i, P_j are ρ_{ij}-related. Arrange tasks in an increasing order of ρ_{i1}, i.e., their relatedness to P_1. Let this ordering be $P_{(1)}, P_{(2)}, \ldots, P_{(n)}$ with $\rho_{(1)} \leq \rho_{(2)} \leq \cdots \leq \rho_{(n)}$ and $P_{(1)} \equiv P_1$ and $\rho_{(1)} = 1$. Let $\hat{h}^k$ be the hypothesis that minimizes the average empirical risk of the first $k \leq n$ tasks. Then, with probability at least $1 - \delta$ over draws of the training data,

$$\mathcal{E}_{P_1}(\hat{h}^k) \leq \frac{1}{k}\sum_{i=1}^{k}\mathcal{E}_{P_1}(h_{(i)}^*) + \frac{c}{k}\left(e_{\bar{S}}(h) + c'\left(\frac{D-\log\delta}{km}\right)^{1/2}\right)^{1/\rho_{\max}} \tag{10}$$

where $\rho_{\max}(k) = \max\left\{\rho_{(1)}, \ldots, \rho_{(k)}\right\}$ and c, c' are constants.

Notice that the first term grows with the number of tasks k because we pick tasks with lower ρ_{i1} that are more and more dissimilar to P_1. The second term typically decreases with k. The empirical risk $e_{\bar{S}}(h)$ is typically small; in our experiments with deep networks we achieve essentially zero training error on all. Increasing the number of tasks k, increases the effective number of samples km, thereby reducing the second term in totality. At the same time, these new samples are increasingly more inefficient because $\rho_{\max}(k)$ increases with k.

Remark 4 (Picking the size of the hypothesis space). The first and second terms characterize synergies and competition between tasks and balancing them is the key to good performance on a given task. Increasing the size of the hypothesis space reduces the first term since it allows a single hypothesis to more easily agree on two distinct distributions P_i and P_j. However, this comes at the cost of increasing the second term which grows with the size of the hypothesis space.

Remark 5 (The set of synergistic tasks can be different for different tasks). The right hand side in (10) is minimized for a choice of k (where $1 \leq k \leq n$) that balances the first and second terms. The optimal k can vary with the task, e.g., for generic tasks most other tasks will be synergistic and

similarly a small optimal k indicates task dissonance where the particular task, say P_1 should be trained on with a specific set of other tasks. Even for typical datasets like CIFAR-100, it is highly nontrivial to understand the ideal set of tasks to train with; Fig. A1 studies this experimentally.

Remark 6 (Continual learning is particularly challenging due to task competition). Theorem 3 indicates that not only is the learner shown tasks sequentially, but it also may have to work against the competition between the current task and the representation learned on a past task. It does not have access to synergistic tasks from the future while learning on the current task. And further, in settings where there is no data replay, the learner cannot benefit from past synergistic tasks explicitly, other than the representation that it has already learnt. This suggests that one must be even more careful about how the representation in continual learning should be updated.

Figure A1: Competition between tasks in continual learning can be non-trivial. In order to demonstrate how some tasks help and some tasks hurt each other, we run a multi-task learner for a varying number of tasks (X-axis) and track the accuracy on a few tasks from CIFAR100 (each task is a superclass). Each cell represents a different experiment, i.e, there is no continual learning being performed here. Cells are colored warm if accuracy is worse than the median accuracy of that row. For instance, multi-task training with 11 tasks is beneficial for "Man-made Outdoor" but accuracy drops drastically upon introducing task #12, it improves upon introducing #14, while task #17 again leads to a drop. One may study the other rows to reach a similar conclusion: there is non-trivial competition between tasks, even in commonly used datasets. As we show, tackling this effectively is the key to obtaining good performance on multi-task learning problems. See Appendix B.1 for a more elaborate version.

B Empirical Validation

B.1 Setup

Datasets. * We evaluate on Rotated-MNIST (Lopez-Paz and Ranzato, 2017), Split-MNIST (Zenke et al., 2017), Permuted-MNIST (Kirkpatrick et al., 2017), Split-CIFAR10 (Zenke et al., 2017), Split-CIFAR100 (Zenke et al., 2017), Coarse-CIFAR100 (Rosenbaum et al., 2017) and Split-miniImagenet (Vinyals et al., 2016; Chaudhry et al., 2019b). Split-MNIST, Split-CIFAR10, Split-CIFAR100 and Split-miniImagenet use consecutive groups of labels (2, 2, 5 and 10, respectively) to form tasks. Coarse-CIFAR100 is a variant of CIFAR100 where each super-class is considered a different task; this dataset has not been used for benchmarking in continual learning prior to our work. Our study in Fig. A1 has found that Coarse-CIFAR100 is a difficult dataset for continual learning, perhaps because of the semantic differences among the different super-classes.

Neural architectures and training methodology. We use a small wide-residual network of Zagoruyko and Komodakis (2016) (WRN-16-4 with 3.6M weights) with task-specific classifiers (one fully-connected layer). We also use an even smaller network (0.12M weights) with 3 convolution layers (kernel size 3 and 80 filters) interleaved with max-pooling, ReLU, batch-norm layers, with task-specific classifier layers. Stochastic gradient descent (SGD) with Nesterov's momentum and cosine-annealed learning rate is used to train all models in mixed precision. Ray Tune (Liaw et al., 2018) was used for hyper-parameter tuning using a multi-task learning model on all tasks from Coarse CIFAR-100. When we do full replay, Model Zoo samples $b = \min(k, 5)$ tasks at the k^{th} episode; for problems with $n = 5$ tasks, we set $b = 2$; note that $b = 1$ indicates no data replay. **All hyper-parameters are kept fixed for all datasets and all experiments (see Appendix B.2).**

See Appendix A for more details.

---

* Some works (Rebuffi et al., 2017a; Lopez-Paz and Ranzato, 2017; Chaudhry et al., 2019a; Mirzadeh et al., 2020b) evaluate on a split of the CIFAR100 dataset where each task is random subset of 5 classes. We do not evaluate on this variant because it is difficult to exactly reproduce the composition of tasks; as Fig. A1 suggests different compositions can have vastly different task accuracy. This is also highlighted by large differences in the accuracy on Split-CIFAR100 and Coarse-CIFAR100 in our work.

B.2   Evaluating continual learning methods

There is a wide variety of problem formulations in the continual learning literature (Farquhar and Gal, 2019; Prabhu et al., 2020; Vogelstein et al., 2020; Lopez-Paz and Ranzato, 2017; Van de Ven and Tolias, 2019). Formulations vary with respect to whether they allow replaying data from past tasks, the number of epochs the learner is allowed to train each task for, and the capacity of the model being fitted. We next explain these different formulations, the rationale behind them, and how we execute Model Zoo to conform to each of these settings.

(i) The **strict formulation**, e.g., Kirkpatrick et al. (2017); Kaushik et al. (2021), does not allow any replay of data. For the strict formulation of Model Zoo, we simply set $\bar{w}_{k,i} = 0$ for all $i \neq k$ in (4). At each episode, a single model is trained on the current task and added to the zoo—we call this rather simplistic learner **Isolated**. From a practical standpoint, such a formulation imposes a constraint on the amount of computational resources (compute and/or memory) available during training.[†]

(ii) One can **replay data to various degrees**, e.g., all of it (Nguyen et al., 2017; Guo et al., 2020b), or a subset of it (Chaudhry et al., 2019a). Just like AdaBoost, Model Zoo is fundamentally designed to allow full replay of past tasks. However, we can easily execute it with limited replay by only using a subset of the data to compute gradient updates and the accuracy on past tasks in (3) in episode k^{th}. We use the nomenclature **Model Zoo (10% replay)** to indicate that only 10% of the data from past tasks is used; algorithms like A-GEM (Chaudhry et al., 2019a) also use 10% of past data on CIFAR100 datasets. Note that Model Zoo without any data replay is simply Isolated. Let us emphasize that across all these problem settings, Model Zoo remains a legitimate continual learner because it gets access to each task sequentially and has a fixed computational budget (b tasks) at each episode. For a multi-task learner, the computational complexity scales with the number of tasks.

(iii) To impose a strict constraint on the computational complexity of each episode some works, e.g., Chaudhry et al. (2019a), train each task for a single epoch. We therefore show results using both **Model Zoo (single epoch)** (where we replay past data for 1 epoch) and **Isolated (single epoch)** (no replay). Even if the rationale behind using each datum only once is well-taken, one single epoch is quite insufficient to train modern deep networks; if one thinks of biological considerations, local-descent algorithms like stochastic gradient descent (SGD) are quite different from recurrent circuits in the biological brain (Kietzmann et al., 2019). We also run single epoch methods using a very small model (0.12M weights); these are **Model Zoo/Isolated-small (single epoch)**.

(iv) **Multi-Head** trains one single model on all tasks to minimize the average empirical risk with task-specific classifiers; mini-batches contain samples from different tasks. Since Multi-Head is trained on all tasks together, it is not a continual learner, but its accuracy is expected to be an upper bound on the accuracy of continual learning methods.

Evaluation criteria. We compare algorithms in terms of the validation accuracy averaged across all tasks at the end of all episodes, average per-task forward transfer (accuracy on a new task when it is first seen, larger this number more the forward transfer), average per-task forgetting (gap in the maximal accuracy of a task during continual learning and its accuracy at the end, larger this number more the forgetting and worse the backward transfer), training and inference time, and memory. Let us note that forward transfer is also sometimes called "learning accuracy" (Lopez-Paz and Ranzato, 2017), and another measure of backward transfer is the gap between the accuracy at the end of training and the initial accuracy of the task.

B.3   Results

Table A1 shows the validation accuracy of different continual learning methods on standard benchmark problems. There are many striking observations here.

(i) **Accuracy of all existing methods** in Table A1, regardless of their specific setting, **is much poorer than Isolated** (more than 10% for both the small and standard versions). This is surprising because Isolated can be thought of as the simplest possible continual learner—one that unfreezes new capacity at each episode and does not replay data. This indicates that existing methods may be failing to achieve forward or backward transfer compared to simply training the task in isolation; Table A2 investigates this further.

(ii) In comparison, **Model Zoo** (**all three variants**: small, small with 10% data replay and the standard method) **has dramatically better accuracy (more than 10% better than existing**

[†] There is an additional restriction in the strict setting, namely no task-specific classifiers. But even a simple permutation of classes of the same task will make continual learning impossible in this case; this is also argued in Chaudhry et al. (2019a). Further, identifying task-specific weights is very expensive at inference time (RMN in Table A2). Therefore, like most existing works, we use task-specific classifiers and assume that the task identity is known at test time.

Method	Rotated-MNIST	Permuted-MNIST	Split-MNIST	Split-CIFAR10	Split-CIFAR100	Coarse-CIFAR100	Split-miniImagenet
EWC (Kirkpatrick et al., 2017)	•84	•96.9	-	-	•42.40	-	46.69
GEM (Lopez-Paz and Ranzato, 2017)	86.07	82.60	-	-	*67.8	-	51.86
RWalk (Chaudhry et al., 2018) †	-	•93.5	99.3	-	*·•40.9	-	-
A-GEM (Chaudhry et al., 2019a) †	-	89.1	-	-	*62.3	-	61.13
Stable-SGD (Mirzadeh et al., 2020b) †	70.8	80.1	-	-	*59.9	-	57.79
ER-Reservoir (Chaudhry et al., 2019b) †	-	79.8	-	-	*68.5	-	64.03
MEGA-II (Guo et al., 2020a)	-	91.20	-	-	66.12	-	-
RMN (Kaushik et al., 2021) (strict)	-	97.73	99.5	-	80.01	-	-
Our methods							
Isolated-small	-	-	-	96.88	90.18	69.07	82.48
Model Zoo-small	-	-	-	96.85	92.06	73.72	94.27
Model Zoo-small (10% replay)	-	-	-	96.58	89.76	77.18	84.6
Isolated	99.64	98.03	99.98	97.46	91.90	80.72	86.28
Model Zoo	99.66	97.71	99.97	98.68	94.99	84.27	96.84
Multi-Head (multi-task)	99.66	98.16	99.98	98.11	95.38	83.19	90.83

Table A1: Average per-task accuracy (%) at the end of all episodes. MNIST, Permuted-MNIST and Rotated-MNIST are not informative benchmarks for judging forward and backward transfer because even Isolated achieves 99%+ accuracy. Model Zoo outperforms, by significant margins, all existing continual learning methods on all datasets. Accuracy of existing methods is worse than Isolated which suggests little to no forward or backward transfer. Model Zoo-small and Isolated-have comparable number of weights as that of existing methods, and in some cases, much fewer. For single-epoch numbers refer to Fig. 1 and Table A2. **Note:** * indicates that the evaluation was on Split-CIFAR100 with each task containing randomly sampled labels and is hence it is not directly comparable to other methods. † train for 1 epoch per episode. * denotes that accuracy is reported from other publications, e.g., (Nguyen et al., 2017; Serra et al., 2018; Chaudhry et al., 2019a).

methods) both compared to existing methods as well as compared to Isolated. This shows the utility of splitting the capacity of the learner across multiple tasks.

(iii) **Model Zoo matches the accuracy of the multi-task learner** in the last row of Table A1 which has access to all tasks beforehand. Surprisingly, **Model Zoo performs better than Multi-Head in spite of being trained in continual fashion**, especially on harder problems like Coarse-CIFAR100 and Split-miniImagenet. This is a direct demonstration of the effectiveness of Model Zoo in mitigating task competition: the capacity splitting mechanism not only avoids catastrophic forgetting, but it can also leverage data from other tasks even if they are shown sequentially.

Table A2 shows a comparison of the methods developed in this paper with existing methods on Split-CIFAR100 in terms of continual-learning specific metrics. We find:

(i) There are no significant differences in the forward transfer performance in the single epoch setting; larger variants of Isolated and Model Zoo do not work well here because a **single epoch is not sufficient to train modern deep networks**. But **Model Zoo and variants show dramatically less forgetting**, it is essentially zero. This indicates that although existing methods are designed to avoid forgetting (the single epoch setting aids this directly), say, A-GEM, or EWC, they do forget. Forgetting can be mitigated by the capacity splitting mechanism in Model Zoo. The per-task accuracy of existing methods is also rather low compared to Model Zoo variants.

(ii) If our methods are implemented in the **multi-epoch setting**, then the **forward transfer** is exceptionally good and **almost as good as the average accuracy** of the task. Surprisingly, this does not come at the cost of **forgetting, which is again essentially zero**.

(iii) Even if Model Zoo and its variants are implemented with **very small models** (0.12M weights/episode, which is 2.42M weights/20 episodes), the **accuracy is dramatically better** (Table A1). This suggests that Model Zoo is a performant and viable approach to continual learning. In fact, even the larger model used in Model Zoo is a WRN-16-4 with 3.6M weights and therefore we can train multiple models on the same GPU easily; this is why the training time of Model Zoo is about the same as that of Model Zoo-small.

(iv) The simplicity of Model Zoo and its variants results in much smaller training times and comparable inference times as compared to existing methods.

A Details of the experimental setup

A.1 Datasets

We performed experiments using the following datasets.

1. Rotated-MNIST (Lopez-Paz and Ranzato, 2017) uses the MNIST dataset to generate 5 different 10-way classification tasks. Each task involves using the entire MNIST dataset rotated by 0, 10, 20, 30, and 40 degrees, respectively.

2. Permuted-MNIST (Kirkpatrick et al., 2017) involves 5 different 10-way classification tasks with each task being a different permutation of the input pixels. The first task is the original

Method	Inference time (ms/sample)	Training time (min)	Storage Samples (%)	#Weights (M)	Metrics (Multi Epoch) Accuracy (%)	Forgetting (%)	Forward (%)	Metrics (Single Epoch) Accuracy (%)	Forgetting (%)	Forward (%)
EWC	10.34	50	0	1.6	-	-	-	42.4	17.52	67.76
Prog-NN	-	82	0	23.7	-	-	-	59.2	0.0	59.2
GEM	10.34	1048	5–10	1.6	-	-	-	61.2	6.0	67.61
A-GEM	10.34	88	5–10	1.6	-	-	-	62.3	7.0	70.13
RMN	2712.4	-	0	11.5	80.01	-	-	-	-	-
Our methods										
Isolated-small	2.34	17.09	0	2.42	90.18	0.0	91.18	71.6	0.0	71.6
Model Zoo-small	11.70	31.71	100	2.42	92.28	0.17	90.0	73.67	0.20	71.91
Model Zoo-small (10% replay)	11.70	22.41	10	2.42	89.76	0.22	89.8	71.09	0.69	70.5
Isolated	2.34	20.76	0	54.8	91.9	0.0	91.0	50.43	0.0	50.43
Model Zoo	31.84	41.86	100	54.8	94.99	0.21	94.02	57.67	0.81	56.58

Table A2: A comparison of **continual learning evaluation metrics on Split-CIFAR100** for existing methods and the methods developed in this paper. Our methods demonstrate strong forward and backward transfer, high per-task accuracy, smaller training times and comparable inference times. Training times of other methods are from Chaudhry et al. (2019a) and it is the total training time in minutes for all tasks. The Inference time is the per sample prediction latency averaged over 50 mini-batches of size 16.

Replay (%)	Split-CIFAR100	Split-miniImagenet
0	71.91	65.80
1	70.48	67.18
5	71.33	70.71
10	71.97	74.22
100	73.67	81.05

# Tasks (β) (100% replay)	Split-CIFAR100	Split-miniImagenet
1	71.91	65.02
2	72.26	67.33
5	73.67	81.05
7	73.97	88.76
9	74.13	84.9

Method	Model Zoo	Ensemble of Isolated (100×)
Split-CIFAR100	73.67	71.46
Split-miniImagenet	81.05	67.26

Figure A2: Ablation studies that show the average per-task accuracy as we vary the size of data replay for Model Zoo (left), the number of past tasks sampled at each episode (middle, $\beta = 1$ implies no replay), and compare Model Zoo with an ensemble of Isolated models (right). These results are for the single-epoch setting and are therefore directly comparable to those in Table A2 and Table A1 as far as comparison to other methods is concerned. Accuracy is roughly the same on Split-CIFAR100 across varying degrees of replay while it improves significantly on Split-miniImagenet; this suggests that Model Zoo also works with very small amounts of data replay. Accuracy on Split-CIFAR100 is consistent as the number of replay tasks is changed but increases dramatically on larger datasets like Split-miniImagenet where there are many more tasks. Finally, the performance of Model Zoo is not merely an artifact of ensembling. Even if Isolated is a strong model, a very large ensemble of Isolated compares poorly to Model Zoo with 100% replay; this indicates that Model Zoo can effectively leverage data from past tasks without forgetting. Se the Appendix for more ablation studies.

MNIST task as is convention. All other tasks are distinct random permutations of MNIST images.

3. Split-MNIST (Zenke et al., 2017) has 5 tasks with each task consisting of 2 consecutive labels (0-1, 2-3, 4-5, 6-7, 8-9) of MNIST.

4. Split-CIFAR10 (Zenke et al., 2017) has 5 tasks with each task consisting of 2 consecutive labels (airplane-automobile, bird-cat, deer-dog, frog-horse, ship-truck) of CIFAR10.

5. Split-CIFAR100 (Zenke et al., 2017) has 20 tasks with each task consisting of 5 consecutive labels of CIFAR100. See the original paper for the exact constitution of each task.

6. Coarse-CIFAR100 (Rosenbaum et al., 2017) has 20 tasks with each task consisting of 5 labels. The tasks are based on an existing categorization of classes into super-classes (https://www.cs.toronto.edu/ kriz/cifar.html).

7. Split-miniImagenet (Vinyals et al., 2016) is a ariant introduced in Chaudhry et al. (2019b), consisting of 20 tasks, with each task consisting of 10 consecutive labels. We merge the meta-train and meta-test categories to obtain a continual learning problem with 20 tasks. Each task containing 10 consecutive labels and 20% of the samples are used as the validation set.

The CIFAR10 and CIFAR100-based datasets consist of RGB images of size 32×32 while MNIST-based datasets consist of images of size 28×28. The Mini-imagenet dataset consists of RGB images of size 84×84.

A.2 Architecture

We use the Wide-Resnet (Zagoruyko and Komodakis, 2016) architecture for some of our experiments. The final pooling layer is replaced with an adaptive pooling layer in order to handle input images of different sizes. Convolutional layers are initialized using the Kaiming-Normal initialization. The bias parameter in batch normalization is set to zero with the affine scaling term set to one. The bias of the

final classification layer is also set to zero; this helps keep the logits of the different tasks on a similar scale.

To ensure that the number of weights is similar to those in other methods, we also consider a smaller convolution neural network consisting of 3 convolution layers, with batch-normalization, ReLU and max-pooling present between each layer.

A.3 Training setup

Optimization. All models are trained in mixed-precision (32-bit weights, 16-bit gradients) using Stochastic Gradient Descent (SGD) with Nesterov's acceleration with momentum coefficient set to 0.9 and cosine annealing of the learning rate schedule for 200 epochs. Training of any model with multiple tasks involves mini-batches that contain samples from all tasks.

Hyper-parameter optimization. We used Ray Tune (Liaw et al., 2018) for hyper-parameter optimization. The Async Successive Halving Algorithm (ASHA) scheduler (Li et al., 2018) was used to prune hyper-parameter choices with the search space determined by Nevergrad (Rapin and Teytaud, 2018). The mini-batch size was varied over [8, 16, 32, 64]; the logarithm (base 10) of the learning rate was sampled from a uniform distribution on $[-4, -2]$; dropout probability was sampled from a uniform distribution on $[0.1, 0.5]$; logarithm of the weight decay coefficient was sampled from $[-6, -2]$. We used a set of experiments for continual learning on the Coarse-CIFAR100 dataset with different samples/class (100 and 500) to perform hyper-parameter tuning.

The final values of traing hyper-parameters that were chosen are, learning-rate of 0.01, mini-batch size of 16, dropout probability of 0.2 and weight-decay of 10^{-5}.

Model Zoo uses $b = \min(k, 5)$ at each round of continual learning where n is the number of tasks; for tasks with only 5 tasks (MNIST-variants) we use $b = 2$. We did not tune these two hyper-parameters using Ray because it is quite cumbersome to do so. We selected these values manually across a few experiments; changing them may result in improved accuracy for Model Zoo.

All hyper-parameters are kept fixed for all datasets, architectures, and experimental settings. . We are interested in characterizing the performance of Model Zoo and its variants across a broad spectrum of problems and datasets. While we believe we can get even better numerical accuracy, by tuning hyper-parameters specially for each problem, we do not so for the sake of simplicity. As the main paper discusses, we outperform existing methods quite convincingly across the board in both multi-task and continual learning.

Data augmentation. MNIST and CIFAR10/100 datasets use padding (4 pixels) with random cropping to an image of size 28×28 or 32×32 respectively for data augmentation. CIFAR10/100 images additionally have random left/right flips for data augmentation. Images are finally normalized to have mean 0.5 and standard deviation 0.25. Split-miniImagenet uses the same augmentation as CIFAR-10 and CIFAR-100. We use augmentation even in the single epoch setting.

B Additional Experiments

B.1 Understanding task competition

To understand which tasks aid each other's learning and which compete for capacity and may thereby deteriorate performance, we investigated the Coarse-CIFAR100 dataset extensively. We first computed the pairwise task competition by comparing the relative gain/drop in classification accuracy of each pair of tasks when the row task is trained in isolated versus training the row and column tasks together using a simple multi-task learner (Multi-Head). Fig. A1 discusses the results.

Fig. A2, is the extended version of Fig. A1. It shows the validation accuracy of each task (along a single row) as more tasks are added to Multi-Head. Each column is a single Multi-Head model trained on a subset of tasks from scratch. As more tasks are added, the accuracy of most tasks increases. However, the increase is not monotonic with each added task, and if one follows a particular row, there are non-trivial patterns wherein adding a particular task may deteriorate the performance on the row task and adding some other task later may recover the lost accuracy. This is a direct demonstration of the tussle between the task competition term (first) and the concentration term (third) in Theorem 3. This indicates that training on the appropriate set of tasks is crucial to learn from multiple tasks.

B.2 Competition between tasks of typical benchmark datasets

Next, we investigated such task competition on other continual learning datasets, namely, Permuted-MNIST, Rot-MNIST, Split-CIFAR10, and Split-MNIST. It is clear from Fig. A3 that there is very little competition in this case. Either the tasks are quite different from each other (like the case of Permuted-MNIST), or they are synergistic (most cells are green), or they do not hurt each other's performance, i.e., they may correspond to the model in Appendix A.2. Note that Rotated-MNIST

Figure A1: Pairwise task competition matrix. Cells are colored by the gain(green)/loss(warm) of accuracy of pairwise Multi-Head training as compared to training the row-task in isolation; this is a good proxy for the transfer coefficient ρ_{ij} in (9). Although most pairs benefit each other (green), certain tasks, e.g., "Food Container" are best trained in isolation while others such as "Aquatic Mammals" are typically detrimental to most other tasks. One can study this matrix and identify many more such properties. In summary, whether tasks aid or hurt each other is quite nuanced even for CIFAR100.

exactly corresponds to the multi-view setting discussed in Appendix A.2 were different input images are simple transformations of each other.

B.3 Visualizing successive iterations of Model Zoo

In order to understand how the accuracy of Model Zoo evolves on all tasks as a function of the episodes, we created Fig. A4. This is a very insightful picture and we can draw the following conclusions from it.

  (i) The accuracy along the diagonal of most tasks increases along the row, i.e., across episodes. Only for a few tasks like Food Container the accuracy drops in later episodes. Note that we also see from Fig. A1 that Food Container is a task that is best trained in isolation because it leads to deterioration of accuracy when trained with essentially any other task.
 (ii) The is strong backward transfer throughout the dataset, i.e., the accuracy of a task shown in earlier rounds increases, sometimes dramatically, as later synergistic tasks are shown to the learner.
(iii) We also see strong forward transfer. Roughly speaking, in the second half of the rows, the initial accuracy of most tasks does not improve much with successive episodes. This suggests that these tasks already have a good initial accuracy, i.e., there is good forward transfer in the learner.

We advocate that such plots should be made for different continual learning algorithms to obtain a precise picture of the amount of forward and backward transfer.

Figure A2: In order to demonstrate how some tasks help and some tasks hurt each other, we run Multi-Head for a varying number of tasks (X-axis) and track the accuracy on a few tasks from Coarse-CIFAR100. The order of tasks is the same for rows (top to bottom) and the columns (left to right). In other words, the first cell (the diagonal) indicates the accuracy of the task trained by itself in isolation (Isolated). Cells are colored warm if accuracy is worse than the median accuracy of that row. For instance, multi-task training with 11 tasks is beneficial for "Man-made Outdoor" but accuracy drops drastically upon introducing task #12, it improves upon introducing #14, while task #17 again leads to a drop. One may study the other rows to reach a similar conclusion: there is non-trivial competition between tasks, even in commonly used datasets. Tackling this issue effectively is the key to obtaining good performance on multi-task learning problems

542   **B.4   Baseline performance of isolated training on Coarse-CIFAR100**

Figure A3: Each row is the relative increase/decrease (green/red) in accuracy of a two task Multi-Head learner compared to Isolated trained on the task corresponding to the particular row; all entries are computed using 100 samples/class. Cells are colored green for accuracy gained, and warm for accuracy dropped; the entries in this matrix are a good proxy for the transfer coefficient ρ_{ij} in (9). A similar plot for Coarse-CIFAR100 tasks is shown in the right panel of Fig. A1. Split-CIFAR10 and Split-MNIST indicate that most tasks mutually benefit each other. This is also true, but to a lesser extent, for Rotated-MNIST. Permuted-MNIST is a qualitatively different problem than these, perhaps because there is no obvious relationship between the tasks and there exist some tasks that lead to a large deterioration of accuracy.

B.5 Additional experiments

Table A1 is a more detailed version of Table A1 in the main paper.

B.6 Single Epoch Metrics

We obtain metrics from publicly available implementations of a few different continual learning algorithms, which are shown in Tables A2 and A3. We see that Model Zoo and its variants uniformly have essentially no forgetting and good forward transfer. The average per-task accuracy is also dramatically higher than existing methods on these datasets. These tables show results for single-epoch training (to be consistent with the implementation of these existing methods).

B.7 Tracking Individual Task Accuracies

We next study how the individual per-task accuracy evolves on different datasets. The following figures are extended versions of the right panel of Fig. 1. We see that the accuracy of all tasks increases with successive episodes. This is quite uncommon for continual learning methods and indicates that Model Zoo essentially does not suffer from catastrophic forgetting. We have also juxtaposed the corresponding curves of the single-epoch setting with the multi-epoch training in Model Zoo; we would like to demonstrate the dramatic gap in the accuracy of these problem settings. Even if single-epoch variant of Model Zoo also does not forget (its accuracy is much better than existing continual learning methods), the multi-epoch variant has much higher accuracy for every task. This indicates that continual learning algorithms should also focus on per-task accuracy in addition to mitigating forgetting, if they are to be performant. The performance of Model Zoo is evidence that we can build effective continual learning methods that do not forget.

Figure A4: The iterations of Model Zoo are visualized for the Split-miniImagenet dataset for 20 rounds, with 5 tasks selected in every iteration of Model Zoo. Red elements are tasks that were selected by boosting in that particular round. We observe that the accuracy of most tasks improves over the rounds, which indicates the utility of Model Zoo-like training scheme This plot also indicates that Model Zoo can improve the per-task accuracy on nearly all tasks. The model is trained for only a single-epch per boosting round.

Figure A6: Evolution of task accuracy on Coarse-CIFAR100

Method	Rot-MNIST	Permuted-MNIST	Split-MNIST	Split-CIFAR10	Split-CIFAR100	Coarse-CIFAR100	Split-miniImagenet
Prog-Nets Rusu et al. (2016)	-	•93.5	-	-	•59.2	-	
iCARL Rebuffi et al. (2017b)	-	-	-	-	61.2*	-	
EWC (strict) Kirkpatrick et al. (2017)	•84	•96.9	-	-	•42.40	-	
SI (strict) Zenke et al. (2017)	-	•97.1	•98.9	-	-	-	
GEM Lopez-Paz and Ranzato (2017)	86.07	82.60	-	-	67.8*	-	
RWalk Chaudhry et al. (2018) [†]	-	•93.5	99.3	-	•40.9*	-	
HATSerra et al. (2018)	-	98.6	99.0	-	-	-	
A-GEM Chaudhry et al. (2019a) [†]	-	89.1	-	-	62.3*	-	
VCL Nguyen et al. (2017)	-	95.5	98.4	-	-	-	
Stable-SGD Mirzadeh et al. (2020b) [†]	70.8	80.1	-	-	59.9*	-	
ER-Reservoir Chaudhry et al. (2019b) [†]	-	79.8	-	-	68.5*	-	
OGD Farajtabar et al. (2020)	88.32	86.44	98.84	-	-	-	
MC-SGD Mirzadeh et al. (2020a) [†]	82.63	85.3	-	-	63.30	-	
TAG Malviya et al. (2021) [†]	-	-	-	-	62.79	-	57.2
FRCL Titsias et al. (2020)	-	94.3	97.8	-	-	-	
FROMP Pan et al. (2020)	-	94.9	99.0	-	-	-	
MEGA-II Guo et al. (2020a)	-	91.20	-	-	66.12	-	
RMN (strict) Kaushik et al. (2021)	-	97.73	99.5	-	80.01	-	
Our methods							
Isolated-small	-	-	-	96.88	90.18	69.07	82.48
Model Zoo-small	-	-	-	96.85	92.06	73.72	94.27
Model Zoo-small (10% replay)	-	-	-	96.58	89.76	77.18	84.6
Isolated	99.64	98.03	99.98	97.46	91.90	80.72	86.28
Model Zoo	99.66	97.71	99.97	98.68	94.99	84.27	96.84
Multi-Head (multi-task)	99.66	98.16	99.98	98.11	95.38	83.19	90.83

Table A1: Average per-task accuracy (%) for continual learning at the end of all episodes. MNIST, Permuted-MNIST and Rotated-MNIST are not informative benchmarks for judging forward and backward transfer because even Isolated achieves 99%+ accuracies. Model Zoo outperforms, by significant margins, all existing continual learning methods; in fact their accuracy is worse than Isolated which suggests little to no forward or backward transfer. **Note:** * indicates that the evaluation was on Split-CIFAR100 with each task containing randomly sampled labels and is hence not directly comparable to other methods. [†] train for 1–5 epochs per episode presumably to avoid forgetting, but this is rather insufficient to learn good features for RGB data. • indicates that these results were reported using the publications of Chaudhry et al. (2019a); Nguyen et al. (2017); Serra et al. (2018).

Method	Avg. Accuracy	Forgetting	Forward
SGD	34.52	19.88	53.30
EWC	34.71	18.60	52.19
AGEM	37.23	16.96	52.72
ER	41.36	14.29	54.87
Stable-SGD	37.27	12.07	48.43
TAG	43.33	12.39	55.1
Isolated-small	58.719	0.0	58.71
Model Zoo-small	60.3	0.370	59.13
Isolated-large	41.28	0.0	41.28
Model Zoo-large	46.98	0.38	44.43

Table A2: Single Epoch continual learning metrics on Coarse-CIFAR100

Individual Task Accuracies on Split-CIFAR100

Method	Avg. Accuracy	Forgetting	Forward
SGD	46.69	16.653	62.35
EWC	47.93	14.26	61.34
AGEM	51.86	10.102	61.13
ER	55.41	9.52	64.03
Stable-SGD	49.28	9.76	57.79
TAG	58.38	5.15	63.00
Isolated-small	65.8	0.0	65.8
Model Zoo-small	81.049	1.278	66.57
Isolated-large	40.2	0.0	40.25
Model Zoo-large	64.12	0.27	48.34

Table A3: Single Epoch continual learning metrics on Split-MinImagenet

Figure A8: Evolution of task accuracy on Split-miniImagenet

B.8   Comparison To Existing Methods

Figure A9: This figure compares Model Zoo to existing continual learning methods on the Coarse-CIFAR100 and Split-CIFAR100 datasets with respect to average task accuracy. Model Zoo and its variants are in bold, similar to the left panel of Fig. 1 (which is for Split-miniImagenet). Isolated-small and Model Zoo-small significantly outperform existing methods. All methods in the figure are run in the single-epoch setting.

B.9   Additional Continual Learning Experiments on 100 samples/label

We also performed continual learning experiments with 100 samples/class in Table A4. We find that Model Zoo-continual obtains an accuracy that lies in between those of Isolated and the approximate upper bound given by Multi-Head (multi-task learning). Note that we have shown that matching or improving upon the performance of Isolated (which trains a model independently for each task) for continual learning is quite difficult because it necessitates effective forward-backward transfer. Doing so indicates strong ability of the learner for *both* forward and backward transfer. In some cases, the continual learner even outperforms Multi-Head trained on all tasks together. This table indicates that Model Zoo can be used as a continual learning and demonstrate nontrivial forward and backward transfer even with few samples from each class.

Dataset	Isolated	Multi-Head (multi-task)	Model Zoo-Continual
Rotated-MNIST	98.17 ± 0.24	98.47 ± 0.18	98.44 ± 0.17
Split-MNIST	97.11 ± 1.21	99.47 ± 0.08	98.98 ± 0.51
Permuted-MNIST	84.59 ± 1.65	86.36 ± 1.15	86.04 ± 1.68
Split-CIFAR10	82.09 ± 0.76	85.73 ± 0.60	84.17 ± 0.60
Split-CIFAR100	80.04 ± 0.44	87.93 ± 0.50	86.27 ± 0.19
Coarse-CIFAR100	65.34 ± 0.41	69.05 ± 0.38	66.80 ± 6.27

Table A4: Average per-task accuracy (%) for continual learning at the end of all episodes using 100 samples/class, bootstrapped across 5 datasets (mean $\pm$ std. dev.). Model Zoo-continual performs better than Isolated on all problems even if tasks are shown sequentially.

We next visualize the evolution of the per-task test accuracy for various datasets. This is a qualitative way to investigate forward and backward transfer in the learner. Forward transfer is positive if the accuracy of a newly introduced task in a particular episode is higher than what it would be if the task were trained in isolation. Backward transfer is positive if successive episodes and tasks result in an increase in the accuracy of tasks that were introduced earlier in continual learning. Both Appendix B.7 and Fig. A10 consistently show non-trivial forward and backward transfer.

Figure A10: Per-task validation accuracy as a function of the number of episodes of continual learning for problems using variants of CIFAR10 and MNIST datasets using Model Zoo-continual. Each task has 100 samples/class. X-markers denote accuracy of Isolated on the new task. We see both forward transfer (Model Zoo often starts with a higher accuracy than Isolated) and backward transfer (accuracy of some past tasks improves in later episodes). For problems like Permuted-MNIST and Rotated-MNIST, there is little forward or backward transfer.

C Proofs

Proof of Theorem 3. From the definition of ρ_{ij} relatedness for tasks, we have

$$c\, \mathcal{E}_{P_i}^{1/\rho_{i1}}(h) \geq \mathcal{E}_{P_1}(h, h_i^*)$$
$$= \mathcal{E}_{P_1}(h) - \mathcal{E}_{P_1}(h_i^*, h_1^*).$$

for any $i, j \leq n$ and $h \in H$. Let us denote $\rho_{(i)} = \rho_{i1}$. We can sum over $i \in \{1, \dots, k\}$ and divide by k to get

$$\mathcal{E}_{P_1}(h) \leq \frac{1}{k}\sum_{i=1}^{k} \mathcal{E}_{P_1}(h_{(i)}^*) + \frac{c}{k}\sum_{i=1}^{k}\mathcal{E}_{P_{(i)}}^{1/\rho_{(i)}}(h).$$

The first term is a discrepancy term that measures how distinct different tasks are as measured by the probability of the disagreement of their individual hypotheses $h_{(i)}^*$ with that of h_1^* under samples drawn from task P_1. We need to bound the second term on the right-hand side to prove Theorem 3. We have

$$\frac{1}{k}\sum_{i=1}^{k}\mathcal{E}_{P_{(i)}}^{1/\rho_{(i)}}(h) \leq \frac{1}{k}\sum_{i=1}^{k}\mathcal{E}_{P_{(i)}}^{1/\rho_{\max}}(h)$$
$$= \frac{1}{k}\sum_{i=1}^{k}\left(e_{P_i}(h) - e_{P_i}(h_i^*)\right)^{1/\rho_{\max}}$$
$$\leq \frac{1}{k}\sum_{i=1}^{k}e_{P_i}^{1/\rho_{\max}}(h) \leq e_{\bar{P}}^{1/\rho_{\max}}(h).$$

where the final step involves Jensen's inequality and $\bar{P} = 1/k \sum_{i=1}^{k} P_{(i)}$. This is the population risk of a hypothesis h on the mixture distribution $\bar{P}$ and by uniform convergence, we can bound it as

$$e_{\bar{P}}^{1/\rho_{\max}}(h) \leq \left(e_{\bar{S}}(h) + c' \left(\frac{D - \log \delta}{km} \right)^{1/2} \right)^{1/\rho_{\max}}$$

for any $h \in H$, in particular $\hat{h}^k$, with probability $1 - \delta$. Putting it all together we have:

$$\mathcal{E}_{P_1}(h) \leq \frac{1}{k} \sum_{i=1}^{k} \mathcal{E}_{P_1}(h_{(i)}^*) + \frac{c}{k} \sum_{i=1}^{k} \mathcal{E}_{P_{(i)}}^{1/\rho_{(i)}}(h)$$

$$\leq \frac{1}{k} \sum_{i=1}^{k} \mathcal{E}_{P_1}(h_{(i)}^*) + \frac{c}{k} \left(e_{\bar{S}}(h) + c' \left(\frac{D - \log \delta}{km} \right)^{1/2} \right)^{1/\rho_{\max}}$$

$\square$

D Frequently asked questions (FAQs)

1. **Why do you consider the setting with unlimited replay?**
   As mentioned in §5, we would like to ground the practice of continual learning. Our investigation is inspired by the existing work on continual learning and with this paper we seek to encourage future works to focus their investigations on key desiderata of continual learning, namely per-task accuracy and forward-backward transfer.

   With this goal, we are motivated by our results in Theorem 3 that fitting a single model on a set of tasks is fundamentally limiting in performance due to competition between tasks, this problem is only exacerbated by introducing the tasks sequentially. We have developed a general method named Model Zoo that, although designed for unlimited replay, can be executed in any of the standard continual learning settings. Our experiments show that Model Zoo significantly outperforms existing methods in all of these settings, including problem settings with no replay.

   We allow Model Zoo to revisit past data and grow its capacity iteratively in order to get to the heart of the problem of learning multiple tasks sequentially. In our view, if we can demonstrate effective continual learning without forgetting at least in this setting, it will provide a good foundation to build methods that conform to the stricter problem formulations.

   We believe that such a foundation is needed today if we are to advance the practice of continual learning. Let us explain why with an example. The simplest "baseline" algorithm named Isolated in our work, surprisingly outperforms all existing continual learning methods, without performing any data replay, or leveraging data from multiple tasks. An upper bound for performance of a continual learner is the accuracy obtained by a multi-task learner that has access to all tasks before training. We argue that a good continual learner's performance should lie in between the above two: it should be—at least–comparable to training the task in isolation, and as close to the performance of the multi-task learner as possible. The fact that existing methods perform much poorly than even Isolated indicates that we need to thoroughly investigate the tradeoffs that these methods make, e.g., while the single epoch setting helps mitigate forgetting, it has quite poor accuracy.

   In short, we would like to argue that before we design new sophisticated methods for continual learning, we should take a step back and evaluate what simple methods can do and ascertain some level of baseline performance, so that we have a sound benchmark to compare the sophisticated method against. This is our rationale for considering the problem setting with unlimited replay. **We would also like to emphasize that Model Zoo is a legitimate continual learner because it gets access to each task sequentially, and has a fixed computational budget at each episode.** For a multi-task learner, the computational complexity scales with the number of tasks.

2. **Why do you call it continual learning, instead of, say, incremental or lifelong learning?**
   The current literature is quite inconclusive about the formal distinction between continual, incremental and lifelong learning. We have chosen to call our problem "continual learning" and, by that, we simply mean that the learner gets access to tasks sequentially instead of having access to all tasks before training begins.

3. **Why are you not using the same neural architectures as those in the existing literature? Perhaps the methods in this paper work better because you use a larger/different neural architecture.**

   We use a small deep network (WRN-16-4 with 3.6M weights) for all our experiments. In particular, this is smaller than the Resnet-12 or Resnet-18 architectures that are used in a number of continual learning experiments (see Kaushik et al. (2021)) and the Model Zoo has a comparable number of weights. The exceptional performance of Model Zoo indicates that these observations indicate that the significant gains in accuracy of Model Zoo are not simply a result of using a larger model. We also demonstrate results on continual learning with a much smaller model, a CNN with 0.12M weights (which entails that Model Zoo has about 2.42M weights). This is an extremely small model, and even this model, under all problem settings, improves the accuracy of continual learning over existing methods.

4. **Why not compare Model Zoo to ensemble versions of other methods?**

   We compare the performance of Model Zoo with ensemble versions of Isolated in Fig. A2. We observe that Model Zoo performs better than an ensemble of Isolated models. We did not compare against ensemble variants of existing continual learning methods because as our results show in multiple places, Isolated significantly outperforms the state of the art as a continual learner. We therefore expect that Model Zoo will also outperform ensembles of existing methods.

5. **Boosting is not novel.**

   We do not claim any novelty in developing boosting and moreover our method is only loosely inspired by it. The key property of Model Zoo that makes it effective is the ability to split the capacity of the learner across different sets of tasks, the ones that are chosen at each round. This entails that the implementation of Model Zoo is similar to that of boosting-based algorithms such as AdaBoost, but that is the extent of the similarity between the two. In particular, Model Zoo only uses the models that were trained on a particular task in order to make predictions for it. Unlike AdaBoost which combines all the weak-learners using specific weights, we simply average the predictions of all models trained on each task. To emphasize, boosting is not novel, but the ability of Model Zoo to split learning capacity across multiple models, one from each round, trained on a set of tasks, *is* novel.

6. **Identifying that tasks compete is not novel.**

   See §5 and the references in Appendix A.1. The fact that tasks compete with each other is broadly appreciated–if not rigorously studied–in the theoretical machine learning literature. It is also appreciated broadly under the name of catastrophic forgetting in continual learning. Theorem 3 elucidates this competition and shows, together with Fig. A1, that it can be quite non-trivial. Even if some tasks compete, i.e., a hypothesis that is optimal for one performs poorly on the other, they may benefit each other if we have access to lots of samples from each task. An effective way to resolve this competition has been missing. Model Zoo is a simple and effective framework to tackle task competition; such a mechanism, and certainly its use for continual learning, is novel to our knowledge.

7. **Why does the rate of convergence in Theorem 3 depend upon $\rho_{\max}$, this seems quite inefficient.**

   The convergence rate in Theorem 3 which depends on $\rho_{\max}$ indeed seems pessimistic if one chooses a bad set of tasks to train together. But this may be a fundamental limitation of non-adaptive methods, e.g., that pool data from all tasks together to compute $\hat{h}^k$. If the learner uses adaptive methods, e.g., if it has access to ρ_{ij} and iteratively restricts the search space at iteration k to only consider hypotheses that achieve a low empirical risk $\hat{e}_{S_{(i)}}$ on all tasks closer than $\rho_{(k)}$, then as (Hanneke and Kpotufe, 2020) shows, we can get better convergence rates if all tasks have the same optimal hypothesis. Let us note that we have chosen some drastic inequalities in Appendix C in order to elucidate the main point, and it may be possible to improve upon the rate.

8. **Can you give some intuition for the transfer exponent?**

   The transfer exponent discussed in (9) is inspired by the work of Hanneke and Kpotufe (2020) and is defined by the smallest value such that

   $$c\,\mathcal{E}_{P_i}^{1/\rho_{ij}}(h) \geq \mathcal{E}_{P_j}(h, h_i^*) = \mathcal{E}_{P_j}(h) + e_{P_j}(h_j^*) - e_{P_j}(h_i^*)$$

   for all $h \in H$. This should be understood as a measure of similarity between tasks that incorporates properties of the hypothesis space. A small value of $\rho_{ij} \approx 1$ suggests that

minimizing the excess risk on task P_i (the left-hand side) is a good strategy if we want to minimize the excess risk on task P_j (the right-hand side). But there may be instances when we can only reduce the left hand-side up to an additive term

$$e_{P_j}(h_j^*) - e_{P_j}(h_i^*)$$

that may be non-zero (or large) if the optimal hypotheses h_j^* and h_i^* perform very differently on samples from P_j. Mathematically, ρ_{ij} is seen as the rate of convergence of the concentration term in Theorem 3 if samples from P_i are used to select a hypothesis for P_j; larger the transfer exponent, more inefficient these samples, even if this additive term is zero.