FR: Folded Rationalization with a Unified Encoder

Abstract

Rationalization aims to strengthen the interpretability of NLP models by extracting a subset of human-intelligible pieces of their inputting texts. Conventional works generally employ a two-phase model in which a generator selects the most important pieces, followed by a predictor that makes predictions based on the selected pieces. However, such a two-phase model may incur the degeneration problem where the predictor overfits to the noise generated by a not yet well-trained generator and in turn, leads the generator to converge to a sub-optimal model that tends to select senseless pieces. To tackle this challenge, we propose Folded Rationalization (FR) that folds the two phases of the rationale model into one from the perspective of text semantic extraction. The key idea of FR is to employ a unified encoder between the generator and predictor, based on which FR can facilitate a better predictor by access to valuable information blocked by the generator in the traditional two-phase model and thus bring a better generator. Empirically, we show that FR improves the F1 score by up to 10.3% as compared to state-of-the-art methods.

1 Introduction

There are growing concerns over the interpretability of NLP models, especially when language models are being rapidly applied on various critical fields(Lipton, 2016; Du et al., 2019; Xiang et al., 2019; Miller, 2019; Sun et al., 2021). Rationalization, using a cooperative game between a generator and a predictor in which the generator selects distinguishable and human-intelligible pieces of the inputting text (i.e., rationale) to the followed predictor that maximizes the predictive accuracy, has become one of the mainstream approaches to improve the interpretability of NLP models. The standard rationalization method named RNP (Lei et al., 2016) organizes the generator and predictor with a two-phase framework (see Figure 2(a)). However, as illustrated in Table 1, such a two-phase model suffers from the degeneration problem where the predictor may overfit to meaningless but distinguishable rationales generated by the not yet well-trained generator (Yu et al., 2019), leading the generator to converge to the sub-optimal model that tends to select these uninformative rationales.

Many approaches have been proposed to address the degeneration issue. The basic idea of these approaches is to regularize the predictor using supplementary modules that make use of the full text such that the predictor does not rely entirely on the rationale provided by the generator. For example, as shown in the Figure 2, 3PLAYER (Yu et al., 2019) adopts an extra predictor to squeeze informative parts from the unselected text pieces into the rationale; DMR (Huang et al., 2021) additionally aligns with prediction distribution and feature distribution of of the full text; A2R (Yu et al., 2021) combines binary selection with soft selection in which every token in the inputting text is partly contained.

Although these regularized methods can greatly alleviate the degeneration problem, they still maintain the two fragmented phases in which the spoiled predictor can only be partially calibrated by the extra

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Table 1: An example of RNP making the right prediction using the uninformative rationale. The underlined piece of the text is the human-annotated rationale. Pieces of the text in red and blue represent the rationales from RNP and our method respectively. Initially, the generator may randomly select some uninformative rationales such as selecting "-" for the negative text. The predictor of RNP overfits to these uninformative rationales and recognizes the category according to whether "-" is included in the rationale. Guided by such a spoiled predictor, the generator in turn tends to select these uninformative rationales.

Label(Aroma): Negative
Input text: 12 oz bottle poured into a pint glass - a - pours a transparent , pale golden color . the head is pale white with no cream , one finger 's height , and abysmal retention . i looked away for a few seconds and the head was gone s **-** stale cereal grains dominate . hardly any other notes to speak of . very mild in strength t - sharp corn/grainy notes throughout it 's entirety . watery , and has no hops characters or esters to be found. very simple (not surprisingly) m - highly carbonated and crisp on the front with a smooth finish d - yes , it is drinkable , but there are certainly better choices , even in the cheap american adjunct beer category . hell , at least drink original coors
Rationale from RNP: ["-"] **Pred:** Negative
Rationale from FR: ["stale cereal grains dominate . hardly any other notes to"] **Pred:** Negative

modules. More specifically, we identify that the predictor has notably higher learning speed than the generator under the two-phase framework, indicating that a regularized predictor will not immediately lead to a well-trained generator and has to continuously learn from generated uninformative rationales until convergence. To show this, we consider the RNP method with different learning rates for the generator and predictor. We defer the experimental details to Appendix B.2 and present the results of rationale quality (F1 score) in Figure 1. As can be seen, the results usually get better when the learning rate of the predictor is smaller than the generator. In particular, the result achieves the best when the learning rate of the predictor is approximately $1/5$ that of the generator, where the learning speed of the predictor is exceptionally limited.

Although balancing the learning speed between the generator and predictor can effectively improve the performance, tuning the learning rates involves careful coordination between the two phases and requires much human effort, especially when some existing methods are designed with more modules. To tackle this challenge, we in this work propose a frustratingly simple but effective method, Folded Rationalization (FR), which folds the two phases of the current rationalization method into one using a unified encoding mechanism. Specifically, FR shares a unified text encoder between the generator and the predictor. The predictor is enforced with the same learning speed as the generator and has significant chances of learning informative rationales from a well-trained generator. On the other hand, the generator can also get a higher learning speed with the auxiliary of the predictor. Additionally, as theoretically analyzed, the encoder of

Figure 1: The rationale quality of RNP with different learning rates for the generator and the predictor.

the generator can also be seen as a special regularizer for the predictor, which helps it get a global view of all the possible rationale candidates from the full text and thus prohibits it from overfitting to the uninformative ones. Furthermore, we evaluate our approach on two widely used rationalization benchmarks, i.e., the Beer Reviews dataset (McAuley et al., 2012) and the Hotel Reviews dataset (Wang et al., 2010), of which the empirical results show that FR outperforms all state-of-the-art methods in terms of the rationale quality. Our contributions are:

• To the best of our knowledge, this paper is the first to solve the degeneration problem in rationalization from the perspective of re-organizing the two-phase framework. We propose a simple but effective method, namely, FR, that folds the two phases into one by sharing a unified encoder between the generator and the predictor.

• The degeneration problem is mainly because the predictor can make correct predictions using uninformative rationales, leading to a sub-optimal generator. In this paper, we theoretically prove that the predictor of FR will not make correct predictions using these uninformative ones and thus mitigate the degeneration problem.

• We conduct extensive experiments over various datasets. The performance superiority of FR is

Figure 2: Standard method (a) RNP (Lei et al., 2016) with other recent methods with additional regularized modules. (b) 3PLAYER (Yu et al., 2019). (c) DMR (Huang et al., 2021). (d) A2R (Yu et al., 2021). X, Z, Y represent the input text, selected rationale, and predictive result, respectively.

demonstrated as compared to traditional rationalization methods. In particular, the F1 score of FR can be up to 10.3% higher than the state-of-the-art method.

2 Related work

Optimization for neural rationales. Most current rationalization methods adopt a cooperative framework between generator and predictor (Lei et al., 2016), which requires careful optimization to coordinate and is hard to train. Considering this challenge, a series of research efforts focus on refining the optimization process to improve the rationalization. For instance, Bao et al. (2018) used Gumbel softmax to do the reparameterization. Bastings et al. (2019) replaced the Bernoulli sampling distributions with rectified Kumaraswamy distributions. Chang et al. (2019) introduced a adversarial game and produces both positive and negative rationales. Jain et al. (2020) disconnected the training regimes of the generator and predictor networks using saliency threshold. Chang et al. (2020) tried to learn the invariance in rationalization. Jiang et al. (2021) used a post-hoc local approach to generate rationales for well-trained models. These methods are orthogonal to our proposed method FR that shares an encoder between the generator and predictor.

Regularization for neural rationales. Another series of efforts seeks to regularize the predictor using supplementary modules which have access to the information of the full text (Yu et al., 2019; Sha et al., 2021; Huang et al., 2021; Yu et al., 2021). Figure 2 shows a comparison of some representative methods, where X, Z, Y represent the input text, the generated rationale, and the predictive output, respectively. Yu et al. (2019) took the unselected text Z^c into consideration by employing a supplementary predictor *Predictor^c*, as shown in Figure 4(c). The generator and the supplementary predictor play an adversarial game. *Predictor^c* tries to maximize the predictive accuracy while the *Generator* seeks to minimize the predictive accuracy of *Predictor^c* such that all the informative pieces is squeezed into Z from Z^c. Huang et al. (2021) tried to align the distributions of rationale with the full input text in both the output space and feature space, as shown in Figure 4(d). To make alignment in the output space, they introduce a teacher predictor *Predictor^t* pre-trained with the full text and minimize the cross-entropy between the distributions of Y and Y^t (*OutPenalty*). In feature space, they minimize the central moment discrepancy (*FeaPenalty*) (Zellinger et al., 2017) between the representation of X and Z. Yu et al. (2021) endowed the predictor with the information of full text by introducing a soft rationale, which is shown in Figure 4(f). Specifically, the supplementary predictor takes the masked text by soft attention Z_{soft} as the input. To convey the formation of full text to the predictor, the model minimizes the JS-divergence between the output Y of the original predictor and Y^s of the supplementary predictor. These methods are mostly related to our work. However, different from these methods, we in this paper solve the degeneration problem from a new perspective. We fold the two phases of the rationalization framework into one such that the predictor gets direct access to the original full text.

3 Problem definition

Notation In the following sections, we use $\mathbb{P}(\cdot)$ and $p(\cdot)$ to represent distribution and probability. $gen(\cdot)$ and $pred(\cdot)$ represent the generator and predictor. θ_g and θ_p represent the parameters of the generator and predictor. $\mathcal{D}$ represents the distribution of dataset. We consider the classification problem, where the input is a text sequence $X=[x_1, x_2, \cdots, x_l]$ with x_i being the i-th token and l being the number of tokens. The label of X is a one-hot vector $Y \in \{0,1\}^c$, where c is the number of categories.

Cooperative rationalization Cooperative rationalization framework consists of a generator and a predictor. The goal of the generator is to find the most informative pieces including several tokens in the original input text X. For each sample $(X, Y) \sim \mathcal{D}$, the generator firstly outputs a sequence of binary mask $M = [m_1, \cdots, m_l] \in \{0,1\}^l$. Then, it forms the rationale Z by the element-wise product of X and M:

$$Z = M \odot X = [m_1 x_1, \cdots, m_l x_l]. \tag{1}$$

To simplify the notation, we denote the rationale Z by $gen(X)$, i.e., $Z = gen(X)$. In cooperative rationalization, the informativeness of the rationale Z provided by the generator is measured by the negative cross entropy $-H(Y, Y_z)$, where Y_z is the output of the predictor with the input being Z. Consequently, the generator and the predictor are usually optimized cooperatively:

$$\min_{\theta_g, \theta_p} \sum_{(X,Y) \sim \mathcal{D}} H(Y, pred(gen(X))). \tag{2}$$

Short and coherent regularizer Instead of using more complicated regularizers in the other models trying to mitigate degeneration (Yu et al., 2019; Huang et al., 2021), our model only needs a basic regularizer (Chang et al., 2019) as follows, which is similar to RNP (Lei et al., 2016), to effectively control the sparsity and coherence of the selected rationales:

$$\Omega(M) = \lambda_1 \left| \frac{||M||}{K} - \alpha \right| + \lambda_2 \sum_t |m_t - m_{t-1}|, \tag{3}$$

where K denotes the number of tokens in the input text. The first term encourages that the percentage of the tokens being selected as rationales is close to a pre-defined level α. The second term encourages the rationales to be coherent.

4 Folded rationalization using unified encoder

In this section, we specify FR and analyze why it works both intuitively and formally.

4.1 Architecture of folded rationalization

Based on the framework of RNP, the architecture of FR is to share the encoder between the generator and the predictor, as shown in Figure 3. It is worthwhile to note that we have no constraints on the types of the encoder and it can be any models such as RNN and Transformer (Vaswani et al., 2017). For the convenience of comparing with crruent methods in experiments, in this paper, we adopt the bidirectional gated recurrent units (GRU) (Cho et al., 2014) as the encoder which has been adopted by most previous works (Huang et al., 2021; Yu et al., 2021). In FR, the full text X is first sent to the unified *Encoder* in the generator and it outputs a representation for each token in X. Then, the representation of each token is independently sent to

Figure 3: The architecture of FR. X is the original full text. Z is the rationale and Y is the predictor's output.

Linear^g which is a linear layer acting as the generator head. *Linear^g* outputs a value of probability following the Bernoulli distribution from which the mask of each token is independently sampled

using gumbel-softmax (Jang et al., 2016). After that, the generator outputs Z using equation 1 and further sends it to the unified encoder *Encoder* in the predictor. By pre-processing the output of *Encoder* with max-pooling, the predictor uses the linear layer *Linear*^{p} to make the prediction. We adopt the similar objective function as RNP, i.e., equation 2 and 3, to optimize the generator and predictor cooperatively.

Intuition for guaranteed predictive accuracy By taking the classification problem for example, we here discuss why FR will not reduce the predictive accuracy of the predictor. In principle, the generator and the prdictor seek to extract the same semantic information from the similar input text. Specifically, to select the most informative pieces from the original text, the generator has to extract the semantic information of the text which is usually specific and distinguishable from other texts. On the other hand, to make the correct prediction, the predictor needs to transform the selected pieces mostly relative to the input text into the semantic features which are distinguishable and separable. Therefore, a unified encoder will not degrade the performance of the predictor, but will encourage them to benefit from each other.

Mutually reinforcing generator and predictor The main problem in RNP is that both the genrator and the predictor only have access to partial information of the original data pairs, which requires careful coordination to obtain the missed information from each other. FR with a unified encoder provides inherent benefits for the coordination and promotes the information sharing. To be more specific, the generator has access to the input text but no true labels, while the predictor is on the contrary. To achieve good results, they have to carefully make a coordination such that receive valuable information from one another. However, there are 2^l candidate rationales for each X with length l, which is exceptionally difficult for a not well trained generator to select informative ones from such a large space. As a consequence, the predictor of RNP has high risks in overfitting the uninformative noise provided by the generator. There is a similar case for the generator as obtaining backward information from the predictor. FR addresses this issue by allowing the generator and predictor to directly access to the full information of the original data. Specifically, the predictor with the unified encoder has a global view of all the rationale candidates by direct access to X, which prevents itself from overfitting to uninformative ones. In turn, with the encoder of the predictor, the generator's ability of summarizing and extracting information from the original text is greatly enhanced.

4.2 Theoretical analysis

In the cooperative rationalization, the generator uses the predictor to evaluate the informativeness of rationales. If the predictor can always classify uninformative rationales into true labels, then the generator may be fooled and converge to be sub-optimal. Here we will show that the predictor in FR is regularized by the generator through the unified encoder and can not stably classify uninformative rationales into true labels any more. In this way, only informative rationales can promise high predictive accuracy. To this end, once the equation 2 is optimized to maximize the final predictive accuracy, the selected rationales is guaranteed to be informative ones. To quantify the uninformativeness, we first give a definition of uninformative tokens:

Definition 1 *For $X \sim \mathcal{D}$, X_s is a subset of X, for a given token t, we say it is uninformative for X if the following equation holds:*

$$\mathbb{P}(Y|X_s) = \mathbb{P}(Y|X_s, t), \quad s.t., \ \forall X_s \subset X \tag{4}$$

It means that token t is independent of Y under the condition of X_s. In this situation, we can say t is uninformative to Y for X naturally. When equation 2 gets the optimal solution, we have $pred(gen(X)) = p(Y|X)$ and $pred(gen([X,t])) = p(Y|X,t)$, where "$[X,t]$" denotes the result of adding token t to any position of X. Then, we derive the following lemma.

Lemma 1 *When an uninformative token t is added to the original text X, the predictive results will hardly change:*

$$pred(gen(X)) = pred(gen([X,t])) + \epsilon, \ s.t., \ \forall X_s \subset X, \ \mathbb{P}(Y|X_s) = \mathbb{P}(Y|X_s, t), \tag{5}$$

where ϵ is an error depending on the learning error of the neural network. When equation 2 gets the optimal solution, the absolute value of ϵ is 0.

Without losing generality, we consider the case when equation 2 achieves the optimal solution for simplicity. For ease of exposition, we here denote $gen(X)$ and $gen([X,t])$ as $Z(X)$ and $[Z_1(X), Z_2(t)]$ respectively, where $Z_1(X)$ represents the binary masks of tokens in X and $Z_2(t)$ represents the mask of the new token t. Using equation 5 and $\epsilon = 0$, we have $pred(Z(X)) = pred([Z_1(X), Z_2(t)])$. To promise the same prediction, we get $Z(X) = Z_1(X)$, which indicates

$$gen(X) = \overline{gen([X,t])}, \ s.t., \ \forall X_s \subset X, \ \mathbb{P}(Y|X_s) = \mathbb{P}(Y|X_s, t), \tag{6}$$

where $\overline{gen([X,t])}$ denotes the first item of generator's output, e.g., $Z_1(X)$. For convenience of analyzing the functionality of the unified encoder, we decompose the generator and the predictor as

$$gen(\cdot) = f_g \circ h_g, \ pred(\cdot) = f_p \circ h_p, \tag{7}$$

where " $\circ$ " stands for functional composition, i.e., $(f \circ h)(X) = f(h(X))$. h and f represent the encoder and linear layer, respectively. Obviously, we have $h_g = h_p$ for FR. We rewrite equation 6 as $f_g \circ h_g(X) = \overline{f_g \circ h_g([X,t])}$. Since f_g is a linear function, and the mask is selected independently for each token in practice, we get $h_g(X) = \overline{h_g([X,t])}$. Now, we have the following lemma.

Lemma 2 *If equation 2 gets the optimal solution, adding an uninformative token t to the text X does not change the representation of the original tokens in X output by the encoder of the generator, i.e.,*

$$h_g(X)_{x_i} = h_g([X,t])_{x_i}, \ \forall x_i \in X, \tag{8}$$

where $h_g(X)_{x_i}$ represents the token x_i's representation with X being the input of the encoder h_g.

In the following, we consider h_g as a general one-way RNN network. Note that bidirectional RNN is almost the same. Besides, our analysis also holds for Transformer encoder which we leave its proof in the Appendix A.2. For the i-th token in X, the representation can be expressed as:

$$h_g(X)_{x_i} = \varphi_g(s_i), \ s_i = \psi_g(e_i, s_{i-1}), \tag{9}$$

where e_i, s_i are the word embedding and hidden state of the i-th token. φ_g, ψ_g are two functions corresponding to the type of RNN units. When an uninformative token t is added between x_i and x_{i-1}, we have

$$s_t = \psi_g(e_t, s_{i-1}), \ s_i^{'} = \psi_g(e_i, s_t). \tag{10}$$

Since t will not influence the representation of x_i, i.e., $s_i = s_i^{'}$, we have $s_t = s_{i-1}$, which is specified in the following lemma.

Lemma 3 *If the i-th token in X is uninformative, the hidden state of it through the encoder of generator is equal to that of the token preceding it:*

$$s_i = s_{i-1}, \ s.t., \ \forall X_s \subset X, \ \mathbb{P}(Y|X_s) = \mathbb{P}(Y|X_s, x_i). \tag{11}$$

Then, let us consider two different uninformative rationales, i.e., Z_{uninf} and $Z_{uninf}^{'}$, which contain only uninformative tokens and come from two different data pairs $(X, Y), (X^{'}, Y^{'})$.

Lemma 4 *If equation 11 holds, any two different uninformative rationales have the same representation through the encoder of generator for each token, i.e., $h_g(Z_{uninf})_{z_i} = h_g(Z_{uninf}^{'})_{z_j}$, where $h_g(Z_{uninf})_{z_i}$ denotes the representation for the i-th token in Z_{uninf}.*

The proof can be seen in Appendix A.1. Now, we immediately get the following theorem.

Theorem 1 *If FR gets the optimal solution of equation 2, i.e., $\mathbb{P}(Y|X) = \mathbb{P}(pred(gen(X)))$, and $Z_{uninf}, Z_{uninf}^{'}$ are two different rationales that contain only uninformative tokens and are selected from two different data pairs $(X, Y), (X^{'}, Y^{'})$, we have*

$$(f_p \circ h_g)(Z_{uninf}) = (f_p \circ h_g)(Z_{uninf}^{'}). \tag{12}$$

Theorem 1 indicates that the predictor in FR will give the same output for any different uninformative rationales. Hence, when we optimize the generator and the predictor by maximizing the final predictive accuracy using equation 2, the predictor only recognizes the informative rationales and ignores the uninformative ones. In this way, our FR greatly mitigates the degeneration problem.

Table 2: Results on Beer Reviews and Hotel Reviews. Each aspect is trained independently.

(a) Beer Reviews

Methods	Appearance					Aroma					Palate				
	S	Acc	P	R	F1	S	Acc	P	R	F1	S	Acc	P	R	F1
RNP	18.7	84.0	72.0	72.7	72.3	15.1	85.2	59.0	57.2	58.1	13.4	90.0	63.1	**68.2**	65.5
DMR	18.2	-	71.1	70.2	70.7	15.4	-	59.8	58.9	59.3	11.9	-	53.2	50.9	52.0
A2R	18.4	83.9	72.7	72.3	72.5	15.4	86.3	63.6	62.9	63.2	12.4	81.2	57.4	57.3	57.4
FR(ours)	18.4	87.2	**82.9**	**82.6**	**82.8**	15.0	88.6	**74.7**	**72.1**	**73.4**	12.1	89.7	**67.8**	66.2	**67.0**

(b) Hotel Reviews

Methods	Location					Service					Cleanliness				
	S	Acc	P	R	F1	S	Acc	P	R	F1	S	Acc	P	R	F1
RNP	8.8	97.5	46.2	48.2	47.1	11.0	97.5	34.2	32.9	33.5	10.5	96.0	29.1	34.6	31.6
DMR	10.7	-	47.5	**60.1**	53.1	11.6	-	43.0	43.6	43.3	10.3	-	31.4	36.4	33.7
A2R	8.5	87.5	43.1	43.2	43.1	11.4	96.5	37.3	37.2	37.2	8.9	94.5	33.2	33.3	33.3
FR(ours)	9.0	93.5	**55.5**	58.9	**57.1**	11.5	94.5	**44.8**	**44.7**	**44.8**	11.0	96.0	**34.9**	**43.4**	**38.7**

5 Experiments

5.1 Experimental setup

Datasets and Models Following (Huang et al., 2021), we consider two widely used rationalization datasets. To the best of our knowledge, none of dataset contains personally identifiable information or offensive content. The details of the two dataset can be found in Appendix B.1. 1) **Beer Reviews** (McAuley et al., 2012) is a multi-aspect sentiment prediction dataset widely used in rationalization (Lei et al., 2016; Yu et al., 2019; Chang et al., 2019; Huang et al., 2021; Yu et al., 2021). There is a high correlation among the rating scores of different aspects in the same review, making it difficult to directly learn a rationalization model from the original data. Following the previous work (Lei et al., 2016; Huang et al., 2021; Yu et al., 2021), we use the subsets decorrelated by Lei et al. (2016) and binarize the labels as Bao et al. (2018) did. 2) **Hotel Reviews** (Wang et al., 2010) is another multi-aspect sentiment classification dataset. The dataset contains reviews of hotels from three aspects including location, cleanliness, and service. Each review has a rating on a scale of 0-5 stars. We binarize the labels as Bao et al. (2018) did. On both two dataset, we adopt the GRU (Cho et al., 2014) as the encoder which has been adopted by most previous works (Huang et al., 2021; Yu et al., 2021).

Baselines and implementation details We compare FR to the cooperative rationalization framework RNP (Lei et al., 2016) and two latest published models that achieve state-of-the-art results: DMR (Huang et al., 2021) and A2R (Yu et al., 2021), both of which have been specified in section 1. For DMR, we adopt its source code and adjust its sparsity constraint to get a sparsity similar to the annotated rationales. For A2R, we re-implement it to do token level selection as other models do. Since DMR and A2R have been validated to outperform 3PLAYER (Huang et al., 2021; Yu et al., 2021), we in this paper ignore its results for clarity of presentation. Following DMR and A2R, we use the 100-dimension Glove (Pennington et al., 2014) as the word embedding and set the hidden dimension of GRU to be 200. We use Adam (Kingma and Ba, 2014) as the optimizer. All the baselines are tuned a lot of times to find the best hyperparameters. All of the models are implemented with PyTorch [1] and trained on a RTX3090 GPU.

Metrics All the methods get similar predictive accuracy. Following (Huang et al., 2021; Yu et al., 2021), we mainly focus on the quality of rationales, which is measured by the overlap between the model selected tokens and human-annotated tokens. $P, R, F1$ indicate the precision, recall, and F1 score, respectively. S indicates the average sparsity of the selected rationales, i.e., the percentage of selected tokens to the whole texts. Acc indicates the predictive accuracy on the test set.

---

[1] https://pytorch.org/

Table 3: Examples of generated rationales. Human-annotated rationales are underlined. Rationales from RNP and FR are highlighted in red and blue respectively.

RNP	FR
Aspect: Beer-Appearance
Label: Negative, **Pred:** Negative
Text: appearance : light yellow to almost clear smell : slight hops , but barely smelled like beer taste : little to none , like a rice lager , zero taste mouthfeel : watery and tasteless drinkability : very easy , goes down easier than water . good for drinking games.	**Aspect:** Beer-Appearance
Label: Negative, **Pred:** Negative
Text: appearance : light yellow to almost clear smell : slight hops , but barely smelled like beer taste : little to none , like a rice lager , zero taste mouthfeel : watery and tasteless drinkability : very easy , goes down easier than water . good for drinking games.
Aspect: Beer-Aroma
Label: Positive, **Pred:** Positive
Text: the appearance was nice . dark gold with not much of a head but nice lacing when it started to dissipate . the smell was ever so hoppy with a hint of the grapefruit flavor that 's contained within . the taste was interesting , up front tart grapefruit , not sweet in the least . more like grapefruit rind even . slight hint of hops and seemingly no malt . the mouth feel was crisp , with some biting carbonation . drinkability was easily above average due to the crispness and lack of sweetness . not the usual taste you expect when drinking a fruit beer . in fact this is my favorite fruit beer ever .	**Aspect:** Beer-Aroma
Label: Positive, **Pred:** Positive
Text: the appearance was nice . dark gold with not much of a head but nice lacing when it started to dissipate . the smell was ever so hoppy with a hint of the grapefruit flavor that 's contained within . the taste was interesting , up front tart grapefruit , not sweet in the least . more like grapefruit rind even . slight hint of hops and seemingly no malt . the mouth feel was crisp , with some biting carbonation . drinkability was easily above average due to the crispness and lack of sweetness . not the usual taste you expect when drinking a fruit beer . in fact this is my favorite fruit beer ever .
Aspect: Hotel-Cleanliness
Label: Negative, **Pred:** Negative
Text: we stayed at the holiday inn new orleans french quarter in late april 2012 . the rooms and hotel did not meet my expectations . the property is tired and worn out . my room had trash behind the furniture , rips in the carpet , wallpaper coming off the wall , no toilet lid , dirty tub and sink and a 110 volt out in the bath that was non functional . i noticed a piece of apple in the corner of the elevator the day i checked in and it was still there 3 days later when i checked out . this property is a cash cow and is always rented so they really do n't have to improve it . i should have spent a little extra money to stay at the weston , sheraton or the hilton . live and learn .	**Aspect:** Hotel-Cleanliness
Label: Negative, **Pred:** Negative
Text: we stayed at the holiday inn new orleans french quarter in late april 2012 . the rooms and hotel did not meet my expectations . the property is tired and worn out . my room had trash behind the furniture , rips in the carpet , wallpaper coming off the wall , no toilet lid , dirty tub and sink and a 110 volt out in the bath that was non functional . i noticed a piece of apple in the corner of the elevator the day i checked in and it was still there 3 days later when i checked out . this property is a cash cow and is always rented so they really do n't have to improve it . i should have spent a little extra money to stay at the weston , sheraton or the hilton . live and learn .

Table 4: Results of methods with low sparsity on Beer Reviews. The results of RNP and CAR are obtained from (Chang et al., 2019), and the results of DMR are from (Huang et al., 2021).

Methods	Appearance					Aroma					Plate				
	S	Acc	P	R	F1	S	Acc	P	R	F1	S	Acc	P	R	F1
RNP	11.9	-	72.0	46.1	56.2	10.7	-	70.5	48.3	57.3	10.0	-	53.1	42.8	47.5
CAR	11.9	-	76.2	49.3	59.9	10.3	-	50.3	33.3	40.1	10.2	-	56.6	46.2	50.9
DMR	11.7	-	**83.6**	52.8	**64.7**	11.7	-	63.1	47.6	54.3	10.7	-	55.8	48.1	51.7
FR(ours)	12.7	83.9	77.6	**53.3**	63.2	10.8	87.6	**82.9**	**57.9**	**68.2**	10.0	84.5	**69.3**	**55.8**	**61.8**

5.2 Results

Comparison with baselines on two dataset Table 2(a) and 2(b) show the results of selected rationales on two dataset. All the methods choose similar percentage of tokens that is close to the human-annotated sparsity by adjusting the sparsity regularization term in equation 3. Obviously, we gain significant improvements in all six aspects. In particular, the F1 score of our method FR is 82.8% in the Beer-Appearance dataset, which improves the state-of-the-art result by up to 10.3%, i.e., 72.5 of A2R. Table 3 shows some visualized examples of rationales from RNP and FR.

Comparison with baselines in low sparsity To show the robustness of our FR, we also conduct an experiment where the sparsity of selected rationales is very low, which is the same as CAR (Chang et al., 2019) and DMR. The results are shown in Table 4. The results of RNP and CAR are obtained from (Chang et al., 2019), and the results of DMR are obtained from (Huang et al., 2021). For the aspects of *Aroma* and *Palate*, we still achieve great improvement over other methods. For *Appearance*, our performance is a little bit worse than DMR. The reason may be that when the sparsity is far from the ground truth, many informative tokens are lost and the predictor can not make the right prediction. While DMR uses an adversarial framework same as CAR in practice and the label is used as an additional input to the generator, so it may work better when the sparsity is extremely low.

Skewed predictor To show that our FR does not suffer from the degeneration problem, we conduct the same synthetic experiment that deliberately induces degeneration as Yu et al. (2021) did. The details of the experimental setup can be found in Appendix B.3. The results are shown in Table 5. The results of RNP and A2R are obtained from (Yu et al., 2021). For all the settings, we outperform both RNP and A2R. Especially, for *Palate-skew*20, RNP and A2R can not work at all while our FR is still effective. It can be concluded that FR is much more robust than the other two methods in this situation.

Skewed generator: To further show that our method is not easy to degenerate, we design a new synthetic experiment with special initialization that induces degeneration from the perspective of

Table 5: Results of skewed predictor that induces degeneration on Beer Reviews.

Aspect	Setting	RNP				A2R				FR(ours)			
		Acc	P	R	F1	Acc	P	R	F1	Acc	P	R	F1
Aroma	skew10	82.6	68.5	63.7	61.5	84.5	**78.3**	70.6	69.2	87.1	73.9	**71.7**	**72.8**
	skew15	80.4	54.5	51.6	49.3	81.8	58.1	53.3	51.7	86.7	**71.3**	**68.0**	**69.6**
	skew20	76.8	10.8	14.1	11.0	80.0	51.7	47.9	46.3	85.5	**72.3**	**69.0**	**70.6**
Palate	skew10	77.3	5.6	7.4	5.5	82.8	50.3	48.0	45.5	75.8	**54.6**	**61.2**	**57.7**
	skew15	77.1	1.2	2.5	1.3	80.9	30.2	29.9	27.7	81.7	**51.0**	**58.4**	**54.5**
	skew20	75.6	0.4	1.4	0.6	76.7	0.4	1.6	0.6	83.1	**48.0**	**58.9**	**52.9**

Table 6: Results of skewed generator that induces degeneration in the *Palate* aspect of Beer Reviews.

Setting	RNP						FR(ours)					
	Pre_acc	S	Acc	R	R	F1	Pre_acc	S	Acc	P	R	F1
skew60.0	63.1	13.1	87.2	42.8	45.1	43.9	62.2	12.5	84.0	**59.3**	**59.8**	**59.6**
skew65.0	66.6	14.0	83.9	40.3	45.4	42.7	66.3	14.2	81.5	**59.5**	**67.9**	**63.4**
skew70.0	71.3	14.7	84.1	10.0	11.7	10.8	70.8	14.1	88.3	**54.7**	**62.1**	**58.1**
skew75.0	75.5	14.7	87.6	8.1	9.6	8.8	75.6	13.1	84.8	**49.7**	**52.2**	**51.0**

skewed generator. We pre-train the generator to be a special classifier that indicates the category using the mask of the first token in each text. For the text of class 1, we force the generator to select the first token, and for the text of class 0, we force the generator not to select the first token. Therefore, the generator learns the category implicitly by whether the first token is chosen and the predictor only needs to learn this misleading position information to make a prediction with high accuracy.

We compare the performance of RNP and our FR in the dataset Beer-Palate, because *Palate* is relatively hard to learn as compared to other aspects (Yu et al., 2021). Besides, the performance of RNP and FR is similar in this aspect when the generator is not deliberately skewed. All the hyperparameters we use here are the same as that of the best results in Table 2(a). The results are shown in Table 6. The k in "*skewk*" denotes the threshold of the skew: we pre-train the special generator-classifier for a few epochs until its predictive accuracy is higher than k. Since the accuracy increases rapidly in the first a few epochs, obtaining a model that precisely achieves the pre-defined accuracy is almost impossible. Therefore, we use "Pre_acc" to denote the actual predictive accuracy of the generator-classifier when the pre-training process stops. Higher "Pre_acc" means easier to degenerate. We find, in this case, both methods get high predictive accuracy while RNP fails to find the human-annotated rationales.

6 Conclusion, limitations, and future work

In this paper, we analyze the relationship between generator and predictor in terms of working mechanism and propose a simple but effective framework to solve the degeneration problem in the two-phase rationalization. The experimental results show that our proposed methods significantly outperform state-of-the-arts in terms of the rationale quality.

One limitation may be that our theoretical analysis mainly focuses on the idealized models which have perfectly fitted the distribution of the dataset. Besides, although sharing the encoder between the generator and predictor is simple, it is limited to the basic RNP which has no extra modules. Existing works have proposed many extra modules to solve the degeneration problem, which demonstrate great effectiveness. Leveraging these extra modules can predictably achieve performance improvement. However, the relationship among multiple modules will become much more sophisticated, simply sharing the generator and predictor may not be the optimal. How to effectively incorporate existing optimized techniques is a challenge for FR.

Besides, the sharing encoder of FR is similar to multi-task learning when training the generator and predictor are viewed as two cooperative tasks. However, existing multi-task learning methods are usually designed for the case where there are multiple output objectives but only one single input sample. How to bridge FR and multi-task learning both intuitively and theoretically, and then improve the rationalization with techniques in multi-task learning, is still unknown. We leave them as future work.

References

Yujia Bao, Shiyu Chang, Mo Yu, and Regina Barzilay. 2018. Deriving machine attention from human rationales. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 1903–1913.

Joost Bastings, Wilker Aziz, and Ivan Titov. 2019. Interpretable neural predictions with differentiable binary variables. In *57th Annual Meeting of the Association for Computational Linguistics*, pages 2963–2977.

Shiyu Chang, Yang Zhang, Mo Yu, and Tommi Jaakkola. 2019. A game theoretic approach to class-wise selective rationalization. *Advances in Neural Information Processing Systems*, 32:10055–10065.

Shiyu Chang, Yang Zhang, Mo Yu, and Tommi Jaakkola. 2020. Invariant rationalization. In *International Conference on Machine Learning*, pages 1448–1458.

Kyunghyun Cho, Bart Van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. 2014. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*.

Mengnan Du, Ninghao Liu, and Xia Hu. 2019. Techniques for interpretable machine learning. *Communications of the ACM*, 63(1):68–77.

Yongfeng Huang, Yujun Chen, Yulun Du, and Zhilin Yang. 2021. Distribution matching for rationalization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 13090–13097.

Sarthak Jain, Sarah Wiegreffe, Yuval Pinter, and Byron C Wallace. 2020. Learning to faithfully rationalize by construction. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4459–4473.

Eric Jang, Shixiang Gu, and Ben Poole. 2016. Categorical reparameterization with gumbel-softmax. *arXiv preprint arXiv:1611.01144*.

Zhongtao Jiang, Yuanzhe Zhang, Zhao Yang, Jun Zhao, and Kang Liu. 2021. Alignment rationale for natural language inference. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing*, pages 5372–5387.

Diederik P Kingma and Jimmy Ba. 2014. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*.

Tao Lei, Regina Barzilay, and Tommi Jaakkola. 2016. Rationalizing neural predictions. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 107–117.

Zachary C Lipton. 2016. The mythos of model interpretability. *arXiv preprint arXiv:1606.03490*.

Julian McAuley, Jure Leskovec, and Dan Jurafsky. 2012. Learning attitudes and attributes from multi-aspect reviews. In *2012 IEEE 12th International Conference on Data Mining*, pages 1020–1025. IEEE.

Tim Miller. 2019. Explanation in artificial intelligence: Insights from the social sciences. *Artificial intelligence*, 267:1–38.

Jeffrey Pennington, Richard Socher, and Christopher D Manning. 2014. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing*, pages 1532–1543.

Lei Sha, Oana-Maria Camburu, and Thomas Lukasiewicz. 2021. Learning from the best: Rationalizing predictions by adversarial information calibration. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 13771–13779.

Xiaofei Sun, Diyi Yang, Xiaoya Li, Tianwei Zhang, Yuxian Meng, Qiu Han, Guoyin Wang, Eduard Hovy, and Jiwei Li. 2021. Interpreting deep learning models in natural language processing: A review. *arXiv preprint arXiv:2110.10470*.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *Advances in neural information processing systems*, 30.

Hongning Wang, Yue Lu, and Chengxiang Zhai. 2010. Latent aspect rating analysis on review text data: a rating regression approach. In *Proceedings of the 16th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 783–792.

Liyao Xiang, Hao Zhang, Haotian Ma, Yifan Zhang, Jie Ren, and Quanshi Zhang. 2019. Interpretable complex-valued neural networks for privacy protection. In *International Conference on Learning Representations*.

Mo Yu, Shiyu Chang, Yang Zhang, and Tommi Jaakkola. 2019. Rethinking cooperative rationalization: Introspective extraction and complement control. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing*, pages 4094–4103.

Mo Yu, Yang Zhang, Shiyu Chang, and Tommi Jaakkola. 2021. Understanding interlocking dynamics of cooperative rationalization. *Advances in Neural Information Processing Systems*, 34.

Werner Zellinger, Thomas Grubinger, Edwin Lughofer, Thomas Natschläger, and Susanne Saminger-Platz. 2017. Central moment discrepancy (cmd) for domain-invariant representation learning. *arXiv preprint arXiv:1702.08811*.

A Theorem proofs

A.1 The proof of Lemma 4 and Theorem 1

Using equation 11, we get that the hidden state of an uninformative token is equal to that of the token precedes it. Considering two specific uninformative rationales $Z = \{\text{"}mask\text{"}, \text{"}t_1\text{"}, \text{"}t_2\text{"}\}$ and $Z^{'} = \{\text{"}mask\text{"}, \text{"}t_3\text{"}, \text{"}t_4\text{"}\}$ where all tokens in them are uninformative, we have:

$$h_g(Z)_{t_1} = h_g(Z)_{t_2} = h_g(Z)_{mask} = h_g(Z^{'})_{mask} = h_g(Z^{'})_{t_3} = h_g(Z^{'})_{t_4}. \tag{13}$$

Note that the token "$mask$" will always appear in any rationales because the hidden state in front of the first token is randomly initialized. So the proof of Lemma 4 is completed. Then, we have $\text{maxpool}(h_g(Z)) = \text{maxpool}(h_g(Z^{'}))$. Theorem 1 is also proved.

A.2 The proof of Theorem 1 when the encoder is a Transformer encoder

In fact, we only need to prove Lemma 4 because Theorem 1 can be easily derived from it. We express h_g as :

$$h_g(X)_{x_i} = \varphi_g(e_i) + \sum_j \psi_g(e_i, e_j) \odot \varphi_g(e_j). \tag{14}$$

If x_j is an uninformative token, it has no influence on $h_g(X)_{x_i}$ for any x_i according to Lemma 2. So, we have $||\varphi_g(e_j)||=0$ for any uninformative x_j.

For any Z_{uninf} that contains only uninformative tokens and z_i, z_j in Z_{uninf}, we have

$$||h_g(Z_{uninf})_{z_i}|| = ||h_g(Z_{uninf})_{z_j}|| = 0. \tag{15}$$

The proof of Lemma 4 is completed.

A.3 More details on the derivation of Lemma 3

From Lemma 2, we know that the representation of each token obtained by the generator's encoder keeps unchanged after an uninformative token is added to the original text, under the condition that $\epsilon = 0$ in Lemma 1. For simplicity, we here consider the general one-way RNN network (the derivation process for Transformer can be found in the original Appendix.A.2). For the i-th token in X, its representation can be expressed as:

$$h_g(X)\,x_i = \varphi_g(s_i),\ s_i = \psi_g(e_i, s_{i-1}), \tag{16}$$

where e_i, s_i are the word embedding and hidden state of the i-th token, respectively. φ_g, ψ_g are two functions corresponding to the type of RNN units. When an uninformative token t is added between x_i and x_{i-1}, we have

$$s_t = \psi_g(e_t, s_{i-1}),\ s_i^{'} = \psi_g(e_i, s_t), \tag{17}$$

where $s_i^{'}$ is the hidden state of the original x_i in this new text and we denote it by $h_g([X,t])_{x_i^{'}} = \varphi_g(s_i^{'})$. From Lemma 2, we have $h_g(X)_{x_i} = h_g([X,t])_{x_i^{'}}$. Using the first term of of the first equation (equation 8 in our original paper), we get

$$\varphi_g(s_i) = h_g(X)_{x_i} = h_g([X,t])_{x_i^{'}} = \varphi_g(s_i^{'}). \tag{18}$$

Then, we have $s_i = s_i^{'}$. Using the second term of of the second equation (equation 9 in our original paper), we get

$$\psi_g(e_i, s_t) = s_i^{'} = s_i = \psi_g(e_i, s_{i-1}). \tag{19}$$

Then, we have $s_t = s_{i-1}$ very smoothly and Lemma 3 is just a formal description of this equation.

Table 7: Statistics of datasets used in this paper

Datasets		Train		Dev		Annotation		
		Pos	Neg	Pos	Neg	Pos	Neg	Sparsity
Beer	Appearance	16891	16891	6628	2103	923	13	18.5
	Aroma	15169	15169	6579	2218	848	29	15.6
	Palate	13652	13652	6740	2000	785	20	12.4
Hotel	Location	7236	7236	906	906	104	96	8.5
	Service	50742	50742	6344	6344	101	99	11.5
	Cleanliness	75049	75049	9382	9382	99	101	8.9

B Details of experimental setup

B.1 Datasets

Beer Reviews Following (Chang et al., 2019; Huang et al., 2021; Yu et al., 2021), we consider a classification setting by treating reviews with ratings ≤ 0.4 as negative and ≥ 0.6 as positive. Then we randomly select examples from the original training set to construct a balanced set.

Hotel Reviews Similar to Beer Reviews, we treat reviews with ratings < 3 as negative and > 3 as positive.

More details are in Table 7. Pos and Neg denote the number of positive and negative examples in each set. $Sparsity$ denotes the average percentage of tokens in human-annotated rationales to the whole texts.

We get the license of Beer Reviews by sending an email to Julian McAuley. The Hotel Reviews is a public dataset and we get it from https://github.com/kochsnow/distribution-matching-rationality.

B.2 The setup of the experiment in Figure 1

We use the dataset of Beer-Aroma, whose details are shown in Table 7. We use a fixed batch size of 256 and initialize the learning rates of the two modules to different sizes as shown in Figure 1. The numbers in the squares are F1 scores that indicate the overlaps between the selected tokens and human-annotated rationales. For different settings, they use the same hyperparameters except the learning rates.

B.3 The details of skewed predictor

The experiment was first designed by Yu et al. (2021). It deliberately induces degeneration to show the robustness of A2R compared to RNP. The predictor is first pre-trained using the first sentence of each text for a few epochs. In Beer Reviews, the first sentence is usually about appearance. So, the predictor will overfit to the aspect of *Appearance*, which is uninformative for *Aroma* and *Palate*.

"*skewk*" denotes the predictor is pre-trained for k epochs. To make a fair comparison, we keep the pre-training process the same as that of A2R: we use a batch size of 500 and a learning rate of 0.001.

B.4 More visualized results

We also provide the visualized rationales from DMR and A2R corresponding to the examples in Table 3. The results are shown in Table 8.

B.5 Visualized results of Lemma 3

To verify Lemma 3, we visualized the representations of the tokens in two special designed sentences "good . , smell"(a,b,c) and "good , . smell "(d,e,f) through different encoders in Figure 4. We choose these two sentences because "," and "." are uninformative in most cases, which is consistent with the

Table 8: Examples of generated rationales. Human-annotated rationales are underlined. Rationales from RNP, DMR, A2R and FR are highlighted in red, orange, purple and blue respectively.

RNP	DMR	A2R	FR
Aspect: Beer-Appearance
Label: Negative
Pred: Negative
Text: appearance : light yellow to almost clear smell : slight hops , but barely smelled like beer taste : little to none , like a rice lager , zero taste mouthfeel : watery and tasteless drinkability : very easy , goes down easier than water . good for drinking games	**Aspect:** Beer-Appearance
Label: Negative
Pred: -
Text: appearance : light yellow to almost clear smell : slight hops , but barely smelled like beer taste : little to none , like a rice lager , zero taste mouthfeel : watery and tasteless drinkability : very easy , goes down easier than water . good for drinking games	**Aspect:** Beer-Appearance
Label: Negative
Pred: Negative
Text: appearance : light yellow to almost clear smell : slight hops , but barely smelled like beer taste : little to none , like a rice lager , zero taste mouthfeel : watery and tasteless drinkability : very easy , goes down easier than water . good for drinking games	**Aspect:** Beer-Appearance
Label: Negative
Pred: Negative
Text: appearance : light yellow to almost clear smell : slight hops , but barely smelled like beer taste : little to none , like a rice lager , zero taste mouthfeel : watery and tasteless drinkability : very easy , goes down easier than water . good for drinking games
Aspect: Beer-Aroma
Label: Positive
Pred: Positive
Text: the appearance was nice . dark gold with not much of a head but nice lacing when it started to dissipate . the smell was ever so hoppy with a hint of the grapefruit flavor that 's contained within . the taste was interesting , up front tart grapefruit , not sweet in the least . more like grapefruit rind even . slight hint of hops and seemingly no malt . the mouth feel was crisp , with some biting carbonation . drinkability was easily above average due to the crispness and lack of sweetness . not the usual taste you expect when drinking a fruit beer . in fact this is my favorite fruit beer ever .	**Aspect:** Beer-Aroma
Label: Positive
Pred: -
Text: the appearance was nice . dark gold with not much of a head but nice lacing when it started to dissipate . the smell was ever so hoppy with a hint of the grapefruit flavor that 's contained within . the taste was interesting , up front tart grapefruit , not sweet in the least . more like grapefruit rind even . slight hint of hops and seemingly no malt . the mouth feel was crisp , with some biting carbonation . drinkability was easily above average due to the crispness and lack of sweetness . not the usual taste you expect when drinking a fruit beer . in fact this is my favorite fruit beer ever .	**Aspect:** Beer-Aroma
Label: Positive
Pred: Positive
Text: the appearance was nice . dark gold with not much of a head but nice lacing when it started to dissipate . the smell was ever so hoppy with a hint of the grapefruit flavor that 's contained within . the taste was interesting , up front tart grapefruit , not sweet in the least . more like grapefruit rind even . slight hint of hops and seemingly no malt . the mouth feel was crisp , with some biting carbonation . drinkability was easily above average due to the crispness and lack of sweetness . not the usual taste you expect when drinking a fruit beer . in fact this is my favorite fruit beer ever .	**Aspect:** Beer-Aroma
Label: Positive
Pred: Positive
Text: the appearance was nice . dark gold with not much of a head but nice lacing when it started to dissipate . the smell was ever so hoppy with a hint of the grapefruit flavor that 's contained within . the taste was interesting , up front tart grapefruit , not sweet in the least . more like grapefruit rind even . slight hint of hops and seemingly no malt . the mouth feel was crisp , with some biting carbonation . drinkability was easily above average due to the crispness and lack of sweetness . not the usual taste you expect when drinking a fruit beer . in fact this is my favorite fruit beer ever .
Aspect: Hotel-Cleanliness
Label: Negative
Pred: Negative
Text: we stayed at the holiday inn new orleans french quarter in late april 2012 . the rooms and hotel did not meet my expectations . the property is tired and worn out . my room had trash behind the furniture , rips in the carpet , wallpaper coming off the wall , no toilet lid , dirty tub and sink and a 110 volt out in the bath that was non functional . i noticed a piece of apple in the corner of the elevator the day i checked in and it was still there 3 days later when i checked out . this property is a cash cow and is always rented so they really do n't have to improve it . i should have spent a little extra money to stay at the weston , sheraton or the hilton . live and learn .	**Aspect:** Hotel-Cleanliness
Label: Negative
Pred: -
Text: we stayed at the holiday inn new orleans french quarter in late april 2012 . the rooms and hotel did not meet my expectations . the property is tired and worn out . my room had trash behind the furniture , rips in the carpet , wallpaper coming off the wall , no toilet lid , dirty tub and sink and a 110 volt out in the bath that was non functional . i noticed a piece of apple in the corner of the elevator the day i checked in and it was still there 3 days later when i checked out . this property is a cash cow and is always rented so they really do n't have to improve it . i should have spent a little extra money to stay at the weston , sheraton or the hilton . live and learn .	**Aspect:** Hotel-Cleanliness
Label: Negative
Pred: Negative
Text: we stayed at the holiday inn new orleans french quarter in late april 2012 . the rooms and hotel did not meet my expectations . the property is tired and worn out . my room had trash behind the furniture , rips in the carpet , wallpaper coming off the wall , no toilet lid , dirty tub and sink and a 110 volt out in the bath that was non functional . i noticed a piece of apple in the corner of the elevator the day i checked in and it was still there 3 days later when i checked out . this property is a cash cow and is always rented so they really do n't have to improve it . i should have spent a little extra money to stay at the weston , sheraton or the hilton . live and learn .	**Aspect:** Hotel-Cleanliness
Label: Negative
Pred: Negative
Text: we stayed at the holiday inn new orleans french quarter in late april 2012 . the rooms and hotel did not meet my expectations . the property is tired and worn out . my room had trash behind the furniture , rips in the carpet , wallpaper coming off the wall , no toilet lid , dirty tub and sink and a 110 volt out in the bath that was non functional . i noticed a piece of apple in the corner of the elevator the day i checked in and it was still there 3 days later when i checked out . this property is a cash cow and is always rented so they really do n't have to improve it . i should have spent a little extra money to stay at the weston , sheraton or the hilton . live and learn .

setting of Lemma 3. Both our FR and RNP are trained on Beer-Aroma, where the predictive accuracy of the two models are similar while RNP selects bad rationales. Note that in FR, the encoder of the predictor is just the generator's encoder.

According to Lemma 3, the hidden states of "," and "." should be the same as that of the word "good" after they are passed through the generator's encoder, thus resulting in the same representation. We take the first 40 dimensions for better observation. From Figure 4, we can see for both RNP and FR,

Figure 4: Visualized examples of Lemma 3

the uninformative tokens "," and "." are closer to "good" by the encoder of the generator than by the encoder of the predictor. These results directly verify the conclusion of Lemma 3.

B.6 Failure examples

Table B.6 show some failure cases of our method. Typically, the failures can be summarized as follows. First, the model fails to grasp high-level language phenomena and world background knowledge. For example, in the case of Beer-Palate, the model fails to understand the analogy statement of "almost feels like drinking champagne" and makes the prediction as negative. Second, the model fails to make logical reasoning. The ground truth of hotel cleanliness should be inferred from the word "comfortable". However, our model makes judgments by selecting the rationales such as "breakfast, staff was friendly..., stay", which have little relevance to the cleanliness but are positive. A similar failure also occurs in the case of Beer-Aroma, where the model selects texts with a strong sentiment but uncorrelated with the predefined ground truth.

C   Boarder impact

The interpretability of neural networks aims to improve trust in the models. However, the problem of degeneration in the traditional two-phase rationalization models makes them untrustworthy for humans. Although the regularization terms introduced by following researches on the predictor can alleviate this problem, adjusting the regularization terms requires significant manual effort to see whether the model has degenerated or not according to the human-annotated rationales, which are very precious and only present in small numbers in the test set. Our FR does not suffer from degeneration as long as the predictive accuracy is high, which can be tuned on the validation set. So, our model saves a lot of manual cost. In addition, our model reduces the number of parameters by roughly half compared to traditional RNP and can be used by more researchers with limited computational resources. To the best of our knowledge, our research has no negative impact on society.

Table 9: Some failure cases of FR. The underlined piece of the text is the human-annotated rationale. Pieces of the text in blue representS the rationales from FR.

Beer-Palate
Label:positive, **Prediction:**negative
Input text: pours a slight tangerine orange and straw yellow . the head is nice and bubbly but fades very quickly with a little lacing . smells like wheat and european hops , a little yeast in there too . there is some fruit in there too , but you have to take a good whiff to get it the taste is of wheat , a bit of malt , and a little fruit flavour in there too almost feels like drinking champagne , medium mouthful otherwise easy to drink , but not somthinf i 'd be trying every night

---

Hotel-Cleanliness
Label: positive, **Prediction:** positive
Input text: my husband and i just spent two nights at the grand hotel francais , and we could not have been happier with our choice . in many ways ,the hotel has exceeded our expectation : the price was within our budget , breakfast was included , and the staff was friendly , helpful and fluent in english . as other travelers have mentioned , the hotel is close to the nation metro station , which makes it easy to get around . the room size was just enough to fit two people , butwe had a comfortable stay throughout . overall , the hotel lives up to its high trip advisor rating . we would love to stay here again anytime .

Beer-Aroma
Label: positive, **Prediction:** positive
Input text: a- amber gold with a solid two maybe even three finger head . looks absolutely delicious , i dare say it is one of the best looking beers i 've had .s- light citrus and hops . not a very strong aroma t-wow , the hops , citrus and pine blow out the taste buds , very tangy in taste , yet perfectly balanced , leaving a crisp dry taste to the palate . m-light and crisp feel with a nice tanginess thrown in the mix . d- could drink this all night , too bad i only have one more of this brew . notes : one of the best balanced and best tasting ipa 's i 've had to date . ipa fans you have to try this one .

D   Experiments with specialized layers

To make a fair comparison with the baseline models, our original paper mainly implemented the encoder with only one layer of GRUs for the experiments, which keeps the same as them.

To better understand the behavior where the encoders are partly shared, we further constructed the encoders with 3,4,5 layers of GRUs. The results can be seen in table 10 and 11

Table 10: More experimental results on encoders with different numbers of shared layers.

Datasets	Beer-Aroma					Beer-Aroma				
	S	Acc	P	R	F1	S	Acc	P	R	F1
0(RNP)	15.7	82.9	63.4	64.0	63.7	9.8	97.0	9.0	9.9	9.4
1st	14.4	83.5	68.2	62.9	65.4	10.1	96.0	7.5	7.7	7.6
1st+2nd	15.2	84.8	75.2	73.2	74.2	10.4	97.0	20.2	23.7	21.8
3rd	15.5	82.4	64.2	63.9	64.1	9.7	97.0	32.5	35.7	34.0
2nd+3rd	14.6	83.9	74.1	69.5	71.7	10.0	97.5	32.6	36.8	34.5
all(FR)	15.3	86.7	75.2	74.5	74.9	11.2	97.0	34.3	43.4	38.3

Notes in table 10:

0(RNP): all 3 layers are not shared

1st: only the 1st layer is shared

1st+2nd: the 1st and 2nd layers are shared

3rd: only the 3rd layer is shared

2st+3rd: the 2nd and 3rd layers are shared

All (FR): the unified encoder (all 3 layers are fully shared)

Notes in table 11:

0(RNP): all layers are not shared

Table 11: More experimental results on encoders with different numbers of shared layers.

Beer-Aroma	4-layer					5-layer				
	S	Acc	P	R	F1	S	Acc	P	R	F1
0(RNP)	14.1	81.2	73.2	66.6	69.4	17.1	85.8	66.9	75.7	71.0
1	16.7	85.1	68.0	73.1	70.5	14.3	83.6	74.3	68.4	71.2
2	14.8	84.7	72.8	69.1	70.9	14.7	85.2	74.2	70.1	72.1
3	14.9	82.3	75.5	72.3	73.9	15.6	85.6	71.0	71.0	71.0
4	-	-	-	-	-	16.3	87.7	71.9	75.2	73.5
all(FR)	15.1	88.0	76.8	74.3	75.1	15.4	87.3	75.2	74.2	74.7

1: the first layer is shared

2: the first two layers are shared

3: the first three layers are shared

4: the first four layers are shared

all(FR): all layers are shared

It can be seen from the table that the case fully sharing the encoder between the generator and predictor always outperforms that where the encoders are partly shared in terms of rationale quality (f1). Besides, the above table showed that the rationale quality gets better as the number of shared layers increases in overall.

We argue that, in order to achieve a good rationale, both the generator and predictor have to capture and encode the same informative sections from an input. Therefore, sharing the entire encoder can help performance. We also showed in the theoretical analysis of the paper, the encoder should be fully shared to make the predictor and the generator regularized by each other to get stable models.