A Quantitative Geometric Approach to Neural Network Smoothness

Abstract

Fast and precise Lipschitz constant estimation of neural networks is an important task for deep learning. Researchers have recently found an intrinsic trade-off between the accuracy and smoothness of neural networks, so training a network with a loose Lipschitz constant estimation imposes a strong regularization, and can hurt the model accuracy significantly. In this work, we provide a unified theoretical framework, a quantitative geometric approach, to address the Lipschitz constant estimation. By adopting this framework, we can immediately obtain several theoretical results, including the computational hardness of Lipschitz constant estimation and its approximability. We implement the algorithms induced from this quantitative geometric approach, which are based on semidefinite programming (SDP). Our empirical evaluation demonstrates that they are more scalable and precise than existing tools on Lipschitz constant estimation for ℓ_∞-perturbations. Furthermore, we also show their intricate relations with other recent SDP-based techniques, both theoretically and empirically. We believe that this unified quantitative geometric perspective can bring new insights and theoretical tools to the investigation of neural-network smoothness and robustness.

1 Introduction

The past decade has witnessed the unprecedented success of deep learning in many machine learning tasks (Krizhevsky et al., 2012; Mikolov et al., 2013). Despite the growing popularity of deep learning, researchers have also found that neural networks are very vulnerable to adversarial attacks (Szegedy et al., 2014; Goodfellow et al., 2015; Papernot et al., 2015). As a result, it is important to train neural networks that are robust against those attacks (Madry et al., 2019). In recent years, the deep learning community starts to focus on certifiably robust neural networks (Albarghouthi, 2021; Hein and Andriushchenko, 2017; Katz et al., 2017; Cohen et al., 2019; Raghunathan et al., 2018; Wang et al., 2022; Leino et al., 2021). One way to achieve certified robustness is to estimate the smoothness of neural networks, where the smoothness is measured by the Lipschitz constant of the neural network. Recent works have found that to achieve both high accuracy and low Lipschitzness, the network has to significantly increase the model capacity (Bubeck and Sellke, 2021). This implies that there is an intrinsic tension between accuracy and smoothness of neural networks.

Commonly considered adversarial attacks are the ℓ_∞ and ℓ_2-perturbations in the input space. Leino et al. (2021); Cohen et al. (2019) have successfully trained networks with low ℓ_2-Lipschitz constant, and Huang et al. (2021) trained networks with low local Lipschitzness for ℓ_∞-perturbations. There are few well-established techniques to train neural networks with low global Lipschitzness for ℓ_∞-perturbations. The techniques for the ℓ_2-perturbation do not easily transfer to the ℓ_∞-case (Leino et al., 2021). One critical step is to measure the Lipschitz constant more precisely and efficiently. Jordan and Dimakis (2020) showed that for ReLU networks, it is NP-hard to approximate the Lipschitz constant for ℓ_∞-perturbations within a constant factor , and proposed an exponential-time

algorithm to compute the exact Lipschitz constant. However, researchers are interested in more scalable approaches to certify and train networks. In this work, we consider the *Formal Global Lipschitz* constant (FGL) (See Equation (3)), which is an upper bound of the exact Lipschitz constant. FGL has been used in Raghunathan et al. (2018); Fazlyab et al. (2019); Latorre et al. (2020).

We address the Lipschitz constant estimation from the quantitative geometric perspective. Quantitative geometry aims to understand geometric structures via quantitative parameters, and has connections with many mathematical disciplines, such as functional analysis and combinatorics (Naor, 2013). In computer science, quantitative geometry plays a central role in understanding the approximability of discrete optimization problems. We approach those hard discrete optimization problems by considering the efficiently solvable continuous counterparts, and analyze the precision loss due to relaxation, which is often the SDP relaxation (Goemans and Williamson, 1995; Nesterov, 1998; Alon and Naor, 2004). By adopting the quantitative geometric approach, we can immediately understand the computational hardness and approximability of FGL estimations. Our algorithms on two-layer networks are the natural SDP relaxations from the quantitative geometric perspective.

Latorre et al. (2020) employed polynomial optimization methods on the FGL estimation for ℓ_∞-perturbations. Polynomial optimization is a very general framework, and many problems can be cast in this framework (Motzkin and Straus, 1965; Goemans and Williamson, 1995). Therefore, we argue that this is not a precise characterization of the FGL-estimation problem. On the other hand, there are also several SDP-based techniques for FGL estimations. Raghunathan et al. (2018) proposed an SDP algorithm to estimate the FGL for ℓ_∞-perturbations of two layer networks, and Fazlyab et al. (2019) devised an SDP algorithm to estimate the ℓ_2-FGL. We will demonstrate the intricate relationships between our algorithms and these existing SDPs on two-layer networks.

Several empirical studies have found that techniques on one ℓ_p-perturbations often do not transfer to another ones, even though the authors claim that *in theory* these techniques should transfer (Fazlyab et al., 2019; Leino et al., 2021). This in-theory claim usually comes from a *qualitative* perspective. In finite-dimensional space, one can always bound one ℓ_p-norm from another one, so techniques for one ℓ_p-perturbations can also provide another bound for a different ℓ_p-perturbations. However, this bound is loose and in practice not useful (Latorre et al., 2020). Instead, we believe that when transferring techniques from one norm to another one, we should consider the quantitative geometric principle: we should separate the geometry-dependent component from the geometry-independent one in those techniques, and modify the geometry-dependent component accordingly for a different normed space. As we will demonstrate, our whole work is guided by this principle. We hope that our unified quantitative geometric framework can bring insights to the empirical hard-to-transfer observations, and new tools to address these issues.

Contributions. To summarize, we have made the following contributions:

1. We provide a unified theoretical framework to address FGL estimations, which immediately yields the computational hardness and SDP-based approximation algorithms on two-layer networks (Section 3).

2. We demonstrate the relations between our algorithms and other SDP-based tools, which in return inspires us to design the algorithms for multi-layer networks. This provides more insightful interpretations of existing works, and make them easier-to-generalize (Section 4).

3. We implement the algorithms and name the tool GeoLIP. We empirically validate our theoretical claims, and compare GeoLIP with existing methods to estimate FGL for ℓ_∞-perturbations. The result shows that GeoLIP provides a tighter bound (20%-60% improvements) than existing tools on small networks, and much better results than the naive matrix-norm-product method for deep networks, which existing tools cannot handle (Section 5).

2   Preliminaries

Notation.   Let $[n] = \{1, \ldots, n\}$. For two functions f and g, $f \circ g(x) = f(g(x))$. A 0-1 cube is $\{0, 1\}^n$, and a norm-1 cube is $\{-1, 1\}^n$ for some integer $n > 0$. $\mathbb{R}_+ = [0, \infty)$. For any vector $v \in \mathbb{R}^n$, $\mathrm{diag}(v)$ is an $n \times n$ diagonal matrix, with diagonal values v. Let $e_n = (1, \ldots, 1) \in \mathbb{R}^n$ be an n-dimensional vector of all 1's; and $I_n = \mathrm{diag}(e_n)$, the identity matrix. $||v||_p$ denotes the ℓ_p norm of v. We use q to denote the Hölder dual of p as a convention, i.e., $\frac{1}{p} + \frac{1}{q} = 1$. If v is an operator in

90 the ℓ_p-space, the operator norm of v is then $||v||_q$. Throughout the paper, we consider the ℓ_p-norm of
91 the input's perturbation, and therefore, the ℓ_q-norm of the gradient, which acts as an operator on the
92 perturbation. A square matrix $X \succeq 0$ means that X positive semidefinite (PSD). $\text{tr}(X)$ denotes the
93 trace of a square matrix X. If $a, b \in \mathbb{R}^n$, $\langle a, b \rangle$ denotes the inner product of a and b.

Lipschitz function. Given two metric spaces (X, d_X) and (Y, d_Y), a function $f : X \to Y$ is
95 *Lipschitz* continuous if there exists $K > 0$ such that for all $x_1, x_2 \in X$,

$$d_Y(f(x_2), f(x_1)) \leq K d_X(x_2, x_1). \tag{1}$$

96 The smallest such K satisfying Equation (1), denoted by K_f, is called the Lipschitz constant of
97 f. For neural networks, X is in general $\mathbb{R}^m$ equipped with the ℓ_p-norm. We will only consider
98 the case when $Y = \mathbb{R}$. In actual applications such as a classification task, a neural network has
99 multiple outputs. The prediction is the class with the maximum score. One can then use the margin
100 between each pair of class predictions and its Lipschitz constant to certify the robustness of a given
101 prediction (Raghunathan et al., 2018; Leino et al., 2021). From Rademacher's theorem, if f is
102 Lipschitz continuous, then f is is almost everywhere differentiable, and $K_f = \sup_x ||\nabla f(x)||_q$.

Neural network as function. A neural network $f : \mathbb{R}^m \to \mathbb{R}$ is characterized by:

$$f_1(x) = W^1 x + b_1; \; f_i(x) = W^i \text{diag}(\sigma(f_{i-1}(x))) + b_i, i = 2, \ldots, d.$$

104 where $W^i \in \mathbb{R}^{n_{i+1} \times n_i}$ is the weight matrix between the layers, $n_1 = m$, d is the depth of the neural
105 network, σ denotes an activation function, $b_i \in \mathbb{R}^{n_{i+1}}$ is the bias term, and $f = f_d \circ \cdots \circ f_1$. Because
106 we only consider the $\mathbb{R}$ as the codomain of f, $W^d = u \in \mathbb{R}^{1 \times n_d}$ is a vector. From chain rule, the
107 gradient of this function is

$$\nabla f(x) = (W^1)^T \Pi_{i=2}^d \text{diag}(\sigma'(f_{i-1}(x))(W^i)^T. \tag{2}$$

108 Common activation functions, including ReLU (Nair and Hinton, 2010), sigmoid functions, and
109 ELU (Clevert et al., 2016) are (almost) everywhere differentiable. As a result, we are interested in the
110 supremum operator norm of Equation (2).

111 However, checking all possible inputs x is infeasible, and common activation functions have bounded
112 derivative values, saying $[a, b]$. We are then interested in the following value instead:

$$\max_{v^i \in [a,b]^{n_i}} ||(W^1)^T \cdot \text{diag}(v^2) \cdot \cdots \cdot \text{diag}(v^d)(W^d)^T||_q, \tag{3}$$

113 where n_i is the dimension of each $\text{diag}(v^i)$. We call this value the *formal* global Lipschitz constant
114 (FGL) because we treat all activation functions independent but in reality not all activation patterns are
115 feasible. Therefore, this is an upper bound of the *true* global Lipschitz constant of the neural network.
116 However, it is the value studied in most global Lipschitzness literature (Scaman and Virmaux, 2018;
117 Fazlyab et al., 2019; Latorre et al., 2020), and also turns out useful in certifying the robustness of
118 neural networks (Raghunathan et al., 2018; Leino et al., 2021; Pauli et al., 2022). We use ℓ_p-FGL to
119 denote the FGL for ℓ_p-perturbations.

120 In this paper, we focus on the ℓ_p-perturbation on the input, where $p = \infty$ or $p = 2$. Because q is the
121 Hölder dual of p, we are interested in the value of Equation (3), when $q = 1$ (for $p = \infty$), and $q = 2$
122 (for $p = 2$). Notice that in the ReLU-network case, $[a, b]$ is $\{0, 1\}$, because the derivative of ReLU
123 is either 0 or 1 almost everywhere. The objective in Equation (3) becomes an integer optimization
124 problem. We will use ReLU-networks as the illustration for the rest of the paper because of the
125 popularity of ReLU in practice and the easy presentation of the 0-1-cube. However, the algorithms
126 presented in this work can be adapted with minor adjustments to other common activation functions.

3 Two-layer neural networks

128 In this section, we consider the two-layer neural network case. We reduce the FGL estimation
129 to the matrix mixed-norm problem. This immediately yields the computational complexity and
130 approximation algorithms for FGL estimations.

Problem description. The two-layer neural networks can be defined as $f(x) = u \text{diag}(y) W x$,
132 where $W \in \mathbb{R}^{n \times m}$, $\text{diag}(y) \in \mathbb{R}^{n \times n}$, and $u \in \mathbb{R}^{1 \times n}$. The FGL of this network is then
133 $\max_{y \in \{0,1\}^n} ||W^T \text{diag}(y) u^T||_q$. If we expand the matrix multiplication, it is easy to check that
134 this equals to $\max_{y \in \{0,1\}^n} ||W^T \text{diag}(u) y||_q$. Let $A = W^T \text{diag}(u)$, then the ℓ_p-FGL is

$$\max_{y \in \{0,1\}^n} ||Ay||_q. \tag{4}$$

3.1 ℓ_∞-FGL estimation

We consider a natural SDP relaxation to Equation (4) when $q = 1$, and analyze the result using the celebrated *Grothendieck Inequality*, which is a fundamental tool in functional analysis.

Mixed-norm problem. The $\infty \to 1$ mixed-norm of a matrix is defined as
$$||A||_{\infty \to 1} = \max_{||x||_\infty = 1} ||Ax||_1.$$
The mixed-norm problem appears similar to Equation (4) when $q = 1$, except for that instead of a norm-1-cube, the cube in Equation (4) is a 0-1-cube. Alon and Naor (2004) constructed a natural SDP relaxation for the mixed-norm problem:
$$\begin{aligned} &\max \operatorname{tr}(BX) \\ &s.t.\ X \succeq 0, X_{ii} = 1, i \in [n+m], \end{aligned} \tag{5}$$
where A is a submatrix of B. We provide the detailed derivation of this relaxation in the appendix. In fact, this relaxation admits a constant approximation factor. Grothendieck (1956) developed the local theory of Banach spaces, and showed that there exists an absolute value K_G such that

Theorem 3.1. *For any $m, n \geq 1$, $A \in \mathbb{R}^{n \times m}$, and any Hilbert space H, the following holds:*
$$\max_{u_i, v_j \in B(H)} \sum_{i,j} A_{ij} \langle u_i, v_j \rangle_H \leq K_G ||A||_{\infty \to 1}.$$

$B(H)$ denotes the unit ball of the Hilbert space. The precise value of K_G is still an outstanding open problem (Krivine, 1979; Braverman et al., 2011). It is known that $K_G < 1.783$. The approximation factor of the SDP relaxation in Equation (5) is K_G.

Alon and Naor (2004) showed that it is NP-hard, specifically MAXSNP-hard, to compute the $\infty \to 1$ mixed-norm of a matrix A, via a reduction to the graph Max-Cut problem. We similarly show that the ℓ_∞-FGL estimation is MAXSNP-hard, via a cube rescaling technique that we introduce later.

Theorem 3.2. ℓ_∞-*FGL estimation for ReLU-networks is* MAXSNP-*hard.*

From 0-1 cube to norm-1 cube. If we can transform the 0-1 cube in Equation (4) to a norm-1 cube, and formulate an equivalent optimization problem, then one can apply the SDP program in Equation (5) to compute an upper bound of the FGL. Indeed, we provide a cube rescaling technique, and it allows us to construct the SDP for the ℓ_∞-FGL estimation. We provide the full detail of this technique in the appendix, and the result SDP for the ℓ_∞-FGL estimation is
$$\begin{aligned} &\max \frac{1}{2} \operatorname{tr}(BX) \\ &s.t.\ X \succeq 0, X_{ii} = 1, i \in [n+m+1], \end{aligned} \tag{6}$$
where B is a $(n+1+m) \times (n+1+m)$ matrix, and $B = \begin{pmatrix} 0 & 0 & 0 \\ A & Ae_n & 0 \end{pmatrix}$. As a result, we have:

Theorem 3.3. *There exists a polynomial-time approximation algorithm to estimate the ℓ_∞-FGL of two-layer neural networks, moreover, the approximation ratio is K_G.*

3.2 ℓ_2-FGL estimation

Scaman and Virmaux (2018) showed that the ℓ_2-FGL estimation is NP-hard. If $q = 2$ in Equation (4), the objective becomes similar to the $\infty \to 2$ mixed-norm problem. This is a quadratic optimization problem with a PSD weight matrix over a cube, and can be viewed as a generalization of the graph Max-Cut problem. In the quadratic optimization formulation of Max-Cut, the weight matrix is the Laplacian of the graph, a special PSD matrix (Goemans and Williamson, 1995). Nesterov (1998) generalized Goemans-Williamson's technique and analyzed the case when the weight matrix is PSD, showing that the natural SDP relaxation in this case has a $\frac{\pi}{2}$-approximation ratio. This provides a $\sqrt{\frac{\pi}{2}}$-approximation algorithm for the ℓ_2-FGL estimation. The SDP for ℓ_2-FGL estimation is:
$$\begin{aligned} &\max \frac{1}{2} \sqrt{\operatorname{tr}(\begin{pmatrix} A^T A & A^T A e_n \\ e_n^T A^T A & e_n^T A^T A e_n \end{pmatrix} \cdot X)} \\ &s.t.\ X \succeq 0, X_{ii} = 1, i \in [n+1]. \end{aligned} \tag{7}$$
The full derivation is provided in the appendix, and we have the following theorem:

Theorem 3.4. *There exists a polynomial-time approximation algorithm to estimate the ℓ_2-FGL of two-layer neural networks with an approximation factor $\sqrt{\frac{\pi}{2}}$.*

Remark 3.5. As we have discussed, for two-layer networks, the ℓ_p-FGL estimation is essentially the $\infty \to q$ mixed-norm problem. Indeed the mixed-norm problem is an outstanding topic in theoretical computer science. As discussed in Bhattiprolu et al. (2018), the $\infty \to q$ mixed norm problem has constant approximation algorithms if $q \leq 2$, and is hard to approximate within almost polynomial factors when $q > 2$. Because when $q > 2$, its Hölder dual $p < 2$. This implies that for two-layer networks, the FGL estimation can be much harder for ℓ_p-perturbations when $p < 2$.

Briët et al. (2017) showed that it is NP-hard to approximate the $\infty \to 2$ mixed-norm problem better than $\sqrt{\frac{\pi}{2}}$. Raghavendra and Steurer (2009) proved that assuming the unique games conjecture (Khot, 2002), it is NP-hard to approximate the $\infty \to 1$ mixed-norm problem better than K_G. These optimal approximation ratios match our SDP relaxations for FGL estimations accordingly.

4 Multi-layer neural networks

Before introducing our approach for multi-layer networks, we first examine some existing SDP works on FGL estimations, and discuss their relationships with our natural SDP relaxations in Section 3.

4.1 Relations to existing SDP works

ℓ_∞**-FGL estimation.** Raghunathan et al. (2018) formulated an SDP that only works for two-layer networks. Theirs is essentially the same as ours in Equation (6) (See the detailed comparison in the appendix). However, we provide a rigorous derivation and simpler formulation, and also a sound theoretical analysis of the bound, which illustrate more insights to this problem. Raghunathan et al. (2018) treated the SDP relaxation as a heuristic to a hard quadratic programming problem. We prove that this relaxation is not only a heuristic, but in fact induces an approximation algorithm with a tight bound.

ℓ_2**-FGL estimation.** Fazlyab et al. (2019) proposed LipSDP, another SDP algorithm for the ℓ_2-FGL estimation problem. Fazlyab et al. (2019) provided several variants of LipSDP to balance the precision and scalability. Pauli et al. (2022) demonstrated that the most precise version of LiPSDP, *LiPSDP-Network*, fails to produce an upper bound for ℓ_2-FGL. In this paper, all the references of LiPSDP are to *LiPSDP-Neuron*, the less precise version. Surprisingly, even though the approach in LipSDP appears quite different from Equation (7), we show that LipSDP is dual of Equation (7) to estimate the ℓ_2-FGL on two-layer networks. LipSDP for two-layer networks is:

$$\min_{\zeta, \lambda} \left\{ \sqrt{\zeta} : \begin{pmatrix} -2abW^TWT - \zeta I_m & (a+b)W^TT \\ (a+b)TW & -2T + u^Tu \end{pmatrix} \preceq 0, \lambda_i \geq 0 \right\},$$

where $T = \text{diag}(\lambda)$ for $\lambda \in \mathbb{R}^n_+$; a and b are the lower and upper bounds of the activation's derivative.

We will construct a new optimization program, which we show is equivalent to Equation (4) when $q = 2$, and LipSDP is its dual SDP relaxation.

Let $\Delta x \in \mathbb{R}^m$ be a perturbation on x, and $\Delta\sigma(x) \in \mathbb{R}^n$ denote the induced perturbation of Δx on $\text{diag}(y)$, and w_i be the row vector of W. Let the input of the i-th activation node on $\text{diag}(y)$ be y_i. Hence, $y_i = w_i x$, and $\Delta y_i = w_i \Delta x$. The ***constraint*** from the activation function is $\frac{\Delta\sigma(x)_i}{\Delta y_i} \in [a, b]$, in other words, $\frac{\Delta\sigma(x)_i}{w_i \Delta x} \in [a, b]$. One can write the range constraint as

$$(\Delta\sigma(x)_i - a \cdot w_i\Delta x)(\Delta\sigma(x)_i - b \cdot w_i\Delta x) \leq 0.$$

This can be written in the quadratic form:

$$\begin{pmatrix} w_i\Delta x \\ \Delta\sigma(x)_i \end{pmatrix}^T \begin{pmatrix} -2ab & a+b \\ a+b & -2 \end{pmatrix} \begin{pmatrix} w_i\Delta x \\ \Delta\sigma(x)_i \end{pmatrix} \geq 0, \quad \forall i \in [n]. \tag{8}$$

Since for the two layer network, $f(x) = u\sigma(x)$, then $\Delta f(x) = u\Delta\sigma(x)$. The ***objective*** for ℓ_2-FGL estimation is $\max_{\Delta x, \Delta\sigma(x)} \sqrt{\frac{(u\Delta\sigma(x))^2}{(\Delta x)^2}}$. The equivalence between this program and Equation (4) when $q = 2$ is presented in the appendix.

Duality to LipSDP. Now we will show that LipSDP is the dual SDP to the program formulated above. The dual SDP derivation is of similar form in Ben-Tal and Nemirovski (2001, Ch.4.3.1). Let us introduce a variable ζ such that $\zeta - \frac{(u\Delta\sigma(x))^2}{(\Delta x)^2} \geq 0$. In other words,

$$\zeta(\Delta x)^2 - (u\Delta\sigma(x))^2 \geq 0. \tag{9}$$

For each constraint in Equation (8), let us introduce a dual variable $\lambda_i \geq 0$. Multiply each constraint with λ_i, then $\begin{pmatrix} \Delta x \\ \Delta\sigma(x)_i \end{pmatrix}^T \begin{pmatrix} -2ab\lambda_i w_i^T w_i & (a+b)\lambda_i w_i^T \\ (a+b)\lambda_i w_i & -2\lambda_i \end{pmatrix} \begin{pmatrix} \Delta x \\ \Delta\sigma(x)_i \end{pmatrix} \geq 0, \quad \forall i \in [n].$

Sum all of them, then we have $\begin{pmatrix} \Delta x \\ \Delta\sigma(x) \end{pmatrix}^T \begin{pmatrix} -2abW^T WT & (a+b)W^T T \\ (a+b)TW & -2T \end{pmatrix} \begin{pmatrix} \Delta x \\ \Delta\sigma(x) \end{pmatrix} \geq 0$, where $T = \text{diag}(\lambda)$ is the $n \times n$ diagonal matrix of dual variables $\lambda_1, \ldots, \lambda_n$.

Equation (9) can be rewritten as: $\begin{pmatrix} \Delta x \\ \Delta\sigma(x) \end{pmatrix}^T \begin{pmatrix} \zeta I_m & 0 \\ 0 & -u^T u \end{pmatrix} \begin{pmatrix} \Delta x \\ \Delta\sigma(x) \end{pmatrix} \geq 0$. As a result, the dual program for the new optimization program is

$$\min_{\zeta,\lambda} \left\{ \sqrt{\zeta} : \begin{pmatrix} -2abW^T WT - \zeta I_m & (a+b)W^T T \\ (a+b)TW & -2T + u^T u \end{pmatrix} \preceq 0, \lambda_i \geq 0 \right\},$$

Remark 4.1. In Remark 3.5, we mention that $\sqrt{\frac{\pi}{2}}$ is the optimal approximation ratio for the $\infty \to 2$ mixed-norm problem, which matches the approximation ratio in Theorem 3.4. Hence, improving the natural SDP relaxation in Equation (7) can be very hard. The duality provides another evidence of LipSDP-Neuron's correctness, and hints that LipSDP-Network, the improved variant, may be wrong.

4.2 ℓ_∞-FGL estimation for multi-layer networks

For a multi-layer neural network, the formal gradient becomes a high-degree polynomial, and its ℓ_q-norm estimation becomes a high-degree polynomial optimization problem over a cube, which is in general a hard problem (Lasserre, 2015). We provide a discussion of the polynomial optimization approach of FGL estimation in the appendix. Here we provide an SDP dual program of the ℓ_∞-FGL estimation inspired by the dual SDP approach in Section 4.1. The difference is that now we consider ℓ_∞-perturbations to the input space instead of ℓ_2. Hence, the objective becomes

$$\max_{\Delta x, \Delta\sigma(x)} \frac{|u\Delta\sigma(x)|}{||\Delta x||_\infty}.$$

If we add an extra constraint $||\Delta x||_\infty = 1$, the above objective becomes

$$\max_{\Delta x, \Delta\sigma(x)} \frac{1}{2}(u\Delta\sigma(x) + u\Delta\sigma(x)). \tag{10}$$

The constraints are

$$\begin{pmatrix} w_i \Delta x \\ \Delta\sigma(x)_i \end{pmatrix}^T \begin{pmatrix} 2ab & -(a+b) \\ -(a+b) & 2 \end{pmatrix} \begin{pmatrix} w_i \Delta x \\ \Delta\sigma(x)_i \end{pmatrix} \leq 0, \ \Delta(x)_j^2 \leq 1, \ \forall i \in [n], j \in [m]$$

We can write $\Delta(x)_j^2 \leq 1$ as $\begin{pmatrix} 1 \\ \Delta x_j \end{pmatrix}^T \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix} \begin{pmatrix} 1 \\ \Delta x_j \end{pmatrix} \geq 0.$

Now let us introduce $n + m$ non-negative dual variables (τ, λ), where $\tau \in \mathbb{R}_+^m$ and $\lambda \in \mathbb{R}_+^n$. If we multiply each dual variable with the constraint and add all the constraints together, we will have

$$\begin{pmatrix} 1 \\ \Delta x \\ \Delta\sigma(x) \end{pmatrix}^T \begin{pmatrix} \sum_{j=1}^m \tau_j & 0 & 0 \\ 0 & -2abW^T WT_2 - T_1 & (a+b)W^T T_2 \\ 0 & (a+b)T_2 W & -2T_2 \end{pmatrix} \begin{pmatrix} 1 \\ \Delta x \\ \Delta\sigma(x) \end{pmatrix} \geq 0,$$

where $T_1 = \text{diag}(\tau)$ and $T_2 = \text{diag}(\lambda)$. As a result, we can incorporate the objective Equation (10) and obtain the dual SDP for the ℓ_∞-FGL estimation:

$$\min_{\zeta,\lambda,\tau} \left\{ \frac{\zeta}{2} : \begin{pmatrix} \sum_{j=1}^m \tau_j - \zeta & 0 & u \\ 0 & -2abW^T WT_2 - T_1 & (a+b)W^T T_2 \\ u^T & (a+b)T_2 W & -2T_2 \end{pmatrix} \preceq 0, \lambda_i, \tau_j \geq 0 \right\}. \tag{11}$$

Multi-layer extension. We can simply extend the dual program to multiple-layer networks. We first vectorize all the units in the input layer and hidden layers, and then constrain them using layer-wise inequalities to formulate an optimization problem. Let us consider a general d-layer multi-layer network: $f(x) = u\,\mathrm{diag}(y^{d-1})W^{d-1}\cdots\mathrm{diag}(y^1)W^1 x$, where $x \in \mathbb{R}^{n_1 \times 1}$, $W_i \in \mathbb{R}^{n_{i+1} \times n_i}$, $\mathrm{diag}(y_i) \in \mathbb{R}^{n_{i+1} \times n_{i+1}}$, for $i \in [d-1]$, $u \in \mathbb{R}^{1 \times n_d}$.

Let Δx denote the perturbation on the input layer, Δy^i be the perturbation on the i-th hidden layer, and w_j^i be the j-th row vector of W^i. The only difference between two layer networks and multi-layer networks is that we have the additional constraints:

$$\begin{pmatrix} \Delta y_j^i \\ \Delta y_j^{i+1} \end{pmatrix}^T \begin{pmatrix} -2ab(w_j^{i+1})^T w_j^{i+1} & (a+b)(w_j^{i+1})^T \\ (a+b)w_j^{i+1} & -2 \end{pmatrix} \begin{pmatrix} \Delta y_j^i \\ \Delta y_j^{i+1} \end{pmatrix} \geq 0,$$

Let $\Lambda_i \in \mathbb{R}_+^{n_i}$ and $T_i = \mathrm{diag}(\Lambda_i)$ for $i \in [d]$. Following the similar SDP dual approach, we can add all the constraints together and formulate the following SDP program:

$$\min_{\zeta, \Lambda_i} \left\{ \frac{\zeta}{2} : (L+N) \preceq 0, i \in [d] \right\}, \tag{12}$$

where

$$L = \begin{pmatrix} 0 & 0 & 0 & \ldots & 0 & 0 \\ 0 & -2ab(W^1)^T W^1 T_2 & (a+b)(W^1)^T T_2 & \ldots & 0 & 0 \\ 0 & (a+b)T_2 W^1 & -2T_2 - 2ab(W^2)^T W^2 T_3 & \ldots & 0 & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots & \vdots \\ 0 & 0 & 0 & \ldots & (a+b)T_d W^{d-1} & -2T_d \end{pmatrix}, \tag{13}$$

$$N = \begin{pmatrix} \sum_{k=1}^{n_1} \Lambda_{1k} - \zeta & 0 & \ldots & u \\ 0 & -T_1 & \ldots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ u^T & 0 & \ldots & 0 \end{pmatrix},$$

Remark 4.2. If we expand the matrix inequality derived from the compact neural-network representation in Fazlyab et al. (2019, Theorem 2), we will have exactly the same matrix for network constraints as L (Equation (13)) in the dual program formulation. In other words, we provide a dual optimization interpretation to the compact neural-network representation in LipSDP. With this interpretation, one can extend the SDP to beyond feed-forward structures, such as skip connections (He et al., 2015).

5 Evaluation and discussion

The primary goal of our work is to provide a theoretical framework, and also algorithms for ℓ_∞-FGL estimations on practically used networks. The ℓ_2-FGL can be computed using LipSDP. We have implemented the algorithms using MATLAB (MATLAB, 2021), the CVX toolbox (CVX Research, 2020) and MOSEK solver (ApS, 2019), and name the tool GeoLIP. To validate our theory and the applicability of our algorithms, we want to empirically answer the following research questions:

> **RQ1:** Is GeoLIP better than existing methods in terms of precision and scalability?
>
> **RQ2:** Are the dual SDP programs devised throughout the paper valid?

As we shall see, GeoLIP is indeed better than existing methods in terms of precision and scalability; and the dual SDP programs produce the same values as their natural-SDP-relaxation counterparts.

5.1 Experimental design

To answer **RQ1**, we will run GeoLIP and existing tools that measure the ℓ_∞-FGL on various feed-forward neural networks trained with the MNIST dataset (LeCun and Cortes, 2010). We will record the computed ℓ_∞-FGL to compare the precision, and the computation time to compare the scalability.

Table 1: ℓ_∞-FGL estimation of various methods: DGeoLIP and NGeoLIP induce the same values on two layer networks. DGeoLIP always produces tighter estimations than LiPopt and MP do.

Network	DGeoLIP	NGeoLIP	LiPopt	MP	Sample	BruF
2-layer/16 units	185.18	185.18	259.44	578.54	175.24	175.24
2-layer/256 units	425.04	425.04	1011.65	2697.38	306.98	N/A
8-layer/64 units per layer	8327.2	——	N/A	$8.237 * 10^7$	1130.6	N/A

Table 2: Running time (in seconds) of various tools on ℓ_∞-FGL estimation: DGeoLIP and NGeoLIP are faster than LiPopt. Notice that the running time is implementation and solver-dependent.

Network	DGeoLIP	NGeoLIP	LiPopt	BruF
2-layer/16 units	28.1	22.3	1572	4.8
2-layer/256 units	976.0	70.9	2690	N/A
8-layer/64 units	329.5	——	N/A	N/A

To answer **RQ2**, we will run the natural SDP relaxations for ℓ_p-FGL estimations proposed in Section 3, LipSDP for ℓ_2-FGL estimation, and the dual program Equation (11) for ℓ_∞-FGL on two-layer neural networks, and compare their computed FGLs.

Measurements.   Our main baseline tool is ***LiPopt*** (Latorre et al., 2020), which is an ℓ_∞-FGL estimation tool.[1] Notice that LiPopt is based on the Python Gurobi solver (Gurobi Optimization, LLC, 2022), while we use the MATLAB CVX and MOSEK solver. LiPopt relies on a linear programming (LP) hierarchy for the polynomial optimization problem. We use LiPopt-k to denote the k-th degree of the LP hierarchy. ***BruF*** stands for an brute-force exhaustive enumeration of all possible activation patterns. This is the ground truth for FGL estimations. However, this is an exponential-time search, so we can only run it on networks with a few hidden units. ***Sample*** means that we randomly sample $200, 000$ points in the input space and compute the gradient norm at those points. Notice that this is a lower bound of the true Lipschitz constant, and thus a lower bound of the FGL. ***MP*** stands for the weight-matrix-norm-product method. This is a naive upper bound of FGL. We use ***NGeoLIP*** to denote the natural SDP relaxations devised in Section 3, and ***DGeoLIP*** to denote the dual SDP Equation (12) for ℓ_∞-FGL estimation. Notice that NGeoLIP only applies to two-layer networks.

We use "—" in the result tables to denote that the experimental setting is not in the scope of the tool's application, and "N/A" to denote the computation takes too much time (> 20 hours).

Network setting.   We run the experiments on fully-connected feed-forward neural networks, trained with the MNIST dataset for 10 epochs using the ADAM optimizer (Kingma and Ba, 2017). All the trained networks have accuracy greater than 92% on the test data. For two-layer networks, we use 8, 16, 64, 128, 256 hidden nodes. For multiple-layer networks, we consider 3, 7, 8-layer networks, and each hidden layer has 64 ReLU units. Because MNIST has 10 classes, we report the estimated FGL with respect to label 8 as in Latorre et al. (2020), and the average running time per class: we record the total computation time for all 10 classes from each tool, and report the average time per class.

5.2   Discussion

We present selected results in Tables 1 and 2, and related major discussions here. The full results, more experimental setup and additional discussions can be found in the appendix.

RQ1.   In the experiments of LiPopt, we only used LiPopt-2. In theory, if one can go higher in the LP hierarchy in LiPopt, the result becomes more precise. However, in the case of fully-connected neural networks, using degree-3 in LiPopt is already impractical. For example, on the simplest network that we used, i.e., the single-hidden-layer neural network with 8 hidden units, using LiPopt-3, one ℓ_∞-FGL computation needs at least 200 hours projected by LiPopt. As a result, for all the LiPopt-related

---

[1]Another method was proposed by Chen et al. (2020), however, the code is not available and we are not able to compare it with GeoLIP.

experiments, we were only able to run LiPopt-2. As Latorre et al. (2020) pointed out, the degree has to be at least the depth of the network to compute a valid bound, so we have to use at least LiPopt-k for k-layer networks. LiPopt is unable to handle neural networks with more than two layers because this requires LiPopt with degrees beyond 2. Even if we only consider LiPopt-2 on two-layer networks, the running time is still much higher compared to GeoLIP. This demonstrates the great advantage of GeoLIP in terms of scalability compared with LiPopt. If we compare LiPopt-2 with GeoLIP on two-layer networks from Table 1, it is clear that GeoLIP produces more precise results. For networks with depth greater than 2, we can only compare GeoLIP with the matrix-norm-product method. As we can see from all experiments, GeoLIP's estimation on the FGL is always much lower than MP.

We have also shown that the two-layer network ℓ_∞-FGL estimation from GeoLIP has a theoretical guarantee with the approximation factor $K_G < 1.783$ (Theorem 3.3). If we compare the two-layer network results from GeoLIP and Sampling in Table 1, which is a lower bound of true Lipschitz constant, the ratio is within 1.783. This validates our theoretical claim.

RQ2. In Section 4.1, we have demonstrated the duality between NGeoLIP and LipSDP for the ℓ_2-FGL estimation on two-layer networks, even though the approaches appear drastically different. The experiments show that on two-layer networks, LipSDP and NGeoLIP for ℓ_2-FGL estimations (see the appendix), and DGeoLIP and NGeoLIP for ℓ_∞-FGL estimations produce the same values. These results empirically validate the duality arguments, and also all the related SDP programs.

SDP relaxation. Applying SDP on intractable combinatorial optimization problem was pioneered by the seminal Goemans-Williamson algorithm for the Max-Cut problem (Goemans and Williamson, 1995). For two-layer networks, we have reduced the FGL estimation to the mixed-norm problem, and provide approximation algorithms with ratios compatible with the known optimal constants in the corresponding mixed-norm problem. Improving them can be a very hard task. We also provide a dual SDP interpretation of LipSDP-Neuron. Although Pauli et al. (2022) demonstrated the flaw in LipSDP-Network, our dual SDP interpretation shows that LipSDP-Neuron is correct. In fact, from the dual SDP interpretation, the program is only constrained by the underlying perturbation geometry and the layer-wise restriction from each hidden unit, so the constraints and objective exactly encode the FGL-estimation problem without additional assumptions. Because often the SDP relaxation for intractable problems gives the optimal known algorithms, we conjecture that GeoLIP and LipSDP are also hard to improve on FGL estimations.

Latorre et al. (2020) used polynomial optimization to address the ℓ_∞-FGL estimation. We argue that approaching FGL-estimations from the perspective of polynomial optimization loses the accurate characterization of this problem. For example, for two-layer networks, we have provided constant approximation algorithms to estimate FGLs in both ℓ_∞ and ℓ_2 cases. However, for a general polynomial optimization problem on a cube, we cannot achieve constant approximation. For example, the maximum independent set of a graph can be encoded as a polynomial optimization problem over a cube (Motzkin and Straus, 1965), but the maximum independent set problem cannot be approximated within a constant factor in polynomial time unless $\mathsf{P} = \mathsf{NP}$ (Trevisan, 2004).

6 Related work

Chen et al. (2020) employed polynomial optimization to compute the true Lipschitz constant of ReLU-networks for ℓ_∞-perturbations, and used Lasserre's hierarchy of SDPs (Lasserre, 2001) to solve the polynomial optimization problem. However, their approach is highly tailored to ReLU networks, while ours, like LipSDP, can handle common activations, such as sigmoid and ELU.

Latorre et al. (2020) also proposed to use LiPopt to estimate the local Lipschitz constant. However, estimating this quantity is not the problem studied in our work, and there are tools specifically designed for local perturbations and the Lipschitz constant (Laurel et al., 2022; Zhang et al., 2019).

7 Conclusion

In this work, we have provided a quantitative geometric framework for FGL estimations, and also algorithms for the ℓ_∞-FGL estimation. One important lesson is that when transferring techniques from one perturbations to another ones, we should also transfer the underlying geometry. One future work is to train smooth neural networks using the SDPs proposed in this paper.

References

Aws Albarghouthi. 2021. Introduction to Neural Network Verification. arXiv:2109.10317 [cs.LG]

Noga Alon and Assaf Naor. 2004. Approximating the Cut-Norm via Grothendieck's Inequality. In *Proceedings of the Thirty-Sixth Annual ACM Symposium on Theory of Computing* (Chicago, IL, USA) *(STOC '04)*. Association for Computing Machinery, New York, NY, USA, 72–80. https://doi.org/10.1145/1007352.1007371

MOSEK ApS. 2019. *The MOSEK optimization toolbox for MATLAB manual. Version 9.0.* http://docs.mosek.com/9.0/toolbox/index.html

Aharon Ben-Tal and Arkadi Nemirovski. 2001. *Lectures on Modern Convex Optimization*. Society for Industrial and Applied Mathematics. https://doi.org/10.1137/1.9780898718829 arXiv:https://epubs.siam.org/doi/pdf/10.1137/1.9780898718829

Vijay Bhattiprolu, Mrinalkanti Ghosh, Venkatesan Guruswami, Euiwoong Lee, and Madhur Tulsiani. 2018. Inapproximability of Matrix $p \to q$ Norms. arXiv:1802.07425 [cs.CC]

Mark Braverman, Konstantin Makarychev, Yury Makarychev, and Assaf Naor. 2011. The Grothendieck Constant is Strictly Smaller than Krivine's Bound. In *2011 IEEE 52nd Annual Symposium on Foundations of Computer Science*. 453–462. https://doi.org/10.1109/FOCS.2011.77

Jop Briët, Oded Regev, and Rishi Saket. 2017. Tight Hardness of the Non-Commutative Grothendieck Problem. *Theory of Computing* 13, 15 (2017), 1–24. https://doi.org/10.4086/toc.2017.v013a015

Sebastien Bubeck and Mark Sellke. 2021. A Universal Law of Robustness via Isoperimetry. In *Advances in Neural Information Processing Systems*, A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (Eds.). https://openreview.net/forum?id=z71OSKqTFh7

Tong Chen, Jean B Lasserre, Victor Magron, and Edouard Pauwels. 2020. Semialgebraic Optimization for Lipschitz Constants of ReLU Networks. In *Advances in Neural Information Processing Systems*, H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (Eds.), Vol. 33. Curran Associates, Inc., 19189–19200. https://proceedings.neurips.cc/paper/2020/file/dea9ddb25cbf2352cf4dec30222a02a5-Paper.pdf

Djork-Arné Clevert, Thomas Unterthiner, and Sepp Hochreiter. 2016. Fast and Accurate Deep Network Learning by Exponential Linear Units (ELUs). *arXiv: Learning* (2016).

Jeremy M Cohen, Elan Rosenfeld, and J. Zico Kolter. 2019. Certified Adversarial Robustness via Randomized Smoothing. arXiv:1902.02918 [cs.LG]

Inc. CVX Research. 2020. CVX: Software for Disciplined Convex Programming, Version 2.2, Build 1148. http://cvxr.com/cvx.

Mahyar Fazlyab, Alexander Robey, Hamed Hassani, Manfred Morari, and George Pappas. 2019. Efficient and Accurate Estimation of Lipschitz Constants for Deep Neural Networks. In *Advances in Neural Information Processing Systems*, H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (Eds.), Vol. 32. Curran Associates, Inc. https://proceedings.neurips.cc/paper/2019/file/95e1533eb1b20a97777749fb94fdb944-Paper.pdf

Michel X. Goemans and David P. Williamson. 1995. Improved Approximation Algorithms for Maximum Cut and Satisfiability Problems Using Semidefinite Programming. *J. ACM* 42, 6 (nov 1995), 1115–1145. https://doi.org/10.1145/227683.227684

Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. 2015. Explaining and Harnessing Adversarial Examples. arXiv:1412.6572 [stat.ML]

A. Grothendieck. 1956. Résumé de la théorie métrique des produits tensoriels topologiques. Bol. Soc. Mat. São Paulo 8, 1-79 (1956)..

Gurobi Optimization, LLC. 2022. Gurobi Optimizer Reference Manual. https://www.gurobi.com

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2015. Deep Residual Learning for Image Recognition. https://doi.org/10.48550/ARXIV.1512.03385

Matthias Hein and Maksym Andriushchenko. 2017. Formal Guarantees on the Robustness of a Classifier against Adversarial Manipulation. In *Proceedings of the 31st International Conference on Neural Information Processing Systems* (Long Beach, California, USA) *(NIPS'17)*. Curran Associates Inc., Red Hook, NY, USA, 2263–2273.

Yujia Huang, Huan Zhang, Yuanyuan Shi, J Zico Kolter, and Anima Anandkumar. 2021. Training Certifiably Robust Neural Networks with Efficient Local Lipschitz Bounds. *NeurIPS* (2021).

Matt Jordan and Alexandros G Dimakis. 2020. Exactly Computing the Local Lipschitz Constant of ReLU Networks. In *Advances in Neural Information Processing Systems*, H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (Eds.), Vol. 33. Curran Associates, Inc., 7344–7353. https://proceedings.neurips.cc/paper/2020/file/5227fa9a19dce7ba113f50a405dcaf09-Paper.pdf

Guy Katz, Clark Barrett, David L. Dill, Kyle Julian, and Mykel J. Kochenderfer. 2017. Reluplex: An Efficient SMT Solver for Verifying Deep Neural Networks. In *Computer Aided Verification*, Rupak Majumdar and Viktor Kunčak (Eds.). Springer International Publishing, Cham, 97–117.

Subhash Khot. 2002. On the Power of Unique 2-Prover 1-Round Games. In *Proceedings of the Thiry-Fourth Annual ACM Symposium on Theory of Computing* (Montreal, Quebec, Canada) *(STOC '02)*. Association for Computing Machinery, New York, NY, USA, 767–775. https://doi.org/10.1145/509907.510017

Diederik P. Kingma and Jimmy Ba. 2017. Adam: A Method for Stochastic Optimization. arXiv:1412.6980 [cs.LG]

J.L Krivine. 1979. Constantes de Grothendieck et fonctions de type positif sur les sphères. *Advances in Mathematics* 31, 1 (1979), 16–30. https://doi.org/10.1016/0001-8708(79)90017-3

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E. Hinton. 2012. Imagenet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems*.

Jean B. Lasserre. 2001. Global Optimization with Polynomials and the Problem of Moments. *SIAM Journal on Optimization* 11, 3 (2001), 796–817. https://doi.org/10.1137/S1052623400366802 arXiv:https://doi.org/10.1137/S1052623400366802

Jean Bernard Lasserre. 2015. *An Introduction to Polynomial and Semi-Algebraic Optimization*. Cambridge University Press. https://doi.org/10.1017/CBO9781107447226

Fabian Latorre, Paul Rolland, and Volkan Cevher. 2020. Lipschitz constant estimation of Neural Networks via sparse polynomial optimization. In *International Conference on Learning Representations*. https://openreview.net/forum?id=rJe4_xSFDB

Jacob Laurel, Rem Yang, Gagandeep Singh, and Sasa Misailovic. 2022. A Dual Number Abstraction for Static Analysis of Clarke Jacobians. *Proc. ACM Program. Lang.* 6, POPL, Article 56 (jan 2022), 30 pages. https://doi.org/10.1145/3498718

Yann LeCun and Corinna Cortes. 2010. MNIST handwritten digit database. http://yann.lecun.com/exdb/mnist/. (2010). http://yann.lecun.com/exdb/mnist/

Klas Leino, Zifan Wang, and Matt Fredrikson. 2021. Globally-Robust Neural Networks. In *International Conference on Machine Learning (ICML)*.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. 2019. Towards Deep Learning Models Resistant to Adversarial Attacks. arXiv:1706.06083 [stat.ML]

MATLAB. 2021. *9.11.0.1837725 (R2021b) Update 2*. The MathWorks Inc., Natick, Massachusetts.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013. Distributed Representations of Words and Phrases and Their Compositionality. In *Proceedings of the 26th International Conference on Neural Information Processing Systems - Volume 2* (Lake Tahoe, Nevada) *(NIPS'13)*. Curran Associates Inc., Red Hook, NY, USA, 3111–3119.

T. S. Motzkin and E. G. Straus. 1965. Maxima for Graphs and a New Proof of a Theorem of Turán. *Canadian Journal of Mathematics* 17 (1965), 533–540. `https://doi.org/10.4153/CJM-1965-053-6`

Vinod Nair and Geoffrey E. Hinton. 2010. Rectified Linear Units Improve Restricted Boltzmann Machines. In *Proceedings of the 27th International Conference on International Conference on Machine Learning* (Haifa, Israel) *(ICML'10)*. Omnipress, Madison, WI, USA, 807–814.

Assaf Naor. 2013. Quantitative geometry. *Proceedings of the National Academy of Sciences* 110, 48 (2013), 19202–19205. `https://doi.org/10.1073/pnas.1320388110` arXiv:https://www.pnas.org/content/110/48/19202.full.pdf

Yu Nesterov. 1998. Semidefinite relaxation and nonconvex quadratic optimization. *Optimization Methods and Software* 9, 1-3 (1998), 141–160. `https://doi.org/10.1080/10556789808805690` arXiv:https://doi.org/10.1080/10556789808805690

Nicolas Papernot, Patrick McDaniel, Somesh Jha, Matt Fredrikson, Z. Berkay Celik, and Ananthram Swami. 2015. The Limitations of Deep Learning in Adversarial Settings. arXiv:1511.07528 [cs.CR]

Patricia Pauli, Anne Koch, Julian Berberich, Paul Kohler, and Frank Allgöwer. 2022. Training Robust Neural Networks Using Lipschitz Bounds. *IEEE Control Systems Letters* 6 (2022), 121–126. `https://doi.org/10.1109/LCSYS.2021.3050444`

Prasad Raghavendra and David Steurer. 2009. Towards Computing the Grothendieck Constant. In *Proceedings of the Twentieth Annual ACM-SIAM Symposium on Discrete Algorithms* (New York, New York) *(SODA '09)*. Society for Industrial and Applied Mathematics, USA, 525–534.

Aditi Raghunathan, Jacob Steinhardt, and Percy Liang. 2018. Certified Defenses against Adversarial Examples. In *International Conference on Learning Representations*. `https://openreview.net/forum?id=Bys4ob-Rb`

Kevin Scaman and Aladin Virmaux. 2018. Lipschitz Regularity of Deep Neural Networks: Analysis and Efficient Estimation. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems* (Montréal, Canada) *(NIPS'18)*. Curran Associates Inc., Red Hook, NY, USA, 3839–3848.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. 2014. Intriguing properties of neural networks. arXiv:1312.6199 [cs.CV]

Luca Trevisan. 2004. Inapproximability of Combinatorial Optimization Problems. arXiv:cs/0409043 [cs.CC]

Zi Wang, Aws Albarghouthi, Gautam Prakriya, and Somesh Jha. 2022. Interval Universal Approximation for Neural Networks. *Proc. ACM Program. Lang.* 6, POPL, Article 14 (jan 2022), 29 pages. `https://doi.org/10.1145/3498675`

Huan Zhang, Pengchuan Zhang, and Cho-Jui Hsieh. 2019. RecurJac: An Efficient Recursive Algorithm for Bounding Jacobian Matrix of Neural Networks and Its Applications. arXiv:1810.11783 [stat.ML]