Uncertainty-Driven Pessimistic Q-Ensemble for Offline-to-Online Reinforcement Learning

Abstract

Re-using existing offline reinforcement learning (RL) agents is an emerging topic for reducing the dominant computational cost for exploration in many settings. To effectively fine-tune the pre-trained offline policies, both offline samples and online interactions may be leveraged. In this paper, we propose the idea of incorporating a pessimistic Q-ensemble and an uncertainty quantification technique to effectively fine-tune offline agents. To stabilize online Q-function estimates during fine-tuning, the proposed method uses uncertainty estimation as a penalization for a replay buffer with a mixture of online interactions from the ensemble agent and offline samples from the behavioral policies. In various robotic tasks on D4RL benchmark, we show that our method outperforms the state-of-the-art algorithms in terms of the average return and the sample efficiency.

1 Motivation

Deep offline reinforcement learning (RL) [9] utilizes deep neural networks trained from previously collected offline datasets to learn powerful robotic agents without additional environmental interactions. Recently, offline RL methods [4, 6, 1, 11, 7] often perform better than the behavioral policies which produce the offline datasets. Offline RL agents, however, may perform suboptimally when the offline datasets follow possibly suboptimal behavioral policies. This requires further online learning (fine-tuning) from additional online interactions generated by offline RL agents.

To fine-tune an offline RL agent, slightly modified off-policy RL methods may be used by leveraging both online and offline samples in training. However, such modification is typically difficult to improve performance due to distributional shift. Fine-tuning an agent trained solely on an offline dataset may yield inaccurate value estimates due to online visitation of out-of-distribution (OOD) state-action samples. This problem accumulates a bootstrapping error and leads to a significant performance drop.

To address this problem, offline-to-online RL (Off2OnRL [8]) leverages a pessimistic Q-ensemble scheme. Off2OnRL pessimistically trains multiple Q-functions to mitigate such bootstrapping error caused by the distributional shift. This constrains the learning policy to visit near the distribution of the behavioral policy to stabilize fine-tuning an offline RL agent. Off2OnRL also introduced a prioritized buffer with balanced replay, which contains not only online interactions collected during fine-tuning but near-on-policy samples from the offline dataset. This scheme enables accurate Q-function estimation by training a network for prioritizing offline samples, which can bring the sampling distribution for Q-functions close to online samples.

However, we find that the balanced replay method tends to be affected by uncertainty estimation since it has online and offline samples generated by various policies. It may suffer from high uncertainty

35 when 1) the network for the balanced replay is not trained sufficiently and 2) the offline dataset tends
36 to be diverse around several trajectories produced by multiple policies.

37 To this end, we introduce an uncertainty-driven pessimistic Q-ensemble (UPQ) for offline-to-online
38 RL. We adopt a pessimistic ensemble of offline actor-critic agents to guide the learning policy with
39 an efficient pessimism. To stabilize online Q-function estimates during fine-tuning, the proposed
40 method leverages uncertainty quantification as a penalization for a prioritized replay buffer where
41 online samples from the ensemble agent and offline samples from the behavioral policy exist together.

2   Methodology

43 We consider a Markov Decision Process (MDP) tuple $\mathcal{G} = (\mathcal{S}, \mathcal{A}, r, \mathbb{P})$ defined by the state space $\mathcal{S}$,
44 the action space $\mathcal{A}$, the reward function r, and the transition distribution $\mathbb{P}$. The objective of an RL
45 agent is to maximize the expected return $\mathbb{E}[\sum_{i=0}^{T-1} \gamma^i r_i]$, where $\gamma \in [0, 1)$ is the discount factor and
46 T is the episode horizon (total number of an episode) that the agent optimizes over.

47 In our proposed method, we use N offline actor-critic agents $\{Q_{\theta_i}, \pi_{\phi_i}\}_{i \in [N]}$ for an ensemble from
48 Off2OnRL [8], where θ_i and ϕ_i are defined as the parameters of the i agent's critic and actor,
49 respectively. We define the Q-function and the policy of the ensemble as follows:

$$Q_\theta^E(s, a) := \frac{1}{N} \sum_{i=1}^N Q_{\theta_i}(s, a), \tag{1}$$

$$\pi_\phi^E(\cdot|s) = \mathcal{N}\left(\frac{1}{N} \sum_{i=1}^N \mu_{\phi_i}(s), \quad \frac{1}{N} \sum_{i=1}^N \left(\sigma_{\phi_i}^2(s) + \mu_{\phi_i}^2(s) \right) - \mu_\phi^2(s) \right), \tag{2}$$

50 where the parameters are defined as $\theta := \{\theta_i\}_{i \in [N]}$ and $\phi := \{\phi_i\}_{i \in [N]}$, respectively. The defined
51 π_ϕ^E follows a normal distribution with mean and variance of the Gaussian mixture $\frac{1}{N} \sum_{i=1}^N \pi_{\phi_i}$ for
52 parameterization. The modeled policy is the same as Off2OnRL [8].

53 Since the ensemble estimates the posterior distribution of its Q-functions, we use the standard
54 deviation-based uncertainty quantification technique proposed in Pessimistic Bootstrapping for
55 offline RL (PBRL [2]). The uncertainty estimation at (s', a') of the target Q-functions is defined as
56 follows:

$$\mathcal{U}_{\theta-}(s', a') := \sigma(Q_{\theta_{i-}}(s', a')) = \sqrt{\frac{1}{N} \sum_{i=1}^N \left(Q_{\theta_{i-}}(s', a') - Q_{\theta-}^E(s', a') \right)^2}, \tag{3}$$

57 where we denote the mean over the ensemble of the target Q-functions by $Q_{\theta-}^E$. In policy evaluation,
58 we use such uncertainty quantification as a penalization to the next Q-value for a mixture of online
59 and offline samples from the prioritized replay buffer $\mathcal{B}$ proposed in Off2OnRL. The Q^E of the
60 ensemble agent is updated through pessimistic Q-function updates by fitting the following target for
61 state-action pairs sampled from $\mathcal{B}$:

$$\mathcal{T} Q_\theta^E(s, a) := r(s, a) + \gamma \mathbb{E}_{a' \sim \pi_\phi^E} \left[Q_{\theta-}^E(s', a') - \alpha \log \pi_\phi^E(a'|s') - \beta \mathcal{U}_{\theta-}(s', a') \right], \tag{4}$$

62 where β is the hyperparameter for the uncertainty penalization. To this end, the parameters of the
63 Q-network and the policy of the ensemble agent, θ and ϕ, are updated by minimizing the following
64 objectives, respectively:

$$\mathcal{L}_{Critic}(\theta) = \mathbb{E}_{(s,a,s') \sim \mathcal{B}} \left[\left(Q_\theta^E(s, a) - \mathcal{T} Q_\theta^E(s, a) \right)^2 \right], \tag{5}$$

$$\mathcal{L}_{Actor}(\phi) = \mathbb{E}_{s \sim \mathcal{B}, a \sim \pi_\phi^E} \left[\alpha \log \pi_\phi^E(a|s) - Q_\theta^E(s, a) \right], \tag{6}$$

Figure 1: Illustration of the overall architecture of the proposed method with a pessimistic Q-ensemble and uncertainty quantification. Our method calculates the Q-target $\mathcal{T}Q^E$ and the corresponding uncertainty $\mathcal{U}$ by using the ensemble of the N offline agents pre-trained from the offline dataset to update the gradients.

where α is the parameter for temperature.

Figure 1 illustrates the overall workflow of the proposed method with uncertainty quantification. The learning Q-function and policy are updated via update rules (5) and (6) by fine-tuning the pre-trained multiple ensemble agents.

3   Experimental Setup and Result

We use the D4RL benchmark [3], which includes datasets for data-driven deep reinforcement learning. To demonstrate the performance of our method, three Mujoco [10] locomotion tasks (HalfCheetah, Walker2d, and Hopper) are adopted with four types of datasets (random, medium, medium-replay, medium-expert) for comparative evaluation. Specifically, the random dataset has collections by a random policy and the medium dataset contains samples from a medium-level policy trained via Soft Actor-Critic (SAC [5]). The medium-replay dataset contains all samples observed during training a medium-level policy and the medium-expert dataset consists of samples recorded by both a medium-level agent and expert demonstrations. We use a total of 12 task setups with the 'v2' version datasets.

We compare the proposed method with several baseline algorithms including CQL [7] and Off2OnRL [8]. CQL provides a good baseline for the performance of an offline approach, which is also used for learning both Off2OnRL and our method. The implementation of CQL and Off2OnRL are adopted from the official implementation at `https://github.com/aviralkumar2907/CQL` and `https://github.com/shlee94/Off2OnRL`, respectively. We fix most of the hyperparameters for our method the same as the official Off2OnRL implementation. We train $N = 4$ CQL agents for 1000 epochs with different seeds for all the locomotion tasks where we experiment. Off2onRL and our method are trained for 200 epochs using the pre-trained CQL agents. In our method, the parameter for uncertainty penalization β is varied from $[0.1, 0.01, 0.001]$.

Table 1 reports the performance of our method and baseline algorithms for each task. UPQ performs similarly or better than the baseline methods in most of the tasks in terms of the average return and sample efficiency. We find that UPQ has advantages in the tasks with non-optimal datasets marked as medium, medium-replay, and medium-expert. The experiments show that UPQ performs the best with $\beta \in [0.01, 0.001]$ in many tasks. Figure 2 illustrates the training curves for UPQ and baseline algorithms in all tasks. We remark that the performance of UPQ shows more stable training curves in the early stage (especially $50000 - 100000$ environmental steps) of fine-tuning in most of the tasks.

Table 1: Average returns for all algorithms in Mujoco locomotion tasks. The highest average return values are highlighted.

		CQL	Off2onRL	UPQ $\beta = 0.1$	UPQ $\beta = 0.01$	UPQ $\beta = 0.001$
Random	HalfCheetah	2455.2	11474.5	11068.6	11172.4	11280.5
	Hopper	323.5	3213	945.3	2622.6	2967.8
	Walker2d	372.2	2706.1	2224.1	3190.8	2759.2
Medium	HalfCheetah	5171.1	10049.7	10364.9	10847.9	10668.2
	Hopper	1973.4	3279.7	3416.8	3361.3	3424.1
	Walker2d	3288.4	4638.5	4356.5	4736.9	4971.2
Medium Replay	HalfCheetah	5214	10413.4	10118.3	10600.4	10313.2
	Hopper	1698.8	3521.6	3195.2	3206.7	3440.4
	Walker2d	3142.1	4760.9	4505.2	4750.9	5100.2
Medium Expert	HalfCheetah	1158.8	11159.0	11261.2	11277.9	11353.4
	Hopper	1272.1	2531.3	2201.1	2594.8	3423.4
	Walker2d	3675	5181.8	5525.7	5682.6	5446

Figure 2: Training curves of all algorithms in Mujoco locomotion tasks.

4 Conclusion

In this work, we propose UPQ with an uncertainty-driven pessimistic Q-ensemble and it is effective for improving offline-to-online RL methods. To stabilize online Q-function estimates during fine-tuning, the proposed method leverages uncertainty quantification as a penalization for a prioritized replay buffer consisting of both online and offline samples. Our experiments show that UPQ outperforms several baselines over robotic locomotion tasks in terms of the average return and the sample efficiency. We expect that our method enables sample-efficient re-use of the existing offline agents and offline datasets. We also expect to implement further improvements as future work.

References

[1] Rishabh Agarwal, Dale Schuurmans, and Mohammad Norouzi. An optimistic perspective on offline reinforcement learning. In *International Conference on Machine Learning*, 2020.

[2] Chenjia Bai, Lingxiao Wang, Zhuoran Yang, Zhi-Hong Deng, Animesh Garg, Peng Liu, and Zhaoran Wang. Pessimistic bootstrapping for uncertainty-driven offline reinforcement learning. In *International Conference on Learning Representations*, 2022.

[3] Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning, 2020.

[4] Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In *Proceedings of the 36th International Conference on Machine Learning*, pages 2052–2062, 2019.

[5] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. 2017.

[6] Aviral Kumar, Justin Fu, Matthew Soh, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. In *Advances in Neural Information Processing Systems*, 2019.

[7] Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 1179–1191, 2020.

[8] Seunghyun Lee, Younggyo Seo, Kimin Lee, Pieter Abbeel, and Jinwoo Shin. Offline-to-online reinforcement learning via balanced replay and pessimistic q-ensemble. In *Conference on Robot Learning*, pages 1702–1712, 2022.

[9] Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

[10] Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 5026–5033, 2012.

[11] Tianhe Yu, Garrett Thomas, Lantao Yu, Stefano Ermon, James Y Zou, Sergey Levine, Chelsea Finn, and Tengyu Ma. Mopo: Model-based offline policy optimization. In *Advances in Neural Information Processing Systems*, pages 14129–14142, 2020.