Directional Message Passing on Molecular Graphs via Synthetic Coordinates

Abstract

Graph neural networks that leverage coordinates via directional message passing have recently set the state of the art on multiple molecular property prediction tasks. However, they rely on atom position information that is often unavailable, and obtaining it is usually prohibitively expensive or even impossible. In this paper we propose synthetic coordinates that enable the use of advanced GNNs without requiring the true molecular configuration. We propose two distances as synthetic coordinates: Graph-based distances based on a symmetric variant of personalized PageRank, and distance bounds that specify the rough range of molecular configurations. To leverage both distance and angular information we propose a method of transforming normal graph neural networks into directional MPNNs. We show that with this transformation we can reduce the error of a normal graph neural network by 49% on ZINC. We furthermore set the state of the art on ZINC and coordinate-free QM9 by incorporating synthetic coordinates in the SMP and DimeNet^{++} models.

1 Introduction

Graph neural networks (GNNs) have set the state of the art on many tasks of molecular machine learning, such as the prediction of quantum mechanical properties (Gilmer et al., 2017), solubility (Wu et al., 2018), or the generation of new molecules (Jin et al., 2020). Thanks to their fast inference time, good generalization and scalability, GNNs are thus promising to revolutionize large parts of chemistry, from ab-initio quantum mechanical simulations and reaction kinetics to synthesis planning and drug discovery. Atom positions are central to many of these tasks, but unavailable in most cases. Many tasks in chemistry instead use a more coarse-grained representation: The molecular graph. Unfortunately, this representation makes many predictive tasks substantially harder, and GNNs have performed significantly better when they have access to the exact molecular configuration (Gilmer et al., 2017). Missing atom positions furthermore precludes the use of many advanced GNNs that were developed with coordinates in mind.

In this work we aim to fill in this information with well-defined coordinates constructed purely from the molecular graph. A molecular configuration is fully specified by the pairwise distances between all atoms, due to rotational, translational, and reflectional invariance. We can thus obtain a molecular geometry from any method that provides pairwise distances between atoms. Since directional message passing does not require the full molecular geometry, these distances do not need to correspond to an actual three-dimensional configuration. We leverage this generality by using

Figure 1: Illustration of transforming a regular molecular graph (ethanol) to a line graph with synthetic coordinates. We first calculate all (bounds of) pairwise distances using our synthetic coordinates. We then calculate the (bounds of) distances and angles for the molecular graph. Finally, we convert the molecular graph to its line graph and embed the distances and angles as features. This process allows us to convert a regular GNN to a directional MPNN, which improves its accuracy and allows incorporating angular information.

purely graph-based distances calculated from a symmetric variant of personalized PageRank (PPR). This distance performs surprisingly well, despite incorporating no chemical knowledge.

We furthermore show that using regular approximation methods for generating atom positions often does not benefit model performance, due to the fundamental ambiguity of molecular configurations. The energy landscape of molecules can have multiple local minima, and a molecule can be in multiple different minima, known as conformers. We propose to circumvent this problem by incorporating the conformational ambiguity via empirical distance *bounds*. Instead of yielding a potentially wrong configuration, these bounds only estimate the range of viable molecular geometries. They are thus valid regardless of which state the molecule was in when generating the data. Both the symmetric PPR distance and the distance bounds require no hand-tuning and can be calculated efficiently, even for large molecules.

We leverage these two variants of *synthetic coordinates* to transform regular GNNs into directional message passing, as illustrated in Fig. 1. We first calculate the synthetic, pairwise distances for the given molecular graph. Based on these, we calculate the edge distances and angles between edges. Finally, we compute the molecule's line graph. Executing a GNN on the line graph improves its expressivity (Garg et al., 2020) and allows us to incorporate angular information. We use the original node and edge attributes together with the distances as node attributes, and the obtained angles as edge attributes. The GNN is then executed on this featurized line graph instead of the original graph. Our experiments show this transformation can significantly improve the performance of the underlying GNN, across multiple models and datasets. Incorporating synthetic coordinates reduces the error of a GNN by 49%, putting it on par with the current state of the art. Our enhanced version of the SMP model (Vignac et al., 2020) improves upon the current state of the art on ZINC by 7%, and DimeNet^{++} (Klicpera et al., 2020b) with synthetic coordinates outcompetes previous methods on coordinate-free QM9 by 20%. In summary, our core contributions are:

- Well-defined synthetic coordinates based on node distances and simple molecular bounds, which significantly improve the performance of GNNs for molecules.
- A general scheme of converting a normal GNN into a directional MPNN, which can improve performance and allows incorporating both distance and angular information.

2 Directional message passing

Graph neural networks. To use GNNs for molecules we represent them as graphs $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, where the atoms define the node set $\mathcal{V}$ and the interactions the edge set $\mathcal{E}$. These interactions are usually the bonds of the molecular graph, but they can also be all atoms pairs within a given cutoff

of e.g. $5\,\text{Å}$. In this work we focus on an extension of message passing neural networks (MPNNs) (Gilmer et al., 2017). MPNNs embed each atom u separately as $\boldsymbol{h}_u \in \mathbb{R}^H$, and can additionally use interaction embeddings $\boldsymbol{e}_{(uv)} \in \mathbb{R}^{H_e}$. These embeddings are updated in each layer using messages passed between neighboring nodes, starting with the atom features $\boldsymbol{h}_u^{(0)} = \boldsymbol{x}_u^{(\mathcal{V})}$ (e.g. its type) and the interaction features $\boldsymbol{e}_{(uv)}^{(0)} = \boldsymbol{x}_{(uv)}^{(\mathcal{E})}$ (e.g. the bond type or a distance representation). Extended MPNNs can be expressed via the following two equations:

$$\boldsymbol{h}_u^{(l+1)} = f_{\text{update}}(\boldsymbol{h}_u^{(l)}, \underset{v \in \mathcal{N}_u}{\text{Agg}} [f_{\text{msg}}(\boldsymbol{h}_u^{(l)}, \boldsymbol{h}_v^{(l)}, \boldsymbol{e}_{(uv)}^{(l)})]), \tag{1}$$

$$\boldsymbol{e}_{(uv)}^{(l+1)} = f_{\text{edge}}(\boldsymbol{h}_u^{(l+1)}, \boldsymbol{h}_v^{(l+1)}, \boldsymbol{e}_{(uv)}^{(l)}). \tag{2}$$

The atom and interaction update functions f_{node} and f_{edge} and the message function f_{msg} are learnable functions, such as simple linear layers or arbitrarily complex neural networks. The aggregation Agg over the atom's neighbors $\mathcal{N}_u$ is usually a simple summation.

Line graph. The directed line graph $\mathcal{L}(\mathcal{G}) = (\mathcal{V}_\mathcal{L}, \mathcal{E}_\mathcal{L})$ expresses the adjacencies between the directed edges in $\mathcal{G}$. Its nodes are the directed edges of the original graph $\mathcal{V}_\mathcal{L} = \{(u, v) \mid u \in \mathcal{V}, v \in \mathcal{N}_u\}$. For undirected graphs like molecular graphs, every undirected edge $\{u, v\}$ is split into two directed edges (u, v) and (v, u). Two nodes in $\mathcal{L}(\mathcal{G})$ are connected if the corresponding edges in $\mathcal{G}$ share a node, i.e. $\mathcal{E}_\mathcal{L} = \{((u, v), (v, w)) \mid (u, v), (v, w) \in \mathcal{V}_\mathcal{L}\}$. We obtain node features for the line graph by embedding the original node and edge features as $\boldsymbol{x}_{(uv)}^{(\mathcal{V}_\mathcal{L})} = f_{\text{emb}}(\boldsymbol{x}_u^{(\mathcal{V})}, \boldsymbol{x}_v^{(\mathcal{V})}, \boldsymbol{x}_{(uv)}^{(\mathcal{E})})$. The line graph can furthermore incorporate additional features for atom triplets as edge features $\boldsymbol{x}_{(uvw)}^{(\mathcal{E}_\mathcal{L})}$, such as the angle between bonds or interactions.

Directional message passing. Directional MPNNs improve upon regular MPNNs in two ways. First, they embed the directed messages instead of the nodes in the graph, essentially operating on the directed line graph. Models using only this first step are also known as directed MPNNs or line graph neural networks (Dai et al., 2016; Yang et al., 2019; Chen et al., 2019). Directed MPNNs are strictly more expressive than regular MPNNs (Morris et al., 2020). We can transform any MPNN to a directed MPNN simply by executing it on the directed line graph instead of the original graph. Second, for graphs with nodes that are embedded in an inner product space (such as molecules in 3D space) the directed edges correspond to directions in that space, via $\boldsymbol{x}_{(uv)}^{(\mathcal{V}_\mathcal{L})} = \boldsymbol{x}_u^{(\mathcal{V})} - \boldsymbol{x}_v^{(\mathcal{V})}$. Directional MPNNs leverage this connection to better represent the molecular configuration, usually by using the angles in $\boldsymbol{x}_{(uvw)}^{(\mathcal{E}_\mathcal{L})}$ (Klicpera et al., 2020b). To fully leverage both aspects of directional MPNNs we therefore need some form of coordinates.

Expressivity of GNNs. A central limitation of GNNs is their inability of distinguishing between certain non-isomorphic graphs. For example, GNNs are not able to distinguish between a hexagon and two triangles if all nodes and edges have the same features. More specifically, Xu et al. (2019); Morris et al. (2019) have shown that GNNs are only as powerful as the 1-Weisfeiler-Lehman (WL) test of isomorphism. While it is still possible to construct indistinguishable examples for directional MPNNs, this is significantly more difficult (Garg et al., 2020). Dym & Maron (2021) have shown that MPNNs using SO(3) group representations and atom positions are even universal, i.e. able to approximate any continuous function to arbitrary precision. This demonstrates that coordinates can alleviate and even solve this central limitation of GNNs.

3 Molecular configurations

To prevent any pitfalls when constructing synthetic coordinates for GNNs based on chemical knowledge we first need to consider the properties of atomic positions in a molecule and how they are normally obtained. At first glance these positions might seem like an obvious and straightforward property. However, molecular configurations are actually ambiguous and difficult to obtain, even for small molecules. This misconception has even led some works to suggest semi-supervised learning methods leveraging positions, effectively treating them as abundant input features (Hao et al., 2020).

To clarify this we will next describe the complexity behind molecular configurations and how to approximate them efficiently.

Finding molecular configurations. The atoms of a molecule can in principle be at any arbitrary position. However, most of these configurations will lead to an extremely high energy and are thus very unlikely to be observed in nature. A molecular configuration therefore usually refers to the atom positions at or close to equilibrium, i.e. at the molecule's energy minimum. To find these positions we have to search the molecule's energy landscape and solve a non-convex optimization problem. This is in fact a bilevel optimization problem, where the atom positions are optimized in the outer and the electron wavefunctions in the inner task. These wave functions can then be ignored in the outer task; they only influence the energy and the forces $\boldsymbol{F}_i = -\frac{\partial E}{\partial \boldsymbol{x}_i}$ acting on each atomic nucleus. We can then use these forces for gradient-based optimization, and avoid saddle points by using quasi-Newton methods.

Difficulties. The above optimization process is very expensive due to the quantum mechanical (QM) computations required for optimizing the electron wavefunction at each gradient step. It is orders of magnitude more expensive than calculating the energy of a *given* molecular configuration, since we calculate the energy's gradient during each optimization step. Furthermore, the optimization will only converge to a local, and not the global minimum. The global minimum is actually not the only state of interest — *any* reasonably low local minimum of the energy landscape is a valid configuration, known as a conformer. A molecule thus does not have a unique configuration; it can be in any of these states. Their statistical distribution and the interaction between them is central for many molecular properties. This ambiguity of atom positions poses a fundamental limit on how precise molecular predictions can be without knowing the exact (ensemble of) configurations. For example, without knowing the molecule's conformer we can not reasonably predict its energy at a precision below roughly $60\,\mathrm{meV}$ (Grimme, 2019) — except for small, rigid molecules that do not have multiple conformers (e.g. Benzol).

Approximating energies and forces. The most prominent way of accelerating the process of finding a valid molecular configuration is by approximating its most expensive part: The quantum mechanical optimization of the electron wavefunction. There is a large hierarchy of methods with various runtime versus accuracy trade-offs (Folmsbee & Hutchison, 2021). The cheapest class of methods are force fields. They allow running molecular dynamics simulations with millions of atoms, and can estimate the equilibrium structure of a small molecule in less than one second. Force fields approximate the quantum-mechanical interactions via a closed-form, differentiable function that only depends on the atom positions. For example, the Merck Molecular Force Field (MMFF94) (Halgren, 1996) defines the energy via the sum

$$
\begin{aligned}
E_{\mathrm{MMFF94}} = \sum_{ij} E_{\mathrm{B},ij} + \sum_{ijk} E_{\mathrm{A},ijk} + \sum_{ijk} E_{\mathrm{BA},ijk} \\
+ \sum_{ijkl} E_{\mathrm{OOP},ijkl} + \sum_{ijkl} E_{\mathrm{T},ijkl} + \sum_{ij} E_{\mathrm{VdW},ij} + \sum_{ij} E_{\mathrm{Q},ij},
\end{aligned}
\tag{3}
$$

where the indices specify atoms, E_{B} defines bond stretching, E_{A} angle bending, E_{BA} stretch-bend, E_{OOP} out-of-plane bending, E_{T} torsion, E_{VdW} Van der Waals, and E_{Q} electrostatic interactions. Each of these terms is approximated using an analytic equation with empirically chosen coefficients that depend on the involved atom types. Forces are again obtained via the analytical gradients $\boldsymbol{F}_i = -\frac{\partial E}{\partial \boldsymbol{x}_i}$, and conformers via gradient-based optimization. Generating configurations with force fields is fast enough to even generate a large ensemble of conformers. However, the resulting conformers are highly biased and require corrections based on expensive QM-based methods for reasonably approximating the molecule's true distribution (Ebejer et al., 2012; Kanal et al., 2018).

Directly predicting the configuration. There are multiple methods that circumvent the optimization process to quickly generate low-energy conformers for a given molecular graph. Distance geometry methods generate conformers using an experimental database of ideal bond lengths, bond angles, and torsional angles (Havel, 2002). The ETKDG method combines this with empirical torsional

angle preferences (Riniker & Landrum, 2015). Multiple machine learning methods for generating conformers have also recently been proposed (Weinreich et al., 2021; Lemm et al., 2021).

Restrictions for ML. All of the above methods yield reasonable molecular configurations. However, they often require many initializations and a considerable amount of hand-tuning to yield a good result for every molecule in a dataset. Furthermore, the obtained conformer might not even be the correct one for the data of interest. The data could have been generated by a different conformer or by a statistical ensemble of multiple conformers. The configuration of a wrong conformer can cause our model to overfit the false training data and lead to bad generalization (see Sec. 7). We could now try to solve this issue by generating an ensemble of conformers and embedding their distribution. However, cheap generation methods yield strongly biased ensembles and would thus require expensive post-processing, defeating the purpose of fast and scalable machine learning (ML) methods (Ebejer et al., 2012; Kanal et al., 2018). We propose to instead solve this issue by using less precise *synthetic* coordinates that are easier and cheaper to obtain.

4   Synthetic coordinates

Graph-based distance. Directional MPNNs only use the distances of interactions and the angles between interactions; they do not require a full three-dimensional geometry. We leverage this generality to propose a distance based on a common graph-based proximity measure: Personalized PageRank (PPR) (Page et al., 1998), also known as random walks with restart. To satisfy the symmetry property of a metric we use a variant of PPR that uses the symmetrically normalized transition matrix, i.e.

$$\mathbf{\Pi}^{\mathrm{sppr}} = \alpha(\boldsymbol{I}_N - (1-\alpha)\boldsymbol{D}^{-1/2}\boldsymbol{A}\boldsymbol{D}^{-1/2})^{-1}, \tag{4}$$

with the teleport probability $\alpha \in (0,1]$, the adjacency matrix $\boldsymbol{A}$, and the diagonal degree matrix $\boldsymbol{D}_{ij} = \sum_k \boldsymbol{A}_{ik}\delta_{ij}$. We found that this method works well even without considering any bond type information in $\boldsymbol{A}$. We convert $\mathbf{\Pi}^{\mathrm{sppr}}$ to a distance via

$$d_{\mathrm{sppr},ij} = \sqrt{\mathbf{\Pi}^{\mathrm{sppr}}_{ii} + \mathbf{\Pi}^{\mathrm{sppr}}_{jj} - 2\mathbf{\Pi}^{\mathrm{sppr}}_{ij}}. \tag{5}$$

Note that $\mathbf{\Pi}^{\mathrm{sppr}}$ defines a positive definite kernel, and this is the induced distance in its reproducing kernel Hilbert space. It therefore satisfies all properties of a metric, i.e. identity of indiscernibles, symmetry, and the triangle inequality (Berg et al., 1984, Chapter 3, §3). However, $d_{\mathrm{sppr},ij}$ is a general metric and does *not* yield atom positions in 3D. Since the law of cosines holds for any inner product space we can calculate the angles for directional message passing via

$$\alpha_{ijk} = \arccos\left(\frac{d_{ij}^2 + d_{jk}^2 - d_{ik}^2}{2d_{ij}d_{jk}}\right). \tag{6}$$

Molecular distance bounds. Real molecular conformers can provide valuable chemical knowledge, despite the problems and ambiguities described in Sec. 3. To circumvent the issues associated with conformational ambiguity, we propose to use pairwise distance bounds instead of simple coordinates, i.e. minimum and maximum distances for every pair of atoms. These bounds only provide the chemical information we are certain of — without being falsely accurate. Specifically, we use the distance bounds provided by RDKit (RDKit, 2021). These bounds provide different estimates depending on how the atoms are bonded in the molecular graph. The edges in the molecular graph correspond to directly bonding atoms, whose bounds are calculated as the equilibrium distance (as parametrized in the universal force field (UFF) (Rappe et al., 1992)) plus or minus a tolerance of $0.01\,\text{Å}$. Similarly, the angles for triplets of atoms are calculated using the equilibrium bond angles and a tolerance. The angles in ring systems are handled separately based on a set of hand-crafted rules. Pairwise distances between higher-order neighbors are not relevant for our method, since we only use the distances and angles of the molecular graph. The distance bounds are then tightened using the triangle inequality. Note that these bounds depend almost exclusively on the directly involved atoms. They thus only provide local structural information.

We calculate three different angles for directional MPNNs using triplets of distances: The maximally and minimally realizable angles, and the center angle, obtained as

$$\alpha_{ijk}^{(\max)} = \arccos\left(\frac{d_{ij}^{(\min)2} + d_{jk}^{(\min)2} - d_{ik}^{(\max)2}}{2d_{ij}^{(\min)}d_{jk}^{(\min)}}\right), \tag{7}$$

$$\alpha_{ijk}^{(\min)} = \arccos\left(\frac{d_{ij}^{(\max)2} + d_{jk}^{(\max)2} - d_{ik}^{(\min)2}}{2d_{ij}^{(\max)}d_{jk}^{(\max)}}\right), \tag{8}$$

$$\alpha_{ijk}^{(\text{center})} = \arccos\left(\frac{\bar{d}_{ij}^2 + \bar{d}_{jk}^2 - \bar{d}_{ik}^2}{2\bar{d}_{ij}^2\bar{d}_{jk}^2}\right), \tag{9}$$

with $\bar{d} = (d^{(\min)} + d^{(\min)})/2$ denoting the center distance. These empirical distance bounds hold for all reasonable molecular structures and thus provide valuable, general information for our model. Their calculation requires no hand-tuning, takes only a few milliseconds, and worked for every molecule we investigated. Note that the graph-based and bounds-based distances encode orthogonal information. The former is based the global molecular graph structure, while the latter provides purely local chemical knowledge. Instead of just choosing one or the other we can therefore combine both to obtain the benefits of both aspects.

Implementation. The additional structural information can directly be incorporated into existing models as edge features. For this purpose we propose to first represent the distances and angles using radial and angular basis functions such as Gaussians, spherical Bessel functions, or cosines. The obtained features can then either directly be used by the GNN or first transformed by multiple layers. We found that using two linear layers for transformation can be very beneficial. The first layer is global and uses a small output dimension to force the model to learn a well-generalizing representation. The second layer is specific to each GNN layer, enabling more flexibility.

5 Limitations and societal impact

Limitations. Converting a GNN to a directional MPNN incurs significant computational overhead, since the line graph is usually substantially larger than the plain graph. However, just incorporating the information provided by graph distances or molecular distance bounds without transforming to directional message passing can also provide benefits, with almost no computational overhead. We furthermore found that transforming a GNN to a directional MPNN does not yield improvements in many cases, while synthetic coordinates still do (see Sec. 7 for details). There are also cases where synthetic coordinates lead to overfitting and do not improve accuracy either. Directional MPNNs appear to be most successful when the molecular configuration is directly relevant.

Societal impact. Improving the predictions of molecular models can positively affect various applications in chemistry, biology, and medicine. Our research is general and not focused on a field where malicious use should be expected. However, similar to most methodological research, our improvements can be misused to accelerate the development of chemical agents and biological weapons. We do not think that this potential for harm goes beyond regular research in theoretical chemistry and related fields. Still, to slightly reduce these negative effects our code will be published under the Hippocratic license (Ehmke, 2020).

6 Related work

Graph neural networks. Sperduti & Starita (1997); Baskin et al. (1997) proposed the first models resembling modern GNNs. Gori et al. (2005); Scarselli et al. (2009) were the first to use the name GNN, but these models are quite different to current GNNs, as described in Sec. 2. GNNs became widely adopted after their potential in a wide range of graph-related tasks was shown by Kipf & Welling (2017); Veličković et al. (2018); Klicpera et al. (2019); Defferrard et al. (2016); Bruna et al. (2014). Notably, Beaini et al. (2021) use the Laplacian eigenvectors of a graph to enable anisotropic

aggregation in MPNNs. This approach is related to our synthetic coordinates. However, it is not rotationally invariant w.r.t. the directions induced by the eigenvectors, and unsuited for enabling existing directional MPNNs.

GNNs for molecules. Molecules have always played a central role in the development of GNNs, both for the very first GNNs (Baskin et al., 1997) and during the modern era of GNNs (Duvenaud et al., 2015; Gilmer et al., 2017). GNNs have been particularly successful when leveraging coordinates (Schütt et al., 2017; Unke & Meuwly, 2019), but many variants only rely on the molecular graph (Fey et al., 2020).

Directionality in GNNs. Incorporating directionality in molecular MPNNs is currently a very active and successful area of research. These methods can roughly be divided into two classes: Models based on SO(3) group representations (Thomas et al., 2018; Anderson et al., 2019), and models incorporating directional information directly (Klicpera et al., 2020b). Multiple promising models have recently been proposed for both classes (Fuchs et al., 2020; Batzner et al., 2021; Schütt et al., 2021; Liu et al., 2021; Satorras et al., 2021). While we focus on directional message passing in this paper, all of these methods can benefit from synthetic coordinates.

Molecular representations. Molecular fingerprints are a useful tool for comparing molecules, e.g. for machine learning. Popular examples include extended connectivity fingerprints (ECFP), also known as Morgan or circular fingerprints (Rogers & Hahn, 2010), MACCS keys (Durant et al., 2002), MHFP (Probst & Reymond, 2018), the subgraph-based RDKit fingerprint (RDKit, 2021), and the SELFIES string representation (Krenn et al., 2020). These can be viewed as an alternative or supplement to synthetic coordinates. However, unlike synthetic coordinates they do not leverage the peculiarities of directional MPNNs, and can usually only be used with regressors that are not graph-based. Another class of molecular representations aims at better encoding the geometry of a molecule (Faber et al., 2017). Examples include FCHL (Faber et al., 2018; Christensen et al., 2020), smooth overlap of atomic positions (SOAP) (Bartók et al., 2013), atomic spectrum of London and ATM potential (aSLATM) (Huang & von Lilienfeld, 2020). OrbNet is an example of a GNN that enhances its input with such a representation (Qiao et al., 2020). Obviously, none of these can be used without access to the molecular configuration.

7 Experiments

7.1 Experimental setup

We use three common benchmarks to evaluate the proposed synthetic coordinates: Coordinate-free QM9 (Ramakrishnan et al., 2014, CC0 license), ZINC (Irwin et al., 2012), and ogbg-molhiv (Hu et al., 2020, MIT license). To exclude effects from regular chemical information we use all available edge (bond types) and node features (acceptor/donor, aromaticity, hybridization) for both datasets. However, unlike previous work we do not use the Mulliken partial charges. These are computed by quantum mechanical calculations that use the molecule's configuration. They thus lead to information leakage and defeat the purpose of QM9's regression task. We use the same data split as Brockschmidt (2020) for QM9, i.e. 10 000 molecules for the validation and test sets, and the remaining ∼110 000 molecules for training. For ZINC we use 10 000 training, 1000 validation, and 1000 test molecules, as established by Dwivedi et al. (2020) and provided by PyTorch Geometric (Fey & Lenssen, 2019). ogbg-molhiv contains 41 127 graphs, out of which 80 % are training samples, and 10 % each are validation and test samples, as provided by the official data splits. The experiments were run on GPUs using an internal cluster equipped mainly with NVIDIA GeForce GTX 1080Ti.

We aim to answer two questions with our experiments: 1. Do synthetic coordinates improve the performance of existing GNNs? 2. Does transforming existing GNNs to directional MPNNs improve accuracy? To answer these questions we investigate three GNNs: DeeperGCN (Li et al., 2020, MIT license), structural message passing (SMP) (Vignac et al., 2020, MIT license), and DimeNet^{++} (Klicpera et al., 2020a, Hippocratic license). We show step-by-step how the changes affect the

Table 1: Ablation study for transforming DeeperGCN and SMP to directional MPNNs (MAE on ZINC). Every step improves the error of DeeperGCN, resulting in a 49% improvement. The combined PPR+bounds encoding performs best. *Replicated using the reference implementation.

		SMP	DeeperGCN
Basic		0.148*	0.331
+distance	PPR	0.144	0.297
	bounds	0.142	0.303
+line graph	PPR	0.143	0.229
	bounds	0.147	0.226
+angle	PPR	**0.129**	0.177
	bounds	0.144	0.194
	PPR+bounds	0.135	**0.169**

Table 2: MAE on ZINC. SMP with synthetic coordinates outcompetes previous models by 7%, without any hyperparameter tuning.

Model	MAE
Gated GCN (Fey et al., 2020)	0.282
GIN (Fey et al., 2020)	0.252
PNA (Corso et al., 2020)	0.188
DGN (Beaini et al., 2021)	0.168
MPNN-JT (Fey et al., 2020)	0.151
SMP (Vignac et al., 2020)	0.138
DeeperGCN-SC	0.169
SMP-SC	**0.129**

resulting error of each model. For context and easier comparison we also provide the results of other GNNs.

7.2 Model hyperparameters

To prevent overfitting we use the SMP and DimeNet^{++} models and hyperparameters largely as-is, without any further optimization. Similarly, we chose the DeeperGCN variant and hyperparameters based on the ogbg-molhiv dataset, and did not further tune on ZINC. More specifically, we use the DeeperGCN (Li et al., 2020) with 12 ResGCN+ blocks, mean aggregation in the graph convolution, and average pooling to obtain the graph embedding. For SMP (Vignac et al., 2020) we use 12 layers, 8 towers, an internal representation of size 32 and no residual connections. For both DeeperGCN and SMP we use an embedding size of 256, and distance and angle bases of size 8 and 9, respectively, with a bottleneck dimension of 4 between the global basis embedding and the local embedding in each layer. We train all models on ZINC with the same training hyperparameters as SMP, particularly the same learning rate schedule with a patience of 100 and minimum learning rate of $1e-5$.

For DimeNet^{++} we use a cutoff of $2.5\,\text{Å}$, radial and spherical bases of size 12, embedding size 128, output embedding size 256, basis embedding size 8 and 4 blocks. We use the same optimization parameters - learning rate 0.001, 3000 warmup steps and a decay rate of 0.01.

7.3 Results

Transforming existing GNNs. Table 1 shows that both DeeperGCN's and SMP's errors improve for each step of the transformation: Adding distance information, switching to the line graph, and adding angles. Interestingly, the PPR distance reduces the error more than molecular distance bounds do. This suggests that this structural information is more relevant for the GNN than the rough bounds. Using both the PPR distance and molecular distance bounds improves the performance further for DeeperGCN, but not for SMP, showing that this combination helps often, but not always. Using full 3D coordinates optimized using the MMFF94 potential (see Sec. 3) yields an MAE of 0.207, which is higher than using the simple molecular bounds we propose. As discussed in Sec. 3, this can be attributed to the ambiguities of different molecular conformers. Furthermore, SMP does not seem to benefit from using the line graph. This is likely due to SMP already encoding structural information as part of its architecture. DeeperGCN with synthetic coordinates performs similarly well to previous methods, while the enhanced SMP sets a new state of the art on this dataset, as shown in Table 2.

Enhancing DimeNet^{++}. DimeNet was originally developed for molecular dynamics and other use cases that provide the true atom positions, such as the full QM9 dataset. Despite this, we can still use it as-is without available positional information by setting the used distance and angle embeddings to constants. DimeNet^{++} still performs surprisingly well in this form, as shown in Table 3. However, its performance increases significantly if we provide it with the proposed synthetic coordinates.

Table 3: MAE on coordinate-free QM9 (meV) for DimeNet^{++} with synthetic coordinates. Both synthetic distances and angles yield significant improvements, reducing the error by $24\,\%$ overall.

	ϵ_{HOMO}	U_0
no dist/angle	74.1	41.9
no angle	63.5	32.1
PPR	63.0	29.5
bounds	63.6	29.4
PPR+bounds	**61.7**	**28.7**

Table 4: MAE on coordinate-free QM9. DimeNet^{++} with synthetic coordinates outperforms previous models by $20\,\%$, without any hyperparameter tuning. *Uses Mulliken partial charges

	Unit	GNN-FiLM*	GNN-FiLM+FA*	DimeNet^{++}-SC
μ	D	0.238	**0.226**	0.303
α	$a_0{}^3$	0.375	0.193	**0.171**
ϵ_{HOMO}	meV	52.5	**47.7**	61.7
ϵ_{LUMO}	meV	55.9	**52**	54.3
$\Delta\epsilon$	meV	84.3	**77**	86.2
$\langle R^2 \rangle$	$a_0{}^2$	18.7	14.3	**12.7**
ZPVE	meV	13.2	5.62	**2.98**
U_0	meV	233	68.8	**28.7**
U	meV	256	75.2	**29.6**
H	meV	240	83	**29.6**
G	meV	222	76.1	**28.2**
c_{v}	$\frac{\text{cal}}{\text{mol K}}$	0.173	0.082	**0.076**

Notably, the PPR distance again causes a larger improvement than the molecular distance bounds. Combining both distances still performs best, though. Table 4 furthermore shows that DimeNet^{++} sets the state of the art for coordinate-less QM9 on eight out of twelve targets — without any further hyperparameter optimization. Interestingly, the achieved energy error lies significantly below the limit of $60\,\text{meV}$ we mentioned in Sec. 3. This is likely due to two reasons. First, QM9 only contains small molecules, many of which are very rigid. These molecules do not have multiple conformers and their energy will thus be more deterministic. Second, QM9's data was generated by initializing each molecule's position with a fast force field method. This can bias the final conformer towards a deterministic state, which might be learnable by a GNN.

Synthetic coordinates without directional message passing. In some cases we found that transforming synthetic coordinates yield performance improvements while transforming the model to a directional MPNN does not. Table 5 shows these results for DeeperGCN on QM9 and ogbg-molhiv. Using the line graph significantly impairs performance on both datasets. Whether directional MPNNs provide a benefit thus seems to depend on both the underlying model and the dataset. This is likely due to these models' different training dynamics, which require further architectural and hyperparameter changes. However, the additional information provided by synthetic coordinates still yield improvements in these cases.

Table 5: Ablation of DeeperGCN on QM9 U_0 (MAE, meV) and ogbg-molhiv (ROC-AUC). Using the line-graph does not always provide benefits. However, synthetic coordinates help even in these cases.

		QM9, U_0	ogbg-molhiv
Basic		106	0.779
+distance	PPR	**85**	0.726
	bounds	91	**0.786**
+line graph	PPR	218	0.689
	bounds	235	0.743
+angle	PPR	184	0.695
	bounds	201	0.720
	PPR+bounds	176	0.720

8 Conclusion

We proposed two methods for providing synthetic coordinates: Graph-based distances based on personalized PageRank scores, and molecular distance bounds based on the interacting atom types. Both of these methods provide well-defined pairwise distances, which can then be used to calculate distances for edge features and angles for edge features in the line graph. These synthetic coordinates improve GNN performance for various models and datasets, and allow transforming a regular GNN into a directional MPNN. This transformation leads to substantial improvements, resulting in state-of-the-art accuracies in multiple datasets.

References

Brandon M. Anderson, Truong-Son Hy, and Risi Kondor. Cormorant: Covariant Molecular Neural Networks. In *NeurIPS*, 2019.

Albert P. Bartók, Risi Kondor, and Gábor Csányi. On representing chemical environments. *Physical Review B*, 87(18):184115, 2013.

Igor I. Baskin, Vladimir A. Palyulin, and Nikolai S. Zefirov. A Neural Device for Searching Direct Correlations between Structures and Properties of Chemical Compounds. *Journal of Chemical Information and Computer Sciences*, 37(4):715–721, 1997.

Simon Batzner, Tess E. Smidt, Lixin Sun, Jonathan P. Mailoa, Mordechai Kornbluth, Nicola Molinari, and Boris Kozinsky. SE(3)-Equivariant Graph Neural Networks for Data-Efficient and Accurate Interatomic Potentials. *arXiv*, 2101.03164, 2021.

Dominique Beaini, Saro Passaro, Vincent Létourneau, William L. Hamilton, Gabriele Corso, and Pietro Liò. Directional Graph Networks. *arXiv*, 2010.02863, 2021.

Christian Berg, Jens Peter Reus Christensen, and Paul Ressel. *Harmonic Analysis on Semigroups*. Number 100 in Graduate Texts in Mathematics. 1984.

Marc Brockschmidt. GNN-FiLM: Graph Neural Networks with Feature-wise Linear Modulation. In *ICML*, 2020.

Joan Bruna, Wojciech Zaremba, Arthur Szlam, and Yann LeCun. Spectral Networks and Deep Locally Connected Networks on Graphs. In *ICLR*, 2014.

Zhengdao Chen, Lisha Li, and Joan Bruna. Supervised Community Detection with Line Graph Neural Networks. In *ICLR*, 2019.

Anders S. Christensen, Lars A. Bratholm, Felix A. Faber, and O. Anatole von Lilienfeld. FCHL revisited: Faster and more accurate quantum machine learning. *The Journal of Chemical Physics*, 152(4):044107, 2020.

Gabriele Corso, Luca Cavalleri, Dominique Beaini, Pietro Liò, and Petar Veličković. Principal Neighbourhood Aggregation for Graph Nets. In *NeurIPS*, 2020.

Hanjun Dai, Bo Dai, and Le Song. Discriminative Embeddings of Latent Variable Models for Structured Data. In *ICML*, 2016.

Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional Neural Networks on Graphs with Fast Localized Spectral Filtering. In *NeurIPS*, 2016.

Joseph L. Durant, Burton A. Leland, Douglas R. Henry, and James G. Nourse. Reoptimization of MDL Keys for Use in Drug Discovery. *Journal of Chemical Information and Computer Sciences*, 42(6):1273–1280, 2002.

David K. Duvenaud, Dougal Maclaurin, Jorge Aguilera-Iparraguirre, Rafael Gómez-Bombarelli, Timothy Hirzel, Alán Aspuru-Guzik, and Ryan P. Adams. Convolutional Networks on Graphs for Learning Molecular Fingerprints. In *NeurIPS*, 2015.

Vijay Prakash Dwivedi, Chaitanya K. Joshi, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Benchmarking Graph Neural Networks. *arXiv*, 2003.00982, 2020.

Nadav Dym and Haggai Maron. On the Universality of Rotation Equivariant Point Cloud Networks. In *ICLR*, 2021.

Jean-Paul Ebejer, Garrett M. Morris, and Charlotte M. Deane. Freely Available Conformer Generation Methods: How Good Are They? *Journal of Chemical Information and Modeling*, 52(5):1146–1158, 2012.

Coraline Ada Ehmke. The Hippocratic License 2.1: An Ethical License for Open Source., 2020. URL https://firstdonoharm.dev.

Felix A. Faber, Luke Hutchison, Bing Huang, Justin Gilmer, Samuel S. Schoenholz, George E. Dahl, Oriol Vinyals, Steven Kearnes, Patrick F. Riley, and O. Anatole von Lilienfeld. Machine learning prediction errors better than DFT accuracy. *arXiv*, 1702.05532, 2017.

Felix A. Faber, Anders S. Christensen, Bing Huang, and O. Anatole von Lilienfeld. Alchemical and structural distribution based representation for universal quantum machine learning. *The Journal of Chemical Physics*, 148(24):241717, 2018.

Matthias Fey and Jan E. Lenssen. Fast Graph Representation Learning with PyTorch Geometric. In *ICLR-W*, 2019.

Matthias Fey, Jan-Gin Yuen, and Frank Weichert. Hierarchical Inter-Message Passing for Learning on Molecular Graphs. In *ICML-W*, 2020.

Dakota Folmsbee and Geoffrey Hutchison. Assessing conformer energies using electronic structure and machine learning methods. *International Journal of Quantum Chemistry*, 121(1):e26381, 2021.

Fabian Fuchs, Daniel Worrall, Volker Fischer, and Max Welling. SE(3)-Transformers: 3D Roto-Translation Equivariant Attention Networks. In *NeurIPS*, 2020.

Vikas Garg, Stefanie Jegelka, and Tommi Jaakkola. Generalization and Representational Limits of Graph Neural Networks. In *ICML*, 2020.

Justin Gilmer, Samuel S. Schoenholz, Patrick F. Riley, Oriol Vinyals, and George E. Dahl. Neural Message Passing for Quantum Chemistry. In *ICML*, 2017.

M. Gori, G. Monfardini, and F. Scarselli. A new model for learning in graph domains. In *IEEE International Joint Conference on Neural Networks*, 2005.

Stefan Grimme. Exploration of Chemical Compound, Conformer, and Reaction Space with Meta-Dynamics Simulations Based on Tight-Binding Quantum Chemical Calculations. *Journal of Chemical Theory and Computation*, 15(5):2847–2862, 2019.

Thomas A. Halgren. Merck molecular force field. I. Basis, form, scope, parameterization, and performance of MMFF94. *Journal of Computational Chemistry*, 17(5-6):490–519, 1996.

Zhongkai Hao, Chengqiang Lu, Zhenya Huang, Hao Wang, Zheyuan Hu, Qi Liu, Enhong Chen, and Cheekong Lee. ASGN: An Active Semi-supervised Graph Neural Network for Molecular Property Prediction. In *KDD*, 2020.

Timothy F. Havel. Distance Geometry: Theory, Algorithms, and Chemical Applications. In *Encyclopedia of Computational Chemistry*. 2002.

Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open Graph Benchmark: Datasets for Machine Learning on Graphs. In *NeurIPS*, 2020.

Bing Huang and O. Anatole von Lilienfeld. Quantum machine learning using atom-in-molecule-based fragments selected on the fly. *Nature Chemistry*, 12(10):945–951, 2020.

John J. Irwin, Teague Sterling, Michael M. Mysinger, Erin S. Bolstad, and Ryan G. Coleman. ZINC: A Free Tool to Discover Chemistry for Biology. *Journal of Chemical Information and Modeling*, 52(7):1757–1768, 2012.

Wengong Jin, Dr Regina Barzilay, and Tommi Jaakkola. Hierarchical Generation of Molecular Graphs using Structural Motifs. In *ICML*, 2020.

Ilana Y. Kanal, John A. Keith, and Geoffrey R. Hutchison. A sobering assessment of small-molecule force field methods for low energy conformer predictions. *International Journal of Quantum Chemistry*, 118(5):e25512, 2018.

Thomas N. Kipf and Max Welling. Semi-Supervised Classification with Graph Convolutional Networks. In *ICLR*, 2017.

Johannes Klicpera, Aleksandar Bojchevski, and Stephan Günnemann. Predict then Propagate: Graph Neural Networks Meet Personalized PageRank. In *ICLR*, 2019.

Johannes Klicpera, Shankari Giri, Johannes T. Margraf, and Stephan Günnemann. Fast and Uncertainty-Aware Directional Message Passing for Non-Equilibrium Molecules. In *NeurIPS-W*, 2020.

Johannes Klicpera, Janek Groß, and Stephan Günnemann. Directional Message Passing for Molecular Graphs. In *ICLR*, 2020.

Mario Krenn, Florian Häse, AkshatKumar Nigam, Pascal Friederich, and Alan Aspuru-Guzik. Self-referencing embedded strings (SELFIES): A 100% robust molecular string representation. *Machine Learning: Science and Technology*, 1(4):045024, 2020.

Dominik Lemm, Guido Falk von Rudorff, and O. Anatole von Lilienfeld. Energy-free machine learning predictions of ab initio structures. *arXiv*, 2102.02806, 2021.

Guohao Li, Chenxin Xiong, Ali Thabet, and Bernard Ghanem. DeeperGCN: All You Need to Train Deeper GCNs. *arXiv*, 2006.07739, 2020.

Yi Liu, Limei Wang, Meng Liu, Xuan Zhang, Bora Oztekin, and Shuiwang Ji. Spherical Message Passing for 3D Graph Networks. *arXiv*, 2102.05013, 2021.

Christopher Morris, Martin Ritzert, Matthias Fey, William L. Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and Leman Go Neural: Higher-Order Graph Neural Networks. In *AAAI*, 2019.

Christopher Morris, Gaurav Rattan, and Petra Mutzel. Weisfeiler and Leman go sparse: Towards scalable higher-order graph embeddings. In *NeurIPS*, 2020.

Lawrence Page, Sergey Brin, Rajeev Motwani, and Terry Winograd. The pagerank citation ranking: Bringing order to the web. Report, Stanford InfoLab, 1998.

Daniel Probst and Jean-Louis Reymond. A probabilistic molecular fingerprint for big data settings. *Journal of Cheminformatics*, 10(1):66, 2018.

Zhuoran Qiao, Matthew Welborn, Animashree Anandkumar, Frederick R. Manby, and Thomas F. Miller. OrbNet: Deep learning for quantum chemistry using symmetry-adapted atomic-orbital features. *The Journal of Chemical Physics*, 153(12):124111, 2020.

Raghunathan Ramakrishnan, Pavlo O. Dral, Matthias Rupp, and O. Anatole von Lilienfeld. Quantum chemistry structures and properties of 134 kilo molecules. *Scientific Data*, 1(1):1–7, 2014.

A. K. Rappe, C. J. Casewit, K. S. Colwell, W. A. Goddard, and W. M. Skiff. UFF, a full periodic table force field for molecular mechanics and molecular dynamics simulations. *Journal of the American Chemical Society*, 114(25):10024–10035, 1992.

RDKit. RDKit: Open-Source Cheminformatics Software, 2021. URL https://rdkit.org/.

Sereina Riniker and Gregory A. Landrum. Better Informed Distance Geometry: Using What We Know To Improve Conformation Generation. *Journal of Chemical Information and Modeling*, 55(12):2562–2574, 2015.

David Rogers and Mathew Hahn. Extended-Connectivity Fingerprints. *Journal of Chemical Information and Modeling*, 50(5):742–754, 2010.

Victor Garcia Satorras, Emiel Hoogeboom, and Max Welling. E(n) Equivariant Graph Neural Networks. *arXiv*, 2102.09844, 2021.

F. Scarselli, M. Gori, Ah Chung Tsoi, M. Hagenbuchner, and G. Monfardini. The Graph Neural Network Model. *IEEE Transactions on Neural Networks*, 20(1):61–80, 2009.

Kristof Schütt, Pieter-Jan Kindermans, Huziel Enoc Sauceda Felix, Stefan Chmiela, Alexandre Tkatchenko, and Klaus-Robert Müller. SchNet: A continuous-filter convolutional neural network for modeling quantum interactions. In *NeurIPS*, 2017.

Kristof T. Schütt, Oliver T. Unke, and Michael Gastegger. Equivariant message passing for the prediction of tensorial properties and molecular spectra. *arXiv*, 2102.03150, 2021.

A. Sperduti and A. Starita. Supervised neural networks for the classification of structures. *IEEE Transactions on Neural Networks*, 8(3):714–735, 1997.

Nathaniel Thomas, Tess Smidt, Steven M. Kearnes, Lusann Yang, Li Li, Kai Kohlhoff, and Patrick Riley. Tensor Field Networks: Rotation- and Translation-Equivariant Neural Networks for 3D Point Clouds. *arXiv*, 1802.08219, 2018.

Oliver T. Unke and Markus Meuwly. PhysNet: A Neural Network for Predicting Energies, Forces, Dipole Moments, and Partial Charges. *Journal of Chemical Theory and Computation*, 15(6):3678–3693, 2019.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph Attention Networks. In *ICLR*, 2018.

Clement Vignac, Andreas Loukas, and Pascal Frossard. Building powerful and equivariant graph neural networks with structural message-passing. In *NeurIPS*, 2020.

Jan Weinreich, Nicholas J. Browning, and O. Anatole von Lilienfeld. Machine learning of free energies in chemical compound space using ensemble representations: Reaching experimental uncertainty for solvation. *The Journal of Chemical Physics*, 154(13):134113, 2021.

Zhenqin Wu, Bharath Ramsundar, Evan N. Feinberg, Joseph Gomes, Caleb Geniesse, Aneesh S. Pappu, Karl Leswing, and Vijay Pande. MoleculeNet: a benchmark for molecular machine learning. *Chemical Science*, 9 (2):513–530, 2018.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How Powerful are Graph Neural Networks? In *ICLR*, 2019.

Kevin Yang, Kyle Swanson, Wengong Jin, Connor Coley, Philipp Eiden, Hua Gao, Angel Guzman-Perez, Timothy Hopper, Brian Kelley, Miriam Mathea, Andrew Palmer, Volker Settels, Tommi Jaakkola, Klavs Jensen, and Regina Barzilay. Analyzing Learned Molecular Representations for Property Prediction. *Journal of Chemical Information and Modeling*, 59(8):3370–3388, 2019.