SYMBOLIC PHYSICS LEARNER: DISCOVERING GOVERNING EQUATIONS VIA MONTE CARLO TREE SEARCH

ABSTRACT

Nonlinear dynamics is ubiquitous in nature and commonly seen in various science and engineering disciplines. Distilling analytical expressions that govern nonlinear dynamics from limited data remains vital but challenging. To tackle this fundamental issue, we propose a novel Symbolic Physics Learner (SPL) machine to discover the mathematical structure of nonlinear dynamics. The key concept is to interpret mathematical operations and system state variables by computational rules and symbols, establish symbolic reasoning of mathematical formulas via expression trees, and employ a Monte Carlo tree search (MCTS) agent to explore optimal expression trees based on measurement data. The MCTS agent obtains an optimistic selection policy through the traversal of expression trees, featuring the one that maps to the arithmetic expression of underlying physics. Salient features of the proposed framework include search flexibility and enforcement of parsimony for discovered equations. The efficacy and superiority of the PSL machine are demonstrated by numerical examples, compared with state-of-the-art baselines.

1 INTRODUCTION

We usually learn the behavior of a nonlinear dynamical system through its nonlinear governing differential equations. These equations can be formulated as $\dot{\mathbf{y}}(t) = d\mathbf{y}/dt = \mathcal{F}(\mathbf{y}(t))$, where $\mathbf{y}(t) = \{y_1(t), y_2(t), ..., y_n(t)\} \in \mathbb{R}^{1 \times n}$ denotes the system state at time t, $\mathcal{F}(\cdot)$ a nonlinear function set defining the state motions and n the system dimension. The explicit form of $\mathcal{F}(\cdot)$ for some nonlinear dynamics remains underexplored. For example, in a mounted double pendulum system, the mathematical description of the underlying physics might be unclear due to unknown viscous and frictional damping forms. These uncertainties yield critical demands for the discovery of nonlinear dynamics given observational data. Nevertheless, distilling the analytical form of governing equations from limited noisy data, commonly seen in practice, is an intractable challenge.

Ever since the early work on the data-driven discovery of nonlinear dynamics (Džeroski & Todorovski, 1993; Dzeroski & Todorovski, 1995), many scientists have stepped into this field of study. In the recent decade, the escalating advances in machine learning, data science, and computing power enabled several milestone efforts of unearthing the governing equations for nonlinear dynamical systems. Notably, a breakthrough model named SINDy based on sparse regression method (Brunton et al., 2016) shedded light on this field of study. SINDy was invented to determine the sparse solution among a pre-defined basis function library recursively through a sequential threshold ridge regression (STRidge) algorithm. SINDy quickly became one of the state-of-art methods and kindled significant enthusiasm in this field of study (Rudy et al., 2017; Long et al., 2018; Champion et al., 2019; Chen et al., 2021; Sun et al., 2021; Rao et al., 2022). However, the success of this sparsity-promoting approach relies on a properly defined candidate function library that requires prior knowledge of the system. It is also restricted by the fact that a linear combination of candidate functions might be insufficient to recover complicated mathematical expressions. Moreover, when the library size is massive, it empirically fails to hold the sparsity constraint.

At the same time, attempts have been made to tackle the nonlinear dynamics discovery problems by introducing neural networks with activation functions replaced by commonly seen mathematical operators (Martius & Lampert, 2017; Sahoo et al., 2018; Kim et al., 2019; Long et al., 2019). The intricate formulas are obtained via the well-trained symbolic network expansion. This interpretation of physics laws results in larger candidate pools compared to the library-based representation of

physics employed by SINDy. Nevertheless, since the sparsity of discovered expressions is primarily achieved by empirical pruning of the weights, this framework exhibits sensitivity to user-defined thresholds and may fall short to produce parsimonious governing equations for noisy and scarce data.

Alternatively, another benchmark work (Bongard & Lipson, 2007; Schmidt & Lipson, 2009) re-envisioned the data-driven nonlinear dynamics discovery tasks by casting them into symbolic regression problems which have been profoundly resolved by the genetic programming (GP) approach (Koza & Koza, 1992; Billard & Diday, 2003). Under this framework, a symbolic regressor is established to identify the differential equations that best describe the underlying governing physical laws through the free combination of mathematical operations and symbols, leveraging great flexibility (i.e, free combination of symbols and operators) in model selection. One essential weakness of this early methodology is that driven exclusively by the goal of empirically seeking the best-fitting expression (e.g. minimizing the mean-square error) in a genetic expansion process, the GP-based model usually overfits the target system with numerous false-positive terms under data noise, even sometimes at a subtle level, causing huge instability and uncertainty. However, this ingenious idea inspired a series of subsequent endeavors (Cornforth & Lipson, 2012; Gaucel et al., 2014; Ly & Lipson, 2012; Quade et al., 2016; Vaddireddy et al., 2020). In a more recent work titled Deep Symbolic Regression (Petersen et al., 2021; Mundhenk et al., 2021), a reinforcement learning-based model for symbolic regression was fabricated and generally outperformed the GP based models including the commercial Eureqa (Langdon & Gustafson, 2010) software. Additionally, the AI-Feynman methods (Udrescu & Tegmark, 2020; Udrescu et al., 2020; Udrescu & Tegmark, 2021) ameliorated the symbolic regression algorithm for distilling physics law from data by combining neural network fitting with a suite of physics-inspired techniques. This approach is also highlighted by a recursive decomposition of a complicated mathematical expression into different parts on a tree-based graph, which disentangles the original problem and speeds up the discovery. It outperformed Eureqa in the data-driven uncovering of Feynman physics equations (Feynman et al., 1965).

The popularity of adopting the tree-based symbolic reasoning of mathematical formulas (Lample & Charton, 2019) has been rising recently to uncover unknown mathematical expressions with a reinforcement learning agent (Kubalík et al., 2019; Petersen et al., 2021; Mundhenk et al., 2021). However, some former work attempting to apply the Monte Carlo tree search (MCTS) algorithm as an alternative to GP for symbolic regression (Cazenave, 2013; White et al., 2015; Islam et al., 2018; Lu et al., 2021) failed to leverage the full flexibility of this algorithm, resulting in the similar shortage with GP-based symbolic regressors as discussed earlier. Despite these outcomes, we are conscious of the strengths of the MCTS algorithm in equation discovery: it enables the flexible representation of search space with customized computational grammars to guide the search tree expansion. A sound mathematical underpinning for the trade-off between exploration and exploitation is remarkably advantageous as well. These features make it possible to guide the MCTS agent by prior physics knowledge in nonlinear dynamics discovery rather than randomly searching in large spaces.

Contribution. We propose a promising model named Symbolic Physics Learner (SPL) machine, empowered by MCTS, for discovery of nonlinear dynamics. This architecture relies on a grammar composed of computational rules and symbols to guide the search tree spanning and a composite objective rewarding function to simultaneously evaluate the generated mathematical expressions with observational data and enforce sparsity of the expression. Moreover, we design multiple adjustments to the conventional MCTS by: (**1**) replacing the expected reward in UCT score with maximum reward to better fit the equation discovery objective, (**2**) employing an adaptive scaling in policy evaluation which would eliminate the uncertainty of the reward value range owing to the unknown error of the system state derivatives, and (**3**) transplanting modules with high returns to the subsequent search as a single leaf node. With these adjustments, the SPL machine is capable of efficiently uncovering the best path to formulate the complex governing equations of the target dynamical system.

2 BACKGROUND

In this section, we expand and explain the background concepts brought up in the introduction to the SPL architecture, including the expression tree (parse tree) and the MCTS algorithm.

Expression tree. Any mathematical expression can be represented by a combinatorial set of symbols and mathematical operations and further expressed by a parse tree structure, (Hopcroft et al., 2006;

Kusner et al., 2017), which is empowered by a context-free grammar (CFG). A CFG is a formal grammar characterized by a tuple comprised of 4 elements $\mathcal{G} = (V, \Sigma, R, S)$, where V denotes a finite set of non-terminal nodes, Σ a finite set of terminal nodes, R a finite set of production rules, each interpreted as a mapping from a single non-terminal symbol in V to one or multiple terminal/non-terminal nodes in $(V \cup \Sigma)^*$ where $*$ represents the Kleene star operation, and S a single non-terminal node standing for a start symbol. In our work, equations are symbolized into parse trees: we define the start node as equation symbol f, terminal symbols (leaf nodes) corresponding to the independent variables from the equation (e.g, x, y), and a *placeholder symbol C* for identifiable constant coefficients that stick to specific production rules. The non-terminal nodes between root and leaf nodes are represented by some symbols distinct from the start and terminal nodes (i.e., M). The production rules denote the commonly seen mathematical operators: unary rules (one non-terminal node mapping to one node) for operators like $\cos(\cdot)$, $\exp(\cdot)$, $\log(|\cdot|)$, and binary rules (one non-terminal node mapping to two nodes) for operators such as $+, -, \times, \div$. A parse tree is then generated via a pre-order traversal of production rules rooted at f and terminates when all leaf nodes are entirely filled with terminal symbols. Each mathematical expression can be denoted as such a traversal set of production rules.

Monte Carlo tree search. Monte Carlo tree search (MCTS) (Coulom, 2006) is an algorithm for searching optimal decisions in large combinatorial spaces represented by search trees. This technique complies with the best-first search principle based on the evaluations of stochastic simulations. It has already been widely employed in and proved the spectacular success by various gaming artificial intelligence systems, including the famous AlphaGo and AlphaZero (Silver et al., 2017) for computer Go game. A basic MCTS algorithm can be regarded as an iterative process of four steps:

1. **Selection.** The MCTS agent, starting from the root node, moves through the visited nodes of the search tre and selects the next node according to a given selection policy until it reaches an expandable node or a leaf node.

2. **Expansion.** At an an expandable node, the MCTS agent expands the search tree by selecting one of its unvisited children.

3. **Simulation.** After expansion, if the current node is non-terminal, the agent performs one or multiple independent simulations starting from the current node until reaching the terminal state. In this process, actions are randomly selected.

4. **Backpropagation.** Statistics of nodes along the path from the current node to the root are updated with respect to search results (scores evaluated from the terminate states reached).

To maintain a proper balance between the less-tested paths and the best policy identified so far, the MCTS agent stikcs to a trade-off between exploration and exploitation through selecting the action that maximizes the Upper Confidence Bounds applied for Trees (UCT), which is formulated as:

$$UCT(s, a) = Q(s, a) + c\sqrt{\ln[N(s)]/N(s, a)} \tag{1}$$

where $Q(s, a)$ denotes the average result/reward of playing action a in state s in the simulations performed in the history, encouraging the exploitation of current best child node; $N(s)$ denotes number of times state s has been visited, $N(s, a)$ the number of times action a has been selected at state s, and $\sqrt{\ln[N(s)]/N(s, a)}$ consequently encourages the exploration of less-visited child nodes. Constant c controls the balance between exploration and exploitation and is usually empirically defined depend on the specific problem.

3 METHODS

It has been demonstrated that the MCTS agent continuously gains knowledge of the given discovery task via the expansion of the search tree and, based on the backpropagation of evaluation results (i.e., rewards and number of visits), render a proper selection policy on visited states to guide the upcoming searching. In the proposed SPL machine, this process is integrated with the symbolic reasoning of mathematical expressions to reproduce and evaluate valid mathematical expressions of the physics laws in nonlinear dynamics step-by-step, and then obtain a favorable selection policy pointing to the best solution. This algorithm is depicted in Figure 1 with an illustrative example and its overall training scheme is shown in Algorithm 1.

Figure 1: Schematic architecture of the SPL machine for nonlinear dynamics discovery. The graph explains the 4 MCTS phases of one learning episode with an illustrative example.

Rewarding. To evaluate the mathematical expression $\tilde{f}$ projected from a parse tree, we define a numerical reward $r \in \mathcal{R} \subset \mathbb{R}$ based on this expression and input data $\mathcal{D} = \{\mathbf{Y}; \dot{Y}_i\}$, serving as the search result of the current expansion or simulation. It is formulated as

$$r = \frac{\eta^n}{1 + \sqrt{\frac{1}{N}\left\|\dot{Y}_i - \tilde{f}(\mathbf{Y})\right\|_2^2}} \tag{2}$$

where $\mathbf{Y} = \{\mathbf{y}_1, \mathbf{y}_2, ..., \mathbf{y}_m\} \in \mathbb{R}^{m \times N}$ is the m dimensional system state variables, $\dot{Y}_i \in \mathbb{R}^{1 \times N}$ the numerically estimated state derivative for ith dimension, and N the number of measurement data points. η denotes a discount factor, assigned slightly smaller than 1; n is empirically defined as the total number of production rules in the parse tree. This numerator arrangement is designated to penalize non-parsimonious solutions. This rewarding formulation outputs a reasonable assessment to the distilled equations and encourages parsimonious solution by discounting the reward of a non-parsimonious one. The rooted mean square error (RMSE) in denominator evaluates the goodness-of-fit of the discovered equation w.r.t. the measurement data.

Training scheme. A grammar $\mathcal{G} = (V, \Sigma, R, S)$ is defined with appropriate nodes and production rules to cover all possible forms of equations. To keep track of non-terminal nodes of the parsing tree, we apply a last-in-first-out (LIFO) strategy and denote the non-terminal node placed last on the stack NT as the current node. We define the action space $\mathcal{A} = R$ and the state space $\mathcal{S}$ as all possible traversals of complete/incomplete parse trees (i.e., production rules selected) in ordered sequences. At the current state $s_t = [a_1, a_2, ...a_t]$ where $t \in \mathbb{N}$ is the discrete traversal step-index of the upcoming production rule, the MCTS agent masks out the invalid production rules for current non-terminal node and on that basis selects a valid rule as action a_{t+1} (i.e, the left-hand side of a valid production rule is the current non-terminal symbol). Consequently, the parse tree gains a new terminal/non-terminal branch in accordance with a_{t+1}, meanwhile the agent finds itself in a new state $s_{t+1} = [a_1, a_2, ...a_t, a_{t+1}]$. The agent subsequently pops off the current non-terminal symbol from NT and pushes the non-terminal nodes, if there are any, on the right-hand side of the selected rule onto the stack. Once the agent attains an unvisited node, a certain amount of simulations are performed, where the agent starts to randomly select the next node until the parse tree is completed.

Algorithm 1: Training the SPL machine for i^{th} dimension governing equation discovery

---

1 **Input:** Grammar $G = (V, \Sigma, R, S)$, measurement data $\mathcal{D} = \{\mathbf{Y}; \dot{Y}_i\}$;
2 **Parameters:** discount factor η, exploration rate c, t_{max};
3 **Output:** Optimal governing equation $\tilde{f}^\star$;
4 **for** *each episode* **do**
5   **Selection:** Initialize $s_0 = \emptyset, t = 0, NT = [S]$;
6   **while** s_t *expandable and* $t < t_{max}$ **do**
7   Choose $a_{t+1} = \arg\max_{\mathcal{A}} UCT(s_t, a)$;
8   Take action a_{t+1}, observe s', NT;
9         $s_{t+1} \leftarrow s'$ note as visited, $t \leftarrow t + 1$;
10   **end**
11   **Expansion:** Randomly take an unvisited path with action a, observe s', NT;
12     $s_{t+1} \leftarrow s'$ note as visited, $t \leftarrow t + 1$;
13   **if** $NT = \emptyset$ **then**
14   Project $\tilde{f}$, **Backpropagate** r_{t+1} and visited count and finish the episode;
15   **end**
16   **Simulation:** Fix the starting point s_t, NT;
17   **for** *each simulation* **do**
18   **while** s_t *non-terminal and* $t < t_{max}$ **do**
19   Randomly take an action a, observe s', NT;
20             $s_{t+1} \leftarrow s', t \leftarrow t + 1$;
21   **end**
22   **if** $NT = \emptyset$ **then**
23   Project $\tilde{f}$ and calculate r_{t+1};
24   **end**
25   **end**
26   **Backpropagate** simulation results;
27 **end**

The reward is calculated or the maximal size is exceeded, resulting in a zero reward. The best result from the attempts counts as the reward of the current simulation phase and backpropagates from the current unvisited node all the way to the root node.

Greedy search. Different from the MCTS-based gaming AIs where the agents are inclined to pick the action with a high expected reward (average returns), the SPL machine seeks the unique optimal solution. In the proposed training framework, we apply a greedy search heuristic to encourage the agent to explore the branch which yields the best solution in the past: $Q(s, a)$ is defined as the maximum reward of the state-action pair, and its value is backpropagated from the highest reward in the simulations upon the selection of the pair. Meanwhile, to overcome the local minima problems due to this greedy approach in policy search, we enforce a certain level of randomness by empirically adopting the ϵ-greedy algorithm, a commonly seen approach in reinforcement learning models.

Adaptive-scaled rewarding. Owing to the unknown level of error from the numerically estimated state derivatives, the range of the RMSE in the SPL reward function is unpredicTable This uncertainty affects the scale of rewarding values thus the balance between exploration and exploitation is presented in Eq. (1). Besides adding "1" to the denominator of Eq. (2) to avoid dramatically large numerical rewards, we also apply an adaptive scale of the reward that

$$Q(s, a) = \frac{r^*(s, a)}{\max_{s' \in \mathcal{S}, a' \in \mathcal{A}} Q(s', a')} \tag{3}$$

where r^* denotes the maximum reward of the state-action pair. It is scaled by the current maximum reward among all states $\mathcal{S}$ and actions $\mathcal{A}$ to reach an equilibrium that the Q-values are stretched to the scale $[0, 1]$ at any time. This self-adaptive fashion yields a well-scaled calculation of UCT under different value ranges of rewards throughout the training.

Module transplantation. A function can be decomposed into smaller modules where each is simpler than the original one (Udrescu et al., 2020). This modularity feature, as shown in Figure 2, helps us develop a divide-and-conquer heuristic for distilling some complicated functions: after every certain amount of MCTS iterations, the discovered parse trees with high rewards are picked out and thereupon

reckoned as individual production rules and appended to the set of production rules R; accordingly, these trees are "transplanted" to the future ones as their modules (i.e, the leaves). To avoid early overfitting problem, we incrementally enlarge the sizes of such modules from a baseline length

Figure 2: A module transplantation process: A complete parse serves as a single production rule and is appended to the grammar pool.

to the maximum allowed size of the parse tree throughout the iterations. The augmentation part of R is refreshed whenever new production rules are created, keeping only the ones engendering high rewards. This approach accelerates the policy search by capturing and locking some modules that likely contribute to, or appear as part of the optimal solution, especially in the cases of the mathematical expression containing "deep" operations (e.g., high-order polynomials) whose structures are difficult for the MCTS agent to repeatedly obtain during the selection and expansion.

4 SYMBOLIC REGRESSION: FINDING MATHEMATICAL FORMULAS

4.1 DATA NOISE & SCARCITY

Data scarcity and noise are commonly seen in measurement data and become one of the bottleneck issues for discovering the governing equations of nonlinear dynamics. Tackling the challenges in high-level data scarcity and noise situations is traditionally regarded as an essential robustness indicator for a nonlinear dynamics discovery model. Prior to this, we present an examination of the proposed SPL machine by an equation discovery task in the presence of multiple levels of

Figure 3: The effect of data noise/scarcity on recovery rate. The heatmaps demonstrate the recovery rate of GP-based symbolic regressor and the SPL machine under different data conditions, summarized over 100 independent trials.

data noise and volumes, comparing with a GP-based symbolic regressor (implemented with *gplearn* python package)[1]. The target equation is $f(x) = 0.3x^3 + 0.5x^2 + 2x$, and the independent variable X is uniformly sampled in the given range $[-10, 10]$. Gaussian white noise is added to the dependent variable Y with the noise level defined as the root-mean-square ratio between the noise and the exact values. For discovery, the two models are fed with equivalent search space: $\{+, -, \times, \div, cost, x\}$ as candidate mathematical operations and symbols. The hyperparameters of te SPL machine are set as $\eta = 0.99$, $t_{max} = 50$, and 10,000 episodes of training is regarded as one trail. For the GP-based symbolic regressor, population of programs is set to as 2000, number of generations as 20, the range of constant values is $[-10, 10]$. For 16 different data noise and scarcity levels, each model performs 100 independent trails. The recovery rates are displayed as a 4×4 mesh grid with different noise and scarcity levels in Figure 3. It is clearly observed that the SPL machine outperforms the GP-based symbolic regressor in all the cases. A T-test also proves that recovery rate of the SPL machine is significantly higher than that of the GP-based symbolic regressor (p-value $= 1.06 \times 10^{-7}$).

4.2 NGUYEN'S SYMBOLIC REGRESSION BENCHMARK

Nguyen's symbolic regression benchmark task (Uy et al., 2011) is widely used by the equation discovery work as an indicator of a model's robustness in symbolic regression problems. Given a set of allowed operators, a target equation, and data generated by this equation, the tested model is supposed to distill mathematical expression that is identical to the target equation, or equivalent to it (e.g., Nguyen-7 equation can be recovered as $\log(x^3 + x^2 + x + 1)$, Nguyen-10 equation can

---

[1]All simulations are performed on a workstation with a NVIDIA GeForce RTX 2080Ti GPU.

Table 1: Recovery rate of three algorithms in Nguyen's benchmark symbolic regression problems. The SPL machine outperforms the other two models in average recovery rate.

Benchmark	Expression	SPL	NGGP	GP
Nguyen-1	$x^3 + x^2 + x$	100%	100%	99%
Nguyen-2	$x^4 + x^3 + x^2 + x$	100%	100%	90%
Nguyen-3	$x^5 + x^4 + x^3 + x^2 + x$	100%	100%	34%
Nguyen-4	$x^6 + x^5 + x^4 + x^3 + x^2 + x$	99%	100%	54%
Nguyen-5	$\sin(x^2)\cos(x) - 1$	95%	80%	12%
Nguyen-6	$\sin(x^2) + \sin(x + x^2)$	100%	100%	11%
Nguyen-7	$\ln(x + 1) + \ln(x^2 + 1)$	100%	100%	17%
Nguyen-8	$\sqrt{x}$	100%	100%	100%
Nguyen-9	$\sin(x) + \sin(y^2)$	100%	100%	76%
Nguyen-10	$2\sin(x)\cos(y)$	100%	100%	86%
Nguyen-11	x^y	100%	100%	13%
Nguyen-12	$x^4 - x^2 + \frac{1}{2}y^2 - y$	28%	4%	0%
Nguyen-1^c	$3.39x^3 + 2.12x^2 + 1.78x$	100%	100%	0%
Nguyen-2^c	$0.48x^4 + 3.39x^3 + 2.12x^2 + 1.78x$	94%	100%	0%
Nguyen-5^c	$\sin(x^2)\cos(x) - 0.75$	95%	98%	1%
Nguyen-8^c	$\sqrt{1.23x}$	100%	100%	56%
Nguyen-9^c	$\sin(1.5x) + \sin(0.5y^2)$	96%	90%	0%
Average		**94.5%**	92.4%	38.2%

be recovered as $\sin(x + y)$, and Nguyen-11 equation can be recovered as $\exp(y\log(x))$). Some variants of Nguyen's benchmark equations are also considered in this experiment. Their discoveries require numerical estimation of constant values. Each equation generates two datasets: one for training and another for testing purposes. The discovered equation that perfectly fits the testing data is regarded as a successful discovery. The recovery rate is calculated based on 100 independent tests for each task. In these benchmark tasks, three algorithms are tested: GP-based symbolic regressor, the neural-guided GP (NGGP) (Mundhenk et al., 2021), and the proposed SPL machine. Note that NGGP is an improved approach over DSR (Petersen et al., 2021). They are given the same set of candidate operations: $\{+, -, \times, \div, \exp(\cdot), \cos(\cdot), \sin(\cdot)\}$ for all benchmarks and $\{\sqrt{\cdot}, \ln(\cdot)\}$ are added to the 7, 8, 11 benchmarks. The hyperparameters of the GP-based symbolic regressor are the same as those mentioned in Section 4.1; configurations of the NGGP models are obtained from its source code[2]; detailed setting of the benchmark tasks and the SPL model is described in Appendix Section A. The success rates are shown in Table 1. It is observed that the SPL machine and the NGGP model both produce reliable results in Nguyen's benchmark problems and the SPL machine slightly outperformed the NGGP. This experiment betokens the capacity of the SPL machine in equation discoveries with divergent forms.

Ablation Study: We consider three ablation studies by removing: (a) the adaptive scaling in reward calculation, (b) the discount factor η^n that drives equation parsimony in Eq. (2), and (c) module transplantation in tree generation. The ablated models were tested on the above 17 Nguyen equations. Results show that the average recovery rates for these models are all below 60% (numbers are not listed due to space limit). Hence, these modules are critical to guarantee the proposed model efficacy.

5 PHYSICS LAW DISCOVERY: FREE FALLING BALLS WITH AIR RESISTANCE

It is well known that in 1589–92 Galileo dropped two objects of unequal mass from the Leaning Tower of Pisa and drew a conclusion that their velocities were not affected by the mass. This has been well recognized globally as the "textbook" physics law for the vertical motion of a free-falling object: the

Table 2: Baseline models (c_i: unknown constants).

Physics Model	Derived model expression
Model-1	$H(t) = c_0 + c_1 t + c_2 t^2 + c_3 t^3$
Model-2	$H(t) = c_0 + c_1 t + c_2 e^{c_3 t}$
Model-3	$H(t) = c_0 + c_1 \log(\cosh(c_2 t))$

[2]NGGP source code: https://github.com/brendenpetersen/deep-symbolic-optimization/tree/master/dso/dso

height of the object is formulated as $H(t) = h_0 + v_0 t - \frac{1}{2} g t^2$, where h_0 denotes initial height, v_0 the initial velocity, and g the gravitational acceleration. However, this ideal situation is rarely reached in our daily life because air resistance serves as a significant damping factor that prevents the above physics law from occurring in real-life cases.

Many efforts have been made to uncover the effect of the air resistance and derive mathematical models to describe the free-falling objects with air resistance (Clancy, 1975; Lindemuth, 1971; Greenwood et al., 1986). This section provides a data-driven discovery of the physics laws of relationships between height and time in the cases of free-falling objects with air resistance based on multiple experimental ball-drop datasets (de Silva et al., 2020), which contain the records of 11 different types of balls dropped from a

Table 3: Mean square error (MSE) between ball motion prediction with the measurements in the test set. The SPL machine reaches the best prediction results in most (9 out of 11) cases.

Type	SPL	Model-1	Model-2	Model-3
baseball	**0.3**	2.798	94.589	3.507
blue basketball	**0.457**	0.513	69.209	2.227
green basketball	**0.088**	0.1	85.435	1.604
volleyball	**0.111**	0.574	80.965	0.76
bowling ball	**0.003**	0.33	87.02	3.167
golf ball	**0.009**	0.214	86.093	1.684
tennis ball	**0.091**	0.246	72.278	0.161
whiffle ball 1	1.58	1.619	65.426	**0.21**
whiffle ball 2	**0.099**	0.628	58.533	0.966
yellow whiffle ball	**0.428**	17.341	44.984	2.57
orange whiffle ball	0.745	**0.379**	36.765	3.257

bridge (see Appendix Figure B.1). For discovery, each dataset is split into a train set (records from the first 2 seconds) and a test set (records after 2 seconds). Three mathematically derived physics models are selected from the literature as baseline models[3,4,5] for this experiment (see Table 2), and the unknown constant values are solved by Powell's conjugate direction method (Powell, 1964). Based on prior knowledge of the physics law that may appear in this case, this experiment uses $\{+, -, \times, \div, \exp(\cdot), \cosh(\cdot), \log(\cdot)\}$ as the candidate grammars of the SPL discovery, with terminal nodes $\{t, const\}$. The hyperparameters are set as $\eta = 0.9999$, $t_{max} = 20$, and one single discovery is built upon 6,000 episodes of training. The physics laws distilled by SPL from training data are applied to the test data and compared with the ground truth. Their prediction errors, in terms of MSE, are presented in Table 3 (the SPL-discovered equations are shown in Appendix Table B.1). The full results can be found in Appendix Section B. It can be concluded that the data-driven discovery of physical laws leads to a better approximation of the free-falling objects with air resistance.

6 CHAOTIC DYNAMICS DISCOVERY: THE LORENZ SYSTEM

The first nonlinear dynamics discovery example is a 3-dimensional Lorenz system (Lorenz, 1963) whose dynamical behavior (x, y, z) is governed by $\dot{x} = \sigma(y - x), \dot{y} = x(\rho - z) - y, \dot{z} = xy - \beta z$ with parameters $\sigma = 10$, $\beta = 8/3$, and $\rho = 28$, under which the Lorenz attractor has two lobes and the system, starting from anywhere, makes cycles around one lobe before switching to the other and iterates repeatedly. The resulting system exhibits strong chaos. The synthetic datasets are generated by solving the nonlinear differential equations using Matlab `ode113` (Shampine, 1975; Shampine & Reichelt, 1997) function. 5% Gaussian white noise is added to the clean data to generate noisy

Table 4: Summary of the discovered governing equations for Lonrez system. Each cell concludes if target physics terms are distilled (if yes, number of false positive terms in uncovered expression).

Model	$\dot{x}$	$\dot{y}$	$\dot{z}$
Eureqa	Yes (1)	Yes (3)	Yes (1)
pySINDy	Yes (1)	No (N/A)	Yes (2)
NGGP	Yes (10)	Yes (8)	Yes (16)
SPL	**Yes (0)**	**Yes (0)**	**Yes (0)**

measurement. The derivatives of the system states are estimated by central difference and smoothed by the Savitzky–Golay filter (Savitzky & Golay, 1964) in order to reduce the noise effect.

In this experiment, the proposed SPL machine will compare with three benchmark methods, Eureqa, pySINDy and NGGP. For Eureqa, NGGP, and the SPL machine, $\{+, -, \times, \div\}$ are used as candidate operations; the upper bound of complexity is set to be 50; for pySINDy, the candidate function library includes all polynomial basis of x, y, z from degree 1 to degree 4. Appendix Table C.1

---

[3]Model 1: https://faraday.physics.utoronto.ca/IYearLab/Intros/FreeFall/FreeFall.html
[4]Model 2: https://physics.csuchico.edu/kagan/204A/lecturenotes/Section15.pdf
[5]Model 3: https://en.wikipedia.org/wiki/Free_fall

presents the distilled governing dynamics by each approach and Table 4 summarizes these results: the SPL machine uncovers the explicit form of equations accurately in the context of active terms, whereas Eureqa, pySINDy and NGGP yield several false-positive terms in the governing equations. In particular, although Eureqa and NGGP are capable of uncovering the correct terms, their performance is very sensitive to the measurement noise as indicated by the redundant terms (despite with small coefficients) shown in Appendix Table C.1. Overall, the baseline methods fail to handle the large noise effect, essentially limiting their applicability in nonlinear dynamics discovery. It is evident that the SPL machine is capable of distilling the concise symbolic combination of operators and variables to correctly formulate parsimonious mathematical expressions that govern the Lorenz system, outperforming the baseline methods of Eureqa, pySINDy and NGGP.

7 EXPERIMENTAL DYNAMICS DISCOVERY: DOUBLE PENDULUM

This section shows SPL-based discovery of a chaotic double pendulum system with experimental data (Asseman et al., 2018) as shown in Appendix Figure C.3. The governing equations can be derived by the Lagrange method, given by:

$$
\begin{aligned}
\dot{\omega}_1 &= c_1\dot{\omega}_2\cos(\Delta\theta) + c_2\omega_2^2\sin(\Delta\theta) + c_3\sin(\theta_1) + \mathcal{R}_1(\theta_1, \theta_2, \dot{\theta}_1, \dot{\theta}_2), \\
\dot{\omega}_2 &= c_1\dot{\omega}_1\cos(\Delta\theta) + c_2\omega_1^2\sin(\Delta\theta) + c_3\sin(\theta_2) + \mathcal{R}_2(\theta_1, \theta_2, \dot{\theta}_1, \dot{\theta}_2)
\end{aligned}
\tag{4}
$$

where θ_1, θ_2 denote the angular displacements; $\omega_1 = \dot{\theta}_1$, $\omega_2 = \dot{\theta}_2$ the velocities; $\dot{\omega}_1$, $\dot{\omega}_2$ the accelerations; $\mathcal{R}_1$ and $\mathcal{R}_2$ denote the unknown damping forces. Note that $\Delta\theta = \theta_1 - \theta_2$.

The data source contains multiple camera-sensed datasets. Here, 5,000 denoised random sub-samples from 5 datasets are used for training, and 2,000 random sub-samples from another 2 datasets for validation, and 1 dataset for testing. The derivatives of the system states are numerically estimated by the same approach discussed in the Lorenz case. Some physics are employed to guide the discovery: (**1**) $\dot{\omega}_2\cos(\Delta\theta)$ for $\dot{\omega}_1$ and $\dot{\omega}_1\cos(\Delta\theta)$ are given; (**2**) the angles (θ_1, θ_2, $\Delta\theta$) are under the trigonometric functions $\cos(\cdot)$ and $\sin(\cdot)$; (**3**) directions of velocities/relative velocities may appear in damping. Production rules fulfilling the above prior knowledge are exhibited in Appendix Section C.2. The hyperparameters are set as $\eta = 1$, $t_{max} = 20$, and 40,000 episodes of training is regarded as one trail. 5 independent trials are performed and the equations with the highest validation scores are selected as the final results. The uncovered equations are given as follows:

$$
\begin{aligned}
\dot{\omega}_1 &= -0.0991\dot{\omega}_2\cos(\Delta\theta) - 0.103\omega_2^2\sin(\Delta\theta) - 69.274\sin(\theta_1) + \underline{0.515\cos(\theta_1)}, \\
\dot{\omega}_2 &= -1.368\dot{\omega}_1\cos(\Delta\theta) + 1.363\omega_1^2\sin(\Delta\theta) - 92.913\sin(\theta_2) + \underline{0.032\omega_1},
\end{aligned}
\tag{5}
$$

where the explicit expression of physics in an ideal double pendulum system, as displayed in Eq. (5), are successfully distilled and damping terms are estimated. This set of equation is validated through interpolation on the testing set and compared with the smoothed derivatives, as shown in Appendix Figure C.4. The solution appears felicitous as the governing equations of the testing responses.

8 CONCLUSION AND DISCUSSION

This paper introduces a Symbolic Physics Learner (SPL) machine to tackle the challenge of distilling the mathematical structure of equations and nonlinear dynamics with unknown forms of measurement data. This framework is built upon the expression tree interpretation of mathematical operations and variables and an MCTS agent that searches for the optimistic policy to reconstruct the target mathematical expression. With some remarkable adjustments to the MCTS algorithms, the SPL model straightforwardly accepts prior or domain knowledge, or any sorts of constraints of the tasks in the grammar design while leveraging great flexibility in expression formulation. The robustness of the proposed SPL for complex target expression discovery with large search space is indicated in Nguyen's symbolic regression benchmark problems, where the SPL machine outperforms state-of-the-art symbolic regression methods. Moreover, encouraging results are obtained in the physics law and nonlinear dynamics discovery tasks that are based on synthetic or experimental datasets. While the proposed SPL framework shows huge potential in both symbolic regression and physics/nonlinear dynamics discovery tasks, there are still some imperfections that can be improved: (i) the computational cost is high for constant value estimation, (ii) graph modularity is underexamined, and (iii) robustness against extreme data noise and scarcity is not optimal. These limitations are further explained in Appendix Section D.

REFERENCES

Alexis Asseman, Tomasz Kornuta, and Ahmet Ozcan. Learning beyond simulated physics. In *Modeling and Decision-making in the Spatiotemporal Domain Workshop–NIPS*, 2018.

L Billard and E Diday. From the statistics of data to the statistics of knowledge: symbolic data analysis. *Journal of the American Statistical Association*, 98(462):470–487, 2003.

Josh Bongard and Hod Lipson. Automated reverse engineering of nonlinear dynamical systems. *Proceedings of the National Academy of Sciences*, 104(24):9943–9948, 2007.

Steven L Brunton, Joshua L Proctor, and J Nathan Kutz. Discovering governing equations from data by sparse identification of nonlinear dynamical systems. *Proceedings of the national academy of sciences*, 113(15):3932–3937, 2016.

Tristan Cazenave. Monte-carlo expression discovery. *International Journal on Artificial Intelligence Tools*, 22(01):1250035, 2013.

Kathleen Champion, Bethany Lusch, J Nathan Kutz, and Steven L Brunton. Data-driven discovery of coordinates and governing equations. *Proceedings of the National Academy of Sciences*, 116(45): 22445–22451, 2019.

Zhao Chen, Yang Liu, and Hao Sun. Physics-informed learning of governing equations from scarce data. *Nature Communications*, 12:6136, 2021.

Laurence Joseph Clancy. *Aerodynamics*. John Wiley & Sons, 1975.

Theodore Cornforth and Hod Lipson. Symbolic regression of multiple-time-scale dynamical systems. In *Proceedings of the 14th annual conference on Genetic and evolutionary computation*, pp. 735–742, 2012.

Rémi Coulom. Efficient selectivity and backup operators in monte-carlo tree search. In *International conference on computers and games*, pp. 72–83. Springer, 2006.

Brian M de Silva, David M Higdon, Steven L Brunton, and J Nathan Kutz. Discovery of physics from data: universal laws and discrepancies. *Frontiers in artificial intelligence*, 3:25, 2020.

Saso Dzeroski and Ljupco Todorovski. Discovering dynamics: from inductive logic programming to machine discovery. *Journal of Intelligent Information Systems*, 4(1):89–108, 1995.

Sašo Džeroski and Ljupéo Todorovski. Discovering dynamics. In *Proc. tenth international conference on machine learning*, pp. 97–103, 1993.

Richard P Feynman, Robert B Leighton, and Matthew Sands. The feynman lectures on physics; vol. i. *American Journal of Physics*, 33(9):750–752, 1965.

Sébastien Gaucel, Maarten Keijzer, Evelyne Lutton, and Alberto Tonda. Learning dynamical systems using standard symbolic regression. In *European Conference on Genetic Programming*, pp. 25–36. Springer, 2014.

Margaret Stautberg Greenwood, Charles Hanna, and Rev John W Milton. Air resistance acting on a sphere: Numerical analysis, strobe photographs, and videotapes. *The Physics Teacher*, 24(3): 153–159, 1986.

John E Hopcroft, Rajeev Motwani, and Jeffrey D Ullman. Automata theory, languages, and computation. *International Edition*, 24(2), 2006.

Mohiul Islam, Nawwaf N Kharma, and Peter Grogono. Expansion: A novel mutation operator for genetic programming. In *IJCCI*, pp. 55–66, 2018.

Samuel Kim, Peter Lu, Srijon Mukherjee, Michael Gilbert, Li Jing, Vladimir Ceperic, and Marin Soljacic. Integration of neural network-based symbolic regression in deep learning for scientific discovery. *arXiv preprint arXiv:1912.04825*, 2019.

John R Koza and John R Koza. *Genetic programming: on the programming of computers by means of natural selection*, volume 1. MIT press, 1992.

Jiří Kubalík, Jan Žegklitz, Erik Derner, and Robert Babuška. Symbolic regression methods for reinforcement learning. *arXiv preprint arXiv:1903.09688*, 2019.

Matt J Kusner, Brooks Paige, and José Miguel Hernández-Lobato. Grammar variational autoencoder. In *Proceedings of the 34th International Conference on Machine Learning*, pp. 1945–1954. JMLR. org, 2017.

Guillaume Lample and François Charton. Deep learning for symbolic mathematics. *arXiv preprint arXiv:1912.01412*, 2019.

William B Langdon and Steven M Gustafson. Genetic programming and evolvable machines: ten years of reviews. *Genetic Programming and Evolvable Machines*, 11(3):321–338, 2010.

Jeffrey Lindemuth. The effect of air resistance on falling balls. *American Journal of Physics*, 39(7): 757–759, 1971.

Zichao Long, Yiping Lu, Xianzhong Ma, and Bin Dong. Pde-net: Learning pdes from data. In *International Conference on Machine Learning*, pp. 3208–3216. PMLR, 2018.

Zichao Long, Yiping Lu, and Bin Dong. Pde-net 2.0: Learning pdes from data with a numeric-symbolic hybrid deep network. *Journal of Computational Physics*, 399:108925, 2019.

Edward N Lorenz. Deterministic nonperiodic flow. *Journal of the atmospheric sciences*, 20(2): 130–141, 1963.

Qiang Lu, Fan Tao, Shuo Zhou, and Zhiguang Wang. Incorporating actor-critic in monte carlo tree search for symbolic regression. *Neural Computing and Applications*, pp. 1–17, 2021.

Daniel L Ly and Hod Lipson. Learning symbolic representations of hybrid dynamical systems. *The Journal of Machine Learning Research*, 13(1):3585–3618, 2012.

Georg S Martius and Christoph Lampert. Extrapolation and learning equations. In *5th International Conference on Learning Representations, ICLR 2017-Workshop Track Proceedings*, 2017.

T Nathan Mundhenk, Mikel Landajuela, Ruben Glatt, Claudio P Santiago, Daniel M Faissol, and Brenden K Petersen. Symbolic regression via neural-guided genetic programming population seeding. *arXiv preprint arXiv:2111.00053*, 2021.

Brenden K Petersen, Mikel Landajuela Larma, Terrell N Mundhenk, Claudio Prata Santiago, Soo Kyung Kim, and Joanne Taery Kim. Deep symbolic regression: Recovering mathematical expressions from data via risk-seeking policy gradients. In *International Conference on Learning Representations*, 2021.

Michael JD Powell. An efficient method for finding the minimum of a function of several variables without calculating derivatives. *The computer journal*, 7(2):155–162, 1964.

Markus Quade, Markus Abel, Kamran Shafi, Robert K Niven, and Bernd R Noack. Prediction of dynamical systems by symbolic regression. *Physical Review E*, 94(1):012214, 2016.

Chengping Rao, Pu Ren, Yang Liu, and Hao Sun. Discovering nonlinear PDEs from scarce data with physics-encoded learning. In *International Conference on Learning Representations*, pp. 1–19, 2022.

Samuel H Rudy, Steven L Brunton, Joshua L Proctor, and J Nathan Kutz. Data-driven discovery of partial differential equations. *Science Advances*, 3(4):e1602614, 2017.

Subham Sahoo, Christoph Lampert, and Georg Martius. Learning equations for extrapolation and control. In *International Conference on Machine Learning*, pp. 4442–4450, 2018.

Abraham Savitzky and Marcel JE Golay. Smoothing and differentiation of data by simplified least squares procedures. *Analytical chemistry*, 36(8):1627–1639, 1964.

Michael Schmidt and Hod Lipson. Distilling free-form natural laws from experimental data. *science*, 324(5923):81–85, 2009.

Lawrence F Shampine. Computer solution of ordinary differential equations. *The initial value problem*, 1975.

Lawrence F Shampine and Mark W Reichelt. The matlab ode suite. *SIAM journal on scientific computing*, 18(1):1–22, 1997.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *Nature*, 550(7676):354–359, 2017.

Fangzheng Sun, Yang Liu, and Hao Sun. Physics-informed spline learning for nonlinear dynamics discovery. In *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence*, pp. 2054–2061, 2021.

Silviu-Marian Udrescu and Max Tegmark. Ai feynman: A physics-inspired method for symbolic regression. *Science Advances*, 6(16):eaay2631, 2020.

Silviu-Marian Udrescu and Max Tegmark. Symbolic pregression: discovering physical laws from distorted video. *Physical Review E*, 103(4):043307, 2021.

Silviu-Marian Udrescu, Andrew Tan, Jiahai Feng, Orisvaldo Neto, Tailin Wu, and Max Tegmark. Ai feynman 2.0: Pareto-optimal symbolic regression exploiting graph modularity. *arXiv preprint arXiv:2006.10782*, 2020.

Nguyen Quang Uy, Nguyen Xuan Hoai, Michael O'Neill, Robert I McKay, and Edgar Galván-López. Semantically-based crossover in genetic programming: application to real-valued symbolic regression. *Genetic Programming and Evolvable Machines*, 12(2):91–119, 2011.

Harsha Vaddireddy, Adil Rasheed, Anne E Staples, and Omer San. Feature engineering and symbolic regression methods for detecting hidden physics from sparse sensor observation data. *Physics of Fluids*, 32(1):015113, 2020.

David R White, Shin Yoo, and Jeremy Singer. The programming game: evaluating mcts as an alternative to gp for symbolic regression. In *Proceedings of the Companion Publication of the 2015 Annual Conference on Genetic and Evolutionary Computation*, pp. 1521–1522, 2015.

APPENDIX

A NGUYEN'S BENCHMARK PROBLEMS

This section provides more detailed experiment settings for Nguyen's benchmark tasks that are described in the Section 4 of the main context and then exhibits the training hyperparameters for the SPL machine in these equation discovery experiments: Table A.1 presents the candidate mathematical operations allowed for three tested models and Table A.2 displays training hyperparameters for the SPL machine in the Nguyen's benchmark tasks.

Table A.1: Candidate operators for each Nguyen's benchmark task. $const$ denotes the constant numerical values.

Benchmark	Candidate Operations
Nguyen-1	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot)$
Nguyen-2	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot)$
Nguyen-3	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot)$
Nguyen-4	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot)$
Nguyen-5	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot)$
Nguyen-6	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot)$
Nguyen-7	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot), \log(\cdot), \sqrt{\cdot}$
Nguyen-8	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot), \log(\cdot), \sqrt{\cdot}$
Nguyen-9	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot)$
Nguyen-10	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot)$
Nguyen-11	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot), \log(\cdot), \sqrt{\cdot}$
Nguyen-12	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot)$
Nguyen-1^c	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot), const$
Nguyen-2^c	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot), const$
Nguyen-5^c	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot), const$
Nguyen-8^c	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot), \log(\cdot), \sqrt{\cdot}, const$
Nguyen-9^c	$+, -, \times, \div, \cos(\cdot), \sin(\cdot), \exp(\cdot), const$

Table A.2: Training Hyperparameter settings for the SPL model in Nguyen's benchmark tasks.

Benchmark	Maximum Module Transplantation	Episodes Between Module Transplantation	Maximum Tree Size	Maximum Augmented Grammars
Nguyen-1	20	10,000	50	5
Nguyen-2	20	10,000	50	5
Nguyen-3	20	100,000	50	5
Nguyen-4	20	100,000	50	5
Nguyen-5	20	100,000	50	5
Nguyen-6	20	10,000	50	5
Nguyen-7	20	5,000	50	5
Nguyen-8	20	5,000	50	5
Nguyen-9	20	10,000	50	5
Nguyen-10	20	10,000	50	5
Nguyen-11	20	10,000	50	5
Nguyen-12	20	100,000	50	5
Nguyen-1^c	20	2,000	50	5
Nguyen-2^c	20	10,000	50	5
Nguyen-5^c	20	10,000	50	5
Nguyen-8^c	20	2,000	50	5
Nguyen-9^c	20	1,000	50	5

Table A.3: Mathematical constraints for the SPL machine in each Nguyen's benchmark problem.

Benchmark	Constraints Utilization
Nguyen-1	{1, 3}
Nguyen-2	{1, 3}
Nguyen-3	{1, 3}
Nguyen-4	{1, 3}
Nguyen-5	{2, 3}
Nguyen-6	{2, 3}
Nguyen-7	{2, 3}
Nguyen-8	{}
Nguyen-9	{2, 3, 4}
Nguyen-10	{2, 3, 4}
Nguyen-11	{2, 3}
Nguyen-12	{1, 3, 4}
Nguyen-1^c	{1, 3}
Nguyen-2^c	{1, 3}
Nguyen-5^c	{2, 3}
Nguyen-8^c	{}
Nguyen-9^c	{2, 3, 4}

Moreover, the utilization of CFG in the SPL machine facilitates the flexibility of applying some prior knowledge including the universal mathematical rules and constraints. This feature empirically turns out to be an accessible and scalable approach for avoiding meaningless mathematical expressions. In the Nguyen's benchmark tasks, one or multiple mathematical constraints are given to the SPL machine. These constraints include

1. Only variables and constant values allowed in trigonometric functions.

2. Variables in trigonometric functions, logarithms and roots are up to the polynomial of 3.

3. Trigonometric functions, logarithms and roots are not allowed to form unreasonable composite functions with each other, such as $\sin(\cos(...))$.

4. Some small integers (e.g. 1, 2) are used directly as leaves.

They can be easily implemented into the SPL machine by defining adjusting non-terminal nodes or production rules in the customized CFG. Constraints adopted by each task is shown in Table A.3.

B FREE FALLING BALLS WITH AIR RESISTANCE

This appendix section reveals more details in the data-driven discovery of the physics laws of relationships between height and time in the cases of free-falling objects with air resistance based on multiple experimental ball-drop datasets (de Silva et al., 2020). The datasets contain the records of 11 different types of balls, as shown in Figure B.1, dropped from a bridge with a 30 Hz sampling rate. The time between dropping and landing varies in each case, which is due to the fact that air resistance has different effects on these free-dropping balls and induces divergent physics laws. Consequently, we consider each ball as an individual experiment and discover physics laws for each of them. The measurement dataset of a free-dropping ball is split into a training set (records from the first 2 seconds, 60 measurement) and a testing set (records after 2 seconds).

The physics laws distilled by the three mathematically derived physics models displayed in the main text and the SPL machine from training data are exhibited in Table B.1. These discovered physics laws are then applied to forecast the height of the balls at the time slots in testing dataset. These predictions, in comparison with the ground truth trajectory recorded, are shown in Figure B.2. Prediction error is shown in the Table 3 of the main context.

Figure B.1: The experimental balls that were dropped from the bridge (de Silva et al., 2020). From left to right: golf ball, tennis ball, whiffle ball 1, whiffle ball 2, baseball, yellow whiffle ball, orange whiffle ball, green basketball, and blue basketball. Volleyball is not shown here.

Table B.1: Uncovered physics from the motions of free falling balls by the SPL machine and three baseline models

Type	Model	Expression
baseball	SPL	$H(t) = 47.8042 + 0.6253t - 4.5383t^2$
	Model-1	$H(t) = 47.682 + 1.456t - 5.629t^2 + 0.376t^3$
	Model-2	$H(t) = 45.089 - 8.156t + 5.448 \exp(0t)$
	Model-3	$H(t) = 48.051 - 183.467 \log(\cosh(0.217t))$
blue basketball	SPL	$H(t) = 46.4726 - 5.105t^2 + t^3 - 0.251t^4$
	Model-1	$H(t) = 46.513 - 0.493t - 3.912t^2 + 0.03t^3$
	Model-2	$H(t) = 43.522 - 7.963t + 5.306 \exp(0t)$
	Model-3	$H(t) = 46.402 - 84.791 \log(\cosh(0.319t))$
green basketball	SPL	$H(t) = 45.9087 - 4.1465t^2 + \log(\cosh(1))$
	Model-1	$H(t) = 46.438 - 0.34t - 3.882t^2 - 0.055t^3$
	Model-2	$H(t) = 43.512 - 8.043t + 5.346 \exp(0t)$
	Model-3	$H(t) = 46.391 - 124.424 \log(\cosh(0.263t))$
volleyball	SPL	$H(t) = 48.0744 - 3.7772t^2$
	Model-1	$H(t) = 48.046 + 0.362t - 4.352t^2 + 0.218t^3$
	Model-2	$H(t) = 45.32 - 7.317t + 5.037 \exp(0t)$
	Model-3	$H(t) = 48.124 - 107.816 \log(\cosh(0.27t))$
bowling ball	SPL	$H(t) = 46.1329 - 3.8173t^2 - 0.2846t^3 + 4.14 \times 10^{-5} \exp(20.7385t^2) \exp(-12.4538t^3)$
	Model-1	$H(t) = 46.139 - 0.091t - 3.504t^2 - 0.431t^3$
	Model-2	$H(t) = 43.336 - 8.525t + 5.676 \exp(0t)$
	Model-3	$H(t) = 46.342 - 247.571 \log(\cosh(0.189t))$
golf ball	SPL	$H(t) = 49.5087 - 4.9633t^2 + \log(\cosh(t))$
	Model-1	$H(t) = 49.413 + 0.532t - 5.061t^2 + 0.102t^3$
	Model-2	$H(t) = 46.356 - 8.918t + 5.964 \exp(0t)$
	Model-3	$H(t) = 49.585 - 178.47 \log(\cosh(0.23t))$
tennis ball	SPL	$H(t) = 47.8577 - 4.0574t^2 + \log(\cosh(0.121t^3))$
	Model-1	$H(t) = 47.738 + 0.658t - 4.901t^2 + 0.325t^3$
	Model-2	$H(t) = 45.016 - 7.717t + 5.212 \exp(0t)$
	Model-3	$H(t) = 47.874 - 114.19 \log(\cosh(0.269t))$
whiffle ball 1	SPL	$H(t) = 4.1563t^2 - t^3 + 47.0133 \exp(-0.1511t^2)$
	Model-1	$H(t) = 46.969 + 0.574t - 4.505t^2 + 0.522t^3$
	Model-2	$H(t) = 44.259 - 6.373t + 4.689 \exp(0t)$
	Model-3	$H(t) = 47.062 - 34.083 \log(\cosh(0.462t))$
whiffle ball 2	SPL	$H(t) = -18.6063 + 65.8583 \exp(-0.0577t^2)$
	Model-1	$H(t) = 47.215 + 0.296t - 4.379t^2 + 0.421t^3$
	Model-2	$H(t) = 44.443 - 6.744t + 4.813 \exp(0t)$
	Model-3	$H(t) = 47.255 - 38.29 \log(\cosh(0.447t))$
yellow whiffle ball	SPL	$H(t) = 148.9911/(\log(\cosh(t)) + 3.065) - 14.5828t^2/(\log(\cosh(t)) + 3.065)$ $+48.6092 \log(\cosh(t))/(\log(\cosh(t)) + 3.065)$
	Model-1	$H(t) = 48.613 - 0.047t - 4.936t^2 + 0.826t^3$
	Model-2	$H(t) = 45.443 - 6.789t + 4.973 \exp(0t)$
	Model-3	$H(t) = 48.594 - 12.49 \log(\cosh(0.86t))$
orange whiffle ball	SPL	$H(t) = -1.6626t + 47.8622 \exp(-0.06815t^2)$
	Model-1	$H(t) = 47.836 - 1.397t - 3.822t^2 + 0.422t^3$
	Model-2	$H(t) = 44.389 - 7.358t + 5.152 \exp(0t)$
	Model-3	$H(t) = 47.577 - 12.711 \log(\cosh(0.895t))$

Figure B.2: Trajectories after 2 seconds predicted by uncovered physics laws.

C NONLINEAR DYNAMICS DISCOVERY

This appendix section expands the two governing equation discovery experiments presented in the main context, including the datasets and full results.

C.1 LORENZ SYSTEM

The 3-dimensional Lorenz system is governed by

$$
\begin{aligned}
\dot{x} &= \sigma(y - x) \\
\dot{y} &= x(\rho - z) - y \\
\dot{z} &= xy - \beta z
\end{aligned}
\tag{6}
$$

with parameters $\sigma = 10$, $\beta = 8/3$, and $\rho = 28$, under which the Lorenz attractor has two lobes and the system, starting from anywhere, makes cycles around one lobe before switching to the other and iterates repeatedly. The measurement data of Lorenz system in this experiment contains a clean signal with 5% Gaussian white noise. The derivatives of Lorenz's state variables are numerically estimated and smoothed by the Savitzky–Golay filter. The noisy synthetic measurement and numerically obtained derivatives are shown in Figure C.1,

Noisy Measurement | Estimated Derivatives

Figure C.1: Lorenz system for experiment. Noisy measurement data and numerically estimated derivatives smoothed by Savitzky–Golay filter.

Table C.1: Discovered governing equations for the Lorenz system.

Model	Discovered Governing Equations
Eureqa	$\dot{x} = -0.56 - 9.02x + 9.01y$
$\dot{y} = -0.047 + 18.79x + 1.86y - 0.046xy - 0.74xz$
$\dot{z} = -3.04 - 2.23z + 0.88xy$
pySINDy	$\dot{x} = -0.46 - 9.18x + 9.17y$
$\dot{y} = 22.32x + 0.15y - 0.85xz$
$\dot{z} = 6.04 - 2.83z + 0.15x^2 + 0.81xy$
NGGP	$\dot{x} = 0.0047 - 10.02x + 10.01y - 0.007x^2 + 0.007xy - 0.37x/z - 0.00074x^2y$
$\quad + 0.00063x^3 + 0.00018x^2z + 0.00011xy^2 - 6.59e^{-5}xyz - 0.00011y^z$
$\dot{y} = 26.36x - 1.5y - 0.83xz - 7.20x/z + 13.08y/z + 4.52e^{-5}x^3 - 0.0038xz^2$
$\quad - 44.25x/z^2 + 0.00028x^3/z - 0.00017x^3z + 5.98e^{-6}x^3z^2$
$\dot{z} = -0.64 - 0.036y - 2.64z + 1.038xy + 0.00021xz + 0.0011yz - 0.00021x/z$
$\quad - 8.04e^{-8}y/x + 0.00022y/z - 8.04e^{-8}z^2 - 0.00021xyz + 0.00021xy/z$
$\quad - 0.001y^2z - 0.00021y^2/z + 1.17y/z^2 - 3.89e^{-7}yz^2/x + 6.66e^{-9}z^2/x$
SPL	$\dot{x} = -9.966x + 9.964y$
$\dot{y} = 27.764x - 0.942y - 0.994xz$
$\dot{z} = -2.655z + 0.996xy$
True	$\dot{x} = -10x + 10y$
$\dot{y} = 28x - y - xz$
$\dot{z} = -2.667z + xy$

Figure C.2: Response prediction for 5 seconds by identified governing equations (dashed plots) under a different validation IC of Lorenz system, in comparison with the ground truth trajectory (grey).

Figure C.3: Double Pendulum system experiment and measurement data (Asseman et al., 2018): A. experiment setup. B. displacements of the two moving masses. C. model the system with θ_1 and θ_2. D. angles of two masses transformed from displacements.

Table C.1 presents the distilled governing equations of the Lorenz system by 4 tested models. It is observed that the SPL uncover the explicit form of equations accurately in the context of active terms, whereas Eureqa, pySINDy and NGGP yield several false-positive terms in governing equations. 5-second predicted system responses (starting from a different initial condition) simulated from these uncovered equations are shown in Figure C.2. Though it is hard to reproduce the most accurate coefficients due to the tremendous errors due to numerical differentiation of noisy measurement as depicted in Figure C.1, the SPL machine is still capable of distilling the most concise symbolic combination of operators and variables to correctly formulate parsimonious mathematical expressions that govern the Lorenz system. The predicted responses from the governing equations unearthed by the SPL machine simulates the system in a decent manner.

C.2 MOUNTED DOUBLE PENDULUM SYSTEM

The second nonlinear dynamics discovery experiment is on a camera-measured chaotic double pendulum system (Asseman et al., 2018). The sensed data is in form of videos of the chaotic motion of a double pendulum on the device shown in Figure C.3A filmed with a high-speed camera. The positional data is converted into angular form by using the model shown in Figure C.3C. The governing equations for a mounted pendulum system can be derived with Euler–Lagrange method:

$$
\begin{aligned}
(m_1 + m_2)l_1\ddot{\theta}_1 + m_2l_2\ddot{\theta}_2\cos(\theta_1 - \theta_2) + m_2l_2\omega_2^2\sin(\theta_1 - \theta_2) + (m_1 + m_2)g\sin(\theta_1) = F_1, \\
m_2l_2\ddot{\theta}_2 + m_2l_1\ddot{\theta}_1\cos(\theta_1 - \theta_2) - m_2l_1\omega_1^2\sin(\theta_1 - \theta_2) + m_2g\sin(\theta_2) = F_2,
\end{aligned}
\tag{7}
$$

which, by denoting ω as the velocity, can be converted to the form of

$$
\begin{aligned}
\dot{\theta}_1 &= \omega_1, \\
\dot{\theta}_2 &= \omega_2, \\
\dot{\omega}_1 &= c_1\dot{\omega}_2\cos(\Delta\theta) + c_2\omega_2^2\sin(\Delta\theta) + c_3\sin(\theta_1) + \mathcal{R}_1(\theta_1, \theta_2, \dot{\theta}_1, \dot{\theta}_2), \\
\dot{\omega}_2 &= c_1\dot{\omega}_1\cos(\Delta\theta) + c_2\omega_1^2\sin(\Delta\theta) + c_3\sin(\theta_2) + \mathcal{R}_2(\theta_1, \theta_2, \dot{\theta}_1, \dot{\theta}_2)
\end{aligned}
\tag{8}
$$

where $\Delta\theta = \theta_1 - \theta_2$, and $\mathcal{R}_1(\theta_1, \theta_2, \dot{\theta}_1, \dot{\theta}_2)$ and $\mathcal{R}_2(\theta_1, \theta_2, \dot{\theta}_1, \dot{\theta}_2)$ denote the damping terms for the last two differential equations.

The data source contains multiple camera-sensed datasets. For this discovery, 5,000 denoised random sub-samples from 5 datasets are used for training purposes, and 2,000 random sub-samples from another 2 datasets for validation, and 1 dataset for testing. Some prior knowledge guiding this the discovery includes:

1. $\dot{\omega}_2\cos(\Delta\theta)$ for $\dot{\omega}_1$ and $\dot{\omega}_1\cos(\Delta\theta)$ for $\dot{\omega}_2$ are easily derived. Both terms are given.

Figure C.4: Discovered governing equations of the mounted double pendulum system on a different dataset in different time sections: in 2-8 seconds the two masses are in chaotic motions while in 30-36 seconds the masses tend to move periodically due to accumulative damping. $\ddot{\theta}_1$ and $\ddot{\theta}_2$ are obtained through smoothed numerical differentiation and predicted from the discovered governing equations.

2. the remaining of the formulas are potentially comprised of the free combination of $\dot{\omega}_1$, $\dot{\omega}_2$, ω_1, ω_2, as well as the angles (θ_1, θ_2, $\Delta\theta$) under the trigonometric functions $\cos(\cdot)$ and $\sin(\cdot)$.

3. velocities and relative velocities of two masses, as well as their directions (sign function) might contribute to the damping.

Based on these information, the candidate production rules for governing differential equations $\dot{\omega}_1$ and $\dot{\omega}_2$ are shown as below, where non-terminal nodes are $V = \{A, W, T, S\}$ and C denotes the placeholder symbol for constant values.

$$A \to A + A, A \to A \times A, A \to C, A \to A + A, A \to W,$$

$$W \to W \times W, W \to \omega_1, W \to \omega_2, W \to \dot{\omega}_1, W \to \dot{\omega}_2,$$

$$A \to \cos(T), A \to \sin(T), T \to T + T, T \to T - T, T \to \theta_1, T \to \theta_2,$$

$$A \to sign(S), S \to S + S, S \to S - S, S \to \omega_1, S \to \omega_2, S \to \dot{\omega}_1, S \to \dot{\omega}_2$$

$$A \to \dot{\omega}_1 \cos(\theta_1 - \theta_2), A \to \dot{\omega}_2 \cos(\theta_1 - \theta_2)$$

The hyperparameters are set as $\eta = 1$, $t_{max} = 20$, and 40,000 episodes of training is regarded as one trail. 5 independent trials are performed and the equations with the highest validation scores are selected as the final results. The uncovered equations are shown in Table C.2. They are validated through interpolation on the testing set and compared with the smoothed derivatives, as shown in Figure C.4. The solution appears felicitous as the governing equations of the testing responses.

Table C.2: Discovered governing equations of the mounted double pendulum by the SPL model.

Phase	Expression
$\dot{\omega}_1$	$-0.0991\dot{\omega}_2\cos(\Delta\theta) - 0.103\omega_2^2\sin(\Delta\theta) - 69.274\sin(\theta_1) + 0.515\cos(\theta_1)$
$\dot{\omega}_2$	$-1.368\dot{\omega}_1\cos(\Delta\theta) + 1.363\omega_1^2\sin(\Delta\theta) - 92.913\sin(\theta_2) + 0.032\omega_1$

Table C.3: Average training time (in seconds) of SPL and NGGP in the Nguyen's benchmark problems

Benchmark	SPL[s]	NGGP[s]
Nguyen-1	8.776	2.734
Nguyen-2	7.296	3.296
Nguyen-3	81.287	3.945
Nguyen-4	567.061	5.764
Nguyen-5	431.228	77.627
Nguyen-6	64.651	104.588
Nguyen-7	14.995	3.024
Nguyen-8	5.59	2.896
Nguyen-9	5.743	13.229
Nguyen-10	53.245	86.497
Nguyen-11	10.163	44.399
Nguyen-12	187.9	334.757
Nguyen-1^c	452.734	362.075
Nguyen-2^c	295.769	1188.215
Nguyen-5^c	2178.891	1365.777
Nguyen-8^c	77.892	129.349
Nguyen-9^c	2001.402	3066.41

D DISCUSSION AND FUTURE DIRECTIONS

While the proposed SPL framework shows huge potential in both symbolic regression and physics law/governing equation discovery tasks, there are still some imperfections to be improved. In this appendix section, a few bottlenecks and their potential solutions are presented:

1. **Computational cost.** Computational cost for this framework is one of the major issues, especially when constant estimation is required. Evaluating the solution in the simulation phase happens very frequently for the MCTS algorithm where the policy selection relies heavily on a large number of historical rewards. However, constant value estimation, which can be slow, is required for evaluation purposes. The SPL machine is not the only symbolic regressor suffering from the computational cost in constant value estimation. In fact, the state-of-the-art symbolic regression model, the neural-guided GP (NGGP) (Mundhenk et al., 2021), becomes much slower in the Nguyen's benchmark variant tasks (see Table C.3).

   The current implementation of the SPL machine tries to empirically avoid this issue by limiting the number of placeholders in a discovered expression and simplifying the expression before evaluating, but still cannot reach a great efficiency. This bottleneck might be mitigated if parallel computing is introduced to the MCTS simulation phase.

2. **Graph modularity underexamined.** The current design of the SPL training scheme does not leverage the full graph modularity: modules are reached by transforming a complete parse tree into a grammar. However, in some cases, there might be some influential modules appearing frequently as part of the tree. This type of graph modularity is described in the AI-Feynman method (Udrescu et al., 2020). Deploying a more comprehensive graph modularity into the SPL machine will boost its efficacy in complex equation and nonlinear dynamics discovery tasks.

3. **Robustness against extreme data noise and scarcity.** Though it is observed that this reinforcement learning-based method is able to unearth the parsimonious solution to the governing equations from synthetic or measurement data with a moderate level of noise and scarcity. It is not effective when the data condition is too extreme, or if there are missing values that make it challenging to numerically calculate the state derivatives. It is reasonable to investigate the integration between the SPL framework with a physics-guided surrogate model that are built upon neural networks (Long et al., 2018; Chen et al., 2021) or spline learning (Sun et al., 2021) for further robustness in nonlinear dynamics discovery tasks.