CONTRASTIVE TRAINING WITH MORE DATA

ABSTRACT

This paper proposes a new method of contrastive training over multiple data points, focusing on the scaling issue present when using in-batch negatives. Our approach compares transformer training with dual encoders versus training with multiple encoders. Our method can provide a feasible approach to improve loss modelling as encoders scale.

1 LINEAR APPROACHES FOR ADDITIONAL ENCODER STREAMS

Typical contrastive training uses two auto-encoders, but we explore instances of n auto-encoders where $n > 2$. Consider the case, $n = 3$, where auto-encoder outputs are X, Y and Z respectively. We maintain the linear relation present in CLIP Radford et al. (2021) by iterating over pairs; $CosineSimilarity(XY)$, $CosineSimilarity(XZ)$, $CosineSimilarity(YZ)$, and then calculating the graphs for each of them. While there are some minor optimizations available for this case, the ratio of in-batch negatives is not improved, and training time is adversely affected as n increases.

2 A CONSIDERATION OF COSINE SIMILARITY WITH ADDITIONAL DIMENSIONS

With two encoders (and their respective data inputs) the loss generated with the cosine similarity is modified for faster execution, to be the matrix multiplication of 2 fractions.

$$(\frac{a}{\sqrt{\sum a}}) \times (\frac{b}{\sqrt{\sum b}}) \tag{1}$$

In this matrix multiplication, a transpose is used, and the operation is limited to just two dimensions. Two dimensions are fine with just two operands. With two encoders, the ratio of positive to negative samples within a batch, B, is simply $1 : B - 1$. For every additional encoder, the exponent of B in the ratio of $1 : B - 1$ will increase by 1.

For $n = 2$ vectors, $y_1.y_2$ is a good similarity metric; 2 negative samples return a positive similarity. Now consider the case of $n > 2$, the dot-product of $y_1 \times y_2 \times y_3....y_n$,and consider the vectors a, b and c. $a \times b \times c$ is positive if a, b and c are positive, and it is negative if all are negative. This means that naturally maximizing $a \times b \times c$ can promote some values within $[a, B, c]$ to become negative.

3 CORRECTING LOSS

Cosine similarity allows a reduction in size as it is performed: matrix multiplications being relatively quick operations. By contrast, calculating a similarity S as $S = 1 - variance$ requires more complex steps of computation. An initial observation may require extra arrays created for computation, such as size $B^n \times F \times n$, where F is the feature space. Even with extensive work to reduce this footprint, it drastically reduces the achievable batch size for a finite amount of hardware.

4 EUCLIDEAN DISTANCE-BASED ERROR

An alternative to cosine similarity can be to sum the distance (D) from the mean of each feature. Thus,

$$Loss = 1 - L2Norm(D), \tag{2}$$

where

$$D = x_i - \bar{x}, \tag{3}$$

with $L2Norm(D)$ as $\sqrt{\sum(D^2)}$. However, the mean across all features is of shape $B^n \times f$. The following holds for when x_i is a single feature in each encoder output, and when x_i is the whole output of shape $B \times f$. We use the following formulae for calculating $1 - L2Norm(D)$:

$$Loss = 1 - \sqrt{\sum_{i=0}^{n}(x_i{}^2 + \bar{x}^2 - 2x_i\bar{x})} \tag{4}$$

$$Loss = 1 - \sqrt{\sum_{i=0}^{n}(x_i{}^2) + \sum_{i=0}^{n}(\bar{x}^2) - \sum_{i=0}^{n}(2x_i\bar{x})} \tag{5}$$

Therefore,

$$Loss = 1 - \sqrt{\sum_{i=0}^{n}(x_i{}^2) + \frac{(\sum x)^2}{n} - \sum_{i=0}^{n}(2x_i\bar{x})} \tag{6}$$

We can further convert the maths expression $\sum_{i=0}^{n}(2x_i\bar{x})$ into $2\bar{x}\sum_{i=0}^{n}x_i$, which can also be expressed as $-2\frac{(\sum x)^2}{n}$. Giving:

$$Loss = 1 - \sqrt{\sum_{i=0}^{n}(x_i^2) - \frac{(\sum x)^2}{n}} \tag{7}$$

Naturally, this means that much less computation is needed with n-dimensional arrays, substantially reducing the computational load.

Batch logits in n=3 dimensions

Figure 1: A plot of logits where $n = 3$ and $B = 10$.

As explained previously, the proposed approach is moving from logits of shape $B \times B$ to logits in the form B^n, as illustrated by Figure 1, where each value corresponds to items in each batch, x_i. The location (i, j, k) in the cube is the variance between the set of features between inputs $[x_{0,i}, x_{1,j}, x_{2,k}]$. All logits are combined in the cube space, with maximum values on the highlighted diagonals being the target.

REFERENCES

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision, 2021. URL `https://arxiv.org/abs/2103.00020`.