Attend to who you are: Supervising self-attention for Keypoint Detection and Instance-Aware Association

Abstract

Bottom-up multi-person pose estimation models need to detect keypoints and learn associative information between keypoints. We argue that these problems can be entirely solved by the Transformer model. Specifically, the self-attention in Transformer measures the pairwise dependencies between locations, which can play a role in providing association information for keypoints grouping. However, the naive attention patterns are still not subjectively controlled, so there is no guarantee that the keypoints will always attend to the instances to which they belong. To address it we propose a novel approach of multi-person keypoint detection and instance association using instance masks to supervise self-attention. By supervising self-attention to be instance-aware, we can assign the detected keypoints to the correct human instances based on the pairwise attention scores, without using pre-defined offset vector fields or embedding like CNN-based bottom-up models. An additional benefit of our method is that the instance segmentation results of any number of people can be directly obtained from the supervised attention matrix, thereby simplifying the pixel assignment pipeline. The experiments on the COCO multi-person keypoint detection challenge and person instance segmentation task demonstrate the effectiveness and simplicity of the proposed method.

1 Introduction

Multi-person pose estimation approaches usually can be classified into two schemes: top-down or bottom-up. Unlike the top-down scheme that converts the pipeline into two independent tasks – detection and single-pose estimation, the bottom-up scheme is confronted with more challenging problems. An unknown number of persons with any scale, posture, or occlusion condition may appear at any location of the input image. The bottom-up approaches need to detect all body joints first and group them into instances second. In the typical systems such as DeeperCut (Insafutdinov et al., 2016), OpenPose (Cao et al., 2017), Associative Embedding (Newell et al., 2017), PersonLab (Papandreou et al., 2018), PifPaf (Kreiss et al., 2019) and CenterNet (Zhou et al., 2019), keypoint detection and grouping are usually regarded as two heterogeneous learning targets. This requires the model to learn the keypoint heatmaps encoding position information and the human knowledge guided signals encoding association information such as part hypotheses, part affinity fields, associative embeddings or offset vector fields.

In this paper we explore whether we can exploit the instance semantic clues implicitly used by the model to group the detected keypoints into individual instances. Our intuition is that when the model predicts a location of a specific keypoint, it may know the human instance region this keypoint belongs to, which means that the model has implicitly associated related joints together. For example, when an elbow is recognized, the model may learn its strong spatial dependencies in its adjacent wrist or shoulder but weak dependencies in the joints of other persons. Therefore, if we can read out such information learned and encoded in the model, the detected keypoints can be correctly grouped into instances without the help of the human pre-defined associative signals.

We argue that self-attention model (Vaswani et al., 2017) can meet this requirement because it can provide image-specific pairwise similarities between image locations and the resulting attention patterns show object-related semantics. Therefore, we attempt to use self-attention mechanism to

Figure 1: We choose two examples to show differences between the naive and supervised self-attention patterns. The association reference for the naive self-attention is the average of all layers.

perform multi-person pose estimation. But instead of following the top-down strategy with the single person region as the input, we feed the Transformer model the input images with the presence of multiple persons and expect it to output the heatmaps encoding multi-person keypoint locations. Then we have such findings that 1) the heatmaps outputted by Transformer can also accurately respond to multiple persons' keypoints at multiple candidate locations; 2) the attention scores between the detected keypoint locations tend to be higher within the same person, but lower across different persons. Based on these findings, we introduce an attention-based parsing algorithm to group the detected keypoints into different human instances.

Unfortunately, the naive self-attention does not always show desirable properties. In some cases, a detected keypoint also probably have relatively higher attention scores with those belonging to different person instances. This will definitely lead to wrong associations and implausible human poses. To address this issue, we propose a novel method that leverages a loss function to explicitly supervise the attention area of each person instance by the mask of the instance. The results show that supervising self-attentions in such a way can achieve the expected instance-discriminative characteristics without affecting the standard forward propagation of Transformer. Such characteristics guarantee the effectiveness and accuracy of the attention-based grouping algorithm. The results on the COCO keypoint detection challenge show that our models with limited refinement can achieve comparable performances compared with the highly optimized bottom-up pose estimation systems (Cao et al., 2017; Newell et al., 2017; Papandreou et al., 2018). Meanwhile, we also can easily obtain the person instance masks by sampling the corresponding attention areas, thereby avoiding an extra pixel assignment or grouping algorithm.

1.1 KEY CONTRIBUTIONS

Using self-attention to unify keypoints detection, grouping and human mask prediction. We use Transformer to solve the challenging multi-person keypoint detection, grouping and mask prediction in a unified way. We realize that the self-attention shows instance-related semantics, which can be served as the association information in a bottom-up fashion. We further use instance masks to supervise the self-attention. It ensures that each keypoint is assigned to the correct human instance according to the attention scores, making it easy to obtain the instance masks as well.

Supervising self-attention "for your need". A common practice of using Transformer models is to use task-specific signals to supervise the final output of transformer-based models, such as class labels, object box coordinates, keypoint positions or semantic masks. A key novelty of our method is that we supervise the immediate self-attention process to control its patterns for our use. The self-attention achieves instance-aware characteristics for the multi-person pose estimation and mask prediction without destroying the standard forward of Transformer. This demonstrates that using appropriate guidance signals can make self-attention show controllable characteristics and help the model learning, which may be useful for other vision tasks such as for instance segmentation (Wang et al., 2021) and object detection (Carion et al., 2020).

2 METHOD

2.1 PROBLEM SETTING

Given a RGB image I of size $3 \times H \times W$, the goal of 2D multi-person pose estimation is to estimate all persons' keypoints locations: $\mathbb{S} = \{(x_i^k, y_i^k)|i = 1, 2, ..., N; k = 1, 2, ..., K\}$, where N is the number of persons in this image and K is the number of defined keypoint types.

We follow the bottom-up strategy. First, the model detects all the candidate locations for each type of keypoints in an image: $\mathbb{C} = \mathbb{C}_1 \bigcup \mathbb{C}_2 \bigcup ... \bigcup \mathbb{C}_K$, where $\mathbb{C}_k = \{(\hat{x}_i, \hat{y}_i)|i = 1, 2, ..., N_k\}$ represents the k-th type of keypoint set with N_k detected candidates. Second, a heuristic decoding algorithm g groups all candidates into M skeletons based on the association information $\mathcal{A}$, which determines a unique person ID for each keypoint location. We formulate this process as: $g((\hat{x}_i, \hat{y}_i), \mathbb{C}, \mathcal{A}) \to m \in \{1, 2, ..., M\}$.

Next, we present the model architecture and show how to use self-attention as the association information $\mathcal{A}$. We analyze the problems when using the naive self-attention as the grouping reference. We propose to supervise self-attention via instance masks for keypoints grouping. We present two types of grouping algorithm from the *body-first* and *part-first* views. Finally, we describe how we obtain the person instance masks and how we use the obtained masks to refine the results.

2.2 NETWORK ARCHITECTURE AND NAIVE SELF-ATTENTION

Architecture. We use a simple architecture combination that includes ResNet (He et al., 2016) and Transformer encoder (Vaswani et al., 2017), like the design of TransPose (Yang et al., 2021). The downsampled feature maps of ResNet with r stride are flattened to a sequence of $L \times d$ size and sent to Transformer where $L = \frac{H}{r} \times \frac{W}{r}$. Several transposed convolutions and a 1×1 convolution are used to upsample the Transformer output into the target keypoint heatmap size $K \times \frac{H}{4} \times \frac{W}{4}$.

Heatmap loss. To observe what patterns the self-attentions layers spontaneously learn, we first only leverage the mean square error (MSE) loss between the predicted heatmap $\hat{\mathbf{H}}_k$ and the groundtruth heatmap $\mathbf{H}_k$ to train the model:

$$\mathcal{L}_{heatmap} = \frac{1}{K} \sum_{k=1}^{K} \mathbf{M} \cdot \left\| \hat{\mathbf{H}}_k - \mathbf{H}_k \right\|, \tag{1}$$

where $\mathbf{M}$ is a mask that masks out the crowd areas and small size person segments in the whole image.

The keypoint detection results show the trained model can accurately localize keypoints of multiple persons. We obtain the local maximum locations from keypoint heatmaps and further visualize the attention areas of these locations. As the examples shown in Figure 1 reveal, using the naive self-attention matrices as the association reference poses several challenges: 1) There are multiple attention layers in Transformer, each of which shows distinct characteristics. Selecting which attention layers as the association reference and how to process the raw attention require a very thoughtful fusion and post-processing strategy. 2) Although most of the sampled keypoint locations show local attention areas, especially for the people they belong to, some keypoints may still produce relatively high attention scores for the parts of other people at a longer distance. It is almost impossible to determine a perfect attention threshold for all situations. As a consequence, the attention-based grouping algorithm cannot ensure the correctness of the keypoint assignment. A wrong connection between a joint of Person A with a joint of Person B will cause more errors in sequential connections.

2.3 SUPERVISING SELF-ATTENTION BY INSTANCE MASKS

To address the aforementioned challenges of using the naive self-attention for keypoints grouping, we **S**upervise **S**elf-**A**ttention (**SSA**) to be what we expect. Ideally, the expected attention pattern should be that each keypoint location only attends to the person instance it belongs to. The person instance mask is an ideal guidance signal. Then we propose a sparse sampling method based on the instance keypoint locations to supervise the specific attention matrix generated by the self-attention computation in Transformer, as illustrated in Figure 2.

Figure 2: Model overview. The model architecture consists of three parts: a regular ResNet, a regular Transformer encoder, and several transposed convolutional layers. The final output of the model is supervised by the groundtruth keypoint heatmaps. We choose one of the immediate self-attention layers to supervise by the instance masks. In particular, we sample the rows of the attention matrix of the chosen attention layer according to the visible keypoint locations of each human instance, reshape them into 2D-like maps, and then use the mask of each instance to supervise the average map. In this figure, we only show a few keypoints of each instance.

Instance mask loss. We suppose that the p-th person's keypoints groudtruth locations are $\left\{(x_p^k, y_p^k, v_p^k)\right\}_{k=1}^{K}$, where $v_p^k \in \{0, 1\}$ is a visibility flag, i.e., $v_p^k = 0$: not labeled, $v_p^k = 1$: labeled. We take out the immediate attention matrix $\mathbf{A} = \mathrm{Softmax}(\frac{\mathbf{Q}\mathbf{K}^\top}{\sqrt{d}}) \in \mathbb{R}^{L \times L}$ of the specific layer in Transformer[1] to leverage the supervision. We first reshape the attention matrix $\mathbf{A}$ into a tensor $\mathbf{A}$ of $(h \times w) \times (h \times w)$ size, where $h = H/r, w = W/r$. Then we transform the keypoint coordinates into the coordinate system of the downsampled feature maps. And then we take out the corresponding rows of the attention matrix specified by these locations. So we can obtain the reshaped attention map at each keypoint location: $\mathbf{A}[int(y_p^k/r), int(x_p^k/r), :, :]$. For a person instance, we sample and average the attention maps based on its *visible* keypoint locations to estimate the mean attention map. We name it as *person attention map* $\mathbf{A}_p$:

$$\mathbf{A}_p = \frac{1}{\sum_{i=1}^{K} v_p^i} \sum_{k=1}^{K} v_p^k \cdot \mathbf{A}[int(y_p^k/r), int(x_p^k/r), :, :]. \tag{2}$$

Assuming the groundtruth mask of the p-th person in the image is $\mathbf{M}_p$, we also use the MSE loss function to supervise the attention matrix sparsely. Since the self-attention scores have been normalized by the softmax function, we need to rescale the $\mathbf{A}_p$ by dividing its maximum value so that the rescaled $\mathbf{A}_p$ is closer to the value range of the annotated mask. Note that the size of $\mathbf{A}_p$ is $\frac{H}{r} \times \frac{W}{r}$ while the groundtruth instance mask is constructed to be $\frac{H}{4} \times \frac{W}{4}$ size. So we use $r/4$ times bilinear interpolation to resize the $\mathbf{A}_p$ to have the same size as the instance mask. We formulate the instance mask loss as:

$$\mathcal{L}_{mask} = \mathrm{MSE}(\mathrm{bilinear}(\mathbf{A}_p/\max(\mathbf{A}_p)), \mathbf{M}_p) = \frac{1}{N} \sum_{p=1}^{N} \|\mathrm{bilinear}(\mathbf{A}_p/\max(\mathbf{A}_p)) - \mathbf{M}_p\|. \tag{3}$$

Objective. So the overall objective for training the model is:

$$\mathcal{L}_{train} = \alpha \cdot \mathcal{L}_{heatmap} + \beta \cdot \mathcal{L}_{mask}, \tag{4}$$

where α and β are two coefficients to balance two types of learning. In the standard self-attention computation of Transformer, the attention matrix is computed by the inner products of *queries* and *keys*. Its gradient back-propagation information is entirely derived from the subsequent attention weighted sum of *values*. By introducing the instance mask loss to supervise the self-attention, the gradient learning direction for the supervised attention matrix has two sources: the implicit gradient signal from keypoint heatmaps learning and the explicit similarity constraint from instance mask learning. Choosing approximate values of α and β is critical for training the model well. We set $\alpha = 1, \beta = 0.01$ to balance both heatmap learning and mask learning.

---

[1]$\mathbf{Q}, \mathbf{K} \in \mathbb{R}^{L \times d}$ are queries and keys. For simplicity we consider there is only one head. For multihead self attention, the attention matrix $\mathbf{A}$ is the average of all heads' attention matrices.

2.4 KEYPOINTS GROUPING

When the well-trained model makes a single forward pass for a given image, we can decode the multi-person human poses and masks from the outputted keypoint heatmaps and the supervised attention matrix in the immediate attention layer. We first conduct non-maximum suppression in a 7×7 local window on the keypoint heatmaps and obtain all local maximum locations whose scores exceed the threshold t. We put all these candidates into a queue and decode them into skeletons using the attention-based algorithm. Using the self-attention similarity matrix with quadratic complexity in-

Figure 3: Self-Attention based Grouping. When the founded keypoints in a skeleton induce a stronger attention attraction to an unmatched keypoint, this candidate will be assigned to this skeleton. The blue edges (thick) have totally higher attention scores than the green edges (slim).

evitably brings redundant computation. However, in part, this also makes minimal assumptions about where the keypoints of the instances may appear. Various unknown situations can be handled. Next we present the self-attention based algorithms from the *body-first* and *part-first* views.

Body-first view. This view aims to decode each person skeleton one-by-one from the queue. Assuming we have the sorted all types of candidate keypoints by descending order of score in a single queue, we pop out the first keypoint (maybe any keypoint type) to seed a new skeleton $\mathcal{S}$, and then greedily find the best matched adjacent candidate keypoint from the queue.

For the seeded $\mathcal{S}$ with the initial keypoint, we find the other keypoints along the search path according to a defined human skeleton kinematic tree. When looking for a certain type of joint, the founded joints (denoted as the set $\mathcal{S}_f$) of this skeleton $\mathcal{S}$ induce a basin of attraction to "attract" the joint that most likely belongs to it. For a certain unmatched point $p_c = (x, y, s)$ in the candidate set $\mathbb{C}_k$ of the keypoint type k, we use the mean attention scores between the current found keypoints and p_c as the metric to measure the attraction from this skeleton[2]: $\text{Attraction}(p_c, \mathcal{S}_f) = \frac{1}{|\mathcal{S}_f|} \sum_{(x', y', s') \in \mathcal{S}_f} s' \cdot \mathbf{A}[y, x, y', x']$. Thus the candidate point with the highest $\text{score} \times \text{Attraction}$ is considered to belong to the current skeleton $\mathcal{S}$:

$$p_c^* = \text{argmax}_{p_c \in \mathbb{C}_k} s \cdot \text{Attraction}(p_c, \mathcal{S}_f). \tag{5}$$

We repeat the process above and record all the matched keypoints until all keypoints of this skeleton have been found. Note if the $\text{Attraction}(p_c^*, \mathcal{S}_f)$ is smaller than a threshold λ (empirically set to 0.0025), this type of keypoint in this skeleton to be empty (zero-filling). Then we need to decode the next skeleton. We pop the first unmatched keypoint to seed a new skeleton $\mathcal{S}'$ again. We follow the previous steps to find keypoints belonging to this instance. It is worth noting that we also consider the keypoints that have already been claimed by a previous skeleton $\mathcal{S}$, but only when $\text{Attraction}(p_c, \mathcal{S}_f') > \text{Attraction}(p_c, \mathcal{S})$, we assign the matched p_c to the current skeleton $\mathcal{S}'$.

Part-first view. This view aims to decode all human skeletons part-by-part. Given all candidates for each keypoint type, we initialize multiple skeleton seeds $\{\mathcal{S}^1, \mathcal{S}^2, ..., \mathcal{S}^m\}$ with the most easily detected keypoints such as nose. Then we follow a fixed order to connect the candidate parts to the current skeletons. These skeletons can be seen as multiple clusters consisting of found keypoints. Like the *body-first* view, we also use the mean attention attraction $\text{Attraction}(p_c, \mathcal{S}_f^t)$ from the found keypoints in the skeletons as the metric to assign the candidate parts. But in the *part-first* view, we compute the pairwise distance matrix between the candidate parts and existing skeletons, and then we use the Hungarian algorithm (Kuhn, 1955) to solve this bipartite graph matching problem. Note, if an $\text{Attraction}(p_c, \mathcal{S}^t)$ that represents a matching in the solution is lower than a threshold λ, we use this corresponding candidate part to start a new skeleton seed. We repeat the process above until all types of candidate parts have been assigned. This part-first grouping algorithm can

---

[2]To obtain the correct coordinate $(int(x/r), int(y/r))$, we use (x, y) to omit the downsampling factor and rounding operation for simplicity.

Table 1: Results on the COCO validation set. (res101, s16, i640) represents that we use ResNet-101; the output stride is 16; the input resolution is 640×640. Refinement#1 represents only refining the keypoints without filling. Refinement#2 represents refining the keypoints with filling.

Method	AP	$AP_{0.5}$	$AP_{0.75}$	AP_M	AP_L	AR
OpenPose (Cao et al., 2017)	58.4	81.5	62.6	54.4	65.1	-
OpenPose + Refinement (Cao et al., 2017)	61.0	84.9	67.5	56.3	69.3	-
PersonLab (res101, s16, i601) (Papandreou et al., 2018)	53.2	76.0	56.3	38.6	73.1	57.0
PersonLab (res101, s16, i801) (Papandreou et al., 2018)	60.0	82.1	64.3	49.7	74.6	64.1
PersonLab (res101, s16, i1401) (Papandreou et al., 2018)	65.6	85.9	71.4	61.1	72.8	70.1
Ours (res101, s16, i640)	50.4	78.5	53.1	41.6	62.8	56.9
Ours (res152, s16, i640)	50.7	77.7	53.6	41.1	64.2	56.9
Ours (res152, s16, i640) + Refinement#1	58.7	81.1	62.9	54.0	66.0	63.9
Ours (res152, s16, i640) + Refinement#2	65.3	85.8	71.3	59.1	74.4	70.5
Ours (res101, s16, i800)	51.6	79.7	55.1	44.6	61.2	57.9
Ours (res101, s16, i800) + Refinement#1	59.3	82.1	63.7	56.4	63.6	64.6
Ours (res101, s16, i800) + Refinement#2	66.4	86.1	72.6	61.1	74.0	71.2

achieve the optimal solution for assigning local parts to the skeletons although it cannot guarantee the global optimal assignment. We choose the part-first grouping as the default. And we compare both algorithms on the performance, complexity and runtime in Appendix A.4.

2.5 MASK PREDICTION

The instance masks are easy to obtain after the detected keypoints have been grouped into skeletons. To produce the instance segmentation results, we sample the visible keypoint locations $\left\{(\hat{x}_m^k, \hat{y}_m^k, \hat{v}_m^k)\right\}_{k=1}^K$ of the m-th instance from the supervised self-attention matrix: $\hat{\mathbf{A}}_m = \frac{\sum_k \delta(\hat{v}_m^k > 0) \cdot \mathbf{A}[\hat{y}_m^k, \hat{x}_m^k, :, :]}{\sum_k \delta(\hat{v}_m^k > 0)}$. Then we achieve the estimated instance mask: $\hat{\mathbf{M}}_m = \frac{\hat{\mathbf{A}}_m}{\max(\hat{\mathbf{A}}_m)} > \sigma$, where σ is a threshold (0.4 by default) to determine the mask region. When we obtain the initial skeletons and masks for all person instances, the joints of a person may fall in multiple incomplete skeletons, but their corresponding segments (sampled attention areas) may overlap. Thus we further perform non-maximum suppression to merge instances if the Intersection-over-Max (IoM) of two masks exceeds 0.3, where Max denotes the maximum area between two masks.

3 EXPERIMENTS

Dataset. We evaluate our method on the COCO keypoint dectection challenge (Lin et al., 2014) and on the instance segmentation of the COCO person category.

Model setup. We follow the model architecture design of TransPose (Yang et al., 2021) to predict the keypoint heatmaps. The setup is built on top of pre-existing ResNet and Transformer Encoder. We use the Imagenet pre-trained ResNet-101 or ResNet-151 as the backbone whose final classification layer is replaced by a 1×1 convolution to reduce the channels from 2048 to d (192). The normal output stride of ResNet backbone is 32 but we increase the feature map resolution of its final stage (C5 stage) by adding the dilation and removing the stride, i.e., the downsampling ratio r of ResNet is 16. We use a regular Transformer with 6 encoder layers with a single attention head for each layer. The hidden dimension of FFN is 384. See more training and inference details in Appendix A.1.

3.1 RESULTS ON COCO KEYPOINT DETECTION AND PERSON INSTANCE SEGMENTATION

The standard evaluation metric for COCO keypoint localization is the object keypoint similarity (OKS) and the mean average precision (AP) over 10 thresholds (0.5,0.55,...,0.95) is regarded as the performance metric. We train our models on COCO train2017 set, and evaluate the model on the val2017 and test-dev2017 sets, as shown in Table 1 and Table 2. We mainly compare with the typical bottom-up models that have similar pipelines to our method: OpenPose (Cao et al., 2017), PersonLab (Papandreou et al., 2018), and AE (Newell et al., 2017). Following the works (Cao et al.,

Figure 4: Visualization results predicted by our pure bottom-up model. For each image, we show the image plotted with human poses and masks. We also show the learned attention areas from the views of different sampled keypoints, each of which has been annotated by a white color pentagram.

2017; Newell et al., 2017), we also refine the grouped skeletons using a single pose estimator. We adopt the COCO pretrained TransPose-R-A4 (Yang et al., 2021) that has a very similar architecture to our model and has only 6M parameters. We apply the single pose estimator to each single scaled person region achieved by the box containing the person mask. Note that the refinement results are highly dependent on the effect of the grouping and mask prediction, and we only update the keypoint estimates where the predictions of the two models are almost the same. The concrete update rule is whether the keypoint similarity (KS) metric[3] computing between two keypoints exceeds 0.75, indicating that the distance between two predicted locations is already very small. We apply this update rule to all the refinement. This step brings about 8 AP improvements, which suggests that the small localization errors of the pure bottom-up model reduce the precision under high thresholds.

(a) OpenPose   (b) TransPose-R   (c) Ours (BU)   (d) Ours (BU+Refine)

Figure 5: Localization errors analysis on COCO validation set.

Analysis. We further analyze the differences between pure bottom-up results and the refined ones through the benchmarking and error diagnosis tool (Ronchi & Perona, 2017). We compare our methods with the typical OpenPose model and the Transformer-based model. The yielded localization error bars (Figure 5) reveal the weaknesses and strengths of our model: (1) *Jitter error*: The heatmap localization precision under the existence of multi-person is still not as accurate as the localization precision of single pose estimate; (2) *Missing error*: Since our algorithm does not ensure that the coordinate of every keypoint in a detected pose has been predicted, if the GT coordinate of a keypoint is annotated, zero-filling coordinates will seriously pull down the calculated OKS value. Thus, for the evaluation, it is necessary to produce complete predictions. When we further use the single pose estimator to fill the missing joints with zero scores in the initially grouped skeletons, it achieves about 7 AP gains (Table 1) and reduces the missing error (shown in Figure 5(d)); (3) *Inversion error*: Forcing diverse keypoint types in an individual instance to have higher query-key similarity may make it difficult for the model to distinguish different keypoint types, especially the left and right inversion; (4) *Swap error*: We notice that our pure bottom-up model has fewer swap

---

[3]We consider the per-keypoint standard deviation and object scale as the standard OKS metric does.

Table 2: Results on the COCO test-dev2017 set. The methods marked with * use the multi-scale inference settings. Our result is achieved based on ResNet-101 model with 16 output stride and 800^2 input resolution.

Method	AP	$AP_{0.5}$	$AP_{0.75}$	AP_M	AP_L	AR	$AR_{0.5}$	$AR_{0.75}$	AR_M	AR_L
Top-down										
G-RMI (Papandreou et al., 2017)	64.9	85.5	71.3	62.3	70.0	69.7	88.7	75.5	64.4	77.1
Mask-RCNN (He et al., 2017)	63.1	87.3	68.7	57.8	71.4	-	-	-	-	-
SimpleBaseline (Xiao et al., 2018)	73.7	91.9	81.1	70.3	80.8	79.0	-	-	-	-
HRNet (Sun et al., 2019)	75.5	92.5	83.3	71.9	81.5	80.5	-	-	-	-
Bottom-up										
OpenPose (Cao et al., 2017)	61.8	84.9	67.5	57.1	68.2	-	-	-	-	-
AE (Newell et al., 2017)	62.8	84.6	69.2	57.5	70.6	-	-	-	-	-
AE* (Newell et al., 2017)	65.5	86.8	72.3	60.6	72.6	70.2	89.5	76.0	64.6	78.1
PersonLab (Papandreou et al., 2018)	66.5	88.0	72.6	62.4	72.3	71.0	90.3	76.6	66.1	77.7
PersonLab* (Papandreou et al., 2018)	68.7	89.0	75.4	64.1	75.5	75.4	92.7	81.2	69.7	83.0
Ours (SSA)	65.0	86.2	72.2	60.1	71.8	70.1	88.9	76.2	64.2	78.2

Table 3: Instance segmentation results (person class only) obtained with 20 proposals per image on the COCO validation set.

Method	AP	$AP_{0.5}$	$AP_{0.75}$	AP_{small}	AP_{medium}	AP_{large}	AR_1	AR_{10}	AR_{20}	AR_{small}	AR_{medium}	AR_{large}
PersonLab (res101, stride=8, input=1401)	33.8	56.0	36.8	7.6	45.9	59.1	15.6	37.0	38.3	8.0	51.4	68.0
Ours (res152, stride=16, input=640)	20.7	43.5	16.9	0.3	24.5	59.0	12.9	29.4	30.3	1.0	36.1	68.5
Ours (res101, stride=16, input=800)	22.0	45.3	18.8	0.9	27.7	55.3	13.2	30.8	32.0	1.8	41.1	66.9

errors (1.2%, shown in Figure 5(c)), which represents less confusion between semantically similar parts of different instances. It indicates that compared with OpenPose model, our attention-based grouping strategy performs relatively better in assigning parts to their corresponding instances.

Person instance segmentation. We evaluate the instance segmentation results on COCO val split (person category only). We compare our method with PersonLab (Papandreou et al., 2018). In Table 3, we report the results with a maximum of 20 person proposals due to the convention of the COCO person keypoint evaluation protocol. The results on the mean average precision (AP) show that our model still has a gap in the segmentation performance compared with PersonLab. We argue that this is mainly because we conduct the mask learning on low-resolution attention maps that have been downsampled 16 times w.r.t. the 640^2 or 800^2 input resolution while the reported PersonLab result is based on 8 times downsampling w.r.t the 1401^2 input resolution. As shown in Table 3, our model performs worse on small and medium scales but achieves comparable or even superior performance on large scale persons even if PersonLab uses a larger resolution.

3.2 ABLATION ON THE NAIVE SELF-ATTENTION VERSUS SUPERVISED SELF-ATTENTION

To study the differences in model learning when trained with and without supervising self-attention, we compare their convergences in the heatmap loss and instance mask loss. As illustrated in Figure 6, compared with training the naive self-attention model, supervising self-attention achieves a better fitting effect in the mask learning, while achieving an acceptable sacrifice on the fitting of heatmap learning. It is worth noting that the instance mask training loss curve of the naive self-attention model drops slightly, which suggests that the spontaneously formed attention pattern has a tendency to instance-awareness. But the naive self-attention pattern under this condition cannot effectively distinguish instances such that the accuracy of the grouping cannot be guaranteed.

4 RELATED WORK

Transformer. Transformer (Vaswani et al., 2017) has shown very powerful visual relation modeling capability in various computer vision tasks, such as image classification (Dosovitskiy et al., 2020; Touvron et al., 2020), object detection (Carion et al., 2020; Zhu et al., 2020), semantic segmentation (Zheng et al., 2021), tracking (Sun et al., 2020; Meinhardt et al., 2021), human pose estimation (Lin et al., 2021; Li et al., 2021a; Yang et al., 2021; Li et al., 2021b; Stoffl et al., 2021)

Figure 6: The convergences on the heatmap loss and instance mask loss when trained with and without supervising self-attention.

and etc. The common practice of these methods is to use the task-specific supervision signals such as class labels, object box coordinates, keypoint positions or semantic masks to supervise the final output of transformer-based models. They may visualize the attention maps to understand the model but few works directly use it as an explicit function in the inference process. Our work gives a successful example of explicitly using and supervising attention for a specific purpose.

Human Pose Estimation & Instance segmentation. Multi-person pose estimation methods are usually classified into two categories: top-down (TD) or bottom-up (BU). TD models first detect persons, and then estimate single pose for each person, such as G-RMI (Papandreou et al., 2017), Mask-RCNN (He et al., 2017), CPN (Chen et al., 2018), SimpleBaseline (Xiao et al., 2018), and HRNet (Sun et al., 2019). BU models need to detect the existence of various types of keypoints at any position and scale. And matching keypoints into instances requires the model to learn dense association signals pre-defined by human knowledge. OpenPose (Cao et al., 2017) proposes part affinity field (PAF) to measure the association between keypoints by computing the integral along the connecting line. Associative Embedding (Newell et al., 2017) abstracts an embedding as the human 'tag' ID to measure the association. PersonLab (Papandreou et al., 2018) constructs mid-range offset as the geometric embedding to group keypoints into instances. In addition, single-stage methods (Zhou et al., 2019; Nie et al., 2019) also use offset field to assign keypoints to their centers. Compared with them, we use Transformer to capture the intra-dependencies within a person and inter-dependencies across different persons. And we explicitly exploit the intrinsic property of self-attention mechanism to solve the association problem, rather than using pre-defined offset fields or embeddings. The generic instance segmentation methods also can be categorized into top-down and bottom-up schemes. Top-down approaches predict the instance masks based on the object proposals, such as FCIS (Li et al., 2017) and Mask-RCNN (He et al., 2017). Bottom-up approaches mainly cluster the semantic segmentation results to obtain instance segmentation using an embedding space or a discriminative loss to measure the pixel association like (Newell et al., 2017; De Brabandere et al., 2017; Fathi et al., 2017). Compared with them, our method uses self-attention to measure the association and estimates instance masks based on instance keypoints.

5 DISCUSSION

This paper proposes to exploit Transformer to solve the keypoint detection and instance association. We supervise the inherent characteristics of self-attention – the feature similarity between any pair of positions – to achieve the clustering/grouping problem of the keypoints or pixels. Unlike a typical CNN-based bottom-up model, it no longer requires a pre-defined vector field or embedding as the associative reference, thus reducing the model redundancy and simplifying the pipeline. We demonstrate the effectiveness and simplicity of the proposed method on the challenging COCO keypoint detection and person instance segmentation tasks.

There remain limitations in the current approach. Due to the quadratic complexity of the standard Transformer, the model performance still struggles in scaling the model size and the input resolution. The selection of loss criteria, architecture, and training procedures can be further optimized. The current approach highly relies on the instance mask annotations. Future works can reduce such reliance by imposing a discriminative loss across instances based only on keypoint locations.

REFERENCES

Zhe Cao, Tomas Simon, Shih-En Wei, and Yaser Sheikh. Realtime multi-person 2d pose estimation using part affinity fields. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7291–7299, 2017.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *ECCV*, pp. 213–229, Cham, 2020.

Yilun Chen, Zhicheng Wang, Yuxiang Peng, Zhiqiang Zhang, Gang Yu, and Jian Sun. Cascaded pyramid network for multi-person pose estimation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7103–7112, 2018.

Bert De Brabandere, Davy Neven, and Luc Van Gool. Semantic instance segmentation with a discriminative loss function. *arXiv preprint arXiv:1708.02551*, 2017.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Alireza Fathi, Zbigniew Wojna, Vivek Rathod, Peng Wang, Hyun Oh Song, Sergio Guadarrama, and Kevin P Murphy. Semantic instance segmentation via deep metric learning. *arXiv preprint arXiv:1703.10277*, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, pp. 770–778, 2016.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pp. 2961–2969, 2017.

Eldar Insafutdinov, Leonid Pishchulin, Bjoern Andres, Mykhaylo Andriluka, and Bernt Schiele. Deepercut: A deeper, stronger, and faster multi-person pose estimation model. In *European Conference on Computer Vision*, pp. 34–50. Springer, 2016.

Sven Kreiss, Lorenzo Bertoni, and Alexandre Alahi. Pifpaf: Composite fields for human pose estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11977–11986, 2019.

Harold W Kuhn. The hungarian method for the assignment problem. *Naval research logistics quarterly*, 2(1-2):83–97, 1955.

Ke Li, Shijie Wang, Xiang Zhang, Yifan Xu, Weijian Xu, and Zhuowen Tu. Pose recognition with cascade transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1944–1953, 2021a.

Yanjie Li, Shoukui Zhang, Zhicheng Wang, Sen Yang, Wankou Yang, Shu-Tao Xia, and Erjin Zhou. Tokenpose: Learning keypoint tokens for human pose estimation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021b.

Yi Li, Haozhi Qi, Jifeng Dai, Xiangyang Ji, and Yichen Wei. Fully convolutional instance-aware semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2359–2367, 2017.

Kevin Lin, Lijuan Wang, and Zicheng Liu. End-to-end human pose and mesh reconstruction with transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1954–1963, 2021.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.

Tim Meinhardt, Alexander Kirillov, Laura Leal-Taixe, and Christoph Feichtenhofer. Trackformer: Multi-object tracking with transformers. *arXiv preprint arXiv:2101.02702*, 2021.

Alejandro Newell, Zhiao Huang, and Jia Deng. Associative embedding: End-to-end learning for joint detection and grouping. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Xuecheng Nie, Jiashi Feng, Jianfeng Zhang, and Shuicheng Yan. Single-stage multi-person pose machines. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6951–6960, 2019.

George Papandreou, Tyler Zhu, Nori Kanazawa, Alexander Toshev, Jonathan Tompson, Chris Bregler, and Kevin Murphy. Towards accurate multi-person pose estimation in the wild. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4903–4911, 2017.

George Papandreou, Tyler Zhu, Liang-Chieh Chen, Spyros Gidaris, Jonathan Tompson, and Kevin Murphy. Personlab: Person pose estimation and instance segmentation with a bottom-up, part-based, geometric embedding model. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 269–286, 2018.

Matteo Ruggero Ronchi and Pietro Perona. Benchmarking and error diagnosis in multi-instance pose estimation. In *IEEE International Conference on Computer Vision, ICCV 2017, Venice, Italy, October 22-29, 2017*, pp. 369–378, 2017.

Lucas Stoffl, Maxime Vidal, and Alexander Mathis. End-to-end trainable multi-instance pose estimation with transformers. *arXiv preprint arXiv:2103.12115*, 2021.

Ke Sun, Bin Xiao, Dong Liu, and Jingdong Wang. Deep high-resolution representation learning for human pose estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5693–5703, 2019.

Peize Sun, Yi Jiang, Rufeng Zhang, Enze Xie, Jinkun Cao, Xinting Hu, Tao Kong, Zehuan Yuan, Changhu Wang, and Ping Luo. Transtrack: Multiple-object tracking with transformer. *arXiv preprint arXiv:2012.15460*, 2020.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. *arXiv preprint arXiv:2012.12877*, 2020.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. pp. 5998–6008, 2017.

Yuqing Wang, Zhaoliang Xu, Xinlong Wang, Chunhua Shen, Baoshan Cheng, Hao Shen, and Huaxia Xia. End-to-end video instance segmentation with transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8741–8750, 2021.

Bin Xiao, Haiping Wu, and Yichen Wei. Simple baselines for human pose estimation and tracking. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 466–481, 2018.

Sen Yang, Zhibin Quan, Mu Nie, and Wankou Yang. Transpose: Keypoint localization via transformer. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021.

Sixiao Zheng, Jiachen Lu, Hengshuang Zhao, Xiatian Zhu, Zekun Luo, Yabiao Wang, Yanwei Fu, Jianfeng Feng, Tao Xiang, Philip HS Torr, et al. Rethinking semantic segmentation from a sequence-to-sequence perspective with transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6881–6890, 2021.

Xingyi Zhou, Dequan Wang, and Philipp Krähenbühl. Objects as points. *arXiv preprint arXiv:1904.07850*, 2019.

Xizhou Zhu, Weijie Su, Lewei Lu, Bin Li, Xiaogang Wang, and Jifeng Dai. Deformable detr: Deformable transformers for end-to-end object detection. *arXiv preprint arXiv:2010.04159*, 2020.

A APPENDIX

A.1 TRAINING DETAILS

In the training phase, we use data augmentation with random scale factor between 0.75 and 1.5, random flip with probability 0.5, random rotation with $\pm$30 degrees, and random translate with $\pm$40 pixels along the horizontal and vertical directions. The input size is 640^2 or 800^2 and thus the input sequence length of Transformer is 1600 or 2500. We use the Post-Norm Transformer architecture and ReLU activation function in FFN. We supervise the 4-th self-attention layer by default (the total layer depth is 6). By convention, we use 2 transposed convolution layers to upsample the Transformer output size to 160×160 or 200×200. The standard deviation for the Gaussian kernel in the generated heatmaps is set to 2. We use Adam optimizer to train the model. The model is distributed across 8 Tesla V100 GPUs with a total batchsize of 16 or 8. The initial learning rate is set to $\frac{\text{batchsize}}{8} \times 0.0001$, and decays 10 times at the 150-th and 200-th epochs respectively, with a total of 240 training epochs.

A.2 INFERENCE DETAILS

The threshold score t for obtaining candidate keypoint from heatmaps is set to 0.0025. The final person masks are achieved by bilinear interploating the estimated $\hat{\mathbf{M}}_m$ to the original image size. The skeleton kinematic tree used in the body-first grouping is defined as a graph structure: the vertices are all types of keypoints that are denoted as the numbers from 0 to 16 by the order defined by COCO dataset; the edges are defined as [(0, 1), (0, 2), (0, 3), (0, 4), (3, 5), (4, 6), (5, 7), (5, 11), (6, 8), (6, 12), (7, 9), (8, 10), (11, 13), (13, 15), (12, 14), (14, 16), (5, 6), (15, 16), (13, 14), (11, 12)].

A.3 ABLATION ON WHICH ATTENTION LAYERS SHOULD BE SUPERVISED

Supervising the self-attention matrix in different Transformer layer depths may have different effects on the heatmap and mask learning. To study such effects, we train a smaller proxy model to compare their differences in the fitting of heatmap and instance mask loss on a small subset (1/5) split of the COCO train set. The model configurations are: ResNet-50 based, 576^2 input resolution and 5 transformer layers with $d = 160$ and 320 hidden dimensions in FFN. Note that using a smaller model and small-scale training data inevitably reduces the overall performances of the model, but we only aim to find the relative differences in supervising at different Transformer layers. As illustrated in Figure 7, we do not observe significant differences in both heatmap loss and instance mask loss when leveraging the mask supervision in different Transformer layers. We further evaluate all these models on the COCO validation set. As shown in Table 4, supervising one of the last three attention layers achieves better performance compared with supervising the first two layers. Especially, supervising the penultimate or third-to-last layer shows a better performance. This suggests that leveraging the instance mask loss in this layer depth is a better trade-off between heatmap learning and mask learning.

Figure 7: The convergences on the heatmap loss and mask loss when supervising the self-attention in different layer depths.

Supervised layer	AP	$AP_{0.5}$	$AP_{0.75}$	AP_M	AP_L	AR	AP (with Refinement)
1-th	32.3	60.9	29.8	23.0	45.5	38.8	52.1
2-th	33.7	62.1	31.7	22.9	48.8	40.0	54.6
3-th	34.1	63.0	31.4	23.4	49.0	40.4	54.6
4-th	34.1	63.0	32.0	23.3	49.0	40.2	54.7
5-th	33.9	62.7	31.4	23.5	48.5	40.5	54.7

Table 4: Comparisons for different supervised layers on COCO validation set when using a small proxy model.

A.4 ABLATION ON THE GROUPING STRATEGY.

We take the ResNet-101 based model as the exemplar to test two types of grouping algorithm. We use the total 5000 images from COCO validation set. For each image, we run the model forward on a single GPU and the grouping algorithm on the CPU. In Table 5, we provide a controlled study to compare their differences in the model performance, theoretical complexity for per part assignment, runtime for the whole inference pipeline (keypoint detection, grouping and instance segmentation). Note that the complexity is a theoretical analysis based on the assumption that there are N existing skeletons and N candidates for a certain part type. We report the performances and runtime for the pure bottom-up result and the ones with refinement.

Grouping Algorithm	Theoretical complexity for per part assignment	AP (BU)	Runtime (BU)	AP (BU+Refine)	Runtime (BU+Refine)
Part-first view	$\mathcal{O}(N^3)$	50.4	8.45 img/sec	65.3	5.69 img/sec
Body-first view	$\mathcal{O}(N^2)$	49.7	8.94 img/sec	64.8	5.72 img/sec

Table 5: Comparison between the body-first and part-first grouping algorithm