Differentially Private Covariance Revisited

Abstract

In this paper, we present three new error bounds, in terms of the Frobenius norm, for covariance estimation under differential privacy: (1) a worst-case bound of $\tilde{O}(d^{1/4}/\sqrt{n})$, which improves the standard Gaussian mechanism $\tilde{O}(d/n)$ for the regime $d > \tilde{\Omega}(n^{2/3})$; (2) a trace-sensitive bound that improves the state of the art by a $\sqrt{d}$-factor, and (3) a tail-sensitive bound that gives a more instance-specific result. The corresponding algorithms are also simple and efficient. Experimental results show that they offer significant improvements over prior work.

1 Introduction

Consider a dataset represented by a matrix $\mathbf{X} \in \mathbb{R}^{d \times n}$, where each column $X_i, i = 1, \ldots, n$ corresponds to one individual's information. As standard in the literature, we assume that all the X_i's live in $\mathcal{B}_d$, the d-dimensional ℓ_2-unit ball centered at the origin. In this paper, we revisit the problem of estimating the (empirical) covariance matrix $\mathbf{\Sigma}(\mathbf{X}) := \frac{1}{n}\sum_i X_i X_i^T = \frac{1}{n}\mathbf{X}\mathbf{X}^T$ under differential privacy (DP), a fundamental problem that requires little motivation. As with most prior work, we use the Frobenius norm $\|\widetilde{\mathbf{\Sigma}} - \mathbf{\Sigma}\|_F$ to measure the error of the estimated covariance $\widetilde{\mathbf{\Sigma}}$. We present improved and new results for the following three settings with increasing generality. To better focus, in the main paper we only state results under *concentrated different privacy (zCDP)* [9]; extensions of our results to pure-DP are given in Appendix G. In cases where prior results do not adopt zCDP, we state their results under approximate-DP, a privacy guarantee that is weaker than zCDP. The formal definitions of these privacy guarantees, as well as their relationships, are given in Section 3.

1.1 Worst-case Bounds

Because the ℓ_2-sensitivity of $\mathbf{\Sigma}$, i.e., $\max_{\mathbf{X} \sim \mathbf{X}'} \|\mathbf{\Sigma}(\mathbf{X}) - \mathbf{\Sigma}(\mathbf{X}')\|_F$ where $\mathbf{X} \sim \mathbf{X}'$ denotes two neighboring datasets that differ by one column, is $O(1/n)$, the standard *Gaussian mechanism* [15] achieves an error of $\tilde{O}(d/n)$[1] by adding an independent Gaussian noise of scale $\tilde{O}(1/n)$ to each of the d^2 entries of $\mathbf{\Sigma}$. In this paper, we show how to achieve $\tilde{O}(d^{1/4}/\sqrt{n})$, which is better than the Gaussian mechanism when $d > \tilde{\Omega}(n^{2/3})$. Note that the hardness of covariance estimation lies between d-dimensional mean estimation (only estimating the diagonal entries of $\mathbf{\Sigma}$) and d^2-dimensional mean estimation (treating $\mathbf{\Sigma}$ as a d^2-dimensional vector). While the Gaussian mechanism simply equates it with the latter, our result indicates that the problem is strictly easier, due to the correlations of the d^2 entries of $\mathbf{\Sigma}$, at least in the high-dimensional regime $d > \tilde{\Omega}(n^{2/3})$. Under pure-DP, there is a lower bound of $\tilde{\Omega}(d/n)$ [17], which is also conjectured to hold under zCDP/approximate-DP [1]. Our result thus refutes this conjecture for $d > \tilde{\Omega}(n^{2/3})$, while demonstrating a separation of zCDP and pure-DP for covariance estimation. Lastly, another interesting consequence is that our error bound

---

[1] We use the $\tilde{O}$ notation to suppress the dependency on the privacy parameters and all polylogarithmic factors. We use e as the base of $\log$ (unless stated otherwise) and define $\log(x) = 1$ for any $x \leqslant e$.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

33 has utility for d up to $\tilde{O}(n^2)$ (utility is lost when the error is $\tilde{O}(1)$, as returning a zero matrix can
34 already achieve this error). This is the highest d that allows for any utility, since even mean estimation
35 requires $d < \tilde{O}(n^2)$ to have utility under zCDP [17, 9].

1.2 Trace-sensitive Bounds

37 For any symmetric matrix $\mathbf{A}$, we use $\mathbf{P}[\mathbf{A}]$ and $\mathbf{\Lambda}[\mathbf{A}]$ to denote its matrices of eigenvectors and
38 eigenvalues, respectively, such that $\mathbf{A} = \mathbf{P}[\mathbf{A}]\mathbf{\Lambda}[\mathbf{A}]\mathbf{P}[\mathbf{A}]^T$; we use $\lambda_i[\mathbf{A}]$ to denote its ith largest
39 eigenvalue. When $\mathbf{A} = \mathbf{\Sigma}$, we simply write $\mathbf{P} = \mathbf{P}[\mathbf{\Sigma}], \mathbf{\Lambda} = \mathbf{\Lambda}[\mathbf{\Sigma}], \lambda_i = \lambda_i[\mathbf{\Sigma}]$, so that $\mathbf{\Lambda} =$
40 $\mathrm{diag}(\lambda_1, \cdots, \lambda_d)$ and $\mathbf{\Sigma} = \mathbf{P}\mathbf{\Lambda}\mathbf{P}^T$. Let $\mathbf{P} = [P_1\ P_2\ \cdots\ P_d]$, where P_i is the orthonormal basis
41 vector corresponding to λ_i. Rudimentary linear algebra yields $\lambda_k = \frac{1}{n}\sum_i (P_k^T X_i)^2$ for $1 \leqslant k \leqslant d$
42 and $||X_i||_2^2 = \sum_k (P_k^T X_i)^2$ for $1 \leqslant i \leqslant n$. Thus, it follows that

$$\mathrm{tr}[\mathbf{\Lambda}] = \sum_k \lambda_k = \sum_k \frac{1}{n}\sum_i (P_k^T X_i)^2 = \frac{1}{n}\sum_i\sum_k (P_k^T X_i)^2 = \frac{1}{n}\sum_i ||X_i||_2^2.$$

43 That is, $0 \leqslant \mathrm{tr}[\mathbf{\Lambda}] \leqslant 1$ is the average ℓ_2 norm (squared) of the X_i's, and we simply write it as tr.

44 Recall that it is assumed that all the X_i's live in $\mathcal{B}_d$. In practice, this is enforced by assuming an
45 upper bound B on the norms and scaling down all X_i by B. As one often uses a conservatively
46 large B, typical values of tr can be much smaller than 1, so a trace-sensitive bound would be
47 more desirable. Indeed, Amin et al. [2] take this approach, describing an algorithm with error
48 $\tilde{O}(d^{3/4}\sqrt{\mathrm{tr}}/\sqrt{n} + \sqrt{d}/n)$ under approximate-DP [2]. Note that the $\sqrt{d}/n$ term inherits from mean
49 estimation and the first term is the "extra" difficulty for covariance estimation. In this paper, we
50 improve this term to $d^{1/4}\sqrt{\mathrm{tr}}/\sqrt{n}$ (we have a similar, albeit lesser, improvement under pure-DP;
51 see Appendix G). In fact, our worst-case bound above follows from this result by simply taking
52 $\mathrm{tr} = 1$, which then absorbs the $\sqrt{d}/n$ term for $d < \tilde{O}(n^2)$. Our algorithm is very simple: We first
53 estimate $\mathbf{\Lambda}$ using the Gaussian mechanism (this is the same as in [2, 19]), then we estimate $\mathbf{P}$ by
54 doing an eigendecomposition of $\mathbf{\Sigma}$ masked with Gaussian noise. Intuitively, we obtain a $\sqrt{d}$-factor
55 improvement over the iterative methods of [2, 19], because we can obtain all eigenvectors from
56 one noisy $\mathbf{\Sigma}$, while the iterative methods must allocate the privacy budget to all d eigenvectors.
57 Our algorithm is also more efficient, performing just two eigendecompositions and one matrix
58 multiplication, whereas the algorithm in [2, 19] needs $O(d)$ such operations.

1.3 Tail-sensitive Bounds

60 A trace-sensitive bound only makes use of the average ℓ_2 norm, which cannot capture the full
61 distribution. Next, we design an algorithm with an error bound that more closely depends on the
62 distribution of the norms. We characterize this distribution using the τ-*tail* ($\mathbb{I}(\cdot)$ is the indicator
63 function):

$$\gamma(\mathbf{X}, \tau) = \frac{1}{n}\sum_i ||X_i||_2^2 \cdot \mathbb{I}(||X_i||_2 > \tau), \tau \in [0, 1]. \tag{1}$$

64 Note that $\gamma(\mathbf{X}, \tau)$ decreases as τ increases. In particular, $\gamma(\mathbf{X}, 0) = \mathrm{tr}, \gamma(\mathbf{X}, 1) = 0$.

65 A common technique to reduce noise, at the expense of some bias, is to clip all the X_i's so that they
66 have norms at most τ, for some threshold τ. This yields an error of $\mathrm{Noise}(\mathbf{X}, \tau) + \gamma(\mathbf{X}, \tau)$, where
67 $\mathrm{Noise}(\mathbf{X}, \tau)$ denotes the error bound of the mechanism when all the X_i's have norm bounded by
68 τ, and $\gamma(\mathbf{X}, \tau)$ is the (additional) bias caused by clipping. Opting for the better of the Gaussian
69 mechanism or our trace-sensitive mechanism, we have

$$\mathrm{Noise}(\mathbf{X}, \tau) = \tilde{O}\left(\min\left(\frac{\tau^2 d}{n}, \frac{\tau d^{1/4}\sqrt{\mathrm{tr}}}{\sqrt{n}} + \frac{\tau^2\sqrt{d}}{n}\right)\right). \tag{2}$$

70 The technical challenge is therefore choosing a good τ in a differentially private manner. We design
71 a DP mechanism to choose the optimal τ up to a polylogarithmic multiplicative factor and an
72 exponentially small additive term. It also adaptively selects the better of Gaussian mechanism or the

---

[2] Their paper states the error bound under pure-DP and for estimating $\mathbf{X}\mathbf{X}^T$ (i.e., without normalization by
$1/n$); we show how this bound is derived from their result in Appendix C.

trace-sensitive mechanism depending on the relationship between d, n, and a privatized tr. More precisely, our adaptive mechanism achieves an error of

$$\tilde{O}\left(\min_{\tau}\left(\mathrm{Noise}(\mathbf{X}, \tau) + \gamma(\mathbf{X}, \tau)\right) + 2^{-dn}\right). \tag{3}$$

Note that this tail-sensitive bound is always no worse (modulo the 2^{-dn} term) than $\mathrm{Noise}(\mathbf{X}, 1)$ (i.e., without clipping), and can be much better for certain norm distributions. For example, suppose $d = n^{3/4}$, and a constant number of data vectors have ℓ_2 norm 1 while the others have norm $n^{-1/4}$, then $\sqrt{\mathrm{tr}} = \Theta(n^{-1/4})$, so $\mathrm{Noise}(\mathbf{X}, 1)$ takes the trace-sensitive bound, which is $\tilde{O}(n^{-9/16})$. On the other hand, (3) is at most $\tilde{O}(n^{-13/16})$ by taking $\tau = n^{-1/4}$. This example also shows that such a tail-sensitive bound could work very well on many real datasets with skewed distributions.

2 Related Work

Mean estimation and covariance estimation are perhaps the most fundamental problems in statistics and machine learning, and how to obtain the best estimates while respecting individual's privacy has attracted a lot of attention in recent years. Mean estimation under differential privacy is now relatively well understood, with the optimal worst-case error being $\tilde{\Theta}(\sqrt{d}/n)$ [17], achieved by the standard Gaussian mechanism [15]. In contrast, the complexity of covariance estimation remains elusive. The trivial upper bound is $\tilde{O}(d/n)$ while there is no lower bound higher than $\tilde{\Omega}(\sqrt{d}/n)$. We have improved the upper bound to $\tilde{O}(d^{1/4}/\sqrt{n})$ for the regime $d > \tilde{\Omega}(n^{2/3})$. It would be interesting to see if it is possible to also improve the $\tilde{O}(d/n)$ upper bound in lower dimensions.

When most data have norms much smaller than the upper bound given *a priori*, the worst-case bounds above are no longer optimal. In these cases, it is more desirable to have an error bound that is instance-specific. Clipping is a common technique for mean estimation [3, 16, 4, 27, 24] and it is known that running the Gaussian mechanism after clipping $\mathbf{X}$ with a certain quantile of the norms of the X_i's achieves instance-optimality in a certain sense [3, 16]. However, for covariance estimation, we show in Appendix D that no quantile can be the optimal clipping threshold achieving the bound in (3). Nevertheless, the bound in (3) is only achieving the optimal clipping threshold; we cannot say that is instance-optimal, since $\mathrm{Noise}(\cdot)$ is not even known to be worst-case optimal.

Closely related to covariance estimation are the PCA problem and low-rank approximation. Instead of finding all eigenvalues and eigenvectors, they only aim at finding the largest one or a few. For these problems, iterative methods [2, 19, 30, 15, 10] should perform better than the Gaussian mechanism or our algorithm, both of which try to recover the full covariance matrix.

Many covariance estimation algorithms have been proposed under the statistical setting, where the X_i's are i.i.d. samples drawn from a certain distribution, e.g., a multivariate Gaussian [17, 8, 7, 1, 18, 23]. Instead of the Frobenius error, many of them adopt the Mahalanobis error $\|\widetilde{\boldsymbol{\Sigma}} - \boldsymbol{\Sigma}\|_{\boldsymbol{\Sigma}} := \|\boldsymbol{\Sigma}^{-1/2}\widetilde{\boldsymbol{\Sigma}}\boldsymbol{\Sigma}^{-1/2} - \mathbf{I}\|_F$, which can be considered as a normalized version of the former. It is known that $\lambda_d\|\mathbf{A}-\boldsymbol{\Sigma}\|_{\boldsymbol{\Sigma}} \leqslant \|\mathbf{A}-\boldsymbol{\Sigma}\|_F \leqslant \lambda_1\|\mathbf{A}-\boldsymbol{\Sigma}\|_{\boldsymbol{\Sigma}}$, so when $\boldsymbol{\Sigma}_{\mathbb{D}}$ is well-conditioned, i.e., $\lambda_1/\lambda_d = O(1)$, any Frobenius error directly translates to a Mahalanobis error. However, for the Mahalanobis error, the more challenging question is how to deal with an ill-conditioned $\boldsymbol{\Sigma}$, for which [17, 7] have provided elegant solutions for the case where $\mathbb{D}$ is a multivariate Gaussian. It would be interesting to see if their methods can be combined with the tail-sensitive techniques in this paper to solve this problem for other distribution families, in particular, heavy-tailed distributions.

3 Preliminaries

3.1 Differential Privacy

We say that $\mathbf{X}, \mathbf{X}' \in \mathbb{R}^{d \times n}$ are neighbors if they differ by one column, denoted $\mathbf{X} \sim \mathbf{X}'$.

Definition 1 (Differential Privacy (DP) [14])**.** For $\varepsilon > 0$ and $\delta \geqslant 0$, a randomized mechanism $\mathcal{M} : \mathbb{R}^{d \times n} \to \mathcal{Y}$ satisfies (ε, δ)-DP if for any $\mathbf{X} \sim \mathbf{X}'$ and any $\mathcal{S} \subseteq \mathcal{Y}$, $\Pr[\mathcal{M}(\mathbf{X}) \in \mathcal{S}] \leqslant e^{\varepsilon} \cdot \Pr[\mathcal{M}(\mathbf{X}') \in \mathcal{S}] + \delta$.

In particular, we call it *pure-DP* if $\delta = 0$; otherwise *approximate-DP*.

Definition 2 (Concentrated Differential Privacy (zCDP) [9])**.** For $\rho > 0$, a randomized mechanism $M : \mathbb{R}^{d \times n} \to \mathcal{Y}$ satisfies ρ-zCDP if for any $\mathbf{X} \sim \mathbf{X}'$, $D_\alpha \left(\mathcal{M}(\mathbf{X}) || \mathcal{M}(\mathbf{X}') \right) \leqslant \rho \cdot \alpha$ for all $\alpha > 1$, where $D_\alpha \left(\mathcal{M}(\mathbf{X}) || \mathcal{M}(\mathbf{X}') \right)$ is the α-Rényi divergence between $\mathcal{M}(\mathbf{X})$ and $\mathcal{M}(\mathbf{X}')$.

The relationship between these DP definitions is as follows. Pure-DP, also written as ε-DP, implies $\frac{\varepsilon^2}{2}$-zCDP, which further implies $\left(\frac{\varepsilon^2}{2} + \varepsilon\sqrt{2 \log \frac{1}{\delta}}, \delta \right)$-DP for any $\delta > 0$.

To preserve ε-DP for a query Q, a standard mechanism is to add independent Laplace noises with scale proportional to the (global) ℓ_1-sensitivity of Q to each dimension.

Lemma 1 (Laplace Mechanism [12])**.** *Given* $Q : \mathbb{R}^{d \times n} \to \mathbb{R}^k$, *let* $\text{GS}_Q := \max_{\mathbf{X} \sim \mathbf{X}'} \|Q(\mathbf{X}) - Q(\mathbf{X}')\|_1$. *The mechanism* $\mathcal{M}(\mathbf{X}) = Q(\mathbf{X}) + \frac{\text{GS}_Q}{\varepsilon} \cdot \mathbf{Y}$ *where* $\mathbf{Y} \sim \text{Lap}(1)^k$, *preserves* ε-*DP.*

The following composition property of ε-DP allows us to design algorithms in a modular fashion.

Lemma 2 (Basic Composition)**.** *If* $\mathcal{M}$ *is an adaptive composition of mechanisms* $\mathcal{M}_1, \mathcal{M}_2, \ldots, \mathcal{M}_t$, *where each* $\mathcal{M}_i$ *satisfies* ε_i-*DP, then* $\mathcal{M}$ *satisfies* $(\sum_i \varepsilon_i)$-*DP.*

For ρ-zCDP, the standard method is the *Gaussian mechanism*:

Lemma 3 (Gaussian Mechanism [9])**.** *Given* $Q : \mathbb{R}^{d \times n} \to \mathbb{R}^k$, *let* $\text{GS}_Q := \max_{\mathbf{X} \sim \mathbf{X}'} \|Q(\mathbf{X}) - Q(\mathbf{X}')\|_2$. *The mechanism* $\mathcal{M}(\mathbf{X}) = Q(\mathbf{X}) + \frac{\text{GS}_Q}{\sqrt{2\rho}} \cdot \mathbf{Y}$ *where* $\mathbf{Y} \sim \mathcal{N}(0, \mathbf{I}_{k \times k})$, *preserves* ρ-*zCDP.*

It has been shown that the covariance matrix has an ℓ_2-sensitivity of $\frac{\sqrt{2}}{n}$ [7]. Thus, the Gaussian mechanism for covariance, denoted GaussCov, simply adds an independent Gaussian noise with scale $\frac{1}{\sqrt{\rho}n}$ to each entry of $\mathbf{\Sigma}$. Considering that $\mathbf{\Sigma}$ is symmetric, symmetric noises also suffice, which preserve the symmetry of the privatized $\mathbf{\Sigma}$. More precisely, we draw a random noise matrix $\mathbf{W}$ where $w_{j,k} \sim \mathcal{N}(0,1)$ i.i.d. for $1 \leqslant j \leqslant k \leqslant d$ and $w_{k,j} = w_{j,k}$, denoted as $\mathbf{W} \sim \text{SGW}(d)$. Then GaussCov outputs $\tilde{\mathbf{\Sigma}}_{\text{Gau}} = \mathbf{\Sigma} + \frac{1}{\sqrt{\rho}n} \cdot \mathbf{W}$.

A similar composition property exists for ρ-zCDP.

Lemma 4 (Composition Theorem [9])**.** *If* $\mathcal{M}$ *is an adaptive composition of algorithms* $\mathcal{M}_1, \mathcal{M}_2, \ldots, \mathcal{M}_t$, *where each* $\mathcal{M}_i$ *satisfies* ρ_i-*zCDP, then* $\mathcal{M}$ *satisfies* $(\sum_i \rho_i)$-*zCDP.*

3.2 The Sparse Vector Technique

The *Sparse Vector Technique* (SVT) [13] has as input a sequence of scalar queries, $f_1(\mathbf{X}), f_2(\mathbf{X}), \ldots, f_t(\mathbf{X})$, where each has sensitivity 1, and a threshold T. It aims to find the first query (if there is) whose answer is approximately above T. See Appendix A for the detailed algorithm. The SVT has been shown to satisfy ε-DP with following utility guarantee.

Lemma 5 (Extension of Theorem 3.24 in [14])**.** *With probability at least* $1 - \beta$, SVT *returns a* k *such that, for any* $i < k$, $f_i(\mathbf{X}) \leqslant T + \frac{6}{\varepsilon} \log(2t/\beta)$, *and if* $k \neq t + 1$, *then* $f_k(\mathbf{X}) \geqslant T - \frac{6}{\varepsilon} \log(2t/\beta)$.

3.3 Concentration Inequalities

Lemma 6 ([21])**.** *Given* $\mathbf{Y} \sim \mathcal{N}(0, \mathbf{I}_{d \times d})$, *with probability at least* $1 - \beta$,

$$\|\mathbf{Y}\|_2 \leqslant \eta(d, \beta) := \sqrt{d + 2\sqrt{d \log(1/\beta)} + 2 \log(1/\beta)}.$$

Lemma 7 ([7, 21])**.** *Given* $\mathbf{W} \sim \text{SGW}(d)$, *with probability at least* $1 - \beta$,

$$\|\mathbf{W}\|_2 \leqslant \upsilon(d, \beta) := 2\sqrt{d} + 2d^{1/6} \log^{1/3} d + \frac{6(1 + (\log d/d)^{1/3})\sqrt{\log d}}{\sqrt{\log(1 + (\log d/d)^{1/3})}} + 2\sqrt{2 \log(1/\beta)}.$$

Also, with probability at least $1 - \beta$,

$$\|\mathbf{W}\|_F \leqslant \omega(d, \beta) := \sqrt{d^2 + 2\sqrt{d \log(2/\beta)}(1 + \sqrt{2(d-1)}) + 6 \log(2/\beta)}.$$

Ignoring polylogarithmic factors, $\eta(d, \beta)$ and $\upsilon(d, \beta)$ are both in $\tilde{O}(\sqrt{d})$, while $\omega(d, \beta)$ is in $\tilde{O}(d)$. These concentration inequalities are very useful for error analysis. For example, the bound on $\|\mathbf{W}\|_F$ immediately implies that GaussCov has error $\frac{1}{\sqrt{\rho}n} \cdot \omega(d, \beta) = \tilde{O}(d/n)$.

4 Trace-sensitive Algorithm

The state-of-the-art trace-sensitive algorithm [2] first obtains an estimate of the eigenvalues, and then iteratively finds the eigenvectors by the exponential mechanism (EM), so we denote this algorithm as EMCov. Under approximate-DP, it has an error of $\tilde{O}(d^{3/4}\sqrt{\mathrm{tr}}/\sqrt{n} + \sqrt{d}/n)$. Below, we present an algorithm that is simpler, faster, and more accurate, improving the trace-dependent term by a $\sqrt{d}$-factor.

The first step of our algorithm SeparateCov (shown in Algorithm 1) is basically the same as EMCov, where we obtain an estimate of the eigenvalues with half of the privacy budget. [2] uses the Laplace mechanism for pure-DP; for zCDP, we use the Gaussian mechanism, which relies on the ℓ_2-sensitivity of $\mathbf{\Lambda}$, which we provide in Lemma 10 in the Appendix B. For the eigenvectors, we use GaussCov to obtain a privatized $\tilde{\mathbf{\Sigma}}_{\mathrm{Gau}}$ with the other half of the privacy budget, and perform an eigendecomposition. Finally, we assemble the eigenvalues of eigenvectors to obtain a privatized $\mathbf{\Sigma}$. It should be clear that, after computing $\mathbf{\Sigma}$, SeparateCov just needs two eigendecompositions and one full matrix multiplication, plus some $O(d^2)$-time operations. On the other hand, EMCov performs $O(d)$ eigendecompositions and matrix multiplications, plus a nontrivial sampling procedure for the EM.

Algorithm 1 SeparateCov

Input: data $\mathbf{X} \in \mathcal{B}_d^n$; privacy parameter $\rho > 0$.
 1: $\mathbf{\Lambda} \leftarrow$ the eigenvalues of $\mathbf{\Sigma} = \frac{1}{n}\mathbf{X}\mathbf{X}^T$
 2: $\tilde{\mathbf{\Lambda}}_{\mathrm{Sep}} \leftarrow \mathbf{\Lambda} + \frac{\sqrt{2}}{\sqrt{\rho}n} \cdot \mathbf{Y}$, where $\mathbf{Y} \sim \mathcal{N}(0, \mathbf{I}_{d \times d})$
 3: $\tilde{\mathbf{\Sigma}}_{\mathrm{Gau}} \leftarrow \mathrm{GaussCov}(\mathbf{X}, \frac{\rho}{2})$
 4: $\tilde{\mathbf{P}}_{\mathrm{Sep}} \leftarrow \mathbf{P}\left[\tilde{\mathbf{\Sigma}}_{\mathrm{Gau}}\right]$
 5: $\tilde{\mathbf{\Sigma}}_{\mathrm{Sep}} \leftarrow \tilde{\mathbf{P}}_{\mathrm{Sep}}\tilde{\mathbf{\Lambda}}_{\mathrm{Sep}}\tilde{\mathbf{P}}_{\mathrm{Sep}}^T$
 6: **return** $\tilde{\mathbf{\Sigma}}_{\mathrm{Sep}}$

That SeparateCov satisfies ρ-zCDP easily follows from the privacy of the Gaussian mechanism and the composition property. The utility is given by the following theorem:

Theorem 1. *Given any $\rho > 0$, for any $\mathbf{X} \in \mathcal{B}_d^n$, and any $\beta > 0$, with probability at least $1 - \beta$,* SeparateCov *returns a $\tilde{\mathbf{\Sigma}}_{\mathrm{Sep}}$ such that* $\|\tilde{\mathbf{\Sigma}}_{\mathrm{Sep}} - \mathbf{\Sigma}\|_F \leqslant \frac{2^{1.25}\sqrt{\mathrm{tr}}}{\rho^{1/4}\sqrt{n}} \cdot \sqrt{\upsilon\left(d, \frac{\beta}{2}\right)} + \frac{\sqrt{2}}{\sqrt{\rho}n} \cdot \eta\left(d, \frac{\beta}{2}\right) = \tilde{O}\left(\frac{d^{1/4}\sqrt{\mathrm{tr}}}{\sqrt{n}} + \frac{\sqrt{d}}{n}\right).$

Remark While SeparateCov strictly improves over EMCov, it does not dominate GaussCov: When $\mathrm{tr} < \tilde{O}(d^{3/2}/n)$, SeparateCov is better; otherwise, GaussCov is better. EMCov is better than GaussCov for a smaller trace range: $\mathrm{tr} < \tilde{O}(\sqrt{d}/n)$.

5 Tail-sensitive Algorithm

5.1 Clipped Covariance

Clipping is a common technique to reduce the sensitivity of functions at the expense of some bias. Given $\tau \geqslant 0$ and a vector $X \in \mathbb{R}^d$, let $\mathrm{Clip}(X, \tau) = \min\left(1, \frac{\tau}{\|X\|_2}\right) \cdot X$. Similarly, for any $\mathbf{X} \in \mathbb{R}^{d \times n}$, $\mathrm{Clip}(\mathbf{X}, \tau)$ denotes the matrix whose columns have been clipped to have norm at most τ. Clipping can be applied to both GaussCov and SeparateCov with a given τ: just run the mechanism on $\frac{1}{\tau} \cdot \mathrm{Clip}(\mathbf{X}, \tau)$ and scale the result back by τ^2. We denote the clipped versions of the two mechanisms as ClipGaussCov and ClipSeparateCov, respectively.

The following lemma bounds the bias caused by clipping in terms of the τ-tail as defined in (1).

Lemma 8. $\|\mathbf{\Sigma}(\mathbf{X}) - \mathbf{\Sigma}(\mathrm{Clip}(\mathbf{X}, \tau))\|_F \leqslant \frac{1}{n} \sum_i \left(\|X_i\|_2^2 - \tau^2\right) \cdot \mathbb{I}\left(\|X_i\|_2 \geqslant \tau\right) \leqslant \gamma(\mathbf{X}, \tau).$

191 Thus, running the better of ClipGaussCov and ClipSeparateCov yields a total error of
192 $\mathrm{Noise}(\mathbf{X}, \tau, \rho, \beta) + \gamma(\mathbf{X}, \tau)$, where

$$\mathrm{Noise}(\mathbf{X}, \tau, \rho, \beta) = \min\left(\frac{\tau^2}{\sqrt{\rho}n} \cdot \omega(d, \beta), \frac{2^{1.25}\tau\sqrt{\mathrm{tr}}}{\rho^{1/4}\sqrt{n}} \cdot \sqrt{\upsilon\left(d, \frac{\beta}{2}\right)} + \frac{\sqrt{2}\tau^2}{\sqrt{\rho}n} \cdot \eta\left(d, \frac{\beta}{2}\right)\right), \quad (4)$$

193 which is the exact version of (2). Note that the trace-sensitive term is only scaled by τ, which follows
194 from the proof of Theorem 1 when all X_i live in $\tau \cdot \mathcal{B}_d$.

195 Ideally, we would like to find the optimal noise-bias trade-off, i.e., achieving an error of
196 $\min_\tau(\mathrm{Noise}(\mathbf{X}, \tau) + \gamma(\mathbf{X}, \tau))$. Two issues need to be addressed towards this goal: The first, minor,
197 issue is that tr is sensitive, so we cannot use it directly to decide whether to use ClipGaussCov
198 or ClipSeparateCov. This can be addressed by using a privatized upper bound of tr. The more
199 challenging problem is how to find the optimal τ in a DP fashion. This problem has been well studied
200 for the clipped mean estimator [16, 3], where it can be shown that setting τ to be the $\tilde{O}(\sqrt{d})$-th
201 largest $\|X_i\|_2$ results in the optimal noise-bias trade-off [16]. Then the problem boils down to finding
202 a privatized quantile, for which multiple solutions exist [16, 11, 25, 5, 29]. For the clipped mean
203 estimator, using such a quantile of the norms results in the optimal trade-off because $\mathrm{Noise}(\mathbf{X}, \tau)$
204 takes the simple form $\tilde{O}(\tau\sqrt{d}/n)$. In fact, if we only had ClipGaussCov, setting τ to be the $\tilde{O}(d)$-th
205 largest $\|X_i\|_2$ would also yield an optimal trade-off, as ClipGaussCov is really just clipped mean in
206 d^2 dimensions. However, due to the trace-sensitive noise term, it is no longer the case. In Appendix D,
207 we give examples showing that no quantile, whose rank may arbitrarily depend on d, n, tr, can achieve
208 an optimal trade-off even ignoring polylogarithmic factors. It thus calls for a new threshold-finding
209 mechanism, which we describe next.

5.2 Adaptive Covariance: Finding the Optimal Clipping Threshold

211 Our basic idea is to try successively smaller values $\tau = 1, \frac{1}{2}, \frac{1}{4}, \dots$. As we reduce τ, the noise
212 decreases while the bias increases. We should stop when they are approximately balanced, which
213 would yield a near-optimal τ.

214 To do so in a DP manner, we need to quantify the noise and bias. Consider the bias first. Given a τ,
215 we divide the interval $(\tau, 1]$ into sub-intervals $(\tau, 2\tau], (2\tau, 4\tau], \dots, (\frac{1}{2}, 1]$. For any $X \in \mathbf{X}$ such that
216 $\|X\|_2 \in (2^s, 2^{s+1}]$, let $\check{X} = \mathrm{Clip}(X, \tau)$ and then by Lemma 8,

$$\|XX^T - \check{X}\check{X}^T\|_F \leqslant 2^{2s+2} - \tau^2. \quad (5)$$

217 That is, clipping X can at most lead to $\frac{1}{n} \cdot (2^{2s+2} - \tau^2)$ bias. Besides, since $\|X\|_2 \in (2^s, 2^{s+1}]$, we
218 have

$$2^{2s+2} - \tau^2 \leqslant 2^{2s+2} \leqslant 2 \cdot \|X\|_2^2. \quad (6)$$

219 Then, given $\mathbf{X}$, for any $s \in \mathbb{Z}$, we define $\mathrm{Count}_s(\mathbf{X}) := \left|\left\{X_i : \|X_i\|_2 \in (2^s, 2^{s+1}]\right\}\right|$. It is easy to
220 see for any $\mathbf{X} \sim \mathbf{X}'$, Count_s differs by at most 1, so does the sum of any subset of Count_s's. We
221 can define an upper bound on the bias: $\widehat{\mathrm{Bias}}(\mathbf{X}, \tau) := \frac{1}{n} \cdot \sum_{s=\log_2(\tau)}^{s<0} \mathrm{Count}_s \cdot (2^{2s+2} - \tau^2)$. Let
222 $\check{\mathbf{X}} = \mathrm{Clip}(\mathbf{X}, \tau)$. By (5) and (6), we have

$$\frac{1}{n}\|\mathbf{X}\mathbf{X}^T - \check{\mathbf{X}}\check{\mathbf{X}}^T\| \leqslant \widehat{\mathrm{Bias}}(\mathbf{X}, \tau) \leqslant 2 \cdot \gamma(\mathbf{X}, \tau). \quad (7)$$

223 By the property of Count_s's, given any τ, the sensitivity of $\widehat{\mathrm{Bias}}(\cdot, \tau)$ is bounded by $\frac{1}{n}$.

224 Now we turn to the noise. Recall that $\mathrm{Noise}(\mathbf{X}, \tau, \rho, \beta)$ is the smaller of two parts. The first part
225 $\mathrm{GaussNoise}(\tau, \rho, \beta) := \tau^2 \cdot \frac{1}{\sqrt{\rho}n} \cdot \omega(d, \beta)$ is independent of $\mathbf{X}$, so can be used directly. The second
226 part depends on tr, is thus sensitive. Since its sensitivity is $\frac{1}{n}$, we can easily privatize it by adding a
227 Gaussian noise of scale $\Theta\left(\frac{1}{\sqrt{\rho}n}\right)$. For technical reasons, we need to use an upper bound, so we add
228 $\Theta\left(\frac{\log(1/\beta)}{\sqrt{\rho}n}\right)$ to it so as to obtain a privatized $\widehat{\mathrm{tr}} \geqslant \mathrm{tr}$. Then we set

$$\mathrm{SeparateNoise}(\widehat{\mathrm{tr}}, \tau, \rho, \beta) := \tau \cdot \frac{2^{1.25}\sqrt{\widehat{\mathrm{tr}}}}{\rho^{1/4}\sqrt{n}} \cdot \sqrt{\upsilon\left(d, \frac{\beta}{2}\right)} + \tau^2 \cdot \frac{\sqrt{2}}{\sqrt{\rho}n} \cdot \eta\left(d, \frac{\beta}{2}\right),$$

Algorithm 2 AdaptiveCov

Input: data $\mathbf{X} \in \mathcal{B}_d^n$; privacy parameter $\rho > 0$; high probablity parameter β.

1: $\tilde{r} \leftarrow \text{PrivRadius}(\mathbf{X}, \frac{\sqrt{\rho}}{2}, \frac{\beta}{8}, 2^{-2dn})$

2: $\widetilde{\mathbf{X}} \leftarrow \text{Clip}(\mathbf{X}, \tilde{r})$

3: $\widetilde{\text{tr}} \leftarrow \frac{1}{n} \sum_i \|\widetilde{X}_i\|_2^2$

4: $\widehat{\text{tr}} \leftarrow \min\left(\widetilde{\text{tr}} + \frac{2\tilde{r}^2}{\sqrt{\rho}n} \cdot \mathcal{N}(0,1) + \frac{2\sqrt{2}\tilde{r}^2}{\sqrt{\rho}n} \cdot \sqrt{\log(8/\beta)}, \tilde{r}^2\right)$

5: $\tilde{t} \leftarrow \log_2(\tilde{r}) + 1 - \text{SVT}\left(\left\{\text{Diff}\left(\widetilde{\mathbf{X}}, \widehat{\text{tr}}, \tilde{r}, \frac{\rho}{2}, \frac{\beta}{2}\right), \text{Diff}\left((\widetilde{\mathbf{X}}, \widehat{\text{tr}}, \frac{\tilde{r}}{2}, \frac{\rho}{2}, \frac{\beta}{2}\right), \ldots, \text{Diff}\left((\widetilde{\mathbf{X}}, \widehat{\text{tr}}, 2^{-dn}, \frac{\rho}{2}, \frac{\beta}{2}\right)\right\}, 0, \frac{\sqrt{\rho}}{\sqrt{2}}\right)$

6: $\tilde{\tau} \leftarrow \min\left(2^{\tilde{t}+1}, \tilde{r}\right)$

7: **if** $\text{SeparateNoise}(\widehat{\text{tr}}, \tilde{\tau}, \frac{\rho}{2}, \frac{\beta}{2}) \geqslant \text{GaussNoise}(\tilde{\tau}, \frac{\rho}{2}, \frac{\beta}{2})$

8: $\quad$ $\widetilde{\mathbf{\Sigma}}_{\text{Ada}} \leftarrow \text{ClipGaussCov}(\widetilde{\mathbf{X}}, \frac{\rho}{2}, \tilde{\tau})$

9: **else**

10: $\quad$ $\widetilde{\mathbf{\Sigma}}_{\text{Ada}} \leftarrow \text{ClipSeparateCov}(\widetilde{\mathbf{X}}, \frac{\rho}{2}, \tilde{\tau})$

11: **return** $\widetilde{\mathbf{\Sigma}}_{\text{Ada}}$

---

and use $\widehat{\text{Noise}}(\widehat{\text{tr}}, \tau, \rho, \beta) := \min\left(\text{GaussNoise}(\tau, \rho, \beta), \text{SeparateNoise}(\widehat{\text{tr}}, \tau, \rho, \beta)\right)$ as a DP upper bound of $\text{Noise}(\mathbf{X}, \tau, \rho, \beta)$. Note that given $\widehat{\text{tr}}$, $\widehat{\text{Noise}}(\widehat{\text{tr}}, \tau, \rho, \beta)$ is independent of $\mathbf{X}$.

Finally, we run SVT on the following sequence of sensitivity-1 queries with $T = 0$:

$$\text{Diff}(\mathbf{X}, \widehat{\text{tr}}, \tau, \rho, \beta) := n \cdot \left(\widehat{\text{Bias}}(\mathbf{X}, \tau) - \widehat{\text{Noise}}(\widehat{\text{tr}}, \tau, \rho, \beta)\right), \tau = 1, \frac{1}{2}, \ldots, 2^{-dn}.$$

The SVT would return a τ that balances the bias and noise. After finding such a τ, we choose to run either GaussCov or SeparateCov by comparing $\text{GaussNoise}(\tau, \rho, \beta)$ and $\text{SeparateNoise}(\widehat{\text{tr}}, \tau, \rho, \beta)$. As the sequence consists of dn queries, SVT has an error of $O(\log(dn))$, which, as we will show, affects the optimality by a logarithmic factor. Meanwhile, the smallest τ we search over will induce an additive 2^{-dn} error.

The algorithm above can almost give us the desired error bound in (3), except that one thing may go wrong: The SVT introduces an error that is a logarithmic factor larger than the optimum, but at least $\widetilde{\Omega}(1/n)$. This would be fine as long as there is one X_i with $\|X_i\|_2 \geqslant \widetilde{\Omega}(1)$, so that the optimum error is $\widetilde{\Omega}(1/n)$. However, when all the X_i's have very small norms, say $1/n^2$, the $\widetilde{\Omega}(1/n)$ error from SVT would not preserve optimality. To address this issue, we first find the radius $\text{rad}(\mathbf{X}) = \max_i \|X_i\|_2$, and use it to clip $\mathbf{X}$. The following lemma shows that, under DP, it is possible to find a 2-approximation of $\text{rad}(\mathbf{X})$ plus an additive b so that only $O(\log\log(1/b))$ vectors are clipped. This allows us to set $b = 2^{-dn}$ while only incurring an $O(\log dn)$ error. Nicely, they match the additive and multiplicative errors that already exist from the SVT, so there is no asymptotic degradation in the optimality.

Lemma 9 ([11]). *For any $\varepsilon > 0$, $\beta > 0$ and $b > 0$, given $\mathbf{X} \in \mathcal{B}_d^n$, with probability at least $1 - \beta$, $\texttt{PrivRadius}$ returns a $\tilde{r} = \texttt{PrivRadius}(\mathbf{X}, \varepsilon, \beta, b)$ such that $\tilde{r} \leqslant 2 \cdot \text{rad}(\mathbf{X}) + b$ and $|\{\|X_i\|_2 > \tilde{r}\}| = O\left(\frac{1}{\varepsilon} \log \frac{\log(\text{rad}(\mathbf{X})/b)}{\beta}\right).$*

The complete algorithm is given in Algorithm 2. Its privacy follows from the privacy of $\texttt{PrivRadius}$, SVT, GaussCov, SeparateCov, and the composition theorem of zCDP; its utility is analyzed in the following theorem:

Theorem 2. *Given any $\rho > 0$ and $\beta > 0$, for any $\mathbf{X} \in \mathcal{B}_d^n$, with probability at least $1 - \beta$, AdaptiveCov returns a $\widetilde{\mathbf{\Sigma}}_{\text{Ada}}$ such that*

$$\left\|\widetilde{\mathbf{\Sigma}}_{\text{Ada}} - \mathbf{\Sigma}\right\|_F = O\left(\min_\tau\left(\text{Noise}\left(\mathbf{X}, \tau, \frac{\rho}{2}, \frac{\beta}{2}\right) \cdot \frac{\log(1/\beta)^{1/4}}{\rho^{1/4}} \cdot \log(n) + \gamma(\mathbf{X}, \tau) \cdot \frac{\log(dn/\beta)}{\sqrt{\rho}}\right) + 2^{-dn}\right)$$

$$= \tilde{O}\left(\min_\tau\left(\text{Noise}\left(\mathbf{X}, \tau\right) + \gamma(\mathbf{X}, \tau)\right) + 2^{-dn}\right).$$

6 Experiments

We conducted experiments to evaluate our algorithms on both synthetic and real-world datasets. We compare SeparateCov and AdaptiveCov against GaussCov [15], EMCov [2]. We implemented EMCov in Python following the pseudo-code provided in [2] and the descriptions of the sampling algorithm in [20]. We also tested CoinPress [7], but since it is designed to minimize the Mahalanobis error, it does not perform well when measured in Frobenius error; as such we omit it from the reported results. As a baseline, we include returning a zero matrix, which has error $O(\mathrm{tr})$, hence a trivial trace-sensitive algorithm. In all of the experiments below, the (ε, δ)-DP version of EMCov will be used, where we fix $\delta = 1e^{-10}$ and compose its steps for eigenvector estimation using advanced composition. ε is set according to the relationship described in Section 3.1 between ρ-zCDP and (ε, δ)-DP. When $\mathrm{rad}(\mathbf{X})$ is much smaller than 1, it is unfair for GaussCov and EMCov, so we scale all datasets such that $0.5 \leqslant \mathrm{rad}(\mathbf{X}) \leqslant 1$. As a result, we do not need the step to obtain a private radius in AdaptiveCov, either. Each experiment is repeated 50 times, and we report the average error. [3] Furthermore, we have also conducted experiments under pure-DP; the results can be found in Appendix H.

Figure 1: Results on synthetic datasets fixing $\mathrm{tr} = 1$.

Figure 2: Results on synthetic datasets as d, n, N or ρ varies.

6.1 Synthetic Datasets

We generate synthetic datasets by first following the method in [2], to obtain a matrix $\mathbf{X} = \mathbf{ZU}$, where $\mathbf{U} \in \mathbb{R}^{d \times d}$ is sampled from $U(0, 1)$, and $\mathbf{Z} \in \mathbb{R}^{n \times d}$ is sampled from $\mathcal{N}(0, \mathbf{I})$. Then the vectors in $\mathbf{X}$ are adjusted to be centred at 0 and their norms scaled. In [2], the vectors are scaled to have unit ℓ_2 norm; in our experiments, to better control tr and data skewness, we scale the norms so that they follow the Zipf's law. More precisely, we divide the norms into N bins. The number of vectors in the k-th bin is proportional to $1/k^s$ and their norm is 2^{k-N}. The parameter s characterizes the skewness, which we fix as $s = 3$. Note that $N = 1$ corresponds to the unit-norm case with $\mathrm{tr} = 1$.

The results on $\mathrm{tr} = 1$ case are shown in Figure 1, which correspond to the worst-case bounds. The ρ here is fixed at 0.1 and we examine the error growth w.r.t. d for $n = 1000, 4000, 16000$. The results generally agree with the theory: For low d, GaussCov is (slightly) better than SeparateCov, while the latter is much better for high d. AdaptiveCov is able to choose the better of the two adaptively, with a small cost due to allocating some privacy budget to estimate tr. Actually, if AdaptiveCov is given the precondition that all norms are 1, this extra cost can be saved.

Next, we vary one of the parameters while fixing the others at their default values $d = 200, n = 50000, N = 4$ and $\rho = 0.1$, and the results are reported in Figure 2. The most interesting case is Figure 2(a), where we increase N, hence reducing tr, which demonstrates the trace-sensitive bounds. Clearly, GaussCov is not trace-sensitive, while the other 4 methods are. In fact, returning the zero matrix is

---

[3]All code can be found at `https://github.com/OpenCode2022/PrivateCovariance`.

the best trace-sensitive algorithm if tr is sufficiently small. However, this may not be very meaningful in practice, as $N = 2^5$ means that most data have norm 2^{-31} but a few have norm 1. These few may be outliers and should be removed anyway. Figure 2(b)–(d) shows that higher d, smaller n, and smaller ρ all have similar effects, i.e., $\mathrm{SeparateCov}$ becomes better while $\mathrm{GaussCov}$ becomes worse, while $\mathrm{AdaptiveCov}$ is able to pick the better one.

Figure 3: Results on MNIST dataset.

Figure 4: Results on the news dataset.

6.2 Real-world Datasets

We also evaluate the algorithms on two real-world datasets. The first dataset is the MNIST [22] dataset, which contains images of handwritten digits. We use its training dataset which contains $60,000$ images represented as vectors in $\mathbb{Z}_{255}^d$, where $d = 784 = 28 \times 28$. These vectors are normalized by $255\sqrt{d}$ in the experiments. We estimate $\widetilde{\boldsymbol{\Sigma}}$ using samples containing all the digits, we also estimate $\widetilde{\boldsymbol{\Sigma}}$ corresponding to individual digits (reported in the Appendix H). In the first case, $\widetilde{\boldsymbol{\Sigma}}$ can be used for further dimensionality reduction analysis; in the second case, individual $\widetilde{\boldsymbol{\Sigma}}$ can be used for modelling the distributions of individual digits, which together can be used in a collective model for classification (e.g. using a mixture model). The second dataset contains news commentary data [26] consisting of approximately $15,000$ articles, each containing $500 - 4300$ words, which we convert into vectors of various dimensions using the hashing trick implemented in the scikit-learn package. In this case, the estimated $\widetilde{\boldsymbol{\Sigma}}$ can be used to help with further feature selection for NLP models, for example. These vectors are normalized to have unit ℓ_2 norm or normalized by the max ℓ_2 norm.

The experimental results on these two real dataset are shown in Figure 3 and 4, where we vary n, d, and ρ, respectively. On these results, we see that $\mathrm{GaussCov}$ never outperforms $\mathrm{SeparateCov}$, except for a very small advantage in a few cases where we have $\mathrm{tr} = 1$, a low d, and a high ρ. Another interesting observation is that $\mathrm{AdaptiveCov}$ outperforms both $\mathrm{GaussCov}$ and $\mathrm{SeparateCov}$ in many cases, something that is not apparent on the synthetic datasets. We believe that this is because these real datasets have heavier tails than the Zipf distribution (we used $s = 3$ for Zipf), which makes the adaptive clipping threshold selection more effective. This really demonstrates the benefits of a tail-sensitive bound.

References

[1] Ishaq Aden-Ali, Hassan Ashtiani, and Gautam Kamath. On the sample complexity of privately learning unbounded high-dimensional gaussians. In *Algorithmic Learning Theory*, pages 185–216. PMLR, 2021.

[2] Kareem Amin, Travis Dick, Alex Kulesza, Andrés Munoz Medina, and Sergei Vassilvitskii. Differentially private covariance estimation. In *NeurIPS*, pages 14190–14199, 2019.

[3] Kareem Amin, Alex Kulesza, Andres Munoz, and Sergei Vassilvtiskii. Bounding user contributions: A bias-variance trade-off in differential privacy. In *International Conference on Machine Learning*, pages 263–271. PMLR, 2019.

[4] Galen Andrew, Om Thakkar, Brendan McMahan, and Swaroop Ramaswamy. Differentially private learning with adaptive clipping. *Advances in Neural Information Processing Systems*, 34, 2021.

[5] Hilal Asi and John C Duchi. Instance-optimality in differential privacy via approximate inverse sensitivity mechanisms. *Advances in neural information processing systems*, 33, 2020.

[6] Afonso S Bandeira and Ramon Van Handel. Sharp nonasymptotic bounds on the norm of random matrices with independent entries. *The Annals of Probability*, 44(4):2479–2506, 2016.

[7] Sourav Biswas, Yihe Dong, Gautam Kamath, and Jonathan Ullman. Coinpress: Practical private mean and covariance estimation. *Advances in Neural Information Processing Systems*, 33, 2020.

[8] Mark Bun, Gautam Kamath, Thomas Steinke, and Steven Z Wu. Private hypothesis selection. *Advances in Neural Information Processing Systems*, 32, 2019.

[9] Mark Bun and Thomas Steinke. Concentrated differential privacy: Simplifications, extensions, and lower bounds. In *Theory of Cryptography Conference*, pages 635–658. Springer, 2016.

[10] Kamalika Chaudhuri, Anand D Sarwate, and Kaushik Sinha. A near-optimal algorithm for differentially-private principal components. *Journal of Machine Learning Research*, 14, 2013.

[11] Wei Dong and Ke Yi. Universal private estimators. *arXiv:2105.05443*, 2021.

[12] Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of cryptography conference*, pages 265–284. Springer, 2006.

[13] Cynthia Dwork, Moni Naor, Omer Reingold, Guy N Rothblum, and Salil Vadhan. On the complexity of differentially private data release: efficient algorithms and hardness results. In *Proceedings of the forty-first annual ACM symposium on Theory of computing*, pages 381–390, 2009.

[14] Cynthia Dwork and Aaron Roth. The algorithmic foundations of differential privacy. *Foundations and Trends® in Theoretical Computer Science*, 9(3–4):211–407, 2014.

[15] Cynthia Dwork, Kunal Talwar, Abhradeep Thakurta, and Li Zhang. Analyze gauss: optimal bounds for privacy-preserving principal component analysis. In *Proceedings of the forty-sixth annual ACM symposium on Theory of computing*, pages 11–20, 2014.

[16] Ziyue Huang, Yuting Liang, and Ke Yi. Instance-optimal mean estimation under differential privacy. *Advances in Neural Information Processing Systems*, 2021.

[17] Gautam Kamath, Jerry Li, Vikrant Singhal, and Jonathan Ullman. Privately learning high-dimensional distributions. In *Proceedings of the 32nd Annual Conference on Learning Theory*, COLT '19, pages 1853–1902, 2019.

[18] Gautam Kamath, Argyris Mouzakis, Vikrant Singhal, Thomas Steinke, and Jonathan Ullman. A private and computationally-efficient estimator for unbounded gaussians. *arXiv preprint arXiv:2111.04609*, 2021.

[19] Michael Kapralov and Kunal Talwar. On differentially private low rank approximation. In *Proceedings of the twenty-fourth annual ACM-SIAM symposium on Discrete algorithms*, pages 1395–1414. SIAM, 2013.

[20] John T Kent, Asaad M Ganeiber, and Kanti V Mardia. A new unified approach for the simulation of a wide class of directional distributions. *Journal of Computational and Graphical Statistics*, 27(2):291–301, 2018.

[21] Beatrice Laurent and Pascal Massart. Adaptive estimation of a quadratic functional by model selection. *Annals of Statistics*, pages 1302–1338, 2000.

[22] Yann LeCun, Corinna Cortes, and Christopher J.C. Burges. The mnist database of handwritten digits, 1998. Available online at: `http://yann.lecun.com/exdb/mnist/`. Last accessed: May. 2022.

[23] Xiyang Liu, Weihao Kong, and Sewoong Oh. Differential privacy and robust statistics in high dimensions. *arXiv preprint arXiv:2111.06578*, 2021.

[24] H Brendan McMahan, Daniel Ramage, Kunal Talwar, and Li Zhang. Learning differentially private recurrent language models. *arXiv preprint arXiv:1710.06963*, 2017.

[25] Kobbi Nissim, Sofya Raskhodnikova, and Adam Smith. Smooth sensitivity and sampling in private data analysis. In *Proceedings of the thirty-ninth annual ACM symposium on Theory of computing*, pages 75–84, 2007.

[26] Sixth Conference on Machine Translation WMT21. News commentary crawl v16, 2021. Available online at: `https://www.statmt.org/wmt20/translation-task.html`. Last accessed: May. 2022.

[27] Venkatadheeraj Pichapati, Ananda Theertha Suresh, Felix X Yu, Sashank J Reddi, and Sanjiv Kumar. Adaclip: Adaptive clipping for private sgd. *arXiv preprint arXiv:1908.07643*, 2019.

[28] Holger Sambale. Some notes on concentration for α-subexponential random variables. *arXiv preprint arXiv:2002.10761*, 2020.

[29] Adam Smith. Privacy-preserving statistical estimation with optimal convergence rates. In *Proceedings of the forty-third annual ACM symposium on Theory of computing*, pages 813–822, 2011.

[30] Jalaj Upadhyay. The price of privacy for low-rank factorization. In *NeurIPS*, 2018.

[31] Martin J Wainwright. *High-dimensional statistics: A non-asymptotic viewpoint*, volume 48. Cambridge University Press, 2019.