REFINING DEEP GENERATIVE MODELS VIA WASSERSTEIN GRADIENT FLOWS

ABSTRACT

Deep generative modeling has seen impressive advances in recent years, to the point where it is now commonplace to see simulated samples (e.g., images) that closely resemble real-world data. However, generation quality is generally inconsistent for any given model and can vary dramatically between samples. We introduce Discriminator Gradient $f$low (DG$f$low), a new technique that improves generated samples via the gradient flow of entropy-regularized f-divergences between the real and the generated data distributions. The gradient flow takes the form of a *non-linear* Fokker-Plank equation, which can be easily simulated by sampling from the equivalent McKean-Vlasov process. By refining inferior samples, our technique avoids expensive sample rejection used by previous methods. Compared to existing works that focus on specific GAN variants, we show our refinement approach can be applied to GANs with vector-valued critics and even other deep generative models such as VAEs and Normalizing Flows. Empirical results on multiple synthetic, image, and text datasets demonstrate that DG$f$low leads to significant improvement in the quality of generated samples for a variety of generative models, outperforming the state-of-the-art Discriminator Optimal Transport (DOT) and Discriminator Driven Latent Sampling (DDLS) methods.

1 INTRODUCTION

Deep generative models (DGMs) have excelled at numerous tasks, from generating realistic images (Brock et al., 2019) to learning policies in reinforcement learning (Ho & Ermon, 2016). Among the variety of proposed DGMs, Generative Adversarial Networks (GANs) (Goodfellow et al., 2014) have received widespread popularity for their ability to generate high quality samples that resemble real data. Unlike Variational Autoencoders (VAEs) (Kingma & Welling, 2014) and Normalizing Flows (Rezende & Mohamed, 2015; Kingma & Dhariwal, 2018), GANs are likelihood-free methods; training is formulated as a minimax optimization problem involving a generator and a discriminator. The generator seeks to generate samples that are similar to the real data by minimizing some measure of distance between the generated samples and real samples. The discriminator is trained to maximize this distance. Once trained, the generator is used to simulate samples and the discriminator has traditionally been discarded.

However, recent work has shown that discarding the discriminator is wasteful — it actually contains useful information about the underlying data distribution. This insight has led to *sample improvement* techniques that use this information to improve the quality of generated samples (Azadi et al., 2019; Turner et al., 2019; Che et al., 2020; Tanaka, 2019; Che et al., 2020). Unfortunately, current methods either rely on expensive rejection operations in the data space (Azadi et al., 2019; Turner et al., 2019), or require a sensitive diffusion term to ensure sample diversity (Che et al., 2020). Prior work has also focussed on improving GANs with scalar-valued discriminators, which excludes a large family of GANs with vector-valued critics, e.g., MMDGAN (Li et al., 2017; Bińkowski et al., 2018) and OCFGAN (Ansari et al., 2020), and likelihood-based generative models.

In this work, we propose Discriminator Gradient $f$low (DG$f$low) which formulates sample improvement as refining inferior samples using the *gradient flow* of f-divergences between the generator and the real data distributions. DG$f$low avoids expensive rejection operations and can be used in a deterministic setting without a diffusion term. Existing state-of-the-art methods — specifically, Discriminator Optimal Transport (DOT) (Tanaka, 2019) and Discriminator Driven Latent Sampling (DDLS) (Che et al., 2020) — can be viewed as special cases of DG$f$low. Similar to

DDLS, DG$f$low recovers the real data distribution when the gradient flow is simulated exactly. We further present a generalized framework that employs existing pre-trained discriminators to refine samples from a *variety* of deep generative models: we demonstrate our method can be applied to GANs with vector-valued critics, and even likelihood-based models such as VAEs and Normalizing Flows. Empirical results on synthetic datasets, and benchmark image (CIFAR10, STL10) and text (Billion Words) datasets demonstrate that our gradient flow-based approach outperforms DOT and DDLS on multiple quantitative evaluation metrics.

In summary, this paper makes the following key contributions:

- DG$f$low, a method to refine deep generative models using the gradient flow of f-divergences;
- a framework that extends DG$f$low to GANs with vector-valued critics, VAEs, and Normalizing Flows;
- experiments on a variety of generative models trained on synthetic, image (CIFAR10 & STL10), and text (Billion Words) datasets demonstrating that DG$f$low is effective in improving samples from generative models.

2   BACKGROUND: GRADIENT FLOWS

The following gives a brief introduction to gradient flows; we refer readers to the excellent overview by Santambrogio (2017) for a more thorough introduction.

Let $(\mathcal{X}, d)$ be a metric space and $F : \mathcal{X} \rightarrow \mathbb{R}$ be a smooth functional. The gradient flow of F in $(\mathcal{X}, d)$ is the smooth curve $\{\mathbf{x}_t\}_{t \in \mathbb{R}_+}$ that follows the direction of steepest descent, i.e.,

$$\mathbf{x}'(t) = -\mathrm{grad}_d F(\mathbf{x}(t)), \tag{1}$$

where grad_d defines a notion of gradient in the metric space $(\mathcal{X}, d)$. The value of the functional F is minimized along this curve. Of particular interest are gradient flows in the space of probability measures that is endowed with the Wasserstein distance ($\mathcal{W}_p$); the Wasserstein distance is a metric and the $\mathcal{W}_p$ topology satisfies weak convergence of probability measures (Villani, 2008). Gradient flows in the Wasserstein space $(\mathcal{P}_2(\Omega), \mathcal{W}_2)$, the space of probability measures with finite second moments and the Wasserstein-2 metric, have been studied extensively. Let $\{\rho_t\}_{t \in \mathbb{R}_+}$ be the gradient flow of a functional $\mathcal{F}$ in the Wasserstein space, where ρ_t is absolutely continuous with respect to the Lebesgue measure. The curve $\{\rho_t\}_{t \in \mathbb{R}_+}$ satisfies the continuity equation (Ambrosio et al., 2008),

$$\partial_t \rho_t = -\nabla \cdot (\rho_t \mathbf{v}_t). \tag{2}$$

The velocity field $\mathbf{v}_t$ in Eq. (2) is given by

$$\mathbf{v}_t(\mathbf{x}) = -\nabla_{\mathbf{x}} \frac{\delta \mathcal{F}}{\delta \rho}(\rho), \tag{3}$$

where $\frac{\delta \mathcal{F}}{\delta \rho}$ denotes the first variation of the functional $\mathcal{F}$.

Since the seminal work of Jordan et al. (1998) that showed that the Fokker-Plank equation is the gradient flow of a particular functional in the Wasserstein space, gradient flows in the Wasserstein metric have been a popular tool in the analysis of partial differential equations (PDEs). For example, they have been applied to the study of the porous-medium equation (Otto, 2001), crowd modeling (Maury et al., 2010; 2011), and mean-field games (Almulla et al., 2017). More recently, gradient flows of various distances used in deep generative modeling literature have been proposed, notably that of the sliced Wasserstein distance (Liutkus et al., 2019), and the maximum mean discrepancy (Arbel et al., 2019), Stein discrepancy (Liu, 2017), and Sobolev discrepancy (Mroueh et al., 2019). Gradient flows have also been used for learning non-parametric and parametric implicit generative models (Liutkus et al., 2019; Gao et al., 2019; 2020). In this work, we present a method using gradient flows for refining samples from deep generative models.

3   GENERATOR REFINEMENT VIA DISCRIMINATOR GRADIENT FLOWS

This section describes our main contribution: Discriminator Gradient $f$low (DG$f$low). As an overview, we begin with the construction of the gradient flow of entropy-regularized f-divergences

and describe its application to sample refinement. We then discuss how to simulate the gradient flow in the latent space of the generator — a procedure more suitable for high-dimensional datasets. Finally, we present a simple technique that extends our method to generative models that have not yet been studied in the context of refinement. Due to space constraints, we focus on conveying the key concepts and relegate details (e.g., proofs) to the appendix.

The entropy-regularized f-divergence functional is defined as

$$\mathcal{F}_\mu^f(\rho) \triangleq \mathcal{D}_f(\mu \| \rho) - \gamma \mathcal{H}(\rho), \tag{4}$$

where the f-divergence term $\mathcal{D}_f(\mu \| \rho)$ ensures that the "distance" between the probability density ρ and the target density μ decreases along the gradient flow. The differential entropy term $\mathcal{H}(\rho)$ improves diversity and expressiveness when the gradient flow is simulated for finite time-steps. We now construct the gradient flow of $\mathcal{F}_\mu^f$.

Lemma 3.1. *Define the functional $\mathcal{F}_\mu^f : \mathcal{P}_2(\Omega) \to \mathbb{R}$ as*

$$\mathcal{F}_\mu^f(\rho) \triangleq \underbrace{\int f\left(\rho(\mathbf{x})/\mu(\mathbf{x})\right)\mu(\mathbf{x})d\mathbf{x}}_{\text{f-divergence}} + \gamma \underbrace{\int \rho(\mathbf{x})\log\rho(\mathbf{x})d\mathbf{x}}_{\text{negative entropy}}, \tag{5}$$

where f is a twice-differentiable convex function with $f(1) = 0$. The gradient flow of the functional $\mathcal{F}_\mu^f(\rho)$ in the Wasserstein space $(P_2(\Omega), \mathcal{W}_2)$ is given by the following PDE,

$$\partial_t\rho_t(\mathbf{x}) - \nabla_\mathbf{x} \cdot \left(\rho_t(\mathbf{x})\nabla_\mathbf{x}f'\left(\rho_t(\mathbf{x})/\mu(\mathbf{x})\right)\right) - \gamma\Delta_{\mathbf{xx}}\rho_t(\mathbf{x}) = 0, \tag{6}$$

where $\nabla_\mathbf{x}\cdot$ and $\Delta_{\mathbf{xx}}$ denote the divergence and the Laplace operators respectively.

The proof is given in Appendix A.1. The PDE in Eq. (6) is a type of Fokker-Plank equation (FPE). FPEs have been studied extensively in the literature of stochastic processes and have a Stochastic Differential Equation (SDE) counterpart (Risken, 1996). In the case of Eq. (6), the equivalent SDE is given by

$$d\mathbf{x}_t = \underbrace{-\nabla_\mathbf{x}f'\left(\rho_t/\mu\right)(\mathbf{x}_t)dt}_{\text{drift}} + \underbrace{\sqrt{2\gamma}d\mathbf{w}_t}_{\text{diffusion}}, \tag{7}$$

where $d\mathbf{w}_t$ denotes the standard Weiner process. Eq. (7) defines the evolution of a particle $\mathbf{x}_t$ under the influence of drift and diffusion. Specifically, it is a McKean-Vlasov process (Braun & Hepp, 1977) which is a type of *non-linear* stochastic process as the drift term at any time t depends on the distribution ρ_t of the particle $\mathbf{x}_t$. Eqs. (6) and (7) are equivalent in the sense that the distribution of particle $\mathbf{x}_t$ in Eq. (7) solves the PDE in Eq. (6). Consequently, samples from the density ρ_t along the gradient flow can be obtained by first drawing samples $\mathbf{x}_0 \sim \rho_0$ and then simulating the SDE in Eq. (7). The SDE can be approximately simulated via the stochastic Euler scheme (also known as the Euler-Maruyama method) (Beyn & Kruse, 2011) given by

$$\mathbf{x}_{\tau_{n+1}} = \mathbf{x}_{\tau_n} - \eta\nabla_\mathbf{x}f'\left(\rho_{\tau_n}/\mu\right)(\mathbf{x}_{\tau_n}) + \sqrt{2\gamma\eta}\boldsymbol{\xi}_{\tau_n}, \tag{8}$$

where $\boldsymbol{\xi}_{\tau_n} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$, the time interval $[0, T]$ is partitioned into equal intervals of size η and $\tau_0 < \tau_1 < \cdots < \tau_N$ denote the discretized time-steps.

Eq. (8) provides a non-parametric procedure to refine samples from a generator g_θ where we let μ be the density of real samples and ρ_{τ_0} the density of samples generated from g_θ obtained by first sampling from the prior latent distribution $\mathbf{z} \sim p_Z(\mathbf{z})$ and then feeding $\mathbf{z}$ into g_θ. We first generate particles $\mathbf{x}_0 \sim \rho_{\tau_0}$ and then update the particles using Eq. (8) for N time steps.

Given a binary classifier (discriminator) D that has been trained to distinguish between samples from μ and ρ_{τ_0}, the density-ratio $\rho_{\tau_0}(\mathbf{x})/\mu(\mathbf{x})$ can be estimated via the well-known *density-ratio trick* (Sugiyama et al., 2012),

$$\rho_{\tau_0}(\mathbf{x})/\mu(\mathbf{x}) = \frac{1 - D(y = 1|\mathbf{x})}{D(y = 1|\mathbf{x})} = \exp(-d(\mathbf{x})), \tag{9}$$

where $D(y = 1|\mathbf{x})$ denotes the conditional probability of the sample $\mathbf{x}$ being from μ and $d(\mathbf{x})$ denotes the logit output of the classifier D. We term this procedure where samples are refined via gradient flow of f-divergences as Discriminator Gradient $f$low (DG$f$low).

3.1 REFINEMENT IN THE LATENT SPACE

Eq. (8) requires a running estimate of the density-ratio $\rho_{\tau_n}(\mathbf{x})/\mu(\mathbf{x})$. However, experiments show that the stale estimate $\rho_{\tau_n}(\mathbf{x})/\mu(\mathbf{x}) \approx \rho_{\tau_0}(\mathbf{x})/\mu(\mathbf{x})$ provides a good enough approximation for the purpose of refining samples; intuitively, for $\eta \to 0$ and small N, the density ρ_{τ_n} will be close to ρ_{τ_0}. That said, refining directly in the data-space using the stale estimate poses problems due to high-dimensionality of real-world data. The error is accumulated at each time-step leading to a visible degradation in the quality of data samples (e.g., appearance of artifacts in images).

To tackle this problem, we propose refining the latent vectors before mapping them to samples in data-space using g_θ. We describe a procedure analogous to Eq. (8) but in the latent space for generators g_θ that take a latent vector $\mathbf{z} \in \mathcal{Z}$ as input and generate a sample $\mathbf{x} \in \mathcal{X}$. We first show in Lemma 3.2 that the density-ratio in the latent space between two distributions can be estimated via the density-ratio of corresponding distributions in the data space.

Lemma 3.2. *Let $g : \mathcal{Z} \to \mathcal{X}$ be a sufficiently well-behaved function where $\mathcal{Z} \subseteq \mathbb{R}^n$ and $\mathcal{X} \subset \mathbb{R}^m$ with $m > n$. Let $p_Z(\mathbf{z})$, $p_{\hat{Z}}(\hat{\mathbf{z}})$ be probability densities on $\mathcal{Z}$ and $q_X(\mathbf{x})$, $q_{\hat{X}}(\hat{\mathbf{x}})$ be the densities of the pushforward measures $g\sharp Z$, $g\sharp\hat{Z}$ respectively. Assume that $p_Z(\mathbf{z})$ and $p_{\hat{Z}}(\hat{\mathbf{z}})$ have same support, and the Jacobian matrix $\mathbf{J}_g$ has full column rank. Then, the density-ratio $p_{\hat{Z}}(\mathbf{u})/p_Z(\mathbf{u})$ at the point $\mathbf{u} \in \mathcal{Z}$ is given by*

$$\frac{p_{\hat{Z}}(\mathbf{u})}{p_Z(\mathbf{u})} = \frac{q_{\hat{X}}(g(\mathbf{u}))}{q_X(g(\mathbf{u}))}. \tag{10}$$

The proof is in Appendix A.2. We let $p_{\hat{Z}}(\hat{\mathbf{z}})$ be the density of the "correct" latent space distribution induced by a generator g_θ, i.e., $p_{\hat{Z}}(\hat{\mathbf{z}})$ is the density of a probability measure whose pushforward under g_θ approximately equals the target data density μ. The density-ratio of the prior latent distribution $p_Z(\mathbf{z})$ and $p_{\hat{Z}}(\hat{\mathbf{z}})$ can now be computed by combining Lemma 3.2 with Eq. (9),

$$\frac{p_Z(\mathbf{u})}{p_{\hat{Z}}(\mathbf{u})} = \frac{\rho_{\tau_0}(g_\theta(\mathbf{u}))}{\mu(g_\theta(\mathbf{u}))} = \exp(-d(g_\theta(\mathbf{u}))). \tag{11}$$

Although a generator g_θ parameterized by a neural network may not satisfy the full column rank condition on its Jacobian matrix $\mathbf{J}_{g_\theta}$ for all $\mathbf{u} \in \mathcal{Z}$, Eq. (11) provides an approximation that works well in practice as shown by our experiments. Combining Eq. (11) with Eq. (8) provides us with an update rule for refining samples in the latent space

---

Algorithm 1 Refinement in the Latent Space using DG$f$low.

Require: First derivative of f (f'), generator (g_θ), discriminator (d_ϕ), number of update steps (N), step-size (η), noise factor (γ).
1: $\mathbf{z}_0 \sim p_Z(\mathbf{z})$ ▷ Sample from the prior.
2: **for** $i \leftarrow 0, N$ **do**
3:      $\boldsymbol{\xi}_i \sim \mathcal{N}(0, I)$
4:      $\mathbf{z}_{i+1} = \mathbf{z}_i - \eta\nabla_{\mathbf{z}_i}f'(e^{-d_\phi(g_\theta(\mathbf{z}_i))}) + \sqrt{2\eta\gamma}\boldsymbol{\xi}_i$
5: **end for**
6: **return** $g_\theta(\mathbf{z}_n)$ ▷ The refined sample.

$$\mathbf{u}_{\tau_{n+1}} = \mathbf{u}_{\tau_n} - \eta\nabla_{\mathbf{u}}f'\left(p_{\mathbf{u}_{\tau_n}}/p_{\hat{Z}}\right)(\mathbf{u}_{\tau_n}) + \sqrt{2\gamma\eta}\boldsymbol{\xi}_{\tau_n}, \tag{12}$$

with $\mathbf{u}_{\tau_0} \sim p_Z(\mathbf{z})$ and the density-ratio $p_{\mathbf{u}_{\tau_n}}/p_{\hat{Z}}$ approximated using the stale estimate $p_{\mathbf{u}_{\tau_0}}/p_{\hat{Z}} = \exp(-d(g_\theta(\mathbf{u})))$. We summarize the complete algorithm in Algorithm 1.

3.2 REFINEMENT FOR ALL

Thus far, prior work (Azadi et al., 2019; Turner et al., 2019; Tanaka, 2019; Che et al., 2020) has focused on improving samples for GANs with scalar-valued discriminators, which comprises the canonical GAN as well as recent variants, e.g., WGAN (Gulrajani et al., 2017), and SNGAN (Miyato et al., 2018). Here, we propose a technique that extends our approach to refine samples from a larger class of DGMs including GANs with vector-valued critics, VAEs, and Normalizing Flows.

Let p_θ be the density of the samples generated by a generator g_θ and μ be the density of the real data distribution. We are interested in refining samples from g_θ; however, a corresponding density-ratio estimator for p_θ/μ is unavailable, as is the case with the aforementioned generative models.

Let D_ϕ be a discriminator that has been trained on the same dataset but for a different generative model g_ϕ (e.g., let g_ϕ and D_ϕ be the generator and discriminator of SNGAN respectively). D_ϕ can be used to compute the density ratio p_ϕ/μ. A straightforward technique would be to use the crude approximation $p_\theta/\mu \approx p_\phi/\mu$, which could work provided p_θ and p_ϕ are not too far from each other. Our experiments show that this simple approximation works to a limited extent (see appendix E).

To improve upon the crude approximation above, we propose to correct the density ratio estimate. Specifically, a discriminator D_λ is initialized with the weights from D_ϕ and is fine-tuned on samples from g_ϕ and g_θ. D_ϕ and D_λ are then used to approximate the density-ratio p_θ/μ,

$$\frac{p_\theta(\mathbf{x})}{\mu(\mathbf{x})} = \frac{p_\phi(\mathbf{x})}{\mu(\mathbf{x})} \frac{p_\theta(\mathbf{x})}{p_\phi(\mathbf{x})} = \exp(-d_\phi(\mathbf{x})) \cdot \exp(-d_\lambda(\mathbf{x})), \tag{13}$$

where d_ϕ and d_λ are logits output from D_ϕ and D_λ, respectively. We term the network D_λ the *density ratio corrector*, which experiments show produces higher quality samples than using $p_\theta/\mu \approx p_\phi/\mu$.

4 RELATED WORK

Azadi et al. (2019) first proposed the idea of improving samples from a GAN's generator by discriminator rejection sampling (DRS), making use of the density-ratio provided by the discriminator to estimate the acceptance probability. Metropolis-Hastings GAN (MH-GAN) (Turner et al., 2019) improved upon the costly rejection sampling procedure via the Metropolis-Hastings algorithm. Unlike DG$f$low, both of these methods reject inferior samples instead of refining them.

Our method is related to recent state-of-the-art techniques, specifically Discriminator-Driven Latent Sampling (DDLS) (Che et al., 2020) and Discriminator Optimal Transport (DOT) (Tanaka, 2019). In fact, both these methods can be seen as special cases of DG$f$low.

DDLS treats a GAN as an energy-based model and uses Langevin dynamics to sample from the energy-based latent distribution $p_t(\mathbf{z}) \propto p_Z(\mathbf{z}) \exp(d(g_\theta(\mathbf{z})))$ induced by performing rejection sampling in the latent space. This distribution is the same as $p_{\hat{Z}}(\hat{\mathbf{z}})$, which can be seen by rearranging terms in Eq. (11). If we use the KL-divergence by setting $f = r \log r$, DG$f$low is equivalent to DDLS. However, there are practical differences that make DG$f$low more appealing. DDLS requires estimation of the score function $\nabla_{\mathbf{z}}\{\log p_Z(\mathbf{z}) + d(g_\theta(\mathbf{z}))\}$ to perform the update which becomes undefined if $\mathbf{z}$ escapes the support of $p_Z(\mathbf{z})$, e.g., in the case of the uniform prior distribution commonly used in GANs. This problem does not arise in the case of DG$f$low since it only uses the density-ratio that is implicitly defined by the discriminator. Moreover, DDLS uses Langevin dynamics which *requires* the sensitive diffusion term to ensure diversity and to prevent points from collapsing to the maximum-likelihood point. Another related method that uses Langevin dynamics is the Generalized Energy-Based Model (GEBM) (Arbel et al., 2020), which jointly trains an implicit generative model with an energy function that are combined. In DG$f$low, the sample diversity is ensured by the density-ratio term and the diffusion term serves as an enhancement. Note that DG$f$low performs well even without the diffusion term (i.e., with $\gamma = 0$, see Tables 10 & 11 in the appendix). This deterministic variant of DG$f$low is a practical alternative with one less hyperparameter to tune.

DOT refines samples by constructing an Optimal Transport (OT) map induced by the WGAN discriminator. The OT map is realized by means of a deterministic optimization problem in the vicinity of the generated samples. If we further analyze the case of DG$f$low with $\gamma = 0$ and solve the resulting ordinary differential equation (ODE) using the backward Euler method,

$$\mathbf{u}_{\tau_{n+1}} = \arg\min_{\mathbf{u} \in \mathbb{R}^n} \left\{ f'\left(p_{\mathbf{u}_{\tau_n}}/p_{\hat{Z}}\right)(\mathbf{u}) + \frac{1}{2\lambda}\|\mathbf{u} - \mathbf{u}_{\tau_n}\|^2 \right\}, \tag{14}$$

DOT emerges as a special case when we consider a single update step of Eq. (14) using gradient descent and set $f'(t) = \log(t)$[1] with $\lambda = \frac{1}{2}$. This connection of DG$f$low to DOT, an optimal transport technique, is perhaps unsurprising given the relationship between gradient flows and the dynamical Benamou-Brenier formulation of optimal transport (Santambrogio, 2017).

---

[1]This implies that $f(t) = t \log t - t + 1$, which is a twice-differentiable convex function with $f(0) = 1$.

5 EXPERIMENTS

In this section, we present empirical results on various deep generative models trained on multiple synthetic and real world datasets. Our primary goals were to determine if (a) DG$f$low is effective in improving the quality of samples from generative models, (b) the proposed extension to other generative models improves their sample quality, and (c) DG$f$low is generalizable to different types of data and metrics. Note that we did not seek to achieve state-of-the-art results for the datasets studied but to demonstrate that DG$f$low is able to significantly improve samples from the bare generators for different models.

We experimented with three f-divergences, namely the Kullback-Leibler (KL) divergence, the Jensen-Shannon (JS) divergence, and the $\log$ D divergence (Gao et al., 2019). The specific forms of the functions f and corresponding derivatives are tabulated in Table 7 (appendix). We compare DG$f$low with two state-of-the-art competing methods: DOT and DDLS. In this section we discuss the main results and relegate details to the appendix.

Figure 1: Qualitative comparison of DG$f$low$_{(KL)}$ with DOT and DDLS on synthetic 2D datasets.

5.1 2D DATASETS

We first tested DG$f$low on two synthetic datasets, 25Gaussians and 2DSwissroll, to visually inspect the improvement in the quality of generated samples. We generated 5000 samples from a trained WGAN-GP generator and refined them using DOT, DDLS, and DG$f$low. We performed refinement in the latent space for DDLS and directly in the data-space for DOT and DG$f$low. Fig. 1 shows the samples generated from the WGAN-GP generator (blue) and the refined samples using different techniques

Table 1: Quantitative comparison on the 25Gaussians dataset. Higher scores are better.

	% High Quality	KDE Score
GAN	26.5 ± .8	-7037 ± 64
DOT	69.8 ± .7	-4149 ± 39
DDLS	**89.3 ± .6**	-2997 ± 17
DG$f$low$_{(KL)}$	**89.5 ± .4**	**-2893 ± 07**
DG$f$low$_{(JS)}$	82.6 ± .4	-3118 ± 19
DG$f$low$_{(\log D)}$	84.5 ± .3	-3036 ± 14

(red) against the real samples from the training dataset (brown). Although the WGAN-GP generator learned the overall structure of the dataset, it also learned a number of spurious modes. DOT is able to refine the spurious samples but to a limited degree. In contrast, DDLS and DG$f$low are able to correct almost all spurious samples and are able to recover the correct structure of the data. Visualizations for DG$f$low with different f-divergences can be found in the appendix (Fig. 4).

We also compared the different methods quantitatively on two metrics: % high quality samples and kernel density estimate (KDE) score. A sample is classified as a high quality sample if it lies within 4 standard deviations of its nearest Gaussian. The KDE score is computed by first estimating the KDE using generated samples and then computing the log-likelihood of the training samples under the KDE estimate. We computed both the metrics 10 times using 5000 samples and report the mean in Table 1. The quantitative metrics reinforce the qualitative analysis and show that DDLS and DG$f$low significantly improve the samples from the generator, with DG$f$low performing slightly better than DDLS in terms of the KDE score.

5.2 IMAGE EXPERIMENTS

We conducted experiments on the CIFAR10 and STL10 datasets to demonstrate the efficacy of DG$f$low in the real-world setting. We followed the setup of Tanaka (2019) for our image exper-

Table 2: Comparison of different variants of DG$f$low with DOT on the CIFAR10 and STL10 datasets. For SN-DCGAN, (hi) denotes the hinge loss and (ns) denotes the non-saturating loss. Lower scores are better.

	Model	Fréchet Inception Distance				
		Base Model	DOT ^{2}	DG$f$low$_{(KL)}$	DG$f$low$_{(JS)}$	DG$f$low$_{(\log D)}$
CIFAR10	WGAN-GP	28.37 (.08)	24.14	24.68 (.09)	**23.15 (.07)**	24.53 (.11)
	SN-DCGAN (hi)	20.70 (.05)	17.12	**15.68 (.07)**	16.45 (.06)	17.36 (.05)
	SN-DCGAN (ns)	20.90 (.11)	15.78	**15.30 (.08)**	15.90 (.11)	16.42 (.05)
	SN-ResNet-GAN	14.10 (.06)	–	**9.62 (.03)**	9.79 (.02)	9.73 (.05)
STL10	WGAN-GP	51.50 (.15)	44.45	**39.07 (.07)**	50.83 (.06)	39.71 (.29)
	SN-DCGAN (hi)	40.54 (.17)	**34.85**	34.95 (.06)	36.37 (.12)	36.56 (.08)
	SN-DCGAN (ns)	41.86 (.12)	34.84	**34.60 (.11)**	35.37 (.12)	37.07 (.14)

iments. We used the Fréchet Inception Distance (FID) (Heusel et al., 2017) and Inception Score (IS) (Salimans et al., 2016) metrics to evaluate the quality of generated samples before and after refinement. A high value of IS and a low value of FID corresponds to high quality samples, respectively.

We first applied DG$f$low to GANs with scalar-valued discriminators (e.g., WGAN-GP, SNGAN) trained on the CIFAR10 and the STL10 datasets. Table 2 shows that DG$f$low significantly improves the quality of the samples in terms of the FID score and outperforms DOT on multiple models. The corresponding values of the Inception score can be found in the Appendix (Table 8), which shows DG$f$low outperforms DOT on all models. In Table 3, we reproduce previously reported IS results for generative models and other sample improvement methods (DRS, MH-GAN, and DDLS) for completeness. DG$f$low performs the best in terms of relative improvement from the base score and even outperforms the state-of-the-art BigGAN (Brock et al., 2019), a conditional generative

(a) CIFAR10   (b) STL10

Figure 2: Improvement in the quality of samples generated from the base model (leftmost columns) over the steps of DG$f$low for SN-ResNet-GAN and SN-DCGAN on the CIFAR10 and STL10 datasets respectively.

model, without the need for additional labels. Qualitatively, DG$f$low improves the vibrance of the samples and corrects deformations in the foreground object. Fig. 2 shows the change in the quality of samples when using DG$f$low where the leftmost columns show the image generated form the base models and the successive columns show the refined sample using DG$f$low over increments of 5 update steps.

We then evaluated the ability of DG$f$low to refine samples from generative models *without corresponding discriminators*, namely MMDGAN, OCFGAN-GP, VAEs, and Normalizing Flows (Glow). We used the SN-DCGAN (ns) as the surrogate discriminator D_ϕ for these models and fine-tuned density ratio correctors D_λ for each model as described in section 3.2. Table 4 shows the FID scores achieved by these models without and with refinement using DG$f$low. We obtain a clear improvement in quality of samples when these generative models are combined with DG$f$low.

---

^{2}Results taken from Tanaka (2019). Note that Tanaka (2019) reported the scores of a single run whereas we report an average over 5 random runs with the standard deviation in parentheses.

Table 3: Inception scores of different generative models, DRS, MH-GAN, DDLS, and DG$f$low on the CIFAR10 dataset. Higher scores are better.

Model	Inception Score
WGAN-GP (Gulrajani et al., 2017)	7.86 (.07)
ProgressiveGAN (Karras et al., 2017)	8.80 (.05)
SN-ResNet-GAN (Miyato et al., 2018)	8.22 (.05)
NCSN (Song & Ermon, 2019)	8.87 (.12)
DCGAN	2.88
DCGAN + DRS (cal) (Azadi et al., 2019)	3.07
DCGAN + MH (cal) (Turner et al., 2019)	3.38
SN-ResNet-GAN (our evaluation)	8.38 (.03)
SN-ResNet-GAN + DDLS (cal) (Che et al., 2020)	9.09 (.10)
SN-ResNet-GAN + DG$f$low$_{(KL)}$	**9.35 (.03)**
BigGAN	9.22

Table 4: Comparison of different variants of DG$f$low applied to MMDGAN, OCFGAN-GP, VAE, and Glow models. Lower scores are better.

	Model	Fréchet Inception Distance			
		Base Model	DG$f$low$_{(KL)}$	DG$f$low$_{(JS)}$	DG$f$low$_{(\log D)}$
CIFAR10	MMDGAN	41.98 (.12)	**36.75 (.09)**	38.06 (.14)	37.75 (.10)
	OCFGAN-GP	31.98 (.12)	**26.89 (.06)**	28.20 (.06)	27.82 (.09)
	VAE	129.5 (.13)	**116.0 (.21)**	128.9 (.13)	115.2 (.06)
	Glow	100.5 (.52)	**79.02 (.23)**	94.61 (.34)	81.12 (.35)
STL10	MMDGAN	47.20 (.07)	43.21 (.06)	46.74 (.05)	**43.06 (.05)**
	OCFGAN-GP	36.55 (.08)	31.12 (.13)	36.05 (.11)	**30.61 (.14)**
	VAE	150.5 (.09)	**130.1 (.18)**	149.9 (.08)	132.5 (.28)

5.3 CHARACTER-LEVEL LANGUAGE MODELING

Finally, we conducted an experiment on the character-level language modeling task proposed by Gulrajani et al. (2017) to show that DG$f$low works on different types of data. We trained a character-level GAN language model on the Billion Words Dataset (Chelba et al., 2013), which was pre-processed into 32-character long strings. We evaluated the generated samples using the JS-4 score which computes the Jensen-Shannon-divergence between the 4-gram probabilities of the data generated by the model and the real data. Table 5 (a) shows that DG$f$low$_{(JS)}$ leads to an improvement in the JS-4 score. Table 5 (b) shows example sentences where DG$f$low visibly improves the quality of generated text.

Table 5: Results of DG$f$low on a character-level GAN language model. Lower scores are better.

(a) JS-4 scores.

Model	JS-4
WGAN-GP	0.224
DG$f$low$_{(KL)}$	0.212
DG$f$low$_{(JS)}$	**0.186**
DG$f$low$_{(\log D)}$	0.209

(b) Examples of text samples refined by DG$f$low.

Generated by WGAN-GP	Refined by DG$f$low
In Ruoduce that fhance would pol	In product that chance could rol
I said thowe toot lind talker .	I said this stood line talked 10
Now their rarning injurer hows	Now their warning injurer shows
Police report in B0sbu does off	Police report inturner will befe
We gine jaid 121 , one bub like	We gave wall said left out like
In years in 19mbisuch said he h	In years in 1900b such said he h

6 CONCLUSION

In this paper, we proposed a technique to improve samples from deep generative models by refining them using gradient flow of f-divergences between the real and the generator data distributions. We also presented a simple framework that extends the proposed technique to commonly used deep generative models: GANs, VAEs, and Normalizing Flows. Experimental results indicate that gradient flows provide an excellent alternative methodology to refine generative models. As future work, we are extending our approach to IPM-based GANs by using the gradient flow of the distance metric that the GAN's critic was trained on.

REFERENCES

Noha Almulla, Rita Ferreira, and Diogo Gomes. Two numerical approaches to stationary mean-field games. *Dynamic Games and Applications*, 7(4), 2017.

Luigi Ambrosio, Nicola Gigli, and Giuseppe Savaré. *Gradient flows: in metric spaces and in the space of probability measures*. Springer Science & Business Media, 2008.

Abdul Fatir Ansari, Jonathan Scarlett, and Harold Soh. A characteristic function approach to deep implicit generative modeling. In *CVPR*, 2020.

Michael Arbel, Anna Korba, Adil Salim, and Arthur Gretton. Maximum mean discrepancy gradient flow. In *NeurIPS*, 2019.

Michael Arbel, Liang Zhou, and Arthur Gretton. Generalized energy based models. 2020.

Samaneh Azadi, Catherine Olsson, Trevor Darrell, Ian Goodfellow, and Augustus Odena. Discriminator rejection sampling. In *ICLR*, 2019.

Adi Ben-Israel. The change-of-variables formula using matrix volume. *SIAM Journal on Matrix Analysis and Applications*, 21(1), 1999.

Wolf-Jurgen Beyn and Raphael Kruse. Numerical methods for stochastic processes. *Lecture Book (in preparation)*, 2011.

Mikołaj Bińkowski, Dougal J Sutherland, Michael Arbel, and Arthur Gretton. Demystifying MMD GANs. *arXiv preprint arXiv:1801.01401*, 2018.

Werner Braun and K Hepp. The vlasov dynamics and its fluctuations in the 1/n limit of interacting classical particles. *Communications in mathematical physics*, 56(2), 1977.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale GAN training for high fidelity natural image synthesis. In *ICLR*, 2019.

Tong Che, Ruixiang Zhang, Jascha Sohl-Dickstein, Hugo Larochelle, Liam Paull, Yuan Cao, and Yoshua Bengio. Your gan is secretly an energy-based model and you should use discriminator driven latent sampling. *arXiv preprint arXiv:2003.06060*, 2020.

Ciprian Chelba, Tomas Mikolov, Mike Schuster, Qi Ge, Thorsten Brants, Phillipp Koehn, and Tony Robinson. One billion word benchmark for measuring progress in statistical language modeling. *arXiv preprint arXiv:1312.3005*, 2013.

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *AISTATS*, 2011.

Yuntian Deng, Anton Bakhtin, Myle Ott, Arthur Szlam, and Marc'Aurelio Ranzato. Residual energy-based models for text generation. In *ICLR*, 2020.

Yuan Gao, Yuling Jiao, Yang Wang, Yao Wang, Can Yang, and Shunkang Zhang. Deep generative learning via variational gradient flow. *arXiv preprint arXiv:1901.08469*, 2019.

Yuan Gao, Jian Huang, Yuling Jiao, and Jin Liu. Learning implicit generative models with theoretical guarantees. *arXiv preprint arXiv:2002.02862*, 2020.

Mevlana C Gemici, Danilo Rezende, and Shakir Mohamed. Normalizing flows on riemannian manifolds. *arXiv preprint arXiv:1611.02304*, 2016.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *NeurIPS*, 2014.

Aditya Grover, Ramki Gummadi, Miguel Lazaro-Gredilla, Dale Schuurmans, and Stefano Ermon. Variational rejection sampling. In *AISTATS*, 2018.

Aditya Grover, Jiaming Song, Ashish Kapoor, Kenneth Tran, Alekh Agarwal, Eric J Horvitz, and Stefano Ermon. Bias correction of learned generative models using likelihood-free importance weighting. In *NeurIPS*, 2019.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. In *NeurIPS*, 2017.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs trained by a two time-scale update rule converge to a local nash equilibrium. In *NeurIPS*, 2017.

Jonathan Ho and S. Ermon. Generative adversarial imitation learning. In *NeurIPS*, 2016.

Richard Jordan, David Kinderlehrer, and Felix Otto. The variational formulation of the fokker–planck equation. *SIAM journal on mathematical analysis*, 29(1), 1998.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of GANs for improved quality, stability, and variation. *arXiv preprint arXiv:1710.10196*, 2017.

Diederik P. Kingma and M. Welling. Auto-encoding variational bayes. *CoRR*, abs/1312.6114, 2014.

Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In *NeurIPS*, 2018.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Chun-Liang Li, Wei-Cheng Chang, Yu Cheng, Yiming Yang, and Barnabás Póczos. MMDGAN: Towards deeper understanding of moment matching network. In *NeurIPS*, 2017.

Qiang Liu. Stein variational gradient descent as gradient flow. In *NeurIPS*, 2017.

Antoine Liutkus, Umut Simsekli, Szymon Majewski, Alain Durmus, and Fabian-Robert Stöter. Sliced-wasserstein flows: Nonparametric generative modeling via optimal transport and diffusions. In *ICML*. PMLR, 2019.

Bertrand Maury, Aude Roudneff-Chupin, and Filippo Santambrogio. A macroscopic crowd motion model of gradient flow type. *Mathematical Models and Methods in Applied Sciences*, 20(10), 2010.

Bertrand Maury, Aude Roudneff-Chupin, Filippo Santambrogio, and Juliette Venel. Handling congestion in crowd motion modeling. *arXiv preprint arXiv:1101.4102*, 2011.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. In *ICLR*, 2018.

Youssef Mroueh, Tom Sercu, and Anant Raj. Sobolev descent. In *AISTATS*, 2019.

Felix Otto. The geometry of dissipative evolution equations: the porous medium equation. 2001.

Danilo Jimenez Rezende and S. Mohamed. Variational inference with normalizing flows. In *ICML*, 2015.

Hannes Risken. *Fokker-planck equation*. Springer, 1996.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training GANs. In *NeurIPS*, 2016.

Filippo Santambrogio. {Euclidean, metric, and Wasserstein} gradient flows: an overview. *Bulletin of Mathematical Sciences*, 7(1), 2017.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. In *NeurIPS*, 2019.

Masashi Sugiyama, Taiji Suzuki, and Takafumi Kanamori. *Density ratio estimation in machine learning*. Cambridge University Press, 2012.

Akinori Tanaka. Discriminator optimal transport. In *NeurIPS*, 2019.

Ryan Turner, Jane Hung, Eric Frank, Yunus Saatchi, and Jason Yosinski. Metropolis-hastings generative adversarial networks. In *ICML*. PMLR, 2019.

Cédric Villani. *Optimal transport: old and new*, volume 338. Springer Science & Business Media, 2008.

A PROOFS

A.1 LEMMA 3.1

Proof. Gradient flows in the Wasserstein space are of the form of the continuity equation (see Ambrosio et al. (2008), page 281), i.e,

$$\partial_t \rho_t + \nabla \cdot (\rho_t \mathbf{v}) = 0, \tag{15}$$

where the velocity field $\mathbf{v}$ is given by

$$\mathbf{v}(\mathbf{x}) = -\nabla_{\mathbf{x}} \frac{\delta \mathcal{F}}{\delta \rho}(\rho), \tag{16}$$

where $\frac{\delta \mathcal{F}}{\delta \rho}(\rho)$ denotes the first variation of the functional F and is defined as

$$\frac{d}{d\varepsilon} \mathcal{F}(\rho + \varepsilon \chi) \Big|_{\varepsilon=0} = \int \frac{\delta \mathcal{F}}{\delta \rho}(\rho) \chi, \tag{17}$$

where $\chi = \nu - \rho$ for some $\nu \in \mathcal{P}_2(\Omega)$.

Let's derive an expression for the the first variation of $\mathcal{F}$. In the following, we drop the notation for dependence on $\mathbf{x}$ for clarity,

$$\frac{d}{d\varepsilon} \mathcal{F}(\rho + \varepsilon \chi) \Big|_{\varepsilon=0} = \frac{d}{d\varepsilon} \int f\left(\frac{\rho + \varepsilon \chi}{\mu}\right) \mu + \gamma \int (\rho + \varepsilon \chi) \log(\rho + \varepsilon \chi) \Big|_{\varepsilon=0} \tag{18}$$

$$= \int f'\left(\frac{\rho + \varepsilon \chi}{\mu}\right) \chi + \gamma \int (\log(\rho + \varepsilon \chi) + 1) \chi \Big|_{\varepsilon=0} \tag{19}$$

$$= \int \left[f'\left(\frac{\rho}{\mu}\right) + \gamma \log(\rho) + \gamma \right] \chi. \tag{20}$$

Substituting $\frac{\delta \mathcal{F}}{\delta \rho}(\rho)$ in Eq. (16) we get,

$$\mathbf{v}(\mathbf{x}) = -\nabla_{\mathbf{x}} \left[f'\left(\frac{\rho}{\mu}\right) + \gamma \log(\rho) + \gamma \right] \tag{21}$$

$$= -\nabla_{\mathbf{x}} f'\left(\frac{\rho}{\mu}\right) - \frac{\gamma}{\rho} \nabla_{\mathbf{x}} \rho. \tag{22}$$

Substituting $\mathbf{v}$ in Eq. (15) we get,

$$\partial_t \rho_t - \nabla_{\mathbf{x}} \cdot \left(\rho_t \nabla_{\mathbf{x}} f'\left(\frac{\rho}{\mu}\right) + \rho_t \frac{\gamma}{\rho} \nabla_{\mathbf{x}} \rho \right) = 0 \tag{23}$$

$$\partial_t \rho_t(\mathbf{x}) - \nabla_{\mathbf{x}} \cdot \left(\rho_t \nabla_{\mathbf{x}} f'\left(\frac{\rho(\mathbf{x})}{\mu(\mathbf{x})}\right) \right) - \gamma \Delta_{\mathbf{xx}} \rho_t(\mathbf{x}) = 0, \tag{24}$$

where $\Delta_{\mathbf{xx}}$ and $\nabla_{\mathbf{x}} \cdot$ denote the Laplace and the divergence operators respectively. $\qquad \square$

A.2 LEMMA 3.2

Proof. Let f be an integrable function on $\mathcal{X}$. If $\mathbf{J}_g$ has full column rank, then we have (Ben-Israel, 1999; Gemici et al., 2016)

$$\int_{\mathcal{X}} f(\mathbf{x}) d\mathbf{x} = \int_{\mathcal{Z}} (f \circ g)(\mathbf{z}) \sqrt{\det \mathbf{J}_g^\top \mathbf{J}_g(\mathbf{z})} d\mathbf{z}. \tag{25}$$

This implies that the infinitesimal volumes $d\mathbf{x}$ and $d\mathbf{z}$ are related as $d\mathbf{x} = \sqrt{\det \mathbf{J}_g^\top \mathbf{J}_g(\mathbf{z})} d\mathbf{z}$ and the densities $p_Z(\mathbf{z})$ and $q_X(\mathbf{x})$ are related as $p_Z(\mathbf{z}) = q_X(g(\mathbf{z})) \sqrt{\det \mathbf{J}_g^\top \mathbf{J}_g(\mathbf{z})}$. Similarly, $p_{\hat{Z}}(\hat{\mathbf{z}}) =$

$q_{\hat{X}}(g(\hat{\mathbf{z}}))\sqrt{\det \mathbf{J}_g^\top \mathbf{J}_g(\hat{\mathbf{z}})}$. Finally, the density-ratio $p_{\hat{Z}}(\mathbf{u})/p_Z(\mathbf{u})$ at the point $\mathbf{u} \in \mathcal{Z}$ is given by

$$\frac{p_{\hat{Z}}(\mathbf{u})}{p_Z(\mathbf{u})} = \frac{q_{\hat{X}}(g(\mathbf{u}))\sqrt{\det \mathbf{J}_g^\top \mathbf{J}_g(\mathbf{u})}}{q_X(g(\mathbf{u}))\sqrt{\det \mathbf{J}_g^\top \mathbf{J}_g(\mathbf{u})}} = \frac{q_{\hat{X}}(g(\mathbf{u}))}{q_X(g(\mathbf{u}))}. \tag{26}$$

$\square$

B A DISCUSSION ON DGfLOW FOR WGAN

We apply DG$f$low to WGAN models by treating the output from their critics as the logit for the estimation of density ratio. However, it is well-known that WGAN critics are not density-ratio estimators as they are trained to maximize the 1-Wasserstein distance with an unconstrained output. In this section, we provide theoretical justification for the good performance of DG$f$low on WGAN models. We show that DG$f$low is related to the gradient flow of the entropy-regularized 1-Wasserstein functional $\mathcal{F}_\mu^{\mathcal{W}} : \mathcal{P}_2(\Omega) \to \mathbb{R}$,

$$\mathcal{F}_\mu^{\mathcal{W}}(\rho) \triangleq \underbrace{\sup_{\|d\|_{\mathrm{Lip}} \leq 1} \int d(\mathbf{x})\, \mu(\mathbf{x})d\mathbf{x} - \int d(\mathbf{x})\, \rho(\mathbf{x})d\mathbf{x}}_{\text{1-Wasserstein distance}} + \gamma \underbrace{\int \rho(\mathbf{x}) \log \rho(\mathbf{x})d\mathbf{x}}_{\text{negative entropy}}, \tag{27}$$

where μ denotes the target density, $\|d\|_{\mathrm{Lip}}$ denotes the Lipschitz constant of the function d.

Let d^* be the function that achieves the supremum in Eq. (27). This results in the functional,

$$\mathcal{F}_\mu^{\mathcal{W}}(\rho) = \int d^*(\mathbf{x})\, \mu(\mathbf{x})d\mathbf{x} - \int d^*(\mathbf{x})\, \rho(\mathbf{x})d\mathbf{x} + \gamma \int \rho(\mathbf{x}) \log \rho(\mathbf{x})d\mathbf{x}. \tag{28}$$

Following a similar derivation as in Appendix A.1, the gradient flow of $\mathcal{F}_\mu^{\mathcal{W}}(\rho)$ is given by the following PDE,

$$\partial_t \rho_t(\mathbf{x}) + \nabla_{\mathbf{x}} \cdot (\rho_t \nabla_{\mathbf{x}} d^*(\mathbf{x})) - \gamma \Delta_{\mathbf{xx}} \rho_t(\mathbf{x}) = 0. \tag{29}$$

If d^* is approximated using the critic (d_ϕ) of WGAN, we get the following gradient flow,

$$\partial_t \rho_t(\mathbf{x}) + \nabla_{\mathbf{x}} \cdot (\rho_t \nabla_{\mathbf{x}} d_\phi(\mathbf{x})) - \gamma \Delta_{\mathbf{xx}} \rho_t(\mathbf{x}) = 0, \tag{30}$$

which is same as the gradient flow of entropy-regularized f-divergence with $f = r \log r$ (i.e., the KL divergence) when d_ϕ is treated as a density-ratio estimator. The gradient flow of entropy-regularized f-divergence with $f = r \log r$ is simplified below,

$$\partial_t \rho_t(\mathbf{x}) - \nabla_{\mathbf{x}} \cdot (\rho_t \nabla_{\mathbf{x}} f'(\exp(-d_\phi(\mathbf{x})))) - \gamma \Delta_{\mathbf{xx}} \rho_t(\mathbf{x}) = 0 \tag{31}$$

$$\partial_t \rho_t(\mathbf{x}) - \nabla_{\mathbf{x}} \cdot (\rho_t \nabla_{\mathbf{x}} (\log(\exp(-d_\phi(\mathbf{x}))) + 1)) - \gamma \Delta_{\mathbf{xx}} \rho_t(\mathbf{x}) = 0 \tag{32}$$

$$\partial_t \rho_t(\mathbf{x}) + \nabla_{\mathbf{x}} \cdot (\rho_t \nabla_{\mathbf{x}} d_\phi(\mathbf{x})) - \gamma \Delta_{\mathbf{xx}} \rho_t(\mathbf{x}) = 0. \tag{33}$$

The equality of Eq. (30) and Eq. (33) implies that DG$f$low approximates the gradient flow of the 1-Wasserstein distance when the critic of WGAN is used for density-ratio estimation.

C OTHER RELATED WORK

Grover et al. (2018) proposed Variational Rejection Sampling, a technique to improve the variational posterior in VAEs by rejecting samples that are assigned low likelihoods by the model. Grover et al. (2019) and Deng et al. (2020) have used additional discriminators for bias correction in generative models and for training energy-based models for text generation respectively.

Table 6: Network architectures used for MMDGAN and VAE models.

(a) Generator or Decoder
Input Shape: (b, d, 1, 1)
Upconv(256)
BatchNorm
ReLU
Upconv(128)
BatchNorm
ReLU
Upconv(64)
BatchNorm
ReLU
Upconv(3)
Tanh
Output Shape: (b, 3, 32, 32)

(b) Discriminator or Encoder
Input Shape: (b, 3, 32, 32)
Conv(64)
LeakyReLU(0.2)
Conv(128)
BatchNorm
LeakyReLU(0.2)
Conv(256)
BatchNorm
LeakyReLU(0.2)
Conv(m)
Output Shape: (b, m, 1, 1)

D IMPLEMENTATION DETAILS

D.1 2D DATASETS

Datasets The 25 Gaussians dataset was constructed by generating 100000 samples from a mixture of 25 equally likely 2D isotropic Gaussians with means $\{-4, -2, 0, 2, 4\} \times \{-4, -2, 0, 2, 4\} \subset \mathbb{R}^2$ and standard deviation 0.05. Once generated, the data-points were normalized by $2\sqrt{2}$ following Tanaka (2019). The 2DSwissroll dataset was constructed by first generating 100000 samples of the 3D swissroll dataset using make_swiss_roll from scikit-learn with noise=0.25 and then only keeping dimensions $\{0, 2\}$. The generated samples were normalized by 7.5.

Base Models We trained a WGAN-GP model for both the datasets. The generator was a fully-connected network with ReLU non-linearities that mapped $z \sim \mathcal{N}(0, I_{2\times2})$ to $x \in \mathbb{R}^2$. Similarly, the discriminator was a fully-connected network with ReLU non-linearities that mapped $x \in \mathbb{R}^2$ to $\mathbb{R}$. We refer the reader to Gulrajani et al. (2017) for the exact network structures. The gradient penalty factor was set to 10. The models were trained for 10K generator iterations with a batch size of 256 using the Adam optimizer with a learning rate of 10^{-4}, $\beta_1 = 0.5$, and $\beta_1 = 0.9$. We updated the discriminator 5 times for each generator iteration.

Hyperparameters We ran DOT for 100 steps and performed gradient descent using the Adam optimizer with a learning rate of 0.01 and $\beta = (0., 0.9)$ as suggested by Tanaka (2019). DDLS was run for 50 iterations with a step-size of 0.01 and the Gaussian noise was scaled by a factor of 0.1 as suggested by Che et al. (2020). For DG$f$low, we set the step-size $\eta = 0.01$, the number of steps $n = 100$, and the noise regularizer $\gamma = 0.01$. We used the output from the WGAN-GP discriminator directly as a logit for estimating the density ratio for DDLS and DG$f$low.

Metrics We compared the different methods quantitatively on two metrics: % high quality samples and kernel density estimate (KDE) score. A sample is classified as a high quality sample if it lies within 4 standard deviations of its nearest Gaussian. The KDE score is computed by first estimating the KDE using generated samples and then computing the log-likelihood of the training samples under the KDE estimate. KDE was performed using sklearn.neighbors.KernelDensity with a Gaussian kernel and a kernel bandwidth of 0.1. The quantitative metrics were averaged over 10 runs with 5000 samples from each method.

D.2 IMAGE EXPERIMENTS

Datasets CIFAR10 (Krizhevsky et al., 2009) is a dataset of 60K natural RGB images of size 32×32 from 10 classes. STL10 is a dataset of 100K natural RGB images of size 96×96 from 10

classes. We resized the STL10 (Coates et al., 2011) dataset to 48×48 for SNGAN and WGAN-GP, and to 32×32 for MMDGAN, OCFGAN-GP, and VAE since the respective base-models were trained on these sizes.

Base Models for CIFAR10   We used the publicly available pre-trained models for WGAN-GP, SN-DCGAN (hi), and SN-DCGAN (ns). We refer the reader to Tanaka (2019) for exact details about these models. For SN-ResNet-GAN and OCFGAN-GP we used the pre-trained models from Miyato et al. (2018) and Ansari et al. (2020) respectively. We used the respective discriminators of SN-DCGAN (ns), SN-DCGAN (hi), and WGAN-GP for density-ratio estimation when refining their generators. For the SN-ResNet-GAN (hi) generator, we used SN-DCGAN (ns) discriminator as the non-saturating loss provides a better density-ratio estimation than a discriminator trained using the hinge loss.

We trained our own models for MMDGAN, VAE, and Glow. We used the generator and discriminator architectures shown in Table 6 for MMDGAN with $d = 32$. VAE used the same architecture with $d = 64$. Our Glow model was trained using the code available at `https://github.com/y0ast/Glow-PyTorch` with a batch size of 56 for 150 epochs. The density ratio correctors, D_λ (see section 3.2), were initialized with the weights from the SN-DCGAN (ns) released by Tanaka (2019). D_λ was then fine-tuned on images from SN-DCGAN (ns)'s generator and the generator being improved (e.g., MMDGAN and OCFGAN-GP) using SGD with a learning rate of 10^{-4} and momentum of 0.9. We fine-tuned D_λ for 10000 iterations with a batch size of 64.

Base Models for STL10   We used the publicly available pre-trained models (Tanaka, 2019; Ansari et al., 2020) for WGAN-GP, SN-DCGAN (hi), SN-DCGAN (ns), and OCFGAN-GP. We trained our own models for MMDGAN and VAE with the same architecture and training details as CIFAR10. We fine-tuned the density ratio correctors for STL10 for 5000 iterations with other details being the same as CIFAR10.

Hyperparameters   We performed 25 updates of DG$f$low for CIFAR10 and STL10 with a step size of 0.1 for models that do not require density ratio corrections. For STL10 models that require a density ratio correction, we performed 15 updates with a step size of 0.05. The noise regularizer (γ), whenever used, was set to 0.01.

Metrics   We used the Fréchet Inception Distance (FID) (Heusel et al., 2017) and Inception Score (IS) (Salimans et al., 2016) metrics to evaluate the quality of generated samples before and after refinement. The IS denotes the confidence in classification of the generated samples using a pretrained InceptionV3 network whereas the FID is the Fréchet distance between multivariate Gaussians fitted to the 2048 dimensional feature vectors extracted from the InceptionV3 network for real and generated data. Both the metrics were computed using 50K samples for all the models, except Glow where we used 10K samples. Following Tanaka (2019), we used the entire training and test set (60K images) for CIFAR10 and the entire unlabeled set (100K images) for STL10 as the set of real images used to compute FID.

D.3   CHARACTER LEVEL LANGUAGE MODELING

Dataset   We used the Billion Words dataset (Chelba et al., 2013) which was pre-processed into 32-character long strings.

Base Model   Our generator was a 1D CNN which followed the architecture used by Gulrajani et al. (2017).

Hyperparameters   We performed 50 updates of DG$f$low with a step size of 0.1 and noise factor $\gamma = 0$.

Metrics   The JS-4 score was computed using the code provided by Gulrajani et al. (2017) at `https://github.com/igul222/improved_wgan_training`. We used 10000 samples from the models to compute the JS-4 score.

Table 7: f-divergences and their derivatives.

f-divergence	f	f'	f''
KL	$r \log r$	$\log r + 1$	$\frac{1}{r}$
JS	$r \log r - (r+1) \log \frac{r+1}{2}$	$\log \frac{2r}{r+1}$	$\frac{1}{r^2 + r}$
log D	$(r+1) \log(r+1) - 2 \log 2$	$\log(r+1) + 1$	$\frac{1}{r+1}$

Figure 4: Qualitative comparison of DG$f$low with different f-divergences on the 25Gaussians and 2DSwissroll datasets.

E   ADDITIONAL RESULTS

Fig. 4 shows the samples generated by WGAN-GP (leftmost, blue) and refined samples generated using DG$f$low with different f-divergences (red). Fig. 3 (right) shows the latent space distribution recovered by DG$f$low when applied in the latent space for the 2D datasets. This latent space is same as the one derived by Che et al. (2020), i.e., $p_t(\mathbf{z}) \propto p_Z(\mathbf{z}) \exp(d(g_\theta(\mathbf{z})))$ which is shown in Fig. 3 (left) for both datasets.

Table 8 shows the comparison of DG$f$low with DOT in terms of the inception score for the CIFAR10 and STL10 datasets. DG$f$low outperforms DOT significantly for all the base GAN models on both the datasets. Table 9 compares different variants of DG$f$low applied to MMDGAN, OCFGAN-GP, VAE, and Glow generators in terms of the inception score. DG$f$low leads to a significant improvement in the quality of samples for all the models. Tables 10 and 11 compare the deterministic variant of DG$f$low ($\gamma = 0$) against DOT and DDLS. These results show that the diffusion term only serves as an enhancement for DG$f$low, not a necessity, and it outperforms competing methods even without added noise. Table 12 shows the results of DG$f$low on MMDGAN, OCFGAN-GP, and VAE models when the SN-DCGAN (ns) discriminator is directly used as a density-ratio estimator without an additional density-ratio corrector. Figures 5, 6, 7, and 8 show the samples generated by the base model (left) and the refined samples (right) using DG$f$low for the CIFAR10 and STL10 datasets.

(a) 25 Gaussians

(b) 2D Swissroll

Figure 3: Latent space recovered by DG$f$low (right) for the 2D datasets is same as the one derived by Che et al. (2020) (left).

Table 8: Comparison of different variants of DG$f$low with DOT on the CIFAR10 and STL10 datasets. Higher scores are better.

	Model	Inception Score				
		Base Model	DOT	DG$f$low$_{(KL)}$	DG$f$low$_{(JS)}$	DG$f$low$_{(\log D)}$
CIFAR10	WGAN-GP	6.51 (.02)	7.45	**7.99 (.02)**	7.71 (.02)	7.11 (.03)
	SN-DCGAN (hi)	7.35 (.03)	8.02	**8.13 (.02)**	7.98 (.01)	7.85 (.02)
	SN-DCGAN (ns)	7.38 (.03)	7.97	**8.14 (.03)**	7.98 (.04)	7.94 (.01)
	SN-ResNet-GAN	8.38 (.03)	–	**9.35 (.03)**	9.13 (.04)	9.05 (.03)
STL10	WGAN-GP	8.72 (.02)	9.31	**10.41 (.02)**	8.85 (.06)	9.80 (.03)
	SNGAN (hi)	8.77 (.03)	9.35	**9.74 (.04)**	9.50 (.05)	9.41 (.07)
	SNGAN (ns)	8.61 (.04)	9.45	**9.66 (.01)**	9.49 (.03)	9.18 (.03)

Table 9: Comparison of different variants of DG$f$low applied to MMDGAN, OCFGAN-GP, VAE, and Glow models. Higher scores are better.

	Model	Inception Score			
		Base Model	DG$f$low$_{(KL)}$	DG$f$low$_{(JS)}$	DG$f$low$_{(\log D)}$
CIFAR10	MMDGAN	5.74 (.02)	**6.27 (.05)**	5.99 (.03)	6.02 (.01)
	OCFGAN-GP	6.52 (.02)	**7.21 (.05)**	6.93 (.03)	6.92 (.03)
	VAE	3.20 (.01)	**3.85 (.01)**	3.21 (.02)	3.57 (.02)
	Glow	3.64 (.02)	**4.57 (.02)**	3.91 (.03)	4.47 (.03)
CIFAR10	MMDGAN	6.07 (.02)	**6.16 (.01)**	6.12 (.03)	6.12 (.03)
	OCFGAN-GP	7.09 (.01)	**7.46 (.04)**	7.10 (.03)	7.33 (.02)
	VAE	3.25 (.01)	**3.72 (.04)**	3.27 (.01)	3.65 (.03)

Table 10: Comparison of different variants of DG$f$low without diffusion (i.e., $\gamma = 0$) on the CIFAR10 and STL10 datasets. Lower scores are better.

	Model	Fréchet Inception Distance				
		Base Model	DOT	DG$f$low$_{(KL)}$	DG$f$low$_{(JS)}$	DG$f$low$_{(\log D)}$
CIFAR10	WGAN-GP	28.34 (.11)	24.14	24.64 (.13)	**23.30 (.11)**	24.42 (.19)
	SNGAN (hi)	20.67 (.09)	17.12	**15.79 (.07)**	16.79 (.09)	17.79 (.05)
	SNGAN (ns)	20.94 (.12)	15.78	**15.47 (.11)**	16.32 (.11)	16.97 (.08)
STL10	WGAN-GP	51.34 (.21)	44.45	**38.96 (.08)**	50.44 (.09)	39.35 (.12)
	SNGAN (hi)	40.82 (.16)	**34.85**	35.18 (.09)	36.53 (.13)	36.75 (.13)
	SNGAN (ns)	41.83 (.20)	**34.84**	34.81 (.08)	35.75 (.10)	37.68 (.08)

Table 11: Comparison of DDLS with DG$f$low (with and without diffusion) on the CIFAR10 dataset. Higher scores are better.

Model	Inception Score
SN-ResNet-GAN (Miyato et al., 2018)	8.22 (.05)
SN-ResNet-GAN + DDLS (cal) (Che et al., 2020)	9.09 (.10)
SN-ResNet-GAN (our evaluation)	8.38 (.03)
SN-ResNet-GAN + DG$f$low$_{(KL)}$ ($\gamma = 0$)	**9.35 (.04)**
SN-ResNet-GAN + DG$f$low$_{(KL)}$ ($\gamma = 0.01$)	**9.35 (.03)**
BigGAN	9.22

(a) WGAN-GP

(b) WGAN-GP + DG$f$low

(c) SN-DCGAN (hi)

(d) SN-DCGAN (hi) + DG$f$low

(e) SN-DCGAN (ns)

(f) SN-DCGAN (ns) + DG$f$low

(g) SN-ResNet-GAN

(h) SN-ResNet-GAN + DG$f$low

Figure 5: Samples from different models for the CIFAR10 dataset before (left) and after (right) refinement using DG$f$low.

(a) MMDGAN

(b) MMDGAN + DG$f$low

(c) OCFGAN-GP

(d) OCFGAN-GP + DG$f$low

(e) VAE

(f) VAE + DG$f$low

(g) Glow

(h) Glow + DG$f$low

Figure 6: Samples from different models for the CIFAR10 dataset before (left) and after (right) refinement using DG$f$low.

Table 12: Comparison of different variants of DG$f$low applied to MMDGAN, OCFGAN-GP, and VAE models without density-ratio correction. Lower scores are better.

Model	Fréchet Inception Distance			
	Base Model	KL	JS	log D
CIFAR10				
MMDGAN	42.03 (.06)	**39.06 (.08)**	39.68 (.06)	39.47 (.07)
OCFGAN-GP	31.95 (.07)	27.92 (.08)	29.25 (.06)	**28.82 (.10)**
VAE	129.49 (.19)	**127.50 (.15)**	128.24 (.11)	128.3 (.14)
Glow	100.7 (.14)	**93.47 (.09)**	97.50 (.11)	97.78 (.14)
STL10				
MMDGAN	47.22 (.04)	**45.75 (.10)**	45.96 (.07)	46.26 (.13)
OCFGAN-GP	36.60 (.15)	**34.17 (.18)**	34.42 (.04)	34.99 (.07)
VAE	**150.49 (.07)**	151.76 (.01)	152.03 (.05)	151.88 (.11)

(a) WGAN-GP

(b) WGAN-GP + DG$f$low

(c) SN-DCGAN (hi)

(d) SN-DCGAN (hi) + DG$f$low

(e) SN-DCGAN (ns)

(f) SN-DCGAN (ns) + DG$f$low

Figure 7: Samples from different models for the STL10 dataset before (left) and after (right) refinement using DG$f$low.

Figure 8: Samples from different models for the STL10 dataset before (left) and after (right) refinement using DG$f$low.