Deep Projective Rotation Estimation through Relative Supervision

Abstract: Orientation estimation is the core to a variety of vision and robotics tasks such as camera and object pose estimation. Deep learning has offered a way to develop image-based orientation estimators; however, such estimators often require training on a large labeled dataset, which can be time-intensive to collect. In this work, we explore whether self-supervised learning from unlabeled data can be used to alleviate this issue. Specifically, we assume access to estimates of the relative orientation between neighboring poses, such that can be obtained via a local alignment method. While self-supervised learning has been used successfully for translational object keypoints, in this work, we show that naively applying relative supervision to the rotational group $SO(3)$ will often fail to converge due to the non-convexity of the rotational space. To tackle this challenge, we propose a new algorithm for self-supervised orientation estimation which utilizes Modified Rodrigues Parameters to stereographically project the closed manifold of $SO(3)$ to the open manifold of $\mathbb{R}^3$, allowing the optimization to be done in an open Euclidean space. We empirically validate the benefits of the proposed algorithm for rotational averaging problem in two settings: (1) direct optimization on rotation parameters, and (2) optimization of parameters of a convolutional neural network that predicts object orientations from images. In both settings, we demonstrate that our proposed algorithm is able to converge to a consistent relative orientation frame much faster than algorithms that purely operate in the $SO(3)$ space. Additional information can be found on our [anonymized website.](#)

1 Introduction

Pose estimation is a critical component for a wide variety of computer vision and robotic tasks. It is a common primitive for grasping, manipulation, and planning tasks. For motion planning and control, estimating an object's pose can help a robot avoid collisions or plan how to use the object for a given task. The current top performing methods for pose estimation use machine learning to estimate the object's pose from an image; however, training these estimators tends to rely on direct supervision of the object orientation [1, 2, 3]. Obtaining such supervision can be difficult and requires either time-consuming annotations or synthetic data, which might differ from the real world. In this work, we explore whether self-supervised learning can be used to alleviate this issue by training an object orientation estimator from unlabeled data. Specifically, we assume that we can estimate the relative rotation of an object between neighboring object poses in a self-supervised manner. Such relative supervision can be easily obtained in practice, for example through a local registration method such as ICP [4] or camera pose estimation.

Relative self-supervision has been previously used for representation learning in estimating translational keypoints [5, 6, 7]. These methods use only relative supervision to ensure that the keypoints are consistent across views of the object, and do not directly supervise the keypoint locations. In this work, we explore whether such relative self-supervision can similarly be used in estimating object orientations. We show that naively applying such relative supervision to rotations on the $SO(3)$ manifold will often fail to converge. Unlike self-supervised learning of translational keypoints, the rotational averaging problem [8] is inherently non-convex, with many local optima. While there exist global optimization algorithms which jointly optimize all pairs of rotations for this problem [9, 10],

they are not easily integrated into the iterative, stochastic gradient descent methods used to train neural network-based pose estimators.

To address this issue, we propose a new algorithm, Iterative Modified Rodrigues Projective Averaging, which uses Modified Rodrigues Parameters to map from the closed manifold of $SO(3)$ to the open space of $\mathbb{R}^3$. In doing so, we obtain faster convergence with a lower likelihood of falling into local optima. Our experiments show that our method converges faster and more consistently than the standard $SO(3)$ optimization and can easily be integrated into a neural network training pipeline. Additionally, In the supplement, we include an intuitive theoretical example describing how, while not all local optima are removed, the dimensionality of a set of problematic configurations is greatly reduced when optimizing using our algorithm, as compared to optimizing in the space of $SO(3)$.

The primary contributions of this work are:

- We propose a new algorithm, Iterative Modified Rodrigues Projective Averaging, which is an iterative method for learning rotation estimation using only relative supervision and can be applied to neural network optimization.
- We empirically investigate the convergence behavior of our algorithm as compared to optimizing on the $SO(3)$ manifold.
- We demonstrate that our algorithm can be used to train a neural network-based pose estimator using only relative supervision.

2 Related Work

Averaging and Consensus Estimation: Consensus methods, sometimes referred to as averaging methods, have a long history of research. The goal of these methods is, given a distributed set of estimates, to produce a consistent prediction of a value using relative information. While there are iterative algorithms with good convergence properties in Euclidean space [11, 12, 13, 14, 15], optimizing over the closed manifold of $SO(3)$ can be more difficult, as the region is non-convex, with many local minima. Hartley et al. [8, 16] describe several methods of finding a consistent set of rotations, though their convergence is similarly not guaranteed outside of a radius $r \leq \frac{\pi}{2}$ ball in $SO(3)$. Wang and Singer [10] find an exact solution to this problem, using a combination of a semidefinite programming relaxation and a robust penalty function. More recently, Shonan Rotation Averaging [9] shows that projecting to higher dimensional spaces allows for the recovery of a globally optimal solution using semidefinite programming. These global methods, however, do not map well to local iterative updates, which are the primary means of neural network optimization. These methods are infeasible for our problem, as they do not well integrate with the SGD training frameworks used for neural networks.

Supervised Orientation Estimation: Past work has explored using a neural network to predict an object's orientation. Traditionally, these methods rely on supervising the rotations using a known absolute orientation, whether in the form of quaternions [17, 1, 18], axis-angle [19], or Euler angles [20]. More recently, 6D [21, 2], 9D [22], and 10D [23] representations have been developed for continuity and smoothness. Recently, Terzakis et al. [24] introduced Modified Rodrigues Parameters, a projection of the unit quaternion sphere $\mathbb{S}^3$ to $\mathbb{R}^3$ used in attitude control [25], to a range of common computer vision problems. Terzakis et al. [24] does not, however, address the unique problems found in the rotation averaging problem.

Some methods, such as DeepIM [26], have posed the rotation estimation problem purely as a relative problem, computing the transform to rotate from one object pose to another. Similarly, $se(3)$-TrackNet [27] tracks object pose using a Lie Algebra-based orientation update. While these methods do remove the need for absolute supervision, the resulting estimates are only useful when compared to an anchor image with an absolute orientation given. In practice, obtaining an absolute pose can be useful for both planning and joint learning of orientation representation and control. For this reason, we seek to estimate an absolute pose using relative supervision.

Recently, there has been research into mapping the Riemannian optimization to the Euclidean optimization used for network training [28, 29, 30, 31, 32]. These methods focus on applying tangent space gradients from losses in 3D transformation groups. Specifically, Projective Manifold Gradient Layer [28] ensures that the gradients take into account any projection operations, such that the gradients point towards the nearest valid representation in the projection's preimage. While this does

map the Riemannian optimization into a Euclidean problem, it does not solve the problems caused by the closed manifold of $SO(3)$, as this does not alter the underlying topology of this manifold.

3 Problem Definition

We formally describe the problem of self-supervised orientation estimation below. We assume that we are given a set of inputs observations $\{I_1, \ldots, I_N\}$, of an object where, in each input observation I_i, the object is viewed from an unknown orientation R_i. These inputs could be in the form of images, point clouds, or some other object representation. While we do not know the absolute object orientations R_i in any reference frame, we assume that we do know a subset of the relative rotations R_j^i, possibly from a local registration method like ICP, between the object in images I_j and I_i, such that $R_i = R_i^j R_j$. Our goal is to learn a function $f(I_i)$ that estimates an orientation of the object in each image, $f(I_i) = \hat{R}_i$ that minimizes the pairwise error of all input pairs, with respect to the geodesic distance metric $d(R_i, R_j) = \|\log(R_i^\top R_j)\|^2$. Given a set of rotations $\mathcal{R} = \{R_1, \ldots, R_N\}$, the core optimization objective is thus:

$$\min_{\hat{R}_i, \hat{R}_j \in \mathcal{R}} \sum_{i,j} d(R_i, R_i^j R_j) \tag{1}$$

Note that this optimization does not have a unique solution, since the solution $\hat{R}_i := SR_i, \forall i$ minimizes this error for any constant rotation S.

In many robotics tasks, relative rotations can be accurately estimated only when their magnitude is small as many registration algorithms, such as ICP, requires a good initialization near the optimum. Following this observation, we assume that we can only accurately supervise relative rotations when they are small in magnitude. This leads to a local neighborhood structure where each rotation R_i is connected to R_j only in a local neighborhood around R_i, when $d(R_i, R_j) < \epsilon$, and the set of all R_j's connected to R_i form the neighborhood set of $\mathcal{N}_i$. While the algorithms described in this manuscript do not rely on this angle ϵ, it can be scaled as needed based on the accuracy of the relative rotation estimation method (e.g. ICP, etc).

Our eventual goal is to represent the function $f(I_i) = \hat{R}_i$ as a neural network. Thus, we restrict the methods with which we compare to iterative methods that are updated using only a sampled subset of the rotations (as opposed to methods that perform a global optimization over the entire set of rotations $\{R_1, \ldots, R_N\}$). This requirement is to match the conditions required by stochastic gradient descent, the primary method of training neural networks.

4 Baselines

Preliminaries. The 3D rotational space of $SO(3) \triangleq \{R \in \mathbb{R}^{3\times3} : R^\top R = \mathbb{I}_{3\times3}, \det(R) = 1\}$ is a compact matrix Lie group, which topologically is a compact manifold. Due to the compactness of the $SO(3)$ manifold, there exist configurations of pairs of points where multiple, non-unique geodesically minimal paths exist between them; for instance, there are two unique geodesically minimal paths for a pair of antipodal points on a circle, and there are infinitely many for a pair of antipodal points on a sphere. This is not the case in an open manifold like the 3D Euclidean space of $\mathbb{R}^3$, over which there exists a unique geodesically minimal path between any arbitrary pair of points. The distinction in compactness between the 3D rotational space of $SO(3)$ and 3D Euclidean space makes optimization over $SO(3)$ more ill-conditioned than over the space of $\mathbb{R}^3$. This results in the optimization over the rotational space being non-convex. These properties of the $SO(3)$ manifold will affect the convergence of self-supervised orientation estimation, which we discuss below.

While self-supervised learning for objects translation, specifically in the form of object keypoints [5, 6, 7], has shown great success, in this work, we show that naively applying such an iterative self-supervised formulation to the rotational group $SO(3)$ will often fail to converge. Below we discuss two approaches to self-supervised orientation estimation in $SO(3)$.

Quaternion Averaging: A standard objective in rotation estimation is to minimize the geodesic distance between a predicted unit quaternion and its corresponding ground-truth orientation [33, 8], $\theta = \arccos(2\langle \hat{q}_i, q_{gt} \rangle^2)$ where $\hat{q}_i$ is the predicted orientation for image i and q_{gt} is the ground-truth orientation. An objective function is often defined to directly minimize this geodesic distance [33].

144 In our task, defined above (Section 3), we are given the relative rotation q_i^j between some pairs of
145 rotations q_i and q_j. Using this relative supervision, we can use the geodesic distance between a
146 sampled estimate, $\hat{q}_i$, its desired relative position with respect to a sampled neighbor and a known
147 relative rotation q_i^j, $\tilde{q}_i = q_i^j \otimes \hat{q}_j$, leading to the loss $\mathcal{L}_q = 1 - \langle \hat{q}_i, q_i^j \otimes \hat{q}_j \rangle^2$, where $\otimes$ denotes the
148 quaternion multiplication. Note that this loss is monotonically related to the geodesic distancewhen
149 using unit quaternions, while avoiding the need to compute an arccos.

150 $SO(3)$ **Averaging:** To optimize the rotations with respect to the non-Euclidean geometry of
151 the rotational manifold of $SO(3)$, one approach is described by Manton [34]. Each orien-
152 tation is iteratively updated in the tangent space using the logmap of $SO(3)$ and projected
153 back to $SO(3)$ using the exponential map. Specifically, we can take the gradient of the loss

$$154 \qquad \mathcal{L}_{SO(3)} = \left\| \log\left(R_i^\top R_i^j R_j \right) \right\|^2 \qquad (2a) \qquad \nabla_{\hat{r}_i} \mathcal{L}_{SO(3)} = r_\Delta = \log\left(R_i^\top R_i^j R_j \right) \qquad (2b)$$

155 which gives the update step $\hat{R}_i \leftarrow \hat{R}_i \exp(\gamma r_\Delta)$, where γ is the learning rate and $\log$ is the logmap
156 of $SO(3)$. When optimizing the full set of orientations, this algorithm can fall into local optima due
157 to the closed nature of the space which allows any orientation to be reached by two unique straight
158 paths, as the space wraps around on itself.

5   Method

160 We propose an alternative that projects the optimization to an open image and optimizes the dis-
161 tances in that space. Specifically, we use the Modified Rodriguez Projection to minimize the relative
162 error between neighboring poses in $\mathbb{R}^3$. We provide experiments in Section 6 that show that self-
163 supervised orientation estimation using Modified Rodriguez Projection converges much faster than
164 self-supervised orientation estimation in $SO(3)$, with theoretic analysis of an illustrative example
165 available in the supplement.

5.1   Iterative Modified Rodrigues Projective Averaging

167 As mentioned previously, optimizing
168 on a closed space, such as $SO(3)$
169 or $\mathbb{S}^3$ can be problematic, since the
170 relative distance between two points
171 can eventually be minimized by mov-
172 ing them in the exact opposite direc-
173 tion of the minimum path between
174 them.   To alleviate this issue, we
175 would like to instead perform self-
176 supervised learning in an open space,
177 where this symmetry is broken. This
178 can be done using Modified Ro-
179 drigues Parameters (MRP) [35, 24].
180 MRP is the stereographic projection
181 of the closed manifold of the quater-
182 nion sphere $\mathbb{S}^3$ to $\mathbb{R}^3$, and has been
183 widely used in attitude estimation and
184 control [25]. In combining this pro-

Figure 1: Projection of relative supervision, q_i^j, shown in red, from
back-projected rotation $\hat{q}_j := \phi^{-1}(\hat{\psi}_j)$ to $\hat{q}_j$ into the MRP space
update, ϕ_Δ, shown in green. While $\tilde{q}_i$ could have been selected as
the the goal rotation, it would have induced a much larger move-
ment in the projected space.

185 jection with the mapping between $SO(3)$ and $\mathbb{S}^3$, this projection can be used to optimize rotations.
186 We define a unit quaternion $q = [\rho \quad \nu] \in \mathbb{S}^3 \triangleq \{x \in \mathbb{R}^4 : \|x\| = 1\}$, where $\rho \in \mathbb{R}$ defines the
187 scalar component and $\nu \in \mathbb{R}^3$ defines the imaginary vector component of the unit quaternion. The
188 projection operator $\phi(q) = \psi \in \mathbb{R}^3$ and its inverse $\phi^{-1}(\psi) = q \in \mathbb{S}^3$ are given by [35, 24] where
189 $\psi = \phi([\rho \quad \nu]) = \frac{\nu}{1+\rho}$ and $[\rho \quad \nu] = \phi^{-1}(\psi) = \left[\frac{1-\|\psi\|^2}{1+\|\psi\|^2} \quad \frac{2\psi}{1+\|\psi\|^2} \right]$. Given this projective orien-
190 tation space, we need to map our relative rotation R_i^j into the projective space in order to use these
191 relative rotations for the self-supervised learning task. This projection is required, as the relative
192 supervision is in $SO(3)$, and the direction and magnitude of this relative measurement are distorted
193 differently in different regions of the projective MRP space. Given a pair of estimated projected ro-

tations $\hat{\psi}_i := \phi(\hat{R}_i)$ and $\hat{\psi}_j := \phi(\hat{R}_j)$, we project $\hat{\psi}_j$ back to a unit quaternion $\phi^{-1}(\hat{\psi}_j) = \hat{q}_j \in \mathbb{S}^3$ and rotate it according to R_i^j, $\tilde{q}_i = q_i^j \otimes \hat{q}_j$, where $\otimes$ is quaternion multiplication and q_i^j is the quaternion form of R_i^j. The resulting unit quaternion $\tilde{q}_i$ is then projected back into the Modified Rodrigues Parameter space, $\tilde{\psi}_i$. A simplified visual analogy of this process is shown in Figure 1.

While this relative rotation could be applied and projected at either the sampled point $\hat{\psi}_i$, or the neighboring location $\hat{\psi}_j$, we select the neighboring location $\hat{\psi}_j$, as it does not require us to compute gradients through the forward or inverse projections $\phi(\cdot)$ and $\phi^{-1}(\cdot)$, respectively. This projected rotation $\tilde{\psi}_i$ represents the value $\hat{\psi}_i$ should hold, relative to the current predicted rotation $\hat{\psi}_j$. It should be noted that $\psi(q) \neq \psi(-q)$, while q and $-q$ represent the same rotation. In terms of the projective space, this means that the sign of $\tilde{q}_i$ matters. To remove this ambiguity, we select the nearest projection to $\hat{\psi}_i$ in the projective MRP space. It should be noted that this is different from selecting the closer antipode on $\mathbb{S}^3$, as the large deformations found near the south pole[1] can cause the nearer antipode in $\mathbf{S}^3$ to be further in MRP space. In contrast, if we were to select a consistent sign for the scalar component $\tilde{q}_i$, for example ensuring the scalar component is always positive, a small change in $\hat{\psi}_j$ can cause large changes in $\tilde{\psi}_i$. While this change is required to stabilize our optimization, it does add some ambiguity to the direction of optimization. However, the directions to each of the projected locations, $\psi(\tilde{q}_i)$ and $\psi(-\tilde{q}_i)$, are only anti-parallel (pulling in exactly opposite directions) when $\tilde{\psi}_i - \hat{\psi}_i$ intersects the origin.

The loss with respect to a given estimate, $\hat{\psi}_i$, can then be written as the l_2 distance between its current value and the projected relative location, $\tilde{\psi}_i$, relative to a given neighbor, $\hat{\psi}_j$:

$$\mathcal{L}_{\Psi+} = \left\| \hat{\psi}_i - \phi(\tilde{q}_i) \right\|^2 \quad (3a) \quad \mathcal{L}_{\Psi-} = \left\| \hat{\psi}_i - \phi(-\tilde{q}_i) \right\|^2 \quad (3b) \quad \mathcal{L}_{\Psi} = \min(\mathcal{L}_{\Psi-}, \mathcal{L}_{\Psi+}) \quad (3c)$$

where we recall that, $\tilde{q}_i = q_i^j \otimes \hat{q}_j$, and $\hat{q}_j = \phi^{-1}(\hat{\psi}_j)$.

Note that, while $\hat{\psi}_j$ is a predicted value, we do not pass gradients through it, allowing it to anchor the update to a consistent orientation. The gradient update[2] is then given by:

$$\nabla_{\hat{\psi}_i} \mathcal{L}_{\Psi} = \psi_\Delta = \begin{cases} \hat{\psi}_i - \phi\left(\tilde{q}_i\right), & \text{if } \mathcal{L}_{\Psi+} < \mathcal{L}_{\Psi-} \\ \hat{\psi}_i - \phi\left(-\tilde{q}_i\right), & \text{otherwise} \end{cases} \quad (4)$$

Additionally, a maximum gradient step, η, in the projective space is imposed, $\psi_\Delta \leftarrow \eta \frac{\psi_\Delta}{\|\psi_\Delta\|}$, if the gradient exceeds a defined amount.This prevents extremely large steps from being taken, as the projective transform can distort the space.

6 Experiments

Next, we perform experiments to show that our method converges faster and more consistently than the alternative approaches. Our empirical results are grouped into two settings: (1) direct optimization of randomly generated rotations, Section 6.1, and (2) optimization of the parameters of a convolutional neural network using synthetically rendered images, Section 6.2. In both cases, relative orientations between elements in a neighborhood are provided. We show Iterative Modified Rodrigues Projective Averaging is able to converge faster and more often than alternative approaches. We further show in Section 6.2 that our method can easily be used to supervise convolutional neural networks, when only relative orientation information is available.

6.1 Direct Parameter Optimization

We evaluate the convergence behaviour of our Iterative Modified Rodrigues Projective Averaging method, **MRP (Ours)** , described in Section 5.1, as well as the $SO(3)$ averaging method, described in Section 4. For the $SO(3)$ averaging method, we implement both the pure Riemannian optimization , **SO(3)**, as well as a method using a Projective Manifold Gradient Layer [28] to map

---

[1]The south pole in this case is described by the quaternion $-1 + 0i + 0j + 0k$

[2]We omit a constant factor for brevity, and integrate it into the learning rate, γ.

Figure 2: Relative rotation consensus with direct optimization of rotation parameters over 50 unique environments with 100 random generated orientations each (**left**) and Alamo 1DSfM [36] (**right**). Median average-pair-wise angular error ($^\circ$) between each estimated rotations is shown, with shaded region representing the first and third quartile for each method. The max average-pair-wise angular error for each algorithm at each iteration is shown as a dashed line.

| | *Avg Pairwise Angular Error* $< 5^\circ$ | | | *Normalized AUC* | | |
Algorithm	Mean Steps	Max Steps	Min Steps	Mean	Max	Min
$SO(3)$	157.7K	Not Converged	85.0K	24.47	82.92	7.55
4D PMG [28]	126.1K	Not Converged	27.0K	15.67	52.40	3.06
6D PMG [21]	235.9K	Not Converged	80.0K	43.53	89.15	11.34
9D PMG [22]	284.5K	Not Converged	150.0K	62.94	101.77	17.77
Quaternion	160.3K	Not Converged	40.0K	23.55	84.85	3.47
MRP (Ours)	**37.5K**	**160.0K**	**15.0K**	**5.08**	**15.56**	**2.18**

Table 1: Number of iteration steps until convergence and Normalized Area Under Curve (nAUC) over 50 unique environments of 100 randomly generated orientations. 300K optimization steps are taken for each experiment.

the Riemannian gradient of the $SO(3)$ averaging loss, Equation 2a, to a Euclidean optimization in $\mathbb{R}^D$, where we test $D = 4$, $D = 6$ [21], and $D = 9$ [22], **4D PMG [28]**, **6D PMG [21]**, **9D PMG [22]**, respectively. Additionally, we evaluate direct quaternion optimization, described in Sections 4, **Quaternion**.

Uniformly Sampled Rotations. We test the performance of each algorithm when directly optimizing the rotation parameters of a set of size $N = 100$ with known relative rotations R_i^j, and local neighborhood structure. Ground truth and initial estimated rotations are both randomly sampled from a uniform distribution in $SO(3)$. Each rotation, R_i, has a neighborhood, $\mathcal{N}_i$, consisting of the closest $|\mathcal{N}_i| = 3$ rotations with respect to geodesic distance. The connectivity of this neighborhood graph is checked to ensure the graph contains only a single connected component. We test all algorithms over 50 sets of unique environments, each with $N = 100$ randomly generated orientations as described above. The estimated rotations are updated by each algorithm in batches of size 8, for 300K iterations.

As the goal of our algorithm is to improve the convergence properties of iterative averaging methods, we analyze each algorithm at various stages of optimization. We are particularly interested in the average number of update steps until the algorithm has converged, which we define as when the average angular error between all pairs of rotations is below 5°. As we can see in Figure 2, the Iterative Modified Rodrigues Projective Averaging method, **MRP (Ours)**, converges before the standard $SO(3)$ averaging method. On average, our method converged to within 5° in 37K steps. The next best method, **4D PMG [28]**, which takes over three times as many iterations to converge to the same level of accuracy. Further, Table 1 shows that our method is the only one to converge across all environments within 300K iterations. For each method, we also compute the mean area under the pairwise error curve, with the number of steps normalized to between zero and one (nAUC), also shown in Table 1. We find that in the best, average, and worst case scenarios, our method has the best convergence behavior. We find that at each stage of training, the Iterative Modified Rodrigues Pro-

| | % Avg Pairwise Angular Error $< 5°$ | | | | | Final Error($°$) | |
Algorithm	30K	70K	100K	150K	300K	Mean	Median
$SO(3)$	0%	0%	6%	57%	94%	2.056	0.10
4D PMG [28]	2%	32%	46%	72%	90%	1.969	0.14
6D PMG [21]	0%	0%	4%	20%	52%	20.096	3.20
9D PMG [22]	0%	0%	0%	2%	20%	40.125	43.02
Quaternion	0%	12%	30%	56%	82%	9.72	0.04
MRP (Ours)	**66%**	**88%**	**96%**	**98%**	**100%**	**0.004**	**0.004**

Table 2: Percentage of experiments converged and final angular errors over 50 unique environments of 100 randomly generated orientations. 300K optimization steps are taken for each experiment.

| | Mean Relative Error ($°$) | | Mean Absolute Error ($°$) | | Mean nAUC | |
Algorithm	E. Island	Alamo	E. Island	Alamo	E. Island	Alamo
4D PGM [28]	11.94	15.00	7.34	9.94	25.60	47.20
6D PGM [21]	11.26	18.84	6.90	13.09	27.77	58.04
9D PGM [22]	10.22	16.32	6.32	11.43	29.31	60.14
Quaternion	11.58	13.40	7.23	8.93	**16.01**	**22.57**
MRP (Ours)	**8.84**	**9.89**	**5.49**	**6.56**	16.21	25.61

Table 3: Final results on 1DSfM [36] datasets after 20K iterations

jective Averaging, **MRP (Ours)**, training has both a lower average pairwise error, shown in Table 2. Our method converged far more often at each stage of training, also shown in Table 2.

Structure from Motion Dataset. To test our algorithms under natural noise conditions, we also evaluate our algorithm on the 1DSfM [36] structure from motions datasets. These datasets contain full transforms for each sample; however, we are only concerned with optimizing the rotations. Each environment is tested with 5 random initializations and the estimated rotations are updated by each algorithm in batches of size 64, for 20K iterations. The results of a subset of the environments are shown in Table 3 and the remainder can be found in the supplement. The noise characteristics of relative rotations in this dataset are similar to those found when capturing relative poses, but, unlike the environments found in the previous section (Uniformly Sampled Rotations), the distribution of rotations does not fully cover the orientation space. As a result, all methods converge relatively quickly. Our algorithm outperforms the baselines in terms of accuracy. While the **Quaternion** optimization converges slightly faster, it consistently finds a lower accuracy configuration, resulting in a low nAUC, but higher relative and absolute accuracy. More details can be found in the supplemental.

6.2 Neural Network Optimization

To show that the Iterative Modified Rodrigues Projective Averaging method, **MRP (Ours)**, can be used to learn orientation using neural networks by optimizing the parameters of a simple CNN, specifically a ResNet18 [37], we follow the procedure as in Section 6.1 with some minor changes. Instead of operating directly on a set of rotation parameters, we learn a function $\hat{\psi}_i = f(I_i)$ from rendered images of the YCB drill [1] model, shown in Figure 3, rendered at each of 100 random orientations R_i. We continue to only supervise each method described in Section 6.1 using the relative rotations between each image. We compare the best performing methods, and, as a lower bound, we also train an oracle network, **Oracle**, with the ground truth rotations, R_i and cosine

Algorithm	Mean Error ($°$)	Median Error ($°$)	$5°$ Acc (%)
4D PMG [28]	123.84	123.96	0
Quaternion	28.83	21.74	50
MRP (Ours)	**3.71**	**3.73**	**100**
Oracle	1.58	1.56	100

Table 4: Final results for image based rotation estimation.

Figure 3: Estimated rotation frame learned for the YCB [1] drill model using Iterative Modified Rodrigues Projective Averaging and relative rotations (x, y, z) (left). Results for rotations estimated by neural networks given images of the YCB drill [1] rendered at each of 100 random rotations with various supervisions, (right). Median average-pairwise angular error (°) is shown with shaded areas representing the first and third quartile over all training sessions. The max average-pairwise angular error for each algorithm at each iteration is shown as a dashed line.

quaternion loss. We use the Adam [38] optimizer, batch size of 32 and learning rate of 1×10^{-4} for all experiments, and with a maximum training time of 10K steps, trained over 8 environments, each with 100 images associated with randomly generated rotations. We find that **MRP (Ours)** is able to converge to a rotational frame consistent with the relative rotations used for supervision relatively quickly, with a significantly lower average-pairwise-error than all other relative methods, shown in Figure 3 and Table 4.

We also perform experiments on generalization to unseen poses and find that a curriculum is required (see supplement for details). For the generalization experiments, we found the **MRP (Ours)** achieves an mean pairwise angular error or $5.19°$, **Quaternion** achieves $12.41°$, and **4D PMG [28]** never converged, with final error of $125.09°$.

7 Limitations

While this parameterization of the rotational space is valuable for learning rotations using only relative supervision, it is not without limitations. One of the primary ones is the need for a curriculum for generalizability to unseen relative rotations. Without this, our experiment show that all representations fall into the local optima of outputting a constant orientation. Additionally, in generalization experiments, we are only able to achieve a final error of 5 degrees. This may not be accurate enough for many fine motor tasks, though an additional refinement network that is trained to handle rotations within a sub-region of the whole rotation space could reduce this error.

8 Conclusion

In this paper, we show that through the use of Modified Rodrigues Parameters, we are able to open the closed manifold of $SO(3)$, improving the convergence behavior of the rotation averaging problem. We show that Iterative Modified Rodrigues Projective Averaging is able to outperform the naive application of relative-orientation supervision in both direct parameter optimization and image-based rotations estimation from neural networks. We hope our method allows more systems to convert the relative supervision of relative methods, like ICP, to consistent and accurate absolute poses.

References

[1] Y. Xiang, T. Schmidt, V. Narayanan, and D. Fox. Posecnn: A convolutional neural network for 6d object pose estimation in cluttered scenes. 2018.

[2] Y. Labbé, J. Carpentier, M. Aubry, and J. Sivic. Cosypose: Consistent multi-view multi-object 6d pose estimation. In *European Conference on Computer Vision*, pages 574–591. Springer, 2020.

[3] C. Wang, D. Xu, Y. Zhu, R. Martín-Martín, C. Lu, L. Fei-Fei, and S. Savarese. Densefusion: 6d object pose estimation by iterative dense fusion. 2019.

[4] Q.-Y. Zhou, J. Park, and V. Koltun. Fast global registration. In *European conference on computer vision*, pages 766–782. Springer, 2016.

[5] L. Manuelli, W. Gao, P. Florence, and R. Tedrake. kpam: Keypoint affordances for category-level robotic manipulation. *International Symposium on Robotics Research (ISRR) 2019*, 2019.

[6] X. Sun, B. Xiao, F. Wei, S. Liang, and Y. Wei. Integral human pose regression. In *ECCV*, 2018.

[7] S. Suwajanakorn, N. Snavely, J. Tompson, and M. Norouzi. Discovery of latent 3d keypoints via end-to-end geometric reasoning. In *NeurIPS*, 2018.

[8] R. Hartley, J. Trumpf, Y. Dai, and H. Li. Rotation averaging. *International journal of computer vision*, 103(3):267–305, 2013.

[9] F. Dellaert, D. M. Rosen, J. Wu, R. Mahony, and L. Carlone. Shonan rotation averaging: Global optimality by surfing $so(p)^n$. In *European Conference on Computer Vision*, pages 292–308. Springer, 2020.

[10] L. Wang and A. Singer. Exact and stable recovery of rotations for robust synchronization. *Information and Inference: A Journal of the IMA*, 2(2):145–193, 2013.

[11] M. H. DeGroot. Reaching a consensus. *Journal of the American Statistical Association*, 69 (345):118–121, 1974.

[12] S. Chatterjee and E. Seneta. Towards consensus: Some convergence theorems on repeated averaging. *Journal of Applied Probability*, 14(1):89–97, 1977.

[13] A. Olshevsky and J. N. Tsitsiklis. Convergence speed in distributed consensus and averaging. *SIAM journal on control and optimization*, 48(1):33–55, 2009.

[14] W. J. Russell, D. J. Klein, and J. P. Hespanha. Optimal estimation on the graph cycle space. *IEEE Transactions on Signal Processing*, 59(6):2834–2846, 2011.

[15] A. Beck and S. Sabach. Weiszfeld's method: Old and new results. *Journal of Optimization Theory and Applications*, 164(1):1–40, 2015.

[16] R. Hartley, K. Aftab, and J. Trumpf. L1 rotation averaging using the weiszfeld algorithm. In *CVPR 2011*, pages 3041–3048. IEEE, 2011.

[17] A. Kendall, M. Grimes, and R. Cipolla. Posenet: A convolutional network for real-time 6-dof camera relocalization. In *Proceedings of the IEEE international conference on computer vision*, pages 2938–2946, 2015.

[18] A. Kendall and R. Cipolla. Geometric loss functions for camera pose regression with deep learning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 5974–5983, 2017.

[19] T.-T. Do, M. Cai, T. Pham, and I. Reid. Deep-6dpose: Recovering 6d object pose from a single rgb image. *arXiv preprint arXiv:1802.10367*, 2018.

[20] H. Su, C. R. Qi, Y. Li, and L. J. Guibas. Render for cnn: Viewpoint estimation in images using cnns trained with rendered 3d model views. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2686–2694, 2015.

[21] Y. Zhou, C. Barnes, J. Lu, J. Yang, and H. Li. On the continuity of rotation representations in neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5745–5753, 2019.

[22] J. Levinson, C. Esteves, K. Chen, N. Snavely, A. Kanazawa, A. Rostamizadeh, and A. Maka-dia. An analysis of svd for deep rotation estimation. *arXiv preprint arXiv:2006.14616*, 2020.

[23] V. Peretroukhin, M. Giamou, D. M. Rosen, W. N. Greene, N. Roy, and J. Kelly. A smooth representation of belief over so(3) for deep rotation learning with uncertainty. *In Proceedings of Robotics: Science and Systems (RSS'20)*, 2020.

[24] G. Terzakis, M. Lourakis, and D. Ait-Boudaoud. Modified rodrigues parameters: an efficient representation of orientation in 3d vision and graphics. *Journal of Mathematical Imaging and Vision*, 60(3):422–442, 2018.

[25] J. Crassidis and F. Markley. Attitude estimation using modified rodrigues parameters. In *Flight Mechanics/Estimation Theory Symposium*, pages 71–86. NASA, 1996.

[26] Y. Li, G. Wang, X. Ji, Y. Xiang, and D. Fox. Deepim: Deep iterative matching for 6d pose estimation. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 683–698, 2018.

[27] B. Wen, C. Mitash, B. Ren, and K. E. Bekris. se (3)-tracknet: Data-driven 6d pose tracking by calibrating image residuals in synthetic domains. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 10367–10373. IEEE, 2020.

[28] J. Chen, Y. Yin, T. Birdal, B. Chen, L. Guibas, and H. Wang. Projective manifold gradient layer for deep rotation regression. *arXiv preprint arXiv:2110.11657*, 2021.

[29] Z. Teed and J. Deng. Tangent space backpropagation for 3d transformation groups. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10338–10347, 2021.

[30] R. Brégier. Deep regression on manifolds: a 3d rotation case study. *arXiv preprint arXiv:2103.16317*, 2021.

[31] R. Arora. On learning rotations. *Advances in neural information processing systems*, 22:55–63, 2009.

[32] S. Bonnabel. Stochastic gradient descent on riemannian manifolds. *IEEE Transactions on Automatic Control*, 58(9):2217–2229, 2013.

[33] S. Mahendran, H. Ali, and R. Vidal. 3d pose regression using convolutional neural networks. In *Proceedings of the IEEE International Conference on Computer Vision Workshops*, pages 2174–2182, 2017.

[34] J. H. Manton. A globally convergent numerical algorithm for computing the centre of mass on compact lie groups. In *ICARCV 2004 8th Control, Automation, Robotics and Vision Conference, 2004.*, volume 3, pages 2211–2216. IEEE, 2004.

[35] T. F. Wiener. *Theoretical analysis of gimballess inertial reference equipment using delta-modulated instruments*. PhD thesis, Massachusetts Institute of Technology, 1962.

[36] K. Wilson and N. Snavely. Robust global translations with 1dsfm. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2014.

[37] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[38] D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.