ATTACKING DEEP NETWORKS WITH SURROGATE-BASED ADVERSARIAL BLACK-BOX METHODS IS EASY

ABSTRACT

A recent branch of the black-box adversarial attack literature has recognised the benefits of incorporating both the surrogate gradient information usually associated with transfer-based methods and the flexible query-based numerical optimisation typical of score-based methods. However, we find that existing approaches of this type underperform their potential, and can be overly complicated besides. Here, we provide a short and simple algorithm which achieves state-of-the-art results by attempting iterative ascent in the direction of the surrogate's loss gradient, and, only when that fails to proceed, sampling alternative search directions from the coimage of the surrogate's local linearisation, i.e. its Jacobian's row space. The former directions produce very low query counts, while the latter serve as a backup for the cases in which more direct transfer fails, delivering very low failure rates. Beyond the fact that this serves as a fast and practical attack when scores and surrogates are available, our experiments demonstrate the empirical correctness of the method's assumption that the studied networks are in an important sense learning similar functions to one another, making the attack problem under this threat model easy.

1 INTRODUCTION

The paper that introduced adversarial examples in computer vision (Szegedy et al., 2014) also initiated the study of their transfer across models. Accordingly, the first papers to propose black-box attacks (Papernot et al., 2017; Liu et al., 2017) did so within a transfer-based framework, typically using a simple "fast-gradient" optimisation with gradients supplied by a surrogate model. This allowed them to assume nothing about the attacked models except their input and output domains and, of course, that they would return the top predicted class for a given input image. This stood in contrast to white-box (or "first-order oracle") approaches, e.g. Goodfellow et al. (2014); Moosavi-Dezfooli et al. (2016); Carlini & Wagner (2017), which assumed full knowledge of the victim model (notably its gradients) while typically seeking to minimise the norm of the adversary and/or the compute time spent finding it. The transfer-based black-box methods instead assumed comparable knowledge of the surrogate, whether provided directly, trained on a similar data distribution, or constructed iteratively by matching the observed behaviour of the victim over repeated queries to it. While these methods demonstrated that some amount of transfer between different networks was feasible, the field widely acknowledged that they fell short of reliable success, and sought alternatives.

Chen et al. (2017) and Bhagoji et al. (2018) introduced a modification of the threat model: they assumed the victim to provide not only the top class prediction, but also the scores/confidences of the candidate classes. This relaxation allowed for doing away with the need to acquire or construct surrogates of the victim, instead using numerical query-based methods to estimate the victim's gradients directly. These approaches and their many descendants are called "score-based" attacks, operating within the "zeroth-order oracle" setting. The common problem they all face, noted in the seminal works above, is that direct numerical estimation of gradients is linear in the dimension of the input space. Depending on the input image resolution, this ranges from being costly to being infeasible. Thus, a core issue in score-based attacks is the need to limit the query count without compromising the quality of the gradient estimate: in Chen et al. (2017) alone, proposals included coordinate descent, basis transformation, coarse-to-fine optimisation, and priors on the gradient. The line of work which followed (Ilyas et al., 2018; 2019; Li et al., 2019; Liu et al., 2020; Guo et al., 2019b; Tu et al., 2019) explored ways to improve the fundamental approach by experimenting with different

Figure 1: Transfer of information from a surrogate to a target in GFCS: Gradient First, Coimage Second. A sequence of optimisation steps is taken through the loss landscape of the target model, as shown on the right. Each candidate direction $\mathbf{q}$ is supplied by the surrogate in one of two ways: either through direct transfer of the surrogate's own gradient $\mathbf{q}_{\mathrm{sur}}$, or as a $\mathbf{q}_{\mathrm{co}}$ generated through a process of coimage sampling described in Sec. 3.2. $\mathbf{q}_{\mathrm{true}}$ is the target's true but inaccessible gradient. As shown in Sec. 4.2, the method relies mostly on the directly transferred $\mathbf{q}_{\mathrm{sur}}$s, using the $\mathbf{q}_{\mathrm{co}}$s to avoid failure.

optimisation methods and priors. Strikingly, and perhaps surprisingly, one of the most successful efforts was SimBA (Guo et al., 2019a), for "Simple Black-Box Attack". Its name derives from the fact that it is an especially basic form of coordinate descent which achieves competitive results despite its deliberately simple approach: the greedy sequential assignment of signs to fixed-length steps along orthogonal basis directions.

Though query-driven score-based black-box attacks were proposed as an alternative to transfer methods, the two approaches are not incompatible with one another. They are actually complementary: a query-based strategy can benefit from search directions that are more promising *a priori*, and a transfer-based strategy can benefit from flexible optimisation that allows it to dynamically correct approximation errors and consider alternative hypotheses. This was first suggested in contemporaneous works by Cheng et al. (2019) and Guo et al. (2019b), which were followed by Tashiro et al. (2020) and Yang et al. (2020). In this paper, we argue that the core intuition of this branch of literature is sound. However, we also argue that when combining transfer- and query-based approaches, it is crucial to recognise that the failure of surrogate gradient transfer is generally overestimated, even by approaches which leverage it. Transfer generally succeeds: it merely requires an occasional source of appropriately chosen alternative hypotheses in order to avoid optimisation failure. It is this core insight that enables us to propose a simple but powerful new algorithm which achieves state-of-the-art results against the most modern competing methods on this problem, under their own experimental setup of minimising the number of queries required to identify ℓ_2-norm-bounded adversarial perturbations. We call our approach "GFCS: Gradient First, Coimage Second".

Our approach is straightforward in both principle and implementation. Each iteration, it attempts up to two fixed-length steps along a given direction, as in Guo et al. (2019a). So long as it yields a successful update, this candidate direction is simply the normalised adversarial loss gradient of a surrogate model. If the method is unable to accept any step in this direction, it instead samples randomly weighted sums of surrogate class-score gradients until one such direction yields a successful update, at which point it reverts to using surrogate adversarial loss gradients as before. All of the "backup" direction proposals are thus drawn from the row space of the surrogate's Jacobian, which is called the "coimage" of the linearised surrogate. Intuitively, this represents the subspace of directions at the current point that the surrogate has any response to at all. As we demonstrate, GFCS is able to overwhelmingly rely on surrogate loss gradients, a fact which accounts for its extreme efficiency. The coimage search, on the other hand, plays a diversifying role which is necessary for achieving the method's high success rate, but without imposing an excessive cost. This is possible because its dimension is bounded above by that of the network's output space, and is thus generally drastically lower in dimension than the input image embedding space, e.g. 1000-D vs. 268203-D for the common ImageNet Inception-v3 implementation. Beyond the success of the attack in its own right, we note that existence of such a fast and effective attack which relies entirely on surrogate output gradients indicates that the studied networks are, in an important sense, very similar to one another.

2 RELATED WORK

Cheng et al. (2019) and Guo et al. (2019b) were the first to, in their words, "bridge the gap between the transfer-based attacks and the query-based ones" in the score-based black-box context, noting that earlier methods "often suffer from low attack success rates (in the transfer case) or poor query efficiency (in the query-based case) since it is non-trivial to estimate the gradient in a high-dimensional space with limited information". Guo et al. (2019b) did this by supplying a bandits optimiser (as used in Ilyas et al. (2019)) with surrogate gradient estimates at each iteration, diversifying the proposed search directions through the use of test-time dropout and drop-layer. Cheng et al. (2019) presented a variant of random gradient-free (RGF) optimisation using the surrogate gradient as a biasing prior (P-RGF) and featuring a dynamically estimated bias parameter, albeit one whose optimal value itself depends on the unknown target gradient. The Output-Diversified Sampling (ODS) approach of Tashiro et al. (2020) sampled gradients of randomly weighted logit sums over multiple surrogate models in order to generate search directions for variations on SimBA, RGF, and some Boundary Attack (Brendel et al., 2018) variants, demonstrating improvement over all of the base methods. Yang et al. (2020) also proposed a surrogate-enhanced version of SimBA ("SimBA++"), sampling candidate pixels to perturb according to the distribution specified by the corresponding magnitudes of the surrogate gradient components, as well as making periodic attempts to directly transfer surrogate gradients estimated using smoothing and momentum. When combined with "High Order Gradient Approximation", a method for dynamically updating the surrogate by matching the first- and zeroth-order victim model behaviour, it is dubbed "Learnable Black-Box Attack" (LeBA).

In addition to the above, we review relevant works on black-box attacks, particularly score-based methods that use (possibly learned) prior information and/or alternative optimisers. When they feature a relevant concept, we also include variations of the Boundary Attack method of Brendel et al. (2018), which avoid requiring scores in exchange for much higher query counts:

Frequency/scale priors: As noted by (Chen et al., 2017; Bhagoji et al., 2018), in order to be practical, any black-box method that relies on gradient estimation must have an approach to effectively reduce the intrinsic dimension of the estimate space. Guo et al. (2019a; 2020) use low-frequency DCT dimensions for this purpose. The Boundary Attack variant of Brunner et al. (2019) uses Perlin noise similarly, and the Gaussian smoothing of the gradient in Yang et al. (2020) is conceptually related. Also closely related to the low-frequency prior is the use of spatial downsampling, whether applied to the image or its gradient, and whether implemented through pooling, interpolation, or striding: Tu et al. (2019); Ilyas et al. (2019); Li et al. (2019); Wang et al. (2021) all involve a version of it. Coarse-to-fine approaches, in which results at a coarser scale either solve the problem or initialise the optimiser of a finer one, appear in Moon et al. (2019); Al-Dujaili & O'Reilly (2020).

Data distribution modelling: Li et al. (2019) assumes the ability to parametrically model an adversarial distribution in the vicinity of the input point. Dolatabadi et al. (2020) replaces this parametric model with a normalising flow model trained on clean data. Tu et al. (2019) represents the data using an autoencoder and conducts the attack in its latent space. Huang & Zhang (2020) likewise conducts a latent-space attack, but in that of an encoder-decoder network trained to output adversaries on a source network.

Attention: Wang et al. (2021) uses the output of CAM (Zhou et al., 2016) on a proxy net as a map of pixels to attack. In Brunner et al. (2019), a similar map is derived from the difference between the adversarial and original images, and used to weight the sampled perturbation elementwise.

Gradient/feature priors: The use of gradient priors in Guo et al. (2019b); Cheng et al. (2019); Tashiro et al. (2020); Yang et al. (2020) is discussed above, and the transfer-based approaches Papernot et al. (2017); Liu et al. (2017) are of course fundamentally based on this. Besides these, the method of Brunner et al. (2019) uses the gradient of a surrogate model to bias the orthogonal perturbation used in Boundary Attack, stating, "even surrogate models that are too weak for direct transfer attacks can be used in our framework". Yan et al. (2021), also a Boundary Attack variant, attempts to learn to mimic the gradients of a victim net using a customised pre-trained policy network. Huang & Zhang (2020) learns a latent space of transferable adversarial features from its surrogate. Andriushchenko et al. (2020) supplies a bespoke feature bank which essentially transfers empirical domain knowledge (i.e. features determined to be likely to fool CNNs), both in the initialisation (vertical stripes) and the feature choice (homogeneous squares in the ℓ_∞ case, pairs of opposite-signed "decaying peaks" in the ℓ_2). Sahu et al. (2020) attempts to perform a "black-box FGSM" by learning correlations between

components of the loss function gradient within a Gaussian Markov random field framework. The "gradient priors" of Ilyas et al. (2019) essentially amount to momentum and downsampling, and do not represent the sort of "flexible gradient transfer" we are otherwise discussing here.

Optimisation algorithms: As explained previously, a standard optimisation framework for black-box score-based attacks is ascent on gradients estimated via numerical derivatives in guessed directions, possibly guided by priors and/or using enhancements or simplifications such as coordinate ascent. We consider the aforementioned SimBA variants (including the method we present) to essentially be of this type. Variations on or alternatives to this approach have included bandits (Ilyas et al., 2019; Guo et al., 2019b), Natural Evolution Strategies (NES) (Li et al., 2019; Huang & Zhang, 2020; Dolatabadi et al., 2020) evolutionary algorithms (Liu et al., 2020; Wang et al., 2021), and training of a policy network by REINFORCE (Yan et al., 2021). Al-Dujaili & O'Reilly (2020) uses a custom "flip/revert" approach based on checking the overall effect of grouped sign changes to pixel perturbations. By assuming submodularity, Moon et al. (2019) uses the max-heap-based "local search algorithm" to alternate between greedily inserting and removing elements defining a partition between positively and negatively signed perturbation pixels. Shi et al. (2019) comprises a set of optimisation heuristics meant to reduce the norms of attacks based on transfer from surrogate models: many of these are in principle applicable to attack vectors obtained otherwise.

3 METHOD

3.1 PRELIMINARIES

The adversarial attack problem appears in slightly different variations. Generally, given a classifier function $\mathbf{f}(\mathbf{x}) \colon \mathcal{X} \to \mathcal{Y}$, the goal is to supply an adversarial example $\mathbf{x}_{\text{adv}} \in \mathcal{X}$ which, while "near" to a given $\mathbf{x}_{\text{in}}$ under some definition, is such that $\mathbf{f}(\mathbf{x}_{\text{adv}})$ differs from $\mathbf{f}(\mathbf{x}_{\text{in}})$ in a particular noteworthy way. In image classification, we typically have the situation that $\mathcal{X} = \mathcal{R}^D$ and $\mathcal{Y} = \mathcal{R}^C$, with $\mathbf{f}$ a network mapping a D-dimensional input image to a C-dimensional class-score/logit vector. The untargeted attack objective, then, is $\text{argmax}_c \, \mathbf{f}_c(\mathbf{x}_{\text{adv}}) \neq \text{argmax}_c \, \mathbf{f}_c(\mathbf{x}_{\text{in}})$, i.e. that the top predicted class of $\mathbf{x}_{\text{adv}}$ is different from that of $\mathbf{x}_{\text{in}}$. The targeted attack objective is $\text{argmax}_c \, \mathbf{f}_c(\mathbf{x}_{\text{adv}}) = t$, meaning that the net predicts a specific target class t other than the original prediction $\text{argmax}_c \, \mathbf{f}_c(\mathbf{x}_{\text{in}})$.

As the subfield has expanded to consider perturbation classes including non-rigid deformation (Xiao et al., 2018), semantically insignificant distortion (Hosseini & Poovendran, 2018; Brown et al., 2018), and movement within the estimated natural image manifold (Zhao et al., 2018; Hendrycks et al., 2021), corresponding definitions of adversarial perturbation magnitude have been adopted, including total variation and manual human assessment. The most common measure, used by all methods to be compared against in this paper, is $\|\mathbf{x}_{\text{in}} - \mathbf{x}_{\text{adv}}\|_p$, with $p \in \{2, \infty\}$: here, we use $p = 2$.

In some experimental setups, the attacker's goal is to satisfy the adversarial objective while minimising the perturbation magnitude. In others, it is to minimise the number of network evaluations performed while finding any adversarial example with a perturbation magnitude within a pre-specified bound. In black-box attacks, the latter setup is common, with "evaluations" being defined as queries to the victim model: this is likewise our focus.

3.2 ALGORITHM

The entirety of the proposed method is given in pseudocode as Algorithm 1. As indicated in Sec. 3.1, the method takes a victim classifier $\mathbf{v}$, an input image $\mathbf{x}_{\text{in}}$, and a norm bound ν. The projection operator $\Pi_{\mathbf{x}_{\text{in}}, \nu}$ confines its input to the ν-ball centred on $\mathbf{x}_{\text{in}}$: its inclusion in the algorithm represents a standard projected gradient ascent (PGA) implementation. Additionally, the method requires a loss function L, a set $\mathcal{S}$ of one or more surrogate models, and a step length ϵ representing the fixed length of the perturbations to be attempted at each iterate[1] along its candidate direction. The loss L can be any function of the iterate that serves as a suitable proxy for the adversarial objective, as in Sec. 3.1: the only requirement here is that it be once differentiable. In our implementation, we make the popular and effective choice of the margin loss $L_{\mathbf{f}}(\mathbf{x}) = \mathbf{f}_{c_t}(\mathbf{x}) - \mathbf{f}_{c_s}(\mathbf{x})$ where $c_s = \text{argmax}_c \, \mathbf{v}_c(\mathbf{x})$ and $c_t = \text{argmax}_{c \neq c_s} \, \mathbf{v}_c(\mathbf{x})$, i.e. the difference between the highest and second-highest (or, in the targeted case, the target) class scores. Note that the class IDs c_t and c_s are defined by the ranking

---

[1] In optimisation, this term refers to any given intermediate value of the variable being optimised.

Algorithm 1 GFCS: Gradient First, Coimage Second

1: **Input:** A targeted image $\mathbf{x}_{\text{in}}$, loss function L, a victim classifier $\mathbf{v}$, a set of surrogate models $\mathcal{S}$, a step length ϵ, and a norm bound ν.
2: **Output:** adversarial image $\mathbf{x}_{\text{adv}}$ within distance ν of $\mathbf{x}_{\text{in}}$
3: $\mathbf{x}_{\text{adv}} \leftarrow \mathbf{x}_{\text{in}}$
4: $\mathcal{S}_{\text{rem}} \leftarrow \mathcal{S}$
5: **while** $\mathbf{x}_{\text{adv}}$ is not adversary **do**
6:     **if** $\mathcal{S}_{\text{rem}} \neq \emptyset$ **then**
7:         Randomly sample surrogate model $\mathbf{s}$ from $\mathcal{S}_{\text{rem}}$
8:         $\mathcal{S}_{\text{rem}} \leftarrow \mathcal{S}_{\text{rem}} \setminus \mathbf{s}$
9:         $\mathbf{q} \leftarrow \frac{\nabla_{\mathbf{x}} L_{\mathbf{s}}(\mathbf{x}_{\text{adv}})}{\|\nabla_{\mathbf{x}} L_{\mathbf{s}}(\mathbf{x}_{\text{adv}})\|_2}$
10:     **else**   ▷ None of the surrogate loss gradients work, so revert to ODS.
11:         Randomly sample surrogate model $\mathbf{s}$ from $\mathcal{S}$
12:         Sample $\mathbf{w} \sim U(-1, 1)^C$
13:         $\mathbf{q} \leftarrow \mathbf{d}_{\text{ODS}}(\mathbf{x}_{\text{adv}}, \mathbf{s}, \mathbf{w})$ ▷ See Eqn. 1 for definition.
14:     **for** $\alpha \in \{\epsilon, -\epsilon\}$ **do**
15:         **if** $L_{\mathbf{v}}(\Pi_{\mathbf{x}_{\text{in}}, \nu}(\mathbf{x}_{\text{adv}} + \alpha \cdot \mathbf{q})) > L_{\mathbf{v}}(\mathbf{x}_{\text{adv}})$ **then**
16:             $\mathbf{x}_{\text{adv}} \leftarrow \Pi_{\mathbf{x}_{\text{in}}, \nu}(\mathbf{x}_{\text{adv}} + \alpha \cdot \mathbf{q})$
17:             $\mathcal{S}_{\text{rem}} \leftarrow \mathcal{S}$ ▷ Reset candidate surrogate set to input set; resume using loss gradients.
18:             **break**

---

according to $\mathbf{v}$, but are evaluated on the net $\mathbf{f}$ parametrising the loss, which is either $\mathbf{s}$ or $\mathbf{v}$ depending on the line of the algorithm (9 and 15, respectively). The natural assumption of a surrogate method is that the surrogate will provide useful information about the victim, but there is no "hard" requirement on the surrogates $\mathbf{s} \in \mathcal{S}$ other than being once-differentiable functions mapping $\mathcal{X} \to \mathcal{Y}$. The definition of ODS direction $\mathbf{d}_{\text{ODS}}$ for network $\mathbf{f}$ and input $\mathbf{x}$ is, as in Tashiro et al. (2020),

$$\mathbf{d}_{\text{ODS}}(\mathbf{x}, \mathbf{f}, \mathbf{w}) = \frac{\nabla_{\mathbf{x}}(\mathbf{w}^\mathsf{T} \mathbf{f}(\mathbf{x}))}{\|\nabla_{\mathbf{x}}(\mathbf{w}^\mathsf{T} \mathbf{f}(\mathbf{x}))\|_2}, \tag{1}$$

where $\mathbf{w}$ is sampled from the uniform distribution over $[-1, 1]^C$. By definition, it is the normalised gradient of a randomly weighted sum of all of the class scores. Equivalently, by linearity, it is a randomly weighted sum of all of the class-score gradients (i.e. rows of the Jacobian matrix), which are themselves a basis of the coimage of the linear approximation of $\mathbf{f}$: the subspace which $\mathbf{f}$ exhibits any nonzero response to.

As covered in Sec. 1, the logic of the method is simple. At any given iterate, the method tries to proceed in a SimBA-like manner by testing the change in adversarial loss at fixed-length steps along candidate directions, projected back into the feasible set where necessary. It does so exclusively using normalised loss gradients from the surrogates in the input set (drawn in random order, without replacement), unless and until it has exhausted them at that iterate without success'. As we will demonstrate in Sec. 4.2, this intermediate failure state is seldom reached. If this state is reached, however, the method instead randomly samples a surrogate (with replacement) and an ODS direction on that surrogate, attempting a SimBA update each time, until an improvement in the loss is realised. Once such a successful update occurs, the method refreshes the working set of surrogates and resumes using normalised loss gradients only. The method terminates on finding an adversarial example or on exceeding an upper bound on the query count if one has been specified.

4 EXPERIMENTS

4.1 UNTARGETED ATTACKS

Experimental setup: We compare GFCS to the methods of Cheng et al. (2019); Tashiro et al. (2020); Yang et al. (2020) by designing an experimental framework covering the key aspects of the original experiments in the respective source works. We use each method to perform ℓ_2-norm-constrained untargeted attacks against the same 2000 randomly chosen correctly classified ILSVRC2012 validation images per victim network. A maximum query count of 10000 is set per example (beyond which

Figure 2: CDFs representing the number of successfully attacked examples at different query counts when performing *untargeted* black-box attacks on VGG-16, ResNet-50, and Inception-v3 networks, with one or four surrogates.

failure is declared), and the ℓ_2 bound (enforced using PGA) is set to the commonly chosen $\sqrt{0.001D}$, where D is the image dimension in the victim network's native input resolution. The victim networks are the commonly chosen VGG-16 (with batch norm), ResNet-50, and Inception-v3. The experiments are repeated for each of two choices of surrogate set: ResNet-152 alone (as in Cheng et al. (2019); Yang et al. (2020)), and the set {VGG-19, ResNet-34, DenseNet-121, MobileNet-v2}, as in Tashiro et al. (2020). The latter is omitted for LeBA (Yang et al., 2020), which does not admit non-singleton surrogate sets. All networks used are pretrained models available via PyTorch/torchvision. Parameter values of competitors are as they specify except where we note otherwise for reasons that will be discussed below. LeBA is run in "train" mode on a held-out set of 1000 images and then evaluated in "test" mode on the same set of 2000 used for all other methods. P-RGF always uses the adaptive coefficient mode. P-RGF and ODS-RGF are based on our own PyTorch port of the reference P-RGF code, the source code for which will be released along with this paper. Note that no public implementation of ODS-RGF exists otherwise as of this writing.

Results: Table 1 reports attack success rates and median query counts, and Fig. 2 plots cumulative success counts against the maximum queries spent per example (CDFs, modulo normalisation). We do not report means, as these are inappropriate for summarising the long-tailed distributions resulting from these methods. Uncertainty is represented as standard error in Table 1 and by 95% confidence intervals in Fig. 2, in both cases having been obtained via bootstrap sampling. Two things are readily apparent in Table 1. First, *all* of the studied methods have very high success rates on this problem, against all of the victim networks: the lowest rate observed is 98.50% for SimBA-ODS on Inception-v3 with ResNet-152 as the lone surrogate. Second, GFCS incurs an *extremely* low median query count while achieving a similarly high success rate to all other methods. This fact can be seen in more detail in the single-surrogate results of Figs. 2a, 2b, and 2c, in which GFCS clearly dominates the low-query regime, and even more strikingly so in the multi-surrogate Figs. 2d, 2e, and 2f. This is despite GFCS's simplicity: compare Alg. 1 against, for example, LeBA's training of its surrogate in a separate step. Note that our choice of SimBA-ODS as the coimage sampler is partly about simplicity: as the results demonstrate, a very small number of failures are expected when it is used on its own, and we effectively inherit them. At the cost of a bit of added complexity in the implementation, e.g. ODS-RGF could be substituted, and would likely lead to further improvements in both the failure rates and query count curves, while still representing a form of GFCS. There is an additional phenomenon of note: Table 1 also demonstrates the dependence of the performance of existing methods on their own choices of parameter values. Strikingly, almost all of the empirical benefit of ODS-RGF over the earlier P-RGF is due to the different choice of default parameters in

Table 1: Median query count for state-of-the-art *untargeted* black-box methods that make use of surrogates. The missing entry at † indicates a bad choice of ϵ for SimBA-ODS on Inception-v3, while the one at ‡ is due to the LeBA code crashing before completing the full set of images for ResNet-50.

Surrogates	Method	Median queries [Success rate]					
		VGG-16		ResNet-50		Inception-v3	
1	Simba-ODS	117 ± 5.1	[99.45%]	91.5 ± 3.2	[99.65%]	—†	
	Simba-ODS $\epsilon=2$	15 ± 0.7	[99.65%]	11 ± 0.4	[99.90%]	36 ± 1.9	[98.50%]
	P-RGF	128 ± 1.1	[99.95%]	62 ± 1.2	[100%]	282 ± 12	[99.25%]
	P-RGF $\epsilon=0.5$, SPD$=10$	48 ± 2.0	[99.90%]	16 ± 0.0	[99.95%]	90 ± 4.9	[99.00%]
	ODS-RGF	44 ± 0.0	[99.95%]	33 ± 0.0	[100%]	77 ± 2.4	[99.95%]
	SimBA++	30 ± 3.0	[100%]	5 ± 0.5	[100%]	59 ± 3.4	[99.4%]
	LeBA	8 ± 0.74	[100%]	—‡		56 ± 3.4	[98.90%]
	GFCS (ours)	$\mathbf{6 \pm 0.3}$	[99.90%]	$\mathbf{4 \pm 0.4}$	[99.85%]	$\mathbf{18 \pm 1.1}$	[98.60%]
4	Simba-ODS	68 ± 2.2	[99.90%]	108.5 ± 4.5	[99.80%]	—†	
	Simba-ODS $\epsilon=2$	10 ± 0.3	[100%]	14 ± 0.5	[99.90%]	29 ± 1.4	[100%]
	P-RGF	64 ± 0.6	[99.95%]	66 ± 0.5	[100%]	232 ± 4.7	[99.15%]
	P-RGF $\epsilon=0.5$, SPD$=10$	16 ± 2.3	[100%]	24 ± 1.2	[100%]	60 ± 2.1	[99.60%]
	ODS-RGF	33 ± 0.0	[100%]	44 ± 0.0	[100%]	77 ± 5.5	[100%]
	GFCS (ours)	$\mathbf{4 \pm 0.2}$	[100%]	$\mathbf{4 \pm 0.0}$	[99.95%]	$\mathbf{9 \pm 0.5}$	[99.40%]

(a) VGG-16; one surrogate.

(b) VGG-16; four surrogates.

Figure 3: Breakdown of the total query count for the proposed method, *GFCS: Gradient First, Coimage Second*. The x-axis represents the number of queries for a successful attack required by the *gradient* part of the method, and the y-axis the number required by the *coimage* part. Histograms on the top and right sides of the scatter plots represent marginal empirical distributions.

the respective methods: when P-RGF simply uses the default parameters of ODS-RGF, it actually considerably outperforms it in terms of median query count on ResNet-50, at the cost of a 0.05% increase in failure rate. SimBA-ODS benefits dramatically from an order-of-magnitude increase in its step-size parameter. This, in and of itself, serves as further evidence of our central thesis that transfer (in the context of the assumption of local linearity) is generally pursued too timidly.

4.2 ANALYSIS OF ALGORITHM BEHAVIOUR

To delve deeper into the results of Sec. 4.1, we plot each attacked example as a 2D point whose x-coordinate is the number of queries expended by the surrogate loss block of the algorithm, and whose y-coordinate is the analogous count for the coimage block. This gives the scatter plot of Fig. 3, which is supplemented by marginal histograms corresponding to the axes opposite them. The figure shows results obtained using VGG-16 as victim. ResNet-50 and Inception-v3 lead to similar figures and are deferred to Appendix A.3. Note that the axes of the main scatter plots are log-log, while those of the marginal histograms are linear-log. Some phenomena are readily evident. For one, there is a large fraction of examples (represented by the dense horizontal rows of dots at the bottom of the plots) that succeed within a very low number of queries (on the order of 1-10), which are entirely or almost entirely due to the surrogate gradient transfer, with ODS used seldom or not at all. As these low-query clusters are extremely dense, the corresponding marginals should be consulted in order to quantify them. For another, the number of examples outside of this regime falls drastically when the four-surrogate set is used instead of ResNet-152 on its own, as can be seen by comparing the left and right sides of the figure. It is clear that the number of examples that rely on the

(a) VGG-16   (b) ResNet-50

Figure 4: CDFs showing the number of successfully attacked examples at different query counts when performing *targeted* black-box attacks on VGG-16 and ResNet-50 models, with four surrogates.

interplay between the gradient- and coimage-based direction generators are reduced to a nontrivial (i.e. sufficient to affect the failure rate if not handled) but nonetheless small handful. Overall, there is an order-of-magnitude difference between surrogate loss gradient queries and ODS queries in the points in the cloud extending away from the dense low-query cluster at the bottom, i.e. the examples that rely on both submethods. That is, when the ODS block is required, it typically requires far more queries to progress the optimiser than in the much more common cases in which the gradient suffices.

4.3 TARGETED ATTACKS

We also test our method in the targeted attack scenario. The setup is the same as in Sec. 4.1, except as noted otherwise. For these experiments, instead of the margin loss, we use the log loss of the target-class softmax score, as is often chosen for targeted attacks: $L_{\mathbf{f}}(\mathbf{x}) = \log p_t$, where $p_t = \frac{e^{\mathbf{f}_t(\mathbf{x})}}{\sum_c e^{\mathbf{f}_c(\mathbf{x})}}$. That is, the goal of the attacker is to push the target-class confidence up at the expense of all other classes generally, rather than suppressing a specific source class. We perform multiple runs for each setting, with the target class for each image chosen at random (uniformly) from all ImageNet classes other than the ground truth. Neither Cheng et al. (2019) nor Yang et al. (2020) provide results or code for targeted attacks. While Tashiro et al. (2020) report targeted attack numbers for both P-RGF and their own ODS-RGF, no supporting implementation is available. As noted before, our own P-RGF and ODS-RGF results in Sec. 4.3 were produced using a port of the public P-RGF repository, which only supports untargeted attacks (a restriction that carries through to the ODS-RGF modification we have made to it). We thus work with the provided SimBA-ODS implementation, comparing it in isolation to GFCS, in which it serves as the backup method. The results are displayed in Fig. 4. As can be seen, even under this more difficult attack scenario, under which the more aggressive transfer strategy of GFCS might be expected to suffer, our method retains its considerable advantage.

While the targeted attack method of Huang & Zhang (2020) is both powerful and conceptually related, it is architecturally tied to the ℓ_∞ norm in its given formulation, and thus not appropriate for our ℓ_2-bound comparisons. Further, given a trained surrogate, the method requires that one *then* train the method's adversarial encoder-decoder network on a held-out validation set: in the case of targeted attacks, this must be done *per target class*, as acknowledged by the authors in the original work. Our approach, by contrast, uses the surrogate directly without any issue, on any target class.

4.4 ON THE IMPORTANCE OF INPUT-SPECIFIC PRIORS

Our approach, and the ones we compare against, are all based on priors that are conditioned on the iterate, i.e. gradient information evaluated at the current point. SimBA, on the other hand, effectively encodes location-independent prior information in the form of the basis matrix from which it draws its search directions, and, if appropriate, a prior ordering strategy for searching them. An example, which has been used in other works as well (see Sec. 2), is the low-frequency DCT basis, which can follow specific orderings if desired. It is well known that there is a sense in which adversariality is location-independent, as in Moosavi-Dezfooli et al. (2017). However, location-specific adversaries can be found with much lower norms (Moosavi-Dezfooli et al., 2016; Carlini & Wagner, 2017) when local information is taken into account, even under simple linear assumptions. It is thus clear that while it is important to understand the points made in the universal adversary literature, local information is

(a) VGG-16. (b) ResNet-50. (c) Inception-v3.

Figure 5: Comparison between GFCS, which makes use of surrogate gradients at the time of attack, vs. flavours of SimBA only leveraging relevant information "offline". Please refer to Sec. 4.4.

nonetheless key to finding optimal adversaries. Thus, it is interesting to try to identify what sorts of limits are reached in confining oneself to location-independent priors: here, we investigate this in the context of SimBA. We propose a variant called "SimBA-SVD", which is defined by the approach it takes to generating the SimBA basis matrix. Following the method used in Moosavi-Dezfooli et al. (2017); Jetley et al. (2018), we gather adversarial examples[2] over a sample input set as columns in a matrix, then compute that matrix's SVD. That is, we produce the ordered set of vectors that would be expected to represent the ℓ_2-optimal basis for reproducing the adversarial examples on the given set, when constrained to follow SimBA's iterative adversary-building optimisation procedure. We then compare this against SimBA using both the canonical pixel and DCT bases in random order, and GFCS. An an interesting aside, we also include the result of using the procedure on raw images directly, i.e. using the principal components of the input data as the search directions. All of these methods are placed within the same norm-bounded PGA framework.

Fig. 5 demonstrates the results of this experiment. As predicted, the gradient-based basis ("SimBA-PCA-gradients") comfortably outperforms the canonical pixel basis ("SimBA pixel"), as well as the principal image components ("SimBA-PCA-images"), the latter fact indicating that the information encoded in adversarial directions indeed goes beyond simple correspondence to modes of data variation. Note, though, that the principal data directions do outperform the naïve pixel basis, unsurprisingly revealing nontrivial correlation between modes of data variation and features learned by the network. However, despite forming a "natural adversarial basis", the adversarial singular vector matrix does *not* outperform the DCT basis: their results are very close, but if anything, the DCT basis slightly outperforms. That is, the DCT basis with a suitably tuned frequency count appears to already represent the limit of what a SimBA-style iteration through a single fixed orthonormal basis can accomplish, and the SimBA-SVD procedure has at best recovered an equivalent to it. GFCS, on the other hand, is far more efficient than all of the compared methods, demonstrating the performance that is available when it is possible to condition the prior on the iterate, i.e. to use local gradient information. This is one way of viewing why it is that the use of surrogates is as powerful as it is.

5 CONCLUSION

We have demonstrated that score-based attacks using surrogates are in fact easy. By "easy", we mean that a very high success rate is achievable within a very low number of queries to the victim model, using an algorithm that is simple to both describe and implement: GFCS. Further, that algorithm is based on a fairly direct type of transfer: it relies first and foremost on transfer of loss gradient directions from the surrogate to the target, falling back to transferring other combinations of features locally significant to the surrogate. One implication of this is that all of the examined surrogate and target networks are in fact similar to one another in the sense that the algorithm not just assumes, but entirely relies on. An interesting avenue for future work is to determine whether there are noteworthy situations in which the assumption of good feature transfer no longer holds, and the attack no longer suitable: this will be tantamount to identifying classes of networks that genuinely learn distinct responses from one another.

---

[2]We have experimented with various methods of generating the source adversaries, as well as comparing the effects of normalising the directions or not doing so. All approaches yield indistinguishable results. Here, we simply use the gradients of random class scores.

ETHICS STATEMENT

Our work introduces a novel (and very effective) black-box attack. As with all adversarial attacks, the method exposes a way of getting a target/victim network to issue responses to inputs that are almost certainly unlike those intended by its designer. Therefore, were an actual harmful practical application of such an attack to be identified in which the assumptions of this method (i.e. that the victim exposes its decision scores, and that a viable surrogate can be found) were satisfied, the publication of this method could in principle facilitate it. As is it not currently well understood how to build useful networks that do not have the sorts of properties being exploited here, there is no straightforward "defence". However, the primary perspective from which we approach this work is that of network analysis. A key goal is to make practitioners aware of potential risks their machine learning systems are exposed to, especially and most realistically *unintended* failure, and to motivate the community to design networks that are more robust, predictable, and comprehensible.

REPRODUCIBILITY STATEMENT

Code and data: We accompany this submission with the the code implementing the proposed GFCS method. The code includes, in a utility file, lists of IDs of the ImageNet validation images used in the experiments, to allow full reproduction. Note that Algorithm 1 itself presents a complete and implementable description of the algorithm. On acceptance, we will also publicly release all code needed to reproduce all of the plots and tables in our paper. Finally, after correspondence with the maintainers of the codebases of methods we have compared against, we will also release forked versions with the small changes necessary to standardise the results against one another.

Statistical significance: As described in Sec. 4.1, we report uncertainty for the results of all the reported methods, for all of the experiments. Moreover, we double the size of the test set typically used in the literature (and keep it fixed across competing methods).

Hyperparameters: Our method contains a single tunable hyperparameter (the step length ϵ). As discussed in Appendix A.4, we chose its value on a held-out set and kept it fixed across all of the experimental configurations. For the competing methods, we use the provided source code and the default hyperparameters, alongside any hyperparameter choice we found to work better than the default(s). For instance (see Appendix A.4), for SimBA-ODS, we found that $\epsilon = 2.0$ is significantly better than $\epsilon = 0.2$, which is the default used in Tashiro et al. (2020).

REFERENCES

Abdullah Al-Dujaili and Una-May O'Reilly. Sign bits are all you need for black-box attacks. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=SygW0TEFwH.

Maksym Andriushchenko, Francesco Croce, Nicolas Flammarion, and Matthias Hein. Square attack: a query-efficient black-box adversarial attack via random search. In *European Conference on Computer Vision*, pp. 484–501. Springer, 2020.

Arjun Nitin Bhagoji, Warren He, Bo Li, and Dawn Song. Practical black-box attacks on deep neural networks using efficient query mechanisms. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 154–169, 2018.

Wieland Brendel, Jonas Rauber, and Matthias Bethge. Decision-based adversarial attacks: Reliable attacks against black-box machine learning models. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=SyZI0GWCZ.

Tom B Brown, Nicholas Carlini, Chiyuan Zhang, Catherine Olsson, Paul Christiano, and Ian Goodfellow. Unrestricted adversarial examples. *arXiv preprint arXiv:1809.08352*, 2018.

Thomas Brunner, Frederik Diehl, Michael Truong Le, and Alois Knoll. Guessing smart: Biased sampling for efficient black-box adversarial attacks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4958–4966, 2019.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *2017 ieee symposium on security and privacy (sp)*, pp. 39–57. IEEE, 2017.

Pin-Yu Chen, Huan Zhang, Yash Sharma, Jinfeng Yi, and Cho-Jui Hsieh. Zoo: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models. In *Proceedings of the 10th ACM workshop on artificial intelligence and security*, pp. 15–26, 2017.

Shuyu Cheng, Yinpeng Dong, Tianyu Pang, Hang Su, and Jun Zhu. Improving black-box adversarial attacks with a transfer-based prior. *Advances in Neural Information Processing Systems*, 32: 10934–10944, 2019.

Hadi M Dolatabadi, Sarah Erfani, and Christopher Leckie. Advflow: Inconspicuous black-box adversarial attacks using normalizing flows. *arXiv preprint arXiv:2007.07435*, 2020.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Chuan Guo, Jacob Gardner, Yurong You, Andrew Gordon Wilson, and Kilian Weinberger. Simple black-box adversarial attacks. In *International Conference on Machine Learning*, pp. 2484–2493. PMLR, 2019a.

Chuan Guo, Jared S Frank, and Kilian Q Weinberger. Low frequency adversarial perturbation. In *Uncertainty in Artificial Intelligence*, pp. 1127–1137. PMLR, 2020.

Yiwen Guo, Ziang Yan, and Changshui Zhang. Subspace attack: Exploiting promising subspaces for query-efficient black-box attacks. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019b. URL `https://proceedings.neurips.cc/paper/2019/file/2cad8fa47bbef282badbb8de5374b894-Paper.pdf`.

Dan Hendrycks, Kevin Zhao, Steven Basart, Jacob Steinhardt, and Dawn Song. Natural adversarial examples. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15262–15271, 2021.

Hossein Hosseini and Radha Poovendran. Semantic adversarial examples. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 1614–1619, 2018.

Zhichao Huang and Tong Zhang. Black-box adversarial attack with transferable model-based embedding. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=SJxhNTNYwB`.

Andrew Ilyas, Logan Engstrom, Anish Athalye, and Jessy Lin. Black-box adversarial attacks with limited queries and information. In *International Conference on Machine Learning*, pp. 2137–2146. PMLR, 2018.

Andrew Ilyas, Logan Engstrom, and Aleksander Madry. Prior convictions: Black-box adversarial attacks with bandits and priors. In *International Conference on Learning Representations*, number 2019, 2019.

Saumya Jetley, Nicholas A Lord, and Philip HS Torr. With friends like these, who needs adversaries? In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pp. 10772–10782, 2018.

Yandong Li, Lijun Li, Liqiang Wang, Tong Zhang, and Boqing Gong. Nattack: Learning the distributions of adversarial examples for an improved black-box attack on deep neural networks. In *International Conference on Machine Learning*, pp. 3866–3876. PMLR, 2019.

Xiaolei Liu, Teng Hu, Kangyi Ding, Yang Bai, Weina Niu, and Jiazhong Lu. A black-box attack on neural networks based on swarm evolutionary algorithm. In *Australasian Conference on Information Security and Privacy*, pp. 268–284. Springer, 2020.

Yanpei Liu, Xinyun Chen, Chang Liu, and Dawn Song. Delving into transferable adversarial examples and black-box attacks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL `https://openreview.net/forum?id=Sys6GJqxl`.

Chen Ma, Shuyu Cheng, Li Chen, and Junhai Yong. Switching gradient directions for query-efficient black-box adversarial attacks. *arXiv preprint arXiv:2009.07191*, 2020.

Seungyong Moon, Gaon An, and Hyun Oh Song. Parsimonious black-box adversarial attacks via efficient combinatorial optimization. In *International Conference on Machine Learning*, pp. 4636–4645. PMLR, 2019.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: a simple and accurate method to fool deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2574–2582, 2016.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Omar Fawzi, and Pascal Frossard. Universal adversarial perturbations. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1765–1773, 2017.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In *Proceedings of the 2017 ACM on Asia conference on computer and communications security*, pp. 506–519, 2017.

Anit Kumar Sahu, Satya Narayan Shukla, and J Zico Kolter. Gaussian mrf covariance modeling for efficient black-box adversarial attacks. *arXiv preprint arXiv:2010.04205*, 2020.

Yucheng Shi, Siyu Wang, and Yahong Han. Curls & whey: Boosting black-box adversarial attacks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6519–6527, 2019.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *2nd International Conference on Learning Representations, ICLR 2014*, 2014.

Yusuke Tashiro, Yang Song, and Stefano Ermon. Diversity can be transferred: Output diversification for white-and black-box attacks. *Advances in Neural Information Processing Systems*, 33, 2020.

Chun-Chen Tu, Paishun Ting, Pin-Yu Chen, Sijia Liu, Huan Zhang, Jinfeng Yi, Cho-Jui Hsieh, and Shin-Ming Cheng. Autozoom: Autoencoder-based zeroth order optimization method for attacking black-box neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 742–749, 2019.

Jie Wang, Zhaoxia Yin, Jin Tang, Jing Jiang, and Bin Luo. Pica: A pixel correlation-based attentional black-box adversarial attack. *arXiv preprint arXiv:2101.07538*, 2021.

Chaowei Xiao, Jun-Yan Zhu, Bo Li, Warren He, Mingyan Liu, and Dawn Song. Spatially transformed adversarial examples. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL `https://openreview.net/forum?id=HyydRMZC-`.

Ziang Yan, Yiwen Guo, Jian Liang, and Changshui Zhang. Policy-driven attack: Learning to query for hard-label black-box adversarial examples. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL `https://openreview.net/forum?id=pzpytjk3Xb2`.

Jiancheng Yang, Yangzhou Jiang, Xiaoyang Huang, Bingbing Ni, and Chenglong Zhao. Learning black-box attackers with transferable priors and query feedback. *Advances in Neural Information Processing Systems*, 33, 2020.

Zhengli Zhao, Dheeru Dua, and Sameer Singh. Generating natural adversarial examples. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL `https://openreview.net/forum?id=H1BLjgZCb`.

Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning deep features for discriminative localization. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2921–2929, 2016.

A APPENDIX

A.1 COIMAGES AND DIMENSION REDUCTION

The assumption of local linearity is ubiquitous in the study of deep networks, and particularly adversarial attacks on them. A simple way of explaining the upper bound on the dimension of the coimage of a network's linear approximation is through the rank-nullity theorem. This points out that for linear transformation T mapping finite-dimensional vector space $\mathcal{V}$ to vector space $\mathcal{W}$, $\mathrm{rank}(T) + \mathrm{nullity}(T) = \dim(\mathcal{V})$, where $\mathrm{rank}(T) := \dim(\mathrm{image}(T))$ and $\mathrm{nullity}(T) := \dim(\mathrm{kernel}(T))$. That is to say, the dimension of the input subspace that has any effect on the output ($\mathrm{rank}(T)$) is no greater than that of the output space (because $\dim(\mathrm{image}(T)) \leq \dim(\mathcal{W})$), and the dimension of the input subspace that has *no* effect on the output ($\mathrm{nullity}(T)$) is at least equal to the difference between the input and output dimensions (because $\mathrm{nullity}(T) = \dim(\mathcal{V}) - \mathrm{rank}(T) \geq \dim(\mathcal{V}) - \dim(\mathcal{W})$). To make this more concrete, in the case of a standard ImageNet Inception-v3 network, $\mathcal{V} = \mathcal{R}^{299*299*3}$ and $\mathcal{W} = \mathcal{R}^{1000}$, and so in the linear approximation, $\mathrm{rank}(T) = \dim(\mathrm{coimage}(T)) \leq 1000$, and $\mathrm{nullity}(T) \geq 267203$. Under the assumption that the features to which a surrogate is locally sensitive will largely transfer to a target network, naïve search of the input space is thus extremely wasteful.

This is the key issue which limits the preprint of Ma et al. (2020), which contains some similarities to our method in its preference for surrogate gradient transfer within a SimBA-like optimisation context. The crucial difference lies in their attempt to use standard RGF gradient estimation in order to progress optimisation when surrogate loss gradients fail, thus falling prey to the inherent issue with estimating gradients in high-dimensional input spaces pointed out in this context as far back as Chen et al. (2017). The dramatic difference in result quality between the two methods owes to this fact.

A.2 IMPLEMENTATION DETAILS

As explicitly written in Alg. 1 and discussed in Sec. 3.2, the SimBA-style search is done within a standard PGA projection of the update candidate onto the feasible set, to avoid the common evaluation issue in the literature in which SimBA is punished *ex post facto* for violating a norm bound that the method was not originally designed to account for. Our method thus avoids this issue by design, but we further note that none of the evaluations we perform on other methods involve this sort of practice: if a bound is to be imposed, a method should always be modified in a straightforward manner to account for it, rather than being deemed to have failed after the fact.

On the other hand, our study of the implementations of competing methods has shown that some of them unnecessarily hobble their own performance by using surrogates with domains that differ from that of the target model without appropriately including interpolation between the domains. This typically shows up when Inception-v3, which is trained to accept an input in $\mathcal{R}^{299*299*3}$, is attacked using networks with the more common input domain of $\mathcal{R}^{224*224*3}$: adaptive pooling layers prevent crashing, but do not fix the issue of feature scale mismatch. As such, each surrogate in our method should be considered to contain an differentiable bilinear interpolation module as an initial layer, thus producing appropriately mapped gradients in the target domain on backpropagation. In the spirit of fair comparison, we implement this option for competitors as well. Additionally, as of this writing, the public LeBA implementation contains non-standard pre-processing of the input images: we replace this with standard practice, again to facilitate fair comparison against other methods.

Finally, note that when $L_{\mathbf{f}}(\mathbf{x})$ is the margin loss, its normalised gradient is just a special case of $\mathbf{d}_{\mathrm{ODS}}(\mathbf{x}, \mathbf{f}, \mathbf{w})$ in which $\mathbf{w}_{c_t} \leftarrow 1$, $\mathbf{w}_{c_s} \leftarrow -1$, and $\mathbf{w}_{c \notin \{c_s, c_t\}} \leftarrow 0$. In our experimental setup, all methods are run on sets of images that, while otherwise randomly selected from the ILSVRC2012 validation set, are guaranteed to be correctly classified by each target network. Thus, there is never any difference between c_s and the ground-truth label in the untargeted attack case.

(a) ResNet-50; one surrogate.

(b) ResNet-50; four surrogates.

(c) Inception-v3; one surrogate.

(d) Inception-v3; four surrogates.

Figure 6: Breakdown of the total query count for the proposed method, i.e. *GFCS: Gradient First, Coimage Second*. The x-axis represents the number of queries for a successful attack required by the *gradient* part of the method, while the y-axis the one required by the *coimage* part. Histograms on the top and right sides of the scatter plots represent marginal empirical distributions.

A.3 ADDITIONAL RESULTS FOR SECTION 4.2

The scatter plots and empirical marginal distributions in Fig. 6 complete the results of Sec. 4.2 and Fig. 3 from the main paper, extending the same analysis to ResNet-50 and Inception-v3 architectures. A very similar trend can be observed: 1) most of the examples are successfully attacked with a handful of queries, 2) the low count is almost entirely due to the surrogate gradient transfer, and 3) using four surrogates amplifies the two previous phenomena.

A.4 ON THE STEP LENGTH ϵ

The simple method we propose in Algorithm 1 presents a single hyperparameter: the step length ϵ (line 14), which indicates the length of the perturbations to be attempted at each iterate along its candidate direction. We chose 2.0 as the default value for our experiments by performing a small grid search over a held-out set (disjoint from the 2000 examples used in the experiments of the main paper). Results for the three architectures used as victim (and ResNet-152 as the single surrogate) are shown in Fig. 7. Note that the figure has two y-axes and two sets of lines: solid and dashed lines should be considered looking at the axis on the left and right hand side of the plot, respectively. Clearly, better performance can be obtained by separately tuning this hyperparameter for each architecture. Instead, we simply chose a fixed value that is reasonable for all models and for both query count and success rate. Note also how it is possible to achieve an even lower query count if one is willing to sacrifice about 1% of the success rate.

We observed that this choice of ϵ is also significantly better than the default one made by SimBA-ODS (Tashiro et al., 2020) (i.e. 0.2), and have reported results for both in our experiments.

Figure 7: The figure illustrates two sets of lines. The solid lines represent the median query count required to successfully attack the three architectures as a function of the step length, while the dashed lines show the success rate.