Towards Optimal Strategies for Training Self-Driving Perception Models in Simulation

Abstract

Autonomous driving relies on a huge volume of real-world data to be labeled to high precision. Alternative solutions seek to exploit driving simulators that can generate large amounts of labeled data with a plethora of content variations. However, the domain gap between the synthetic and real data remains, raising the following important question: *What is the optimal way to use a self-driving simulator for perception tasks in the absence of real-world labels?* In this work, we build on top of recent advances in domain-adaptation theory, and from this perspective, propose ways to minimize the reality gap. Our approach introduces both a principled way to learn neural-invariant representations and a theoretically inspired view on how to sample the data from the simulator. Our method is easy to implement in practice as it is agnostic of the network architecture and the choice of a simulator. It also allows us to leverage labeled data in the target domain, if available. We showcase our approach on the bird's-eye-view vehicle segmentation task with multi-sensor data (cameras, lidar) using an open-source simulator (CARLA), and evaluate the entire framework on a real-world dataset (nuScenes).

1 Introduction

The dominant strategy in self-driving for training perception models is to deploy cars that collect massive amounts of real-world data, hire a large pool of annotators to label it and then train the models on that data using supervised learning. Although this approach is likely to succeed asymptotically, the financial cost scales with the amount of data being collected and labeled. Furthermore, changing sensors may require redoing the effort to a large extent. Some tasks such as labeling ambiguous far away or occluded objects may be hard or even impossible for humans.

In comparison, sampling data from self-driving simulators such as [42, 1, 5, 11] has several benefits. First, one has control over the content inside a simulator which makes all self-driving scenarios equally efficient to generate, indepedent of how rare the event might be in the real world. Second, full world state information is known in a simulator, allowing one to synthesize *perfect labels* for information that humans might annotate noisily, as well as labels for fully occluded objects that would be impossible to label outside of simulation. Finally, one has control over sensor extrinsics and intrinsics in a simulator, allowing one to collect data for a fixed scenario under any chosen sensor rig.

Given these features of simulation, it would be tremendously valuable to be able to train deployable perception models on data obtained from a self-driving simulation. There are, however, two critical challenges in using a driving simulator out of the box. First, sensor models in simulation do not mimic real world sensors perfectly; even with exact calibration of extrinsics and intrinsics, it is infeasible to perfectly label all scene materials and model complicated interactions between sensors and objects – at least today [30, 7, 52, 38]. Second, real world content is difficult to incorporate into simulation; world layout may be different, object assets may not be diverse enough, and synthetic materials, textures and weather may all not align well with their real world counterparts [47, 5, 17, 51]. To make

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Figure 1: **nuScenes vs CARLA** Visualization of real-world data & labels from nuScenes [6] (top) and synthetic data & labels we obtain from CARLA [11] (bottom). As in nuScenes, we scrape 6 cameras, 1 LiDAR, ego-motion (for temporal fusion of LiDAR scans), and 3D bounding boxes from CARLA. On the right, we show the target binary image for the bird's-eye-view vehicle segmentation task that we consider in this paper [39, 33, 20].

matters worse, machine learning models and more specifically neural networks are very sensitive to this discrepancies, and are known to generalize poorly from virtual (source domain) to real world (target domain)[48, 12, 40].

Contributions and Outline. In this paper, we seek an optimal strategy for exploiting a driving simulator. Specifically, we build on recent advances in domain-adaptation theory, and from this perspective, propose a theoretically inspired method for training neural networks for driverless perception tasks using data obtained from the simulator.

We start by formalizing our problem from a DA perspective. In Section 2, we introduce the mathematical tools, generalization bounds and highlight main similarities and *differences* between standard DA and learning from a simulator. Our analysis leads to a novel method for sampling data from the self-driving simulator introduced in Section 3. This technique is simulator agnostic, simple to implement in practice and builds on the principle of reducing the distance between the labels' marginals, thereby effectively reducing the domain-gap and allowing adversarial frameworks to learn meaningfully in a representation space. Section 4 generalizes recently proposed *discrepancy* minimization adversarial methods using Pearson χ^2 to dense prediction tasks. It also shows a novel way to combine this with pseudo-labels. In Section 6, we experimentally validate the efficacy of our method and show the same approach can be simply applied to different sensors and data modalities (oftentimes implying different architectures). In contrast with baselines, we show our framework also provide noticeable gains when data in the target domain is available. Finally, we show that expensive variations such as number of vehicle assets, or map design can be compensated with our method, thus showing self-driving engineers what is and is not paramount to include in the simulators. The "synthetic nuScenes" datasets we generated for this paper along with the scripts that created them will be open-sourced in order to encourage other researchers in domain adaptation to apply their algorithms on the tasks and sensor suites relevant to contemporary self-driving cars.

2 Learning from a Simulator: A Domain Adaptation Perspective

In this section, we interpret learning from a simulator as a domain adaptation problem. We first formulate the problem and introduce the notation that will be used throughout the work. Then, we introduce mathematical tools and generalization bounds that this work builds upon. We also highlight main similarities and *differences* between standard DA and learning from a simulator.

We start by assuming the self-driving simulator can automatically produce labels for the task in hand (as is typical), and refer to data samples obtained from the simulator as the synthetic dataset (S) with *labeled* datapoints $S = \{(x_i^s, y_i^s)\}_{i=1}^{n_s}$. Let's also assume we have access to another dataset (T) with *unlabeled* examples $T = \{(x_i^t)\}_{i=1}^{n_t}$ that are collected in the real world. We emphasize that *no labels are available* for T. Our goal then is to learn a model (hypothesis) h for the task using data from the labeled dataset S such that h performs well in the real-world. Intuitively, one should incorporate the unlabeled dataset T during the learning process as it captures the real world data distribution.

Certainly, there are different ways in which the dataset S can be generated (e.g. domain randomization [48, 34]), and also several algorithms that a practitioner can come up with in order to solve the task

(e.g. style transfer). In order to narrow the scope and propose a formal solution to the problem, we propose to interpret this problem from a DA perspective. The goal of this learning paradigm is to deal with the lack of labeled data in a target domain (e.g real world) by transferring knowledge from a labeled source domain (e.g. virtual word). Therefore, clearly applicable to our problem setting.

In order to properly formalize this view, we must add a few extra assumptions and notation. Specifically, we assume that both the source inputs x_i^s and target inputs x_i^t are sampled i.i.d. from distributions P_s and P_t respectively, both over $\mathcal{X}$. We also let the output domain be $\mathcal{Y} = \{0, 1\}$ and define the indicator of performance to be the risk of a hypothesis $h : \mathcal{X} \to \mathcal{Y}$ w.r.t. the labeling function f, using a loss function $\ell : \mathcal{Y} \times \mathcal{Y} \to \mathbb{R}_+$ under distribution $\mathcal{D}$, or formally $R_{\mathcal{D}}^{\ell}(h, f) := \mathbb{E}_{\mathcal{D}}[\ell(h(x), f(x))]$. We let the labeling function be the optimal Bayes classifier $f(x) = \arg\max_{\hat{y} \in \mathcal{Y}} P(y = \hat{y}|x)$ [31], where $P(y|x)$ denotes the class conditional distribution for either the source-domain (simulator) $(P_s(y|x))$ or the target domain (real-world) $(P_t(y|x))$. For simplicity, we define $R_S^{\ell}(h) := R_{P_s}^{\ell}(h, f_s)$ and $R_T^{\ell}(h) := R_{P_t}^{\ell}(h, f_t)$.

For reasons that will become obvious later (Sec. 4), we will interpret the hypothesis h (model) as the composition of $h = \hat{h} \circ g$ with $g : \mathcal{X} \to \mathcal{Z}$, and $\hat{h} : \mathcal{Z} \to \mathcal{Y}$, where $\mathcal{Z}$ is a representation space. Thus, we define the hypothesis class $\mathcal{H} := \{\hat{h} \circ g : \hat{h} \in \hat{\mathcal{H}}, g \in \mathcal{G}\}$ such that $h \in \mathcal{H}$. With this in hand, we can use the generalization bound from [2] to measure the generalization performance of a model h:

Theorem 1 *(Acuna et al. [2]). Suppose $\ell : \mathcal{Y} \times \mathcal{Y} \to [0, 1]$ and denote $\lambda^* := \min_{h \in \mathcal{H}} R_S^{\ell}(h) + R_T^{\ell}(h)$. We have:*

$$R_T^{\ell}(h) \leq R_S^{\ell}(h) + D_{h,\mathcal{H}}^{\phi}(P_s \| P_t) + \lambda^*, \quad where \tag{1}$$

where: $D_{h,\mathcal{H}}^{\phi}(P_s \| P_t) := \sup_{h' \in \mathcal{H}} |\mathbb{E}_{x \sim P_s}[\ell(h(x), h'(x))] - \mathbb{E}_{x \sim P_t}[\phi^*(\ell(h(x), h'(x)))]|$, and the function $\phi : \mathbb{R}_+ \to \mathbb{R}$ defines a particular f-divergence with ϕ^* being its (Fenchel) conjugate.

Theorem 1 is important for our analysis as it shows us what we must take into account such that a model can generalize from the virtual to the real-world. Intuitively, the first term in the bound accounts for the performance of the model on simulation, and shows us, first and foremost, that we must perform well on S (this is intuitive). The second term corresponds to the discrepancy between the marginal distributions $P_s(x)$ and $P_t(x)$, in simpler words, how dissimilar the virtual and real world are from an observer's view (this is also intuitive). The third term measures the ideal joint hypothesis (λ^*) which incorporates the notion of adaptability and can be tracked back to the dissimilarity between the labeling functions [2, 54, 3]. In short, when the optimal hypothesis performs poorly in either domain, we cannot expect successful adaptation. We remark that this condition is necessary for adaptation [4, 3, 2, 54].

Comparison vs standard DA. In standard DA, two main lines of work dominate. These mainly depend on what assumptions are put on λ^*. The first group (1) assumes that the last term in equation 1 is negligible thus learning is performed in an adversarial fashion by minimizing the risk in source domain and the domain discrepancy in $\mathcal{Z}$ [14, 2, 29, 53]. The second group (2) introduces reweighting schemes to account for the dissimilarity between the label marginals $P_s(y)$ and $P_t(y)$. This can be either implicit [22] or explicit [28, 46, 44]. The main reason for the second group is because in standard DA the problem formulation assumes that the source dataset and target datasets are fixed. In sharp contrast, in our scenario the synthetic dataset is sampled from the self-driving simulator. Therefore, we have control over how the data is generated, what variations are introduced and where the objects are placed. Thus, theorem 1 additionally tell us that the data generation process must be done in such a way that λ^* is negligible, and if so, we can get away without complex reweighing schemes and simply focus on learning invariant-representations. We will exploit this property in section 3 for the data generation procedure, and in section 4 for the training algorithm.

We emphasize the importance of controlling the dissimilarity between the label marginals $P_s(y)$ and $P_t(y)$, as it determines the training strategy that we can use as illustrated by lower bound from [54]:

Theorem 2 *(Zhao et al. [54]) Suppose that $D_{\mathrm{JS}}(P_s(y) \| P_t(y)) \geq D_{\mathrm{JS}}(P_s(z) \| P_t(z))$ We have:*

$$R_T^{\ell}(h) + R_S^{\ell}(h) \geq \frac{1}{2} \left(\sqrt{D_{\mathrm{JS}}(P_s(y) \| P_t(y))} - \sqrt{D_{\mathrm{JS}}(P_s(z) \| P_t(z))} \right)^2 \tag{2}$$

where D_{JS} corresponds to the Jensen-Shanon divergence.

Figure 2: **Marginals Induced by Sampling Strategies** On the far left, we show $P(y)$ for the nuScenes val. set. To the right, we display $P(y)$ for a certain sampling strategy as well as the marginal that the sampling strategy is seeking to match in the top right, if applicable. For the right two images, the NPCs are sampled according to the CARLA's drivable area, pseudocode for which is included in Appendix. The Jensen-Shannon Divergence between the marginal of the dataset and the marginal of the nuScenes val. set is included in the top left corner.

Theorem 2 is important since it is placing a lower bound on the joint risk, and it is particularly applicable to algorithms that aim to learn domain-invariant representations. In our case, it illustrates the paramount importance of the data generation procedure in the simulator. If we deliberately sample data from the simulator and position objects in a way that creates a mismatch between real and virtual world, simply minimizing the risk in the source domain and the discrepancy between source and target domain in the representation space will not help. Simply put, failing to align the marginals will prevent us from using recent SoTA adversarial learning algorithms.

3 Synthetic Data Generation

In the previous section, we analyzed learning from a simulator from a domain-adaptation perspective, and showed the importance of the data sampling strategy as this could create a mismatch between the label marginals (necessary condition for transfer). In this section, we build on this analysis and propose two simple, but effective methods to sample data from the self-driving simulator. The first one proposes the use of spatial priors and is targeted to a regime where there is a complete absence of real-world labeled data. The second one assumes there is some labeled data in the target domain and exploits these labels to build a prior for the positions of the vehicles in the map.

3.1 Sampling with Spatial Priors

If labels in the target domain are not available, we cannot measure the divergence between the labels marginals $P_t(y)$ between the generated and the real world data. That said, given the bird-eye view segmentation map, it is not hard for a human to design spatial priors representing locations with high probability of finding a vehicle. As visualized in Figure 3, we design a simple prior that samples locations for non-player characters (NPCs) proportional to the longitudinal distance of the vehicle to the ego car. For position $(x, y) \in \mathbb{R}^2$ in meters relative to the ego car

Figure 3: **Sampling Methods** One option is to sample NPC locations from the map's drivable area (left). Another is to write a prior over $P(y)$ and sample locations to minimize JSD with respect to that prior (right).

$$P_{\text{spatial}}(x, y) \propto \begin{cases} -\frac{1}{125}|y| + 0.6 & |y| \leq 12.5 \\ -\frac{1}{75}(|y| - 50) & 12.5 \leq |y| \end{cases} \tag{3}$$

These numbers correspond to linearly interpolating between a probability proportional to 0.0 for $|y| = 50$ meters, 0.5 for $|y| = 12.5$ meters, and 0.6 for $|y| = 0$ meters. Intuitively, the prior models the fact that other vehicles are generally located along the length-wise axis of the ego vehicle. The density is independent of x which models our prior that on a straight road, a car is equally likely to be x_0 meters in front of the ego car as it is to be x_1 meters behind the ego car, for any $x_0, x_1 \in \mathbb{R}$.

3.2 Sampling based on Target Priors

Often in practical applications, a small proportion of data is available in the target domain. In such scenarios a natural prior for sampling would be to compute $P_t(y)$ (see Figure 2 for an example), and generate the data based on that. Depending on how large the amount of data in the target domain is, we could also create a blend $\alpha P_{\text{spatial}} + (1 - \alpha)P_t$ and sample from that.

4 Training Strategy

In the previous section, we designed a simulator-agnostic strategy to sample data in a way such that the distance between the label marginals is minimized. However, it is also clear from Theorem 1

Figure 4: **Matching nuScenes Statistics** From left to right, we show the distribution of number of vehicles per scene in nuScenes, the distribution of field of view of the nuScenes cameras, the yaw relative to the ego coordinate frame of the cameras (6 peaks for the 6 different camera directions), and the height of the LiDAR (roughly the same across all scenes). These statistics are matched when sampling data from CARLA.

that in order to improve performance in the real world, we must minimize the distance between the input distributions $P_s(x)$ and $P_t(x)$. In this section, we propose a training algorithm that learns domain-invariant representations and thus effectively minimizes the divergence between virtual and real world in a latent space $\mathcal{Z}$. Minimizing the divergence in a representation space allows our algorithm to be sensor and architecture agnostic. Specifically, we generalize the algorithm proposed in [2] to dense prediction tasks and incorporate the use of pseudo-labels. We remark in our scenario we cannot effectively learn such representations unless the data sampling strategy from section 3 is used (Theorem 2) because otherwise there is considerable misalignment between the label marginals.

Learning Domain-Invariant Representations. Our training algorithm can be interpreted as simultaneously minimizing the source domain error and aligning the two distributions (virtual and real worlds) in some representation space $\mathcal{Z}$. Formally, we aim at finding a hypothesis h that jointly minimizes the first two terms of Theorem 1. Let $h : \mathcal{X} \to \mathcal{Y}$ with $\mathcal{Y} \subseteq \mathbb{R}^{h \cdot w}$ which corresponds to a pixel-wise binary segmentation map of dimensions h and w respectively, with $\mathcal{X}$ corresponding to an unordered set of multi-view images for camera-based bird's-eye-view segmentation $\mathcal{X} \subseteq \mathbb{R}^{N \cdot 3 \cdot H \cdot W}$ and a point cloud for the lidar-based bird's-eye-view segmentation $\mathcal{X} \subseteq \mathbb{R}^{3 \cdot N}$. Our objective function is then formulated in an adversarial fashion by minimizing the following objective:

$$\min_{\hat{h} \in \hat{\mathcal{H}}, g \in \mathcal{G}} \max_{\hat{h}' \in \hat{\mathcal{H}}} \quad \mathbb{E}_{x, y \sim p_s}[\ell(\hat{h} \circ g, y)] + d_{st}, \tag{4}$$

where $\ell : \mathbb{R}^{h \cdot w} \times \mathbb{R}^{h \cdot w} \to \mathbb{R}_+$ is defined as: $\ell(p, q) := \frac{1}{h \cdot w} \sum_{i=0}^{h \cdot w} \beta p_i \log q_i + (1 - p_i) \log(1 - q_i)$, and p_i and $q_i \in [0, 1]$ (the averaged binary-cross entropy loss). β is a hyperparameter that weights the importance of positive pixels in the pixel-wise binary segmentation map. We define d_{st} as:

$$d_{st} := \mathbb{E}_{x \sim p_s} \left[\mathbb{E}_{h \cdot w}[(\hat{h}' \circ g)] \right] - \mathbb{E}_{x \sim p_t} \left[\mathbb{E}_{h \cdot w}[\frac{1}{4}(\hat{h}' \circ g)_i^2 + \hat{h}' \circ g(x)_i] \right] \tag{5}$$

which corresponds to the Pearson χ^2 divergence, and $\mathbb{E}_{h \cdot w}[x] := \frac{1}{h \cdot w} \sum_{i=0}^{h \cdot w} x_i$. Different from the original formulation of f-DAL Pearson [2], d_{st} can be interpreted in our case as a per-location-domain-classifier. For simplicity, we use the gradient reversal layer from [14, 13] to deal with the min-max objective in a single forward-backward pass.

Pseudo-Labels. In addition to the objective in Equation 4, we use the following pseudo-loss:

$$\ell_{\text{pseudo}}(p, p_{\text{aug}}) := \sum_{i=0}^{h \cdot w} \mathbb{1}[p_i \geq \tau][\beta \log p_{\text{aug}_i}] + \mathbb{1}[1 - p_i \leq 1 - \tau] \log(1 - p_{\text{aug}_i}) \tag{6}$$

where $\tau \in [0, 1]$, $\mathbb{1}[x]$ corresponds to the indicator function, $p := h \circ g(x^t)$ and $p_{\text{aug}} := h \circ g \circ \text{aug}(x^t)$ with aug $: \mathcal{X} \to \mathcal{X}$ a function that produces a strong augmentation on the input data point. For camera sensors, we let aug be a version of RandAugment [9] that additionally incorporates camera dropping. For lidar, we follow the same idea from [9] but replace the image augmentations by random

Figure 5: **Style Transfer Baseline (MUNIT)** For our style transfer baseline, we sample a style indepedently for each image and "translate" the CARLA images into nuScenes as shown above. The Lift Splat model receives images like those on the right as input during training.

noise over the points positions as well as points dropout. We let $\tau = 0.9$ in all our experiments. More details are provided in the supplementary material.

The objective in Equation 6 is inspired by [43]. Intuitively, it is based on the generation of pseudo-labels using the confident pixels in the model's predictions, as determined by τ, on the target domain, on a non-strongly augmented version of the same data point. Therefore, it explicitly exposes the model during training to real-world data. We experimentally observed that using pseudo-labels without enforcing invariant representations performs worse than a simple vanilla model trained only on the source dataset, likely because as opposed to [43] in our scenario the target/unlabeled data come from different distributions. The use of pseudo-labels and adversarial learning in our algorithm can be justified through the results of [41] and Theorem 1. In summary, our training algorithm jointly minimizes equations 4 and 6.

Other theoretically inspired training strategies. In principle several other training algorithms that minimize the discrepancy between source and target can be used. For example, Style Transfer using MUNIT [21], the original formulation of [14] or simply f-DAL [2]. Experimentally, we found our generalization of f-DAL-Pearson and the use of pseudo-labels to be more performant (see Table 3). We hypothesise the reason for domain-invariant representation methods being better is because these minimize the dissimilarity between source and target in a low dimensional space. In contrast, Style-Transfer like approaches operate directly on higher dimensional input data (e.g images). As explained above, pseudo-labels further exposes the model to training examples on real-world data.

5   Related Work

Synthetic Data Generation.   The use of synthetic data as an alternative to dataset collection and annotation has received significant interest in recent years. Various datasets have been proposed for tasks such as object detection, semantic segmentation, and home robotics among many others [35, 32, 12, 40, 37]. Our setting is different in that we directly generate sensor data from a self-driving simulator. Several techniques have also been proposed to use graphics simulators to generate data along with labels. For example, [48] proposed to randomize the parameters of the simulator in non-realistic ways with the aim of forcing the neural network to learn the essential features of the object of interest. In a similar vein, [34] proposes to procedurally generate synthetic images while preserving the structure, or context, of the problem at hand. Instead of randomizing, [23, 10, 27] proposed a data-driven approach. Specifically, the authors aim to resemble a target dataset by searching over set of parameters of a surrogate function that interfaces with a synthesizer. These methods are all different from us because 1) they require access to the procedural model of the simulator, thus they are not easy to apply to off-the-self self-driving simulators, 2) they mostly deal with a single object category (e.g. cars), 3) they are focused on the generation of single dashcam RGB images instead of a sensor suite, and 4) data-driven approaches require a significant amount of data in the target domain. Most importantly, the transfer performance that a practitioner may observe lacks justification, e.g. methods such as randomization may clearly increase the divergence between the label marginals.

Domain Adaptation on Synthetic Data.   There is a significant body of work on domain adaptation ranging from theory and algorithms to applications [3, 53, 2, 14, 13, 19], some of them applicable to sim-to-real datasets such as [40, 37] and tasks such as semantic segmentation and object detection [16, 24, 49]. Most of the literature in this direction however analyzes the problem with a fixed dataset perspective. They assume that the source and target datasets are given and aim to find way to minimize the gap. In our formulation, we have access to the self-driving simulator. Therefore, we have control over how the data is generated, what variations are introduced and where the objects are placed. Our method thus is a unified view that minimizes the discrepancy between source and target distribution by building on previous work such as [15, 2] and ensuring the effectiveness of them through a sampling strategy that aims at minimizing the distance between the labels' marginals.

6   Experimental Section

In this section we quantify the performance of the proposed data-generation and training strategies using an open source self-driving simulator (Carla, MIT license [11]) and a real-world dataset (nuScenes, Apache license [6]) . We first introduce the self-driving simulator and the data generation setup. We then discuss the methods in comparison and our proposed baselines. In Section 6.2, we show our main experimental results on the task of bird-eye-view (BEV) vehicle segmentation. Finally, we provide an extensive experimental analysis where we ablate our data and training strategy, and aim to understand what defficiencies of the self-driving simulator can be compensated with our approach.

Figure 6: **Lift Splat Adapt** We visualize the output of Lift Splat (LS) for a single timestep from nuScenes val. The model takes as input the 6 images shown on the left, outputs the heatmap shown on the right, and we project the prediction back onto the input images colorized according to depth. Top is a LS model without adaptation, middle is a LS model trained with our method, and bottom is a LS model trained directly on nuScenes.

6.1 Self-Driving Simulator and Methods in Comparison

Self-Driving Simulator. We use CARLA version 0.9.11 as the self-driving simulator. For the synthetic data generation, we sample nuScenes-like datasets from CARLA such that dataset consists of 4000 episodes; each episode lasts 4 seconds during which all vehicles are controlled by CARLA's default traffic manager. 3D bounding boxes and images are stored synchronously at 2hz [50], and LiDAR scans are stored at 20hz as in nuScenes [6]. We also store the ego pose to facilitate accumu-

Table 1: Lift-Splat Virtual → Real. We compare the performance of our method vs RS. To account for the reality gap, we also show results of RS with different adaptation techniques.

Method	IOU
RS-No Adaptation	9.76
RS-Style Transfer (MUNIT)	13.33
RS-DANN	13.76
Ours	**17.84**

lating LiDAR scans across multiple timesteps. Each CARLA dataset is 260 GB. We split each dataset into a training set of 28k timesteps (which matches the number of timesteps in the nuScenes training set) and a validation set of 4k timesteps. The datasets and scripts for generating them will be publicly released. In the base case for all datasets, we match the distribution of number of vehicles per episode to nuScenes and the distribution of camera and lidar extrinsics and intrinsics as visualized in Fig 4.

Methods in Comparison. For the Synthetic Data Generation strategy, we propose a baseline where we sample data based on the road structure, and randomize what is possible in the simulator, e.g. sampling the color of vehicle assets or weather parameters independently and uniformly. This method is inspired by [48, 34] but within the realistic restriction of the self-driving simulator. We refer to this strategy as **RS** (road structure). We also add two extra baselines on top of RS to account for the domain-gap. These are vs Style-Transfer with MUNIT [21] and using a domain

Table 2: Point Pillars Virtual → Real. We compare performance of our method vs RS.

Method	IOU
RS-No Adaptation	15.09
RS-DANN	14.41
Ours	**17.20**

adaptation inspired by [14]. Details on the MUNIT architecture with example translations can be found in the supplementary. We refer to this as **RS-Style-Transfer** and **RS-DANN** respectively. We also add a version without adaptation which we refer to as **RS-No-Adaptation**.

6.2 Bird's-Eye-View Vehicle Segmentation

Our main experiments and analysis are based on the task of BEV vehicle segmentation from multi-camera sensor data. We additionally compare to baselines using Lidar observations.

Camera In this experiment, the input data corresponds to an unordered set of multi-view images. We use the recently proposed Lift Splat method [33]. We use the same efficientnet backbone [45] and training scheme [25, 8] as in Lift Splat.

Figure 7: **IOU vs. JSD** Transfer performance is negatively correlated with the distance between $P_s(y)$ and $P_t(y)$ as expected from Theorem 2.

Figure 8: **Semi-Super. Learning** Our method improves over baselines when $p\%$ of the labeled data is available at training.

Figure 9: **Better Sampling Improves Town Robustness** We compare transfer performance of Lift Splat models when NPCs are sampled according to geometry of the town roads (left) vs the hard-coded prior (right). Performance greatly improves when using a sampling strategy that doesn't condition on road structure.

Figure 10: **Camera Intrinsics and Extrinsics** Instead of sampling camera extrinsics and intrinsics that exactly correspond to extrinsics and intrinsics from nuScenes, we sample yaw (left) and field of view (middle) from nuScenes with some variance.

Figure 11: **Weather** variation does not appear to be a limiting factor in our setting.

Lidar In this experiment the input data corresponds to point cloud obatained from the lidar scan. We additionally show our method can be used in a completely different sensor such as Lidar Data. For the network architecture, we follow Point Pillars [26], a standard LiDAR architecture consisting of a shallow pointnet [36] followed by a deep 2D CNN based on resnet18 [18].

Semi-Supervised Scenario We also show if labeled real world data is available our method achieves notable gains vs baselines. In Figure 8, we plot transfer performance when we incorporate 2%, 5%, and 25% of nuScenes during training.

6.3 Analysis

In this section, we first ablate the choice of the training strategy and then analyze the correlation between transfer performance and the distance between the labels' marginals as this constitutes the main motivation behind our sampling strategy. We then analyze functionality of the self-driving simulator to improve transfer performance and what deficiencies can be compensated with adaptation.

Training Strategy In Table 3 we keep the data generation strategy fixed and evaluate the performance of different training strategy such as Style-Transfer, DANN, our generalized version of f-DAL, and f-DAL-Pearson with pseudo-labels as proposed in section 4. Our method achieves the best results. Similar to what was found [2], we observe f-DAL performs better than DANN. We also observe that domain-adversarial approaches perform better than Style-Transfer. We believe this is because it is easier to close the reality gap in a latent space rather than in the very high dimensional image space.

Table 3: Ablation on the Training Strategy. In this scenario, we fix the data-generation strategy to be the best.

Name	IOU
No Adaptation	10.33
Style Transfer (MUNIT)	14.32
DANN	14.45
f-DAL Jensen	16.19
f-DAL Pearson	17.03
Ours	**17.84**

Transfer performance vs JSD. Here, we evaluate the distance between the label marginals computed as $D_{\mathrm{JS}}(P_s(y)||P_t(y))$ vs. the transfer performance (IoU). Datasets with a smaller distance perform much better.

Maps When simulating with CARLA, different "towns" can be chosen. Each town has a different road topology and different static obstacles like buildings and foliage. In Figure 9, we show that performance is sensitive to the town if a simple sampling strategy based on the road structure is used. However, by sampling NPC locations to minimize the JSD in the marginals, we increase performance by a large amount.

Vehicle Assets An intuitive goal for self-driving simulators has been to improve the quantity and quality of vehicle assets [51, 17]. In Figure 12, we show that performance is sensitive to the number of vehicle assets used in the simulator and the number of NPCs sampled per episode, but is not so sensitive to the variance in the colors chosen for the NPCs.

Figure 12: **Vehicle Assets** (Left) We vary the number of vehicle assets used when sampling CARLA data. Interestingly, Lift-Splat-Adapt (ours) is able to compensate for performance when very few assets are used. (Middle) We compare performance when the number of NPCs per episode is sampled from $\mathrm{Unif}(0, 40)$, fixed at 1/10/20/30/40 NPCs per episode, or sampled from the distribution in Figure 4. Finally, we compare performance on datasets in which car colors are independently sampled from $\mathrm{Unif}(0, x)$ vs. default car colors.

Weather nuScenes contains sunny, rainy, and nighttime scenes. We test the extent to which it's important for CARLA data to also have variance in weather in Figure 11. CARLA has 15 different "standard" weather settings as well as controls for cloudiness, precipitation, precipitation deposits (e.g. puddles), wind intensity, wetness, fog density, and sun altitude angle (which controls nighttime vs. daytime on a sliding scale). We randomly sample these controls from $x \sim \mathrm{Unif}(0, v)$ for $v \in \{0.2, 0.4, 0.6, 0.8, 1.0\}$ and compare performance against sampling categorically from the 15 preset weather settings. We also compare against exclusively using the "sunny" weather setting but sampling the location of the NPCs according to the hard-coded prior. We find that our method is able to compensate for much of the loss in weather diversity and using only the sunny weather setting on data where NPCs are sampled according to the prior achieves higher performance than any amount of weather diversity with NPCs sampled according to the town.

7 Limitations and Societal Impact

Limitations In Figure 13, we qualitatively demonstrate certain limitations of our method. It is unlikely that adaptation can be used to fix errors for vehicles that look significantly different from the vehicle assets used in CARLA. We also found that our adapted model misdetects pedestrians for vehicles occasionally, perhaps because it has learned a non-causal correlation between legs and bicicyles. Finally, the adapted model occasionally midpredicts the depth of vehicles.

Societal Impact In this paper, we primarily seek to optimize the intersection-over-union of bird's-eye-view segmentation models by leveraging synthetic data rendered in CARLA. While simulated data can be controlled to mitigate some of the biases of real world data (for instance by uniformly sampling vehicles of any color), synthetic data also brings it's own biases in that not all materials, lighting conditions, or weather patterns can be simulated equally realistically; snow is notoriously difficult to simulate correctly, for instance, so simulated data may not be the solution for improving perception in snowy climates. We believe using simulation will be crucial for training and testing safe self-driving systems that have the potential to make public roads safer and more efficient.

Figure 13: **Limitations** Predictions of the best Lift Splat Adapt model vs. ground-truth when the model makes an error. (Left) The model does not detect the orange bus in the garage. (Middle) The model predicts a vehicle where there are pedestrians. (Right) The model predicts a car behind it is much closer than it actually is.

8 Conclusion

Using recent advances in domain adaptation, we motivate methods for both sampling and for training on synthetic data such that models transfer well to real world data. We demonstrate the effectiveness of our method by training camera-based and lidar-based bird's-eye-view vehicle segmentation models on data sampled from the CARLA simulator and evaluated on real world data from nuScenes.

References

[1] Nvidia drive sim, powered by omniverse. `https://www.nvidia.com/en-us/self-driving-cars/simulation/`. Accessed: 2021-05-20.

[2] David Acuna, Guojun Zhang, Marc Law, and Sanja Fidler. f-domain-adversarial learning: Theory and algorithms. In *Proceedings of the 38th International Conference on Machine Learning (to appear)*, 2021.

[3] Shai Ben-David, John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Wortman Vaughan. A theory of learning from different domains. *Machine learning*, 79 (1-2):151–175, 2010.

[4] Shai Ben-David, Tyler Lu, Teresa Luu, and Dávid Pál. Impossibility theorems for domain adaptation. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pages 129–136, 2010.

[5] Alex Bewley, Jessica Rigley, Yuxuan Liu, Jeffrey Hawke, Richard Shen, Vinh-Dieu Lam, and Alex Kendall. Learning to drive from simulation without real world labels. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 4818–4824, 2019. doi: 10.1109/ICRA.2019.8793668.

[6] Holger Caesar, Varun Bankiti, Alex H. Lang, Sourabh Vora, Venice Erin Liong, Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, and Oscar Beijbom. nuscenes: A multimodal dataset for autonomous driving. *CoRR*, abs/1903.11027, 2019. URL `http://arxiv.org/abs/1903.11027`.

[7] Yun Chen, Frieda Rong, Shivam Duggal, Shenlong Wang, Xinchen Yan, Sivabalan Manivasagam, Shangjie Xue, Ersin Yumer, and Raquel Urtasun. Geosim: Photorealistic image simulation with geometry-aware composition. *CoRR*, abs/2101.06543, 2021. URL `https://arxiv.org/abs/2101.06543`.

[8] Dami Choi, Christopher J. Shallue, Zachary Nado, Jaehoon Lee, Chris J. Maddison, and George E. Dahl. On empirical comparisons of optimizers for deep learning. *CoRR*, abs/1910.05446, 2019. URL `http://arxiv.org/abs/1910.05446`.

[9] Ekin D Cubuk, Barret Zoph, Jonathon Shlens, and Quoc V Le. Randaugment: Practical automated data augmentation with a reduced search space. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pages 702–703, 2020.

[10] Jeevan Devaranjan, Amlan Kar, and Sanja Fidler. Meta-sim2: Unsupervised learning of scene structure for synthetic data generation. *CoRR*, abs/2008.09092, 2020. URL `https://arxiv.org/abs/2008.09092`.

[11] Alexey Dosovitskiy, Germán Ros, Felipe Codevilla, Antonio M. López, and Vladlen Koltun. CARLA: an open urban driving simulator. *CoRR*, abs/1711.03938, 2017. URL `http://arxiv.org/abs/1711.03938`.

[12] Adrien Gaidon, Qiao Wang, Yohann Cabon, and Eleonora Vig. Virtual worlds as proxy for multi-object tracking analysis. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4340–4349, 2016.

[13] Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *International conference on machine learning*, pages 1180–1189. PMLR, 2015.

[14] Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *The Journal of Machine Learning Research*, 17(1):2096–2030, 2016.

[15] Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks, 2016.

[16] Muhammad Ghifary, W Bastiaan Kleijn, and Mengjie Zhang. Domain adaptive neural networks for object recognition. In *Pacific Rim international conference on artificial intelligence*, pages 898–904. Springer, 2014.

[17] Jiayuan Gu, Wei-Chiu Ma, Sivabalan Manivasagam, Wenyuan Zeng, Zihao Wang, Yuwen Xiong, Hao Su, and Raquel Urtasun. Weakly-supervised 3d shape completion in the wild. *CoRR*, abs/2008.09110, 2020. URL `https://arxiv.org/abs/2008.09110`.

[18] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *CoRR*, abs/1512.03385, 2015. URL `http://arxiv.org/abs/1512.03385`.

[19] Judy Hoffman, Eric Tzeng, Taesung Park, Jun-Yan Zhu, Phillip Isola, Kate Saenko, Alexei Efros, and Trevor Darrell. Cycada: Cycle-consistent adversarial domain adaptation. In *International conference on machine learning*, pages 1989–1998. PMLR, 2018.

[20] Anthony Hu, Zak Murez, Nikhil Mohan, Sofía Dudas, Jeff Hawke, Vijay Badrinarayanan, Roberto Cipolla, and Alex Kendall. FIERY: future instance prediction in bird's-eye view from surround monocular cameras. *CoRR*, abs/2104.10490, 2021. URL `https://arxiv.org/abs/2104.10490`.

[21] Xun Huang, Ming-Yu Liu, Serge J. Belongie, and Jan Kautz. Multimodal unsupervised image-to-image translation. *CoRR*, abs/1804.04732, 2018. URL `http://arxiv.org/abs/1804.04732`.

[22] Xiang Jiang, Qicheng Lao, Stan Matwin, and Mohammad Havaei. Implicit class-conditioned domain alignment for unsupervised domain adaptation. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 4816–4827. PMLR, 13–18 Jul 2020. URL `http://proceedings.mlr.press/v119/jiang20d.html`.

[23] Amlan Kar, Aayush Prakash, Ming-Yu Liu, Eric Cameracci, Justin Yuan, Matt Rusiniak, David Acuna, Antonio Torralba, and Sanja Fidler. Meta-sim: Learning to generate synthetic datasets. *CoRR*, abs/1904.11621, 2019. URL `http://arxiv.org/abs/1904.11621`.

[24] Mehran Khodabandeh, Arash Vahdat, Mani Ranjbar, and William G Macready. A robust learning approach to domain adaptive object detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 480–490, 2019.

[25] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization, 2014. URL `http://arxiv.org/abs/1412.6980`. cite arxiv:1412.6980Comment: Published as a conference paper at the 3rd International Conference for Learning Representations, San Diego, 2015.

[26] Alex H. Lang, Sourabh Vora, Holger Caesar, Lubing Zhou, Jiong Yang, and Oscar Beijbom. Pointpillars: Fast encoders for object detection from point clouds. *CoRR*, abs/1812.05784, 2018. URL `http://arxiv.org/abs/1812.05784`.

[27] Daiqing Li, Amlan Kar, Nishant Ravikumar, Alejandro F Frangi, and Sanja Fidler. Federated simulation for medical imaging. In *MICCAI*, 2020.

[28] Zachary Lipton, Yu-Xiang Wang, and Alexander Smola. Detecting and correcting for label shift with black box predictors. In *International conference on machine learning*, pages 3122–3130. PMLR, 2018.

[29] Mingsheng Long, Zhangjie Cao, Jianmin Wang, and Michael I Jordan. Conditional adversarial domain adaptation. In *Advances in Neural Information Processing Systems*, pages 1640–1650, 2018.

[30] Sivabalan Manivasagam, Shenlong Wang, Kelvin Wong, Wenyuan Zeng, Mikita Sazanovich, Shuhan Tan, Bin Yang, Wei-Chiu Ma, and Raquel Urtasun. Lidarsim: Realistic lidar simulation by leveraging the real world. *CoRR*, abs/2006.09348, 2020. URL `https://arxiv.org/abs/2006.09348`.

[31] Mehryar Mohri, Afshin Rostamizadeh, and Ameet Talwalkar. *Foundations of machine learning*. MIT press, 2018.

[32] Xingchao Peng, Ben Usman, Neela Kaushik, Judy Hoffman, Dequan Wang, and Kate Saenko. Visda: The visual domain adaptation challenge. *arXiv preprint arXiv:1710.06924*, 2017.

[33] Jonah Philion and Sanja Fidler. Lift, splat, shoot: Encoding images from arbitrary camera rigs by implicitly unprojecting to 3d. *CoRR*, abs/2008.05711, 2020. URL https://arxiv.org/abs/2008.05711.

[34] Aayush Prakash, Shaad Boochoon, Mark Brophy, David Acuna, Eric Cameracci, Gavriel State, Omer Shapira, and Stan Birchfield. Structured domain randomization: Bridging the reality gap by context-aware synthetic data. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 7249–7255. IEEE, 2019.

[35] Xavier Puig, Kevin Ra, Marko Boben, Jiaman Li, Tingwu Wang, Sanja Fidler, and Antonio Torralba. Virtualhome: Simulating household activities via programs. In *CVPR*, 2018.

[36] Charles Ruizhongtai Qi, Hao Su, Kaichun Mo, and Leonidas J. Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. *CoRR*, abs/1612.00593, 2016. URL http://arxiv.org/abs/1612.00593.

[37] Stephan R Richter, Vibhav Vineet, Stefan Roth, and Vladlen Koltun. Playing for data: Ground truth from computer games. In *European conference on computer vision*, pages 102–118. Springer, 2016.

[38] Stephan R. Richter, Hassan Abu AlHaija, and Vladlen Koltun. Enhancing photorealism enhancement, 2021.

[39] Thomas Roddick and Roberto Cipolla. Predicting semantic map representations from images using pyramid occupancy networks. *CoRR*, abs/2003.13402, 2020. URL https://arxiv.org/abs/2003.13402.

[40] German Ros, Laura Sellart, Joanna Materzynska, David Vazquez, and Antonio M Lopez. The synthia dataset: A large collection of synthetic images for semantic segmentation of urban scenes. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3234–3243, 2016.

[41] Kuniaki Saito, Yoshitaka Ushiku, and Tatsuya Harada. Asymmetric tri-training for unsupervised domain adaptation. In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 2988–2997. PMLR, 06–11 Aug 2017. URL http://proceedings.mlr.press/v70/saito17a.html.

[42] J. Scanlon, Kristofer D. Kusano, Tom Daniel, C. Alderson, A. Ogle, Trent Victor, and Waymo. Waymo simulated driving behavior in reconstructed fatal crashes within an autonomous vehicle operating domain. 2021.

[43] Kihyuk Sohn, David Berthelot, Chun-Liang Li, Zizhao Zhang, Nicholas Carlini, Ekin D Cubuk, Alex Kurakin, Han Zhang, and Colin Raffel. Fixmatch: Simplifying semi-supervised learning with consistency and confidence. *arXiv preprint arXiv:2001.07685*, 2020.

[44] Remi Tachet, Han Zhao, Yu-Xiang Wang, and Geoff Gordon. Domain adaptation with conditional distribution matching and generalized label shift. *arXiv preprint arXiv:2003.04475*, 2020.

[45] Mingxing Tan and Quoc Le. EfficientNet: Rethinking model scaling for convolutional neural networks. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 6105–6114. PMLR, 09–15 Jun 2019. URL http://proceedings.mlr.press/v97/tan19a.html.

[46] Shuhan Tan, Xingchao Peng, and Kate Saenko. Class-imbalanced domain adaptation: An empirical odyssey. In *European Conference on Computer Vision*, pages 585–602. Springer, 2020.

[47] Shuhan Tan, Kelvin Wong, Shenlong Wang, Sivabalan Manivasagam, Mengye Ren, and Raquel Urtasun. Scenegen: Learning to generate realistic traffic scenes. *CoRR*, abs/2101.06541, 2021. URL https://arxiv.org/abs/2101.06541.

[48] Jonathan Tremblay, Aayush Prakash, David Acuna, Mark Brophy, Varun Jampani, Cem Anil, Thang To, Eric Cameracci, Shaad Boochoon, and Stan Birchfield. Training deep networks with synthetic data: Bridging the reality gap by domain randomization. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pages 969–977, 2018.

[49] Haoran Wang, Tong Shen, Wei Zhang, Ling-Yu Duan, and Tao Mei. Classes matter: A fine-grained adversarial approach to cross-domain semantic segmentation. In *European Conference on Computer Vision*, pages 642–659. Springer, 2020.

[50] Anqi Joyce Yang, Can Cui, Ioan Andrei Bârsan, Raquel Urtasun, and Shenlong Wang. Asynchronous multi-view SLAM. *CoRR*, abs/2101.06562, 2021. URL https://arxiv.org/abs/2101.06562.

[51] Ze Yang, Siva Manivasagam, Ming Liang, Bin Yang, Wei-Chiu Ma, and Raquel Urtasun. Recovering and simulating pedestrians in the wild. *CoRR*, abs/2011.08106, 2020. URL https://arxiv.org/abs/2011.08106.

[52] Zhenpei Yang, Yuning Chai, Dragomir Anguelov, Yin Zhou, Pei Sun, Dumitru Erhan, Sean Rafferty, and Henrik Kretzschmar. Surfelgan: Synthesizing realistic sensor data for autonomous driving. *CoRR*, abs/2005.03844, 2020. URL https://arxiv.org/abs/2005.03844.

[53] Yuchen Zhang, Tianle Liu, Mingsheng Long, and Michael Jordan. Bridging theory and algorithm for domain adaptation. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 7404–7413, Long Beach, California, USA, 09–15 Jun 2019. PMLR.

[54] Han Zhao, Remi Tachet des Combes, Kun Zhang, and Geoffrey J Gordon. On learning invariant representation for domain adaptation. *arXiv preprint arXiv:1901.09453*, 2019.