Rate-Optimal Online Convex Optimization in Adaptive Linear Control

Abstract

We consider the problem of controlling an unknown linear dynamical system under adversarially-changing convex costs and full feedback of both the state and cost function. We present the first computationally-efficient algorithm that attains an optimal $\sqrt{T}$-regret rate compared to the best stabilizing linear controller in hindsight, while avoiding stringent assumptions on the costs such as strong convexity. Our approach is based on a careful design of non-convex lower confidence bounds for the online costs, and uses a novel technique for computationally-efficient regret minimization of these bounds that leverages their particular non-convex structure.

1 Introduction

We study a general setting of online adaptive linear control, where a learner attempts to stabilize an initially unknown discrete-time linear dynamical system while minimizing its cumulative cost with respect to an arbitrary sequence of convex loss functions. The system dynamics evolve according to

$$x_{t+1} = A_\star x_t + B_\star u_t + w_t,$$

where $x_t \in \mathbb{R}^{d_x}$, $u_t \in \mathbb{R}^{d_u}$ are the (fully observable) system's state and learner's control at time step t, and $w_t \in \mathbb{R}^{d_x}$ is the system noise added at step t which is a zero-mean i.i.d. Gaussian random variable. The matrices $A_\star \in \mathbb{R}^{d_x \times d_x}$ and $B_\star \in \mathbb{R}^{d_x \times d_u}$ are the system parameters, which are assumed to be unknown ahead of time and need to be learned adaptively. The goal is to minimize regret with respect to a sequence of convex loss functions $c_1, \ldots, c_T$ over T time steps, namely, the difference between the learner's cumulative control cost $\sum_{t=1}^{T} c_t(x_t, u_t)$ and the best cumulative cost achieved by a control policy from a given set of benchmark policies.

This general framework encapsulates numerous variations of learning in linear control that have been studied extensively in the literature. When the system parameters are known ahead of time and the costs are fixed and known (convex) quadratics, this amounts to the classical "planning" formulation of linear-quadratic (LQ) stochastic control; see [13]. The special case where the costs are fixed and known quadratics but the system parameters are unknown has been addressed much more recently [1, 21, 30]. This was recently extended to allow for a fixed and known convex cost [32] and later for stochastic i.i.d. costs [16]. On the other hand, the case where the system parameters are known but the quadratic costs are allowed to vary arbitrarily between rounds was first addressed in [20], and has been later extended in various ways to allow for arbitrarily-varying convex costs [6, 7, 34, 14]. In all of these special cases, we now know of efficient algorithms with rate-optimal $\sqrt{T}$ regret guarantees.

For the online adaptive linear control problem in its full generality, however, no regret-optimal algorithms are presently known. The state-of-the-art is due to [34] that achieved $T^{2/3}$-regret using a simple explore-then-exploit strategy: in the exploration phase, it estimates the dynamics parameters

---

by exciting the system with noise; then, in the exploitation phase it runs an online algorithm for known dynamics using the estimated transitions. This simple strategy has also been shown to achieve the optimal $\sqrt{T}$-regret when the online costs are additionally *strongly convex*, demonstrating that the stringent strong convexity assumption allows one to circumvent the challenge of balancing exploration and exploitation in online adaptive linear control.

In this paper, we resolve this gap and give the first rate-optimal algorithm for the general online adaptive linear control problem, accommodating arbitrarily changing general convex (and Lipschitz) costs and unknown system parameters. Our algorithm is computationally efficient and attains a $\sqrt{T}$ regret guarantee with polynomial dependence on the natural parameters of the problem.

Techniques. Our approach builds upon a combination of recent techniques in online linear control. First, we rely on the Disturbance Action Policies (DAPs) of Agarwal et al. [6]: our algorithm generates DAPs that choose the control at each time step as a linear transformation of past noise terms; the DAPs themselves are maintained by online convex optimization algorithms that generate slowly-changing decisions for guaranteeing the stability of the system throughout the learning process. Moreover, since the dynamics are unknown, our algorithm estimates the noise terms on-the-fly, and uses these estimates in place of the true noise vectors (this is akin to a technique in [32]).

Second, following the recent developments of Cassel et al. [16] for the case of stochastic costs, we perform regret minimization with respect to optimistic lower confidence bounds of the online costs. However, these confidence bounds turn out to be inherently nonconvex. To maintain computational efficiency, we adapt a trick of Dani et al. [22] (in the context of stochastic linear bandits) for relaxing the nonconvex objectives so as to assume the form of a minimum of a small number of convex objectives; then, we hedge over multiple copies of online gradient descent as "experts" in a meta-algorithm, where each copy minimizes regret with respect to one of these convex objectives.

Even so, the decisions of the hedging meta-algorithm are random and can thus change abruptly, interfering with the slowly-moving nature of the DAPs that is crucial for the stability of the system. We address this issue by using a lazy version of Follow the Perturbed Leader due to [8] that employs only a small number of switches between experts. Overall, this results in a computationally efficient scheme that maintains the $\sqrt{T}$ regret rate of the individual gradient-based experts.

Related work. The problem of adaptive linear-quadratic control has a long history [e.g., 13]. Recent years have seen a renewed interest in this problem through the modern view of regret minimization— building on classic asymptotic results to obtain finite-time guarantees [1, 4, 10, 23, 24, 27, 31]. More recently [21, 30] provided polynomial-time algorithms obtaining an optimal $\sqrt{T}$ regret rate. The optimality of the $\sqrt{T}$ rate was proved concurrently by [15, 33].

More recently, [32] gave an efficient algorithm with $\sqrt{T}$ regret for learning the dynamics under a fixed known convex cost. [32] also observed that the problem of learning both dynamics and stochastic convex costs under bandit feedback is reducible to an instance of stochastic bandit convex optimization for which complex, yet polynomial-time, generic algorithms exist [5]. Cassel et al. [16] later study the problem of learning the dynamics and stochastic convex costs under full-information feedback. Unlike the approach of [32], their algorithm is based on an "optimism in the face of uncertainty" principle and is thus conceptually simpler and more efficient to implement.

Our approach relies on the standard assumption that the controller is provided with some initial stabilizing policy. First proposed in [23], such an assumption enables to obtain regret that is polynomial in the problem dimensions, and was later shown to be necessary by [18].

Past work has also considered adaptive LQG control, namely linear-quadratic control under partial observability of the state [for example, 34]. However, it turned out that in the stochastic setting, learning the optimal partial-observation linear controller is in a sense easier than learning the full-observation controller, and in fact, it is possible to obtain $\mathrm{poly}(\log T)$ regret for adaptive LQG [28]. This result is facilitated by simplifying assumptions on both the noise distribution as well as the benchmark policy, assumptions which we do not make in this work.

Most works on regret minimization in adaptive control are model-based; meaning, the algorithm attempts to estimate the model parameters. Previous literature also considered the alternative approach of model-free control [e.g., 3, 17, 25, 29, 35]. These works, however, rely heavily on the assumption of quadratic strongly-convex costs and do not apply to general convex costs.

Lastly, [14, 26, 32] consider control under bandit feedback. These results are unfortunately impeded by the state-of-the-art in Bandit Convex Optimization, that is either not efficient in practice (namely, high-degree polynomial runtime) or requires further assumptions on the curvature of the cost functions. For this reason we focus here on full-information feedback, with the hope that our techniques can be adapted to bandit feedback in subsequent work, contingent on future advancements in BCO.

2 Preliminaries

2.1 Linear control background

A discrete-time linear control system is one whose dynamics are governed by the following rule:

$$x_{t+1} = A_\star x_t + B_\star u_t + w_t,$$

where $A_\star \in \mathbb{R}^{d_x \times d_x}$, $B_\star \in \mathbb{R}^{d_x \times d_u}$, and where $w_t \in \mathbb{R}^{d_x}$ is zero-mean i.i.d. In the planning version of the problem the controller knows $A_\star, B_\star$ and, at each time t, can choose u_t as a function of $x_1, \ldots, x_t$. After choosing u_t, the controller incurs a known cost $c(x_t, u_t)$. Classic results pertain to quadratic costs, and state that the control rule that minimizes the steady state cost $J(\pi) = \lim_{T \to \infty} \mathbb{E}_\pi [\frac{1}{T} \sum_{t=1}^T c(x_t, u_t)]$, chooses $u_t = K x_t$ for some matrix $K \in \mathbb{R}^{d_u \times d_x}$. Moreover, the optimal rule $\pi_\star$ stabilizes the system, implying that $J(\pi_\star)$ is finite and well-defined for any quadratic cost function.

We require the following notion of strong stability [20], which is standard in the literature and whose purpose is to quantify the classic notion of (asymptotic) stability.

Definition 1 (Strong stability). A controller K for the system $(A_\star, B_\star)$ is (κ, γ)−strongly stable $(\kappa \geq 1, 0 < \gamma \leq 1)$ if there exist matrices Q, L such that $A_\star + B_\star K = Q L Q^{-1}$, $\|L\| \leq 1 - \gamma$, and $\|K\|, \|Q\|\|Q^{-1}\| \leq \kappa$.

2.2 Problem setup

We address the problem of controlling an unknown linear dynamical system subject to general adversarial convex costs with full state and cost observation. In particular, the system parameters $A_\star$, $B_\star$ are initially unknown and the learner repeatedly interacts with the system as follows:

(1) The player observes state x_t;
(2) The player chooses control u_t;
(3) The player observes the cost function $c_t : \mathbb{R}^{d_x} \times \mathbb{R}^{d_u} \to \mathbb{R}$, and incurs cost $c_t(x_t, u_t)$.

Note that $(w_t)_{t=1}^\infty$ are unobserved, and the cost c_t is revealed only after selecting u_t. Our goal is to minimize regret with respect to any policy π in a benchmark policy class Π. To that end, denote by x_t^π, u_t^π the state and action sequence resulting when following a policy π; then the regret compared to π is defined as

$$\text{regret}_T(\pi) = \sum_{t=1}^T c_t(x_t, u_t) - c_t(x_t^\pi, u_t^\pi),$$

and we seek to bound this quantity with high probability for a fixed $\pi \in \Pi$. We focus on the benchmark policy class of strongly stable linear policies that choose $u_t = K x_t$. i.e.,

$$\Pi_{\text{lin}} = \{K \in \mathbb{R}^{d_u \times d_x} \ : \ K \text{ is } (\kappa, \gamma)\text{-strongly stable}\}.$$

We make the following assumptions on our learning problem:

- **Non-stochastic convex and Lipschitz costs.** The costs c_t are arbitrarily determined by an oblivious adversary[1] such that each $c_t(x, u)$ is convex in the pair (x, u) and for any $(x, u), (x', u')$ we have $|c_t(x, u) - c_t(x', u')| \leq \|(x - x', u - u')\|$;[2]
- **i.i.d. Gaussian noise.** $(w_t)_{t=1}^T$ is a sequence of i.i.d. random variables such that $w_t \sim \mathcal{N}(0, \sigma^2 I)$;
- **Stabilizable system.** $A_\star$ is (κ, γ)−strongly stable, and $\|B_\star\| \leq R_B$.

---

[1] An oblivious adversary does not use past random choices of the learner to select its loss functions.

[2] In the supplementary material we also explain how to accommodate quadratic losses via an appropriate choice of a normalizing constant.

Note the assumption that $A_\star$ is strongly stable is without loss of generality. Otherwise, given access to a stabilizing controller K_0, we show in the supplementary material a generic black-box reduction that takes any learning algorithm that assumes strongly-stable $A_\star$, augments its observations and adds $K_0 x_t$ to its predicted actions. This essentially replaces $A_\star$ with $A_\star + B_\star K_0$, which is $(\kappa, \gamma)-$strongly stable as desired, and only incurs a 2κ multiplicative factor in the regret.

2.3 Disturbance Action Policies

We use the, now standard, class of Disturbance Action Policies (DAPs) first proposed by [6]. This class is parameterized by a sequence of matrices $\{M^{[h]} \in \mathbb{R}^{d_u \times d_x}\}_{h=1}^H$. For brevity of notation, these are concatenated into a single matrix $M \in \mathbb{R}^{d_u \times H d_x}$ defined as $M = \left(M^{[1]} \cdots M^{[H]}\right)$. A DAP π_M chooses actions

$$u_t = \sum_{h=1}^H M^{[h]} w_{t-h},$$

where recall that the w_t are system disturbances. Consider the benchmark policy class[3]

$$\Pi_{\text{DAP}} = \{\pi_M \ : \ \|M\|_F \le R_{\mathcal{M}}\}.$$

There are two main reasons for considering the DAP parameterization. First, the loss functions are convex in M, a fact which is generally untrue for K in a linear policy $u_t = K x_t$. This paves the way for tools from the online convex optimization literature. Second, as shown in [6, Lemma 5.2], if $H \in \Omega(\gamma^{-1} \log T)$ and $R_{\mathcal{M}} \in \Omega(\kappa^2 \sqrt{d_u/\gamma})$ then Π_{DAP} is a good approximation for Π_{lin} in the sense that a regret guarantee with respect to Π_{DAP} gives the same guarantee with respect to Π_{lin} up to a constant additive factor. In light of the above, our regret guarantee will be given with respect to Π_{DAP}.

Bounded memory representation. As observed in recent literature, the linear dynamics have an infinitely long memory, i.e., all past actions have some effect on the current state, and as such on the losses. However, due to the stability of $A_\star$, the effective memory of the system, H, is essentially a constant. To see this, unroll the transition model to get that

$$x_t = A_\star^H x_{t-H} + \sum_{i=1}^H \left(A_\star^{i-1} B_\star u_{t-i} + A_\star^{i-1} w_{t-i}\right) = A_\star^H x_{t-H} + \Psi_\star \tilde{\rho}_{t-1} + w_{t-1}, \tag{1}$$

where $\Psi_\star = [A_\star^{H-1} B_\star, \ldots, A_\star B_\star, B_\star, A_\star^{H-1}, \ldots, A_\star] \in \mathbb{R}^{d_x \times d_\Psi}$ and $\tilde{\rho}_t = [u_{t-H}^\mathsf{T}, \ldots, u_t^\mathsf{T}, w_{t-H}^\mathsf{T}, \ldots, w_{t-1}^\mathsf{T}]^\mathsf{T} \in \mathbb{R}^{d_\Psi}$, where $d_\Psi := H d_u + (H-1) d_x$. Now, since $A_\star$ is strongly stable, the term $A_\star^H x_{t-H}$ quickly becomes negligible. Following the notation set by [16], this observation is combined with the DAP policy parameterization to define the following bounded memory representations. For an arbitrary sequence of disturbances $w = \{w_t\}_{t \ge 1}$ define

$$u_t(M; w) = \sum_{h=1}^H M^{[h]} w_{t-h};$$

$$P(M) = \begin{pmatrix} M^{[H]} & M^{[H-1]} & & \cdots & & M^{[1]} & & & \\ & M^{[H]} & M^{[H-1]} & & \cdots & & M^{[1]} & & \\ & \ddots & \ddots & & & \ddots & & \ddots & \\ & & M^{[H]} & M^{[H-1]} & & \cdots & & M^{[1]} \\ & & & I & & & & \\ & & & & I & & & \\ & & & & & \ddots & & \\ & & & & & & I \end{pmatrix};$$

$$\rho_t(M; w) = (u_{t+1-H}(M; w)^\mathsf{T}, \ldots u_t(M; w)^\mathsf{T}, w_{t+1-H}, \ldots, w_{t-1})^\mathsf{T} = P(M) w_{t+1-2H:t-1};$$

$$x_t(M; \Psi, w) = \Psi \rho_{t-1}(M; w) + w_{t-1}.$$

Notice that u_t, ρ_t, x_t do not depend on the entire sequence w, but only $w_{t-H:t-1}, w_{t+1-2H:t-1}$, and $w_{t-2H:t-1}$ respectively. Importantly, this means that we can compute these functions with knowledge of only the last (at most) $2H$ disturbances. While this notation does not reveal this fact explicitly, it helps with both brevity and clarity.

---

[3]We note that a more common definition uses $\sum_{h=1}^H \|M^{[h]}\|$ to measure the size of the class. We chose the Frobenius norm for simplicity of the analysis, but replacing it would not change the results significantly.

3 Algorithm and Main Result

In this section we present our algorithm for regret minimization in linear systems with unknown dynamics and adversarial convex costs; see Algorithm 1.

Algorithm 1 OCO in Adaptive Linear Control

1: **input**: confidence parameter δ, memory length H, optimism parameter α, regularization parameters λ_Ψ, λ_w, learning rate η_G, noise bound W.
2: **set** $i = 1, \tau = 1, V_1 = \lambda_\Psi I, M_1 = 0$ and $\hat{w}_t = 0, \tilde{w}_t, u_t = 0$ for all $t < 1$.
3: **for** $t = 1, 2, \ldots, T$ **do**
4:      **play** $u_t = \sum_{i=1}^{H} M_t^{[h]} \hat{w}_{t-h}$.
5:      **set** $V_{t+1} = V_t + \rho_t \rho_t^\mathsf{T}$ for $\rho_t = (u_{t+1-H}^\mathsf{T}, \ldots, u_t^\mathsf{T}, \hat{w}_{t+1-H}^\mathsf{T}, \ldots, \hat{w}_{t-1}^\mathsf{T})^\mathsf{T}$.
6:      **observe** x_{t+1} and cost function c_t.
7:      **calculate**

$$(A_t \ B_t) = \underset{(A\ B) \in \mathbb{R}^{d_x \times (d_x+d_u)}}{\arg\min} \sum_{s=1}^{t} \|(A\ B)z_s - x_{s+1}\|^2 + \lambda_w \|(A\ B)\|_F^2, \quad \text{where } z_s = \begin{pmatrix} x_s \\ u_s \end{pmatrix}.$$

8:      **estimate noise** $\hat{w}_t = \Pi_{B_2(W)}[x_{t+1} - A_t x_t - B_t u_t]$.
9:      **if** $\det(V_{t+1}) > 2\det(V_{\tau_i})$ **then**
10:          **start new epoch**: $i = i + 1, \tau_i = t + 1$.
11:          **estimate system parameters**

$$\Psi_{\tau_i} = \underset{\Psi \in \mathbb{R}^{d_x \times d_\Psi}}{\arg\min} \left\{ \sum_{s=1}^{t} \|\Psi \rho_s - x_{s+1}\|^2 + \lambda_\Psi \|\Psi\|_F^2 \right\}.$$

12:          **initialize** $\mathcal{A}$ - new instance of $\text{BFPL}^*_{\delta/6}$.
13:      **else**
14:          **sample** $\tilde{w}_t \sim \mathcal{N}(0, \sigma^2 I_{d_x})$.
15:          **define** expert loss functions: $\forall k \in [d_\Psi] \times [d_\Psi], \chi \in \{\pm 1\}$

$$\tilde{f}_t(M; k, \chi) = c_t(x_t(M; \Psi_{\tau_i}, \tilde{w}), u_t(M; \tilde{w})) - \alpha \sigma \chi \cdot \left(V_{\tau_i}^{-1/2} P(M) \right)_k.$$

16:          **define** loss vector $\tilde{\ell}_t \in \mathbb{R}^{2d_\Psi^2}$ s.t. $(\tilde{\ell}_t)_{k,\chi} = \tilde{f}_t(M_t(k, \chi); k, \chi) / (4R_\mathcal{M} W H \|(\Psi_{\tau_i}\ I)\|)$.
17:          **update** experts: $\forall k \in [d_\Psi] \times [d_\Psi], \chi \in \{\pm 1\}$

$$M_{t+1}(k, \chi) = \Pi_\mathcal{M} \left[M_t(k, \chi) - \eta_G \nabla_M \tilde{f}_t(M_t(k, \chi); k, \chi) \right].$$

18:          **update** prediction $(k_{t+1}, \chi_{t+1}) = \mathcal{A}(\tilde{\ell}_t)$ and **set** $M_{t+1} = M_{t+1}(k_{t+1}, \chi_{t+1})$

The algorithm mediates between least squares estimation of the system dynamics (Lines 7 and 11), and optimizing the policy w.r.t. to adversarially-changing cost functions. For OCO, the algorithm uses a combination of Online Gradient Descent [36] (Line 17) and BFPL* [8] (Line 12)—a high-probability experts algorithm that also guarantees an overall small number of switches. Our algorithm uses Disturbance Action Policy parameterization (Line 4; see Section 2.3 and notations therein), and feeds the aforementioned online optimization algorithms with lower confidence bounds of the online costs. See below for further details on the algorithm's operation.

We have the following guarantee for our algorithm. The proof is deferred to the supplementary material.

Theorem 2 (Simplified version of Theorem 10 in the supplementary material). *Let* $\delta \in (0, 1)$ *and suppose that we run Algorithm 1 with parameters* $R_\mathcal{M}, R_B \geq 1$ *and for proper choices of* $W, H, \lambda_w, \lambda_\Psi, \eta_G, \alpha$. *If* $T \geq 8$ *then with probability at least* $1 - \delta$ *for all* $\pi \in \Pi_{\text{DAP}}$

$$\text{regret}_T(\pi) \leq \text{poly}(\kappa, \gamma^{-1}, \sigma, R_B, R_\mathcal{M}, d_x, d_u, \log(T/\delta))\sqrt{T}.$$

Our algorithm is comprised of multiple components working in tandem. We now give a brief overview of each of the components and how they play together.

3.1 Prerequisites: system estimation and DAP parameterization

Parameter estimation: The algorithm proceeds in epochs. At the beginning of each epoch, it estimates the unrolled model via least squares using all past observations (Line 11), and the estimate Ψ_{τ_i} is then kept fixed throughout the epoch. The epoch ends when the determinant of V_t is doubled (Line 9); intuitively, when the confidence of the unrolled model increases substantially.[4] Throughout the epoch, the algorithm maintains estimates of the transition noise $(\hat{w}_t)_{t=1}^T$ (Lines 7 and 8). We observe that these noise estimates are essentially produced for "free" and no explicit exploration is needed.

DAP implementation: While the benefits of Π_{DAP} are clear, notice that it cannot be implemented as is since we do not have access to the system disturbances w_t nor can we accurately recover them due to the uncertainty in the transition model. Similarly to previous works, our algorithm thus uses estimated disturbances $\hat{w}_t$ to compute its actions. At each time step t, the algorithm chooses u_t as a linear function of the past H noise estimates, and parameterized by M_t (Line 4). M_t itself is updated using OCO on surrogate cost functions that are formed as a composition between $c_t(x, u)$ and the bounded memory representations $u_t(M; \hat{w}), x_t(M; \Psi_{\tau_i}, \hat{w})$, which implicit assume that M_t was kept fixed for the last H time steps. It is therefore crucial that these representations closely reflect the state and action that are actually observed, hence the OCO procedure has to make sure that the sequence $(M_t)_{t=1}^T$ changes slowly (more on this below).

Construction of lower confidence bounds: The algorithm uses the estimated unrolled model to minimize regret with respect to lower confidence bounds of the form:

$$c_t(x_t(M; \Psi_{\tau_i}, \hat{w}), u_t(M; \hat{w})) - \alpha' \cdot \|V_{\tau_i}^{-1/2} \rho_{t-1}(M; \hat{w})\|. \tag{2}$$

This lower confidence bound follows immediately by combining the Lipschitzness of c_t and standard self-normalizing concentration bounds [1]. In our analysis, we show that it indeed lower bounds $c_t(x_t, u_t)$. Such lower confidence bounds are used extensively in multi-armed bandit and reinforcement learning literature to efficiently combine exploration and exploitation [11, 12]. Intuitively, their minimization steers the resulting policy towards state-action pairs that either yield low cost, or are insufficiently explored.

3.2 Key idea: making the algorithm efficient

The functions in Eq. (2) are, unfortunately, nonconvex (being a difference of two convex functions), and thus cannot be used in OCO algorithms in their current form. However, we overcome this by relaxing the functions in Eq. (2); we do so in two steps. First, we move to an expected, amortized notion of optimism. We can do this since since $\hat{w} \approx w$, which are i.i.d, and thus standard concentration arguments imply that the realized bonus term is close to its conditional expectation, which takes the form:

$$\sqrt{\mathbb{E}\|V_{\tau_i}^{-1/2} \rho_{t-1}(M; w)\|^2} = \sigma \|V_{\tau_i}^{-1/2} P(M)\|_F.$$

Second, building on a trick from [22], we further bound $\|V_{\tau_i}^{-1/2} P(M)\|_F \leq d_\Psi \|V_{\tau_i}^{-1/2} P(M)\|_\infty$ (where $\|\cdot\|_\infty$ is the entry-wise matrix infinity norm). Due to an adaptivity issue (more on this below), we also replace the estimated noises $\hat{w}$ in the cost term with random simulated noises $\tilde{w} \sim \mathcal{N}(0, \sigma^2 I)$. After this relaxation, the resulting $\tilde{f}_t$ can be written as a minimum of convex function of the form

$$\tilde{f}_t(M; k, \chi) = c_t(x_t(M; \Psi_{\tau_i}, \hat{w}), u_t(M; \hat{w})) - \alpha \sigma \chi \cdot (V_{\tau_i}^{-1/2} P(M))_k, \tag{3}$$

where $\alpha = d_\Psi \alpha'$. Crucial to this trick is the fact that, unlike Eq. (2), the linearized non-convex term is independent of the time index t. This observation yields computationally-efficient regret minimization via a two-tier approach described as follows. We run a different copy of Online Gradient Descent [36] for each value of k, χ, maintaining a different set of DAP parameters $M_t(k, \chi)$, and fed with $\tilde{f}_t(\cdot; k, \chi)$ (Line 17). On top of the OGD algorithms, we run an experts meta-algorithm to minimize $\tilde{f}_t(M_t(k, \chi); k, \chi)$ over k, χ (Line 18), treating the output of each OGD algorithm as an expert.

Observe that having initially taken expectation over the noises yields an exploration bonus term that, for fixed M, is fixed throughout each epoch. This makes sure that our OCO algorithms, that are restarted at every epoch, can compare against $M_\star$ (the best in hindsight) with k and χ being fixed at the start of the epoch.

---

[4]Concretely, the volume of the confidence ellipsoid around the unrolled model decreases by a constant factor.

3.3 Additional challenges

Stabilizing the meta-algorithm: Our hedging approach nevertheless comes at a price. The choices of the meta-algorithm are inherently random, thus M_t might change abruptly between consecutive rounds (recall that DAP require slowly-changing M_t). We therefore use a version of Follow the Lazy Leader (BFPL*; [8]) that guarantees, with high probability, both no-regret and a small number of switches. The small number of switches in conjunction with the fact that each of the expert algorithms generate slowly-changing decisions, guarantee that M_t itself is slowly-changing overall.

Mitigating adaptivity in costs: Even so, the guarantees of BFPL* hold only against *oblivious* adversaries (and this limitation is inherent, as [8] discuss extensively), yet the loss sequence constituting of the functions in Eq. (3) is unfortunately *not* oblivious. This is because the noise estimate $\hat{w}$ were generated using policies derived from previous choices of BFPL*. We overcome this hindrance relying on the fact that the noise vectors are drawn from a known (Gaussian) distribution. This allows to sample i.i.d. copies of the noise vectors $\tilde{w}$ (Line 14) that we use in $\tilde{w}$ instead of $\hat{w}$, arriving at the functions defined in Line 15, and ensuring that BFPL* receives obliviously-generated losses.

4 Analysis

In this section we give a (nearly) complete proof of Theorem 2 in a simplified setup with $A_\star = 0$, inspired by [32]. The analysis in the general case is significantly more technical and thus deferred from this extended abstract (see the supplementary material for full details).

Suppose that $A_\star = 0$ and thus $x_{t+1} = B_\star u_t + w_t$, assume that $c_t(x, u) = c_t(x)$, i.e., the costs do not depend on u, and aim to minimize the pseudo regret,

$$\max_{u: \|u\| \leq R_u} \sum_{t=1}^{T} [J_t(B_\star u_t) - J_t(B_\star u)],$$

where $J_t(x) = \mathbb{E}_w c_t(x + w)$, is the expected instantaneous cost, which can be computed from $c_t(x)$ for a known noise distribution. The resulting problem is an instance of the following variant of online convex optimization, which we now define with clean notation as to avoid confusion with our general setting.

4.1 Simplified setting: OCO with a Hidden Linear Transform

Consider the following setting of online convex optimization. Let $\mathcal{S} \subseteq \mathbb{R}^{d_a}$ be a convex decision set. At round t the learner

   (i) predicts $a_t \in \mathcal{S}$;
   (ii) observes cost function $\ell_t : \mathbb{R}^{d_y} \to \mathbb{R}$ and state $y_{t+1} = Q_\star a_t + \epsilon_t$;
   (iii) incurs cost $\ell_t(Q_\star a_t)$.

We have that $\epsilon_t \in \mathbb{R}^{d_y}$ are i.i.d. noise terms, $Q_\star \in \mathbb{R}^{d_y \times d_a}$ is an unknown linear transform, and $y_t \in \mathbb{R}^{d_y}$ are noisy observations. The cost functions are chosen by an oblivious adversary, and we consider minimizing the regret, defined as

$$\text{regret}_T = \max_{a \in \mathcal{S}} \sum_{t=1}^{T} [\ell_t(Q_\star a_t) - \ell_t(Q_\star a)].$$

Assumptions. We make the following assumptions:

- $\ell_t(\cdot)$ are convex and 1−Lipschitz;
- There exist known $W, R_Q \geq 0$ such that $\|\epsilon_t\| \leq W$, and $\|Q_\star\| \leq R_Q$.
- For all $a \in \mathcal{S}$ we have $\|a\| \leq R_a/2$.

Algorithm. Our algorithm for this simplified setup is detailed in Algorithm 2. Unlike the full control setting, the adversarial costs here have no memory, thus enable the following simplifications compared to Algorithm 1. First, we can forgo the DAP parameterization and directly optimize the prediction a_t. This both removes the need to estimate the disturbances, and simplifies the construction of the lower confidence bound. Moreover, the lack of memory obviates the need to make our predictions change slowly over time, and we replace the BFPL* sub-routine with Multiplicative Weights (MW) [see 9].

Algorithm 2 OCO with a hidden linear transform

1: **input:** optimism parameter α, regularizer λ, learning rates η_G, η_M
2: **set:** $V_1 = \lambda I, \widehat{Q}_1 = 0, i = 1, \tau_1 = 1$, and $a_1(k, \chi) \in \mathcal{S}, p_t(k, \chi) = 1/2d_a \ \ \forall k \in [d_a], \chi \in \{\pm 1\}$.
3: **for** $t = 1, 2, \ldots, T$ **do**
4:      **draw** $(k_t, \chi_t) \sim p_t$, and **play** $a_t(k_t, \chi_t)$.
5:      **observe** $y_{t+1} = Q_\star a_t + w_t$ and cost function ℓ_t, and **set** $V_{t+1} = V_t + a_t a_t^\mathsf{T}$.
6:      **if** $\det(V_{t+1}) > 2 \det(V_{\tau_i})$ **then**
7:          **start new** episode $i = i+1, \tau_i = t+1$, and **set** $p_{t+1}(k, \chi) = 1/2d_a, a_{t+1}(k, \chi) = a_t(k, \chi)$.
8:          **estimate** parameters: $\widehat{Q}_{\tau_i} = \arg\min_{Q \in \mathbb{R}^{d_y \times d_a}} \sum_{s=1}^t \{\|Qa_s - y_{s+1}\|^2 + \lambda \|Q\|_F^2\}$.
9:      **else**
10:          **define** expert loss functions: $\bar{\ell}_t(a; k, \chi) = \ell_t(\widehat{Q}_{\tau_i} a) - \alpha \chi \cdot (V_{\tau_i}^{-1/2} a)_k$.
11:          **update** experts: $a_{t+1}(k, \chi) = \Pi_\mathcal{S} [a_t(k, \chi) - \eta_G \nabla_a \bar{\ell}_t(a_t(k, \chi); k, \chi)]$.   ▷ OGD
12:          **update** prediction: $p_{t+1}(k, \chi) \propto p_t(k, \chi) \exp(-\eta_M \bar{\ell}_t(a_t(k, \chi); k, \chi))$.   ▷ MW

4.2 Analysis

The main result of this section bounds the regret of Algorithm 2 with high probability.

Theorem 3. *Let $\delta \in (0, 1)$ and suppose that we run Algorithm 2 with parameters*

$$\eta_G = \frac{R_a}{(2\alpha R_a^{-1} + R_Q)\sqrt{T}}, \eta_M = \frac{\sqrt{\log(2d_a)}}{2(2\alpha + R_a R_Q)\sqrt{T}}, \lambda = R_a^2, \alpha = \sqrt{d_a}\Big(W d_y \sqrt{8 \log \tfrac{2T}{\delta}} + \sqrt{2} R_a R_Q\Big).$$

If $T \geq 8$ then with probability at least $1 - \delta$,

$$regret_T \leq 77 d_a^{3/2}\Big(W d_y \sqrt{8 \log \tfrac{2T}{\delta}} + R_a R_Q\Big)\sqrt{T \log^2 \frac{4 d_a T^2}{\delta}}.$$

The proof of Theorem 3 is composed of two main lemmas. Similarly to the control setting, we first
define an optimistic loss

$$\bar{\ell}_t(a) = \ell_t(\widehat{Q}_{\tau_{i(t)}} a) - \alpha \|V_{\tau_{i(t)}}^{-1/2} a\|_\infty,$$

where $i(t) = \max\{i : \tau_i \leq t\}$. The following lemma shows that the optimistic loss lower bounds the
true loss, and bounds the error between the two (See proof in the supplementary material).

Lemma 4 (optimism). *Suppose that $\sqrt{d_a}\|\widehat{Q}_{\tau_{i(t)}} - Q_\star\|_{V_{\tau_{i(t)}}} \leq \alpha$. Then for any $a \in \mathbb{R}^{d_a}$,*

$$\bar{\ell}_t(a) \leq \ell_t(Q_\star a) \leq \bar{\ell}_t(a) + 2\alpha \sqrt{a^\mathsf{T} V_{\tau_{i(t)}}^{-1} a}.$$

Next, the following result bounds the regret with respect to the optimistic cost functions.

Lemma 5. *Define $G_i = \|\widehat{Q}_{\tau_i}\| + \alpha \lambda^{-1/2}$ and $\bar{G} = 2\alpha \lambda^{-1/2} + R_Q$. With probability at least $1 - \delta$:*

$$\sum_{t=\tau_i}^{\tau_{i+1}-1} (\bar{\ell}_t(a_t) - \bar{\ell}_t(a)) \leq 3R_a\Big(\bar{G} + \bar{G}^{-1} G_i^2\Big)\sqrt{T \log \frac{2 d_a T}{\delta}}.$$

Proof. First, notice that $a_t(k, \chi)$ are the result of running Online Gradient Descent (OGD) on the
functions $\bar{\ell}_t(\cdot; k, \chi)$, which are G_i Lipschitz. A classic result (see Lemma 23 in the supplementary
material) then gives us that for all $a \in \mathcal{S}$ and $\tau_i \leq s \leq T$

$$\sum_{t=\tau_i}^{s} \bar{\ell}_t(a_t(k, \chi); k, \chi) - \bar{\ell}_t(a; k, \chi) \leq R_a(\bar{G} + G_i^2 \bar{G}^{-1})\sqrt{T}.$$

Next, note that MW is invariant to a constant shift in the loss vectors. Letting $a_0 \in \mathcal{S}$ be arbi-
trary, we have that p_t is updated according to the MW rule with the loss of each expert being
$\bar{\ell}_t(a_t(k, \chi); k, \chi) - \ell_t(\widehat{Q}_{\tau_i} a_0)$. Using the Lipschitz property of ℓ_t, these are bounded as

$$|\bar{\ell}_t(a_t(k, \chi); k, \chi) - \ell_t(\widehat{Q}_{\tau_i} a_0)| \leq \|\widehat{Q}_{\tau_i}\| \|a_t(k, \chi) - a_0\| + \alpha \lambda^{-1/2} \|a_t(k, \chi)\| \leq G_i R_a.$$

A standard result (Lemma 24 in the supplementary material) thus gives us that with probability at least $1 - \delta$

$$\sum_{t=\tau_i}^{s} \bar{\ell}_t(a_t(k_t, \chi_t); k_t, \chi_t) - \bar{\ell}_t(a_t(k, \chi); k, \chi) \le R_a\left(\bar{G} + \bar{G}^{-1}G_i^2\right)\sqrt{6T \log \frac{2d_a T}{\delta}},$$

for all $k \in [d_a], \chi \in \{-1, 1\}$, and $\tau_i \le s \le T$.

Now, let $k_t^*(a), \chi_t^*(a)$ be such that $\bar{\ell}_t(a) = \bar{\ell}_t(a; k_t^*(a), \chi_t^*(a))$ for all $\tau_i \le t < \tau_{i+1}$. Importantly, notice that $k_t^*(a), \chi_t^*(a)$ are independent of the time index t. This is because the minimum in $\bar{\ell}_t$ is taken over the optimism term, which is independent of t inside a given epoch. For ease of notation, the following will omit the dependence of k^*, χ^* on a, which will be kept as a fixed (arbitrary) comparator. Combining the above, with probability $\ge 1 - \delta$ we have that for all $a \in \mathcal{S}$:

$$
\begin{aligned}
\sum_{t=\tau_i}^{\tau_{i+1}-1} \bar{\ell}_t(a_t) - \bar{\ell}_t(a) &\le \sum_{t=\tau_i}^{\tau_{i+1}-1} \bar{\ell}_t(a_t; k_t, \chi_t) - \bar{\ell}_t(a; k^*, \chi^*) && (\bar{\ell}_t(\cdot) \le \bar{\ell}_t(\cdot; k, \chi)) \\
&= \sum_{t=\tau_i}^{\tau_{i+1}-1} \left(\bar{\ell}_t(a_t(k_t, \chi_t); k_t, \chi_t) - \bar{\ell}_t(a_t(k^*, \chi^*); k^*, \chi^*)\right) \\
&\quad + \sum_{t=\tau_i}^{\tau_{i+1}-1} \left(\bar{\ell}_t(a_t(k^*, \chi^*); k^*, \chi^*) - \bar{\ell}_t(a; k^*, \chi^*)\right) \\
&\le 3R_a\left(\bar{G} + \bar{G}^{-1}G_i^2\right)\sqrt{T \log \frac{2d_a T}{\delta}}. && \blacksquare
\end{aligned}
$$

We are now ready to prove Theorem 3. We focus here on the main ideas, deferring some details to the supplementary material.

Proof of Theorem 3. We decompose the regret as

$$\text{regret}_T(a) \le \underbrace{\sum_{t=1}^{T} \ell_t(Q_\star a_t) - \bar{\ell}_t(a_t)}_{R_1} + \underbrace{\sum_{t=1}^{T} \bar{\ell}_t(a_t) - \bar{\ell}_t(a)}_{R_2} + \underbrace{\sum_{t=1}^{T} \bar{\ell}_t(a) - \ell_t(Q_\star a)}_{R_3},$$

and conclude the proof by bounding each term on the following good event. Suppose Lemma 5 holds for all epochs with $\delta/2T$, and that $\sqrt{d_a}\|\widehat{Q}_t - Q_\star\|_{V_t} \le \alpha$ for all $t \le T$, which follows from a standard least squares estimation bound (Lemma 7). Taking a union bound, this event holds with probability at least $1 - \delta$. We conclude that Lemma 4 holds and thus $R_3 \le 0$. Moreover, we get that

$$R_1 \le \sum_{i=1}^{N} \sum_{t=\tau_i}^{\tau_{i+1}-1} 2\alpha \sqrt{a_t^\intercal V_{\tau_i}^{-1} a_t} \le 2\alpha \sum_{t=1}^{T} \sqrt{2 a_t^\intercal V_t^{-1} a_t} \le 2\alpha \sqrt{2T \sum_{t=1}^{T} a_t^\intercal V_t^{-1} a_t} \le 2\alpha \sqrt{10 T d_a \log T},$$

where the second inequality uses Lemma 27 of [21], which states that for $V_1 \succeq V_2 \succeq 0$ we have $V_1 \preceq V_2(\det(V_1)/\det(V_2))$, the third is due to Jensen's inequality, and the fourth is a standard algebraic argument (Lemma 8).

Now, an immediate corollary (see Eq. (4)) of the least square error bound is that $\|\widehat{Q}_t\| \le \alpha\lambda^{-1/2} + R_Q$. We thus have that $G_i \le \bar{G}$ for all $i \le N$. Next, notice that the number of epochs satisfies $N \le 2d_a \log T$ (Lemma 9). We conclude that

$$
\begin{aligned}
R_2 &= \sum_{i=1}^{N} \sum_{t=\tau_i}^{\tau_{i+1}-1} \left(\bar{\ell}_t(a_t) - \bar{\ell}_t(a)\right) \\
&\le \sum_{i=1}^{N} 3R_a\left(\bar{G} + \bar{G}^{-1}G_i^2\right)\sqrt{T \log \frac{4d_a T^2}{\delta}} && (\text{Lemma 5}) \\
&\le 12 d_a\left(2\alpha + R_a R_Q\right)\sqrt{T \log^2 \frac{4d_a T^2}{\delta}}. && \blacksquare
\end{aligned}
$$

References

[1] Y. Abbasi-Yadkori and C. Szepesvári. Regret bounds for the adaptive control of linear quadratic systems. In *Proceedings of the 24th Annual Conference on Learning Theory*, pages 1–26, 2011.

[2] Y. Abbasi-Yadkori, D. Pál, and C. Szepesvári. Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems*, pages 2312–2320, 2011.

[3] Y. Abbasi-Yadkori, N. Lazic, and C. Szepesvári. Model-free linear quadratic control via reduction to expert prediction. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 3108–3117. PMLR, 2019.

[4] M. Abeille and A. Lazaric. Improved regret bounds for thompson sampling in linear quadratic control problems. In *International Conference on Machine Learning*, pages 1–9. PMLR, 2018.

[5] A. Agarwal, D. P. Foster, D. J. Hsu, S. M. Kakade, and A. Rakhlin. Stochastic convex optimization with bandit feedback. *Advances in Neural Information Processing Systems*, 24, 2011.

[6] N. Agarwal, B. Bullins, E. Hazan, S. Kakade, and K. Singh. Online control with adversarial disturbances. In *International Conference on Machine Learning*, pages 111–119. PMLR, 2019.

[7] N. Agarwal, E. Hazan, and K. Singh. Logarithmic regret for online control. In *Advances in Neural Information Processing Systems*, pages 10175–10184, 2019.

[8] J. Altschuler and K. Talwar. Online learning over a finite action set with limited switching. In *Conference On Learning Theory*, pages 1569–1573. PMLR, 2018.

[9] S. Arora, E. Hazan, and S. Kale. The multiplicative weights update method: a meta-algorithm and applications. *Theory of computing*, 8(1):121–164, 2012.

[10] S. Arora, E. Hazan, H. Lee, K. Singh, C. Zhang, and Y. Zhang. Towards provable control for unknown linear dynamical systems. 2018.

[11] P. Auer, N. Cesa-Bianchi, and P. Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2):235–256, 2002.

[12] P. Auer, T. Jaksch, and R. Ortner. Near-optimal regret bounds for reinforcement learning. *Advances in neural information processing systems*, 21, 2008.

[13] D. P. Bertsekas. *Dynamic programming and optimal control*, volume 1. Athena scientific Belmont, MA, 1995.

[14] A. Cassel and T. Koren. Bandit linear control. *Advances in Neural Information Processing Systems*, 33, 2020.

[15] A. Cassel, A. Cohen, and T. Koren. Logarithmic regret for learning linear quadratic regulators efficiently. In *International Conference on Machine Learning*, pages 1328–1337. PMLR, 2020.

[16] A. Cassel, A. Cohen, and T. Koren. Efficient online linear control with stochastic convex costs and unknown dynamics. *arXiv preprint arXiv:2203.01170*, 2022.

[17] A. B. Cassel and T. Koren. Online policy gradient for model free learning of linear quadratic regulators with $\sqrt{T}$ regret. In *International Conference on Machine Learning*, pages 1304–1313. PMLR, 2021.

[18] X. Chen and E. Hazan. Black-box control for linear dynamical systems. In *Conference on Learning Theory*, pages 1114–1143. PMLR, 2021.

[19] A. Chernov and F. Zhdanov. Prediction with expert advice under discounted loss. In *International Conference on Algorithmic Learning Theory*, pages 255–269. Springer, 2010.

[20] A. Cohen, A. Hasidim, T. Koren, N. Lazic, Y. Mansour, and K. Talwar. Online linear quadratic control. In *International Conference on Machine Learning*, pages 1029–1038, 2018.

[21] A. Cohen, T. Koren, and Y. Mansour. Learning linear-quadratic regulators efficiently with only $\sqrt{T}$ regret. In *International Conference on Machine Learning*, pages 1300–1309, 2019.

[22] V. Dani, T. P. Hayes, and S. M. Kakade. Stochastic linear optimization under bandit feedback. 2008.

[23] S. Dean, H. Mania, N. Matni, B. Recht, and S. Tu. Regret bounds for robust adaptive control of the linear quadratic regulator. *Advances in Neural Information Processing Systems*, 31, 2018.

[24] M. K. S. Faradonbeh, A. Tewari, and G. Michailidis. Finite time analysis of optimal adaptive policies for linear-quadratic systems. *arXiv preprint arXiv:1711.07230*, 2017.

[25] M. Fazel, R. Ge, S. Kakade, and M. Mesbahi. Global convergence of policy gradient methods for the linear quadratic regulator. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80, 2018.

[26] P. Gradu, J. Hallman, and E. Hazan. Non-stochastic control with bandit feedback. *Advances in Neural Information Processing Systems*, 33:10764–10774, 2020.

[27] M. Ibrahimi, A. Javanmard, and B. Roy. Efficient reinforcement learning for high dimensional linear quadratic systems. *Advances in Neural Information Processing Systems*, 25, 2012.

[28] S. Lale, K. Azizzadenesheli, B. Hassibi, and A. Anandkumar. Logarithmic regret bound in partially observable linear dynamical systems. *Advances in Neural Information Processing Systems*, 33:20876–20888, 2020.

[29] D. Malik, A. Pananjady, K. Bhatia, K. Khamaru, P. L. Bartlett, and M. J. Wainwright. Derivative-free methods for policy optimization: Guarantees for linear quadratic systems. *Journal of Machine Learning Research*, 21(21):1–51, 2020.

[30] H. Mania, S. Tu, and B. Recht. Certainty equivalence is efficient for linear quadratic control. In *Advances in Neural Information Processing Systems*, volume 32, pages 10154–10164, 2019.

[31] Y. Ouyang, M. Gagrani, and R. Jain. Control of unknown linear systems with thompson sampling. In *2017 55th Annual Allerton Conference on Communication, Control, and Computing (Allerton)*, pages 1198–1205. IEEE, 2017.

[32] O. Plevrakis and E. Hazan. Geometric exploration for online control. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 7637–7647. Curran Associates, Inc., 2020.

[33] M. Simchowitz and D. Foster. Naive exploration is optimal for online lqr. In *International Conference on Machine Learning*, pages 8937–8948. PMLR, 2020.

[34] M. Simchowitz, K. Singh, and E. Hazan. Improper learning for non-stochastic control. In *Conference on Learning Theory*, pages 3320–3436. PMLR, 2020.

[35] S. Tu and B. Recht. The gap between model-based and model-free methods on the linear quadratic regulator: An asymptotic viewpoint. In *Conference on Learning Theory*, pages 3036–3083. PMLR, 2019.

[36] M. Zinkevich. Online convex programming and generalized infinitesimal gradient ascent. In *Proceedings of the 20th international conference on machine learning (icml-03)*, pages 928–936, 2003.