Pruning and Distilling Mixture-of-Experts into Dense Language Models

Junhyuck Kim [1] **Jihun Yun** [1] **Haechan Kim** [2] **Gyeongman Kim** [1] **Joonghyun Bae** [1] **Jaewoong Cho** [1]

Abstract

Mixture-of-Experts (MoE) is now the dominant architecture for frontier language models, yet it requires all expert parameters to be loaded in memory, making it less preferable for memory-constrained deployment. Existing compression methods reduce the number of experts but the output remains an MoE model with the same fundamental limitation. We present the first systematic framework for converting a trained MoE into a standard *fully dense* architecture: experts are scored, selected, and grouped, then concatenated into a dense FFN and refined by knowledge distillation from the MoE teacher. We evaluate 7 scoring, 5 grouping, and 2 magnitude scaling methods across a range of selected expert counts on Qwen3-30B-A3B, yielding 350 configurations. We find that the choice of scoring method is the most impactful, with our novel diversity-aware scoring consistently outperforming prior methods on Qwen3-30B-A3B, DeepSeek-V2-Lite, and GPT-OSS-20B. Under a controlled comparison at matched parameter count, MoE-to-dense outperforms dense-to-dense pruning by +6.3 pp in average downstream accuracy after ∼4B-token distillation at 1.6× faster training wall-clock speed.

1. Introduction

Mixture-of-Experts (MoE) (Shazeer et al., 2017; Fedus et al., 2022) has become the dominant architecture for the most capable models from LLM providers (DeepSeek-AI, 2026; Yang et al., 2025; Meta, 2025; Zeng et al., 2026) as it enables scaling the total number of parameters while remaining practical to train and serve. However, MoE models require loading all expert parameters into memory despite activating only a fraction per token, making them less preferable for

memory-constrained scenarios such as on-device deployment or single-GPU serving. To address these deployment needs, many providers release families of small dense models alongside their flagship MoE (Yang et al., 2025; Google DeepMind, 2026; Liu et al., 2026). These dense models are typically either trained from scratch or produced through cascaded pruning and distillation of a large dense teacher, which must itself first be trained (Muralidharan et al., 2024; Sreenivas et al., 2024; Liu et al., 2026). Both approaches require substantial compute and do not leverage the capability present in the MoE model, which, as we show, provides a stronger starting point for distillation than a dense teacher of matched parameter count.

Recent work has demonstrated that MoE models can be compressed into a smaller MoE by reducing the number of experts (Table 3 in Appendix A). While highly effective, the resulting models still require loading all remaining experts into memory, preserving the fundamental memory inefficiency. Although individual methods can be adapted to produce dense outputs, no prior work has systematically studied MoE-to-dense conversion (Appendix A discusses related work in detail).

To fill this gap, we introduce the first systematic framework for converting a trained MoE language model into a standard *fully dense* architecture. Our approach proceeds in three steps: (1) experts are scored by importance, and the top-scoring experts are selected, grouped, and merged within groups, (2) the merged experts are concatenated into a dense FFN, with down-projection matrices scaled to preserve output magnitude, and (3) knowledge distillation (Hinton et al., 2015) from the MoE teacher recovers quality lost during compression. Figure 1 illustrates the pipeline.

To identify the best recipe, we evaluate 7 different expert scoring methods, including our novel diversity-aware scoring metric, 5 different grouping methods, 2 different down-projection scaling options, and a wide range of the number of selected experts on Qwen3-30B-A3B, resulting in 350 combinations. Below are our key findings, which are further validated across DeepSeek-V2-Lite and GPT-OSS-20B:

1. **Expert scoring is the dominant factor.** Best and worst scoring methods differ by 5.7 pp in average downstream accuracy, while grouping strategy contributes only ∼1 pp (Section 3.2).

[1]KRAFTON [2]KAIST. Correspondence to: Junhyuck Kim <j4ckkim@krafton.com>, Jaewoong Cho <jw-cho@krafton.com>.

Proceedings of the 43rd International Conference on Machine Learning, Seoul, South Korea. PMLR 306, 2026. Copyright 2026 by the author(s).

Figure 1. **Left:** Average downstream accuracy (Section 3.1) after ∼4B-token distillation, comparing three approaches to producing a 3B-parameter dense student. *MoE-to-dense* uses the MoE teacher (Qwen3-30B-A3B) to initialize and distill the student; *Dense-to-dense* prunes a dense teacher of matched total parameter count (Qwen3-32B); *Random Init* trains the same architecture from scratch via distillation. **Right:** The MoE-to-dense pipeline. From the original MoE layer, we score and select a subset, group and merge them into k groups, then concatenate into a standard dense FFN with appropriate magnitude scaling. We evaluate 7 scoring, 5 grouping, and 2 magnitude scaling methods to identify the best configuration.

2. **Selecting diverse experts without merging is the best strategy.** On all three models, the best configuration uses diversity-aware scoring with pure pruning (no weight averaging). In contrast, frequency-based scoring selects redundant experts and benefits from merging them (Section 3.2, 3.3).

3. **MoE-to-dense outperforms dense-to-dense pruning.** In a controlled comparison at matched total parameter count (∼30B teacher, 3B student), our best configuration outperforms dense-to-dense pruning (Muralidharan et al., 2024) by +6.3 pp after ∼4B-token distillation, and is 1.6× faster in training wall-clock time (Section 3.2, 3.3).

Our contributions are:

1. **First MoE-to-dense pruning and distillation framework.** We present the first end-to-end study of converting a trained MoE language model into a fully dense architecture.

2. **Diversity-aware expert selection via Gram log-determinant.** We introduce a D-optimal selection criterion that maximizes the log-determinant of an importance-weighted Gram matrix, jointly capturing expert importance and mutual diversity. Combined with activation-weighted scoring, it achieves the best accuracy across all configurations and all three models.

3. **Comprehensive evaluation and cross-model validation.** We evaluate 350 configurations and identify the best recipe under 0.3B-token distillation. The advantage persists under extended training (∼4B tokens) and generalizes to DeepSeek-V2-Lite and GPT-OSS-20B.

2. Method

We present a method for converting a Mixture-of-Experts (MoE) language model into a dense model with a total number of parameters equivalent to the active number of parameters of the teacher MoE model. Given E experts per MoE layer with k routed per token, the method selects the top-K experts by importance ($K \geq k$), assigns them to k groups (copying directly when $K = k$, or merging via score-weighted averaging when $K > k$), and concatenates the resulting weights into a standard dense FFN. Knowledge distillation from the MoE teacher then recovers quality lost during compression. Throughout this section, k denotes the MoE router's top-k count (an architecture constant), while K denotes the number of routed experts we select for conversion (a design choice).

2.1. MoE-to-dense conversion

Consider an MoE transformer with L layers, each containing a router that maps a hidden representation $\mathbf{h} \in \mathbb{R}^d$ to logits over E experts. The router selects the top-k experts per token and computes a weighted combination of their outputs. We consider the case where each expert is a gated MLP (SwiGLU (Shazeer, 2020)) with intermediate dimension d_{expert}, parameterized by $\mathbf{W}_{\text{gate}}^{(e)}, \mathbf{W}_{\text{up}}^{(e)} \in \mathbb{R}^{d_{\text{expert}} \times d}$ and $\mathbf{W}_{\text{down}}^{(e)} \in \mathbb{R}^{d \times d_{\text{expert}}}$. MoE architectures typically size experts so that $d_{\text{expert}} \times k$ falls in the typical dense FFN range of ∼3–5 × d (Table 1), keeping the active computation per token comparable to a dense model.

We convert each MoE layer into a dense FFN by first scoring all E experts by importance and retaining the top-K. How experts are scored is detailed in Section 2.2; we evaluate seven methods and find that the choice of scoring is the most impactful decision. When $K > k$, the selected experts are assigned to k groups and merged within each group via score-weighted averaging (grouping strategies are compared in Section 2.3). Let $s^{(e)}$ denote the importance score of

Table 1. MoE expert dimensions across models used in this work. The active FFN width per token ($d_{\text{expert}} \times k$) falls in the typical dense range of $\sim$3–5 $\times d$.

Model	d	d_{expert}	E	k	d_{dense} $= d_{\text{expert}} \times k$	d_{dense}/d
Qwen3-30B-A3B	2048	768	128	8	6144	3.0$\times$
GPT-OSS-20B	2880	2880	32	4	11520	4.0$\times$
DeepSeek-V2-Lite	2048	1408	64	6	8448*	4.1$\times$

*DeepSeek-V2-Lite also has 2 shared (always-on) experts; the full dense equivalent is $2 \times 1408 + 6 \times 1408 = 11264$.

expert e and $\mathcal{G}_g$ the set of experts assigned to group g:

$$\mathbf{W}_{\text{proj}}^{(g)} = \sum_{e \in \mathcal{G}_g} \frac{s^{(e)}}{\sum_{e' \in \mathcal{G}_g} s^{(e')}} \mathbf{W}_{\text{proj}}^{(e)}, \quad \text{proj} \in \{\text{gate}, \text{up}, \text{down}\}. \tag{1}$$

When $K = k$, each group contains exactly one expert and no merging is needed.

The k resulting weight matrices are then concatenated into a single dense FFN with intermediate dimension $d_{\text{dense}} = k \times d_{\text{expert}}$:

$$\begin{aligned}
\mathbf{W}_{\text{gate}} &= \left[\mathbf{W}_{\text{gate}}^{(1)}; \ldots; \mathbf{W}_{\text{gate}}^{(k)}\right] \in \mathbb{R}^{d_{\text{dense}} \times d}, \\
\mathbf{W}_{\text{up}} &= \left[\mathbf{W}_{\text{up}}^{(1)}; \ldots; \mathbf{W}_{\text{up}}^{(k)}\right] \in \mathbb{R}^{d_{\text{dense}} \times d}, \\
\mathbf{W}_{\text{down}} &= \left[\tilde{\mathbf{W}}_{\text{down}}^{(1)}, \ldots, \tilde{\mathbf{W}}_{\text{down}}^{(k)}\right] \in \mathbb{R}^{d \times d_{\text{dense}}}, \tag{2}
\end{aligned}$$

where $[\cdot\,;\cdot]$ denotes row-concatenation, $[\cdot,\cdot]$ column-concatenation, each $\mathbf{W}_{\text{proj}}^{(g)}$ is the weight matrix for group g, and $\tilde{\mathbf{W}}_{\text{down}}^{(g)} = \alpha_g \mathbf{W}_{\text{down}}^{(g)}$ is the down-projection scaled to approximate the average routing behavior (Section 2.4). Block concatenation preserves the intermediate activations of the constructed group representatives exactly (Appendix B); when $K=k$, these representatives are copied experts, while for $K>k$ they are parameter-averaged proxies. The final aggregation still differs from the original MoE because static α_g cannot simulate token-dependent router weights. Attention layers, embeddings, and layer norms are copied unchanged from teacher to student.

The parameter K controls a prune/merge tradeoff: $K=k$ copies experts directly (pure pruning), $K>k$ averages K/k experts per group, and $K=E$ retains all experts (pure merging). The full algorithmic pseudocode is provided in Algorithm 1 in Appendix C.

2.2. Scoring

Expert scores determine which experts to retain (top-K selection) and how to weight them during merging. We evaluate seven methods spanning three families, all computed from statistics collected in the calibration forward pass. For each token t and layer ℓ, the router produces a distribution $p_\ell^{(e)}(t)$ via softmax over all E experts, then selects $\mathcal{S}_\ell(t) = \text{top-k}\{p_\ell^{(e)}(t)\}_{e=1}^E$.

Frequency-based scoring (SF, PP, PS). Prior work (Li et al., 2024; Chen et al., 2025; Miao et al., 2025) universally uses **selection frequency (SF)**, the fraction of tokens for which expert e is among the top-k, as the importance metric. We additionally evaluate **pre-selection probability (PP)**, the average softmax probability over all tokens regardless of selection, and **post-selection probability (PS)**, the average over all tokens, taking the softmax probability when e was selected and zero otherwise. All three favor generalist experts that appear frequently. Formal definitions are in Appendix D.

Conditional probability (CP). The frequency-based scores above conflate how often an expert is chosen with how confident the router is when it chooses. CP isolates the latter as the average softmax probability over only the tokens where e was selected:

$$s_\ell^{(e)} = \frac{\sum_{t:e \in \mathcal{S}_\ell(t)} p_\ell^{(e)}(t)}{\left|\{t : e \in \mathcal{S}_\ell(t)\}\right|}. \tag{3}$$

CP is not diluted by frequency, so specialist experts that are rarely selected but confidently routed score highly. As shown in Figure 4 (Appendix E), CP selects a very different top-8 set of experts from the frequency-based methods.

Activation-weighted conditional probability (ACP). Routing probabilities ignore the magnitude of expert outputs. Following REAP (Lasby et al., 2025), which scores experts by the product of routing weight and output norm, we define a factorized variant: $s_\ell^{(e)} = \bar{p}_\ell^{(e)} \cdot \sqrt{\mathbb{E}_t[\|f_e(t)\|^2]}$, where $\bar{p}_\ell^{(e)}$ is the conditional probability from Eq. 3 and $f_e(t)$ is the output of expert e on token t. This factorization decouples routing confidence from output magnitude, producing a per-expert scalar that composes directly with the D-optimal selection criterion we introduce next.

D-Optimal selection (DO). The methods above rank experts independently, ignoring redundancy among high-scoring experts. We introduce a D-optimal criterion that jointly maximizes importance and diversity. Given base importance $I_e = s^{(e)}$ (instantiated as CP or ACP) and the expert output Gram matrix $\mathbf{G}_{ij} = \mathbb{E}_t[\langle f_i(t), f_j(t)\rangle]$, we form the importance-weighted kernel $\mathcal{K}_{ij} = \sqrt{I_i I_j} \cdot \mathbf{G}_{ij}$ and select:

$$S^* = \arg\max_{|S|=K} \log \det(\mathcal{K}_S + \lambda_{\text{reg}} \mathbf{I}), \tag{4}$$

where $\lambda_{\text{reg}} = \frac{1}{KE} \sum_{e=1}^E \mathcal{K}_{ee}$. Since exhaustive search over $\binom{E}{K}$ subsets is intractable, we solve this greedily: starting from $S = \emptyset$, we iteratively add the expert that maximally increases $\log \det(\mathcal{K}_S + \lambda_{\text{reg}}\mathbf{I})$, computed efficiently via Schur complement evaluations in $O(K^3 E)$ total time (Algorithm 2

Figure 2. Marginal effect of each design axis on post-distillation downstream accuracy (0.3B tokens). **(a)** Scoring: DO-ACP dominates (42.64% mean), with a 5.7 pp gap to PP (36.94%). **(b)** Grouping: small effect ($\sim$1 pp spread); round-robin (40.08%) narrowly leads.

in Appendix C). Applying DO to the two best base scores yields **DO-CP** and **DO-ACP**; DO-ACP is the overall best method (Section 3.2). We measure the diversity of a selected expert set by its effective rank (Roy & Vetterli, 2007): the number of significant independent directions in the expert output space, ranging from 1 (all experts are near-duplicates) to K (maximally diverse). Figure 5 (Appendix E) confirms that D-Optimal selection substantially increases the effective rank compared to independent scoring, avoiding redundant experts as predicted by Theorem 2.1. Excluded scoring methods are discussed in Appendix F.

Theoretical properties. The log-determinant objective in Eq. 4 has three useful properties (full statements and proofs in Appendix G).

Theorem 2.1 (Independent scoring can fail under redundancy). *There exists a family of MoE layers, calibration distributions, and a positive regularization choice for which selecting the top-K experts by ACP incurs a constant reconstruction error, while a size-K subset maximizing the log-determinant objective achieves zero error.*

If several high-scoring experts are near-duplicates, selecting all of them wastes dense capacity. Appendix G.1 constructs such a failure mode explicitly for ACP and shows that the log-determinant objective can avoid it.

Beyond this failure mode, the greedy algorithm we use is provably near-optimal: for a positive semidefinite kernel and fixed $\lambda_{\mathrm{reg}} > 0$, the normalized log-determinant objective $\log \det(\mathbf{I} + \lambda_{\mathrm{reg}}^{-1}\mathcal{K}_S)$ is monotone submodular, so greedy achieves the standard $(1-1/e)$ approximation (Nemhauser et al., 1978) (Appendix G.2). And when the expert kernel is incoherent (off-diagonal entries small), the diagonal proxy

$\sum_{e \in S} \log(\mathcal{K}_{ee} + \lambda_{\mathrm{reg}})$ approximates the full objective up to a coherence-controlled gap (Appendix G.3); this supports the intuition that diversity corrections matter most when redundant experts create large off-diagonal interactions. This is consistent with the cross-model trend in Appendix S, where Qwen3 (128 experts) shows a large D-Optimal gain while GPT-OSS (32 experts) shows a compressed scoring gap. Additional theoretical results (finite-sample calibration, grouping, merging) are in Appendix H.

2.3. Grouping

After selecting the top-K experts, we assign them to k groups. We evaluate five strategies: **round-robin (RR)**, which assigns score-sorted experts to groups cyclically, producing balanced groups by construction; **weight clustering (WC)** and **router clustering (RC)**, which cluster experts by weight or router-vector similarity; **anchor-based (AB)** (Li et al., 2024), which uses the k highest-scoring experts as anchors and assigns the rest by router-vector similarity; and **output clustering (OC)** (Chen et al., 2025), which clusters on hidden-state outputs. Full definitions are in Appendix I.

2.4. Down-projection scaling

In the original MoE, the router dynamically weights each expert's output per token. The concatenated dense FFN has no router, so we apply static scaling factors α_g to each group's down-projection to approximate the average routing behavior. We consider **uniform** scaling ($\alpha_g = 1/k$, splitting routing mass equally across the k groups) and **proportional** scaling ($\alpha_g \propto \sum_{e \in \mathcal{G}_g} s^{(e)}$, weighting each group by its share of selected-expert importance). Full equations are in Appendix J.

Table 2. Comparison to baselines on Qwen3-30B-A3B (0.3B-token distillation). DO-ACP at $K=8$ uses our diversity-aware scoring; SF×AB and SF×OC use the metrics of MC-SMoE (Li et al., 2024) and HC-SMoE (Chen et al., 2025) repurposed for a dense student. D2D pruning is Dense-to-dense pruning of a matched-parameter dense teacher (Qwen3-32B). Random FFN + teacher attn copies the teacher's attention with a random FFN. Random initialization trains the same architecture from scratch.

Configuration	Wino	Hella	ARC-E	ARC-C	MMLU	Avg (%)
DO-ACP, $K=8$ (best)	**57.0**	**41.1**	**57.4**	**29.9**	**31.7**	**43.41**
SF×AB (MC-SMoE metrics)	52.2	31.6	47.1	23.1	27.5	36.31
SF×OC (HC-SMoE metrics)	53.1	33.1	49.3	24.7	27.3	37.52
D2D pruning (Qwen3-32B → 3.4B)	51.7	27.7	38.9	22.4	25.7	33.28
Random FFN + teacher attn	53.4	28.0	34.7	22.2	25.2	32.70
Random initialization	51.2	25.3	28.9	22.4	23.0	30.15

3. Experiments

We validate our pipeline on Qwen3-30B-A3B, converting the 30B-parameter MoE into a 3.3B dense model. Section 3.1 describes the setup and experimental workflow. Section 3.2 evaluates every possible scoring×grouping combination after knowledge distillation. Section 3.3 summarizes extended training to ∼4B tokens and validation on DeepSeek-V2-Lite and GPT-OSS-20B; full results are deferred to Appendices R and S. Distillation-method ablations and a qualitative error analysis are in Appendices K and L.

3.1. Experimental setup

Workflow. Our evaluation proceeds in three stages. First, we sweep all combinations of 7 scoring methods, 5 grouping strategies, 2 down-projection (DP) scalings, and $K \in \{8, 16, 32, 64, 128\}$, yielding 350 configurations. Each is evaluated by WikiText-2 perplexity before distillation (we refer to it as pre-distill PPL), measuring initialization quality. Second, for each of the 35 scoring×grouping pairs, we select the best $(K, \text{DP scaling})$ by pre-distill PPL and distill for 0.3B tokens. Third, all distilled models are evaluated on five downstream benchmarks.

Models. Our primary teacher is **Qwen3-30B-A3B** (Yang et al., 2025), a 30B-parameter MoE with $E=128$ experts and $k=8$ active per token. We use the post-trained variant. (We find that the main findings are consistent when using the base model as the teacher model, see Appendix M for a detailed comparison.) The dense student has 3.3B parameters with $d_{\text{dense}} = k \times d_{\text{expert}} = 6{,}144$. For cross-model validation (Appendix S), we additionally test **DeepSeek-V2-Lite** (Dai et al., 2024; DeepSeek-AI, 2024) and **GPT-OSS-20B** (Agarwal et al., 2025); full specs are in Table 1.

Training. Expert importance is calibrated on 512 WikiText-103 (Merity et al., 2017) sequences of 2048 tokens. Unless otherwise noted, distillation minimizes forward KL between teacher and student output logits per token, on FineWeb-Edu (Penedo et al., 2024) with global batch size 384, sequence length 4096, learning rate 10^{-4} with cosine

decay to 10^{-5}, and AdamW ($\beta_1=0.9$, $\beta_2=0.95$). Full distillation setup, loss/routing ablations, hyperparameters, and infrastructure details are in Appendices K and N.

Evaluation. Following Muralidharan et al. (2024); Sreenivas et al. (2024), downstream accuracy is measured on Winogrande (5-shot), HellaSwag (10-shot), ARC-Easy (25-shot), ARC-Challenge (25-shot), and MMLU (5-shot). We report the unweighted average across all five tasks.

3.2. Scoring and grouping evaluation

From the 350-configuration pre-distill PPL sweep (see Appendix O for the complete 350-configuration pre-distill PPL grid), the best K for each scoring×grouping pair is overwhelmingly $K=8$ or $K=16$ (32 of 35 configs, only 3 select $K \geq 32$), indicating that retaining a small number of high-quality experts is more effective than merging many. We distill all 35 best scoring×grouping combinations for 0.3B tokens each and evaluate on five downstream benchmarks (Figure 2). The full 35-combination accuracy matrix with per-benchmark breakdown is in Appendix P (Table 13).

Specialist selection and diversity are crucial. Three distinct tiers emerge across the 35-combination grid (Figure 2), with a 5.7 pp gap between the best and worst scoring families, roughly $5\times$ the grouping spread (1.2 pp). At the bottom tier (∼37%), frequency-based methods (SF, PP, PS) favor generalist experts that serve many tokens but capture broadly shared features; they select nearly identical expert sets (Figure 4 in Appendix E), explaining their tight clustering. The middle tier (40–41%) shows that *focusing on rare-but-confident experts matters*: CP removes the frequency factor, promoting specialists that are rarely selected but confidently routed, yielding +3 pp. ACP further adds output magnitude information (+0.5 pp). The top tier (42–43%) demonstrates that *diversity among selected experts matters*: DO-ACP and DO-CP apply the D-optimal criterion to explicitly penalize redundancy, gaining another +2 pp. This progression, from generalist to specialist to diverse specialist, demonstrates that routing confidence and inter-

Figure 3. Cross-model validation: post-distillation accuracy (0.3B tokens) by scoring method and K on three MoE architectures. Green bars: pure pruning ($K{=}k$, one expert per slot), coral bars: merging ($K{>}k$, multiple experts averaged per slot). Dashed line: random FFN baseline. The scoring hierarchy and the benefit of pure pruning both persist across architectures, though the gap compresses with smaller expert pools.

expert diversity provide complementary signals for expert selection, with additive gains when combined.

Grouping matters less when few experts are selected. The best-performing configurations all use small K (8 or 16), which limits the role of grouping (Appendix O). At $K{=}8\,({=}\,k)$, each group contains exactly one expert, making grouping completely irrelevant; all five strategies produce identical results. At $K{=}16$, pre-distill PPL varies by up to $\sim3\times$ across grouping methods within a scoring family (ACP 2,002–6,334, CP 2,148–6,033; Table 13), but distillation largely compensates and the post-distill PPL spread collapses to within 3 perplexity points. Across the 35 best-per-row configurations, the grouping-induced accuracy spread remains small: RR leads at 40.08%, the three clustering methods trail by only ~0.4 pp, and AB underperforms by ~1 pp (Figure 2).

Pure pruning outperforms merging for diversity-aware scoring. The top-7 configurations all use $K{=}8$ (pure pruning: one expert per group, no weight averaging; see Table 13). Although $K{>}8$ yields lower pre-distill PPL, distillation reverses the ranking: ACP $K{=}8$ reaches 42.52% post-distill vs. 40.50% for ACP×OC $K{=}16$, a $+2.0$ pp gap. This is consistent with a base vs. instruct teacher comparison (Appendix M); cross-model results reveal a more nuanced interaction between scoring and K (Appendix S). DO-ACP at $K{=}8$ achieves the highest average accuracy across all 35 configurations (43.41%; Table 13). Since $K{=}8$ dominates and grouping is irrelevant at $K{=}k$, we refer to the best configuration simply as DO-ACP hereafter.

Comparison to baselines. We find that MC-SMoE's (Li et al., 2024) (SF×AB, 36.31%) and HC-SMoE's (Chen et al., 2025) (SF×OC, 37.52%) scoring×grouping metrics, evaluated within our framework, lag DO-ACP by 7.1 pp

and 5.9 pp (Table 2). Beyond our framework, the strongest comparison is dense-to-dense (D2D) pruning: following the Minitron approach (Muralidharan et al., 2024), we search over five student architectures at matched parameter count (~3.4B), select the best by pre-distill PPL, and distill it with its dense teacher (Qwen3-32B) using identical hyperparameters and token budget (Appendix Q). Despite this careful setup, D2D reaches only 33.28%, $+10.1$ pp below DO-ACP. D2D is also barely above the *random FFN* baseline (32.70%, $+0.6$ pp), which copies the teacher's attention layers but initializes FFN weights randomly; this gap suggests that dense pruning provides little structural advantage at this compression ratio. A full random initialization baseline (30.15%) confirms that expert structure provides a powerful initialization for distillation.

3.3. Extended training and cross-model validation

The ranking established at 0.3B tokens holds at scale and across architectures. Under extended ~4B-token distillation on Qwen3, DO-ACP at $K{=}8$ reaches **58.10%** average accuracy, outperforming D2D pruning by $+6.3$ pp and random FFN by $+12.7$ pp; MoE-to-dense distillation also runs $1.6\times$ faster than D2D thanks to the more efficient MoE teacher (full numbers, validation loss curves, and qualitative analysis in Appendix R). On DeepSeek-V2-Lite (64 routed + 2 shared experts) and GPT-OSS-20B (32 experts), the best configuration uses pure pruning with DO-ACP scoring on all three architectures; the scoring gap (best vs. worst at $K{=}k$) shrinks from 7.1 pp on Qwen3 to 4.3 pp on DeepSeek to 1.6 pp on GPT-OSS, mirroring the redundancy available in the expert pool (Figure 3; full setup, ablations, and per-benchmark tables in Appendix S; model architecture details in Appendix T).

See Appendices U and V for conclusion and limitations.

Impact Statement

This paper presents work whose goal is to advance the field of machine learning. There are many potential societal consequences of our work, none of which we feel must be specifically highlighted here.

References

Agarwal, S., Ahmad, L., Ai, J., Altman, S., Applebaum, A., Arbus, E., Arora, R. K., Bai, Y., Baker, B., Bao, H., et al. gpt-oss-120b & gpt-oss-20b model card. *arXiv preprint arXiv:2508.10925*, 2025.

Bai, S., Li, H., Zhang, J., Hong, Z., and Guo, S. DiEP: Adaptive mixture-of-experts compression through differentiable expert pruning. *arXiv preprint arXiv:2509.16105*, 2025.

Chen, I.-C., Liu, H.-S., Sun, W.-F., Chao, C.-H., Hsu, Y.-C., and Lee, C.-Y. Retraining-free merging of sparse MoE via hierarchical clustering. In *International Conference on Machine Learning*, 2025.

Chen, T., Huang, S., Xie, Y., Jiao, B., Jiang, D., Zhou, H., Li, J., and Wei, F. Task-specific expert pruning for sparse mixture-of-experts. *arXiv preprint arXiv:2206.00277*, 2022.

Dai, D., Deng, C., Zhao, C., Xu, R., Gao, H., Chen, D., Li, J., Zeng, W., Yu, X., Wu, Y., Xie, Z., Li, Y., Huang, P., Luo, F., Ruan, C., Sui, Z., and Liang, W. DeepSeekMoE: Towards ultimate expert specialization in mixture-of-experts language models. *arXiv preprint arXiv:2401.06066*, 2024.

DeepSeek-AI. DeepSeek-V2: A strong, economical, and efficient mixture-of-experts language model. *arXiv preprint arXiv:2405.04434*, 2024.

DeepSeek-AI. Deepseek-v4: Towards highly efficient million-token context intelligence. Technical report, 2026. URL https://huggingface.co/deepseek-ai/DeepSeek-V4-Pro/blob/main/DeepSeek_V4.pdf.

Fedus, W., Zoph, B., and Shazeer, N. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23:1–39, 2022.

Google DeepMind. Gemma 4. https://deepmind.google/models/gemma/gemma-4/, 2026.

Hinton, G., Vinyals, O., and Dean, J. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Jha, S., Hashemzadeh, M., Saheb Pasand, A., Parviz, A., Lee, M.-J., and Knyazev, B. REAM: Merging improves pruning of experts in LLMs. *arXiv preprint arXiv:2604.04356*, 2026.

Kim, B.-K., Kim, G., Kim, T.-H., Castells, T., Choi, S., Shin, J., and Song, H.-K. Shortened llama: Depth pruning for large language models with comparison of retraining methods. *arXiv preprint arXiv:2402.02834*, 2024.

Kim, G., Chu, G., and Yang, E. Every expert matters: Towards effective knowledge distillation for mixture-of-experts language models. *arXiv preprint arXiv:2502.12947*, 2025.

Lasby, M., Lazarevich, I., Sinnadurai, N., Lie, S., Ioannou, Y., and Thangarasa, V. Reap the experts: Why pruning prevails for one-shot moe compression. *arXiv preprint arXiv:2510.13999*, 2025.

Li, L., Qiyuan, Z., Wang, J., Li, W., Gu, H., Han, S., and Guo, Y. Sub-MoE: Efficient mixture-of-expert LLMs compression via subspace expert merging. *arXiv preprint arXiv:2506.23266*, 2025a.

Li, P., Zhang, Z., Yadav, P., Sung, Y.-L., Cheng, Y., Bansal, M., and Chen, T. Merge, then compress: Demystify efficient SMoE with hints from its routing policy. In *International Conference on Learning Representations*, 2024.

Li, Z., Liang, C., Zhang, Z., Hong, I., Kim, Y. J., Chen, W., and Zhao, T. SlimMoE: Structured compression of large MoE models via expert slimming and distillation. *arXiv preprint arXiv:2506.18349*, 2025b.

Liu, A. H., Khandelwal, K., Subramanian, S., Jouault, V., et al. Ministral 3. *arXiv preprint arXiv:2601.08584*, 2026.

Merity, S., Xiong, C., Bradbury, J., and Socher, R. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2017.

Meta. The llama 4 herd: The beginning of a new era of natively multimodal ai innovation. https://ai.meta.com/blog/llama-4-multimodal-intelligence/, 2025.

Miao, R., Yao, Y., Wang, Z., Wang, Z., Yi, B., Liu, L., Zhao, Y., and Yang, T. MergeMoE: Efficient compression of MoE models via expert output merging. *arXiv preprint arXiv:2510.14436*, 2025.

Morrison, J., Adhikesaven, S., Bhagia, A., Zaharia, M., Smith, N. A., and Min, S. Train separately, merge together: Modular post-training with mixture-of-experts. *arXiv preprint arXiv:2604.18473*, 2026.

Muralidharan, S., Sreenivas, S. T., Joshi, R., Chochowski, M., Patwary, M., Shoeybi, M., Catanzaro, B., Kautz, J., and Molchanov, P. Compact language models via pruning and knowledge distillation. *arXiv preprint arXiv:2407.14679*, 2024.

Nemhauser, G. L., Wolsey, L. A., and Fisher, M. L. An analysis of approximations for maximizing submodular set functions—I. *Mathematical Programming*, 14(1):265–294, 1978.

Nguyen, D. V., Nguyen, A. T., Nguyen, M. H., Nguyen, L. Q., Jiang, S., Fetaya, E., Tran, L. D., Chechik, G., and Nguyen, T. M. Expert merging in sparse mixture of experts with nash bargaining. *arXiv preprint arXiv:2510.16138*, 2025.

Penedo, G., Kydlíček, H., Lozhkov, A., Mitchell, M., Raffel, C., Von Werra, L., Wolf, T., et al. The fineweb datasets: Decanting the web for the finest text data at scale. *Advances in Neural Information Processing Systems*, 37: 30811–30849, 2024.

Pukelsheim, F. *Optimal Design of Experiments*. SIAM, 2006.

Roy, O. and Vetterli, M. The effective rank: A measure of effective dimensionality. *15th European Signal Processing Conference*, pp. 606–610, 2007.

Shazeer, N. GLU variants improve transformer. *arXiv preprint arXiv:2002.05202*, 2020.

Shazeer, N., Mirhoseini, A., Maziarz, K., Davis, A., Le, Q., Hinton, G., and Dean, J. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. *arXiv preprint arXiv:1701.06538*, 2017.

Sreenivas, S. T., Muralidharan, S., Joshi, R., Chochowski, M., Patwary, M., Shoeybi, M., Catanzaro, B., Kautz, J., and Molchanov, P. LLM pruning and distillation in practice: The minitron approach. *arXiv preprint arXiv:2408.11796*, 2024.

Sun, M., Liu, Z., Bair, A., and Kolter, J. Z. A simple and effective pruning approach for large language models. *arXiv preprint arXiv:2306.11695*, 2023.

Xia, M., Gao, T., Zeng, Z., and Chen, D. Sheared LLaMA: Accelerating language model pre-training via structured pruning. *arXiv preprint arXiv:2310.06694*, 2024.

Xie, Y., Zhang, Z., Zhou, D., Xie, C., Song, Z., Liu, X., Wang, Y., Lin, X., and Xu, A. MoE-Pruner: Pruning mixture-of-experts large language model using the hints from its router. *arXiv preprint arXiv:2410.12013*, 2024.

Yang, A., Li, A., Yang, B., Zhang, B., Hui, B., Zheng, B., Yu, B., Gao, C., Huang, C., Lv, C., et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Yang, C., Sui, Y., Xiao, J., Huang, L., Gong, Y., Duan, Y., Jia, W., Yin, M., Cheng, Y., and Yuan, B. MoE-I^2: Compressing mixture of experts models through inter-expert pruning and intra-expert low-rank decomposition. In *Findings of EMNLP*, 2024.

Zeng, A., Lv, X., Hou, Z., Du, Z., Zheng, Q., Chen, B., Yin, D., Ge, C., Huang, C., Xie, C., et al. Glm-5: from vibe coding to agentic engineering. *arXiv preprint arXiv:2602.15763*, 2026.

Zhao, Y., Wang, Z., and Zhang, M. PuzzleMoE: Efficient compression of large mixture-of-experts models via sparse expert merging and bit-packed inference. *arXiv preprint arXiv:2511.04805*, 2025.

A. Related work

Table 3. MoE compression methods and their design choices. Prior work produces smaller MoE models, while ours is the first to target a fully dense architecture.

Output	Method	Scoring	Grouping	Distill
MoE	MC-SMoE (Li et al., 2024)	Selection freq	Router-logit anchor-based	✓
	HC-SMoE (Chen et al., 2025)	Selection freq	Output-sim agglomerative	–
	Sub-MoE (Li et al., 2025a)	Selection freq	Output-sim K-means	–
	MergeMoE (Miao et al., 2025)	Selection freq	Weight-sim anchor-based	–
	PuzzleMoE (Zhao et al., 2025)	Weight × activation	Entry-wise diff	–
	REAP (Lasby et al., 2025)	Gate × act. mag.	–	–
Dense	**This work**	**7 methods**
(best: gate × act. mag. + diversity)	**5 methods**	✓

MoE expert pruning. A growing line of work reduces the number of active experts while retaining sparse routing. REAP (Lasby et al., 2025) scores experts by gate value × activation norm and removes the lowest-scoring ones. We adapt this principle into a factorized variant and combine it with the D-optimal selection criterion (Section 2.2). SlimMoE (Li et al., 2025b) retains all experts but progressively prunes neurons within each expert through multi-stage distillation. MoE-Pruner (Xie et al., 2024) one-shot prunes weights within experts using a scoring rule that combines weight magnitude, input activation, and router weight. DiEP (Bai et al., 2025) learns non-uniform pruning rates per layer via differentiable optimization. MoE-I^2 (Yang et al., 2024) scores experts by per-expert loss degradation, requiring $E \times L$ forward passes. Earlier task-specific MoE pruning (Chen et al., 2022) selects experts specialized for a target downstream task; in contrast, our approach is task-agnostic and produces a general-purpose dense model. All these methods produce *smaller MoE* models, whereas our work produces a fully dense model.

MoE expert merging. Rather than removing experts, merging methods combine multiple experts into fewer groups. REAM (Jha et al., 2026) shows that merging experts by router-weighted averaging can outperform pruning them entirely. MC-SMoE (Li et al., 2024) groups experts around dominant (most frequently activated) experts using router-logit similarity, then merges each group via permutation-aligned frequency-weighted averaging. HC-SMoE (Chen et al., 2025) showed that output-similarity clustering outperforms router-logit and weight similarity for grouping. Sub-MoE (Li et al., 2025a) uses output-based K-means++ clustering before joint SVD merging. MergeMoE (Miao et al., 2025) proves the optimality of frequency-based weighting and clusters by concatenated gate/up weight similarity. PuzzleMoE (Zhao et al., 2025) constructs new experts via entry-wise selection that combines weight similarity and activation-weight saliency. NAMEx (Nguyen et al., 2025) computes merging coefficients via Nash Bargaining optimization. In a different paradigm, BAR (Morrison et al., 2026) trains independent domain experts and composes them at inference through a learned router rather than merging their weights. These methods all produce smaller MoE or specialized sparse models, while our pipeline uses expert selection and merging as an initialization for a dense model refined by knowledge distillation.

Dense model compression and distillation. Minitron (Muralidharan et al., 2024; Sreenivas et al., 2024) showed that activation-based importance scoring followed by width/depth pruning and logit-level knowledge distillation produces compact LLMs competitive with models trained from scratch. Other approaches include targeted depth removal (Kim et al., 2024) and joint structured pruning with continued pre-training (Xia et al., 2024). Our pipeline follows the general flow of pruning first and then recovering with knowledge distillation, but the pruning focuses on selecting a smaller set of experts and converting to a dense model, and the teacher model stays MoE during distillation.

Subset selection and D-optimal design. Selecting a diverse, high-quality subset from a large candidate pool is a classical problem in experimental design (Pukelsheim, 2006). The D-optimality criterion maximizes the log-determinant of an information matrix and is monotone submodular, admitting greedy $(1-1/e)$-approximation (Nemhauser et al., 1978). Our D-Optimal expert selection (Section 2.2) instantiates this in the expert output space: the importance-weighted Gram matrix captures both individual quality and pairwise redundancy, so maximizing its log-determinant selects experts that are jointly informative rather than individually top-ranked. To our knowledge, this is the first application of D-Optimal subset selection to MoE compression.

B. Block concatenation preserves representative activations

We show that, once a layer has been converted into k representative FFNs, block concatenation produces the same intermediate activations as those representatives and differs only in the final static aggregation weights. When $K=k$, the representatives are copied experts, so this is an exact statement about the selected original experts. When $K>k$, the representatives are first formed by parameter-space averaging; the result below applies to those constructed representatives, not to every original expert before averaging.

Consider a single representative FFN with SwiGLU activation. Representative g computes:

$$f_g(\mathbf{h}) = \mathbf{W}_{\text{down}}^{(g)}\big(\sigma(\mathbf{W}_{\text{gate}}^{(g)}\mathbf{h}) \odot \mathbf{W}_{\text{up}}^{(g)}\mathbf{h}\big), \tag{5}$$

where σ is the SiLU activation and $\odot$ is element-wise multiplication. The original MoE output uses token-dependent routing weights:

$$f_{\text{MoE}}(\mathbf{h}) = \sum_{e \in \mathcal{S}(\mathbf{h})} w_e(\mathbf{h}) \cdot f_e(\mathbf{h}), \tag{6}$$

where $\mathcal{S}(\mathbf{h})$ is the top-k routed expert set and $w_e(\mathbf{h})$ are the router weights.

Now consider the concatenated dense FFN with $\mathbf{W}_{\text{gate}} = [\mathbf{W}_{\text{gate}}^{(1)}; \ldots; \mathbf{W}_{\text{gate}}^{(k)}]$ and similarly for $\mathbf{W}_{\text{up}}$. Since row-concatenation distributes over matrix–vector multiplication:

$$\mathbf{W}_{\text{gate}}\mathbf{h} = \begin{bmatrix} \mathbf{W}_{\text{gate}}^{(1)}\mathbf{h} \\ \vdots \\ \mathbf{W}_{\text{gate}}^{(k)}\mathbf{h} \end{bmatrix}, \qquad \mathbf{W}_{\text{up}}\mathbf{h} = \begin{bmatrix} \mathbf{W}_{\text{up}}^{(1)}\mathbf{h} \\ \vdots \\ \mathbf{W}_{\text{up}}^{(k)}\mathbf{h} \end{bmatrix}. \tag{7}$$

The SwiGLU activation applies element-wise, so the intermediate activation decomposes into k independent blocks, each identical to the corresponding representative's intermediate activation. The column-concatenated down-projection then sums over these blocks:

$$f_{\text{dense}}(\mathbf{h}) = \mathbf{W}_{\text{down}}\big(\sigma(\mathbf{W}_{\text{gate}}\mathbf{h}) \odot \mathbf{W}_{\text{up}}\mathbf{h}\big) = \sum_{g=1}^{k} \alpha_g \cdot f_g(\mathbf{h}). \tag{8}$$

The representative intermediate activations (gate projections, up projections, and SwiGLU outputs) are *exactly* preserved by block concatenation. Within this block-concatenation step, the only approximation is that the dense model uses static α_g from down-projection scaling (Section 2.4) instead of token-dependent router weights; the full MoE-to-dense conversion also fixes the selected experts and, when $K>k$, replaces groups of original experts by parameter-averaged representatives. Knowledge distillation compensates for these approximations.

C. Algorithms

This section presents the two core procedures of our pipeline: the per-layer MoE-to-dense conversion (Algorithm 1) and the greedy D-Optimal subset selection used by the DO scoring family (Algorithm 2).

MoE-to-dense conversion. Algorithm 1 gives the per-layer conversion, where E is the number of experts, k the MoE top-k count (also the number of groups), $K \geq k$ the experts selected for conversion, $\mathcal{G}_g \subseteq [E]$ the experts assigned to group $g \in [k]$, and α_g the down-projection scaling factor (uniform $1/k$ or score-proportional, Section 2.4).

Algorithm 1 MoE-to-dense conversion for layer ℓ

Require: Experts $\{\mathbf{W}^{(e)}\}_{e=1}^{E}$, scores $\{s^{(e)}\}_{e=1}^{E}$, top-K, number of groups k; scoring, grouping, and scaling method choices.

Ensure: Dense projections $\mathbf{W}_{\text{gate}}, \mathbf{W}_{\text{up}} \in \mathbb{R}^{d_{\text{dense}} \times d}, \mathbf{W}_{\text{down}} \in \mathbb{R}^{d \times d_{\text{dense}}}$

1: **Score:** Compute scores $s^{(e)}$ for all E experts; select top-K.

2: **Group:** Partition the K selected experts into k groups using the chosen grouping method.

3: **for** each group g **do**

4:     Compute within-group weights: $w^{(e)} = s^{(e)} \big/ \sum_{e' \in \mathcal{G}_g} s^{(e')}$ for each $e \in \mathcal{G}_g$.

5:     **for** proj $\in \{\text{gate}, \text{up}, \text{down}\}$ **do**

6:         **Merge:** $\mathbf{W}_{\text{proj}}^{(g)} = \sum_{e \in \mathcal{G}_g} w^{(e)} \mathbf{W}_{\text{proj}}^{(e)}$ $\triangleright$ Weighted average (identity for $|\mathcal{G}_g| = 1$)

7:     **end for**

8:     **Scale:** $\tilde{\mathbf{W}}_{\text{down}}^{(g)} = \alpha_g \cdot \mathbf{W}_{\text{down}}^{(g)}$ $\triangleright$ Uniform or proportional

9: **end for**

10: **Concatenate:** $\mathbf{W}_{\text{gate}} = [\mathbf{W}_{\text{gate}}^{(1)}; \ldots; \mathbf{W}_{\text{gate}}^{(k)}], \quad \mathbf{W}_{\text{up}} = [\mathbf{W}_{\text{up}}^{(1)}; \ldots; \mathbf{W}_{\text{up}}^{(k)}]$ $\triangleright$ Row-concat

11:             $\mathbf{W}_{\text{down}} = [\tilde{\mathbf{W}}_{\text{down}}^{(1)}, \ldots, \tilde{\mathbf{W}}_{\text{down}}^{(k)}]$ $\triangleright$ Column-concat

---

The algorithm applies independently to each of the L MoE layers. All non-MoE parameters (attention, embeddings, layer norms) are copied unchanged from teacher to student.

Greedy D-Optimal selection. Algorithm 2 gives the greedy size-K subset selection used by the DO scoring family, instantiating the $(1-1/e)$-approximation of Proposition G.1. The importance-weighted Gram matrix $\mathcal{K} \in \mathbb{R}^{E \times E}$ has entries $\mathcal{K}_{ij} = \sqrt{I_i I_j}\, \mathbf{G}_{ij}$, with base importance $I_e = s^{(e)} \geq 0$ (CP or ACP) and Gram entries $\mathbf{G}_{ij} = \mathbb{E}_t[\langle f_i(t), f_j(t) \rangle]$ over calibration tokens. For $S \subseteq [E]$, $\mathcal{K}_S$ is the principal submatrix indexed by S, and $\mathcal{K}_{eS}, \mathcal{K}_{Se}$ the corresponding row and column slices for $e \notin S$. The objective is $F(S) := \log \det(\mathcal{K}_S + \lambda_{\text{reg}} \mathbf{I})$ with $\lambda_{\text{reg}} = \frac{1}{KE} \sum_{e=1}^{E} \mathcal{K}_{ee}$.

Algorithm 2 Greedy D-Optimal expert selection (per layer)

Require: Importance-weighted Gram $\mathcal{K}$ (positive semidefinite), target subset size K, regularizer λ_{reg}.

Ensure: Ordered subset $S \subseteq [E]$ with $|S| = K$

1: $S \leftarrow \emptyset$

2: **for** step $= 1, \ldots, K$ **do**

3:     **if** $S = \emptyset$ **then**

4:         gain$(e) \leftarrow \log(\mathcal{K}_{ee} + \lambda_{\text{reg}})$ for each $e \in [E]$

5:     **else**

6:         $A_S \leftarrow \mathcal{K}_S + \lambda_{\text{reg}} \mathbf{I}$; precompute A_S^{-1} $\triangleright$ once per step

7:         **for** each $e \notin S$ **do**

8:             $\sigma_e \leftarrow \mathcal{K}_{ee} + \lambda_{\text{reg}} - \mathcal{K}_{eS} A_S^{-1} \mathcal{K}_{Se}$ $\triangleright$ Schur complement

9:             gain$(e) \leftarrow \log \sigma_e$

10:         **end for**

11:     **end if**

12:     $e^\star \leftarrow \arg\max_{e \notin S} \text{gain}(e)$

13:     $S \leftarrow S \cup \{e^\star\}$

14: **end for**

15: **return** S

A_S^{-1} is recomputed each step at cost $O(K^3)$, and the Schur complement is evaluated for each of the E candidates at $O(K^2)$ per evaluation, yielding overall $O(K^3E)$ time.

D. Scoring baseline definitions

For completeness, we provide the formal definitions of the three routing-based baseline scoring methods (Section 2.2). Let $p_\ell^{(e)}(t)$ be the softmax routing probability and $\mathcal{S}_\ell(t)$ the set of top-k selected experts for token t in layer ℓ.

Selection frequency (SF). $\quad s_\ell^{(e)} = \frac{1}{N} \sum_{t=1}^{N} \mathbb{1}[e \in \mathcal{S}_\ell(t)].$

Pre-selection probability (PP). $\quad s_\ell^{(e)} = \frac{1}{N} \sum_{t=1}^{N} p_\ell^{(e)}(t).$

Post-selection probability (PS). $\quad s_\ell^{(e)} = \frac{1}{N} \sum_{t:e \in \mathcal{S}_\ell(t)} p_\ell^{(e)}(t).$

PS decomposes as SF $\times$ CP: $s_\ell^{(e)} = f_\ell^{(e)} \cdot \mathbb{E}[p_\ell^{(e)}(t) \mid e \in \mathcal{S}_\ell(t)].$

E. Expert selection diagnostics

We characterize the scoring methods of Section 2.2 along two complementary axes: *which* experts each method selects (selection overlap) and *how diverse* the resulting set is (effective rank of the expert kernel submatrix). Figure 4 reports pairwise overlap of the top-K=8 sets, averaged across all layers of Qwen3-30B-A3B; Figure 5 reports the effective rank (Roy & Vetterli, 2007) of the corresponding kernel submatrices.

Figure 4. Selection overlap between the top-K=8 experts chosen by each scoring method, averaged across all layers of Qwen3-30B-A3B. Frequency-based methods (SF, PP, PS) select nearly identical experts, while DO-ACP shares ≤0.08 overlap with them.

Figure 5. Effective rank (Roy & Vetterli, 2007) of the K=8 selected expert kernel submatrix (max 8) for Qwen3-30B-A3B. D-Optimal selection increases effective rank from 6.07 to 7.37 (CP) and 6.31 to 6.93 (ACP).

F. Excluded scoring and grouping methods

Scoring methods excluded. We do not evaluate Fisher information scoring, which MC-SMoE (Li et al., 2024) showed is dominated by frequency weighting (their Table 8). We omit loss-degradation scoring from MoE-I^2 (Yang et al., 2024), requiring $E \times L = 6{,}144$ forward passes, impractical at our scale. We exclude Nash Bargaining coefficients (NAMEx (Nguyen et al., 2025)), which lack validation against standard baselines. Per-weight saliency metrics (Wanda (Sun et al., 2023)) operate at intra-expert granularity, orthogonal to our per-expert framework.

Grouping methods excluded. We do not evaluate K-means++ clustering, which HC-SMoE (Chen et al., 2025) showed is inferior to agglomerative clustering by a 12.96% variance gap (their Table 5). We omit entry-wise weight similarity from PuzzleMoE (Zhao et al., 2025), designed for their sparse dual-mask paradigm requiring custom CUDA kernels incompatible with dense inference.

G. Proofs for D-Optimal expert selection

This section provides full statements and proofs for the theoretical results introduced in Section 2.2. We use the notation established there: $f_e(t) \in \mathbb{R}^d$ is the output of expert e on token t, $I_e = s^{(e)} \geq 0$ is a base importance score (CP or ACP), and $\mathcal{K}_{ij} = \sqrt{I_i I_j} \cdot \mathbb{E}_t[\langle f_i(t), f_j(t) \rangle]$ is the importance-weighted kernel. For any subset $S \subseteq [E]$, we define:

$$F(S) := \log \det\left(\mathcal{K}_S + \lambda_{\mathrm{reg}} \mathbf{I}\right), \qquad\qquad \widetilde{F}(S) := \log \det\left(\mathbf{I} + \lambda_{\mathrm{reg}}^{-1} \mathcal{K}_S\right). \tag{9}$$

For fixed cardinality $|S| = K$, F and $\widetilde{F}$ differ by the additive constant $K \log \lambda_{\mathrm{reg}}$. We use $\widetilde{F}$ for the submodularity argument (it is monotone for any $\lambda_{\mathrm{reg}} > 0$, while F is not) and F in the incoherence and stability proofs (it factors cleanly with the diagonal proxy G).

G.1. Redundancy counterexample (Proof of Theorem 2.1)

This counterexample uses a valid positive regularization chosen for the construction. It is intended to show that log-determinant selection can avoid a redundancy failure mode of independent ACP ranking; the empirical algorithm uses the fixed regularization in Section 2.2.

Proof. Fix $K \geq 2$ and set $E = 2K - 1$. Let the calibration space be

$$\mathcal{X} := \{a_1, \ldots, a_K, b_2, \ldots, b_K\}, \tag{10}$$

and let $\mathcal{D}$ be the uniform distribution on $\mathcal{X}$. We construct a top-1 MoE layer with scalar expert outputs. Define

$$f_e(x) = \mathbf{1}\{x \in \{a_1, \ldots, a_K\}\}, \quad e = 1, \ldots, K, \tag{11}$$

$$f_{K+j-1}(x) = \mathbf{1}\{x = b_j\}, \quad j = 2, \ldots, K. \tag{12}$$

Thus the first K experts are identical, while the remaining $K - 1$ experts are pairwise orthogonal specialists.

Define a deterministic router $r : \mathcal{X} \to [E]$ by

$$r(a_j) = j, \quad j = 1, \ldots, K, \tag{13}$$

$$r(b_j) = K + j - 1, \quad j = 2, \ldots, K, \tag{14}$$

and let the routing probabilities be $p^{(e)}(x) := \mathbf{1}\{e = r(x)\}$. The resulting MoE teacher output is

$$F_{\mathrm{MoE}}(x) := \sum_{e=1}^{E} p^{(e)}(x) f_e(x) = 1 \qquad \text{for every } x \in \mathcal{X}. \tag{15}$$

We take ACP as the base importance score. Because the router is deterministic, every selected expert has conditional probability 1, so the ACP score of expert e reduces to $\sqrt{\mathbb{E}[f_e(x)^2]}$. Therefore

$$I_1 = \cdots = I_K =: I_A = \sqrt{\frac{K}{2K - 1}}, \qquad I_{K+1} = \cdots = I_{2K-1} =: I_B = \sqrt{\frac{1}{2K - 1}}, \tag{16}$$

and hence $I_A > I_B > 0$. Independent top-K ranking by the base importances therefore selects

$$S_{\mathrm{ind}} = \{1, \ldots, K\}. \tag{17}$$

For any subset $S \subseteq [E]$, define its best linear reconstruction error against the teacher output by

$$\mathcal{L}(S) := \inf_{a \in \mathbb{R}^{|S|}} \mathbb{E}_{x \sim \mathcal{D}}\left[\left(\sum_{e \in S} a_e f_e(x) - F_{\mathrm{MoE}}(x)\right)^2\right]. \tag{18}$$

Independent ranking incurs constant error. For S_{ind}, every selected feature equals $\mathbf{1}\{x \in \{a_1, \ldots, a_K\}\}$. Hence every linear combination over S_{ind} has the form

$$x \mapsto c\,\mathbf{1}\{x \in \{a_1, \ldots, a_K\}\} \tag{19}$$

for some scalar c. The choice $c = 1$ is optimal, because it matches $F_{\text{MoE}}(x) = 1$ on the K points $a_1, \ldots, a_K$. On the remaining $K - 1$ points $b_2, \ldots, b_K$, the reconstruction is zero, so the squared error is one. Therefore

$$\mathcal{L}(S_{\text{ind}}) = \frac{K - 1}{2K - 1}. \tag{20}$$

Log-det selects a zero-error subset. Now define

$$S_{\text{good}} := \{1\} \cup \{K + 1, \ldots, 2K - 1\}. \tag{21}$$

For this subset, choosing coefficient vector $a \equiv 1$ gives

$$\sum_{e \in S_{\text{good}}} a_e f_e(x) = \mathbf{1}\{x \in \{a_1, \ldots, a_K\}\} + \sum_{j=2}^{K} \mathbf{1}\{x = b_j\} = 1 = F_{\text{MoE}}(x) \tag{22}$$

for every $x \in \mathcal{X}$, so $\mathcal{L}(S_{\text{good}}) = 0$.

To identify the log-determinant maximizer, let

$$\alpha := \mathcal{K}_{11} = I_A\,\mathbb{E}[f_1(x)^2] = \left(\frac{K}{2K-1}\right)^{3/2}, \qquad \beta := \mathcal{K}_{K+1, K+1} = I_B\,\mathbb{E}[f_{K+1}(x)^2] = \left(\frac{1}{2K-1}\right)^{3/2}. \tag{23}$$

Because the first block of experts is identical and the specialist block is orthogonal to it and to itself off-diagonal, every size-K subset S is characterized by

$$t := |S \cap \{1, \ldots, K\}| \in \{1, \ldots, K\}, \tag{24}$$

and the nonzero eigenvalues of $\mathcal{K}_S$ are

$$t\alpha \qquad \text{and} \qquad \underbrace{\beta, \ldots, \beta}_{K-t \text{ times}}. \tag{25}$$

The remaining $t - 1$ eigenvalues are zero. For this construction, setting $\lambda_{\text{reg}} := \beta$, we obtain

$$\det(\mathcal{K}_S + \lambda_{\text{reg}}\mathbf{I}) = (\beta + t\alpha)\,\beta^{t-1}(2\beta)^{K-t} = \beta^{K-1}2^{K-t}(\beta + t\alpha). \tag{26}$$

Let $D(t) := \beta^{K-1}2^{K-t}(\beta + t\alpha)$. For every $t \geq 1$,

$$\frac{D(t+1)}{D(t)} = \frac{\beta + (t+1)\alpha}{2(\beta + t\alpha)} < 1 \tag{27}$$

because

$$\beta + (t+1)\alpha < 2\beta + 2t\alpha \iff (1-t)\alpha < \beta, \tag{28}$$

and the right-hand side is true for all $t \geq 1$ since $\beta > 0$. Thus $D(t)$ is strictly decreasing in t, so every maximizer of the log-determinant objective has $t = 1$. Every such maximizer has the form

$$\{i\} \cup \{K + 1, \ldots, 2K - 1\} \qquad \text{for some } i \in \{1, \ldots, K\}. \tag{29}$$

Because all first-block experts are identical, each of these maximizing subsets has the same reconstruction error as S_{good}, namely zero. Consequently, any size-K subset maximizing the log-determinant objective achieves zero reconstruction error. $\qquad\square$

G.2. Submodularity and greedy guarantee (Proposition G.1)

Proposition G.1 (Greedy D-Optimal selection is near-optimal). *For any positive semidefinite kernel $\mathcal{K}$ and any $\lambda_{\text{reg}} > 0$, the normalized objective $\widetilde{F}(S) = \log \det(\mathbf{I} + \lambda_{\text{reg}}^{-1} \mathcal{K}_S)$ is monotone submodular. The greedy algorithm returns S_{greedy} with $\widetilde{F}(S_{\text{greedy}}) \geq (1 - 1/e) \max_{|S|=K} \widetilde{F}(S)$.*

D-Optimal selection is therefore not a heuristic but the canonical cardinality-constrained D-optimal design in expert-output space. The result holds for any base importance I_e, and we instantiate it with both CP and ACP (yielding DO-CP and DO-ACP).

Proof. Fix $S \subseteq [E]$ and $e \notin S$. Let $A_S := \mathcal{K}_S + \lambda_{\text{reg}}\mathbf{I}$ and define the Schur complement $\sigma_e(S) := \mathcal{K}_{ee} + \lambda_{\text{reg}} - \mathcal{K}_{eS} A_S^{-1} \mathcal{K}_{Se}$. By the block-determinant formula:

$$\det\big(\mathcal{K}_{S \cup \{e\}} + \lambda_{\text{reg}}\mathbf{I}\big) = \det(A_S) \cdot \sigma_e(S). \tag{30}$$

Now

$$\begin{bmatrix} A_S & \mathcal{K}_{Se} \\ \mathcal{K}_{eS} & \mathcal{K}_{ee} \end{bmatrix} = \begin{bmatrix} \mathcal{K}_S & \mathcal{K}_{Se} \\ \mathcal{K}_{eS} & \mathcal{K}_{ee} \end{bmatrix} + \begin{bmatrix} \lambda_{\text{reg}}\mathbf{I} & 0 \\ 0 & 0 \end{bmatrix} \succeq 0, \tag{31}$$

because both summands are positive semidefinite and $A_S \succ 0$. Taking the Schur complement with respect to the positive-definite block A_S gives

$$\mathcal{K}_{ee} - \mathcal{K}_{eS} A_S^{-1} \mathcal{K}_{Se} \geq 0. \tag{32}$$

Therefore $\sigma_e(S) \geq \lambda_{\text{reg}}$, and hence

$$\widetilde{F}(S \cup \{e\}) - \widetilde{F}(S) = \log\left(\frac{\sigma_e(S)}{\lambda_{\text{reg}}}\right) \geq 0, \tag{33}$$

which proves monotonicity.

For diminishing returns, fix $S \subseteq T \subseteq [E]$ and $e \notin T$. We show $\sigma_e(S) \geq \sigma_e(T)$, i.e., $\mathcal{K}_{eT} A_T^{-1} \mathcal{K}_{Te} \geq \mathcal{K}_{eS} A_S^{-1} \mathcal{K}_{Se}$. By the variational characterization of quadratic forms with positive-definite matrices:

$$\mathcal{K}_{eT} A_T^{-1} \mathcal{K}_{Te} = \max_{z \in \mathbb{R}^{|T|}} \left\{ 2z^\top \mathcal{K}_{Te} - z^\top A_T z \right\}. \tag{34}$$

Restricting z to have support only on S (i.e., $z = (z_S, \mathbf{0}_{T \setminus S})$), the $S \times S$ principal subblock of A_T is A_S, so the restricted maximum equals $\mathcal{K}_{eS} A_S^{-1} \mathcal{K}_{Se}$. Since the unrestricted maximum is at least the restricted one:

$$\mathcal{K}_{eT} A_T^{-1} \mathcal{K}_{Te} \geq \mathcal{K}_{eS} A_S^{-1} \mathcal{K}_{Se}. \tag{35}$$

Hence $\widetilde{F}(S \cup \{e\}) - \widetilde{F}(S) = \log(\sigma_e(S)/\lambda_{\text{reg}}) \geq \log(\sigma_e(T)/\lambda_{\text{reg}}) = \widetilde{F}(T \cup \{e\}) - \widetilde{F}(T)$, which is submodularity. The $(1-1/e)$ greedy bound follows from Nemhauser et al. (1978). □

G.3. Incoherence bound (Theorem G.3)

Definition G.2 (Mutual coherence). *For $i \neq j$ with $\mathcal{K}_{ii}\mathcal{K}_{jj} > 0$, define $\rho_{ij} := \mathcal{K}_{ij}/\sqrt{\mathcal{K}_{ii}\mathcal{K}_{jj}}$ and $\mu := \max_{i \neq j} |\rho_{ij}|$.*

Theorem G.3 (When does D-Optimal selection help most?). *Let $G(S) := \sum_{e \in S} \log(\mathcal{K}_{ee} + \lambda_{\text{reg}})$ and $S_{\text{diag}} \in \arg\max_{|S|=K} G(S)$. If $(K-1)\mu < 1$, then*

$$F(S_{\text{diag}}) \geq \max_{|S|=K} F(S) - K \log\left(\frac{1 + (K-1)\mu}{1 - (K-1)\mu}\right).$$

When experts are nearly incoherent ($\mu \approx 0$), the diagonal proxy is a good approximation to the full log-determinant objective; the off-diagonal diversity interactions contribute less.

Proof. Fix S with $|S| = K$. Define the matrices:

$$B_S := \mathrm{diag}(\mathcal{K}_{ee} + \lambda_{\mathrm{reg}})_{e \in S}, \qquad\qquad R_S := B_S^{-1/2}(\mathcal{K}_S - \mathrm{diag}(\mathcal{K}_{ee})_{e \in S})B_S^{-1/2}. \tag{36}$$

Then $\mathcal{K}_S + \lambda_{\mathrm{reg}}\mathbf{I} = B_S^{1/2}(\mathbf{I} + R_S)B_S^{1/2}$, so $F(S) = G(S) + \log\det(\mathbf{I} + R_S)$.

The matrix R_S is symmetric with zero diagonal, and every off-diagonal entry has magnitude at most μ. By Gershgorin's theorem, every eigenvalue of R_S lies in $[-(K{-}1)\mu,\ (K{-}1)\mu]$. Since $(K{-}1)\mu < 1$ by assumption, $\mathbf{I} + R_S$ is positive definite with eigenvalues in $[1{-}(K{-}1)\mu,\ 1{+}(K{-}1)\mu]$. Taking logarithms and summing over the K eigenvalues:

$$K\log\big(1 - (K{-}1)\mu\big) \le \log\det(\mathbf{I} + R_S) \le K\log\big(1 + (K{-}1)\mu\big). \tag{37}$$

Applying the upper bound to $S^\star = \arg\max_{|S|=K} F(S)$ and the lower bound to $S_{\mathrm{diag}} = \arg\max_{|S|=K} G(S)$, and using $G(S_{\mathrm{diag}}) \ge G(S^\star)$:

$$F(S_{\mathrm{diag}}) \ge F(S^\star) - K\log\left(\frac{1 + (K{-}1)\mu}{1 - (K{-}1)\mu}\right). \tag{38}$$

$\square$

H. Additional theoretical results

H.1. Finite-sample calibration guarantee

In practice, the DO kernel is estimated from a finite calibration set using the paper's actual CP or ACP scores. The following theorem analyzes those estimators directly.

Theorem H.1 (Uniform stability of empirical DO-CP and DO-ACP). *For each token t, let $\mathcal{S}(t) = \mathrm{top\text{-}k}\{p^{(e)}(t)\}_{e=1}^{E}$, with any fixed tie-breaking rule, and define*

$$z_e(t) := \mathbf{1}\{e \in \mathcal{S}(t)\}, \tag{39}$$

$$q_e := \mathbb{E}[z_e(t)], \qquad a_e := \mathbb{E}[z_e(t)\,p^{(e)}(t)], \qquad v_e := \mathbb{E}[\|f_e(t)\|_2^2], \tag{40}$$

$$\mathrm{CP}_e := \frac{a_e}{q_e}, \qquad \mathrm{ACP}_e := \frac{a_e}{q_e}\sqrt{v_e}, \qquad G_{ij} := \mathbb{E}[\langle f_i(t), f_j(t)\rangle]. \tag{41}$$

Given i.i.d. calibration tokens $t_1, \ldots, t_n \sim \mathcal{D}$, define empirical quantities

$$\widehat{q}_e := \frac{1}{n}\sum_{m=1}^{n} z_e(t_m), \qquad\qquad \widehat{a}_e := \frac{1}{n}\sum_{m=1}^{n} z_e(t_m)\,p^{(e)}(t_m), \tag{42}$$

$$\widehat{v}_e := \frac{1}{n}\sum_{m=1}^{n} \|f_e(t_m)\|_2^2, \qquad\qquad \widehat{G}_{ij} := \frac{1}{n}\sum_{m=1}^{n} \langle f_i(t_m), f_j(t_m)\rangle. \tag{43}$$

Set

$$\widehat{\mathrm{CP}}_e := \begin{cases} \widehat{a}_e/\widehat{q}_e, & \widehat{q}_e > 0, \\ 0, & \widehat{q}_e = 0, \end{cases} \tag{44}$$

$$\widehat{\mathrm{ACP}}_e := \widehat{\mathrm{CP}}_e\sqrt{\widehat{v}_e}. \tag{45}$$

Choose the base score either as DO-CP, with

$$I_e := \mathrm{CP}_e, \qquad \widehat{I}_e := \widehat{\mathrm{CP}}_e, \tag{46}$$

or as DO-ACP, with

$$I_e := \mathrm{ACP}_e, \qquad \widehat{I}_e := \widehat{\mathrm{ACP}}_e. \tag{47}$$

Let

$$\mathcal{K}_{ij} := \sqrt{I_i I_j}\, G_{ij}, \qquad \widehat{\mathcal{K}}_{ij} := \sqrt{\widehat{I}_i \widehat{I}_j}\, \widehat{G}_{ij}. \tag{48}$$

For a target subset size K, set the population and empirical regularizers by the same diagonal rule as Section 2.2:

$$\lambda_{\mathrm{reg}} := \frac{1}{KE} \sum_{e=1}^{E} \mathcal{K}_{ee}, \qquad \widehat{\lambda}_{\mathrm{reg}} := \frac{1}{KE} \sum_{e=1}^{E} \widehat{\mathcal{K}}_{ee}, \tag{49}$$

Assume $\lambda_{\mathrm{reg}} > 0$, and define

$$F(S) := \log \det(\mathcal{K}_S + \lambda_{\mathrm{reg}}\mathbf{I}), \qquad\qquad \widehat{F}(S) := \log \det(\widehat{\mathcal{K}}_S + \widehat{\lambda}_{\mathrm{reg}}\mathbf{I}). \tag{50}$$

Assume $\|f_e(t)\|_2 \le B_f$ almost surely for all $e \in [E]$, $q_e \ge q_{\min} > 0$ for all e, and $I_e \in [I_{\min}, I_{\max}]$ for all e. In the DO-ACP case, also assume $v_e \ge v_{\min} > 0$ for all e. Define

$$r_n := \sqrt{\frac{2 \log(8E^2/\delta)}{n}}, \tag{51}$$

$$C_{\mathrm{CP}} := \frac{4}{q_{\min}}, \tag{52}$$

$$C_{\mathrm{ACP}} := \frac{4B_f}{q_{\min}} + \frac{B_f^2}{\sqrt{2v_{\min}}}, \tag{53}$$

$$C_I := \begin{cases} C_{\mathrm{CP}}, & \text{for DO-CP,} \\ C_{\mathrm{ACP}}, & \text{for DO-ACP,} \end{cases} \tag{54}$$

$$C_h := B_f^2 \sqrt{\frac{2I_{\max}}{I_{\min}} + 1} + I_{\max} + \frac{I_{\min}}{2}, \tag{55}$$

$$\varepsilon_n := C_h \max\{C_I, B_f^2\}\, r_n, \tag{56}$$

$$\Delta_n := \left(K + \frac{1}{K}\right) \varepsilon_n. \tag{57}$$

If

$$r_n \le \frac{q_{\min}}{2}, \qquad C_I r_n \le \frac{I_{\min}}{2}, \tag{58}$$

and, in the DO-ACP case,

$$B_f^2 r_n \le \frac{v_{\min}}{2}, \tag{59}$$

then with probability at least $1 - \delta$:

$$\max_{i,j \in [E]} |\widehat{\mathcal{K}}_{ij} - \mathcal{K}_{ij}| \le \varepsilon_n. \tag{60}$$

Consequently, if $\Delta_n < \lambda_{\mathrm{reg}}$, then

$$\left|\widehat{F}(S) - F(S)\right| \le -K \log\left(1 - \frac{\Delta_n}{\lambda_{\mathrm{reg}}}\right) \qquad \text{for all } |S| = K, \tag{61}$$

and if $\widehat{S}$ maximizes $\widehat{F}$ while $S^\star$ maximizes F, then

$$F(\widehat{S}) \ge F(S^\star) - K \log\left(\frac{1 + \Delta_n/\lambda_{\mathrm{reg}}}{1 - \Delta_n/\lambda_{\mathrm{reg}}}\right). \tag{62}$$

Proof. We proceed in four steps. Write $\lambda := \lambda_{\mathrm{reg}}$ for brevity.

Step 1: Uniform concentration of the empirical moments. For each $e \in [E]$, the random variables $z_e(t)$ and $z_e(t)p^{(e)}(t)$ lie in $[0,1]$, while $\|f_e(t)\|_2^2$ lies in $[0, B_f^2]$. Also, for every $i, j \in [E]$,

$$|\langle f_i(t), f_j(t) \rangle| \le \|f_i(t)\|_2 \|f_j(t)\|_2 \le B_f^2 \tag{63}$$

almost surely. Therefore Hoeffding's inequality gives

$$\Pr\left(\max_{e \in [E]} |\widehat{q}_e - q_e| > r_n \right) \le 2E \exp(-2nr_n^2), \tag{64}$$

$$\Pr\left(\max_{e \in [E]} |\widehat{a}_e - a_e| > r_n \right) \le 2E \exp(-2nr_n^2), \tag{65}$$

$$\Pr\left(\max_{e \in [E]} |\widehat{v}_e - v_e| > B_f^2 r_n \right) \le 2E \exp(-2nr_n^2), \tag{66}$$

$$\Pr\left(\max_{i,j \in [E]} |\widehat{G}_{ij} - G_{ij}| > B_f^2 r_n \right) \le 2E^2 \exp\left(-\frac{nr_n^2}{2} \right). \tag{67}$$

By the definition of r_n and a union bound over these four events, with probability at least $1 - \delta$ we are on an event Ω such that

$$\max_{e \in [E]} |\widehat{q}_e - q_e| \le r_n, \qquad\qquad \max_{e \in [E]} |\widehat{a}_e - a_e| \le r_n, \tag{68}$$

$$\max_{e \in [E]} |\widehat{v}_e - v_e| \le B_f^2 r_n, \qquad\qquad \max_{i,j \in [E]} |\widehat{G}_{ij} - G_{ij}| \le B_f^2 r_n. \tag{69}$$

Step 2: Concentration of the paper's actual CP and ACP scores. Fix the event Ω. Since $r_n \le q_{\min}/2$ and $q_e \ge q_{\min}$, we have $\widehat{q}_e \ge q_{\min}/2 > 0$ for every e, so $\widehat{\text{CP}}_e$ is well-defined on Ω. Moreover, $0 \le a_e \le q_e$ because $0 \le p^{(e)}(t) \le 1$, so

$$|\widehat{\text{CP}}_e - \text{CP}_e| = \left| \frac{\widehat{a}_e}{\widehat{q}_e} - \frac{a_e}{q_e} \right| \tag{70}$$

$$\le \frac{|\widehat{a}_e - a_e|}{\widehat{q}_e} + a_e \left| \frac{1}{\widehat{q}_e} - \frac{1}{q_e} \right| \tag{71}$$

$$\le \frac{2r_n}{q_{\min}} + q_e \frac{|\widehat{q}_e - q_e|}{q_e \widehat{q}_e} \tag{72}$$

$$\le \frac{2r_n}{q_{\min}} + \frac{2r_n}{q_{\min}} = C_{\text{CP}} r_n. \tag{73}$$

This proves the score concentration bound for DO-CP.

In the DO-ACP case, the condition $B_f^2 r_n \le v_{\min}/2$ implies $\widehat{v}_e \ge v_{\min}/2$ for every e. Since the derivative of $x \mapsto \sqrt{x}$ is bounded by $1/\sqrt{2v_{\min}}$ on $[v_{\min}/2, \infty)$, the mean-value theorem gives

$$|\sqrt{\widehat{v}_e} - \sqrt{v_e}| \le \frac{|\widehat{v}_e - v_e|}{\sqrt{2v_{\min}}} \le \frac{B_f^2}{\sqrt{2v_{\min}}} r_n. \tag{74}$$

Also $\widehat{v}_e \le B_f^2$, hence $\sqrt{\widehat{v}_e} \le B_f$, and $\text{CP}_e \le 1$. Therefore

$$|\widehat{\text{ACP}}_e - \text{ACP}_e| = \left| \widehat{\text{CP}}_e \sqrt{\widehat{v}_e} - \text{CP}_e \sqrt{v_e} \right| \tag{75}$$

$$\le \sqrt{\widehat{v}_e} |\widehat{\text{CP}}_e - \text{CP}_e| + \text{CP}_e |\sqrt{\widehat{v}_e} - \sqrt{v_e}| \tag{76}$$

$$\le B_f C_{\text{CP}} r_n + \frac{B_f^2}{\sqrt{2v_{\min}}} r_n = C_{\text{ACP}} r_n. \tag{77}$$

Thus, in either score choice,

$$\max_{e \in [E]} |\widehat{I}_e - I_e| \le C_I r_n. \tag{78}$$

Step 3: Entrywise kernel concentration. Because $C_I r_n \leq I_{\min}/2$ and $I_e \geq I_{\min}$, we have

$$\widehat{I}_e \in \left[\frac{I_{\min}}{2}, I_{\max} + \frac{I_{\min}}{2}\right] \qquad \text{for every } e \in [E]. \tag{79}$$

Consider the map $h(a, b, c) := \sqrt{ab}\, c$ on the compact domain

$$D := \left[\frac{I_{\min}}{2}, I_{\max} + \frac{I_{\min}}{2}\right]^2 \times [-B_f^2, B_f^2]. \tag{80}$$

On D, its partial derivatives satisfy

$$\left|\frac{\partial h}{\partial a}\right|, \left|\frac{\partial h}{\partial b}\right| \leq \frac{B_f^2}{2}\sqrt{\frac{2 I_{\max}}{I_{\min}} + 1}, \tag{81}$$

$$\left|\frac{\partial h}{\partial c}\right| \leq I_{\max} + \frac{I_{\min}}{2}. \tag{82}$$

By the mean-value theorem,

$$|\widehat{\mathcal{K}}_{ij} - \mathcal{K}_{ij}| = |h(\widehat{I}_i, \widehat{I}_j, \widehat{G}_{ij}) - h(I_i, I_j, G_{ij})| \tag{83}$$

$$\leq C_h \max\left\{|\widehat{I}_i - I_i|, |\widehat{I}_j - I_j|, |\widehat{G}_{ij} - G_{ij}|\right\} \tag{84}$$

$$\leq C_h \max\{C_I, B_f^2\}\, r_n = \varepsilon_n \tag{85}$$

for all $i, j \in [E]$.

Step 4: Transfer to the log-det objective. The diagonal regularizer is stable under the same entrywise bound:

$$|\widehat{\lambda}_{\mathrm{reg}} - \lambda_{\mathrm{reg}}| \leq \frac{\varepsilon_n}{K}. \tag{86}$$

For any S with $|S| = K$, the matrix $\widehat{\mathcal{K}}_S - \mathcal{K}_S$ is $K \times K$ and has entrywise bound ε_n, so

$$\left\|\widehat{\mathcal{K}}_S + \widehat{\lambda}_{\mathrm{reg}}\mathbf{I} - \mathcal{K}_S - \lambda_{\mathrm{reg}}\mathbf{I}\right\|_{\mathrm{op}} \leq K\varepsilon_n + \frac{\varepsilon_n}{K} = \Delta_n. \tag{87}$$

Let $\sigma_1, \ldots, \sigma_K$ be the eigenvalues of $\mathcal{K}_S + \lambda\mathbf{I}$ and $\widehat{\sigma}_1, \ldots, \widehat{\sigma}_K$ those of $\widehat{\mathcal{K}}_S + \widehat{\lambda}_{\mathrm{reg}}\mathbf{I}$. Weyl's inequality gives

$$|\widehat{\sigma}_i - \sigma_i| \leq \Delta_n \qquad \text{for each } i \in [K]. \tag{88}$$

Since $\Delta_n < \lambda$, every $\widehat{\sigma}_i$ is positive. Therefore

$$\widehat{F}(S) - F(S) = \sum_{i=1}^{K} \log\left(\frac{\widehat{\sigma}_i}{\sigma_i}\right) = \sum_{i=1}^{K} \log\left(1 + \frac{\widehat{\sigma}_i - \sigma_i}{\sigma_i}\right). \tag{89}$$

Because $\sigma_i \geq \lambda$ and $|\widehat{\sigma}_i - \sigma_i| \leq \Delta_n$, we have

$$K \log\left(1 - \frac{\Delta_n}{\lambda}\right) \leq \widehat{F}(S) - F(S) \leq K \log\left(1 + \frac{\Delta_n}{\lambda}\right). \tag{90}$$

Taking absolute values yields

$$\left|\widehat{F}(S) - F(S)\right| \leq -K \log\left(1 - \frac{\Delta_n}{\lambda}\right). \tag{91}$$

Applying the one-sided bounds to $\widehat{S}$ and $S^\star$ gives

$$F(\widehat{S}) \geq \widehat{F}(\widehat{S}) - K \log\left(1 + \frac{\Delta_n}{\lambda}\right) \tag{92}$$

$$\geq \widehat{F}(S^\star) - K \log\left(1 + \frac{\Delta_n}{\lambda}\right) \tag{93}$$

$$\geq F(S^\star) + K \log\left(1 - \frac{\Delta_n}{\lambda}\right) - K \log\left(1 + \frac{\Delta_n}{\lambda}\right), \tag{94}$$

which is exactly the claimed transfer bound. $\qquad\square$

H.2. Grouping recovery

This subsection analyzes the specific OC variant defined in Appendix I: average-linkage agglomerative clustering on empirical cosine dissimilarities.

Fix a selected expert set $S \subseteq [E]$ with $|S| = K$ and a target group count G. Define the population second moments

$$M_{ij} := \mathbb{E}[\langle f_i(t), f_j(t) \rangle], \qquad i, j \in S, \tag{95}$$

and assume throughout this subsection that

$$M_{ee} > 0 \qquad \text{for every } e \in S, \tag{96}$$

so that the population cosine similarities below are well defined. Define

$$\rho_{ij} := \frac{M_{ij}}{\sqrt{M_{ii}M_{jj}}}, \qquad i, j \in S, \tag{97}$$

the population cosine similarities, and

$$d(i, j) := 1 - \rho_{ij}. \tag{98}$$

For two nonempty disjoint clusters $C, C' \subseteq S$, define the average-linkage distance

$$d_{\text{avg}}(C, C') := \frac{1}{|C| \, |C'|} \sum_{i \in C} \sum_{j \in C'} d(i, j). \tag{99}$$

Definition H.2 (Average-linkage output clustering). *Starting from the singleton partition of S, repeatedly merge the pair of clusters with minimum $d_{\text{avg}}(C, C')$. Stop when exactly G clusters remain.*

Assumption H.3 (Output-space separation). *There exists a partition $\mathcal{P}^\star = \{\mathcal{G}_1^\star, \ldots, \mathcal{G}_G^\star\}$ of S and constants $\Delta_{\text{in}}, \Delta_{\text{out}}$ with $\Delta_{\text{in}} < \Delta_{\text{out}}$ such that*

$$\max_{g \in [G]} \max_{i,j \in \mathcal{G}_g^\star} d(i,j) \leq \Delta_{\text{in}} < \Delta_{\text{out}} \leq \min_{\substack{g \neq h}} \min_{\substack{i \in \mathcal{G}_g^\star \\ j \in \mathcal{G}_h^\star}} d(i,j). \tag{100}$$

Theorem H.4 (Exact recovery of output clustering). *Assume Assumption H.3. Then average-linkage output clustering returns $\mathcal{P}^\star$ (up to permutation of the group labels).*

Proof. Step 1: Cluster-level separation. Let $C \subseteq \mathcal{G}_g^\star$ and $C' \subseteq \mathcal{G}_g^\star$ be disjoint clusters contained in the same true group. Then every pair $(i, j) \in C \times C'$ satisfies $d(i, j) \leq \Delta_{\text{in}}$, hence

$$d_{\text{avg}}(C, C') \leq \Delta_{\text{in}}. \tag{101}$$

Similarly, if $C \subseteq \mathcal{G}_g^\star$ and $C' \subseteq \mathcal{G}_h^\star$ with $g \neq h$, then every pair $(i, j) \in C \times C'$ satisfies $d(i, j) \geq \Delta_{\text{out}}$, so

$$d_{\text{avg}}(C, C') \geq \Delta_{\text{out}}. \tag{102}$$

Step 2: Induction on the merge steps. Initially every cluster is a singleton and is therefore contained in some true group. Suppose inductively that, at a given iteration, every current cluster is contained in a true group. If a true group $\mathcal{G}_g^\star$ is represented by at least two current clusters $C_1, C_2 \subseteq \mathcal{G}_g^\star$, then Step 1 gives

$$d_{\text{avg}}(C_1, C_2) \leq \Delta_{\text{in}}. \tag{103}$$

By contrast, any pair of clusters drawn from different true groups has average-linkage distance at least Δ_{out}. Since $\Delta_{\text{in}} < \Delta_{\text{out}}$, the globally closest pair must lie within the same true group. Therefore the algorithm performs an intra-group merge, and the merged cluster remains contained in a true group. This preserves the induction hypothesis.

Step 3: Termination. By Step 2, the algorithm performs only intra-group merges until each true group has been merged into a single cluster. At that moment exactly G clusters remain, namely $\mathcal{G}_1^\star, \ldots, \mathcal{G}_G^\star$. □

Assumption H.5 (Bounded outputs and nondegenerate norms for output clustering). *There exist constants $B_f, \sigma_{\min} > 0$ such that*

$$\|f_e(t)\|_2 \leq B_f \quad \text{almost surely} \qquad \text{and} \qquad M_{ee} \geq \sigma_{\min}^2 \tag{104}$$

for every $e \in S$.

Lemma H.6 (Uniform concentration of empirical cosine similarities). *Assume Assumption H.5. Given i.i.d. calibration tokens $t_1, \ldots, t_n \sim \mathcal{D}$, define*

$$\widehat{M}_{ij} := \frac{1}{n} \sum_{m=1}^n \langle f_i(t_m), f_j(t_m) \rangle, \tag{105}$$

$$\widehat{\rho}_{ij} := \begin{cases} \widehat{M}_{ij}/\sqrt{\widehat{M}_{ii}\widehat{M}_{jj}}, & \widehat{M}_{ii}\widehat{M}_{jj} > 0, \\ 0, & \widehat{M}_{ii}\widehat{M}_{jj} = 0, \end{cases} \tag{106}$$

$$\widehat{d}(i,j) := 1 - \widehat{\rho}_{ij}. \tag{107}$$

Let

$$C_{\text{oc}} := \frac{2}{\sigma_{\min}^2} + \frac{4B_f^2}{\sigma_{\min}^4}. \tag{108}$$

Then for any $\tau \in (0, \sigma_{\min}^2/2]$,

$$\Pr\left(\max_{i,j \in S} |\widehat{M}_{ij} - M_{ij}| > \tau \text{ or } \max_{i,j \in S} |\widehat{\rho}_{ij} - \rho_{ij}| > C_{\text{oc}}\tau \right) \leq 2|S|^2 \exp\left(-\frac{n\tau^2}{2B_f^4} \right). \tag{109}$$

Proof. Fix $i, j \in S$ and define $X_m^{(ij)} := \langle f_i(t_m), f_j(t_m) \rangle$. By Cauchy–Schwarz and Assumption H.5,

$$|X_m^{(ij)}| \leq \|f_i(t_m)\|_2 \|f_j(t_m)\|_2 \leq B_f^2 \tag{110}$$

almost surely, and $\mathbb{E}[X_m^{(ij)}] = M_{ij}$. Hoeffding's inequality therefore gives

$$\Pr\left(|\widehat{M}_{ij} - M_{ij}| > \tau \right) \leq 2\exp\left(-\frac{n\tau^2}{2B_f^4} \right). \tag{111}$$

Applying a union bound over $(i,j) \in S \times S$, we obtain an event Ω_τ of probability at least

$$1 - 2|S|^2 \exp\left(-\frac{n\tau^2}{2B_f^4} \right) \tag{112}$$

on which

$$\max_{i,j \in S} |\widehat{M}_{ij} - M_{ij}| \leq \tau. \tag{113}$$

Fix this event. Since $M_{ii} \geq \sigma_{\min}^2$ and $\tau \leq \sigma_{\min}^2/2$, we have

$$\widehat{M}_{ii} \geq M_{ii} - \tau \geq \sigma_{\min}^2/2 > 0 \tag{114}$$

for every $i \in S$. Hence $\widehat{\rho}_{ij} = \widehat{M}_{ij}/\sqrt{\widehat{M}_{ii}\widehat{M}_{jj}}$ on Ω_τ. Now fix $i, j \in S$. Using $\sqrt{\widehat{M}_{ii}\widehat{M}_{jj}} \geq \sigma_{\min}^2/2$,

$$|\widehat{\rho}_{ij} - \rho_{ij}| \leq \frac{|\widehat{M}_{ij} - M_{ij}|}{\sqrt{\widehat{M}_{ii}\widehat{M}_{jj}}} + |M_{ij}| \left| \frac{1}{\sqrt{\widehat{M}_{ii}\widehat{M}_{jj}}} - \frac{1}{\sqrt{M_{ii}M_{jj}}} \right| \tag{115}$$

$$\leq \frac{2\tau}{\sigma_{\min}^2} + B_f^2 \left| \frac{1}{\sqrt{\widehat{M}_{ii}\widehat{M}_{jj}}} - \frac{1}{\sqrt{M_{ii}M_{jj}}} \right|. \tag{116}$$

For the reciprocal term,

$$\left| \frac{1}{\sqrt{\widehat{M}_{ii}\widehat{M}_{jj}}} - \frac{1}{\sqrt{M_{ii}M_{jj}}} \right| \leq \frac{1}{\sqrt{\widehat{M}_{jj}}} \left| \frac{1}{\sqrt{\widehat{M}_{ii}}} - \frac{1}{\sqrt{M_{ii}}} \right| + \frac{1}{\sqrt{M_{ii}}} \left| \frac{1}{\sqrt{\widehat{M}_{jj}}} - \frac{1}{\sqrt{M_{jj}}} \right|. \tag{117}$$

Since $x \mapsto x^{-1/2}$ has derivative $-\frac{1}{2}x^{-3/2}$, it is $\sqrt{2}/\sigma_{\min}^3$-Lipschitz on $[\sigma_{\min}^2/2, \infty)$. Therefore

$$\left| \frac{1}{\sqrt{\widehat{M}_{ii}}} - \frac{1}{\sqrt{M_{ii}}} \right|, \left| \frac{1}{\sqrt{\widehat{M}_{jj}}} - \frac{1}{\sqrt{M_{jj}}} \right| \leq \frac{\sqrt{2}}{\sigma_{\min}^3}\tau. \tag{118}$$

Using $1/\sqrt{\widehat{M}_{jj}} \leq \sqrt{2}/\sigma_{\min}$ and $1/\sqrt{M_{ii}} \leq 1/\sigma_{\min}$, we obtain

$$\left| \frac{1}{\sqrt{\widehat{M}_{ii}\widehat{M}_{jj}}} - \frac{1}{\sqrt{M_{ii}M_{jj}}} \right| \leq \frac{2 + \sqrt{2}}{\sigma_{\min}^4}\tau \leq \frac{4}{\sigma_{\min}^4}\tau. \tag{119}$$

Combining the preceding bounds yields

$$|\widehat{\rho}_{ij} - \rho_{ij}| \leq \left(\frac{2}{\sigma_{\min}^2} + \frac{4B_f^2}{\sigma_{\min}^4} \right)\tau = C_{\mathrm{oc}}\tau. \tag{120}$$

This holds uniformly over $i, j \in S$ on Ω_τ. □

Theorem H.7 (Finite-sample recovery of output clustering). *Assume Assumptions H.3 and H.5. Let*

$$\gamma := \Delta_{\mathrm{out}} - \Delta_{\mathrm{in}} > 0, \qquad \tau_\star := \min\left\{ \frac{\sigma_{\min}^2}{2}, \frac{\gamma}{4C_{\mathrm{oc}}} \right\}. \tag{121}$$

If

$$n \geq \frac{2B_f^4}{\tau_\star^2} \log\left(\frac{2|S|^2}{\delta} \right), \tag{122}$$

then average-linkage output clustering on the empirical dissimilarities $\widehat{d}(i, j)$ returns $\mathcal{P}^\star$ with probability at least $1 - \delta$.

Proof. By Lemma H.6 with $\tau = \tau_\star$, the stated lower bound on n guarantees that with probability at least $1 - \delta$,

$$\max_{i,j \in S} |\widehat{\rho}_{ij} - \rho_{ij}| \leq C_{\mathrm{oc}}\tau_\star \leq \frac{\gamma}{4}. \tag{123}$$

Fix this event and set $\varepsilon := \gamma/4$. Then

$$|\widehat{d}(i, j) - d(i, j)| = |\widehat{\rho}_{ij} - \rho_{ij}| \leq \varepsilon \qquad \text{for all } i, j \in S. \tag{124}$$

Hence, if i, j lie in the same true group, Assumption H.3 gives

$$\widehat{d}(i, j) \leq d(i, j) + \varepsilon \leq \Delta_{\mathrm{in}} + \varepsilon. \tag{125}$$

If i, j lie in different true groups, then

$$\widehat{d}(i, j) \geq d(i, j) - \varepsilon \geq \Delta_{\mathrm{out}} - \varepsilon. \tag{126}$$

Since $\varepsilon = \gamma/4$, we have

$$\Delta_{\mathrm{in}} + \varepsilon < \Delta_{\mathrm{out}} - \varepsilon. \tag{127}$$

Thus the empirical dissimilarity $\widehat{d}$ satisfies the same strict separation property as in Assumption H.3, with thresholds $\Delta_{\mathrm{in}} + \varepsilon$ and $\Delta_{\mathrm{out}} - \varepsilon$. Theorem H.4 therefore applies to $\widehat{d}$ and yields exact recovery of $\mathcal{P}^\star$. □

H.3. Merging optimality

Fix a selected subset $S \subseteq [E]$ and a partition $\{\mathcal{G}_g\}_{g=1}^G$ of S. View each expert output f_e as an element of the Hilbert space

$$\mathcal{H} := L^2(\mathcal{D}; \mathbb{R}^d) \tag{128}$$

with inner product

$$\langle u, v \rangle_{\mathcal{H}} := \mathbb{E}_{t \sim \mathcal{D}}[\langle u(t), v(t) \rangle]. \tag{129}$$

Theorem H.8 (Score-weighted output averaging is the oracle proxy representative)**.** *Let $s^{(e)} \geq 0$ be the expert scores used for within-group weighting, and assume that every group has strictly positive score mass*

$$S_g := \sum_{e \in \mathcal{G}_g} s^{(e)} > 0. \tag{130}$$

For group representatives $\mu_1, \ldots, \mu_G \in \mathcal{H}$, define the quadratic merge distortion

$$\mathcal{L}(\mu_1, \ldots, \mu_G) := \sum_{g=1}^G \sum_{e \in \mathcal{G}_g} s^{(e)} \|f_e - \mu_g\|_{\mathcal{H}}^2. \tag{131}$$

Then the unique minimizer is

$$\mu_g^\star := \frac{1}{S_g} \sum_{e \in \mathcal{G}_g} s^{(e)} f_e, \qquad g \in [G]. \tag{132}$$

Thus, if merging were performed directly in output-function space, the oracle representative would use the same score weights that Eq. (1) uses in parameter space.

Proof. Fix a group g and write

$$L_g(\mu) := \sum_{e \in \mathcal{G}_g} s^{(e)} \|f_e - \mu\|_{\mathcal{H}}^2. \tag{133}$$

Set $\mu_g^\star := S_g^{-1} \sum_{e \in \mathcal{G}_g} s^{(e)} f_e$. For any $\mu \in \mathcal{H}$, expand

$$f_e - \mu = (f_e - \mu_g^\star) + (\mu_g^\star - \mu), \tag{134}$$

so

$$\|f_e - \mu\|_{\mathcal{H}}^2 = \|f_e - \mu_g^\star\|_{\mathcal{H}}^2 + \|\mu_g^\star - \mu\|_{\mathcal{H}}^2 + 2\langle f_e - \mu_g^\star, \mu_g^\star - \mu \rangle_{\mathcal{H}}. \tag{135}$$

Multiply by $s^{(e)}$ and sum over $e \in \mathcal{G}_g$:

$$L_g(\mu) = \sum_{e \in \mathcal{G}_g} s^{(e)} \|f_e - \mu_g^\star\|_{\mathcal{H}}^2 + S_g \|\mu_g^\star - \mu\|_{\mathcal{H}}^2$$
$$+ 2\left\langle \sum_{e \in \mathcal{G}_g} s^{(e)}(f_e - \mu_g^\star), \mu_g^\star - \mu \right\rangle_{\mathcal{H}}. \tag{136}$$

The last inner-product term vanishes by the definition of $\mu_g^\star$, giving

$$L_g(\mu) = L_g(\mu_g^\star) + S_g \|\mu - \mu_g^\star\|_{\mathcal{H}}^2. \tag{137}$$

Since $S_g > 0$, the unique minimizer of L_g is $\mu_g^\star$. Summing this identity over $g = 1, \ldots, G$ proves that $(\mu_g^\star)_{g=1}^G$ uniquely minimizes $\mathcal{L}$. $\square$

Remark H.9 (Parameter-space averaging is a proxy)**.** *Theorem H.8 is a statement about output functions in $\mathcal{H}$. It does not imply that averaging the parameters of nonlinear SwiGLU experts exactly realizes $\mu_g^\star$. The implemented merge in Eq. (1) applies the oracle function-space weights to parameters as a practical proxy; it is exact only in special cases such as linear experts or singleton groups.*

Proposition H.10 (Scaling induces explicit global weights in the function-space proxy)**.** *Let*

$$w^{(e)} := \frac{s^{(e)}}{S_g}, \qquad e \in \mathcal{G}_g, \tag{138}$$

be the score weights from Eq. (1), define the function-space proxy representative

$$\mu_g^{\text{proxy}} := \sum_{e \in \mathcal{G}_g} w^{(e)} f_e, \tag{139}$$

and let $\alpha_1, \ldots, \alpha_G \geq 0$ be arbitrary group scaling factors. Then the scaled proxy output can be written exactly as

$$\sum_{g=1}^{G} \alpha_g \mu_g^{\text{proxy}} = \sum_{e \in S} \eta_e f_e, \qquad \eta_e := \alpha_{g(e)} \frac{s^{(e)}}{S_{g(e)}}, \tag{140}$$

where $g(e)$ is the unique group index such that $e \in \mathcal{G}_{g(e)}$.

Proof. By definition of $w^{(e)}$,

$$\sum_{g=1}^{G} \alpha_g \mu_g^{\text{proxy}} = \sum_{g=1}^{G} \alpha_g \left(\sum_{e \in \mathcal{G}_g} \frac{s^{(e)}}{S_g} f_e \right) \tag{141}$$

$$= \sum_{g=1}^{G} \sum_{e \in \mathcal{G}_g} \alpha_g \frac{s^{(e)}}{S_g} f_e \tag{142}$$

$$= \sum_{e \in S} \alpha_{g(e)} \frac{s^{(e)}}{S_{g(e)}} f_e, \tag{143}$$

because $\{\mathcal{G}_g\}_{g=1}^{G}$ partitions S. $\qquad\square$

Corollary H.11 (Proportional scaling recovers global score weighting in the proxy)**.** *Under proportional scaling,*

$$\alpha_g = \frac{S_g}{\sum_{e' \in S} s^{(e')}}, \tag{144}$$

the induced global weights are

$$\eta_e = \frac{s^{(e)}}{\sum_{e' \in S} s^{(e')}}. \tag{145}$$

Thus proportional scaling makes the scaled proxy output exactly equal to the global score-weighted average over the selected experts.

Proof. Substitute the proportional-scaling formula into Proposition H.10:

$$\eta_e = \frac{S_{g(e)}}{\sum_{e' \in S} s^{(e')}} \cdot \frac{s^{(e)}}{S_{g(e)}} = \frac{s^{(e)}}{\sum_{e' \in S} s^{(e')}}. \tag{146}$$

$$\square$$

Corollary H.12 (Uniform scaling equalizes group mass in the proxy). *Under uniform scaling,*

$$\alpha_g = \frac{1}{G}, \tag{147}$$

the induced global weights are

$$\eta_e = \frac{s^{(e)}}{G\, S_{g(e)}}, \tag{148}$$

each group's total weight is exactly

$$\sum_{e \in \mathcal{G}_g} \eta_e = \frac{1}{G}, \tag{149}$$

and the total weight across all selected experts sums to 1, *matching the simplex constraint of the original MoE router.*

Proof. The first identity is Proposition H.10 with $\alpha_g = 1/G$. Summing over one group gives

$$\sum_{e \in \mathcal{G}_g} \eta_e = \frac{1}{G\, S_g} \sum_{e \in \mathcal{G}_g} s^{(e)} = \frac{1}{G}, \tag{150}$$

and summing over all G groups yields $\sum_{e \in S} \eta_e = 1$. □

I. Grouping strategy definitions

Given K selected experts assigned to k groups:

Round-robin (RR). Experts are sorted by descending score and assigned cyclically: expert with rank r goes to group $r \bmod G$. This produces balanced groups by construction, with each group containing one high-scoring and one low-scoring expert.

Weight clustering (WC). Agglomerative clustering on the concatenated flattened gate, up, and down projection matrices ($\sim$4.7M dimensions) with cosine similarity.

Router clustering (RC). Agglomerative clustering on router gate weight vectors (Li et al., 2024), using cosine similarity in the d-dimensional router space.

Anchor-based (AB). The k highest-scoring experts serve as anchors; remaining experts are assigned to the anchor with highest router-vector cosine similarity (Li et al., 2024).

Output clustering (OC). Average-linkage agglomerative clustering on the empirical cosine dissimilarities. Let $\bar{G}_{ij} = \frac{1}{n} \sum_{m=1}^{n} \langle f_i(t_m), f_j(t_m) \rangle$ and $\bar{V}_i = \frac{1}{n} \sum_{m=1}^{n} \|f_i(t_m)\|_2^2$. Then:

$$\widehat{\rho}_{ij} := \begin{cases} \bar{G}_{ij} / \sqrt{\bar{V}_i \bar{V}_j}, & \bar{V}_i \bar{V}_j > 0, \\ 0, & \text{otherwise,} \end{cases} \tag{151}$$

$$\widehat{d}(i,j) := 1 - \widehat{\rho}_{ij}, \tag{152}$$

computed from the calibration tokens $t_1, \ldots, t_n$. HC-SMoE (Chen et al., 2025) showed output-based clustering substantially outperforms weight and router similarity for grouping.

J. Down-projection scaling equations

After merging, each group's down-projection is scaled by α_g.

Uniform scaling. Each group is scaled equally so that the total contribution sums to 1, matching the simplex constraint of the MoE router:

$$\tilde{\mathbf{W}}_{\text{down}}^{(g)} = \frac{1}{k}\,\mathbf{W}_{\text{down}}^{(g)}. \tag{153}$$

Proportional scaling.

$$\tilde{\mathbf{W}}_{\text{down}}^{(g)} = \frac{\sum_{e \in \mathcal{G}_g} s_\ell^{(e)}}{\sum_{e' \in S} s_\ell^{(e')}}\,\mathbf{W}_{\text{down}}^{(g)}, \tag{154}$$

where S is the set of K selected experts. Proportional scaling preserves relative contribution magnitude and is particularly important when scores are highly non-uniform (e.g. with CP scoring).

K. Knowledge distillation: setup and method exploration

Forward KL training loss. The concatenated dense model provides an initialization for knowledge distillation from the MoE teacher. We minimize the forward KL divergence between the teacher and student output distributions:

$$\mathcal{L}_{\text{KD}} = \frac{1}{|\mathcal{T}|}\sum_{t \in \mathcal{T}} D_{\text{KL}}\big(\,p_{\text{teacher}}(\cdot \mid x_t) \,\|\, p_{\text{student}}(\cdot \mid x_t)\,\big), \tag{155}$$

where $\mathcal{T}$ is the set of tokens in a batch and x_t is the context preceding token t. Training hyperparameters are given in Section 3.1.

Starting from the best initialization (DO-ACP, $K{=}8$), we ablate two distillation choices on top of this default loss.

Expanded teacher routing. Kim et al. (2025) show that non-activated MoE experts contain useful knowledge for distillation. We test overriding the teacher's routing to activate $k' > k$ experts during distillation:

$$F_{\text{teacher}}(t) = \sum_{e \in \mathcal{S}_{k'}(t)} p_\ell^{(e)}(t)\,f_e(t), \tag{156}$$

where $\mathcal{S}_{k'}(t)$ is the set of k' highest-probability experts for token t. This exposes the student to knowledge from experts the router would not normally select, at the cost of $\sim k'/k$ times more expert activations per MoE layer. We sweep $k' \in \{8, 16, 32, 64, 96, 128\}$. Consistent with Kim et al. (2025), an intermediate routing breadth ($k'{=}16$, i.e., $2k$) improves quality by $+0.70$ pp (Table 4), likely because the next-highest-scoring experts provide complementary knowledge. Beyond $k'{=}32$, performance degrades monotonically as low-ranked experts contribute noise. However, the gain is modest and comes at $\sim 2\times$ teacher FLOPs per MoE layer; when training is not bottlenecked by data availability, this tradeoff favors standard routing.

Table 4. Effect of expanded teacher routing during distillation (0.3B tokens each). All configurations use the same pruned student (DO-ACP). An intermediate $k'{=}16$ yields the best accuracy ($+0.70$ pp), not the default 8 or all 128 experts.

k'	Wino	Hella	ARC-E	ARC-C	MMLU	Avg (%)	Δ
8 (default)	57.0	**41.1**	57.4	29.9	31.7	43.41	−
16	**57.9**	40.9	**57.8**	**31.1**	**32.8**	**44.11**	$+0.70$
32	57.1	40.6	57.0	31.0	32.5	43.63	$+0.22$
64	55.0	39.5	56.1	30.8	32.1	42.71	-0.70
96	56.0	38.8	55.8	29.8	31.6	42.39	-1.02
128 (all)	55.6	38.3	54.5	29.0	31.6	41.78	-1.63

Loss function ablation. We compare forward KL (baseline), reverse KL, and forward KL augmented with intermediate hidden-state MSE loss (Muralidharan et al., 2024). Forward KL substantially outperforms both alternatives (Table 5). Reverse KL loses -6.24 pp, likely because the student benefits more by recovering the full teacher distribution rather than concentrating on high-probability modes. Adding intermediate hidden-state MSE also hurts (-1.91 pp). This is consistent with the Minitron finding that logit-only distillation is optimal when the student preserves all teacher layers (Muralidharan et al., 2024). For the extended training in Appendix R, we use forward KL with standard teacher routing ($k'{=}k$) to maximize training throughput.

Table 5. Loss function ablation (0.3B tokens each). All use the same pruned student (DO-ACP). Forward KL is the clear winner, while reverse KL and intermediate loss both degrade quality.

Loss	Wino	Hella	ARC-E	ARC-C	MMLU	Avg (%)	Δ
Forward KL	**57.0**	**41.1**	**57.4**	**29.9**	**31.7**	**43.41**	–
Intermediate (logit + hidden MSE)	55.5	39.1	53.3	28.7	30.9	41.50	−1.91
Reverse KL	53.0	33.8	42.4	25.6	31.0	37.17	−6.24

L. Qualitative analysis

To complement the benchmark evaluation, we analyze the generation quality of the four model checkpoints from Appendix R. Each model is prompted on 567 MMLU samples (10 per subject, 57 subjects) with a chain-of-thought zero-shot format and generates free-form responses (temperature 0.7, up to 2048 tokens). We classify each response into six categories using rule-based heuristics for surface-level failures and LLM-as-a-judge (Claude Opus 4.6) for semantic errors: *incoherent* (nonsensical output), *repetitive loop* (same phrases cycling without progress), *knowledge error* (coherent but factually wrong), *reasoning error* (flawed logic in STEM), and *other* (topic drift, truncation, out-of-range).

Figure 6. Error distribution on MMLU chain-of-thought zero-shot (567 samples, 4B-token models). As model quality improves (left to right), catastrophic failures (incoherent, repetitive) decrease and the correct rate rises. DO-ACP achieves the lowest total failure rate while maintaining the lowest knowledge error rate.

Catastrophic failures. Figure 6 shows the error distribution. We define catastrophic failures as responses that never reach meaningful reasoning: incoherent outputs and repetitive loops. DO-ACP has the lowest total catastrophic failure rate (54.5%), followed by D2D (57.5%), SF (62.3%), and Random FFN (79.0%). The pattern differs by failure mode: D2D has the lowest incoherent rate (31.4%), while SF has the lowest repetitive loop rate (16.8%). DO-ACP achieves the best overall rate by reducing both failure modes simultaneously.

Knowledge errors. Random FFN produces almost no knowledge errors (2.6%) because the vast majority of its outputs are catastrophic failures that never reach the stage of factual reasoning. Among the three models that do attempt reasoning, knowledge error rates differ substantially: D2D shows 12.5%, SF shows 8.1%, and DO-ACP shows only 4.2%. DO-ACP achieves the highest accuracy (37.6%) with the lowest knowledge error rate, indicating that diversity-aware expert selection preserves factual knowledge more effectively than both dense-to-dense pruning and frequency-based expert selection.

Subject-level breakdown. Breaking down accuracy by MMLU subject category confirms this pattern. DO-ACP reaches 49.2% on humanities, compared to 25.4% (SF), 19.2% (D2D), and 18.5% (Random FFN). The gap is largest on knowledge-intensive subjects (humanities +24 pp over SF, social sciences +11 pp) and smallest on STEM (+6 pp), where all models struggle with mathematical reasoning. This suggests that the experts selected by DO-ACP carry richer factual and cultural knowledge, consistent with the low knowledge error rate observed above.

Error taxonomy and examples. Table 6 defines the six error categories used above. Surface-level failures (incoherent, repetitive loop, other) are classified by rule-based heuristics applied in priority order; semantic errors (knowledge error, reasoning error) are classified by LLM-as-a-judge using Claude Opus 4.6. Table 7 shows representative examples from each category.

Table 6. Error taxonomy for qualitative MMLU analysis. Categories are applied in priority order (top to bottom): a response matching an earlier category is not checked against later ones.

Category	Definition
Incoherent	Nonsensical output that fails to convey meaning: circular redefinitions, meta-commentary without substance, or degenerate numeric sequences. Detected by filler-word ratio $>35\%$ and unique-word ratio $<15\%$, or digit ratio $>30\%$.
Repetitive Loop	The same phrases or sentences cycle repeatedly without making progress toward an answer. Detected by 3-gram repetition count ≥ 5.
Knowledge Error	The reasoning structure is coherent and on-topic, but the response contains factual errors (e.g., hallucinated definitions, incorrect attributions).
Reasoning Error	The response attempts logical or mathematical reasoning but arrives at an incorrect conclusion through flawed logic.
Other	Topic drift (coherent but off-topic, keyword overlap $<15\%$), truncation without a final answer, or out-of-range answer selection.

Table 7. Representative error examples from the qualitative MMLU analysis.

Category	Model	Example (excerpt)
Incoherent	Random FFN	"The duty is a principle, but the principle is a norm. The duty is a moral obligation, but the norm is a standard of conduct..." (circular redefinition, no content)
Incoherent	SF	"We need to find the correct answer. First, the first step is to check the list of options...the next question is: what is the correct fact?" (meta-commentary about answering without engaging the question)
Repetitive Loop	D2D	"Jaden's score is a multiple of 7. The number of points Jaden scored is less than 45. So, Jaden's score is a multiple of 7..." (same two premises repeated with no computation)
Knowledge Error	D2D	"Miaphystism is the doctrine that God is present in the Eucharist...mīaphysos is a word that can be translated as disease..." (hallucinated definition and fabricated etymology)
Reasoning Error	DO-ACP	"1/2 exponent is the smallest...1/2 is the fastest." Self-contradiction within two sentences; growth rate ordering reversed.
Other	Random FFN	Four answer choices paraphrased at equal length; response truncated mid-sentence without selecting A–D.

M. Base vs. post-trained teacher comparison

All primary experiments use the post-trained (instruct/reasoning hybrid) variant of Qwen3-30B-A3B as the teacher model. To verify that this choice does not bias our findings, we repeat the full 350-configuration pre-distill PPL sweep and distill the top-1 configuration per scoring method at both $K{=}8$ and $K{=}16$ using the base variant (`Qwen3-30B-A3B-Base`) with identically collected importance scores and Gram matrices.

Scoring rankings are preserved across model variants. Table 8 compares the best pre-distill PPL per scoring method between the base and post-trained teacher variants. The ranking by best PPL is nearly identical:

The top-4 scoring methods (ACP, DO-CP, DO-ACP, CP) maintain their exact ranking across both variants. The bottom three (PP, PS, SF) swap positions 5–7 but remain tightly clustered. Base PPL values are systematically higher than post-trained values (1.2–1.6×), consistent with the base model's weaker language modeling performance prior to instruction tuning.

Table 8. Best pre-distill PPL per scoring method: post-trained (instruct) vs. base teacher. Rankings match in the top-4 positions (ACP, DO-CP, DO-ACP, CP), confirming that scoring method conclusions are robust to teacher variant choice.

Scoring	Post-trained (Instruct)		Base	
	Best PPL	Rank	Best PPL	Rank
ACP	2,002	1	2,424	1
DO-CP	2,840	2	4,608	2
DO-ACP	3,939	3	5,697	3
CP	4,280	4	8,175	4
PP	9,463	5	9,326	5
PS	8,509	6	11,308	6
SF	8,638	7	13,370	7

Downstream benchmarks confirm PPL rankings. We distill the top-1 base configuration per scoring method at both $K=8$ (pure pruning) and $K=16$ (merging) for 0.3B tokens and evaluate on all five benchmarks. Table 9 shows results.

Table 9. Base teacher distillation results ($K=8$ and $K=16$, 0.3B tokens each). **Bold**: best per scoring. ACP and DO-ACP at $K=8$ outperform their $K=16$ counterparts, confirming the "pure pruning wins" finding from the main experiments.

Scoring	K	Pre-distill PPL	Wino	Hella	ARC-E	ARC-C	MMLU	Avg (%)
ACP	**8**	9,049	54.8	**42.2**	**57.5**	**31.4**	28.1	**42.81**
ACP	16	2,424	54.5	39.2	53.5	28.0	25.4	40.13
DO-ACP	**8**	10,220	55.6	41.2	55.5	29.6	**31.0**	**42.59**
DO-ACP	16	5,697	54.6	39.6	53.7	28.6	28.1	40.93
CP	8	9,223	**55.6**	39.8	54.6	28.5	26.9	41.08
CP	16	8,175	54.9	37.7	56.9	29.5	26.3	41.07
SF	8	29,059	51.7	29.5	39.7	22.1	27.0	34.01
SF	16	13,370	52.6	33.4	48.4	24.1	27.2	37.17
Random FFN	–	–	51.9	28.0	33.0	22.3	26.1	32.26
Random init	–	–	50.4	25.2	28.0	23.8	22.9	30.08

The three-tier scoring hierarchy from the main experiments is preserved: ACP and DO-ACP lead at $\sim$42.7%, followed by CP at $\sim$41.1%, then SF at 34–37%, and random baselines at 30–32%. Pure pruning ($K=8$) outperforms merging ($K=16$) for ACP (+2.68 pp) and DO-ACP (+1.66 pp), confirming the finding from Section 3.2. CP shows a near-tie across K values, and only SF benefits from merging. Absolute accuracy is comparable between teacher variants: the best base configuration (ACP at $K=8$, 42.81%) slightly exceeds its instruct counterpart (42.52%, +0.29 pp), while DO-ACP at $K=8$ on the base model (42.59%) is 0.82 pp below instruct (43.41%).

Overall, scoring method rankings from the main experiments (Section 3.2) are robust to teacher variant, and the pure pruning advantage (Section 3.2) holds for both variants. This is consistent with Liu et al. (2026), who found that post-trained teachers produce comparable or stronger students for knowledge distillation. We retain the post-trained teacher as the primary setting since it is the default download and requires no additional setup.

N. Full distillation hyperparameters

Table 10 lists all hyperparameters used for knowledge distillation. Each configuration processes approximately 0.3B tokens $(200 \times 384 \times 4096)$ and takes $\sim$5.5 hours on $4\times$ H200 GPUs.

Table 10. Distillation hyperparameters for 200-step (0.3B-token) runs.

Parameter	Value
Optimizer	AdamW ($\beta_1 = 0.9$, $\beta_2 = 0.95$)
Weight decay	0.01
Peak learning rate	10^{-4}
Min learning rate	10^{-5}
LR schedule	Cosine decay (warmup 20 steps)
Temperature (τ)	1.0
Loss function	Forward KL divergence on logits
Sequence length	4096
Micro-batch size	4 per GPU
Gradient accumulation	24 steps
Global batch size	384 sequences
Total steps	200 (0.3B tokens)
Infrastructure	
GPUs	$4\times$ NVIDIA H200 (140 GB HBM3e each)
Parallelism	DeepSpeed ZeRO Stage 2
Precision	BF16 mixed precision
Attention	Flash Attention 2
Training data	FineWeb-Edu (streaming, no repeat)
Calibration data	512 samples from WikiText-103
Evaluation data	WikiText-2 test set (full)

O. Full pre-distill PPL grid

Tables 11 and 12 present the comprehensive WikiText-2 perplexity for all 350 pre-distill configurations: 7 scoring $\times$ 5 grouping $\times$ 2 scaling (Uniform/Proportional) $\times$ 5 values of K. Both down-projection scaling options are shown separately for each scoring$\times$grouping pair. At $K=8$ ($=k$), each group contains exactly one expert; for DO-CP, ACP, and DO-ACP the same 8 experts are selected regardless of grouping, so all five grouping rows share the same value.

Table 11. WikiText-2 pre-distill perplexity ($\downarrow$) for frequency-based scoring methods. Each row shows one scoring $\times$ grouping $\times$ DP scaling combination across all K values. **Bold**: best K per row. "–": numerical instability. Values $\geq$100k in compact notation.

Scoring	Grouping	DP Scaling	$K=8$	$K=16$	$K=32$	$K=64$	$K=128$
Selection Frequency	Round-Robin	Uniform	**20,633**	21,112	22,343	22,853	22,799
		Proportional	21,074	**19,440**	21,036	21,950	22,022
	Weight Cluster	Uniform	20,633	**12,896**	22,333	31,088	–
		Proportional	21,074	**17,661**	20,733	64,433	–
	Router Cluster	Uniform	20,633	**11,342**	14,833	13,473	14,607
		Proportional	21,074	**11,594**	18,269	30,705	80,436
	Anchor-Based	Uniform	**11,988**	15,494	16,796	17,916	17,963
		Proportional	**11,668**	13,863	15,362	16,385	16,661
	Output Cluster	Uniform	11,988	12,499	17,518	**8,638**	26,775
		Proportional	**11,668**	17,565	56,400	34,566	120k
Pre-Selection Probability	Round-Robin	Uniform	**14,983**	15,523	36,409	162k	315k
		Proportional	**13,340**	13,555	23,351	79,675	152k
	Weight Cluster	Uniform	14,983	**11,085**	12,528	19,148	20,430
		Proportional	13,340	**11,794**	22,710	74,225	430k
	Router Cluster	Uniform	14,983	14,665	**14,585**	15,038	15,176
		Proportional	13,340	**13,299**	30,706	82,825	122k
	Anchor-Based	Uniform	**9,463**	13,981	22,389	26,906	35,660
		Proportional	**10,697**	16,254	33,221	46,464	62,482
	Output Cluster	Uniform	**9,463**	10,223	36,539	61,045	44,465
		Proportional	**10,697**	18,176	77,920	206k	395k
Post-Selection Probability	Round-Robin	Uniform	18,027	**15,236**	15,276	15,405	15,378
		Proportional	**15,409**	15,996	16,281	16,178	15,976
	Weight Cluster	Uniform	18,027	**10,976**	13,436	15,552	–
		Proportional	15,409	**14,076**	16,900	20,448	–
	Router Cluster	Uniform	18,027	**11,379**	11,960	12,506	14,086
		Proportional	15,409	**8,850**	13,105	16,681	24,100
	Anchor-Based	Uniform	11,385	10,453	**10,425**	11,264	11,185
		Proportional	**12,269**	12,946	13,889	14,828	14,871
	Output Cluster	Uniform	11,385	10,914	16,675	**8,509**	25,862
		Proportional	**12,269**	15,557	41,130	24,286	62,593

Table 12. WikiText-2 pre-distill perplexity (↓) for conditional probability, activation-weighted, and D-optimal scoring methods. Each row shows one scoring × grouping × DP scaling combination across all K values. **Bold**: best K per row. "–": numerical instability. Values $\geq$100k in compact notation.

Scoring	Grouping	DP Scaling	$K=8$	$K=16$	$K=32$	$K=64$	$K=128$
Conditional Probability	Round-Robin	Uniform	**4,280**	20,580	311k	6.3m	21.8m
		Proportional	25,495	**6,846**	77,402	3.9m	18.5m
	Weight Cluster	Uniform	**4,280**	10,836	37,955	18,543	–
		Proportional	25,495	**11,730**	35,458	250k	–
	Router Cluster	Uniform	**4,280**	9,473	21,755	24,590	18,008
		Proportional	25,495	**5,068**	18,650	317k	1.6m
	Anchor-Based	Uniform	**6,033**	132k	54,246	92,860	170k
		Proportional	31,189	**25,609**	32,057	147k	348k
	Output Cluster	Uniform	**6,033**	6,085	12,998	55,860	186k
		Proportional	31,189	**6,897**	47,979	660k	956k
Activation-Wtd Cond. Prob.	Round-Robin	Uniform	**6,334**	13,080	67,926	417k	1.1m
		Proportional	31,273	31,129	**21,519**	32,031	129k
	Weight Cluster	Uniform	6,334	**5,527**	11,223	30,095	16,821
		Proportional	31,273	**16,018**	23,598	38,933	35,822
	Router Cluster	Uniform	6,334	**3,384**	7,586	9,161	15,296
		Proportional	31,273	10,450	**9,248**	19,192	203k
	Anchor-Based	Uniform	6,334	**4,829**	12,612	17,082	60,169
		Proportional	31,273	**7,273**	10,824	20,683	65,647
	Output Cluster	Uniform	6,334	**2,002**	12,079	26,600	151k
		Proportional	31,273	**30,198**	33,533	68,216	320k
D-Optimal + CP	Round-Robin	Uniform	**3,837**	5,137	60,925	1.1m	3.3m
		Proportional	10,928	**4,897**	65,655	1.1m	3.3m
	Weight Cluster	Uniform	**3,837**	4,970	17,150	36,424	16,186
		Proportional	10,928	**4,013**	41,808	260k	463k
	Router Cluster	Uniform	**3,837**	4,964	12,789	11,815	15,709
		Proportional	10,928	**6,050**	35,575	147k	728k
	Anchor-Based	Uniform	3,837	**2,840**	5,420	12,823	52,050
		Proportional	10,928	**3,022**	12,467	69,341	736k
	Output Cluster	Uniform	**3,837**	4,063	107k	42,441	113k
		Proportional	10,928	**3,805**	370k	333k	920k
D-Optimal + ACP	Round-Robin	Uniform	**5,134**	10,572	66,588	1.0m	2.8m
		Proportional	11,949	**10,945**	72,395	992k	2.8m
	Weight Cluster	Uniform	5,134	**4,779**	8,632	28,519	16,340
		Proportional	11,949	**4,333**	24,579	208k	431k
	Router Cluster	Uniform	**5,134**	8,553	8,751	9,410	15,635
		Proportional	11,949	**11,352**	34,707	109k	714k
	Anchor-Based	Uniform	5,134	**4,776**	15,564	18,842	50,751
		Proportional	11,949	**3,939**	16,248	78,899	743k
	Output Cluster	Uniform	**5,134**	5,521	22,932	102k	97,865
		Proportional	11,949	**6,230**	313k	552k	912k

P. Full distillation results

Table 13 presents the full per-benchmark distillation results for all 35 scoring×grouping combinations on Qwen3-30B-A3B.

Table 13. Full distillation results (0.3B tokens) for all 35 configurations on Qwen3-30B-A3B. *Pre/Post* = WikiText-2 PPL before/after distillation. Color scale: best → mid → worst . **Bold**: best average per scoring method.

Scoring	Grouping	DP Scaling	K	PPL (↓) Pre	Post	Wino	Hella	ARC-E	ARC-C	MMLU	Avg
Selection Frequency	Round-robin	Proportional	16	19,440	29.3	53.04	32.58	49.07	25.51	27.62	37.56
	Weight cluster	Uniform	16	12,896	27.9	54.38	32.65	49.49	24.40	27.16	**37.62**
	Router cluster	Uniform	16	11,342	28.5	52.09	32.99	49.62	24.49	27.08	37.25
	Anchor-based	Proportional	8	11,668	29.2	52.17	31.64	47.14	23.12	27.50	36.31
	Output cluster	Uniform	64	8,638	27.7	53.12	33.06	49.33	24.74	27.34	37.52
Pre-Selection Probability	Round-robin	Proportional	8	13,340	30.9	53.12	31.85	48.53	23.89	27.57	36.99
	Weight cluster	Uniform	16	11,085	30.1	53.43	32.21	48.74	23.63	27.59	**37.12**
	Router cluster	Proportional	16	13,299	29.9	52.41	32.19	47.77	23.98	27.22	36.71
	Anchor-based	Uniform	8	9,463	28.6	53.35	32.17	48.65	24.15	27.28	**37.12**
	Output cluster	Uniform	8	9,463	28.7	52.88	32.14	47.47	23.63	27.70	36.77
Post-Selection Probability	Round-robin	Uniform	16	15,236	29.2	51.78	32.51	48.61	23.98	27.28	36.83
	Weight cluster	Uniform	16	10,976	27.7	52.64	32.84	49.79	24.66	27.07	**37.40**
	Router cluster	Proportional	16	8,850	28.8	51.85	32.68	49.07	25.09	27.33	37.21
	Anchor-based	Uniform	32	10,425	28.6	51.62	31.95	47.60	23.89	27.48	36.51
	Output cluster	Uniform	64	8,509	28.2	52.49	32.45	50.04	24.40	27.30	37.34
Conditional Probability	Round-robin	Proportional	16	3,696	24.4	53.83	36.18	56.36	27.82	27.60	40.35
	Weight cluster	Proportional	16	2,148	24.3	54.46	36.02	56.44	27.73	27.50	**40.43**
	Router cluster	Proportional	16	2,264	23.3	53.67	36.06	56.69	27.39	27.77	40.32
	Anchor-based	Uniform	8	6,033	21.5	53.67	35.73	55.51	26.96	27.11	39.80
	Output cluster	Uniform	8	6,033	21.5	53.83	35.73	55.72	27.82	26.80	39.98
Activation-Wtd Cond. Prob.	Round-robin	Uniform	8	6,334	19.1	56.35	39.78	56.02	29.69	30.73	**42.52**
	Weight cluster	Uniform	16	5,527	21.3	55.01	38.67	53.83	29.61	28.91	41.21
	Router cluster	Uniform	16	3,384	21.3	54.54	36.95	53.11	25.94	28.24	39.76
	Anchor-based	Uniform	16	4,829	21.7	52.01	37.30	53.41	26.88	27.64	39.45
	Output cluster	Uniform	16	2,002	20.5	54.78	38.11	55.05	27.47	27.11	40.50
D-Optimal + CP	Round-robin	Uniform	8	3,837	19.1	54.46	41.30	57.37	30.12	31.19	42.89
	Weight cluster	Uniform	8	3,837	19.0	55.56	41.13	57.53	29.61	31.06	**42.98**
	Router cluster	Uniform	8	3,837	19.0	55.25	41.39	57.41	29.61	31.16	42.96
	Anchor-based	Uniform	16	2,840	20.7	55.25	38.93	55.35	28.67	27.45	41.13
	Output cluster	Proportional	16	3,805	20.5	56.75	38.96	55.89	29.86	28.74	42.04
D-Optimal + ACP	Round-robin	Uniform	8	5,134	19.2	56.99	41.13	57.37	29.86	31.70	**43.41**
	Weight cluster	Proportional	16	4,333	20.6	54.22	39.59	54.67	28.24	28.91	41.13
	Router cluster	Uniform	8	5,134	19.2	56.59	40.99	57.45	29.18	32.30	43.30
	Anchor-based	Proportional	16	3,939	19.8	56.12	40.20	55.77	28.92	29.59	42.12
	Output cluster	Uniform	8	5,134	19.2	56.99	41.08	57.07	29.27	31.86	43.25

Q. Dense-to-Dense (D2D) pruning baseline

To ensure a fair comparison, we implement a strong D2D baseline following the Minitron methodology (Muralidharan et al., 2024): structured pruning of a dense teacher (Qwen3-32B, 32B parameters) to a student of comparable size to our MoE-to-dense models, followed by distillation with the same dense teacher using matched hyperparameters and token budget.

Architecture search. Following the Minitron approach (Muralidharan et al., 2024), we search over five candidate architectures at matched parameter count (∼3.4B), varying pruning strategy (width-only vs. combined width+depth), number of layers, and hidden/FFN dimensions. All candidates are pruned using activation-based importance scoring (Muralidharan et al., 2024) calibrated on 1,024 WikiText-103 samples and evaluated by WikiText-2 perplexity before distillation (Table 14).

The best architecture preserves all 64 layers with aggressive width pruning (d=2048, d_{dense}=6144, 3.44B parameters),

Table 14. D2D architecture search: five candidate architectures pruned from Qwen3-32B (64 layers, $d=5120$, $d_{\text{dense}}=25600$). Width-only pruning that preserves all layers achieves the best pre-distill PPL. **Bold**: selected configuration.

Strategy	Layers	d	d_{dense}	Heads	Params	Pre-distill PPL
Width-only	**64**	**2,048**	**6,144**	**8**	**3.44B**	**15,300**
Width-only	64	1,536	8,192	12	3.29B	44,605
Combined	56	2,048	6,144	16	3.44B	20,299
Combined	48	2,048	6,144	16	3.44B	44,100
Combined	40	2,048	6,144	16	2.55B	286,698

achieving a pre-distill PPL of 15,300. Removing layers consistently degrades quality: even retaining 56 of 64 layers substantially increases PPL, confirming that depth preservation is critical for structured pruning at this compression ratio.

Distillation. The selected D2D student is distilled with its dense teacher (Qwen3-32B) using identical hyperparameters, data, and token budget as all MoE-to-dense experiments. Despite this careful setup, D2D achieves only 33.28% average accuracy, barely above the random FFN baseline (32.70%, +0.6 pp) and far below even the weakest MoE-to-dense configuration (SF×AB, 36.31%, +3.0 pp). This suggests that dense pruning at this compression ratio provides little structural advantage, while MoE-to-dense conversion preserves expert-level structure as a stronger initialization for distillation.

R. Extended training

Table 15. Extended training results after ~4B tokens. The ranking established at 0.3B tokens holds at scale: DO-ACP maintains its advantage, reaching 58.10% average accuracy, +6.3 pp over D2D and +12.7 pp over random FFN.

Configuration	Wino	Hella	ARC-E	ARC-C	MMLU	Avg (%)
DO-ACP, $K=8$	**63.1**	**60.3**	**75.6**	**45.4**	**46.1**	**58.10**
SF, $K=16$	61.2	56.3	74.0	43.1	32.7	53.46
D2D pruning (Qwen3-32B → 3.4B)	60.5	57.5	73.1	41.5	26.6	51.84
Random FFN + teacher attn	54.4	45.4	66.0	34.2	27.1	45.44
Qwen3-1.7B (pretrained reference)	66.1	67.1	81.9	55.5	62.6	66.63
Qwen3-4B (pretrained reference)	72.0	75.8	86.2	64.6	73.1	74.34

All results in Section 3.2 use 0.3B-token distillation. To investigate whether our findings persist at scale, we train four configurations for ~4B tokens. The four configurations are: **DO-ACP** $K=8$ (our best), **SF** $K=16$ with weight clustering (best selection-frequency configuration from Section 3.2), **D2D** (dense-to-dense pruning baseline), and **Random FFN** (random FFN + teacher attention).

The ranking established at 0.3B tokens holds at scale. DO-ACP reaches **58.10%** average accuracy, outperforming D2D pruning (51.84%) by +6.3 pp, SF (53.46%) by +4.6 pp, and random FFN (45.44%) by +12.7 pp (Table 15). The gap is especially pronounced on MMLU: DO-ACP reaches 46.1% versus 32.7% (SF), 26.6% (D2D), and 27.1% (random), suggesting that diversity-aware expert selection may particularly benefit

Figure 7. Validation CE loss during extended training. DO-ACP maintains the lowest loss throughout.

knowledge-intensive tasks during extended training. Figure 7 confirms that DO-ACP maintains the lowest validation CE loss throughout training. We provide a qualitative analysis of these checkpoints, including a taxonomy of failure modes, knowledge-error rates, and a subject-level breakdown, in Appendix L.

We also highlight that MoE-to-dense distillation is faster than dense-to-dense (D2D) pruning: 73 s/step vs. 116 s/step on identical hardware (2×B200 GPUs, GBS=384), a **1.6× speedup**. This is due to the more efficient inference of the MoE teacher (Qwen3-30B-A3B), which activates only 3B parameters per token, while the dense teacher (Qwen3-32B) runs all 32B.

S. Cross-model validation

To test whether our findings generalize beyond Qwen3, we apply the pipeline to two additional MoE architectures that span different expert counts (32–128), routing widths (4–8), and training stages: **DeepSeek-V2-Lite** (DeepSeek-AI, 2024) (16B, 64 routed + 2 shared experts, top-6, base) and **GPT-OSS-20B** (Agarwal et al., 2025) (21B, 32 experts, top-4, post-trained). For each, the dense FFN width matches the teacher's active FFN computation per token; model-specific architectural adjustments are described in Appendix T. Figure 3 (main text) summarizes the results, and Tables 16 and 17 below provide per-benchmark numbers for all cross-model configurations.

The best configuration uses pure pruning on all architectures. On all three models, the single best configuration uses pure pruning ($K=k$): DO-ACP at $K=8$ on Qwen3 (Section 3.2), DO-ACP at $K=6$ on DeepSeek (42.39% vs. 41.07% at $K=12$), and DO-ACP at $K=4$ on GPT-OSS (33.71% vs. 32.11% at $K=8$). However, the interaction between scoring and K is more nuanced: on DeepSeek, merging ($K=12$) outperforms pure pruning ($K=6$) for SF (+1.1 pp), CP (+2.5 pp), and ACP (+0.6 pp), while only DO-ACP benefits from pure pruning (+1.3 pp). This suggests that diversity-aware scoring selects experts that are individually strong enough to stand alone, whereas frequency-based methods select redundant generalists that benefit from averaging.

Expert pool size modulates the benefit of expert selection. DO-ACP and ACP remain among the top scoring methods on both additional models, but the advantage of diversity-aware scoring diminishes with smaller expert pools. The scoring gap (best vs. worst method at $K=k$) shrinks from 7.1 pp on Qwen3 (128 experts) to 4.3 pp on DeepSeek (64 experts) to 1.6 pp on GPT-OSS (32 experts). The overall benefit of MoE-to-dense over random baselines follows the same trend: +13.3 pp, +12.1 pp, and +3.7 pp respectively. We attribute this to redundancy in the expert pool: with 128 experts and $K=8$, many candidates are interchangeable, giving diversity-aware methods room to outperform naive selection, while with only 32 experts and $K=4$, each expert handles a larger share of tokens, leaving less room for scoring to differentiate.

Table 16. DeepSeek-V2-Lite cross-model validation (16B → dense, 0.3B-token distillation). Rows sorted by scoring method; both $K=6$ (pure pruning) and $K=12$ (merging) shown. **Bold**: best per column.

Scoring	K	Wino	Hella	ARC-E	ARC-C	MMLU	Avg (%)
SF	6	54.9	38.9	52.4	27.1	26.9	40.04
SF	12	56.9	41.1	**54.8**	**28.4**	24.6	41.16
CP	6	53.0	36.9	49.4	25.7	25.3	38.07
CP	12	55.6	40.2	53.5	26.6	26.8	40.53
ACP	6	56.8	38.6	51.0	27.5	28.1	40.37
ACP	12	57.1	40.9	52.9	27.4	26.4	40.93
DO-ACP	6	**60.3**	41.0	53.7	28.2	**28.7**	**42.39**
DO-ACP	12	59.0	**41.5**	51.7	26.2	26.9	41.07
Random FFN + teacher attn		50.6	25.6	30.6	20.9	23.6	30.25
Random initialization		50.1	25.4	28.8	24.1	22.9	30.27
Teacher (DeepSeek-V2-Lite)		76.2	80.5	84.4	56.3	58.0	71.09

Table 17. GPT-OSS-20B cross-model validation (21B → dense, 0.3B-token distillation). Both $K=4$ (pure pruning) and $K=8$ (merging) shown. **Bold**: best per column. [†]Post-trained reasoning model evaluated in completion mode; native-format performance is expected to be substantially higher.

Scoring	K	Wino	Hella	ARC-E	ARC-C	MMLU	Avg (%)
SF	4	51.6	29.4	34.0	22.4	23.3	32.15
SF	8	51.6	29.3	33.3	21.7	22.8	31.72
CP	4	50.9	30.4	**36.4**	23.0	23.6	32.86
CP	8	49.7	29.3	32.2	23.2	23.1	31.49
ACP	4	53.0	31.9	35.6	23.0	23.3	33.36
ACP	8	**53.1**	30.5	33.6	23.3	**23.7**	32.82
DO-ACP	4	53.0	**32.1**	36.7	23.2	**23.7**	**33.71**
DO-ACP	8	51.3	29.9	33.5	22.5	23.3	32.11
Random FFN + teacher attn		50.2	27.5	28.5	23.0	23.2	30.46
Random initialization		50.0	26.0	25.8	**25.3**	23.0	30.02
Teacher (GPT-OSS-20B)[†]		59.3	39.9	80.9	53.7	49.6	56.67

T. Model architecture details

Table 18 summarizes the original teacher architectures and the dense students produced by our pipeline for all three models. Below, for each non-Qwen3 model we describe the original MoE architecture and then the adjustments needed to convert it to a dense FFN whose width matches the teacher's active FFN computation per token.

Table 18. Architecture of each MoE teacher and the corresponding dense student produced by our pipeline. [†]DeepSeek-V2-Lite has 2 shared experts per MoE layer; layer 0 is a standard dense FFN (zero-padded to match d_{dense}).

Property	Qwen3-30B-A3B	DeepSeek-V2-Lite	GPT-OSS-20B
Teacher			
Total parameters	30.5B	15.7B	20.9B
Active parameters	3.3B	2.4B	3.6B
Hidden dimension (d)	2,048	2,048	2,880
Routed experts / layer (E)	128	64[†]	32
Active routed experts (k)	8	6	4
Shared experts / layer	–	2[†]	–
Dense Student			
Total / active parameters	3.3B	2.4B	3.6B
Groups	8	8 (2 shared + 6 routed)	4
FFN intermediate dim (d_{dense})	6,144 ($= 8 \times 768$)	11,264 ($= 8 \times 1,408$)	11,520 ($= 4 \times 2,880$)

DeepSeek-V2-Lite. The original 16B-parameter model has 64 routed experts plus 2 shared (always-on) experts per MoE layer with top-k=6 routing, expert intermediate dimension 1,408, and a single non-MoE first layer (a standard dense FFN of intermediate dimension 10,944). Unlike Qwen3 and GPT-OSS, it does *not* renormalize routing probabilities after the top-k cut, so the routed experts' weights do not sum to one. To convert, we treat the two shared experts as always-on additions alongside the routed experts: $2 + 6 = 8$ FFN components are active per token, giving $d_{\text{dense}} = 8 \times 1408 = 11,264$. The shared experts are copied directly with DP scale 1.0 since router weighting does not apply to them, and our K parameter governs only the routed experts. Because routing is not renormalized, we use each group's average conditional probability as the DP scaling ratio, matching the average scaling the MoE applies to each expert's output. The first layer is zero-padded from 10,944 to 11,264 to match subsequent layers.

GPT-OSS-20B. The original 21B-parameter model has 32 routed experts per MoE layer with top-k=4 routing, expert intermediate dimension 2,880, and renormalizes routing probabilities after the top-k cut. It is a post-trained reasoning model that generates chain-of-thought traces before answers in its native chat-template format. To convert, we set $d_{\text{dense}} = 4 \times 2880 = 11,520$. Because routing is renormalized (matching Qwen3), we sweep both uniform and proportional DP scaling (Section 2.4). We evaluate all models (teacher and students) in standard completion mode for consistency with the other two architectures; this underestimates the teacher's native-format capability (e.g., MMLU 49% in completion mode vs. 72% with the chat template).

U. Conclusion

We presented the first systematic framework for converting a Mixture-of-Experts language model into a fully dense architecture via expert scoring, grouping, and concatenating, followed by knowledge distillation. We introduced a diversity-aware expert selection criterion (DO-ACP) based on the Gram log-determinant that jointly maximizes expert importance and mutual diversity. We evaluated 350 scoring$\times$grouping$\times$scaling$\times K$ combinations on Qwen3-30B-A3B (128 experts) and validated findings on DeepSeek-V2-Lite (64+2 experts) and GPT-OSS-20B (32 experts).

Our evaluation reveals that expert scoring is the dominant design axis (5.7 pp spread vs. $\sim$1 pp for grouping), with DO-ACP achieving the best accuracy across all configurations and all three models. Diversity-aware scoring enables effective pure pruning: on every architecture, the best configuration retains exactly $K=k$ experts with no weight averaging. MoE-to-dense outperforms dense-to-dense pruning by +6.3 pp after $\sim$4B-token distillation at 1.6$\times$ faster training wall-clock speed. Together, these findings point to a simple recipe: scoring with DO-ACP, retaining exactly the top-k experts per layer, and distilling with forward KL.

V. Limitations

When merging is used ($K > k$), our framework ties merge weights to selection scores, and decoupling these may improve such configurations. Our extended training reaches $\sim$4B tokens, and scaling to tens of billions is needed to establish the quality ceiling. The benefit of our method over random FFN initialization on GPT-OSS (+3.3 pp with 32 experts) is smaller than on Qwen3 (+10.7 pp with 128 experts), suggesting effectiveness depends on expert pool size.