# Provably Efficient Adversarial Imitation Learning with Unknown Transitions

## Abstract

The process of learning good policies from expert demonstrations, known as imitation learning (IL), has been proven effective in many applications. Adversarial imitation learning (AIL), a subset of IL methods, is particularly promising, but its theoretical foundation in the presence of unknown transitions has yet to be fully developed. This paper explores the theoretical underpinnings of AIL in this context, where the primary challenge is the stochastic and uncertain nature of environment transitions. We examine the expert sample complexity and interaction complexity required to recover good policies, which are of great practical interest. To this end, we establish a framework connecting reward-free exploration and AIL, and propose an algorithm, MB-TAIL, that achieves the minimax optimal expert sample complexity of $\widetilde{\mathcal{O}}(H^{3/2}|\mathcal{S}|/\varepsilon)$ and interaction complexity of $\widetilde{\mathcal{O}}(H^3|\mathcal{S}|^2|\mathcal{A}|/\varepsilon^2)$. Here, $H$ represents the planning horizon, $|\mathcal{S}|$ is the state space size, $|\mathcal{A}|$ is the action space size, and $\varepsilon$ is the desired imitation gap. MB-TAIL is the first algorithm to achieve this level of expert sample complexity in the unknown transition setting and improves upon the interaction complexity of the best-known algorithm, OAL, by $\mathcal{O}(H)$. Additionally, we demonstrate the generalization ability of MB-TAIL by extending it to the function approximation setting and proving that it can achieve expert sample and interaction complexity independent of $|\mathcal{S}|$.

## 1 INTRODUCTION

In real-life scenarios, sequential decision-making tasks are ubiquitous, where agents devise policies to maximize the long-term return. Reinforcement learning (RL) [Sutton and Barto, 2018] is a popular paradigm for learning effective policies through trial and error in unknown environments. However, RL often requires millions of samples to achieve satisfactory performance in practice [Mnih et al., 2015, Duan et al., 2016]. Alternatively, imitation learning (IL) [Argall et al., 2009, Osa et al., 2018] provides a more sample-efficient approach to policy optimization by directly learning from expert demonstrations, and has been proven successful in various applications [Levine et al., 2016, Shi et al., 2019, Jang et al., 2022]. By leveraging existing expert knowledge, IL methods enable efficient policy learning in situations where RL might be infeasible or expensive. Therefore, IL has become an increasingly popular and practical alternative for real-world applications.

Imitation learning (IL) is a framework that aims to minimize the difference between the expert policy and the imitated policy [Ross and Bagnell, 2010, Xu et al., 2020, Rajaraman et al., 2020]. The two prominent IL methods are behavioral cloning (BC) [Pomerleau, 1991, Ross and Bagnell, 2010] and adversarial imitation learning (AIL) [Abbeel and Ng, 2004, Syed and Schapire, 2007, Ziebart et al., 2008, Ho and Ermon, 2016]. BC employs supervised learning to minimize the discrepancy between the policy distribution of the imitated policy and the expert policy. On the other hand, AIL focuses on state-action distribution matching, where the learner estimates an adversarial reward function that maximizes the policy value gap and then learns a policy to minimize the gap with the inferred reward function through a min-max optimization. Practical algorithms that build upon these principles have been developed and applied to various domains [Torabi et al., 2018, Fu et al., 2018, Ke et al., 2019, Kostrikov et al., 2019, Brantley et al., 2020, Garg et al., 2021, Dadashi et al., 2021].

A remarkable observation from empirical studies [Ho and Ermon, 2016, Kostrikov et al., 2019, Ghasemipour et al., 2019] is that adversarial imitation learning (AIL) often outperforms behavioral cloning (BC) by a significant margin. This phenomenon has spurred numerous theoretical investigations [Zhang et al., 2020, Wang et al., 2020b, Rajaraman

et al., 2020, 2021a, Xu et al., 2020, Liu et al., 2021, Li et al., 2022, Xu et al., 2022] aimed at understanding the mechanisms of AIL. However, analyzing AIL is challenging because both the expert policy and environment transitions are unknown, making expert estimation and policy optimization/evaluation inaccurate. The complex min-max implementation of AIL further compounds the theoretical analysis difficulty. As a result, several prior works [Abbeel and Ng, 2004, Syed et al., 2008, Rajaraman et al., 2020, 2021a, Xu et al., 2022] have made the simplifying assumption of a known transition function to facilitate the analysis.

However, the characterization of environment transitions is often challenging in practical tasks, as noted in previous studies [Duan et al., 2016, Shi et al., 2019]. Therefore, there has been growing interest in investigating AIL with unknown transitions, where the learner does not have prior knowledge of the transition function but can collect trajectories by interacting with the environment. This setup is widely used in empirical studies [Ho and Ermon, 2016, Fu et al., 2018, Ke et al., 2019, Kostrikov et al., 2019, Brantley et al., 2020, Garg et al., 2021]. From a theoretical perspective, it is important to understand both the expert sample complexity (i.e., the number of expert trajectories required) and the interaction complexity (i.e., the number of environment interactions required) to achieve good policies, as these are of practical interest. In this paper, we investigate AIL with unknown transitions and focus on analyzing the required expert sample and interaction complexity.

Compared with the progress made in IL with known transitions, AIL with unknown transitions still lacks a well-developed theoretical foundation. Earlier works, such as FEM [Abbeel and Ng, 2005] and GTAL [Syed and Schapire, 2007], estimated the transition function from expert demonstrations for imitation, rendering their algorithms impractical due to the prohibitively large expert sample complexity (as shown in Table 1). To the best of our knowledge, the online apprenticeship learning (OAL) algorithm in [Shani et al., 2022] is a promising approach that updates the policy and reward function using no-regret algorithms during environment interaction. In particular, OAL achieves an expert sample complexity $\widetilde{\mathcal{O}}(H^2|\mathcal{S}|/\varepsilon^2)$ and interaction complexity $\widetilde{\mathcal{O}}(H^4|\mathcal{S}|^2|\mathcal{A}|/\varepsilon^2)$[1], where $|\mathcal{S}|$ and $|\mathcal{A}|$ are the state and action space sizes, $H$ is the planning horizon, and $\varepsilon = V^{\pi^{\mathrm{E}}} - V^{\pi}$ is the desired imitation gap. However, even with infinite environment interactions, OAL's expert sample complexity is sub-optimal, as the best expert sample complexity in the known transition setting is $\widetilde{\mathcal{O}}(H^{3/2}|\mathcal{S}|/\varepsilon)$ [Rajaraman et al., 2020]. Thus, improving AIL with unknown transitions is a significant area of research.

---

[1]In [Shani et al., 2022], a regret $\widetilde{\mathcal{O}}(\sqrt{H^4|\mathcal{S}|^2|\mathcal{A}|K} + \sqrt{H^3|\mathcal{S}||\mathcal{A}|K^2/m})$ is proved, where $K$ is the number of interaction episodes and $m$ is the number of expert trajectories. We convert this regret guarantee to the sample complexity guarantee (see Appendix B).

Table 1: Expert sample complexity and interaction complexity of BC [Rajaraman et al., 2020], FEM [Abbeel and Ng, 2004], GTAL [Syed and Schapire, 2007], OAL [Shani et al., 2022], and MB-TAIL (ours) with unknown expert and transitions. We use $\widetilde{\mathcal{O}}$ to hide logarithmic factors.

| | Expert Sample Complexity | Interaction Complexity |
|---|---|---|
| BC | $\widetilde{\mathcal{O}}\left(\frac{H^2|\mathcal{S}|}{\varepsilon}\right)$ | 0 |
| FEM | $\widetilde{\mathcal{O}}\left(\frac{H^2|\mathcal{S}|}{\varepsilon^2} + \frac{H^8|\mathcal{S}|^3|\mathcal{A}|}{\varepsilon^5}\right)$ | 0 |
| GTAL | $\widetilde{\mathcal{O}}\left(\frac{H^2|\mathcal{S}|}{\varepsilon^2} + \frac{H^6|\mathcal{S}|^3|\mathcal{A}|}{\varepsilon^3}\right)$ | 0 |
| OAL | $\widetilde{\mathcal{O}}\left(\frac{H^2|\mathcal{S}|}{\varepsilon^2}\right)$ | $\widetilde{\mathcal{O}}\left(\frac{H^4|\mathcal{S}|^2|\mathcal{A}|}{\varepsilon^2}\right)$ |
| MB-TAIL | $\widetilde{\mathcal{O}}\left(\frac{H^{3/2}|\mathcal{S}|}{\varepsilon}\right)$ | $\widetilde{\mathcal{O}}\left(\frac{H^3|\mathcal{S}|^2|\mathcal{A}|}{\varepsilon^2}\right)$ |

**Contribution.** This paper presents a new and general framework (Algorithm 1) that overcomes the challenge of unknown transitions and unknown expert policies. At a high level, our framework establishes a connection between AIL and reward-free exploration (RFE) [Jin et al., 2020, Ménard et al., 2021, Chen et al., 2022], which is an emerging topic in online RL. We prove that any effective AIL algorithm that works with known transitions can be transferred to the unknown transition setting using an efficient RFE method, as shown in Proposition 1.

Further, we also introduce a new algorithm called MB-TAIL[2], which incorporates recent advances in AIL with known transitions and RFE. MB-TAIL builds on MIMIC-MD [Rajaraman et al., 2020] and RF-Express [Ménard et al., 2021] but requires new designs to apply their main ideas in the unknown transition setting. Notably, MB-TAIL achieves an expert sample complexity of $\widetilde{\mathcal{O}}(H^{3/2}|\mathcal{S}|/\varepsilon)$, meeting the lower bound $\Omega(H^{3/2}/\varepsilon)$ [Rajaraman et al., 2021b] in $H$ and $\varepsilon$. This sample complexity is nearly minimax optimal and the first to be achieved in the unknown transition setting. Additionally, MB-TAIL has an interaction complexity of $\widetilde{\mathcal{O}}(H^3|\mathcal{S}|^2|\mathcal{A}|/\varepsilon^2)$, which improves upon the best-known OAL algorithm by a factor of $\mathcal{O}(H)$.

Finally, we extend the MB-TAIL algorithm to the function approximation setting and demonstrate its ability to achieve the expert sample and interaction complexity independent of the state space size $|\mathcal{S}|$. Specifically, we investigate the case of state abstraction [Li et al., 2006], which involves approximating functions using piecewise constant functions. By employing appropriate state abstractions, MB-TAIL can estimate the abstract state-action distribution instead of the tabular counterpart, which is crucial for generalization.

---

[2]MB-TAIL standards for model-based transition-aware adversarial imitation learning.

## 2 RELATED WORK

In the realm of AIL with known transitions, there have been numerous theoretical investigations into expert sample complexity [Abbeel and Ng, 2004, Syed and Schapire, 2007, Zahavy et al., 2020, Rajaraman et al., 2020, Swamy et al., 2022, Xu et al., 2021, 2022]. For example, FEM and GTAL, which are traditional AIL algorithms, have expert sample complexity of $\widetilde{\mathcal{O}}(H^2|\mathcal{S}|/\varepsilon^2)$ [3]. This upper bound is proven to be tight in the worst-case [Xu et al., 2022, Swamy et al., 2022]. Additionally, Rajaraman et al. [2020] proposed a novel AIL technique, MIMIC-MD, which leverages the transition function to obtain an enhanced expert sample complexity of $\widetilde{\mathcal{O}}(H^{3/2}|\mathcal{S}|/\varepsilon)$. MIMIC-MD meets the information-theoretic lower bound of expert sample complexity with known transitions, which is $\widetilde{\Omega}(H^{3/2}/\varepsilon)$ [Rajaraman et al., 2021b], in terms of both $H$ and $\varepsilon$. Recently, horizon-free expert sample complexity was studied in [Xu et al., 2022], which explains the superior performance of AIL with known transitions. However, there are only a limited number of theoretical investigations into AIL with unknown transitions. We have already discussed these in the previous section and thus will not repeat them here.

Our research establishes a connection between adversarial imitation learning and reward-free exploration, which is an emerging area of interest in online reinforcement learning. The reward-free exploration framework was introduced in [Jin et al., 2020] with two primary goals: 1) isolating the exploration and planning problems within a standard RL framework and 2) learning an environment that is robust enough to cover all possible training scenarios. Since then, several advances have been made in this field [Kaufmann et al., 2021, Wang et al., 2020a, Zhang et al., 2021, Chen et al., 2022]. Specifically, [Ménard et al., 2021] achieved the minimax rate in the tabular setting.

## 3 BACKGROUND

**Episodic Markov Decision Process.** In this paper, we consider episodic Markov decision process (MDP), which can be described by the tuple $\mathcal{M} = (\mathcal{S}, \mathcal{A}, \mathcal{P}, r, H, \rho)$. Here $\mathcal{S}$ and $\mathcal{A}$ are the state and action space, respectively. $H$ is the planning horizon and $\rho$ is the initial state distribution. $P = \{P_1, \cdots, P_H\}$ specifies the non-stationary transition function of this MDP; concretely, $P_h(s_{h+1}|s_h, a_h)$ determines the probability of transiting to state $s_{h+1}$ conditioned on state $s_h$ and action $a_h$ at time step $h$, for $h \in [H]$, where $[x]$ denotes the set of integers from 1 to $x$. Similarly, $r = \{r_1, \cdots, r_H\}$ specifies the reward function

---

of this MDP; without loss of generality, we assume that $r_h : \mathcal{S} \times \mathcal{A} \to [0, 1]$, for $h \in [H]$. A non-stationary policy $\pi = \{\pi_1, \cdots, \pi_h\}$ with $\pi_h : \mathcal{S} \to \Delta(\mathcal{A})$, where $\Delta(\mathcal{A})$ is the probability simplex and $\pi_h(a|s)$ gives the probability of selecting action $a$ on state $s$ at time step $h$, for $h \in [H]$.

The sequential decision process runs as follows: at the beginning of an episode, the environment is reset to an initial state according to $\rho$; then the agent observes a state $s_h$ and takes an action $a_h$ based on $\pi_h(a_h|s_h)$; consequently, the environment makes a transition to the next state $s_{h+1}$ according to $P_h(s_{h+1}|s_h, a_h)$ and sends a reward $r_h(s_h, a_h)$ to the agent. This episode ends after $H$ repeats.

The quality of a policy is measured by its *policy value* (i.e., the expected return): $V^\pi = \mathbb{E}[\sum_{h=1}^{H} r_h(s_h, a_h)|s_1 \sim \rho; a_h \sim \pi_h(\cdot|s_h), s_{h+1} \sim P_h(\cdot|s_h, a_h), \forall h \in [H]]$. To facilitate later analysis, we introduce the state-action distribution induced by a policy $\pi$:

$$d_h^\pi(s, a) = \mathbb{P}(s_h = s, a_h = a|s_1 \sim \rho; a_\ell \sim \pi_\ell(\cdot|s_\ell),$$
$$s_{\ell+1} \sim P_\ell(\cdot|s_\ell, a_\ell), \forall \ell \in [h]).$$

In other words, $d_h^\pi(s, a)$ qualifies the visitation probability of state-action pair $(s, a)$ at time step $h$. In this way, we get an equivalent dual form of the policy value [Puterman, 2014]:

$$V^\pi = \sum_{h=1}^{H} \sum_{(s,a) \in \mathcal{S} \times \mathcal{A}} d_h^\pi(s, a) r_h(s, a), \qquad (1)$$

which will be used in later analysis.

**Imitation Learning.** The goal of IL is to learn a high quality policy *without* the environment reward function. To this end, we often assume there is a nearly optimal expert policy $\pi^E$ that could interact with the environment to generate a dataset (i.e., $m$ trajectories of length $H$):

$$\mathcal{D} = \{\mathbf{tr} = (s_1, a_1, s_2, a_2, \cdots, s_H, a_H); s_1 \sim \rho;$$
$$a_h \sim \pi_h^E(\cdot|s_h), s_{h+1} \sim P_h(\cdot|s_h, a_h), \forall h \in [H]\}.$$

Then, the learner can use the dataset $\mathcal{D}$ to mimic the expert and to obtain a good policy. The quality of imitation is measured by the *imitation gap* [Abbeel and Ng, 2004, Ross and Bagnell, 2010, Rajaraman et al., 2020]: $V^{\pi^E} - V^\pi$, where $\pi$ is the learned policy. That is, we hope the learned policy can perfectly imitate the expert such that the imitation gap is small. In this paper, we assume the expert policy is deterministic, which is common in the literature [Rajaraman et al., 2020, Swamy et al., 2022, Xu et al., 2022].

**Notation.** We denote $\Pi$ as the set of all stochastic policies for the learner. Furthermore, $|\mathcal{D}|$ is the number of trajectories in $\mathcal{D}$. We reserve the symbol $m$ to denote the number of expert trajectories. We write $a(n) \gtrsim b(n)$ if there exist constants $C > 0, n_0 \geq 1$ such that $a(n) \geq Cb(n)$ for $n \geq n_0$.

---

[3]The infinite-horizon results from [Abbeel and Ng, 2004, Syed and Schapire, 2007] are transformed to the episodic setting by 1) substituting the effective planning horizon $1/(1 - \gamma)$ with the finite planning horizon $H$; 2) instantiating the linear feature with the one-hot feature under the tabular setting.

# 4 WARM-UP: AIL WITH KNOWN TRANSITIONS

To imitate the expert policy, AIL methods solve the state-action distribution matching problem [Ho and Ermon, 2016, Ke et al., 2019, Xu et al., 2020]. As an introduction to general readers, we consider the known transition setting in this section. Our starting point is the following state-action distribution matching problem:

$$\min_{\pi \in \Pi} \sum_{h=1}^{H} \left\| d_h^\pi - \widetilde{d}_h^{\pi^{\mathrm{E}}} \right\|_1. \tag{2}$$

where $\widetilde{d}_h^{\pi^{\mathrm{E}}}$ is an estimation of the expert state-action distribution $d_h^{\pi^{\mathrm{E}}}$. We can explain why Equation (2) is a good learning objective with the following two definitions.

**Definition 1.** *An estimator $\widetilde{d}_h^{\pi^{\mathrm{E}}}$ is said to be $\varepsilon_{\mathrm{EST}}$-accurate for $d_h^{\pi^{\mathrm{E}}}$ if $\sum_{h=1}^{H} \|\widetilde{d}_h^{\pi^{\mathrm{E}}} - d_h^{\pi^{\mathrm{E}}}\|_1 \leq \varepsilon_{\mathrm{EST}}$.*

**Definition 2.** *For optimization problem (2), a policy $\overline{\pi}$ is said to be $\varepsilon_{\mathrm{OPT}}$-optimal if $\sum_{h=1}^{H} \|d_h^{\overline{\pi}} - \widetilde{d}_h^{\pi^{\mathrm{E}}}\|_1 \leq \min_{\pi \in \Pi} \sum_{h=1}^{H} \|d_h^\pi - \widetilde{d}_h^{\pi^{\mathrm{E}}}\|_1 + \varepsilon_{\mathrm{OPT}}$.*

**Lemma 1.** *Given an $\varepsilon_{\mathrm{EST}}$-accurate estimator $\widetilde{d}_h^{\pi^{\mathrm{E}}}$, suppose that $\overline{\pi}$ is $\varepsilon_{\mathrm{OPT}}$-optimal for problem (2), then we have that $V^{\pi^{\mathrm{E}}} - V^{\overline{\pi}} \leq \varepsilon_{\mathrm{OPT}} + 2\varepsilon_{\mathrm{EST}}$.*

Proof of Lemma 1 can be found in the Appendix along with other theoretical results. This lemma establishes a strong theoretical foundation for state-action distribution matching. It is worth noting that similar versions of this lemma have been presented in prior works such as [Syed and Schapire, 2007, Rajaraman et al., 2020]. We will discuss how to control estimation and optimization errors in the next section.

While significant theoretical progress has been made in the known transition setting, this assumption is not always practical in real-world applications where the transition function is unknown. In such cases, empirical studies have been carried out under the unknown transition setting, where the interaction with environments is allowed but the analytic form of transition function is not available. In addition to expert sample complexity, the interaction complexity is also of great interest in this scenario, which we will explore in the next section.

# 5 MAIN RESULTS: AIL WITH UNKNOWN TRANSITIONS

In this section, we consider the unknown transition setting where $d_h^\pi$ is not accessible, rendering the learning objective in Equation (2) inapplicable. A sound solution is to replace $d_h^\pi$ with its estimated version $\widehat{d}_h^\pi$ in Equation (2). We highlight that the unknown transition leads to the exploration-and-exploitation trade-off, which is shared with online RL

[Agarwal et al., 2022]. The prior work OAL addresses this challenge by an optimistic estimation of the value function [Shani et al., 2022].

In this paper, we explore an alternative model-based approach: we first learn the transition function from collected trajectories and subsequently estimate $d_h^\pi$ based on the recovered transition model. The key challenge is how to recover a good transition model such that policy evaluation/optimization can be conducted accurately. To this end, we propose a general algorithmic framework, which connects AIL with reward-free exploration (or RFE for short) [Jin et al., 2020, Ménard et al., 2021], which is an emerging topic in online RL. Under this framework, a proper AIL algorithm that works under the known transition setting could be transferred to the unknown transition setting by leveraging an efficient RFE method. Before presenting the details of our framework, we formally introduce RFE.

**Definition 3** ([Ménard et al., 2021]). *Given an MDP $\mathcal{M}$ without reward function $r$, an algorithm is said to be $(\varepsilon, \delta)$-PAC for reward-free exploration (RFE) if*

$$\mathbb{P}(\text{for any reward function } r, |V^{\pi_r^*} - V^{\widehat{\pi}_r^*}| \leq \varepsilon) \geq 1 - \delta,$$

*where $\pi_r^*$ is the optimal policy in the MDP with the reward function $r$, and $\widehat{\pi}_r^*$ is the optimal policy in the MDP with the learned transition model $\widehat{P}$ by RFE and reward function $r$.*

**Lemma 2** (Lemma 3.6 of Jin et al. [2020]). *An $(\varepsilon, \delta)$-PAC reward-free exploration (RFE) method enables the uniform policy evaluation property, i.e., with probability at least $1 - \delta$, for any reward function $r$ and policy $\pi$, we have*

$$\left| V^{\pi, P, r} - V^{\pi, \widehat{P}, r} \right| \leq \varepsilon,$$

*where $V^{\pi, P, r}$ and $V^{\pi, \widehat{P}, r}$ are the policy values of policy $\pi$ with reward function $r$ under the real transition model $P$ and recovered transition model $\widehat{P}$ by RFE, respectively.*

Lemma 2 is crucial for AIL. To see this point, we note that

$$\sum_{h=1}^{H} \|\widehat{d}_h^\pi - d_h^\pi\|_1$$

$$= \max_{w \in \mathcal{W}} \sum_{h=1}^{H} \sum_{(s,a)} w_h(s,a)(\widehat{d}_h^\pi(s,a) - d_h^\pi(s,a))$$

$$= \max_{w \in \mathcal{W}} V^{\pi, \widehat{P}, w} - V^{\pi, P, w} \leq \varepsilon.$$

Here the first equality follows the dual representation of $\ell_1$-norm, and $\mathcal{W} = \{w : \|w\|_\infty \leq 1\}$ is the unit ball. The second equality follows Equation (1). The last inequality follows Definition 3. In plain language, the above formula shows that we can get an accurate estimation of $d_h^\pi$, based on the recovered model by RFE.

Based on the above relation, with a transition model learned by RFE, AIL can be implemented as if this empirical transition function were the same as the true transition function. More specifically, the state-action distribution matching problem Equation (2) becomes

$$\min_{\pi \in \Pi} \sum_{h=1}^{H} \left\| \widetilde{d}_h^{\pi^{\mathrm{E}}} - d_h^{\pi, \widehat{P}} \right\|_1 \tag{3}$$

where $d_h^{\pi, \widehat{P}}$ is the state-action distribution of policy $\pi$ with the transition model $\widehat{P}$. We outline the whole procedure in Algorithm 1 and the theoretical guarantee is provided below.

**Proposition 1.** *Suppose that*

(a) *an algorithm A solves the reward-free exploration problem (see Definition 3) up to an error $\varepsilon_{\mathrm{RFE}}$ with probability at least $1 - \delta_{\mathrm{RFE}}$;*

(b) *an algorithm B has a state-action distribution estimator for $d_h^{\pi^{\mathrm{E}}}$, which satisfies $\sum_{h=1}^{H} \|\widetilde{d}_h^{\pi^{\mathrm{E}}} - d_h^{\pi^{\mathrm{E}}}\|_1 \leq \varepsilon_{\mathrm{EST}}$, with probability at least $1 - \delta_{\mathrm{EST}}$;*

(c) *with the transition model in (a) and the estimator in (b), an algorithm C solves the optimization problem in Equation (3) up to an error $\varepsilon_{\mathrm{OPT}}$.*

*Then applying algorithms A, B and C under the framework in Algorithm 1 could return a policy $\overline{\pi}$, which has a policy value gap (i.e., $V^{\pi^{\mathrm{E}}} - V^{\overline{\pi}}$) at most $2\varepsilon_{\mathrm{EST}} + 2\varepsilon_{\mathrm{RFE}} + \varepsilon_{\mathrm{OPT}}$, with probability at least $1 - \delta_{\mathrm{EST}} - \delta_{\mathrm{RFE}}$.*

---

**Algorithm 1** Meta-algorithm For AIL with Unknown Transitions

---

**Input:** Expert demonstrations $\mathcal{D}$.
1: $\widehat{P} \leftarrow$ Invoke a reward-free exploration method to collect $n$ trajectories and learn a transition model.
2: $\widetilde{d}_h^{\pi^{\mathrm{E}}} \leftarrow$ Estimate the expert state-action distribution.
3: $\overline{\pi} \leftarrow$ Apply an AIL approach to perform imitation with the expert estimation $\widetilde{d}_h^{\pi^{\mathrm{E}}}$ under transition model $\widehat{P}$.
**Output:** Policy $\overline{\pi}$.

---

Next, we show how to substantiate the framework in Algorithm 1 with detailed procedures. We will consider the tabular formulation, where the space of parameterized value functions spans all possible functions. In this scenario, expert policies and reward functions are realizable. We discuss how to control $\varepsilon_{\mathrm{RFE}}$, $\varepsilon_{\mathrm{EST}}$, and $\varepsilon_{\mathrm{OPT}}$ in a sequential order.

## 5.1 CONTROLLING REWARD-FREE EXPLORATION ERROR

We leverage the advanced algorithm called RF-Express in [Ménard et al., 2021] to control $\varepsilon_{\mathrm{RFE}}$, whose theoretical property is stated below.

**Lemma 3** (Theorem 1 in [Ménard et al., 2021]). *Fix $\varepsilon \in (0, 1)$ and $\delta \in (0, 1)$. Consider the RF-Express algorithm (see Algorithm 4 in Appendix) and $\widehat{P}$ is the empirical transition function built on the collected trajectories, if the number of trajectories collected by RF-Express satisfies*

$$n \gtrsim \frac{H^3 |\mathcal{S}||\mathcal{A}|}{\varepsilon^2} \left( |\mathcal{S}| + \log\left(\frac{|\mathcal{S}|H}{\delta}\right) \right).$$

*Then with probability at least $1 - \delta$, for any policy $\pi$ and any bounded reward function $r$ between $[-1, 1]$, we have[4] $|V^{\pi, P, r} - V^{\pi, \widehat{P}, r}| \leq \varepsilon/2$; furthermore, for any bounded reward function $r$ between $[-1, 1]$, we have $\max_{\pi \in \Pi} V^{\pi, P, r} \leq V^{\widehat{\pi}_r^*, P, r} + \varepsilon$, where $\widehat{\pi}_r^*$ is the optimal policy under the empirical transition function $\widehat{P}$ with reward function $r$.*

## 5.2 CONTROLLING EXPERT STATE-ACTION DISTRIBUTION ESTIMATION ERROR

In this part, we talk about how to control the expert state-action distribution estimation error. Quite often, the maximum likelihood estimator (MLE) is considered in the literature [Abbeel and Ng, 2004, Syed and Schapire, 2007, Shani et al., 2022]. Mathematically, MLE counts how frequently a state-action pair appears in the observed expert trajectories:

$$\widehat{d}_h^{\pi^{\mathrm{E}}}(s, a) = \frac{\sum_{\mathbf{tr} \in \mathcal{D}} \mathbb{I}\{\mathbf{tr}_h(\cdot, \cdot) = (s, a)\}}{|\mathcal{D}|}, \tag{4}$$

where $\mathbf{tr}_h(\cdot, \cdot)$ indicates the specific state-action pair of trajectory $\mathbf{tr}$ in time step $h$. The sample complexity of MLE is well-known.

**Lemma 4** (Rajaraman et al. [2020]). *Fix $\varepsilon \in (0, H)$ and $\delta \in (0, 1)$, if the number of expert trajectories in $\mathcal{D}$ satisfies*

$$m \gtrsim \frac{H^2 |\mathcal{S}|}{\varepsilon^2} \log\left(\frac{H}{\delta}\right),$$

*then with probability at least $1 - \delta$, we have $\sum_{h=1}^{H} \|\widehat{d}_h^{\pi^{\mathrm{E}}} - d_h^{\pi^{\mathrm{E}}}\|_1 \leq \varepsilon$.*

The above sample complexity of MLE is tight in the worst case; see, e.g., [Kamath et al., 2015, Lemma 8]. Though MLE can be implemented under our framework, this estimator cannot lead to the minimax optimal expert sample complexity $\Theta(H^{3/2}|\mathcal{S}|/\varepsilon)$. To address this issue, in light of [Rajaraman et al., 2020], we develop a new estimator. For a better presentation, let us introduce the following notations.

- Similar to $\mathbf{tr}_h(\cdot, \cdot)$, $\mathbf{tr}_h(\cdot)$ indicates the specific state of trajectory $\mathbf{tr}$ in time step $h$.

---

[4]This is implied by the stopping rule in RF-Express algorithm and Lemma 1 in [Ménard et al., 2021].

- Without $(\cdot)$ or $(\cdot,\cdot)$, $\mathbf{tr}_h$ is the truncated version of trajectory $\mathbf{tr}$ up to time step $h$, i.e., $\mathbf{tr}_h = (s_1, a_1, \cdots, s_h, a_h)$.

- $\mathcal{S}_h(\mathcal{D}) = \{s : \exists \mathbf{tr} \in \mathcal{D} \text{ such that } s = \mathbf{tr}_h(\cdot)\}$ is the set of states visited at time step $h$ in $\mathcal{D}$.

- $\mathrm{Tr}_h^{\mathcal{D}} = \{\mathbf{tr}_h = (s_1, a_1, \ldots, s_h, a_h) : s_\ell \in \mathcal{S}_\ell(\mathcal{D}), \forall \ell \in [h]\}$ is the set of truncated trajectories (that may not appear in $\mathcal{D}$), along which each state has been visited in $\mathcal{D}$ up to time step $h$.

Now, consider the dataset $\mathcal{D}$ is randomly divided into two equal parts, i.e., $\mathcal{D} = \mathcal{D}_1 \cup \mathcal{D}_1^c$ and $\mathcal{D}_1 \cap \mathcal{D}_1^c = \emptyset$ with $|\mathcal{D}_1| = |\mathcal{D}_1^c| = m/2$. We start from the following decomposition:

$$
d_h^{\pi^{\mathrm{E}}}(s,a) = \underbrace{\sum_{\mathbf{tr}_h \in \mathrm{Tr}_h^{\mathcal{D}_1}} \mathbb{P}^{\pi^{\mathrm{E}}}(\mathbf{tr}_h) \mathbb{I}\{\mathbf{tr}_h(\cdot,\cdot) = (s,a)\}}_{:= \clubsuit}
$$
$$
+ \underbrace{\sum_{\mathbf{tr}_h \notin \mathrm{Tr}_h^{\mathcal{D}_1}} \mathbb{P}^{\pi^{\mathrm{E}}}(\mathbf{tr}_h) \mathbb{I}\{\mathbf{tr}_h(\cdot,\cdot) = (s,a)\}, \quad (5)}_{:= \spadesuit}
$$

where $\mathbb{P}^{\pi^{\mathrm{E}}}(\mathbf{tr}_h)$ is the probability of the truncated trajectory $\mathbf{tr}_h$ induced by the deterministic expert policy $\pi^{\mathrm{E}}$. If the transition function is known, we can calculate $\mathbb{P}^{\pi^{\mathrm{E}}}(\mathbf{tr}_h)$ directly: $\mathbb{P}^{\pi^{\mathrm{E}}}(\mathbf{tr}_h) = \rho(s_1) \prod_{\ell=1}^{h-1} P_\ell(s_{\ell+1}|s_\ell, a_\ell)$ with $\mathbf{tr}_h = (s_1, a_1, \cdots, s_h, a_h)$

We explain two terms in Equation (5) separately. On the one hand, term $\clubsuit$ can be calculated exactly if we know both the transition function and $\mathcal{D}_1$, as explained previously. This is the key idea of MIMIC-MD [Rajaraman et al., 2020]: we can break the sample barrier with known transitions. However, this is not applicable in our case as the transition function is unknown. We will discuss how to deal with this trouble later. On the other hand, term $\spadesuit$ is not easy to compute as term $\clubsuit$, because we have no clue about expert actions on states that are not covered by $\mathcal{D}_1$. To address this issue, Rajaraman et al. [2020] propose to use trajectories in $\mathcal{D}_1^c$ to make a maximum likelihood estimation. This is because, $\mathcal{D}_1^c$ is statistically independent of $\mathcal{D}_1$ and therefore can be viewed as a new dataset. We follow the approach in [Rajaraman et al., 2020] to estimate term $\spadesuit$.

Now, we explain how to estimate term $\clubsuit$ in the unknown transition setting. Our solution has two steps. The first step is to apply BC on $\mathcal{D}_1$ to learn policy $\pi'$: $\pi'_h(a|s) = n_h^1(s,a)/n_h^1(s)$ if $n_h^1(s) > 0$; $\pi'_h(a|s) = 1/|\mathcal{A}|$, otherwise. Here $n_h^1(s,a)$ ($n_h^1(s)$) is the number of state-action (state) pairs that appeared in $\mathcal{D}_1$ in step $h$. The second step is to let $\pi'$ interact with the environment to collect a new dataset $\mathcal{D}'_{\mathrm{env}}$, from which we can estimate term $\clubsuit$ by MLE. To get a better sense, we mention that the uncertainty of estimating term $\clubsuit$ comes from the transition function, rather than the expert policy. Furthermore, by our design, trajectories in

$\mathcal{D}'_{\mathrm{env}}$ are collected as if the expert policy were roll-out (because $\pi'$ can perfectly match $\pi^{\mathrm{E}}$ on $\mathcal{S}(\mathcal{D}_1)$, see Lemma 7 in Appendix for more details), so the randomness of MLE is only caused by the stochastic transitions.

In summary, we arrive at the following estimator:

$$
\widetilde{d}_h^{\pi^{\mathrm{E}}}(s,a) = \frac{\sum_{\mathbf{tr}_h \in \mathcal{D}'_{\mathrm{env}}} \mathbb{I}\{\mathbf{tr}_h(\cdot,\cdot) = (s,a), \mathbf{tr}_h \in \mathrm{Tr}_h^{\mathcal{D}_1}\}}{|\mathcal{D}'_{\mathrm{env}}|}
$$
$$
+ \frac{\sum_{\mathbf{tr}_h \in \mathcal{D}_1^c} \mathbb{I}\{\mathbf{tr}_h(\cdot,\cdot) = (s,a), \mathbf{tr}_h \notin \mathrm{Tr}_h^{\mathcal{D}_1}\}}{|\mathcal{D}_1^c|}. \quad (6)
$$

Two terms in Equation (6) give estimation for terms $\clubsuit$ and $\spadesuit$, respectively.

**Lemma 5.** *Given the expert dataset $\mathcal{D}$, let $\mathcal{D}$ be divided into two equal subsets, i.e., $\mathcal{D} = \mathcal{D}_1 \cup \mathcal{D}_1^c$ and $\mathcal{D}_1 \cap \mathcal{D}_1^c = \emptyset$ with $|\mathcal{D}_1| = |\mathcal{D}_1^c| = m/2$. Fix $\pi' \in \Pi_{BC}(\mathcal{D}_1)$, let $\mathcal{D}'_{\mathrm{env}}$ be the dataset collected by $\pi'$ and $|\mathcal{D}'_{\mathrm{env}}| = n'$. Fix $\varepsilon \in (0,1)$ and $\delta \in (0,1)$; suppose $H \geq 5$. Consider the estimator $\widetilde{d}_h^{\pi^{\mathrm{E}}}$ shown in (6), if the expert sample complexity ($m$) and the interaction complexity ($n'$) satisfy*

$$
m \gtrsim \frac{H^{3/2}|\mathcal{S}|}{\varepsilon} \log\left(\frac{|\mathcal{S}|H}{\delta}\right), \quad n' \gtrsim \frac{H^2|\mathcal{S}|}{\varepsilon^2} \log\left(\frac{|\mathcal{S}|H}{\delta}\right),
$$

*then with probability at least $1 - \delta$, we have*

$$
\sum_{h=1}^{H} \left\|\widetilde{d}_h^{\pi^{\mathrm{E}}} - d_h^{\pi^{\mathrm{E}}}\right\|_1 \leq \varepsilon.
$$

To our best knowledge, the estimator (6) is the first to enjoy a better expert sample complexity than MLE in the unknown transition setting. After solving the estimation issue, we design computation-efficient algorithms to control $\varepsilon_{\mathrm{OPT}}$.

### 5.3 CONTROLLING OPTIMIZATION ERROR

We now consider the optimization issue. Again, we utilize the dual representation of $\ell_1$-norm and the min-max theorem [Bertsekas, 2016] to obtain the following max-min optimization problem:

$$
\max_{w \in \mathcal{W}} \min_{\pi \in \Pi} \sum_{h=1}^{H} \sum_{(s,a)} w_h(s,a)(\widetilde{d}_h^{\pi^{\mathrm{E}}}(s,a) - d_h^{\pi,\widehat{P}}(s,a)). \quad (7)
$$

where $\mathcal{W} = \{w : \|w\|_\infty \leq 1\}$ is the unit ball. We see that the inner problem in (7) is to maximize the policy value of $\pi$ given the reward function $w_h(s,a)$ (see Equation (1) for the dual form of policy value). For the outer optimization problem, we can use online gradient descent methods [Shalev-Shwartz, 2012] so that the overall objective can finally reach an approximate saddle point. Formally, let us define the objective $f^{(t)}(w)$:

$$
\underbrace{\sum_{h=1}^{H} \sum_{(s,a) \in \mathcal{S} \times \mathcal{A}} w_h(s,a) \left(d_h^{\pi^{(t)}, \widehat{P}}(s,a) - \widetilde{d}_h^{\pi^{\mathrm{E}}}(s,a)\right),}_{:= f^{(t)}(w)} \quad (8)
$$

where $\pi^{(t)}$ is the optimized policy in iteration $t$. Then the update rule for $w$ is:

$$w^{(t+1)} := \mathcal{P}_{\mathcal{W}}(w^{(t)} - \eta^{(t)} \nabla f^{(t)}(w^{(t)})),$$

where $\eta^{(t)} > 0$ is the stepsize to be chosen later, and $\mathcal{P}_{\mathcal{W}}$ is the Euclidean projection on the unit ball $\mathcal{W}$, i.e., $\mathcal{P}_{\mathcal{W}}(w) := \operatorname{argmin}_{z \in \mathcal{W}} \|z - w\|_2$. The procedure for solving (7) is outlined in Algorithm 2.

---

**Algorithm 2** Gradient-based Optimization

---

**Input:** Transition model $\widehat{P}$, and expert state-action distribution estimator $\widetilde{d}_h^{\pi^{\mathrm{E}}}$.

1: **for** $t = 1, 2, \cdots, T$ **do**
2:   $\pi^{(t)} \leftarrow$ Solve the optimal policy with the transition model $\widehat{P}$ and reward function $w^{(t)}$ up to an error $\varepsilon_{\mathrm{RL}}$.

3:   Compute the state-action distribution $d_h^{\pi^{(t)}, \widehat{P}}$ for $\pi^{(t)}$.

4:   Update $w^{(t+1)} := \mathcal{P}_{\mathcal{W}}\left(w^{(t)} - \eta^{(t)} \nabla f^{(t)}(w^{(t)})\right)$ with $f^{(t)}(w)$ defined in Equation (8).

5: **end for**
6: Compute the mean state-action distribution $\bar{d}_h(s, a) = \sum_{t=1}^{T} d_h^{\pi^{(t)}, \widehat{P}}(s, a) / T$.
7: Derive $\bar{\pi}_h(a|s) \leftarrow \bar{d}_h(s, a) / \sum_a \bar{d}_h(s, a)$.

**Output:** Policy $\bar{\pi}$.

---

Line 2 in Algorithm 2 formulates a typical reinforcement learning (RL) optimization problem. We allow $\pi^{(t)}$ to be $\varepsilon_{\mathrm{RL}}$-optimal with respect to the optimal policy with reward function $w^{(t)}$, i.e., $V^{\pi^{(t)}, \widehat{P}, w^{(t)}} \geq V^{\pi_{w^{(t)}}^*, \widehat{P}, w^{(t)}} - \varepsilon_{\mathrm{RL}}$. In the tabular case, $\varepsilon_{\mathrm{RL}} = 0$ by value iteration with finite and polynomial computation steps. For approximate methods such as policy gradient ascent, we require that they can guarantee $\varepsilon_{\mathrm{RL}}$ is small with low computational cost.

**Lemma 6.** *Fix $\varepsilon > 0$. Consider the gradient-based optimization procedure in Algorithm 2 with $\varepsilon_{\mathrm{RL}} \leq \varepsilon/2$. If we take $T \gtrsim H^2 |\mathcal{S}||\mathcal{A}| / \varepsilon^2$ and $\eta^{(t)} := \sqrt{|\mathcal{S}||\mathcal{A}| / (8T)}$, then we have*

$$\sum_{h=1}^{H} \left\| d_h^{\bar{\pi}, \widehat{P}} - \widetilde{d}_h^{\pi^{\mathrm{E}}} \right\|_1 \leq \min_{\pi \in \Pi} \sum_{h=1}^{H} \left\| d_h^{\pi, \widehat{P}} - \widetilde{d}_h^{\pi^{\mathrm{E}}} \right\|_1 + \varepsilon.$$

## 5.4 MB-TAIL: COMBING ALL TOGETHER

Combing the above all pieces together, we obtain the final approach called MB-TAIL presented in Algorithm 3. Here "MB-TAIL" standards for model-based transition-aware adversarial imitation learning.

**Theorem 1.** *Fix $\varepsilon \in (0, 1)$ and $\delta \in (0, 1)$; suppose $H \geq 5$. Under the unknown transition setting, consider MB-TAIL displayed in Algorithm 3 and $\bar{\pi}$ is output policy, assume that the RL error $\varepsilon_{\mathrm{RL}} \leq \varepsilon/2$, the number of iterations and the*

---

**Algorithm 3** Model-based Transition-aware AIL

---

**Input:** Expert demonstrations $\mathcal{D}$.
1: Invoke RF-Express to collect $n$ trajectories and learn an empirical transition function $\widehat{P}$.
2: Randomly split $\mathcal{D}$ into two equal parts: $\mathcal{D} = \mathcal{D}_1 \cup \mathcal{D}_1^c$.
3: Learn $\pi' \in \Pi_{\mathrm{BC}}(\mathcal{D}_1)$ by BC and roll out $\pi'$ to obtain dataset $\mathcal{D}_{\mathrm{env}}'$ with $|\mathcal{D}_{\mathrm{env}}'| = n'$.
4: Obtain the estimator $\widetilde{d}_h^{\pi^{\mathrm{E}}}$ in (6) with $\mathcal{D}$ and $\mathcal{D}_{\mathrm{env}}'$.
5: $\bar{\pi} \leftarrow$ Apply Algorithm 2 with the estimation $\widetilde{d}_h^{\pi^{\mathrm{E}}}$ under transition model $\widehat{P}$.

**Output:** Policy $\bar{\pi}$.

---

*step size are the same as in Lemma 6, if the expert sample complexity and the interaction complexity satisfy*

$$m \gtrsim \frac{H^{3/2}|\mathcal{S}|}{\varepsilon} \log\left(\frac{H|\mathcal{S}|}{\delta}\right), n' \gtrsim \frac{H^2|\mathcal{S}|}{\varepsilon^2} \log\left(\frac{H|\mathcal{S}|}{\delta}\right),$$

$$n \gtrsim \frac{H^3|\mathcal{S}||\mathcal{A}|}{\varepsilon^2}\left(|\mathcal{S}| + \log\left(\frac{H|\mathcal{S}||\mathcal{A}|}{\delta\varepsilon}\right)\right),$$

*then with probability at least $1 - \delta$, we have $V^{\pi^{\mathrm{E}}} - V^{\bar{\pi}} \leq \varepsilon$.*

**Remark 1.** *Our MB-TAIL algorithm achieves expert sample complexity $m = \widetilde{\mathcal{O}}(H^{3/2}|\mathcal{S}|/\varepsilon)$ and total interaction complexity $n + n' = \widetilde{\mathcal{O}}(H^3|\mathcal{S}|^2|\mathcal{A}|/\varepsilon^2)$, even in the case of unknown transitions. In comparison, the OAL algorithm in [Shani et al., 2022] has expert sample complexity $\widetilde{\mathcal{O}}(H^2|\mathcal{S}|/\varepsilon^2)$ and interaction complexity $\widetilde{\mathcal{O}}(H^4|\mathcal{S}|^2|\mathcal{A}|/\varepsilon^2)$ in the same scenario. Theorem 1 validates that our approach provides significant improvements over OAL in terms of both expert sample complexity and interaction complexity.*

**Simulation Studies.** Finally, we conclude by validating our theoretical results through experiments, where we compare the performance of MB-TAIL with four other state-of-the-art algorithms: BC [Pomerleau, 1991], FEM [Abbeel and Ng, 2005], GTAL [Syed and Schapire, 2007], and OAL [Shani et al., 2022]. All algorithms are given 100 expert trajectories, and we evaluate their performance on the Reset Cliff MDP (shown in Figure 2 in Appendix), which is known to be challenging for imitation learning algorithms [Rajaraman et al., 2020, Xu et al., 2021]. We conduct experiments with 20 random seeds, and provide more experimental details in Appendix F.

Figure 1 shows the imitation gap for each algorithm. Note that BC, FEM, and GTAL do not leverage environment interactions. Our results show that MB-TAIL outperforms FEM and GTAL when the number of interactions exceeds 500. Additionally, we observe that MB-TAIL outperforms OAL with the same number of interactions, which confirms the superior theoretical bounds of MB-TAIL.

Figure 1: The imitation gap (i.e., $V^{\pi^{\mathrm{E}}} - V^\pi$) in Reset Cliff.

## 6 MB-TAIL WITH STATE ABSTRACTION

Previously, we considered the tabular representation, which leads to theoretical bounds that depend on the size of the problem $|\mathcal{S}|$. However, as suggested by the lower bounds in [Rajaraman et al., 2020, Theorem 6.1, 6.2], this dependence is inevitable and could be unacceptable when $|\mathcal{S}|$ is huge. In this section, we investigate the use of state abstractions [Li et al., 2006] within MB-TAIL, so the dependence on $|\mathcal{S}|$ can be eliminated.

Specifically, we assume that we have a set of state abstractions $\{\phi_h\}_{h=1}^H$, where $\phi_h : \mathcal{S} \to \Phi$ and $\Phi$ is the abstract state space. State abstractions correspond to function approximations using a series of piecewise constant functions [Chen and Jiang, 2019]. The abstract state space is much smaller than the original state space, i.e., $|\Phi| \ll |\mathcal{S}|$. We also assume that $\{\phi_h\}_{h=1}^H$ satisfies a condition that is common in the literature [Li et al., 2006, Jiang et al., 2015].

**Assumption 1.** *There exists a set of known state abstractions $\{\phi_h\}_{h=1}^H$, which satisfies $\forall h \in [H]$, for any $s^1, s^2 \in \mathcal{S}$ such that $\phi_h(s^1) = \phi_h(s^2)$,*

$$\text{bisimulation} : \forall a \in \mathcal{A}, x' \in \Phi, r_h(s^1, a) = r_h(s^2, a) \quad (9)$$

$$\sum_{s' \in \phi_h^{-1}(x')} P_h(s'|s^1, a) = \sum_{s' \in \phi_h^{-1}(x')} P_h(s'|s^2, a); \quad (10)$$

$$\pi^{\mathrm{E}}\text{-irrelevant} : \pi_h^{\mathrm{E}}(s^1) = \pi_h^{\mathrm{E}}(s^2), \quad (11)$$

*where $\phi_h^{-1}(x') = \{s' \in \mathcal{S} : \phi_h(s) = x'\}$.*

In bisimulation, the reward-consistent condition in (9) ensures that two different states mapped to the same abstract state share an identical reward. We highlight that this condition is important for MB-TAIL to avoid the dependence of *expert sample complexity* on $|\mathcal{S}|$. In particular, the bottleneck of the sample complexity of AIL methods is the estimation of $d_h^{\pi^{\mathrm{E}}}(s, a)$. Under the reward-consistent condition, we can calculate the expert policy value as

$$V^{\pi^{\mathrm{E}}} = \sum_{h=1}^H \sum_{(s,a) \in \mathcal{S} \times \mathcal{A}} r_h(s, a) d_h^{\pi^{\mathrm{E}}}(s, a)$$

$$= \sum_{h=1}^H \sum_{(x,a) \in \Phi \times \mathcal{A}} r_h^\phi(x, a) d_h^{\pi^{\mathrm{E}}, \phi}(x, a),$$

where $r_h^\phi(x, a) = r_h(s, a)$ for an arbitrary $s \in \phi_h^{-1}(x)$ and $d_h^{\pi, \phi}(x, a) = \mathbb{P}^{\pi^{\mathrm{E}}}(\phi_h(s_h) = x, a_h = a) = \sum_{s \in \phi_h^{-1}(x)} d_h^\pi(s, a)$ is the abstract state-action distribution. With the above formulation, to estimate the expert policy value, we can estimate the *abstract* state-action distribution rather than the tabular counterpart, which can remove the dependence on $|\mathcal{S}|$. Analogously, the transition-consistent condition in (10) guarantees that two different states mapped to the same abstract state share an identical transition. This condition is crucial for removing the dependence of *interaction complexity* on $|\mathcal{S}|$ since it allows estimating the "abstract transition function".

We now extend MB-TAIL to the state abstraction setting, which we describe in detail in Appendix E.2 due to space limitations. We prove that under Assumption 1, MB-TAIL achieves expert sample and interaction complexities that are independent of $|\mathcal{S}|$. However, the proof is not straightforward, and the primary challenge is to connect the state-action distributions in the original and abstract MDPs. We provide a detailed discussion of the specialized analysis tools in the Appendix.

**Theorem 2.** *Under Assumption 1, fix $\varepsilon \in (0, 1)$ and $\delta \in (0, 1)$; suppose $H \geq 5$. Under the unknown transition setting, consider Algorithm 7 in Appendix and $[\overline{\pi}^\phi]^M$ is output policy. Assume that the RL error $\varepsilon_{\mathrm{RL}} \leq \varepsilon/2$, the number of iterations $T \gtrsim H^2|\Phi||\mathcal{A}|/\varepsilon^2$, and the step size $\eta^{(t)} := \sqrt{|\Phi||\mathcal{A}|/(8T)}$. If the number of expert trajectories $(m)$, the number of interaction trajectories for estimation $(n')$, and the number of interaction trajectories for reward-free exploration $(n)$ satisfy*

$$m \gtrsim \frac{|\Phi|H^{3/2}}{\varepsilon} \log\left(\frac{|\Phi|H}{\delta}\right), n' \gtrsim \frac{|\Phi|H^2}{\varepsilon^2} \log\left(\frac{|\Phi|H}{\delta}\right),$$

$$n \gtrsim \frac{|\Phi||\mathcal{A}|H^3}{\varepsilon^2} \left(|\Phi| + \log\left(\frac{|\Phi||\mathcal{A}|H}{\delta\varepsilon}\right)\right),$$

*then with probability at least $1-\delta$, we have $V^{\pi^{\mathrm{E}}} - V^{[\overline{\pi}^\phi]^M} \leq \varepsilon$.*

## 7 CONCLUSION

This paper contributes to the establishment of theoretical foundations for AIL with unknown transitions. We propose a new and general framework that enables AIL to explore and imitate efficiently. As mentioned, AIL methods can enjoy much better bounds on structured instances, such as horizon-free bounds suggested in [Xu et al., 2022]. Thus, we believe that investigating AIL with unknown transitions on structured instances is an interesting and valuable direction for future research.

# References

Pieter Abbeel and Andrew Y. Ng. Apprenticeship learning via inverse reinforcement learning. In *ICML*, pages 1–8, 2004.

Pieter Abbeel and Andrew Y. Ng. Exploration and apprenticeship learning in reinforcement learning. In *ICML*, pages 1–8, 2005.

Alekh Agarwal, Nan Jiang, Sham M. Kakade, and Wen Sun. *Reinforcement Learning: Theory and Algorithms*. https://rltheorybook.github.io/, 2022.

Brenna D Argall, Sonia Chernova, Manuela Veloso, and Brett Browning. A survey of robot learning from demonstration. *Robotics and Autonomous Systems*, 57(5):469–483, 2009.

Dimitri P. Bertsekas. *Nonlinear Programming*. Athena Scientific, 2016.

Kianté Brantley, Wen Sun, and Mikael Henaff. Disagreement-regularized imitation learning. In *ICLR*, 2020.

Jinglin Chen and Nan Jiang. Information-theoretic considerations in batch reinforcement learning. In *ICML*, pages 1042–1051, 2019.

Xiaoyu Chen, Jiachen Hu, Lin Yang, and Liwei Wang. Near-optimal reward-free exploration for linear mixture mdps with plug-in solver. In *ICLR*, 2022.

Robert Dadashi, Léonard Hussenot, Matthieu Geist, and Olivier Pietquin. Primal wasserstein imitation learning. In *ICLR*, 2021.

Yan Duan, Xi Chen, Rein Houthooft, John Schulman, and Pieter Abbeel. Benchmarking deep reinforcement learning for continuous control. In *ICML*, pages 1329–1338, 2016.

Justin Fu, Katie Luo, and Sergey Levine. Learning robust rewards with adverserial inverse reinforcement learning. In *ICLR*, 2018.

Divyansh Garg, Shuvam Chakraborty, Chris Cundy, Jiaming Song, and Stefano Ermon. Iq-learn: Inverse soft-q learning for imitation. In *NeurIPS*, pages 4028–4039, 2021.

Seyed Kamyar Seyed Ghasemipour, Richard S. Zemel, and Shixiang Gu. A divergence minimization perspective on imitation learning methods. In *CoRL*, pages 1259–1277, 2019.

Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. In *NeurIPS*, pages 4565–4573, 2016.

Eric Jang, Alex Irpan, Mohi Khansari, Daniel Kappler, Frederik Ebert, Corey Lynch, Sergey Levine, and Chelsea Finn. Bc-z: Zero-shot task generalization with robotic imitation learning. In *CoRL*, pages 991–1002, 2022.

Nan Jiang, Alex Kulesza, and Satinder Singh. Abstraction selection in model-based reinforcement learning. In *ICML*, pages 179–188, 2015.

Chi Jin, Zeyuan Allen-Zhu, Sébastien Bubeck, and Michael I. Jordan. Is q-learning provably efficient? In *NeurIPS*, pages 4868–4878, 2018.

Chi Jin, Akshay Krishnamurthy, Max Simchowitz, and Tiancheng Yu. Reward-free exploration for reinforcement learning. In *ICML*, pages 4870–4879, 2020.

Sudeep Kamath, Alon Orlitsky, Dheeraj Pichapati, and Ananda Theertha Suresh. On learning distributions from their samples. In *COLT*, pages 1066–1100, 2015.

Emilie Kaufmann, Pierre Ménard, Omar Darwiche Domingues, Anders Jonsson, Edouard Leurent, and Michal Valko. Adaptive reward-free exploration. In *ALT*, pages 865–891, 2021.

Liyiming Ke, Matt Barnes, Wen Sun, Gilwoo Lee, Sanjiban Choudhury, and Siddhartha S. Srinivasa. Imitation learning as f-divergence minimization. *arXiv*, 1905.12888, 2019.

Ilya Kostrikov, Kumar Krishna Agrawal, Debidatta Dwibedi, Sergey Levine, and Jonathan Tompson. Discriminator-actor-critic: Addressing sample inefficiency and reward bias in adversarial imitation learning. In *ICLR*, 2019.

Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. *Journal of Machine Learning Research*, 17(39): 1–40, 2016.

Lihong Li, Thomas J Walsh, and Michael L Littman. Towards a unified theory of state abstraction for mdps. *ISAIM*, 4:5, 2006.

Ziniu Li, Tian Xu, Yang Yu, and Zhi-Quan Luo. Rethinking valuedice: Does it really improve performance? *arXiv*, 2202.02468, 2022.

Zhihan Liu, Yufeng Zhang, Zuyue Fu, Zhuoran Yang, and Zhaoran Wang. Provably efficient generative adversarial imitation learning for online and offline setting with linear function approximation. *arXiv*, 2108.08765, 2021.

Pierre Ménard, Omar Darwiche Domingues, Anders Jonsson, Emilie Kaufmann, Edouard Leurent, and Michal Valko. Fast active learning for pure exploration in reinforcement learning. In *ICML*, pages 7599–7608, 2021.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Francesco Orabona. A modern introduction to online learning. *arXiv*, 1912.13213, 2019.

Takayuki Osa, Joni Pajarinen, Gerhard Neumann, J. Andrew Bagnell, Pieter Abbeel, and Jan Peters. An algorithmic perspective on imitation learning. *Foundations and Trends in Robotic*, 7(1-2):1–179, 2018.

Dean Pomerleau. Efficient training of artificial neural networks for autonomous navigation. *Neural Computation*, 3(1):88–97, 1991.

Martin L. Puterman. *Markov Decision Processes: Discrete Stochastic Dynamic Programming*. John Wiley & Sons, 2014.

Nived Rajaraman, Lin F. Yang, Jiantao Jiao, and Kannan Ramchandran. Toward the fundamental limits of imitation learning. In *NeurIPS*, pages 2914–2924, 2020.

Nived Rajaraman, Yanjun Han, Lin Yang, Jingbo Liu, Jiantao Jiao, and Kannan Ramchandran. On the value of interaction and function approximation in imitation learning. In *NeurIPS*, pages 1325–1336, 2021a.

Nived Rajaraman, Yanjun Han, Lin F. Yang, Kannan Ramchandran, and Jiantao Jiao. Provably breaking the quadratic error compounding barrier in imitation learning, optimally. *arXiv*, 2102.12948, 2021b.

Stéphane Ross and Drew Bagnell. Efficient reductions for imitation learning. In *AISTATS*, pages 661–668, 2010.

Shai Shalev-Shwartz. Online learning and online convex optimization. *Foundations and Trends in Machine Learning*, 4(2):107–194, 2012.

Lior Shani, Tom Zahavy, and Shie Mannor. Online apprenticeship learning. In *AAAI*, pages 8240–8248, 2022.

Jing-Cheng Shi, Yang Yu, Qing Da, Shi-Yong Chen, and Anxiang Zeng. Virtual-taobao: virtualizing real-world online retail environment for reinforcement learning. In *AAAI*, pages 4902–4909, 2019.

Richard S Sutton and Andrew G Barto. *Reinforcement Learning: An Introduction*. MIT press, 2018.

Gokul Swamy, Nived Rajaraman, Matthew Peng, Sanjiban Choudhury, J Andrew Bagnell, Zhiwei Steven Wu, Jiantao Jiao, and Kannan Ramchandran. Minimax optimal online imitation learning via replay estimation. *arXiv*, 2205.15397, 2022.

Umar Syed and Robert E. Schapire. A game-theoretic approach to apprenticeship learning. In *NeurIPS*, pages 1449–1456, 2007.

Umar Syed, Michael H. Bowling, and Robert E. Schapire. Apprenticeship learning using linear programming. In *ICML*, pages 1032–1039, 2008.

Faraz Torabi, Garrett Warnell, and Peter Stone. Behavioral cloning from observation. In *IJCAI*, pages 4950–4957, 2018.

Roman Vershynin. *High-Dimensional Probability: An Introduction with Applications in Data Science*. Cambridge University Press, 2018.

Ruosong Wang, Simon S. Du, Lin F. Yang, and Russ R. Salakhutdinov. On reward-free reinforcement learning with linear function approximation. In *NeurIPS*, pages 17816–17826, 2020a.

Yizhou Wang, Tianyi Liu, Zhuoran Yang, Xingguo Li, Zhaoran Wang, and Tuo Zhao. On computation and generalization of generative adversarial imitation learning. In *ICLR*, 2020b.

Tian Xu, Ziniu Li, and Yang Yu. Error bounds of imitating policies and environments. In *NeurIPS*, pages 15737–15749, 2020.

Tian Xu, Ziniu Li, and Yang Yu. Error bounds of imitating policies and environments for reinforcement learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

Tian Xu, Ziniu Li, Yang Yu, and Zhi-Quan Luo. Understanding adversarial imitation learning in small sample regime: A stage-coupled analysis. *arXiv*, 2208.01899, 2022.

Tom Zahavy, Alon Cohen, Haim Kaplan, and Yishay Mansour. Apprenticeship learning via frank-wolfe. In *AAAI*, pages 6720–6728, 2020.

Weitong Zhang, Dongruo Zhou, and Quanquan Gu. Reward-free model-based reinforcement learning with linear function approximation. *NeurIPS*, 2021.

Yufeng Zhang, Qi Cai, Zhuoran Yang, and Zhaoran Wang. Generative adversarial imitation learning with neural network parameterization: Global optimality and convergence rate. In *ICML*, pages 11044–11054, 2020.

Brian D Ziebart, Andrew L Maas, J Andrew Bagnell, and Anind K Dey. Maximum entropy inverse reinforcement learning. In *AAAI*, pages 1433–1438, 2008.