Neural Collapse with Normalized Features:
A Geometric Analysis over the Riemannian Manifold

Abstract

When training overparameterized deep networks for classification tasks, it has been widely observed that the learned features exhibit a so-called "neural collapse" phenomenon. More specifically, for the output features of the penultimate layer, for each class the within-class features converge to their means, and the means of different classes exhibit a certain tight frame structure, which is also aligned with the last layer's classifier. As feature normalization in the last layer becomes a common practice in modern representation learning, in this work we theoretically justify the neural collapse phenomenon for normalized features. Based on an unconstrained feature model, we simplify the empirical loss function in a multi-class classification task and obtain a nonconvex optimization problem over the Riemannian manifold by constraining all features and classifiers over the sphere. In this context, we analyze the nonconvex landscape of the Riemannian optimization problem over the product of spheres, showing a benign global landscape in the sense that the only global minimizers are the neural collapse solutions while all other critical points are strict saddles with negative curvature. Experimental results on practical deep networks corroborate our theory and demonstrate that better representations can be learned faster via feature normalization.

1 Introduction

Despite the tremendous success of deep learning in engineering and scientific applications over the past decades, the underlying mechanism of deep neural networks (DNNs) still largely remains mysterious. Towards the goal of understanding the learned deep representations, a recent seminal line of works [1–5] presents an intriguing phenomenon that persists across a range of canonical classification problems during the terminal phase of training. Specifically, it has been widely observed that last-layer features (i.e., the output of the penultimate layer) and last-layer linear classifiers of a trained DNN exhibit simple but elegant mathematical structures, in the sense that

- **(NC1) Variability Collapse:** the individual features of each class concentrate to their class-means.
- **(NC2) Convergence to Simplex ETF:** the class-means have the same length and are maximally distant. In other words, they form a Simplex Equiangular Tight Frame (ETF).
- **(NC3) Convergence to Self-Duality:** the last-layer linear classifiers perfectly match their class-means.

Such a phenomenon is referred to as *Neural Collapse* ($\mathcal{NC}$) [1], which has been shown empirically to persist across a broad range of canonical classification problems, on different loss functions (e.g., cross-entropy (CE) [1, 3, 4], mean-squared error (MSE) [5, 6], and supervised contrasive (SC) losses [7]), different neural network architectures (e.g., VGG [8], ResNet [9], and DenseNet [10]), and on a variety of standard datasets (such as MNIST [11], CIFAR [12], and ImageNet [13], etc).

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: **Comparison of features found with and without normalization.** $K = 100$ classes with $n = 5$ samples per class. Features and classifiers are found through optimizing the cross-entropy loss with a UFM, where features are embedded in 2-dimensional space, i.e., $d = 2$. (a) No normalization of features or classifiers. (b) Features and classifiers are constrained to the unit sphere (features are scaled down for visualization purposes).

Table 1: Average UFM feature loss and accuracy over 10 trials with and without normalization to sphere, with the same set-up as in Figure 1.

	Average CE Loss	**Average Accuracy**
No Normalization	1.63 ± 0.03	$49.9\% \pm 2.39\%$
Normalization	3.84 ± 0.00	$100.0\% \pm 0.00\%$

Recently, in independent lines of research, many works are devoted to learning maximally compact and separated features; see, e.g., [14–22]. This has also been widely demonstrated in a number of recent works [23–29], including state-of-the-art natural language models (such as BERT, RoBERTa, and GPT) [24].

Motivations & contributions. In this work, we further demystify why $\mathcal{NC}$ happens in network training with a common practice of feature normalization (i.e., normalizing the last-layer features on the unit hypersphere), mainly motivated by the following reasons:

- *Feature normalization is a common practice in training model deep networks.* Recently, many existing results demonstrated that training with feature normalization often improves the quality of learned representation with better class separation [7, 16, 18–20, 30–32]. Such a representation is closely related to the discriminative representation in literature; see, e.g., [16, 18, 19, 33]. As illustrated in Fig. 1 and Table 1, experimental results visualized in low-dimensional space show that features learned with normalization are more uniformly distributed over the sphere and hence are more linearly separable than those learned without normalization. In particular, it has been shown that the learned representations with larger class separation usually lead to improved test performances; see, e.g., [7, 34]. Moreover, it has been demonstrated that discriminative representations can also improve robustness to mislabeled data [30, 31], and has become a common practice in recent advances on (self-supervised) pretrained models [32, 35].

- *A common practice of theoretically studying $\mathcal{NC}$ with norm constraints.* Due to these practical reasons, many existing theoretical studies on $\mathcal{NC}$ consider formulations with both the norms of features and classifiers constrained [3, 7, 36–38]. Based upon assumptions of simplified unconstrained feature models [3, 4, 39], these works show that the only global solutions are $\mathcal{NC}$ for a variety of loss functions (e.g., MSE, CE, SC losses, etc). Nonetheless, they only focused on the global optimality conditions without looking into their nonconvex landscapes, and therefore fail to explain why global $\mathcal{NC}$ solutions can be efficiently reached by classical training algorithms such as stochastic gradient descent (SGD).

In this work we study the global nonconvex landscape of training deep networks with norm constraints on the features and classifiers. We consider the commonly used CE loss and formulate the problem as a Riemannian optimization problem over products of unit spheres (i.e., the oblique manifold). Our

study is also based upon the assumption of the so-called *unconstrained feature model* (UFM) [4,5,39] or *layer-peeled model* [40], where the last-layer features of the deep network are treated as free optimization variables to simplify the nonlinear interactions across layers. The underlying reasoning is that modern deep networks are often highly overparameterized with the capacity of learning any representations [41–43], so that the last-layer features can approximate, or interpolate, any point in the feature space.

Assuming the UFM, we show that the Riemannian optimization problem has a benign global landscape, in the sense that the loss with respect to (w.r.t.) the features and classifers is a strict saddle function [44,45] over the Riemannian manifold. More specifically, we prove that *every* local minimizer is a global solution satisfying the $\mathcal{NC}$ properties, and *all* the other critical points exhibit directions with negative curvature. Our analysis for the manifold setting is based upon a nontrivial extension of recent studies for the $\mathcal{NC}$ with penalized formulations [2,4–6], which could be of independent interest. Our work brings new tools from Riemannian optimization for analyzing optimization landscapes of training deep networks with an increasingly common practice of feature normalization. At the same time, we empirically demonstrate the advantages of the Riemannian/constrained formulation over its penalized counterpart for training deep networks – faster training and higher quality representations. Lastly, under the UFM we believe the benign landscape over the manifold could hold for many other popular training losses beyond CE, such as the (supervised) contrastive loss [34]. We leave this for future exploration.

Prior arts and related works on $\mathcal{NC}$. The empirical $\mathcal{NC}$ phenomenon has inspired a recent line of theoretical studies on understanding why it occurs [4–7,36,39,40]. Like ours, most of these works studied the problem under the UFM. In particular, despite of the nonconvexity, recent works showed that the *only* global solutions are $\mathcal{NC}$ solutions for a variety of nonconvex training losses (e.g., CE [4,36,40], MSE [5,6], SC losses [7]) and different problem formulations (e.g., penalized, constrained, and unconstrained) [2,4–6,36]. Recently, this study has been extended to deeper models with the MSE training loss [6]. More surprisingly, it has been further shown that the nonconvex losses under the UFM have benign global optimization landscapes, in the sense that every local minimizer satisfies $\mathcal{NC}$ properties and the remaining critical points are strict saddles with negative curvature. Such results have been established for both CE and MSE losses [4,5], where they considered the unconstrained formulations with regularization on both features and classifiers.

Moreover, there is a line of recent works investigating the benefits of $\mathcal{NC}$ on generalizations of deep networks. The work [46] shows that $\mathcal{NC}$ also happens on test data drawn from the same distribution asymptotically, but less collapse for finite samples [47]. Other works [47,48] demonstrated that the variability collapse of features is actually happening progressively from shallow to deep layers, and [49] showed that test performance can be improved when enforcing variability collapse on features of intermediate layers. The works [50,51] showed that fixing the classifier as a simplex ETF improves test performance on imbalanced training data and long-tailed classification problems. For more details on related works, we refer interested readers to the Appendix A.

Notation. Let $\mathbb{R}^n$ be the n-dimensional Euclidean space and $\|\cdot\|_2$ be the Euclidean norm. We write matrices in bold capital letters such as $\boldsymbol{A}$, vectors in bold lower-case such as $\boldsymbol{a}$, and scalars in plain letters such as a. Given a matrix $\boldsymbol{A} \in \mathbb{R}^{d \times K}$, we denote its k-th column by $\boldsymbol{a}_k$, its i-th row by $\boldsymbol{a}^i$, its (i,j)-th element by a_{ij}, and let $\|\boldsymbol{A}\|$ be its spectral norm. We use $\mathrm{diag}(\boldsymbol{A})$ to denote a vector that consists of diagonal elements of $\boldsymbol{A}$, and we use $\mathrm{ddiag}(\boldsymbol{A})$ to denote a diagonal matrix composed by only the diagonal entries of $\boldsymbol{A}$. Given a positive integer n, we denote the set $\{1, \ldots, n\}$ by $[n]$. We denote the unit hypersphere in $\mathbb{R}^d$ by $\mathbb{S}^{d-1} := \{\boldsymbol{x} \in \mathbb{R}^d : \|\boldsymbol{x}\|_2 = 1\}$.

2 Nonconvex Formulation with Spherical Constraints

In this section, we review the basic concepts of deep neural networks and introduce notation that will be used throughout the paper. Based upon this, we formally introduce the problem formulation over the Riemannian manifold under the assumption of the UFM.

2.1 Basics of Deep Neural Networks

In this work, we focus on the multi-class (e.g., K class) classification problem. Given input data $\boldsymbol{x} \in \mathbb{R}^D$, the goal of deep learning is to learn a deep hierarchical representation (or feature) $\boldsymbol{h}(\boldsymbol{x}) =$

$\phi_{\boldsymbol{\theta}}(\boldsymbol{x}) \in \mathbb{R}^d$ of the input along with a linear classifier[1] $\boldsymbol{W} \in \mathbb{R}^{d \times K}$ such that the output $\psi_{\Theta}(\boldsymbol{x}) = \boldsymbol{W}^\top \boldsymbol{h}(\boldsymbol{x})$ of the network fits the input $\boldsymbol{x}$ to an one-hot training label $\boldsymbol{y} \in \mathbb{R}^K$. More precisely, in the vanilla form an L-layer fully connected deep neural network can be written as

$$\psi_{\Theta}(\boldsymbol{x}) = \underbrace{\boldsymbol{W}_L}_{\text{linear classifier } \boldsymbol{W} = \boldsymbol{W}_L^\top} \underbrace{\sigma\left(\boldsymbol{W}_{L-1} \cdots \sigma\left(\boldsymbol{W}_1 \boldsymbol{x} + \boldsymbol{b}_1\right) + \boldsymbol{b}_{L-1}\right)}_{\text{feature } \boldsymbol{h} = \phi_{\boldsymbol{\theta}}(\boldsymbol{x})} + \boldsymbol{b}_L, \qquad (1)$$

where each layer is composed of an affine transformation, represented by some weight matrix $\boldsymbol{W}_k$, and bias $\boldsymbol{b}_k$, followed by a nonlinear activation $\sigma(\cdot)$, and $\Theta = \{\boldsymbol{W}_k, \boldsymbol{b}_k\}_{k=1}^L$ and $\boldsymbol{\theta} = \{\boldsymbol{W}_k, \boldsymbol{b}_k\}_{k=1}^{L-1}$ denote the weights for *all* the network parameters and those up to the last layer, respectively. Given training samples $\{\boldsymbol{x}_{k,i}, \boldsymbol{y}_k\} \in \mathbb{R}^D \times \mathbb{R}^K$ drawn from the same data distribution $\mathcal{D}$, we learn the network parameters Θ via minimizing the empirical risk over these samples,

$$\min_{\Theta} \sum_{k=1}^K \sum_{i=1}^{n_k} \mathcal{L}_{\text{CE}}\left(\psi_{\Theta}(\boldsymbol{x}_{k,i}), \boldsymbol{y}_k\right), \quad \text{s.t.} \quad \Theta \in \mathcal{C}, \qquad (2)$$

where $\boldsymbol{y}_k \in \mathbb{R}^K$ is a one-hot vector with only the kth entry equal to unity and the remaining ones equal to zero for all $k \in [K]$, $\boldsymbol{x}_{k,i} \in \mathbb{R}^D$ is the i-th sample in the k-th class, $\{n_k\}_{k=1}^K$ denotes the number of training samples in each class, and the set $\mathcal{C}$ denotes the constraint set of the network parameters Θ that we will specify later. Here, we study the most widely used CE loss of the form

$$\mathcal{L}_{\text{CE}}(\boldsymbol{z}, \boldsymbol{y}_k) := -\log\left(\frac{\exp(z_k)}{\sum_{\ell=1}^K \exp(z_\ell)}\right).$$

2.2 Riemannian Optimization over the Product of Spheres

For the K-class classification problem, let us consider a simple case where the number of training samples in each class is balanced (i.e., $n = n_1 = n_2 = \cdots = n_K$) and let $N = Kn$, and we assume that all the biases $\{\boldsymbol{b}_k\}_{k=1}^L$ are zero with the last activation function $\sigma(\cdot)$ before the output to be linear. Analyzing deep networks $\psi_{\Theta}(\boldsymbol{x})$ is a tremendously difficult task mainly due to the *nonlinear interactions* across a large number of layers. To simplify the analysis, we assume the so-called *unconstrained feature models* (UFM) following the previous works [4, 7, 38, 39]. More specifically, we simplify the nonlinear interactions across layers by treating the last-layer features $\boldsymbol{h}_{k,i} = \phi_{\boldsymbol{\theta}}(\boldsymbol{x}_{k,i}) \in \mathbb{R}^d$ as *free* optimization variables, where the underlying reasoning is that modern deep networks are often highly overparameterized to approximate any continuous function [41–43]. Concisely, we rewrite all the features in a matrix form as

$$\boldsymbol{H} = [\boldsymbol{H}_1 \quad \boldsymbol{H}_2 \quad \cdots \quad \boldsymbol{H}_K] \in \mathbb{R}^{d \times N}, \boldsymbol{H}_k = [\boldsymbol{h}_{k,1} \quad \boldsymbol{h}_{k,2} \quad \cdots \quad \boldsymbol{h}_{k,n}] \in \mathbb{R}^{d \times n}, \forall k \in [K],$$

and correspondingly denote the classifier $\boldsymbol{W}$ by

$$\boldsymbol{W} = [\boldsymbol{w}_1 \quad \boldsymbol{w}_2 \quad \cdots \quad \boldsymbol{w}_K] \in \mathbb{R}^{d \times K}, \quad \boldsymbol{w}_k \in \mathbb{R}^d, \quad \forall k \in [K].$$

Based upon the discussion in Section 1, we assume that both the features $\boldsymbol{H}$ and the classifiers $\boldsymbol{W}$ are normalized,[2] in the sense that $\|\boldsymbol{h}_{k,i}\|_2 = \tau, \|\boldsymbol{w}_k\|_2 = 1$, for all $k \in [K]$ and all $i \in [n]$, where $\tau > 0$ is a temperature parameter. As a result, we study $\mathcal{NC}$ with a *constrained* formulation over a Riemannian manifold

$$\min_{\boldsymbol{W}, \boldsymbol{H}} \frac{1}{N} \sum_{k=1}^K \sum_{i=1}^n \mathcal{L}_{\text{CE}}\left(\boldsymbol{W}^\top \boldsymbol{h}_{k,i}, \boldsymbol{y}_k\right) \text{ s.t. } \|\boldsymbol{w}_k\|_2 = \tau, \|\boldsymbol{h}_{k,i}\|_2 = 1, \forall i \in [n], \forall k \in [K].$$

Since the temperature parameter τ can be absorbed into the loss function, we replace $\boldsymbol{h}_{k,i}$ by $\tau \boldsymbol{h}_{k,i}$ by a change of variable, so that the original constraint becomes $\|\boldsymbol{h}_{k,i}\|_2 = 1$ for all $k \in [K]$ and all $i \in [n]$. Moreover, the product of spherical constraints forms an *oblique manifold* [52] embedded in Euclidean space,

$$\mathcal{OB}(d, K) := \left\{\boldsymbol{Z} \in \mathbb{R}^{d \times K} \mid \boldsymbol{z}_k \in \mathbb{S}^{d-1}, \forall k \in [K]\right\}.$$

---

[1]We write $\boldsymbol{W} = \boldsymbol{W}_L^\top$ in the transposed form for the simplicity of analysis.

[2]In practice, it is a common practice to normalize the output feature $\boldsymbol{h}_o$ by its norm, i.e., $\boldsymbol{h} = \boldsymbol{h}_o / \|\boldsymbol{h}_o\|_2$, so that $\|\boldsymbol{h}\|_2 = 1$.

149 Consequently, we can rewrite the constrained problem as a Riemannian optimization problem over
150 the oblique manifold w.r.t. $\boldsymbol{W}$ and $\boldsymbol{H}$ as

$$\min_{\boldsymbol{W},\boldsymbol{H}} f(\boldsymbol{W}, \boldsymbol{H}) := \frac{1}{N} \sum_{k=1}^{K} \sum_{i=1}^{n} \mathcal{L}_{\mathrm{CE}}\left(\tau \boldsymbol{W}^{\top} \boldsymbol{h}_{k,i}, \boldsymbol{y}_k\right), \tag{3}$$
$$\text{s.t.} \quad \boldsymbol{H} \in \mathcal{OB}(d, N), \ \boldsymbol{W} \in \mathcal{OB}(d, K).$$

151 In Section 3, we will show that all global solutions satisfy $\mathcal{NC}$ properties, and the function (3) is a
152 strict saddle function [53, 54] of $(\boldsymbol{W}, \boldsymbol{H})$ over the oblique manifold so that the $\mathcal{NC}$ solution can be
153 efficiently achieved.

154 **Riemannian derivatives over the oblique manifold.** In
155 Section 3, we will use tools from Riemannian optimization to
156 characterize the global optimality condition and the geomet-
157 ric properties of the optimization landscape of Problem (3).
158 Before that, let us first briefly introduce some basic deriva-
159 tions of the Riemannian gradient and Hessian, defined on the
160 tangent space of the oblique manifold. For more technical
161 details, we refer the readers to Appendix B.1. According
162 to [55, Chapter 3 & 5] and [56, 57], we can calculate the
163 Riemannian gradients and Hessian of Problem (3) as follows.
164 Since those quantities are defined on the tangent space, ac-
165 cording to [56, Section 3.1] and the illustration in Figure 2,
166 we first have the tangent space to $\mathcal{OB}(d, K)$ at $\boldsymbol{W}$ as

Figure 2: **An illustration of the Riemannian gradient of $f(\boldsymbol{h})$ on a simple manifold $\mathcal{OB}(3, 1) = \mathbb{S}^2$.**

$$\mathrm{T}_{\boldsymbol{W}}\mathcal{OB}(d, K) = \left\{ \boldsymbol{Z} \in \mathbb{R}^{d \times K} \mid \mathrm{diag}\left(\boldsymbol{W}^{\top}\boldsymbol{Z}\right) = \mathbf{0} \right\}.$$

167 That is, the tangent space contains all $\boldsymbol{Z}$ such that $\boldsymbol{z}_k$ is orthogonal to $\boldsymbol{w}_k$ for all k; when $K = 1$, it
168 reduces to the tangent space to the unit sphere $\mathbb{S}^{d-1}$.

169 Analogously, we can derive the tangent space for $\boldsymbol{H}$ with a similar form. Let us define

$$\boldsymbol{M} := \tau \boldsymbol{W}^{\top} \boldsymbol{H}, \ g(\boldsymbol{M}) := f(\boldsymbol{W}, \boldsymbol{H}).$$

170 First, the Riemannian gradient of $f(\boldsymbol{W}, \boldsymbol{H})$ of Problem (3) is basically the projection of
171 the ordinary Euclidean gradient $\nabla f(\boldsymbol{W}, \boldsymbol{H})$ onto its tangent space, i.e., $\mathrm{grad}_{\boldsymbol{W}} f(\boldsymbol{W}, \boldsymbol{H}) =$
172 $\mathcal{P}_{\mathrm{T}_{\boldsymbol{W}}\mathcal{OB}(d,K)}(\nabla_{\boldsymbol{W}} f(\boldsymbol{W}, \boldsymbol{H}))$ and $\mathrm{grad}_{\boldsymbol{H}} f(\boldsymbol{W}, \boldsymbol{H}) = \mathcal{P}_{\mathrm{T}_{\boldsymbol{H}}\mathcal{OB}(d,N)}(\nabla_{\boldsymbol{H}} f(\boldsymbol{W}, \boldsymbol{H}))$. More specif-
173 ically, we have

$$\mathrm{grad}_{\boldsymbol{W}} f(\boldsymbol{W}, \boldsymbol{H}) = \tau \boldsymbol{H} \nabla g(\boldsymbol{M})^{\top} - \tau \boldsymbol{W} \, \mathrm{ddiag}\left(\boldsymbol{W}^{\top} \boldsymbol{H} \nabla g(\boldsymbol{W})^{\top}\right), \tag{4}$$

$$\mathrm{grad}_{\boldsymbol{H}} f(\boldsymbol{W}, \boldsymbol{H}) = \tau \boldsymbol{W} \nabla g(\boldsymbol{M}) - \tau \boldsymbol{H} \, \mathrm{ddiag}\left(\boldsymbol{H}^{\top} \boldsymbol{W} \nabla g(\boldsymbol{M})\right). \tag{5}$$

174 Second, for any $\boldsymbol{\Delta} = (\boldsymbol{\Delta}_{\boldsymbol{W}}, \boldsymbol{\Delta}_{\boldsymbol{H}}) \in \mathbb{R}^{d \times K} \times \mathbb{R}^{d \times N}$, we compute the Hessian bilinear form of
175 $f(\boldsymbol{W}, \boldsymbol{H})$ along the direction $\boldsymbol{\Delta}$ by

$$\begin{aligned}\nabla^2 f(\boldsymbol{W}, \boldsymbol{H})[\boldsymbol{\Delta}, \boldsymbol{\Delta}] &= \nabla^2 g(\boldsymbol{M})\left[\tau\left(\boldsymbol{W}^{\top}\boldsymbol{\Delta}_{\boldsymbol{H}} + \boldsymbol{\Delta}_{\boldsymbol{W}}^{\top}\boldsymbol{H}\right), \tau\left(\boldsymbol{W}^{\top}\boldsymbol{\Delta}_{\boldsymbol{H}} + \boldsymbol{\Delta}_{\boldsymbol{W}}^{\top}\boldsymbol{H}\right)\right] \\ &\quad + 2\tau\left\langle \nabla g(\boldsymbol{M}), \boldsymbol{\Delta}_{\boldsymbol{W}}^{\top}\boldsymbol{\Delta}_{\boldsymbol{H}}\right\rangle.\end{aligned} \tag{6}$$

176 We can derive the Riemannian Hessian bilinear form of $f(\boldsymbol{W}, \boldsymbol{H})$ along any direction $\boldsymbol{\Delta} \in$
177 $\mathrm{T}_{\boldsymbol{W}}\mathcal{OB}(d, K) \times \mathrm{T}_{\boldsymbol{H}}\mathcal{OB}(d, N)$ as

$$\begin{aligned}\mathrm{Hess}\, f(\boldsymbol{W}, \boldsymbol{H})[\boldsymbol{\Delta}, \boldsymbol{\Delta}] &= \nabla^2 f(\boldsymbol{W}, \boldsymbol{H})[\boldsymbol{\Delta}, \boldsymbol{\Delta}] - \left\langle \boldsymbol{\Delta}_{\boldsymbol{W}} \, \mathrm{ddiag}\left(\boldsymbol{M} \nabla g(\boldsymbol{M})^{\top}\right), \boldsymbol{\Delta}_{\boldsymbol{W}}\right\rangle \\ &\quad - \left\langle \boldsymbol{\Delta}_{\boldsymbol{H}} \, \mathrm{ddiag}\left(\boldsymbol{M}^{\top} \nabla g(\boldsymbol{M})\right), \boldsymbol{\Delta}_{\boldsymbol{H}}\right\rangle,\end{aligned} \tag{7}$$

178 where the extra terms besides $\nabla^2 f(\boldsymbol{W}, \boldsymbol{H})[\boldsymbol{\Delta}, \boldsymbol{\Delta}]$ compensate for the curvatures on the oblique
179 manifold. For derivations of (6) and (7), see Appendix B.2. In the following section, we will use the
180 Riemannian gradient and Hessian to characterize the optimization landscape of Problem (3).

3 Main Theoretical Analysis

182 In this section, we first characterize the structure of the global solution set of Problem (3). Based upon
183 this, we analyze the global landscape of Problem (3) via characterizing its Riemannian derivatives.

Figure 3: **Global optimization of** (3) **under UFM with** $d = 100$ **and** $n = 5$**.** Theoretical line refers to lower bound (global minimum) from Theorem 1. Empirical values found using gradient descent with random initialization. Left: Lower bound against number of classes K while fixing $\tau = 1$. Right: Lower bound against temperature τ while fixing $K = 10$. The same empirical values are achieved over many trials due to the benign global landscape.

3.1 Global Optimality Condition

For the feature matrix $\boldsymbol{H}$, let us denote the class mean for each class as

$$\overline{\boldsymbol{H}} := \begin{bmatrix} \overline{\boldsymbol{h}}_1 & \cdots & \overline{\boldsymbol{h}}_K \end{bmatrix} \in \mathbb{R}^{d \times K}, \quad \text{and} \quad \overline{\boldsymbol{h}}_k := \frac{1}{n} \sum_{i=1}^{n} \boldsymbol{h}_{k,i}, \quad 1 \leq k \leq K. \tag{8}$$

Based upon this, we show any global solution of Problem (3) exhibits $\mathcal{NC}$ properties in the sense that it satisfies (**NC1**) variability collapse, (**NC2**) convergence to simplex ETF, and (**NC3**) convergence to self-duality.

Theorem 1 (Global Optimality Condition)**.** *Suppose that the feature dimension is no smaller than the number of classes (i.e., $d \geq K$) and the training labels are balanced in each class (i.e., $n = n_1 = \cdots = n_K$). Then for the CE loss $f(\boldsymbol{W}, \boldsymbol{H})$ in Problem (3), it holds that*

$$f(\boldsymbol{W}, \boldsymbol{H}) \geq \log\left(1 + (K-1)\exp\left(-\frac{K\tau}{K-1}\right)\right)$$

for all $\boldsymbol{W} = [\boldsymbol{w}_1, \ldots, \boldsymbol{w}_K] \in \mathcal{OB}(d, K)$ and $\boldsymbol{H} = [\boldsymbol{h}_{1,1}, \ldots, \boldsymbol{h}_{K,n}] \in \mathcal{OB}(d, N)$. In particular, equality holds if and only if there are $\overline{\boldsymbol{h}}_1, \overline{\boldsymbol{h}}_2, \cdots, \overline{\boldsymbol{h}}_K \in \mathbb{S}^{d-1}$ such that

- *(**NC1**) Variability collapse: $\boldsymbol{h}_{k,i} = \overline{\boldsymbol{h}}_k, \ \forall \, i \in [n]$;*

- *(**NC2**) Simplex ETF structure: $\{\overline{\boldsymbol{h}}_k\}_{k=1}^{K}$ form a sphere-inscribed simplex ETF in the sense that*

$$\overline{\boldsymbol{H}}^\top \overline{\boldsymbol{H}} = \frac{1}{K-1}\left(K\boldsymbol{I}_K - \boldsymbol{1}_K\boldsymbol{1}_K^\top\right), \quad \overline{\boldsymbol{H}} \in \mathcal{OB}(d, K).$$

- *(**NC3**) Self-duality: $\boldsymbol{w}_k = \overline{\boldsymbol{h}}_k, \ \forall \, k \in [K]$.*

Compared to the unconstrained regularized problems in [4,5], it is worth noting that the regularization parameters there influence the structure of global solutions, while the temperature parameter τ only affects the optimization landscape but not the global solutions. On the other hand, the result of our problem (3) is closely related to [7, Theorem 1] (i.e., spherical constraints vs. that of ball constraints). In fact, our problem and that in [7] share the same global solution set. As such, the proof follows similar ideas of a line of recent works [4–7, 36, 40], and we refer the readers to Appendix C for the proof. It should be noted that we do not claim originality of this result compared to previous works; instead our major contribution lies in the following global landscape analysis.

3.2 Global Landscape Analysis

Due to the nonconvex nature of Problem (3), the characterization of global optimality alone in Theorem 1 is not sufficient for guaranteeing efficient optimization to those desired global solutions. Thus, we further study the global landscape of Problem (3) by characterizing all the *Riemannian critical points* $(\boldsymbol{W}, \boldsymbol{H}) \in \mathcal{OB}(d, K) \times \mathcal{OB}(d, N)$ with

$$\operatorname{grad}_{\boldsymbol{H}} f(\boldsymbol{W}, \boldsymbol{H}) = \boldsymbol{0}, \quad \operatorname{grad}_{\boldsymbol{W}} f(\boldsymbol{W}, \boldsymbol{H}) = \boldsymbol{0}.$$

As such, we state our major result below.

Theorem 2 (Global Landscape Analysis). *Assume that the number of training samples in each class is balanced $n = n_1 = \cdots = n_K$. If the feature dimension is larger than the number of classes $d > K$ and the temperature parameter satisfies $\tau < 2(d-2)(1 + (K \bmod 2)/K)^{-1}$, then the function $f(\boldsymbol{W}, \boldsymbol{H})$ is a strict saddle function that has no spurious local minimum, in the sense that*

- *Any local minimizer of Problem (3) is a global minimizer of the form shown in Theorem 1.*

- *Any Riemannian critical point $(\boldsymbol{W}, \boldsymbol{H})$ of Problem (3) that is not a local minimizer is a Riemannian strict saddle point with negative curvatures, in the sense that the Riemannian Hessian $\operatorname{Hess} f(\boldsymbol{W}, \boldsymbol{H})$ at the critical point $(\boldsymbol{W}, \boldsymbol{H})$ is non-degenerate, and there exists a direction $\boldsymbol{\Delta} = (\boldsymbol{\Delta_W}, \boldsymbol{\Delta_H}) \in \mathrm{T}_{\boldsymbol{W}} \mathcal{OB}(d, K) \times \mathrm{T}_{\boldsymbol{H}} \mathcal{OB}(d, N)$ such that*

$$\operatorname{Hess} f(\boldsymbol{W}, \boldsymbol{H})[\boldsymbol{\Delta}, \boldsymbol{\Delta}] < 0.$$

In other words, $\lambda_{\min}(\operatorname{Hess} f(\boldsymbol{W}, \boldsymbol{H})) < 0$ at the corresponding Riemannian critical point.

For the details of the proof, we refer readers to Appendix D. The first bullet point naturally follows from Theorem 1. The major challenge of our analysis is showing the second bullet, i.e., to find a negative curvature direction $\boldsymbol{\Delta}$ for $\operatorname{Hess} f(\boldsymbol{W}, \boldsymbol{H})$. Our key observation is that the set of non-global critical points can be partitioned into two separate cases. In the first case, the last two terms of (7) vanish, and we show that the second term of (6) is negative and dominates the first term for an appropriate direction. We require τ to not be too large, since the first term is $O(\tau^2)$, whereas the second term is $O(\tau)$. In the second case, using the assumption that $d > K$ we can find a rank-one direction that makes the first term of (6) vanishing. In this case, we similarly show that the second term of (6) is negative but instead dominates the last two terms of (7). In the following, we discuss the implications, relationship, and limitations of our results in Theorem 2.

- *Efficient global optimization to $\mathcal{NC}$ solutions.* Our theorem implies that, for optimizing $(\boldsymbol{W}, \boldsymbol{H})$ via Problem (3), the $\mathcal{NC}$ solutions can be efficiently reached by Riemannian first-order methods (e.g., Riemannian stochastic gradient descent) with random initialization [53, 58, 59]; see Figure 3 for a demonstration. For training practical deep networks, this can be efficiently implemented by normalizing last-layer features when running SGD.

- *Relation to existing works on $\mathcal{NC}$.* Most existing results have only studied the global minimizers under the UFM [6, 7, 36, 40], which has limited implication for optimization. On the other hand, our landscape analysis is based upon a nontrivial extension of that with the unconstrained problem formulation [4, 5]. Compared to those works, Problem (3) is much more challenging for analysis, due to the fact that the set of critical points of our problem is essentially much larger than that of [4, 5]. Moreover, we empirically demonstrate the advantages of the manifold formulation over its regularized counterpart, in terms of representation quality and training speed.

- *Assumptions on the feature dimension d and temperature parameter τ.* Our current result requires that $d > K$, which is the same requirement in [4, 5]. Furthermore, through numerical simulations we conjecture that the global landscape also holds even when $d \ll K$, while the global solutions are uniform over the sphere [36] rather than being simplex ETFs (see Figure 1). The analysis on $d \ll K$ is left for future work. On the other hand, the required upper bound on τ is for the ease of analysis and it holds generally in practice,[3] but we conjecture that the benign landscape holds without it.

---

[3]For instance, a standard ResNet-18 [9] model trained on CIFAR-10 [12] has $d = 512$ and $K = 10$. In the same setting, we assume $\tau < 1020$, which is far larger than any useful setting of the temperature parameter (see Appendix E.3).

Figure 4: **Validation of UFM on ResNet with varying network width.** $\mathcal{NC}$ metrics and training accuracy of ResNet-18 networks of various widths on CIFAR10 with $n = 200$ over 200 epochs.

- *Relation to other Riemannian nonconvex problems.* Our result joins a recent line of work on the study of global nonconvex landscapes over Riemannian manifolds, such as orthogonal tensor decomposition [44], dictionary learning [60–64], and sparse blind deconvolution [65–68]. For all these problems constrained over a Riemannian manifold, it can be shown that they exhibit "equivalently good" global minimizers due to symmetries and intrinsic low-dimensional structures, and the loss functions are usually strict saddles [44, 45, 69]. As we can see, the global minimizers (i.e., simplex ETFs) of our problem here also exhibit a similar rotational symmetry, in the sense that $\boldsymbol{W}^\top \boldsymbol{H} = (\boldsymbol{Q}\boldsymbol{W})^\top (\boldsymbol{Q}\boldsymbol{H})$ for any orthogonal matrix $\boldsymbol{Q}$. Additionally, our result show how tools from Riemmanian optimization can be powerful for the study of deep learning.

4 Experiments

In this section, we support our theoretical results in previous sections and provide further motivation with experimental results on practical deep network training. In the first experiment, we validate the assumption of UFM introduced in Section 2 for analyzing $\mathcal{NC}$, by demonstrating that $\mathcal{NC}$ occurs for increasingly overparameterized deep networks. In the second experiment, we further motivate feature normalization with empirical results showing that feature normalization can lead to faster training and better collapse than the unconstrained counterpart with regularization. This occurs not only with the UFM but also with practical overparameterized networks. We detail the network architectures, datasets, training details, and metrics used in these experiments, as well as additional experiments in Appendix E.

4.1 Validation of the UFM for training networks with feature normalization

In Section 2, our study of the Riemannian optimization problem (3) is based upon the UFM, where we assume $\boldsymbol{H}$ is a free optimization variable. Here, we justify this assumption by showing that $\mathcal{NC}$ happens for training overparameterized networks even when the training labels are completely random. By using random labels, we disassociate the input from their class labels, by which we can characterize the approximation power of the features of overparmeterized models. To show this, we train ResNet-18 with varying widths (i.e., the number of feature maps resulting from the first convolutional layer) on CIFAR10 with random labels, with normalized features and classifiers.

As shown in Figure 4, we observe that increasing the width of the network allows for perfect classification on the training data even when the labels are random. Furthermore, increasing the network width also leads to better $\mathcal{NC}$, measured by the decrease in each $\mathcal{NC}$ metric. This corroborates that (*i*) our assumption of UFM is reasonable given that $\mathcal{NC}$ seems to be independent of the input data, and (*ii*) $\mathcal{NC}$ happens under the our constraint formulation (3) on practical networks.

4.2 Improved training speed and better representation quality with feature normalization

We now investigate the benefits of using feature normalization, more specifically for improved training speed and better representation quality. First, we consider the UFM formulation, where we optimize Problem (3) and compare to the regularized UFM in [4]. The results are shown in Figure 5. We can see that normalizing features over the sphere consistently results in reaching perfect classification and greater feature collapse (i.e., smaller $\mathcal{NC}_1$) quicker than penalizing the features. To demonstrate that these behaviors are reflected in training practical deep networks, we train both ResNet-18 and ResNet-50 architectures on a reduced CIFAR100 [12] dataset with $N = 3000$ total

Figure 5: **Faster training/feature collapse of UFM with feature normalization.** Average (deviation denoted by shaded area) training accuracy and $\mathcal{NC}_1$ of UFM over 10 trials of (Riemmanian) gradient descent with exact line search. We set $K = 100$ classes, $n = 30$ samples per class.

Figure 6: **Faster training/feature collapse with ResNet on CIFAR100 with feature normalization.** Training accuracy and $\mathcal{NC}_1$ of ResNet-18 and ResNet-50 on CIFAR100 with $n = 30$ over 100 epochs.

samples, comparing the training accuracy and metrics of $\mathcal{NC}$ with and without feature normalization. The results are shown in Figure 6.

From Figure 6 (left), we can see that for the ResNet-18 network, we reach perfect classification of the training data about 10-20 epochs sooner by using feature normalization compared to that of the unconstrained formulation. From Figure 6 (right), training the ResNet-50 network without feature normalization for 100 epochs shows slow convergence with poor training accuracy, whereas using feature normalization arrives at above 90% training accuracy in the same number of epochs. By keeping the size of the dataset the same and increasing the number of parameters, it is reasonable that optimizing the ResNet-50 network is more challenging due to the higher degree of overparameterization, yet this effect is mitigated by using feature normalization.

At the same time, for both architectures, using feature normalization leads to greater feature collapse (i.e., smaller $\mathcal{NC}_1$) compared to that of the unconstrained counterpart. As shown in recent work [1, 5, 46] , better $\mathcal{NC}$ often leads to better generalization performance. Experimental results demonstrating that feature normalization generalizes better than regularization are provided in Appendix E.2. Last but not least, we conjecture that the benign landscape holds beyond the CE loss (e.g., SC [7], see Appendix E.4); and we believe the benefits of feature normalization are not limited to the evidence that we showed here, as it could also lead to better robustness [30, 31] that is worth further exploration.

5 Conclusion & Discussion

In this work, we study the prevalence of the $\mathcal{NC}$ phenomenon with normalized features. Based upon the assumption of UFM, we formulate the problem as a Riemannian optimization problem over the product of spheres. We showed that the loss function is a strict saddle function over the manifold with respect to the last-layer features and classifiers, with no other spurious local minimizers. We demonstrate this on practical deep network training, and show practical benefits of feature normalization in terms of training speed and learned representation quality. As future work, we would like to expand the study to other popular loss functions such as contrastive loss and study the settings $d \ll K$, which could be of great importance for studying self-supervised learning.

References

[1] Vardan Papyan, XY Han, and David L Donoho. Prevalence of neural collapse during the terminal phase of deep learning training. *Proceedings of the National Academy of Sciences*, 117(40):24652–24663, 2020.

[2] XY Han, Vardan Papyan, and David L Donoho. Neural collapse under mse loss: Proximity to and dynamics on the central path. *arXiv preprint arXiv:2106.02073*, 2021.

[3] Cong Fang, Hangfeng He, Qi Long, and Weijie J Su. Exploring deep neural networks via layer-peeled model: Minority collapse in imbalanced training. *Proceedings of the National Academy of Sciences*, 118(43), 2021.

[4] Zhihui Zhu, Tianyu Ding, Jinxin Zhou, Xiao Li, Chong You, Jeremias Sulam, and Qing Qu. A geometric analysis of neural collapse with unconstrained features. *Advances in Neural Information Processing Systems*, 34, 2021.

[5] Jinxin Zhou, Xiao Li, Tianyu Ding, Chong You, Qing Qu, and Zhihui Zhu. On the optimization landscape of neural collapse under mse loss: Global optimality with unconstrained features. *arXiv preprint arXiv:2203.01238*, 2022.

[6] Tom Tirer and Joan Bruna. Extended unconstrained features model for exploring deep neural collapse. *arXiv preprint arXiv:2202.08087*, 2022.

[7] Florian Graf, Christoph Hofer, Marc Niethammer, and Roland Kwitt. Dissecting supervised constrastive learning. In *International Conference on Machine Learning*, pages 3821–3830. PMLR, 2021.

[8] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[9] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[10] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4700–4708, 2017.

[11] Yann LeCun, Corinna Cortes, and CJ Burges. Mnist handwritten digit database. at&t labs, 2010.

[12] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[13] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[14] Yandong Wen, Kaipeng Zhang, Zhifeng Li, and Yu Qiao. A discriminative feature learning approach for deep face recognition. In *European conference on computer vision*, pages 499–515. Springer, 2016.

[15] Weiyang Liu, Yandong Wen, Zhiding Yu, and Meng Yang. Large-margin softmax loss for convolutional neural networks. *arXiv preprint arXiv:1612.02295*, 2016.

[16] Rajeev Ranjan, Carlos D Castillo, and Rama Chellappa. L2-constrained softmax loss for discriminative face verification. *arXiv preprint arXiv:1703.09507*, 2017.

[17] Feng Wang, Xiang Xiang, Jian Cheng, and Alan Loddon Yuille. Normface: L2 hypersphere embedding for face verification. In *Proceedings of the 25th ACM international conference on Multimedia*, pages 1041–1049, 2017.

[18] Weiyang Liu, Yandong Wen, Zhiding Yu, Ming Li, Bhiksha Raj, and Le Song. Sphereface: Deep hypersphere embedding for face recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 212–220, 2017.

[19] Hao Wang, Yitong Wang, Zheng Zhou, Xing Ji, Dihong Gong, Jingchao Zhou, Zhifeng Li, and Wei Liu. Cosface: Large margin cosine loss for deep face recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 5265–5274, 2018.

[20] Jiankang Deng, Jia Guo, Niannan Xue, and Stefanos Zafeiriou. Arcface: Additive angular margin loss for deep face recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4690–4699, 2019.

[21] Federico Pernici, Matteo Bruni, Claudio Baecchi, and Alberto Del Bimbo. Maximally compact and separated features with regular polytope networks. In *CVPR Workshops*, pages 46–53, 2019.

[22] Federico Pernici, Matteo Bruni, Claudio Baecchi, and Alberto Del Bimbo. Regular polytope networks. *IEEE Transactions on Neural Networks and Learning Systems*, 2021.

[23] Uri Cohen, SueYeon Chung, Daniel D Lee, and Haim Sompolinsky. Separability and geometry of object manifolds in deep neural networks. *Nature communications*, 11(1):1–13, 2020.

[24] Jonathan Mamou, Hang Le, Miguel Del Rio, Cory Stephenson, Hanlin Tang, Yoon Kim, and Sueyeon Chung. Emergence of separable manifolds in deep language representations. In *International Conference on Machine Learning*, pages 6713–6723. PMLR, 2020.

[25] Diego Doimo, Aldo Glielmo, Alessio Ansuini, and Alessandro Laio. Hierarchical nucleation in deep neural networks. *Advances in Neural Information Processing Systems*, 33:7526–7536, 2020.

[26] Gregory Naitzat, Andrey Zhitnikov, and Lek-Heng Lim. Topology of deep neural networks. *J. Mach. Learn. Res.*, 21(184):1–40, 2020.

[27] Stefano Recanatesi, Matthew Farrell, Madhu Advani, Timothy Moore, Guillaume Lajoie, and Eric Shea-Brown. Dimensionality compression and expansion in deep neural networks. *arXiv preprint arXiv:1906.00443*, 2019.

[28] Nicholas Frosst, Nicolas Papernot, and Geoffrey Hinton. Analyzing and improving representations with the soft nearest neighbor loss. In *International conference on machine learning*, pages 2012–2020. PMLR, 2019.

[29] Christoph Hofer, Florian Graf, Marc Niethammer, and Roland Kwitt. Topologically densified distributions. In *International Conference on Machine Learning*, pages 4304–4313. PMLR, 2020.

[30] Kwan Ho Ryan Chan, Yaodong Yu, Chong You, Haozhi Qi, John Wright, and Yi Ma. Deep networks from the principle of rate reduction. *arXiv preprint arXiv:2010.14765*, 2020.

[31] Yaodong Yu, Kwan Ho Ryan Chan, Chong You, Chaobing Song, and Yi Ma. Learning diverse and discriminative representations via the principle of maximal coding rate reduction. *arXiv preprint arXiv:2006.08558*, 2020.

[32] Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *International Conference on Machine Learning*, pages 9929–9939. PMLR, 2020.

[33] En Yu, Zhuoling Li, and Shoudong Han. Towards discriminative representation: Multi-view trajectory contrastive learning for online multi-object tracking. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8834–8843, 2022.

[34] Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschinot, Ce Liu, and Dilip Krishnan. Supervised contrastive learning. *Advances in Neural Information Processing Systems*, 33:18661–18673, 2020.

[35] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. *arXiv preprint arXiv:2002.05709*, 2020.

[36] Jianfeng Lu and Stefan Steinerberger. Neural collapse with cross-entropy loss. *arXiv preprint arXiv:2012.08465*, 2020.

[37] Stephan Wojtowytsch et al. On the emergence of simplex symmetry in the final and penultimate layers of neural network classifiers. *arXiv preprint arXiv:2012.05420*, 2020.

[38] Wenlong Ji, Yiping Lu, Yiliang Zhang, Zhun Deng, and Weijie J Su. An unconstrained layer-peeled perspective on neural collapse. *arXiv preprint arXiv:2110.02796*, 2021.

[39] Dustin G Mixon, Hans Parshall, and Jianzong Pi. Neural collapse with unconstrained features. *arXiv preprint arXiv:2011.11619*, 2020.

[40] Cong Fang, Hangfeng He, Qi Long, and Weijie J Su. Layer-peeled model: Toward understanding well-trained deep neural networks. *arXiv preprint arXiv:2101.12699*, 2021.

[41] Zhou Lu, Hongming Pu, Feicheng Wang, Zhiqiang Hu, and Liwei Wang. The expressive power of neural networks: a view from the width. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 6232–6240, 2017.

[42] Kurt Hornik. Approximation capabilities of multilayer feedforward networks. *Neural networks*, 4(2):251–257, 1991.

[43] Uri Shaham, Alexander Cloninger, and Ronald R Coifman. Provable approximation properties for deep neural networks. *Applied and Computational Harmonic Analysis*, 44(3):537–557, 2018.

[44] Rong Ge, Furong Huang, Chi Jin, and Yang Yuan. Escaping from saddle points—online stochastic gradient for tensor decomposition. In *Proceedings of The 28th Conference on Learning Theory*, pages 797–842, 2015.

[45] Ju Sun, Qing Qu, and John Wright. When are nonconvex problems not scary? *arXiv preprint arXiv:1510.06096*, 2015.

[46] Tomer Galanti, András György, and Marcus Hutter. On the role of neural collapse in transfer learning. In *International Conference on Learning Representations*, 2022.

[47] Like Hui, Mikhail Belkin, and Preetum Nakkiran. Limitations of neural collapse for understanding generalization in deep learning. *arXiv preprint arXiv:2202.08384*, 2022.

[48] Vardan Papyan. Traces of class/cross-class structure pervade deep learning spectra. *Journal of Machine Learning Research*, 21(252):1–64, 2020.

[49] Ido Ben-Shaul and Shai Dekel. Nearest class-center simplification through intermediate layers. *arXiv preprint arXiv:2201.08924*, 2022.

[50] Liang Xie, Yibo Yang, Deng Cai, Dacheng Tao, and Xiaofei He. Neural collapse inspired attraction-repulsion-balanced loss for imbalanced learning. *arXiv preprint arXiv:2204.08735*, 2022.

[51] Yibo Yang, Liang Xie, Shixiang Chen, Xiangtai Li, Zhouchen Lin, and Dacheng Tao. Do we really need a learnable classifier at the end of deep neural network? *arXiv preprint arXiv:2203.09081*, 2022.

[52] Nicolas Boumal. An introduction to optimization on smooth manifolds. *Available online, May*, 3, 2020.

[53] C Jin, MI Jordan, R Ge, P Netrapalli, and SM Kakade. How to escape saddle points efficiently. In *International Conference on Machine Learning*, pages 2727–2752, 2017.

[54] Simon S Du, Chi Jin, Jason D Lee, Michael I Jordan, Aarti Singh, and Barnabas Poczos. Gradient descent can take exponential time to escape saddle points. In *Advances in neural information processing systems*, pages 1067–1077, 2017.

[55] Nicolas Boumal. An introduction to optimization on smooth manifolds. To appear with Cambridge University Press, Jan 2022.

[56] Jiang Hu, Xin Liu, Zai-Wen Wen, and Ya-Xiang Yuan. A brief introduction to manifold optimization. *Journal of the Operations Research Society of China*, 8(2):199–248, 2020.

[57] P-A Absil, Robert Mahony, and Rodolphe Sepulchre. *Optimization algorithms on matrix manifolds*. Princeton University Press, 2009.

[58] Christopher Criscitiello and Nicolas Boumal. Efficiently escaping saddle points on manifolds. *Advances in Neural Information Processing Systems*, 32, 2019.

[59] Yue Sun, Nicolas Flammarion, and Maryam Fazel. Escaping from saddle points on riemannian manifolds. *Advances in Neural Information Processing Systems*, 32, 2019.

[60] Qing Qu, Ju Sun, and John Wright. Finding a sparse vector in a subspace: Linear sparsity using alternating directions. In *Advances in Neural Information Processing Systems*, pages 3401–3409, 2014.

[61] Ju Sun, Qing Qu, and John Wright. Complete dictionary recovery over the sphere I: Overview and the geometric picture. *IEEE Transactions on Information Theory*, 63(2):853–884, 2016.

[62] Ju Sun, Qing Qu, and John Wright. Complete dictionary recovery over the sphere II: Recovery by Riemannian trust−region method. *IEEE Transactions on Information Theory*, 63(2):853–884, 2017.

[63] Qing Qu, Yuexiang Zhai, Xiao Li, Yuqian Zhang, and Zhihui Zhu. Geometric analysis of nonconvex optimization landscapes for overcomplete learning. In *International Conference on Learning Representations*, 2020.

[64] Qing Qu, Zhihui Zhu, Xiao Li, Manolis C. Tsakiris, John Wright, and René Vidal. Finding the sparsest vectors in a subspace: Theory, algorithms, and applications. *arXiv preprint arXiv:2001.06970*, 2020.

[65] Han-Wen Kuo, Yenson Lau, Yuqian Zhang, and John Wright. Geometry and symmetry in short-and-sparse deconvolution. In *International Conference on Machine Learning*, pages 3570–3580. PMLR, 2019.

[66] Qing Qu, Xiao Li, and Zhihui Zhu. Exact recovery of multichannel sparse blind deconvolution via gradient descent. *SIAM Journal on Imaging Sciences*, 13(3):1630–1652, 2020.

[67] Yenson Lau, Qing Qu, Han-Wen Kuo, Pengcheng Zhou, Yuqian Zhang, and John Wright. Short and sparse deconvolution — a geometric approach. In *International Conference on Learning Representations*, 2020.

[68] Yuqian Zhang, Han-Wen Kuo, and John Wright. Structured local optima in sparse blind deconvolution. *IEEE Transactions on Information Theory*, 66(1):419–452, 2019.

[69] Yuqian Zhang, Qing Qu, and John Wright. From symmetry to geometry: Tractable nonconvex problems. *arXiv preprint arXiv:2007.06753*, 2020.

[70] Vignesh Kothapalli, Ebrahim Rasromani, and Vasudev Awatramani. Neural collapse: A review on modelling principles and generalization. *arXiv preprint arXiv:2206.04041*, 2022.

[71] Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. *arXiv preprint arXiv:1611.03530*, 2016.

[72] Simon Kornblith, Ting Chen, Honglak Lee, and Mohammad Norouzi. Why do better loss functions lead to less transferable features? In *NeurIPS*, 2021.

[73] Kwan Ho Ryan Chan, Yaodong Yu, Chong You, Haozhi Qi, John Wright, and Yi Ma. Redunet: A white-box deep network from the principle of maximizing rate reduction. *ArXiv*, abs/2105.10446, 2021.

[74] Akshay Rangamani, Mengjia Xu, Andrzej Banburski, Qianli Liao, and Tomaso Poggio. Dynamics and neural collapse in deep classifiers trained with the square loss. *Technical report, Center for Brains, Minds and Machines (CBMM)*, 2021.

[75] Florian Graf, Christoph Hofer, Marc Niethammer, and Roland Kwitt. Neural collapse in deep homogeneous classifiers and the role of weight decay. In *International Conference on Machine Learning*, pages 3821–3830. PMLR, 2021.

[76] Tomaso Poggio and Qianli Liao. Implicit dynamic regularization in deep networks. Technical report, Center for Brains, Minds and Machines (CBMM), 2020.

[77] Tomaso Poggio and Qianli Liao. Explicit regularization and implicit bias in deep network classifiers trained with the square loss. *arXiv preprint arXiv:2101.00072*, 2020.

[78] Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection, 2017.

[79] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jonathon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision, 2015.