Boosting Adversarial Robustness with CLAT: Criticality-Leveraged Adversarial Training

Abstract

Adversarial training (AT) is a common technique for enhancing neural network robustness. Typically, AT updates all trainable parameters, but such comprehensive adjustments can lead to overfitting and increased generalization errors on clean data. Research suggests that fine-tuning specific parameters may be more effective; however, methods for identifying these essential parameters and establishing effective optimization objectives remain unclear and inadequately addressed. We present CLAT, an innovative adversarial fine-tuning algorithm that mitigates adversarial overfitting by integrating "criticality" into the training process. Instead of tuning the entire model, CLAT identifies and fine-tunes fewer parameters in robustness-critical layers—those predominantly learning non-robust features—while keeping the rest of the model fixed. Additionally, CLAT employs a dynamic layer selection process that adapts to changes in layer criticality during training. Empirical results demonstrate that CLAT can be seamlessly integrated with existing adversarial training methods, enhancing clean accuracy and adversarial robustness by over 2% compared to baseline approaches.

1 Introduction

Advancements in deep learning models have markedly improved image classification accuracy. Despite this, their vulnerability to adversarial attacks — subtle modifications to input images that mislead the model — remains a significant concern (Goodfellow et al., 2015; Szegedy et al., 2014). The research community has been rigorously exploring theories to comprehend the mechanics behind adversarial attacks (Bai et al., 2021). Ilyas et al. (2019) uncover the coexistence of robust and non-robust features in standard datasets. Adversarial vulnerability largely stems from the presence of non-robust features in models trained on standard datasets, which, while highly predictive and beneficial for clean accuracy, are susceptible to noise (Szegedy et al., 2014). Unfortunately, it is observed that deep learning models tend to preferentially learn these non-robust features. Inkawhich et al. (2019; 2020) further demonstrate that adversarial images derived from the hidden features of certain intermediate non-robust/"critical" layers exhibit enhanced transferability to unseen models. This suggests a commonality in the non-robust features captured by these layers. While identifying these critical layers to improve their robustness is appealing, this process often requires the time-consuming generation of attacks against each individual layer. Methods to identify and effectively address the criticality of such layers are still lacking.

In contrast to layer-wise feature vulnerability analysis, adversarial training (Athalye et al., 2018; Madry et al., 2019; Croce & Hein, 2020), involves training entire neural networks with adversarial examples generated in real-time. This approach inherently encourages all layers in the model to learn

Figure 1: **CLAT overview.** CLAT fine-tunes the selected critical layers (red) while freezing other layers (grey). fine-tuning objective is computed per Eq. (9). Critical layers are adjusted periodically. Pseudocode is provided in **Appendix A**.

robust features from adversarial images, thereby enhancing the model's resilience against attacks. However, given the more challenging optimization process of learning from adversarial examples than from clean ones, adversarial training also brings hurdles such as heightened errors on clean data and susceptibility to overfitting, ultimately diminishing its effectiveness in practical applications (Schmidt et al., 2018; Zhang et al., 2019; Raghunathan et al., 2019; Javanmard et al., 2020). Despite various efforts to enhance adversarial training, such as modifying input data and adjusting loss functions (Hitaj et al., 2021; Raghunathan et al., 2019; Zhang et al., 2019; Wang et al., 2020; Wu et al., 2020b; Pang et al., 2022), these approaches still frequently fall short in alleviating the aforementioned issues.

In light of these challenges, we introduce CLAT, a paradigm shift in adversarial training, where we mitigate overfitting during adversarial training by identifying and tuning only the robustness-critical model layers. CLAT commences by pinpointing critical layers within a model using our novel, theoretically grounded, and easily computable,**"criticality index"**, which we developed to identify layers which have learned non-robust features dominantly. Subsequently, our algorithm meticulously fine-tunes these critical layers to remove their non-robust features and reduce their criticality, while freezing the other, non-critical layers. Dynamic selection of critical layers is conducted during the training process to always focus fine-tuning on the most-in-need layers, avoiding the overfitting of full-model adversarial training. CLAT therefore achieves both clean and adversarial state-of-the-art (SOTA) accuracy compared to previous adversarial training methods.

In summary, we make the following contributions in this paper:

- We introduce the "criticality index", a quantitative metric designed to identify critical layers for the adversarial vulnerability of a model with minimal overhead.
- We develop a specialized adversarial training objective focused on reducing the criticality of the identified critical layers to bolster overall model robustness.
- We propose CLAT, an adversarial fine-tuning algorithm that mitigates overfitting by focusing on reducing the criticality of fewer than 4% of trainable parameters. CLAT integrates seamlessly into diverse model training scenarios and baseline adversarial training methods.

CLAT stands out by markedly reducing overfitting risks, boosting both clean accuracy and adversarial resilience by approximately *2%*.

2 RELATED WORK

2.1 ADVERSARIAL TRAINING

Adversarial Training (AT) was first introduced by (Goodfellow et al., 2015), who demonstrated how the integration of adversarial examples into the training process could substantially improve model robustness. This idea evolved into a sophisticated minimax optimization approach with Projected Gradient Descent Adversarial Training (PGD-AT) (Madry et al., 2019), which employs PGD attacks in training. Regarded as the gold standard in AT, PGD-AT generates adversarial training samples using multiple steps of projected gradient descent, leading to substantially improved empirical robustness (Carlini & Wagner, 2017; Athalye et al., 2018; Croce & Hein, 2020). Further refining this approach, TRADES (Zhang et al., 2019) optimizes a novel loss function to balance classification accuracy with adversarial robustness. Recent enhancements in AT, including model ensemble and data augmentation, have also produced notable improvements in model resilience. (Xie et al., 2020; Yang et al., 2020; Carmon et al., 2022). Inkawhich et al. (2019) propose "Activation Attacks" (AA) which underscore the efficacy of leveraging intermediate model layers for generating stronger adversarial attacks, suggesting that incorporating AA in adversarial training could fortify defenses. Their findings provide a foundation for our method which integrates these intermediate critical layers into our adversarial training strategy.

2.2 ADVERSARIAL TRAINING IMPROVEMENTS AND ROBUST OVERFITTING

Adversarial training methods like PGD-AT and TRADES are computationally expensive and prone to overfitting, requiring multi-step adversary generation, complex objectives, and extensive model tuning (Shafahi et al., 2019). To improve efficiency, Shafahi et al. (2019) proposed "Free" AT, which accelerates training by using a single backpropagation step for both training and PGD adversary

generation. However, gradient alignment issues led to reduced robustness and increased overfitting. Similarly, Wong et al. (2020) introduced "Fast" AT, but it also suffered from similar weaknesses (Andriushchenko & Flammarion, 2020), prompting the development of GradAlign. Unfortunately, GradAlign tripled training time due to second-order gradient computation. Later efforts sought to address robust overfitting. RiFT (Zhu et al., 2023) improved general performance by leveraging layer redundancies but was constrained by heuristic redundancy measurements. Zhang et al. (2024) mitigated overfitting by disentangling natural and adversarial objectives, yet model-wide adjustments still limited robustness. In contrast, CLAT uses a theoretically grounded, dynamic, critical layer selection mechanism, resulting in improved robust generalization by tuning a critical subset of layers. Furthermore, CLAT is agnostic to attack generation methods in the AT processing, making it an ideal complement to existing fast-AT methods to mitigate overfitting.

3 METHODS

Building on prior attack and defense research (Inkawhich et al., 2019; 2020; Zhu et al., 2023) which demonstrates that not all model layers equally learn non-robust features and having all layers learn robust features leads to overfitting, we aim to improve model robustness by identifying and fine-tuning only those critical layers that are prone to learning non-robust features, while keeping the non-critical layers frozen. In this section, we begin by defining and identifying critical layers, then outline our objectives for reducing their criticality. Finally, we present our complete CLAT algorithm, which effectively mitigates overfitting and enhances model robustness.

3.1 LAYER CRITICALITY

Consider a deep learning model with n layers, and an input x, defined as:

$$F(x) = f_n(f_{n-1}(\ldots f_1(x))), \tag{1}$$

where the functionality of the i-th layer is denoted as f_i. During the standard training process, all layers learn useful features which contribute to the correct outputs of the model. We denote the hidden feature learned at the output of the i-th layer as $F_i(x) = f_i(f_{i-1}(\ldots f_1(x)))$.

Under adversarial perturbation, features from all layers will be altered, leading to incorrect outputs. To understand how the learned parameters of the model affect the features under perturbation, we consider a function $G_i(\cdot)$ defined at the output of layer i on inputs close to a clean data point x:

$$G_i(z) = ||F_i(z) - F_i(x)||_2^2. \tag{2}$$

Clearly, $z = x$ is a minima of $G_i(z)$. The worst-case curvature of the function G_i at the neighborhood of $z = x$ can be estimated following the formulation by Moosavi-Dezfooli et al. (2019) as

$$\nu_i(x) = \frac{\nabla G_i(x') - \nabla G_i(x)}{||x' - x||_2} = \frac{\nabla G_i(x')}{||x' - x||_2}, \tag{3}$$

where x' is a worst-case perturbation (adversarial attack) maximizing $G_i(z)$ in the vicinity of x, and $\nabla G_i(x) = 0$ by definition given it is a minimum.

To avoid the high cost of computing higher-order gradients when optimizing with the curvature, the numerator in the curvature formulation can be further derived as

$$\nu_i(x) = \frac{\frac{\partial F_i(x')}{\partial x'}^T (F_i(x') - F_i(x))}{||x' - x||_2}. \tag{4}$$

Following the observation in Moosavi-Dezfooli et al. (2019), a higher curvature indicates the feature to be more non-robust to adversarial examples. We can therefore use the curvature formulation $\nu_i(x)$ under a fixed perturbation budget $||x' - x||_p \leq \epsilon$ to estimate the layer non-robustness, or weakness.

In practice, it is difficult to explicitly instantiate $\frac{\partial F_i(x')}{\partial x'}$ for a neural network. To this end, we simplify the formulation in Eq. (4) by assuming $\frac{\partial F_i(x')}{\partial x'}$ as a uniform vector. This leads to our definition of the ϵ-weakness of layer i's feature as:

$$\mathcal{W}_\epsilon(F_i) = \frac{1}{N_i} \mathbb{E}_x \left[\sup_{||\delta||_p \leq \epsilon} ||F_i(x + \delta) - F_i(x)||_2 \right], \tag{5}$$

where N_i denotes the dimensionality of the output features at layer i, therefore normalizing the weakness measurement of layers with different output sizes. The weakness measurement is proportional to the curvature estimation in Eq. (4). A higher weakness value indicates that the feature vector is more vulnerable to input perturbations. The functionality of cascading layers from 1 to i affects the vulnerability of the hidden features, as described by this formulation.

For the purpose of mitigating overfitting, we want to identify the layers that are the most critical to the lack of robustness, characterized by their increased susceptibility to perturbations from adversarial inputs. Other already-robust layers shall then be fixed to avoid further overfitting to the adversarial training objective. We therefore provide the following definition:

Definition 3.1. Critical layer: A layer is considered critical if it exhibits a greater propensity to learn non-robust features or demonstrates diminished robustness to adversarial input perturbations relative to other layers in the model.

To this end, we single out the contribution of each layer's functionality to the weakness of the features after it with a *Layer Criticality Index* $\mathcal{C}_{f_i}$, which is formulated as

$$\mathcal{C}_{f_i} = \frac{\mathcal{W}_\epsilon(F_i)}{\mathcal{W}_\epsilon(F_{i-1})}. \tag{6}$$

For the first layer, we define $\mathcal{C}_{f_1} = \mathcal{W}_\epsilon(F_1)$ as only the first layer contributes to the weakness.

As a sanity check, the feature weakness at the output of layer i can be attributed to the criticality of all previous layers as $\mathcal{W}_\epsilon(F_i) = \prod_{k=1}^{i} \mathcal{C}_{f_k}$. Conversely, a layer with a larger criticality index will increase the weakness of the features after it, indicating the layer is critical according to Definition 3.1, as it weakens the feature robustness to the adversarial input.

One drawback of the formulation in Eq. (6) is that computing the feature weakness involves finding the worst-case perturbation against the hidden features at each layer, which is a costly process to conduct sequentially for all layers. In practice, we approximate the worst-case perturbation against features with an untargeted PGD attack against the model output, so that we can use the same PGD perturbation δ to estimate the feature weakness of all layers following Eq. (5). In this way, with a reasonably sufficient batch size, we can compute the critical indices for all layers in a model with two forward passes: one with the clean input x and one with the PGD attack input $x + \delta$. We make the following proposition:

Proposition 3.2. *Critical layers defined as in Definition 3.1 can be identified as the layers with the largest criticality indices* $\arg\max_i \mathcal{C}_{f_i}$.

To verify Proposition 3.2, we conduct an ablation study in Table 7, where we show that model robustness is improved more by CLAT fine-tuning of critical layers compared to equivalent fine-tuning of randomly selected layers. We will discuss how to reduce the criticality of the critical layers and make them more robust in the next subsection.

3.2 Criticality-targeted fine-tuning

Once the critical layers are identified, we fine-tune them to reduce their criticality, thereby decreasing the weakness of subsequent hidden features and enhancing model robustness. For a critical layer i, we optimize the trainable parameters to minimize $\mathcal{C}_{f_i}$. Note that in the criticality formulation in Eq. (6), the weakness of the previous layer's output, $\mathcal{W}_\epsilon(F_{i-1})$, is constant with respect to f_i. Thus, the optimization objective for f_i can be simplified as

$$\mathcal{L}_C(f_i) = \mathbb{E}_x \left[\sup_{||\delta||_p \leq \epsilon} ||F_i(x + \delta) - F_i(x)||_2 \right]. \tag{7}$$

In the case where multiple critical layers are considered in the fine-tuning process, the fine-tuning objective can be expanded to accommodate all critical layers simultaneously. Formally, suppose we have a set S where layers $i \in S$ are all selected for fine-tuning, the fine-tuning objective for these critical layers can be formulated as

$$\mathcal{L}_C(f_S) = \mathbb{E}_x \left[\sup_{||\delta||_p \leq \epsilon} \sum_{i \in S} ||F_i(x + \delta) - F_i(x)||_2 \right], \tag{8}$$

where a single perturbation is utilized to capture the weakness across all critical layers. In the common setting, a projected gradient ascent optimization with random start is used for the inner maximization.

Minimizing the objective in Eq. (8) by adjusting the trainable variables of the critical layers will reduce their feature weaknesses. However, the removal of non-robust features in these layers may affect the functionality of the model on clean inputs. As a tradeoff, we also include the cross entropy loss $\mathcal{L}(\cdot)$ in the final optimization objective, which derives the optimization objective on the critical layers during the fine-tuning process

$$\min_{f_S} \mathbb{E}_{x,y} \mathcal{L}(F(x), y) + \lambda \mathcal{L}_C(f_S), \tag{9}$$

where the hyperparameter λ serves as a balancing factor between the two loss terms. Note that only the selected critical layers f_S are optimized in Eq. (9) while the other non-critical layers are frozen, preventing them from further overfitting.

3.3 CLAT ADVERSARIAL TRAINING

We design CLAT as a fine-tuning approach, which is applied to neural networks that have undergone preliminary training. The pretraining phase allows all layers in the model to capture useful features, which will facilitate the identification of critical layers in the model. Notably, CLAT's versatility allows it to adapt to various types of pretrained models, either adversarially trained or trained on a clean dataset only. In practice, we find that models do not need to fully converge during the pretraining phase to benefit from CLAT fine-tuning. For example, in case of the CIFAR-10 dataset, 50 epochs of PGD-AT training would be adequate. We consider the number of adversarial pretraining epochs as a hyperparameter and provide further analysis on the impact of pretraining epochs in Section 4.3.1.

After the pretraining, CLAT begins by identifying and selecting critical layers in the pretrained model. We then fine-tune critical layers only while freezing the rest of the layers. This process is illustrated in Fig. 1, and the pseudocode is provided in Algorithm 1 in **Appendix A** for greater clarity. As fine-tuning progresses, the critical layers will be updated to reduce their criticality, making them less critical than some of the previously frozen layers. Subsequently, we perform periodic reevaluation of the top k critical indices, ensuring continuous adaptation and optimization of the layers that are the most in need in the training process. Through hyperparameter optimization, we find 10 epochs to be adequate to optimize the selected critical layers for all models that we tested.

4 EXPERIMENTS

4.1 EXPERIMENTAL SETTINGS

Datasets and models We conducted experiments using two widely recognized image classification datasets, CIFAR10 and CIFAR100. Each dataset includes 60,000 color images, each 32×32 pixels, divided into 10 and 100 classes respectively (Krizhevsky & Hinton, 2009). For our experiments, we deployed a suite of network architectures: WideResnets (34-10, 70-16) (Zagoruyko & Komodakis, 2017), ResNets (50, 18) (He et al., 2016b), DenseNet-121 (Huang et al., 2017), PreAct ResNet-18(He et al., 2016a), and VGG-19 (Simonyan & Zisserman, 2015). In this paper, these architectures are referred to as WRN34-10, WRN70-16, RN50, RN18, DN121, Preact RN18 and VGG19 respectively.

Training and evaluation Since CLAT can be layered over clean pretraining, partial training, or other adversarial methods, results incorporating CLAT are denoted in our tables as "X + CLAT," where "X" refers to the baseline method applied prior to CLAT. Typically, this baseline method is run for the first 50 epochs, followed by fine-tuning during which CLAT is applied for an additional 50 epochs. The total number of epochs is in line with the 100 epochs used in previous PGD-based adversarial training work (Zhang et al., 2019; Zhu et al., 2023).

For our baseline, we use PGD for attack generation during training, following a random start (Madry et al., 2019), with an attack budget of $\epsilon = 0.03$ under the ℓ_∞ norm, a step size of $\alpha = 0.007$, and 10 attack steps. The same settings apply to PGD attack evaluations. AutoAttack evaluations (Croce & Hein, 2020) also use a budget of $\epsilon = 0.03$ under the ℓ_∞ norm, with no restarts for untargeted APGD-CE, 9 target classes for APGD-DLR, 3 target classes for Targeted FAB, and 5000 queries for Square Attack. These settings remain consistent unless explicitly noted otherwise.

Experiments were conducted on a Titan XP GPU, starting with an initial learning rate of 0.1, which was adjusted according to a cosine decay schedule. To ensure the reliability of robustness measurements, we conducted each experiment a minimum of 10 times, reporting the lowest adversarial accuracies we observed.

CLAT settings We select critical layers as described in Section 3.1. Table 8 outlines the Top-5 most critical layers for some of the models and corresponding datasets at the start of the CLAT fine-tuning, after adversarially training with pgd-at for 50 epochs. In customizing the CLAT methodology to various network sizes, we select approximately 5% of layers as critical through hyperparameter optimization. For instance, DN121 uses 5 critical layers, while WRN70-16, RN50, WRN34-10, VGG19, and RN18 use 4, 3, 2, 1, and 1 critical layers, respectively.

4.2 CLAT PERFORMANCE

White-box robustness Table 1 and Table 2 present white-box evaluation results using the PGD and Auto attack frameworks, respectively. These tables illustrate CLAT's versatility and effectiveness when combined with various standard adversarial training methods, including state-of-the-art benchmarks from RobustBench (Croce et al., 2020). CLAT effectively mitigates the overfitting typically observed in traditional adversarial training, thereby enhancing both clean and adversarial accuracy compared to baseline methods.

Table 1 further highlights that reducing trainable parameters alone does not necessarily lead to improved performance. CLAT surpasses other parameter-efficient fine-tuning methods, such as LoRA (Aleem et al., 2024) and RiFT (Zhu et al., 2023), due to its ability to precisely identify critical layers and eliminate non-robust features from these layers. Additionally, we show that fast adversarial training techniques, as discussed by Wong et al. (2020), can be applied to address the inner maximization problem in the CLAT training objective described in Eq. (8). The "CLAT (Fast)" method not only enhances performance but also improves robustness compared to Fast-AT baselines.

Notably, CLAT models are trained with PGD-like attacks on hidden features without seeing Auto Attacks directly, but their robustness persists under these attacks (see Table 2). This suggests that different attacks across various networks share similarities in exploiting non-robust features. By addressing these non-robust features through critical layer fine-tuning, CLAT ensures that the robustness is adaptable across different attack settings and models. Lastly, we assess the robustness across various attack strengths in **Appendix B**.

Black-box robustness Table 3 and Table 4 evaluate the robustness against black-box attacks (Auto Attack and PGD-AT respectively) between models trained solely using PGD-AT and those augmented with CLAT. Attack settings are the same as those of the white-box attacks. As a sanity check, the accuracies under black-box attack surpass those observed under white-box scenarios, indicating that gradient masking does not appear in the CLAT model, and that the white-box robustness evaluation is valid. More significantly, models trained with CLAT consistently outperform those trained with PGD-AT, maintaining superior resilience in both black-box and white-box settings, regardless of the attack method or models employed.

4.3 ABLATION STUDIES

4.3.1 ABLATING ON PRETRAINING EPOCHS BEFORE CLAT

As discussed in Section 3.3, we apply CLAT after the model has been adversarially trained for some epochs. Here, we analyze how the number of pretraining epochs affects CLAT performance. Fig. 2 shows the training curves for different allocations of PGD pretraining epochs and CLAT fine-tuning epochs within a 100-epoch training budget. The overfitting of PGD-AT is evident as adversarial accuracy plateaus and declines towards the end, as documented in previous research (Rice et al., 2020). In contrast, CLAT continues to improve adversarial accuracy, effectively addressing this issue. Including CLAT at any stage of training results in higher clean accuracy and robustness at convergence. Additional results on pretrained clean models are provided in **Appendix C**.

Furthermore, an intriguing aspect of our experiments involves running CLAT from scratch (0 PGD-AT epochs). Although CLAT ultimately surpasses PGD-AT with sufficient epochs, using CLAT without

Table 1: Comparative performance of CLAT across various networks and adversarial training/fine-tuning techniques. Robustness is evaluated with white-box PGD attacks.

MODEL	METHOD	CIFAR-10 ACC. (%)		CIFAR-100 ACC. (%)	
		CLEAN	ADVERSARIAL	CLEAN	ADVERSARIAL
DN121	PGD-AT (MADRY ET AL., 2019)	80.05	58.15	57.18	31.76
	PGD-AT + CLAT	**81.03**	**60.60**	**58.79**	**33.23**
WRN70-16	(PENG ET AL., 2023)	93.27	71.07	70.20	42.61
	PENG ET AL. + CLAT	**93.56**	**72.25**	**71.94**	**44.12**
	(BAI ET AL., 2024)	92.23	64.55	69.17	40.86
	BAI ET AL. + CLAT	**92.77**	**64.92**	**70.17**	**41.64**
RN50	PGD-AT	81.38	56.35	58.16	33.01
	PGD-AT + CLAT	**83.78**	**59.54**	**61.88**	**36.23**
WRN34-10	PGD-AT	87.41	55.40	59.19	31.66
	PGD-AT + LORA (ALEEM ET AL., 2024)	73.36	56.17	55.56	31.43
	PGD-AT + RIFT (ZHU ET AL., 2023)	87.89	55.41	62.35	31.64
	PGD-AT + CLAT	**88.97**	**57.11**	**62.38**	**32.05**
	TRADES (ZHANG ET AL., 2019)	87.60	56.61	60.56	31.85
	TRADES + RIFT	87.55	56.72	61.01	32.03
	TRADES + CLAT	**88.23**	**57.89**	**61.45**	**33.56**
VGG19	PGD-AT	78.38	50.35	50.16	26.54
	PGD-AT + CLAT	**79.88**	**52.54**	**50.98**	**28.41**
RN18	PGD-AT	81.46	53.63	57.10	30.15
	PGD-AT + LORA	76.57	55.38	48.49	32.36
	PGD-AT + RIFT	83.44	53.65	58.74	30.17
	PGD-AT + CLAT	**83.89**	**55.37**	**59.22**	**32.04**
	TRADES	81.54	53.31	57.44	30.20
	TRADES + RIFT	81.87	53.30	57.78	30.22
	TRADES + CLAT	**81.89**	**54.57**	**58.82**	**31.06**
	MART (WANG ET AL., 2019)	76.77	56.90	51.46	31.47
	MART + RIFT	77.14	56.92	52.42	31.48
	MART + CLAT	**76.82**	**57.55**	**53.01**	**33.23**
	AWP (WU ET AL., 2020B)	78.40	53.83	52.85	31.00
	AWP + RIFT	78.79	53.84	54.89	31.05
	AWP + CLAT	**79.01**	**55.27**	**55.39**	**32.08**
	SCORE (PANG ET AL., 2022)	84.20	54.59	54.83	29.49
	SCORE + RIFT	85.65	54.62	57.63	29.50
	SCORE + CLAT	**86.11**	**55.78**	**57.66**	**30.23**
	AUTOLORA (ZHANG ET AL., 2024)	84.2	54.27	62.1	32.71
	AUTOLORA + CLAT	**86.45**	**58.53**	**64.91**	**35.82**
PREACT RN18	FAST-AT (WONG ET AL., 2020)	81.46	45.55	50.10	27.72
	FAST-AT + CLAT	**84.46**	**52.13**	**54.33**	**29.22**
	FAST-AT + CLAT (FAST)	**82.72**	**49.62**	**52.10**	**27.99**

any prior adversarial training results in significantly slower model convergence. We believe this suggests that "layer criticality" emerges during the adversarial training process, allowing critical layers to be identified as the model undergoes adversarial training. This phenomenon supports our theoretical insight that criticality can be linked to the curvature of the local minima to which each layer converges during adversarial training.

Figure 2: Comparative analysis of CLAT performance on WRN34-10: Clean and adversarial accuracy on CIFAR-10 across partially trained models.

Table 2: Adversarial Accuracy on CIFAR-10 and CIFAR-100 when subjected to AutoAttack (AA).

NETWORK	METHOD	ADVERSARIAL ACCURACY (%)	
		CIFAR-10	CIFAR-100
DN121	PGD-AT	47.56	23.13
	PGD-AT + CLAT	**49.91**	**25.74**
WRN70-16	PGD-AT	54.32	28.25
	PGD-AT + CLAT	**57.64**	**30.98**
	(CARLINI & WAGNER, 2017)	66.1	-
	(CARLINI & WAGNER, 2017) + CLAT	**68.43**	-
RN50	PGD-AT	46.22	23.48
	PGD-AT + CLAT	**49.45**	**25.81**
	(MADRY ET AL., 2019)	49.25	-
	(MADRY ET AL., 2019) + CLAT	**51.64**	-
WRN34-10	PGD-AT	51.50	25.56
	PGD-AT + CLAT	**52.88**	**27.62**
	(CROCE & HEIN, 2020)	57.3	-
	(CROCE & HEIN, 2020) + CLAT	**59.98**	-
VGG19	PGD-AT	40.42	19.54
	PGD-AT + CLAT	**41.72**	**20.45**
RN18	PGD-AT	40.48	20.21
	PGD-AT + CLAT	**42.86**	**21.76**
	TWINS (LIU ET AL., 2023)	47.89	25.45
	TWINS + CLAT	**51.39**	**28.12**
	AUTOLORA (ZHANG ET AL., 2024)	48.95	27.48
	AUTOLORA + CLAT	**53.21**	**30.49**

Table 3: Comparative Analysis of Black-box Auto Attack (AA) Accuracy on CIFAR-10 and CIFAR-100. Model in each row is the attacker and each column the victim.

NETWORK	METHOD	CIFAR-10 ADV. ACC. (%)				CIFAR-100 ADV. ACC. (%)			
		DN121	RN50	VGG19	RN18	DN121	RN50	VGG19	RN18
DN121	PGD-AT	-	52.50	44.21	45.45	-	27.64	23.21	24.26
	PGD-AT + CLAT	-	55.83	47.53	48.92	-	29.89	26.71	26.93
RN50	PGD-AT	54.23	-	43.56	43.24	27.91	-	23.02	23.51
	PGD-AT + CLAT	56.72	-	46.21	47.01	30.11	-	26.34	25.86
VGG19	PGD-AT	55.32	55.45	-	46.72	27.84	28.15	-	24.20
	PGD-AT + CLAT	59.83	59.72	-	49.31	30.20	29.79	-	26.55
RN18	PGD-AT	53.21	51.73	43.21	-	29.31	26.75	22.91	-
	PGD-AT + CLAT	56.75	54.45	46.53	-	31.25	29.41	25.95	-

4.3.2 ABLATING ON CRITICAL LAYER SELECTION

The choice of critical layer selection is another important feature impacting the performance of CLAT. We begin by examining the effect of dynamic layer selection. Table 5 and Table 6 highlight that dynamic selection is crucial to CLAT's performance. Using the same layers throughout the process tends to cause overfitting and results in lower accuracies compared to the PGD-AT baseline.

To verify the significance of the selected critical layers, we compare CLAT with an alternative approach in which random layers are dynamically selected for fine-tuning instead of the critical layers. The results of this comparison are detailed in Table 7 and Table 12 (in **Appendix C**). The data demonstrates that selecting critical layers significantly enhances the model's adversarial robustness and clean accuracy. Moreover, Table 8 indicates near-identical critical layer selections within the same model even across diverse datasets. This evidence supports our assertion that the variation in layer criticality stems from inherent properties within the model architecture, wherein certain layers are predisposed to learning non-robust features.

Table 4: Comparative Analysis of Black-box PGD Accuracy on CIFAR-10 and CIFAR100. Model in each row is the attacker and each column the victim.

Network	Method	Cifar-10 Adv. Acc. (%)				Cifar-100 Adv. Acc. (%)			
		RN50	DN121	VGG19	RN18	RN50	DN121	VGG19	RN18
RN50	PGD-AT	-	74.83	68.01	67.44	-	46.82	40.55	40.10
	PGD-AT + CLAT	-	**76.45**	**71.25**	**70.12**	-	**48.49**	**44.34**	**43.91**
DN121	PGD-AT	72.24	-	69.53	68.38	44.45	-	40.63	41.22
	PGD-AT + CLAT	**74.55**	-	**71.78**	**70.56**	**46.78**	-	**43.62**	**42.88**
VGG19	PGD-AT	65.72	67.56	-	62.26	47.86	46.56	-	40.55
	PGD-AT + CLAT	**66.46**	**70.72**	-	**65.78**	**49.25**	**48.72**	-	**42.72**
RN18	PGD-AT	74.82	70.21	61.83	-	46.28	45.59	39.21	-
	PGD-AT + CLAT	**76.23**	**73.19**	**63.96**	-	**48.89**	**47.72**	**41.78**	-

Table 5: Adversarial accuracy under PGD attack: Comparison of PGD-AT, PGD-AT + CLAT, and PGD-AT + CLAT (Non-dynamic) on CIFAR-10 and CIFAR-100.

Table 6: Adversarial accuracy under Auto attack: Comparison of PGD-AT, PGD-AT + CLAT, and PGD-AT + CLAT (Non-dynamic) on CIFAR-10 and CIFAR-100.

Method	CIFAR-10		CIFAR-100	
	DN121	RN50	DN121	RN50
PGD-AT	58.15	56.35	31.76	33.01
CLAT	**60.60**	**59.54**	**33.23**	**36.23**
CLAT (ND)	57.01	54.22	30.34	32.98

Method	CIFAR-10		CIFAR-100	
	DN121	RN50	DN121	RN50
PGD-AT	47.56	46.22	23.13	23.48
CLAT	**49.91**	**49.45**	**25.74**	**25.81**
CLAT (ND)	47.12	46.08	22.26	22.91

Lastly, we ablate on the number of critical layers used in CLAT for fine-tuning. Fig. 3 illustrates the trade-off between adversarial accuracy and the quantity of critical layers selected. Allowing more layers to be fine-tuned enhances the model flexibility, which initially improves CLAT performance. However, fine-tuning more layers diminishes CLAT's effectiveness. This is likely due to the diversion of attention towards fine-tuning less-critical layers, detracting from more critical ones. This pattern highlights the crucial influence of specific layers on network robustness and suggests a need for deeper research to understand the roles and dynamics of individual layers influencing network robustness.

4.4 Overhead and stability analysis

The cost of optimizing the CLAT training objective in Eq. (9) is similar to that of the standard adversarial training given its min-max formulation. Here, we show that the computational overhead for determining critical indices is negligible. We verify in Table 10 that criticality indices can be stably computed with a single training batch as small as 10, with top-ranking layers consistent with those achieved with a larger batch. We further conducted over 1000 runs for each network to randomly select the data used for criticality estimation, where we find remarkable consistency in computed critical layers, differing in less than 5% of cases, typically involving only one layer change among the top five critical layers. The stability means we can use a mere **0.0002%** of the training data for

Table 7: Ablating CLAT Layer choices on CIFAR-10: The columns present PGD-10 and Auto Attack (AA) evaluation adversarial accuracies for models trained with CLAT, where layers are selected based on criticality or randomly.

Network	Critical Layers			Random Layers		
	Clean Acc.	PGD-10	AA	Clean Acc.	PGD-10	AA
DN121	81.03	60.60	49.91	78.85	51.35	39.81
RN50	83.78	59.54	49.45	79.01	51.44	40.29
RN18	83.89	55.37	42.86	78.02	51.03	33.50

Table 8: Top-5 criticality indices by model and dataset. Layers used in CLAT are bolded.

MODEL	CIFAR10	CIFAR100
DN121	**39, 14, 1, 3, 88**	**39, 15, 1, 2, 91**
WRN70-16	**4, 17, 1, 59**, 62	**3, 17, 2, 59**, 61
RN50	**34, 41, 48**, 3, 36	**34, 43, 45**, 6, 32
WRN34-10	**26, 1** 30, 3, 28	**26, 2**, 30, 3, 27
VGG19	**9**, 11, 5, 3, 1	**8**, 13, 5, 3, 1
RN18	**11**, 10, 4, 2, 12	**12**, 9, 5, 2, 13

Table 9: Trainable Parameters during CLAT in Various Networks

NETWORK	TRAINABLE PARAMS		% USED
	TOTAL	CLAT	
DN121	6.96M	217K	3.1%
WRN70-16	267M	8.29M	3.0%
RN50	23.7M	823K	3.4%
WRN34-10	46.16M	1.24M	2.7%
RN18	11.2M	590K	5.2%
VGG19	39.3M	236K	0.6%

Figure 3: Comparative analysis on CLAT performance/PGD-10 adversarial accuracy with respect to number of critical layers used during CLAT

criticality estimation every 10 epochs, which introduces a neglectable **0.4%** additional time to the standard adversarial training process as measured in Table 10.

5 CONCLUSIONS

In this work, we introduce CLAT, an innovative adversarial training approach that addresses robust overfitting issues by fine-tuning only the critical layers vulnerable to adversarial perturbations. This method not only emphasizes layer-specific interventions for enhanced network robustness but also sheds light on the commonality in non-robust features captured by these layers, offering a targeted and effective defense strategy. Our results reveal that CLAT effectively selects less than 4% critical trainable variables to achieve significant improvements in clean accuracy and adversarial robustness across diverse network architectures and baseline adversarial training methods. We limit the scope of this work to improving the empirical robustness of the model by utilizing the critical layers. In this sense, open questions remain on why these specific layers become critical, whether they can be identified more effectively, and whether the issues can be resolved with architectural or training scheme changes. We leave a more theoretical understanding of these questions as future work.

Table 10: DenseNet-121 critical layers identified with different amount of data. Time taken to compute critical layers evaluated on TITAN RTX GPU. As a reference, 1 PGD-AT epoch takes 67s.

BATCH SIZE	CIFAR10		CIFAR100	
	CRITICAL LAYERS	TIME (S)	CRITICAL LAYERS	TIME(S)
10	39, 14, 1, 3, 90	2.64	39, 15, 1, 2, 91	2.82
30	39, 14, 1, 3, 88	2.72	39, 15, 1, 2, 88	2.91
50	39, 14, 1, 3, 89	2.83	39, 15, 1, 3, 91	3.14
100	39, 14, 1, 3, 88	3.15	39, 15, 1, 2, 91	3.54

REFERENCES

Sidra Aleem, Julia Dietlmeier, Eric Arazo, and Suzanne Little. Convlora and adabn based domain adaptation via self-training. *arXiv preprint arXiv:2402.04964*, 2024.

Maksym Andriushchenko and Nicolas Flammarion. Understanding and improving fast adversarial training, 2020.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples, 2018.

Tao Bai, Jinqi Luo, Jun Zhao, Bihan Wen, and Qian Wang. Recent advances in adversarial training for adversarial robustness, 2021.

Yatong Bai, Brendon G. Anderson, Aerin Kim, and Somayeh Sojoudi. Improving the accuracy-robustness trade-off of classifiers via adaptive smoothing, 2024.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks, 2017.

Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, Percy Liang, and John C. Duchi. Unlabeled data improves adversarial robustness, 2022.

Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks, 2020.

Francesco Croce, Maksym Andriushchenko, Vikash Sehwag, Nicolas Flammarion, Mung Chiang, Prateek Mittal, and Matthias Hein. Robustbench: a standardized adversarial robustness benchmark. *CoRR*, abs/2010.09670, 2020. URL https://arxiv.org/abs/2010.09670.

Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks, 2016a.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016b.

Dorjan Hitaj, Giulio Pagnotta, Iacopo Masi, and Luigi V. Mancini. Evaluating the robustness of geometry-aware instance-reweighted adversarial training, 2021.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Joong-Won Hwang, Youngwan Lee, Sungchan Oh, and Yuseok Bae. Adversarial training with stochastic weight average, 2020. URL https://arxiv.org/abs/2009.10526.

Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and Aleksander Madry. Adversarial examples are not bugs, they are features. *Advances in neural information processing systems*, 32, 2019.

Nathan Inkawhich, Wei Wen, Hai (Helen) Li, and Yiran Chen. Feature space perturbations yield more transferable adversarial examples. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Nathan Inkawhich, Kevin Liang, Binghui Wang, Matthew Inkawhich, Lawrence Carin, and Yiran Chen. Perturbing across the feature hierarchy to improve standard and strict blackbox attack transferability. *Advances in Neural Information Processing Systems*, 33:20791–20801, 2020.

Adel Javanmard, Mahdi Soltanolkotabi, and Hamed Hassani. Precise tradeoffs in adversarial training for linear regression, 2020.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. 2009.

Lin Li and Michael Spratling. Data augmentation alone can improve adversarial training, 2023. URL https://arxiv.org/abs/2301.09879.

Ziquan Liu, Yi Xu, Xiangyang Ji, and Antoni B. Chan. Twins: A fine-tuning framework for improved transferability of adversarial robustness and generalization, 2023. URL https://arxiv.org/abs/2303.11135.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks, 2019.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Jonathan Uesato, and Pascal Frossard. Robustness via curvature regularization, and vice versa. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9078–9086, 2019.

Tianyu Pang, Min Lin, Xiao Yang, Jun Zhu, and Shuicheng Yan. Robustness and accuracy could be reconcilable by (proper) definition, 2022.

ShengYun Peng, Weilin Xu, Cory Cornelius, Matthew Hull, Kevin Li, Rahul Duggal, Mansi Phute, Jason Martin, and Duen Horng Chau. Robust principles: Architectural design principles for adversarially robust cnns, 2023.

Aditi Raghunathan, Sang Michael Xie, Fanny Yang, John C Duchi, and Percy Liang. Adversarial training can hurt generalization. *arXiv preprint arXiv:1906.06032*, 2019.

Leslie Rice, Eric Wong, and J. Zico Kolter. Overfitting in adversarially robust deep learning, 2020.

Ludwig Schmidt, Shibani Santurkar, Dimitris Tsipras, Kunal Talwar, and Aleksander Madry. Adversarially robust generalization requires more data, 2018.

Ali Shafahi, Mahyar Najibi, Amin Ghiasi, Zheng Xu, John Dickerson, Christoph Studer, Larry S. Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free!, 2019.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *3rd International Conference on Learning Representations, ICLR 2015 - Conference Track Proceedings*, 2015.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks, 2014.

Yisen Wang, Difan Zou, Jinfeng Yi, James Bailey, Xingjun Ma, and Quanquan Gu. Improving adversarial robustness requires revisiting misclassified examples. In *International conference on learning representations*, 2019.

Yisen Wang, Difan Zou, Jinfeng Yi, James Bailey, Xingjun Ma, and Quanquan Gu. Improving adversarial robustness requires revisiting misclassified examples. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rklOg6EFwS.

Zekai Wang, Tianyu Pang, Chao Du, Min Lin, Weiwei Liu, and Shuicheng Yan. Better diffusion models further improve adversarial training, 2023. URL https://arxiv.org/abs/2302.04638.

Eric Wong, Leslie Rice, and J. Zico Kolter. Fast is better than free: Revisiting adversarial training, 2020.

Dongxian Wu, Shu tao Xia, and Yisen Wang. Adversarial weight perturbation helps robust generalization, 2020a. URL https://arxiv.org/abs/2004.05884.

Dongxian Wu, Shu tao Xia, and Yisen Wang. Adversarial weight perturbation helps robust generalization, 2020b.

Cihang Xie, Mingxing Tan, Boqing Gong, Jiang Wang, Alan Yuille, and Quoc V. Le. Adversarial examples improve image recognition, 2020.

Huanrui Yang, Jingyang Zhang, Hongliang Dong, Nathan Inkawhich, Andrew Gardner, Andrew Touchet, Wesley Wilkes, Heath Berry, and Hai Li. Dverge: diversifying vulnerabilities for enhanced robust generation of ensembles. *Advances in Neural Information Processing Systems*, 33:5505–5515, 2020.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks, 2017.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P. Xing, Laurent El Ghaoui, and Michael I. Jordan. Theoretically principled trade-off between robustness and accuracy, 2019.

Ruiyi Zhang, Rushi Qiang, Sai Ashish Somayajula, and Pengtao Xie. Autolora: Automatically tuning matrix ranks in low-rank adaptation based on meta learning, 2024. URL `https://arxiv.org/abs/2403.09113`.

Kaijie Zhu, Jindong Wang, Xixu Hu, Xing Xie, and Ge Yang. Improving generalization of adversarial training via robust critical fine-tuning, 2023.

A   PSEUDOCODE OF CLAT

To better facilitate an understanding of the CLAT process, we illustrate the pseudocode of the dynamic critical layer identification process and the criticality-targeted fine-tuning process in **Algorithm 1**. Only the selected critical layers are being fine-tuned while all the other layers are frozen.

Algorithm 1 CLAT Algorithm

1: **Input:** Dataset $\mathcal{D}$, pre-trained model F, batch size bs, total epochs N.

2: **for** $epoch = 1$ **to** N **do**
3:     **if** $epoch\%10 == 1$ **then**
4:         # Find critical layers
5:         $x \leftarrow$ Batch of training data in $\mathcal{D}$
6:         $x + \delta \leftarrow$ PGD attack against F
7:         Compute $\mathcal{W}_\epsilon(F_i)$ for all layers with Eq. (5)
8:         Compute $\mathcal{C}_{f_i}$ for all layers with Eq. (6)
9:         Critical layers $\mathcal{S} \leftarrow TopK(\mathcal{C}_{f_i})$
10:     # fine-tune critical layers
11:     $minibatches \leftarrow CreateMinibatches(\mathcal{D}, bs)$
12:     **for** x, y in $minibatches$ **do**
13:         Perturbation $\delta \leftarrow$ Eq. (8) inner maximization
14:         $\mathcal{L}_C(f_\mathcal{S}) \leftarrow$ Eq. (8)
15:         Weight update $w[\mathcal{S}]$ with Eq. (9)

B   ADDITIONAL EXPERIMENT RESULTS

We further compare the CLAT model robustness with the robustness of the SAT model against white-box attacks of various strengths. As illustrated in Fig. 4, though both models are only trained against an attack of one strength ($\epsilon = 0.03$), the improved robustness of CLAT is consistent across the full spectrum of attack strengths. This shows that CLAT is not overfitting to the specific attack strength used in training.

Figure 4: White-box adversarial accuracy (y-axis) on CIFAR-10 for models trained with CLAT (red) and pgd-at (blue), against PGD attacks of varying strengths (x-axis)

C   ADDITIONAL ABLATION STUDY

C.1   CLAT ON PRETRAINED CLEAN MODEL

Besides the discussion on performing CLAT after adversarial pretraining in Section 4.3.1, Table 11 details the performance of CLAT on clean pretrained models. Although the adversarial accuracies of clean pretrained models are relatively low compared to those of adversarially trained models, CLAT demonstrates its capability to facilitate adversarial fine-tuning on clean models effectively to some extent. This is a novel achievement, showcasing the algorithm's versatility.

Table 11: Adversarial and clean accuracies for performing CLAT on various PyTorch pretrained models on the CIFAR-10 dataset.

MODEL	ADV. ACC.	CLEAN ACC.
DN-121	39.21%	80.89%
WRN70-16	42.1%	83.35%
RN-50	35.67%	78.23%
WRN34-10	40.1%	81.78%
VGG-19	32.67%	75.05%
RN-18	34.45%	76.51%

C.2 ADDITIONAL RESULTS ON LAYER SELECTION

Here in Table 12, we provide additional results contrasting CLAT with an alternative approach where random layers are dynamically selected for fine-tuning instead of the critical layers on the CIFAR-100 dataset.

Table 12: Ablating CLAT layer choices on CIFAR-100: The columns present PGD-10 and AutoAttack (AA) evaluation adversarial accuracies for models trained with CLAT, where layers are selected based on criticality or randomly.

NETWORK	CRITICAL LAYERS			RANDOM LAYERS		
	CLEAN ACC.	PGD-10	AA	CLEAN ACC.	PGD-10	AA
DN121	58.79	33.23	25.74	50.45	25.48	20.21
RN50	61.88	36.23	25.81	52.20	25.51	20.45
RN18	50.98	28.41	20.45	43.15	20.24	15.89

D REBUTTAL EXPERIMENTS

We thank the constructive feedback from all reviewers. We consolidate all additional experimental results suggested by the reviewers in this appendix section. We will integrate these results and our discussions in the rebuttal text into the finalized version.

D.1 FULL TRAINING CURVES

Figure 5: White-box PGD-10 adversarial accuracy (y-axis) on CIFAR-10 for WRN34-10 models trained with CLAT fine-tuning starting at Epoch 70 (red), CLAT from scratch (orange), and PGD-AT (blue). The learning rate decays to 0 by Epoch 150.

D.2 REDUCED LEARNING RATE PERFORMANCE

See Fig. 6.

Figure 6: White-box accuracies (y-axis) for WRN34-10 on CIFAR-10 for models trained with the original learning rate multiplied by 0.1 at Epoch 70, using CLAT (green) and PGD-AT (red), compared to normal PGD-AT learning rate (purple).

D.3 CRITICAL INDEX VARIATION OVER TIME

Please see Table 13.

Table 13: Critical layers identified at different epochs for various networks.

NETWORK	EP. 70	EP. 80	EP. 90
DN121	[39, 14, 1, 3, 88]	[38, 1, 5, 88, 15]	[1, 5, 88, 2, 15]
RN50	[34, 41, 48]	[48, 3, 36]	[36, 2, 40]
RN18	[11]	[11]	[4]

D.4 CLEAN ACCURACY AND CRITICAL LAYER SELECTION

Please see Fig. 7.

Figure 7: Comparative analysis on CLAT performance clean accuracies with respect to the number of critical layers used during CLAT.

D.5 ABLATION STUDY: DYNAMIC AND FIXED CRITICAL INDICES

Please see Table 14.

Table 14: Comparison of CIFAR-100 Clean and Adversarial Accuracies (PGD-10) on Different Networks with Fixed and Dynamic Layers for CLAT.

Model		Fixed Layers	Dynamic Layers
DN121	Clean	53.21	**58.79**
	Adv	39.45	**44.12**
RN50	Clean	55.72	**61.88**
	Adv	31.89	**36.23**
WRN34-10	Clean	56.45	**62.38**
	Adv	28.56	**32.05**

D.6 PERFORMANCE ON OTHER DATASETS

D.6.1 IMAGENETTE

See Table 15.

Table 15: Comparative performance of CLAT across various networks on Imagenette. Robustness is evaluated with white-box PGD-10 and Auto Attack.

Model	Method	Clean (%)	PGD-10 (%)	AA (%)
DN121	PGD-AT	83.40	61.78	51.23
	PGD-AT + CLAT	**86.91**	**65.45**	**54.82**
WRN70-16	PGD-AT	90.20	67.96	58.91
	PGD-AT + CLAT	**93.52**	**72.39**	**61.43**
RN50	PGD-AT	84.02	62.10	50.45
	PGD-AT + CLAT	**87.11**	**64.89**	**54.31**
WRN34-10	PGD-AT	90.45	65.45	56.31
	PGD-AT + CLAT	**93.21**	**69.82**	**60.04**
VGG19	PGD-AT	85.45	56.71	46.53
	PGD-AT + CLAT	**89.72**	**59.45**	**51.22**
RN18	PGD-AT	83.01	60.04	49.01
	PGD-AT + CLAT	**86.42**	**62.91**	**51.23**

D.6.2 IMAGENET

Please see Table 16.

Table 16: Clean and Adversarial Accuracies (PGD-10) performance comparison on ImageNet.

Model	Method	Clean	Adv
DN121	PGD-AT	63.25	32.56
	PGD-AT + CLAT	**66.10**	**35.48**
RN50	PGD-AT	65.88	33.18
	PGD-AT + CLAT	**67.12**	**36.91**
WRN34-10	PGD-AT	64.31	31.08
	PGD-AT + CLAT	**66.12**	**33.59**

D.7 ROBUSTNESS AGAINST OTHER ATTACKS

We report that performance on varying strengths of PGD-10 in Appendix B. Table 17 highlights the robustness against stronger white-box attacks, including those not limited to ℓ_∞-bounded constraints.

Table 17: Adversarial accuracies across various attacks on CIFAR-10, highlighting the difference between models trained with the baseline and those utilizing CLAT. Positive blue values indicate the improvement in performance achieved with CLAT.

Attack	Method	DN121 (%)	WRN34-10 (%)
FAB	PGD-AT	44.80	40.12
	PGD-AT + CLAT	+3.70	+5.03
StAdv	PGD-AT	48.50	45.15
	PGD-AT + CLAT	+0.91	+1.89
Pixle	PGD-AT	10.40	9.50
	PGD-AT + CLAT	+2.21	+1.90
PGD-ℓ_2 ($\epsilon = 0.03$)	PGD-AT	61.79	60.25
	PGD-AT + CLAT	+1.92	+1.45
PGD-ℓ_∞ ($\epsilon = 0.03$, 50 steps)	PGD-AT	57.01	54.01
	PGD-AT + CLAT	+1.92	+2.03
PGD-ℓ_∞ ($\epsilon = 0.03$, 100 steps)	PGD-AT	56.89	53.12
	PGD-AT + CLAT	+1.63	+1.89

D.8   ADDITIONAL PERFORMANCE COMPARISONS TO BASELINES

D.8.1   STOCHASTIC WEIGHT AVERAGING AND ADVERSARIAL WEIGHT PERTURBATION

Table 18 shows results when CLAT is augmented with SWA (Hwang et al., 2020) and AWP (Wu et al., 2020a) techniques. Omitted values are not reported in the original work.

Table 18: PGD-10 Adversarial Accuracies on CIFAR-10 and CIFAR-100 for PreAct RN-18 and WRN34-10 compared to baselines.

Network	Method	CIFAR-10	CIFAR-100
PreAct RN-18	AWP (Wu et al., 2020a)	55.39	30.71
	AWP + CLAT	**58.41**	**33.97**
	SWAAT (Hwang et al., 2020)	58.32	28.43
	SWAAT + CLAT	**60.76**	**30.74**
WRN34-10	AWP	58.10	-
	AWP + CLAT	**60.89**	-
	SWAAT	61.45	31.97
	SWAAT + CLAT	**63.82**	**34.55**

D.8.2   DATA AUGMENTATION TECHNIQUES

Please see Table 19

Table 19: Adversarial accuracies on CIFAR-10 for PreAct RN-18 (using PGD-10) and WRN70-16 (using Auto Attack).

Network	Method	Adv. Accuracy (%)
PreAct RN-18	Data Aug (weak) (Li & Spratling, 2023)	50.34
	Data Aug (weak) + CLAT	**54.01**
	Data Aug (strong)	49.99
	Data Aug (strong) + CLAT	**52.37**
WRN70-16	Wang et al. (2023)	70.69
	Wang et al. (2023) + CLAT	**72.34**