Implicit regularization in Heavy-ball momentum accelerated stochastic gradient descent

Abstract

It is well known that the finite step-size (h) in Gradient Descent (GD) implicitly regularizes solutions to flatter minima. A natural question to ask is *"Does the momentum parameter β play a role in implicit regularization in Heavy-ball (H.B) momentum accelerated gradient descent (GD+M)?"* To answer this question, first, we show that the trajectory traced by discrete H.B momentum update (GD+M) is $O(h^2)$ close to a continuous trajectory induced by a modified loss, which consists of an original loss and an implicit regularizer. This implicit regularizer for (GD+M) is indeed stronger than that of (GD) by factor of $\left(\frac{1+\beta}{1-\beta}\right)$, thus explaining why (GD+M) shows better generalization performance and higher test accuracy than (GD). Furthermore, we extend our analysis to stochastic version of gradient descent with momentum (SGD+M) and propose a deterministic continuous trajectory that is $O(h^2)$ close to the discrete update of (SGD+M) in a strong approximation sense. We explore the implicit regularization in (SGD+M) and (GD+M) through a series of experiments validating our theory.

1 Introduction

Deep neural networks (NN) have led to huge empirical successes in recent years across a wide variety of tasks, ranging from computer vision, natural language processing, autonomous driving to medical imaging, astronomy and physics (Bengio & LeCun, 2007; Hinton et al., 2006; Goodfellow et al., 2016). Most deep learning problems are in essence solving an over-parameterized, large-scale non-convex optimization problem. A mysterious phenomenon about NN that attracted much attention in the past few years is why NN generalizes so well. Indeed, even with extremely over-parametrized model, NNs rarely show a sign of over-fitting (Neyshabur, 2017). Thus far, studies along this line have successfully revealed many forms of implicit regularization that potentially lead to good generalization when gradient descent (GD) or stochastic gradient descent (SGD) algorithms are used for training, including norm penalty (Soudry et al., 2018), implicit gradient regularization (Barrett & Dherin, 2020), and implicit Hessian regularization (Orvieto et al., 2022a;b) through noise injection.

In contrast, the family of momentum accelerated gradient descent methods including Polyak's Heavy-ball momentum (Polyak, 1964), Nesterov's momentum (Sutskever et al., 2013), RMSProp (Tieleman et al., 2012), and Adam (Kingma & Ba, 2014), albeit being powerful alternatives to SGD with faster convergence rates, are far from well-understood in the aspect of implicit regularization. In this paper, we analyze the implicit gradient regularization in the Heavy-ball momentum accelerated SGD (SGD+M) algorithm with the goal of gaining more theoretical insights on how momentum affects the generalization performance of SGD, and why it tends to introduce a variance reduction effect whose strength increases with the momentum parameter.

2 Related literature

It has been well studied that gradient based optimization implicitly biases solutions towards models of lower complexity which encourages better generalization. For example, in an over-parameterized

quadratic model, gradient descent with a near-zero initialization implicitly biases solutions towards having a small nuclear norm (Arora et al., 2019; Gunasekar et al., 2017; Razin & Cohen, 2020), in a least-squares regression problem, gradient descent solutions with 0 initial guess are biased towards having a minimum ℓ_2 norm (Soudry et al., 2018; Neyshabur et al., 2014; Ji & Telgarsky, 2019; Poggio et al., 2020). Similarly, in a linear classification problem with separable data, the solution of gradient descent is biased towards the max-margin (i.e., the minimum ℓ_2 norm) solution (Soudry et al., 2018). However in (Vardi & Shamir, 2021), the authors showed that these norm-based regularization results proved on simple settings might not extend to non-linear neural networks.

The first general implicit regularization for GD discovered for all non-linear models (including neural networks) is the Implicit Gradient Regularization (IGR) (Barrett & Dherin, 2020). It is shown that the learning rate in gradient descent (GD) penalizes the second moment of the loss gradients, hence encouraging discovery of flatter optima. Flatter optima usually give higher test-accuracy and are more robust to parameter perturbations (Barrett & Dherin, 2020).

Implicit Gradient Regularization was also discovered for Stochastic Gradient Descent (SGD) (Smith et al., 2021), as one (but perhaps not the only one) reason for its good generalization. SGD is believed to also benefit from its stochasticity, which might act as a type of noise injection to enhance the performance. Indeed, it is shown in (Wu et al., 2020) that, by injecting noise to the gradients, full-batch gradient descent will be able to match the performance of SGD with small batch sizes. Besides injecting noise to the gradients, many other ways of noise injections have been discovered to have an implicit regularization effect on the model parameters, including noise injection to the model space (Orvieto et al., 2022b) and those to the network activations (Camuto et al., 2020). However, how these different types of regularization cooperatively affect generalization is still quite unclear.

The effect of generalization in momentum accelerated gradient descent has been studied much less. Recently, in (Wang et al., 2021), the authors analyzed the implicit regularization in momentum (GD+M) based on a linear classification problem with separable data and show that (GD+M) converges to the L_2 max-margin solution. Although this is one of the first proposed forms of implicit regularization for momentum based methods, it fails to provide an insight on the implicit regularization for momentum in non-linear neural networks.

Recently, (Jelassi & Li, 2022) has shown that the (GD+M) increases the generalization capacity of networks in some special settings (i.e., a simple binary classification problem with a two layer network and part of the input features are much weaker than the rest), but it is unclear to which extent the insight obtained from this special setting can be extended to practical NN models.

To the best of our knowledge, no prior work has derived an implicit regularization for (SGD+M) for general non-linear neural networks.

3 IMPLICIT GRADIENT REGULARIZATION FOR GRADIENT DESCENT AND ITS RELATION TO GENERALIZATION

We briefly review the IGR defined for GD (Barrett & Dherin, 2020) which our analysis will be based on. Let $E(\mathbf{x})$ be the loss function defined over the parameters space $\mathbf{x} \in \mathbb{R}^p$ of the neural network. Gradient descent iterates take a discrete step (h) opposite to the gradient of the loss at the current iterate

$$\mathbf{x}^{k+1} = \mathbf{x}^k - h\nabla E(\mathbf{x}^k). \tag{1}$$

With an infinitesimal step-size $(h \to 0)$, the trajectory of GD converges to that of the first order ODE

$$\mathbf{x}'(t) = -\nabla E(\mathbf{x}(t)) \tag{2}$$

known as the gradient flow. But for a finite (albeit small) step size h, the updates of GD steps off the path of gradient flow and follow more closely the path of a modified flow:

$$\mathbf{x}'(t) = -\nabla \hat{E}(\mathbf{x}(t)), \qquad \text{where } \hat{E}(\mathbf{x}) = E(\mathbf{x}) + \frac{h}{4}\|\nabla E(\mathbf{x})\|^2. \tag{3}$$

More specifically, it is shown (Barrett & Dherin, 2020) through the classical backward analysis in numerical ODE that when GD and the two gradient flows 2 and 3 all set off from the same point $\mathbf{x}^k$, the next gradient update $\mathbf{x}^{k+1}$ is $O(h^2)$ close to the original gradient flow (equation 2) evaluated at the next time point $t_{k+1} = h + t_k$, but is $O(h^3)$ close to the modified flow (equation 3) evaluated at t_{k+1}. This immediately implies that if all three set off from the same initial point $\mathbf{x}^0$, then the GD update $\mathbf{x}^k$ at a fixed t_0 (i.e., $k = \lfloor \frac{t_0}{h} \rfloor$) is only $O(h)$ close to the original flow but $O(h^2)$ close to the modified flow. Based on this observation, the authors defined the extra term $\frac{h}{4}\|\nabla E(\mathbf{x})\|^2$ in the modified flow as the IGR term and concluded by stating that it guides the solutions to flatter minima in a highly non-convex landscape.

To justify why minimizing $\|\nabla E(\mathbf{x})\|^2$ is a good idea and why it encourages flat minimizers (which seems to be missing from the original paper), we borrow an argument from (Foret et al., 2020) that was originally developed for a different purpose.

Due to the PAC-Bayes analysis (Neyshabur, 2017), a simplified generalization bound for NN derived under some technical conditions can be stated as (Foret et al., 2020)

$$\mathcal{L}_{\mathcal{D}}(\mathbf{x}) \leq \max_{\|\epsilon\| \leq \rho} \mathcal{L}_{\mathcal{S}}(\mathbf{x} + \epsilon) + \hat{h}\left(\frac{\|\mathbf{x}\|^2}{\rho}\right), \text{ for any } \rho > 0,$$

where $\mathcal{L}_{\mathcal{D}}$ is the population loss (i.e., the generalization error), $\mathcal{L}_{\mathcal{S}}$ is the empirical/training loss, and $\hat{h} : \mathbb{R}_+ \to \mathbb{R}_+$ is some strictly increasing function. One can try to minimize this upper bound in order to minimize the generalization error $\mathcal{L}_{\mathcal{D}}$. The term $\hat{h}\left(\frac{\|\mathbf{x}\|^2}{\rho}\right)$ in the upper bound can be controlled by activating a weight decay penalty during training, and the first term in the bound is usually written into

$$\max_{\|\epsilon\| \leq \rho} \mathcal{L}_{\mathcal{S}}(\mathbf{x} + \epsilon) = \underbrace{\max_{\|\epsilon\| \leq \rho} \left(\mathcal{L}_{\mathcal{S}}(\mathbf{x} + \epsilon) - \mathcal{L}_{\mathcal{S}}(\mathbf{x})\right)}_{\text{sharpness}} + \underbrace{\mathcal{L}_{\mathcal{S}}(\mathbf{x})}_{\text{training loss}}$$

which consists of the training loss and an extra term called sharpness, minimizing which will help with generalization. Since directly minimizing the sharpness is difficult, one can then use the following first-order Taylor approximation

$$\max_{\|\epsilon\| \leq \rho} \left(\mathcal{L}_{\mathcal{S}}(\mathbf{x} + \epsilon) - \mathcal{L}_{\mathcal{S}}(\mathbf{x})\right) \approx \max_{\|\epsilon\| \leq \rho} \epsilon^T \nabla \mathcal{L}_{\mathcal{S}}(\mathbf{x}) = \rho \|\nabla \mathcal{L}_{\mathcal{S}}(\mathbf{x})\|.$$

Using our notation, $\nabla \mathcal{L}_{\mathcal{S}}(\mathbf{x})$ is $\nabla E(\mathbf{x})$, so the sharpness is approximately proportional to $\|\nabla E\|$ which is the square root of the IGR term.

4 IMPLICIT GRADIENT REGULARIZATION FOR HEAVY BALL ACCELERATED GRADIENT DESCENT

The main mathematical challenge in studying the IGR in momentum updates is that we now need to perform global error analysis instead of the local backward analysis, as the momentum updates utilizes the entire update history.

The IGR for Heavy-ball momentum was previously analyzed in (Kovachki & Stuart, 2021) through studying its relationship with the damped second order Hamiltonian dynamic

$$m\mathbf{x}'(t) + \gamma\mathbf{x}''(t) + \nabla E(\mathbf{x}(t)) = 0$$

which has been well-known as the underlying ODE for the momentum updates. However, only $O(h)$ closeness is proven between the momentum updates and this ODE trajectory under general step size assumptions [1], which is not enough since the implicit regularization term $\frac{h}{4}\|\nabla E\|^2$ itself is of order $O(h)$. In addition, this approach is difficult to be applied to the stochastic setting.

---

[1] An $O(h^2)$ closeness is proven under very stringent conditions on the learning rate, which excludes the interesting regime where momentum has an advantage over plain GD in terms of the convergence rate and stability

In this paper, we circumvent the use of the second order ODE (as it only gives $O(h)$ closeness) and directly obtain a continuous path that is $O(h^2)$-close to the momentum update for both GD and SGD. This is achieved by linking the momentum updates with a first order piecewise ODE, proving that the ODE has a piece-wise differentiable trajectory that is $O(h^2)$-close to the momentum updates, and then using its trajectory to study the IGR. The detailed argument can be found in the appendix. Here we provide the final mathematical formula for the implicit regularization of (Heavy-Ball) momentum based gradient descent method (IGR-M).

Theorem 4.1. *((IGR-M): Let the loss for the full-batch gradient E be smooth and 4-times differentiable, then the (GD+M) updates*

$$\mathbf{x}^{k+1} = \mathbf{x}^k - h\nabla E(\mathbf{x}^k) + \beta(\mathbf{x}^k - \mathbf{x}^{k-1}) \quad \forall k = 1, 2, ..., n$$

are $O(h^2)$ close to the flow of the continuous trajectory of the piecewise first-order ODE

$$\widetilde{\mathbf{x}}'(t) = -\frac{1 - \beta^{k+1}}{1 - \beta}\nabla E(\widetilde{\mathbf{x}}(t)) - \frac{h\gamma(1 + \beta)}{2(1 - \beta)^3}\nabla^2 E(\widetilde{\mathbf{x}}(t))\nabla E(\widetilde{\mathbf{x}}(t)), t \in [t_k, t_{k+1}] \qquad (4)$$

where $t_k = kh$ and

$$\gamma = (1 - \beta^{2k+2}) - 4(k + 1)\beta^{k+1}\frac{(1 - \beta)}{(1 + \beta)}.$$

Since β^k quickly decays to 0 as k grows, for a sufficiently large iteration k, equation 4 reduces to:

$$\widetilde{\mathbf{x}}'(t) = -\frac{1}{1 - \beta}\nabla \hat{E}(\widetilde{\mathbf{x}}(t)), \quad t \in [0, T] \qquad (5)$$

driven by the modified loss $\hat{E}(\widetilde{\mathbf{x}}(t)) := E(\widetilde{\mathbf{x}}(t)) + \frac{(1+\beta)h}{4(1-\beta)^2}\|\nabla E(\widetilde{\mathbf{x}}(t))\|_2^2$. More specifically, for a fixed time T, there exists a constant C, such that for any learning rate $0 < h < T$, we have

$$\|\widetilde{\mathbf{x}}(t_k) - \mathbf{x}^k\|_2 \le Ch^2, \ t_k = kh, \quad k = 1, 2, ..., \lfloor\frac{T}{h}\rfloor. \qquad (6)$$

Comparing the continuous trajectory traced with 5 and the one without momentum 3, we immediately have a few important observations:

Remark 4.1. Ignoring the $O(h)$ terms in 5 and 3, we see that the momentum trajectory is driven by a force that is $\frac{1}{1-\beta}$ times as large as that for GD. Therefore, using the same learning rate, (GD+M) is expected to converge $\frac{1}{1-\beta}$ times as fast as GD. Alternatively, (GD+M) with a learning rate h has roughly the same convergence rate as GD with a learning rate $\frac{h}{1-\beta}$. From now on, we call $\frac{h}{1-\beta}$ the effective learning rate of (GD+M).

Remark 4.2. In terms of the IGR, we can see that adding the momentum amplifies the strength of the IGR (the coefficient in front of the IGR term increased from the $\frac{h}{4}$ in (GD) to the $\frac{h}{4}\frac{1+\beta}{(1-\beta)^2}$ in (GD+M). Even when letting the effective learning rates of the two methods equal (i.e., $\frac{h_{GD+M}}{1-\beta} = h_{GD}$), the implicit regularization in (GD+M) is still $\frac{1+\beta}{1-\beta}$ times stronger.

Remark 4.3. The IGR for (GD+M) reduces to the IGR for GD when $\beta = 0$.

With an additional momentum parameter β, the strength of the implicit regularizer increases by a factor of $\frac{1+\beta}{1-\beta}$. Hence for increasing values of momentum parameter β, the strength of the regularization increases, thus preferring more flatter trajectories through its descent.

4.1 IGR-M in a 2D Linear Model

We first show the impact of IGR-M in a very simple setting that minimizes a loss function with two learnable parameters, i.e., $(\hat{w}_1, \hat{w}_2) = \arg\min_{w_1, w_2} E(w_1, w_2)$ where $E(w_1, w_2) = \frac{1}{2}(y - w_1w_2x)^2$. Here x, y, w_1, w_2 are all scalars and mimics a simple scalar linear two-layer network. For a given scalar (x, y), the global minima of $E(w_1, w_2)$ are all the points on the curve $w_1w_2 = \frac{y}{x}$. The continuous gradient flow of the parameters are $w_1'(t) = -\frac{\partial E}{\partial w_1}$ and $w_2'(t) = -\frac{\partial E}{\partial w_2}$.

The IGR for this problem is $\frac{h_{GD}}{4}\|\nabla E\|_2^2 = \frac{h_{GD}}{4}(w_1^2 + w_2^2)E$, which will regularize the trajectory to find minima with a smaller value $(w_1^2 + w_2^2)$ (towards the cross) among all the global minima lying on $w_1 w_2 = \frac{y}{x}$. We intentionally chose the same experiment as in (Barrett & Dherin, 2020) to compare the effect of implicit regularization for (GD) and (GD+M).

For a fair comparison between (GD) and (GD+M), we set the effective learning rates to be the same, i.e, $h_{GD} = \frac{h_{GD+M}}{1-\beta}$ as in Remark 4.1. With the same initialization $(w_1^0, w_2^0) = (2.8, 3.4)$ we explore and track the path of four trajectories with (h_{GD+M}, β) being $(5 \times 10^{-3}, 0.5)$, $(2 \times 10^{-3}, 0.8)$, $(10^{-3}, 0.9)$ and $(10^{-2}, 0.0)$. In all the four cases, the effective learning rates are the same, i.e, $\frac{h_{GD+M}}{(1-\beta)} = h_{GD} = 10^{-2}$. We make the following observations: a) For all the four trajectories, the converged weight parameters $w^* = (w_1^*, w_2^*)$ lie on the global minima curve. b) With increasing value of β, the converged solutions have decreasing value of ℓ_2 norm (or increasing

Figure 1: Implicit regularization for (GD+M) is stronger than that of (GD) for the same effective learning rate $\frac{h}{(1-\beta)}$. As β increases the optima seems to find solution with a lower norm. This confirms Remark-2 that the strength of implicit regularization increases with β.

strength of implicit regularization), i.e, $\|w^*_{(10^{-3},0.9)}\|_2 < \|w^*_{(2\times10^{-3},0.8)}\|_2 < \|w^*_{(5\times10^{-3},0.5)}\|_2 < \|w^*_{(10^{-2},0.0)}\|_2$. This observation supports Remark 4.2, that the strength of implicit regularization increases with β, even with the effective learning rate. As a good critic of our own work, we would like to mention beforehand that implicit regularization is one of the tools to explain generalization but it is not a necessary condition for generalization. As for example, it fails to explain why the trajectory for a higher momentum $\beta = 0.9$ overshoots the minima to settle for another minima (preferably a better one).

5 IMPLICIT REGULARIZATION IN SGD WITH MOMENTUM

In SGD, the full-batch gradient is replaced by it's sampled unbiased estimator. Assume that the loss function $E(\mathbf{x})$ has the following form

$$E(\mathbf{x}) = \frac{1}{M}\sum_{j=1}^{M} E_{(j)}(\mathbf{x}) \tag{7}$$

where $E_{(j)}$ is the j^{th} mini-batch loss. In the k^{th} iteration, we randomly pick a mini-batch, whose loss is denoted by E_k, and update the parameters accordingly. The heavy-ball accelerated SGD iterates as

$$\begin{cases} \mathbf{x}^{k+1} = \mathbf{x}^k - h\nabla E_k(\mathbf{x}^k) + \beta(\mathbf{x}^k - \mathbf{x}^{k-1}) & k = 1, 2, ..., n \\ \mathbf{x}^1 = \mathbf{x}^0 - h\nabla E_0(\mathbf{x}^0) \\ \mathbf{x}^0 = \mathbf{x}^{-1} = \mathbf{0} \end{cases} \tag{8}$$

For each iteration k, the update is driven by the current mini-batch loss E_k. Its continuous approximation is

$$\mathbf{x}'(t) = -\nabla E_k(\mathbf{x}(t)) + \frac{\beta}{h}(\mathbf{x}(t_k) - \mathbf{x}(t_{k-1})) \quad \text{for } t_k < t < t_{k+1} \tag{9}$$

during the time $[t_k, t_{k+1}]$. As a result, the trajectory of $\mathbf{x}$ is continuous but piece-wise differentiable as it is easy to see that the left and right-side derivatives are not equal at a transit point t_k from one batch to another, $\mathbf{x}'(t_k^+) \neq \mathbf{x}'(t_k^-)$. Therefore, we expect the implicit regularization term to also

have discontinuous derivatives on different intervals. Below we present the mathematical formula for IGR-M in the stochastic setting.

Theorem 5.1. *[IGR-M stochastic version (IGRM$_s$)] Let the loss for each mini-batch E_k be 4-times differentiable, then the Heavy Ball momentum updates 8 are $O(h^2)$ close to the trajectory of the gradient flow with the modified loss,*

$$\widetilde{\mathbf{x}}'(t) = -\nabla \hat{E}_k(\widetilde{\mathbf{x}}(t)) \quad for\ t_k \le t < t_{k+1}$$

$$where, \quad \hat{E}_k(\widetilde{\mathbf{x}}) = \underbrace{G_k(\widetilde{\mathbf{x}})}_{force} + \underbrace{\frac{h}{4}(\|\nabla G_k(\widetilde{\mathbf{x}})\|_2^2 + 2\sum_{r=0}^{k-1}\beta^{k-r}\|\nabla G_r(\widetilde{\mathbf{x}})\|_2^2)}_{IGRM_s} \tag{10}$$

with $G_k(\widetilde{\mathbf{x}}(t)) = \sum_{r=0}^k \beta^{k-r} E_k(\widetilde{\mathbf{x}}(t))$. Specifically, there exists a constant C such that

$$\|\widetilde{\mathbf{x}}(t_k) - \mathbf{x}^k\|_2 \le Ch^2, \quad k=1,2,...,n.$$

The theorem tells us that the IGR for momentum is in the form of ℓ_2 norms of ∇G_k which is a weighted sum of the historical gradients ∇E_k, $k = 0, ..., n$, by powers of β and evaluated at the current location $\tilde{\mathbf{x}}(t)$. In addition, the stochastic IGR-M has different expressions on different intervals, caused by the abrupt changes between adjacent batches. Some further remarks about the (SGD+M) algorithm are listed below.

Remark 5.1. The flow of the continuous trajectory is governed by the driving-force $-\nabla G_k(\mathbf{x}(t))$ and the negative gradient of an implicit regularizer $IGRM_s(\widetilde{\mathbf{x}}) = \frac{h}{4}(\|\nabla G_k(\widetilde{\mathbf{x}})\|_2^2 + 2\sum_{r=0}^{k-1}\beta^{k-r}\|\nabla G_r(\widetilde{\mathbf{x}})\|_2^2$ which depends on both the learning rate h and momentum β.

Remark 5.2. When $\beta = 0$, 10 reduces to

$$\widetilde{\mathbf{x}}'(t) = -\nabla \left(\underbrace{E_k(\widetilde{\mathbf{x}}(t)}_{force} + \underbrace{\frac{h}{4}\|\nabla E_k(\widetilde{\mathbf{x}}(t))\|_2^2)}_{IGR} \right), \quad t \in [t_k, t_{k+1}], \tag{11}$$

which is the modified loss for SGD.

Remark 5.3. Taking expectation over the random selections of batches, we get $\mathbb{E}(IGRM_s)(\mathbf{x}) = \frac{h(1+\beta)}{4(1-\beta)^3}\|\nabla E\|^2 + \frac{h}{4(1-\beta)^2}F$, where $F := \mathbb{E}\|E_n - E\|^2$ (appendix Th 3.1). In comparison, the IGR term in SGD after taking expectation is $\frac{h}{4}(F + \|\nabla E\|^2)$ (Smith et al., 2021), which is much weaker. Even with the adjusted learning rate, the IGR in (SGD+M) is still about $1/(1 - \beta)$ times stronger than SGD.

Remark 5.4 (Variance reduction). We notice that momentum has a variance reduction effect. Explicitly, suppose the adjusted learning rate (Remark 4.1) is used so that the force terms in (SGD) and (SGD+M) have the same expectation, and then we can compare their variance. Let the covariance matrix of ∇E_k at a fixed point $\mathbf{x}$ be $C := \mathbb{E}(\nabla E_k(\mathbf{x}) - \nabla E(\mathbf{x}))(\nabla E_k(\mathbf{x}) - \nabla E(\mathbf{x}))^T$. Then the covariance matrix of the force $-E_k$ driving (SGD) is exactly C, while that of the force $-G_k$ driving (SGD+M) is only $\frac{(1-\beta)}{1+\beta}C$ (appendix Th 4.1), which is about $\frac{(1-\beta)}{(1+\beta)}$ times smaller.

Remark 5.5. It is observed and confirmed by many literature that a larger variance of SGD iterations (caused by either a small batch size or a larger learning rate (Smith & Le, 2017; Li et al., 2017)) increases the generalization power. Therefore, the variance reduction effect of SGD+M hurts generalization. On the other hand, the fact that (SGD+M) has a stronger IGR (Remark 5.3) and that (SGD+M) is more stable than (SGD) to the use of large effective learning rates (see e.g., (Cohen et al., 2021)) tend to help with its generalization. This explains why in practice we usually observe that (SGD+M) is only slightly better than (SGD).

6 NUMERICAL EXPERIMENTS

Our first experiment is to compare the full-batch (GD) with (GD+M). For a linear least-squares problem with a Hessian matrix bounded by L in the spectral norm, it is well-known that (e.g., (Cohen

(a) Accuracy

(b) Loss

Figure 2: (GD): Classification results of ResNet-18 on MNIST dataset performed with full-batch gradient descent. Figure shows the effect of implicit regularization due to the finite learning rate h. Test accuracy improves with higher learning rate till $h = 0.2$. For $h = 0.2$, the best test-accuracy is achieved at 95.72%

(a) Accuracy

(b) Loss

Figure 3: (GD+M): Classification results of ResNet-18 on MNIST dataset trained with various values of momentum parameter β for full-batch gradient descent. The best test-accuracy is reported to be 96.22%

et al., 2021)) (GD+M) is stable as long as $h < \frac{2+2\beta}{L}$, and GD is stable as long as $h < \frac{2}{L}$. This means, the maximum achievable effective learning rate by (GD) is $\frac{2}{L}$, while that by (GD+M) can be as large as $\frac{2(1+\beta)}{L(1-\beta)}$. Since larger effective learning rates means a stronger IGR, (GD+M) clearly benefits from its large stability region. To confirm this, ResNet-18 is used to classify a uniformly sub-sampled MNIST dataset with 1000 training images. All external regularization schemes except learning rate decay and batch normalization have been turned off. We perform the following experiments : **1**) Full-batch gradient descent with $\beta = 0$ (i.e., GD) for various learning rate h and the best test accuracy is noted (in Figure 2) to be 95.72%. **2**) Full-batch gradient descent with momentum (GD+M) performed for various β with a fixed step-size $h - 0.1$ and the best test-accuracy is noted (in Figure 3) to be 96.22%. Our observation is that the best performance of GD (across all learning rates) is worse than the best performance of (GD+M) (across all β's). (Cohen et al., 2021) showed that gradient descent (GD) has an overwhelming tendency to increase the sharpness [2] till it reaches $\frac{2}{h}$, called "the edge of stability". And for (GD+M), the sharpness can reach up to $\frac{2(1+\beta)}{h}$, hence allowing it to enter a sharper region before becoming unstable. As greater allowable sharpness for (GD+M) than that of (GD) may suggest a higher test accuracy for (GD), this is not what we observe from the above experiment. We think the implicit regularization for (GD+M) plays a part in it. We believe IGR for momentum outweighs the sharpness effect in achieving better test accuracy.

To study the effect of implicit regularization (SGD+M), a series of experiments have been performed on an image classification task. Four well-known and popular network architectures namely DenseNet (Iandola et al., 2014), ResNet-18, ResNet-50 (He et al., 2016) and WideResNet (Zagoruyko & Komodakis, 2016) are trained to classify images from the CIFAR-10 and CIFAR-100 datasets. We are interested to know how well training these networks with (SGD) and (SGD+M) respectively can generalize well onto the test dataset. To solely observe the effects of the momen-

---

[2]maximum eigenvalue of Hessian evaluated at $\mathbf{x}$

(a) WideresNet-16-8   (b) ResNet-18

(c) ResNet-50   (d) DenseNet-121

Figure 4: Classification results for CIFAR-10 dataset with various network architectures with combinations of (h, β) chosen such that the effective learning rate $\frac{h}{(1-\beta)}$ remains same. In all of the experiments, external regularization like weight-decay, l.r scheduler, dropout,label-smoothing are kept off (except Batch-normalization). The results have been averaged over 3 random seeds having different initializations. (SGD+M) has a) higher test accuracy for increasing β than (SGD) confirming Remark 5.4 b) Less variance for test accuracy confirming Remark 5.3.

.

tum parameter β and learning rate h in generalization, we turn off all the external regularization like dropout, weight-decay and label-smoothing. We fix the batch-size to 640 in all our experiments.

	CIFAR-10				CIFAR-100			
β /h	DN-121	RN-18	RN-50	WRN-16-8	DN-121	RN-18	RN-50	WRN-16-8
0.0/0.10	84.0±5.0	79.7±5.6	79.3±2.5	65.3±18.1	60.4±4.9	53.1±0.6	47.4±2.1	38.6±3.8
0.3/0.07	85.1±5.4	78.7±9.3	80.0±1.5	72.5±7.4	60.0±8.6	52.7±1.0	48.9±2.2	37.0±6.1
0.5/0.05	87.6±1.2	81.5±0.9	80.7±0.7	71.8±9.8	63.2±2.4	53.3±1.1	**50.3±1.0**	39.4±3.9
0.8/0.02	**88.6±0.7**	**82.4±0.4**	**82.4±0.7**	**75.4±2.8**	**64.7±0.8**	**54.3±0.6**	49.6±0.7	**40.6±1.2**

Table 1: Testing accuracy of CIFAR-10 and CIFAR-100 with different momentum β and learning rates h, but the same effective learning rate $\frac{h}{(1-\beta)} = 0.1$. The best performance of different models is highlighted. The mean and the standard deviation of test accuracy is calculated over the last 5 epochs and three random seed initializations. DN-121 is the Densenet-121, RN-18 and RN-50 denote the Resnet-18 and Resnet-50, WRN-16-8 represents the WideResnet with depth 16 and width-factor 8.

In the first experiment, we showed (GD+M) has a larger stability region than (GD) and hence allows for the use of a larger effective learning rate. The same conclusion holds for (SGD+M) and (SGD). However, here we want to show that even in the region where both algorithms are stable, (SGD+M) is still not just a scaled version of (SGD). For this purpose, we pick a small learning rate to ensure stability of both algorithms, and keep the effective learning rate $\frac{h}{(1-\beta)}$ for (SGD+M) to be the same as the learning rate for (SGD) (both equal 0.1). We observe from Table 1 (also Figure 4), that the maximum test accuracy is almost always achieved at the highest value for β. This observation is consistent with Remark-5.3 where we showed that the implicit regularization in (SGD+M) is indeed stronger than (SGD), even after the learning rate adjustment.

The standard deviation of test accuracy in Table 1 is calculated over the last 5 epochs and three random seed initialization. Lower standard deviation indicates a smoother test accuracy curve meaning less variation of test accuracy within an epoch interval. We observe that the lowest standard deviation is achieved at the highest value of β. Hence the observation that variance reduction effect is more prominent with higher β is consistent with Remark 5.4.

7 COMBINED EFFECTS OF IGR AND NOISE INJECTION

Despite its close relation to sharpness (Section 3), the IGR term $\|\nabla E\|^2$ gets very weak and irrelevant as $\mathbf{x}^k$ approaches a local minimizer, since $\nabla E \to 0$. However, we find that this would not be the case if there was noise injection, which can help the IGR term retain its power even near local minima. More specifically, as studied in previous literature (Orvieto et al., 2022b; Camuto et al., 2020), the algorithm resulting from injecting noise to each iteration of GD is usually called PGD (Perturbed gradient descent) that essentially minimizes an averaged objective function

$$R(\mathbf{x}) := \mathbb{E}_{\eta \sim N(0, \sigma^2 \mathbf{I})} E(\mathbf{x} + \eta).$$

For small values of σ, we can expand $R(\mathbf{x})$ into

$$R(\mathbf{x}) = E(\mathbf{x}) + \mathbb{E}_\eta \eta^T \nabla E(\mathbf{x}) + \frac{1}{2} \mathbb{E}_\eta \eta^T \nabla^2 E(\mathbf{x})\eta + O(\sigma^3) = E(\mathbf{x}) + \frac{1}{2}\sigma^2 Tr(\nabla^2 E(\mathbf{x})) + O(\sigma^3),$$

where Tr denotes the trace operator. Thus minimizing $R(\mathbf{x})$ regularizes the trace Hessian of E. When minimizing $R(\mathbf{x})$ using an SGD type of update, the iterations would be

$$\mathbf{x}^{k+1} = \mathbf{x}^k - h\nabla E(\mathbf{x}^k + \eta_k), \text{ where } \eta_k \sim \mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I}),$$

which is known as a form of PGD. Because of the finite learning rate, the updates would follow the modified flow with an IGR term, which in this case is

$$E(\mathbf{x} + \eta_k) + \frac{h}{4}\|\nabla E(\mathbf{x} + \eta_k)\|^2.$$

In expectation, the modified loss is

$$\mathbb{E}_{\eta_k}\left[E(\mathbf{x} + \eta_k) + \frac{h}{4}\|\nabla E(\mathbf{x} + \eta_k)\|^2)\right]$$

$$=\mathbb{E}_{\eta_k}\left[E(\mathbf{x}) + \eta_k^T \nabla E(\mathbf{x}) + \frac{1}{2}(\eta_k)^T \nabla^2 E(\mathbf{x})\eta_k\right]$$

$$+ \frac{h}{4}\mathbb{E}_{\eta_k}\|\nabla E(\mathbf{x}) + \nabla^2 E(\mathbf{x})\eta_k + \nabla^3 E(\mathbf{x})[\eta_k, \eta_k]\|^2) + O(\sigma^3)$$

$$=E(\mathbf{x}) + \sigma^2 Tr(\nabla^2 E(\mathbf{x})) + \frac{h}{4}\left[\sigma^2\|\nabla^2 E(\mathbf{x})\|_F^2 + \mathbb{E}_{\eta_k}\|\nabla E(\mathbf{x}) + \nabla^3 E(\mathbf{x})[\eta_k, \eta_k]\|^2\right] + O(\sigma^3).$$

We see that now there is a Hessian regularization term $\frac{h}{4}\sigma^2\|\nabla^2 E(\mathbf{x})\|_F^2$ coming out of IGR which does not vanish even around local minimizers, and it's strength is proportional to the learning rate. We expect this new regularization term to get stronger when momentum is added, as momentum amplifies the power of IGR (Remark 4.2, 5.3). This observation suggests that IGR and noise injection as two different types of implicit regularization might be able to reinforce each other when used collaboratively.

8 CONCLUSION

This work studies the generalization of momentum driven gradient descent approach through the lens of implicit regularization (IR) with both theoretical analysis and experimental validation provided. We examined the similarities and differences between (SGD) and (SGD+M) and find that (SGD+M) outperforms (SGD) in almost all settings. Moreover, we found that in addition to momentum, IGR may also be magnified by noise injection, which is a topic we want to further explore in the future.

REFERENCES

Sanjeev Arora, Nadav Cohen, Wei Hu, and Yuping Luo. Implicit regularization in deep matrix factorization. Advances in Neural Information Processing Systems, 32, 2019.

David GT Barrett and Benoit Dherin. Implicit gradient regularization. arXiv preprint arXiv:2009.11162, 2020.

Yoshua Bengio and Yann LeCun. Scaling learning algorithms towards AI. In Large Scale Kernel Machines. MIT Press, 2007.

Alexander Camuto, Matthew Willetts, Umut Simsekli, Stephen J Roberts, and Chris C Holmes. Explicit regularisation in gaussian noise injections. Advances in Neural Information Processing Systems, 33:16603–16614, 2020.

Jeremy M Cohen, Simran Kaur, Yuanzhi Li, J Zico Kolter, and Ameet Talwalkar. Gradient descent on neural networks typically occurs at the edge of stability. arXiv preprint arXiv:2103.00065, 2021.

Pierre Foret, Ariel Kleiner, Hossein Mobahi, and Behnam Neyshabur. Sharpness-aware minimization for efficiently improving generalization. arXiv preprint arXiv:2010.01412, 2020.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. Deep learning, volume 1. MIT Press, 2016.

Suriya Gunasekar, Blake E Woodworth, Srinadh Bhojanapalli, Behnam Neyshabur, and Nati Srebro. Implicit regularization in matrix factorization. Advances in Neural Information Processing Systems, 30, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 770–778, 2016.

Geoffrey E. Hinton, Simon Osindero, and Yee Whye Teh. A fast learning algorithm for deep belief nets. Neural Computation, 18:1527–1554, 2006.

Forrest Iandola, Matt Moskewicz, Sergey Karayev, Ross Girshick, Trevor Darrell, and Kurt Keutzer. Densenet: Implementing efficient convnet descriptor pyramids. arXiv preprint arXiv:1404.1869, 2014.

Samy Jelassi and Yuanzhi Li. Towards understanding how momentum improves generalization in deep learning. In International Conference on Machine Learning, pp. 9965–10040. PMLR, 2022.

Ziwei Ji and Matus Telgarsky. The implicit bias of gradient descent on nonseparable data. In Conference on Learning Theory, pp. 1772–1798. PMLR, 2019.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. arXiv preprint arXiv:1412.6980, 2014.

Nikola B Kovachki and Andrew M Stuart. Continuous time analysis of momentum methods. Journal of Machine Learning Research, 22(17):1–40, 2021.

Qianxiao Li, Cheng Tai, and E Weinan. Stochastic modified equations and adaptive stochastic gradient algorithms. In International Conference on Machine Learning, pp. 2101–2110. PMLR, 2017.

Behnam Neyshabur. Implicit regularization in deep learning. arXiv preprint arXiv:1709.01953, 2017.

Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. In search of the real inductive bias: On the role of implicit regularization in deep learning. arXiv preprint arXiv:1412.6614, 2014.

Antonio Orvieto, Hans Kersting, Frank Proske, Francis Bach, and Aurelien Lucchi. Anticorrelated noise injection for improved generalization. arXiv preprint arXiv:2202.02831, 2022a.

Antonio Orvieto, Anant Raj, Hans Kersting, and Francis Bach. Explicit regularization in over-parametrized models via noise injection. arXiv preprint arXiv:2206.04613, 2022b.

Tomaso Poggio, Andrzej Banburski, and Qianli Liao. Theoretical issues in deep networks. Proceedings of the National Academy of Sciences, 117(48):30039–30045, 2020.

Boris T Polyak. Some methods of speeding up the convergence of iteration methods. Ussr computational mathematics and mathematical physics, 4(5):1–17, 1964.

Noam Razin and Nadav Cohen. Implicit regularization in deep learning may not be explainable by norms. Advances in neural information processing systems, 33:21174–21187, 2020.

Samuel L Smith and Quoc V Le. A bayesian perspective on generalization and stochastic gradient descent. arXiv preprint arXiv:1710.06451, 2017.

Samuel L Smith, Benoit Dherin, David GT Barrett, and Soham De. On the origin of implicit regularization in stochastic gradient descent. arXiv preprint arXiv:2101.12176, 2021.

Daniel Soudry, Elad Hoffer, Mor Shpigel Nacson, Suriya Gunasekar, and Nathan Srebro. The implicit bias of gradient descent on separable data. The Journal of Machine Learning Research, 19 (1):2822–2878, 2018.

Ilya Sutskever, James Martens, George Dahl, and Geoffrey Hinton. On the importance of initialization and momentum in deep learning. In International conference on machine learning, pp. 1139–1147. PMLR, 2013.

Tijmen Tieleman, Geoffrey Hinton, et al. Lecture 6.5-rmsprop: Divide the gradient by a running average of its recent magnitude. COURSERA: Neural networks for machine learning, 4(2):26–31, 2012.

Gal Vardi and Ohad Shamir. Implicit regularization in relu networks with the square loss. In Conference on Learning Theory, pp. 4224–4258. PMLR, 2021.

Bohan Wang, Qi Meng, Huishuai Zhang, Ruoyu Sun, Wei Chen, Zhi-Ming Ma, and Tie-Yan Liu. Does momentum change the implicit regularization on separable data?, 2021. URL https://arxiv.org/abs/2110.03891.

Jingfeng Wu, Wenqing Hu, Haoyi Xiong, Jun Huan, Vladimir Braverman, and Zhanxing Zhu. On the noisy gradient descent that generalizes as sgd. In International Conference on Machine Learning, pp. 10367–10376. PMLR, 2020.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. arXiv preprint arXiv:1605.07146, 2016.