Probabilistic Inference in Reinforcement Learning Done Right

Abstract

A popular perspective in Reinforcement learning (RL) casts the problem as probabilistic inference on a graphical model of the Markov decision process (MDP). The core object of study is the probability of each state-action being visited under the optimal policy. Previous approaches to approximate this quantity can be arbitrarily poor, leading to algorithms that do not implement genuine statistical inference and consequently do not perform well in challenging problems. In this work, we undertake a rigorous Bayesian treatment of the posterior probability of state-action optimality and clarify how it flows through the MDP. We first reveal that this quantity can indeed be used to generate a policy that explores efficiently, as measured by regret. Unfortunately, computing it is intractable, so we derive a new variational Bayesian approximation yielding a tractable convex optimization problem and establish that the resulting policy also explores efficiently. We call our approach VAPOR and show that it has strong connections to Thompson sampling, K-learning, and maximum entropy exploration. We conclude with some experiments demonstrating the performance advantage of a deep RL version of VAPOR.

1 Introduction

Reinforcement learning (RL) is the problem of learning to control an unknown system by taking actions to maximize its cumulative reward through time [74]. As the agent navigates the environment, it receives noisy observations which it can use to update its (posterior) beliefs about the environment [21]. Unlike supervised learning, where the performance of an algorithm does not influence the data it will later observe, in RL the policy of the agent affects the data it will collect, which in turn affects the policy, and so on. As a result, an agent must sometimes take actions that lead to states where it has *epistemic uncertainty* about the value of those states, and sometimes take actions that lead to more certain payoff. The tension between these two modes is the *exploration-exploitation* trade-off [2, 35]. In this light, RL is a *statistical inference problem* wrapped in a *control problem*, and the two problems must be tackled simultaneously for good data efficiency.

It is natural to apply Bayesian probabilistic inference to the uncertain parameters in RL [21] and, since the goal of the agent is to find the optimal policy, a relevant object of study is the posterior probability of *optimality* for each state-action pair. In fact, the popular 'RL as inference' approach, most clearly summarized in the tutorial and review of [37], embeds the control problem into a graphical model by introducing optimality binary random variables that indicate whether a state-action is optimal. In the 'RL as inference' setup these optimality variables are assumed to be observed and take the value one with probability depending on the local reward. This surrogate potential seems like a peculiar and arbitrary choice, yet it has been widely accepted due to its mathematical convenience: for deterministic dynamics, the resulting probabilistic inference is equivalent to maximum entropy RL [78, 85]. However, this approximation leads to a critical shortcoming: The surrogate potential

Submitted to 16th European Workshop on Reinforcement Learning (EWRL 2023). Do not distribute.

functions do not take into account the Bayesian (epistemic) uncertainty, and consequently do not perform genuine statistical inference on the unknowns in the MDP. This leads to 'posteriors' that are in no way related to the *true* posteriors in the environment, and acting with those false posteriors leads to poor decision making and agents that require exponential time to solve even small problems [52].

Our first contribution is a formal and rigorous Bayesian treatment of the posterior probability of each state-action being visited under the optimal policy. We go on to prove that knowledge of this quantity is sufficient to derive a policy that explores efficiently, as measured by regret (Section 3). Unfortunately, computing this probability is intractable in general, so we turn to a form of variational Bayesian inference [18]. Typically, variational inference minimizes some notion of distance (*e.g.*, a KL-divergence) to the posterior. Yet unlike standard variational inference techniques, we cannot minimize the KL-divergence to this distribution as we do not have access to samples. However, we do have a downstream *control* objective. That is to say, we are not simply interested in approximating the distribution, but also in our approximation doing well in the control problem. This insight provides an alternative objective that takes into account the rewards and uncertainties that the agent is likely to encounter. It yields a tractable convex optimization that we can solve for a policy (Section 4), which we prove explores efficiently (Section 5). Moreover, although we do not explicitly minimize the KL-divergence to the true posterior, we provide a bound quantifying the dissimilarity, as well as experiments confirming that the variational approximation is close in practice. Our *variational Bayesian* approximation, which can be seen as extending the multi-armed bandit algorithm VBOS [50] to the RL setting, has strong connections to Thompson sampling [76, 73, 58, 69], K-learning [46] and maximum entropy exploration [29, 77] (Section 6). We also propose a principled approximation which can be readily solved in deep RL with policy-gradient techniques (Appendix E). A unique feature of our approach is that it adaptively tunes optimism and entropy regularization for *each* state-action, which is empirically beneficial as our experiments on 'DeepSea' and Atari show (Section 7).

2 Preliminaries

We model the RL environment as a finite state-action, time-inhomogeneous MDP given by the tuple $\mathcal{M} := \{\mathcal{S}, \mathcal{A}, L, \{P_l\}_{l=1}^L, \{R_l\}_{l=1}^L, \rho\}$, where $\mathcal{S}$ is the state space with cardinality S, $\mathcal{A}$ is the action space with A possible actions, L is the horizon length, $P_l : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$ denotes the transition dynamics at step l, $R_l : \mathcal{S} \times \mathcal{A} \to \Delta(\mathbb{R})$ is the reward function at step l and $\rho \in \Delta(\mathcal{S})$ is the initial state distribution. Concretely, the initial state $s_1 \in \mathcal{S}$ is sampled from ρ, then for steps $l = 1, \ldots, L$ the agent is in state $s_l \in \mathcal{S}$, selects action $a_l \in \mathcal{A}$, receives a reward sampled from $R_l(s_l, a_l)$ with mean $r_l(s_l, a_l) \in \mathbb{R}$ and transitions to the next state $s_{l+1} \in \mathcal{S}$ with probability $P_l(s_{l+1} \mid s_l, a_l)$. An agent following a policy $\pi_l \in \Delta(\mathcal{A})^S$ at state s at step l selects action a with probability $\pi_l(s, a)$. The value functions are defined as

$$Q_l^\pi(s,a) = r_l(s,a) + \sum_{s' \in \mathcal{S}} P_l(s' \mid s,a) V_{l+1}^\pi(s'), \qquad V_l^\pi(s) = \sum_{a \in \mathcal{A}} \pi(s,a) Q_l^\pi(s,a), \qquad V_{L+1}^\pi = 0,$$

$$Q_l^\star(s,a) = r_l(s,a) + \sum_{s' \in \mathcal{S}} P_l(s' \mid s,a) V_{l+1}^\star(s'), \qquad V_l^\star(s) = \max_{a \in \mathcal{A}} Q_l^\star(s,a), \qquad V_{L+1}^\star = 0.$$

An optimal policy $\pi^\star$ satisfies $V_l^{\pi^\star}(s) = V_l^\star(s)$ for each state s and step l. We denote by $\{\pi_l^\star(s) = a\}$ the event that action a is optimal for state s at step l, with ties broken arbitrarily to ensure that only one action is optimal at each state. Let $\mathbb{R}_+^{L,S,A} := \{\mathbb{R}_+^{S \times A}\}_{l=1}^L$ and $\sum_{l,s,a} \equiv \sum_{l=1}^L \sum_{s \in \mathcal{S}} \sum_{a \in \mathcal{A}}$.

Occupancy measures. We denote the set of occupancy measures (a.k.a. stationary state-action distributions) with respect to the transition dynamics P as

$$\Lambda(P) := \left\{ \lambda \in \mathbb{R}_+^{L,S,A} : \sum_a \lambda_1(s,a) = \rho(s), \sum_{a'} \lambda_{l+1}(s',a') = \sum_{s,a} P_l(s' \mid s,a) \lambda_l(s,a) \right\}.$$

Note the following correspondence between $\Lambda(P)$ and the set of policies $\Pi = \{\Delta(A)^S\}_{l=1}^L$ [65]. Any policy $\pi \in \Pi$ induces $\lambda^\pi \in \Lambda(P)$ such that $\lambda_l^\pi(s,a)$ denotes the probability of reaching (s,a) at step l under π. Conversely, any $\lambda \in \Lambda(P)$ induces $\pi^\lambda \in \Pi$ given by $\pi_l^\lambda(s,a) := \lambda_l(s,a)/(\sum_{a'} \lambda_l(s,a'))$ so long as $\sum_{a'} \lambda_l(s,a') > 0$; otherwise $\pi_l^\lambda(s, \cdot)$ can be any distribution, *e.g.*, uniform.

Bayesian RL. We consider the Bayesian view of the RL problem, where the agent has some (posterior) beliefs about the MDP represented by a distribution ϕ on the space of all MDPs. We use the shorthand notation $\mathbb{E}_\phi$ and $\mathbb{P}_\phi$ to denote the expectation and probability under ϕ. In the Bayesian view, the quantities r and P are random variables, and thus so are $Q^\star, V^\star, \pi^\star$.

2.1 Previous Approach to 'RL as Inference'

The popular line of research casting 'RL as inference' is most clearly summarized in the tutorial and review of Levine, 2018 [37]. It embeds the control problem into a graphical model, mirroring the dual relationship between optimal control and inference [79, 34, 66]. As shown in Figure 5a, this approach defines an additional *optimality* binary random variable denoted by $\Gamma_l^\star$, which indicates which state-action at timestep l is 'optimal', *i.e.*, which state-action is visited under the (unknown) optimal policy. In these works the probability of $\Gamma_l^\star$ is then modeled as proportional to the exponentiated reward.

Approximation 1 (Inference over exponentiated reward [37])**.** *Denoting by* $\Gamma_l^\star(s, a)$ *the event that state-action pair* (s, a) *is 'optimal' at timestep* l*, set* $\mathbb{P}(\Gamma_l^\star(s, a)) \propto \exp(r_l(s, a))$.

Under Approximation 1, the optimality variables become observed variables in the graphical model, over which we can apply standard tools for inference. This approach has the advantage of being mathematically and computationally convenient. In particular, under deterministic dynamics it directly leads to RL algorithms with 'soft' Bellman updates and added entropy regularization, thus recovering the maximum-entropy RL framework [78, 85] and giving a natural, albeit heuristic exploration strategy. Many popular algorithms lie within this class [64, 25, 1] and have demonstrated strong empirical performance in domains where efficient exploration is not a bottleneck.

Despite its popularity and convenience, the potential function of Approximation 1 *ignores epistemic uncertainty* [52]. Due to this shortcoming, the inference procedure produces invalid and arbitrarily poor posteriors. It can be shown that the resulting algorithms fail even in basic bandit-like problems (*e.g.*, [52, Problem 1]), as they underestimate the probability of optimal actions and take actions which have no probability of optimality under the true posterior. This implies that the resulting agents (*e.g.*, Soft Q-learning [25]) can perform poorly in simple domains that require deep exploration [56]. The fact that the 'RL as inference' framework does not perform valid inference on the optimality variables leads us to consider how a proper Bayesian inference approach might proceed. This leads us to the first contribution of this manuscript.

3 A Principled Bayesian Inference Approach to RL

In this section, we provide a principled Bayesian treatment of statistical inference over 'optimality' variables in an MDP. Although it is the main quantity of interest of the popular 'RL as inference' framework, a rigorous definition of whether a state-action is optimal has remained elusive. We provide a recursive one below.

Definition 1 (State-action optimality)**.** *For any step* $l \in [L]$*, state-action* $(s, a) \in \mathcal{S} \times \mathcal{A}$*, we define*

$$\Gamma_1^\star(s) := \{s_1 = s\}, \qquad \Gamma_{l+1}^\star(s') := \bigcup_{s \in \mathcal{S}, a \in \mathcal{A}} \Gamma_l^\star(s, a) \cap \{s_{l+1} = s'\},$$

$$\Gamma_1^\star(s, a) := \Gamma_1^\star(s) \cap \{\pi_1^\star(s) = a\}, \qquad \Gamma_{l+1}^\star(s', a') := \Gamma_{l+1}^\star(s') \cap \{\pi_{l+1}^\star(s') = a'\}.$$

In other words, $\Gamma_l^\star(s)$ is the *random* event that state s is reached at step l after executing optimal actions from steps 1 to $l-1$, and the event $\Gamma_l^\star(s, a)$ further requires that the action a is optimal at state s in step l. Equipped with this definition, 'optimality' in an MDP flows both in a *backward* way (via action optimality $\pi^\star$, which can be computed using dynamic programming) and in a *forward* way (via state-action optimality $\Gamma^\star$). We illustrate this bidirectional property in the simplified graphical model of Figure 5b (which isolates a single trajectory). In general, state-action optimality encapsulates all possible trajectories leading to a given state being optimal (and there may be exponentially many of them). Thanks to the MDP structure and Bayes' rule, we show in Lemma 1 that the *posterior probability* of state-action optimality lies in the space of occupancy measures. To simplify exposition, we first assume that the transition dynamics P are known (only rewards are unknown), and we extend our analysis to unknown P in Section 5.

Lemma 1. *For known* P*, it holds that* $\mathbb{P}_{\Gamma^\star} := \{\mathbb{P}_\phi(\Gamma_l^\star)\}_{l=1}^L \in \Lambda(P)$.

The significance of Lemma 1 is that we can readily *sample* from $\mathbb{P}_{\Gamma^\star}$ with the induced policy

$$\pi_l(s, a) = \frac{\mathbb{P}_\phi(\Gamma_l^\star(s, a))}{\sum_{a' \in \mathcal{A}} \mathbb{P}_\phi(\Gamma_l^\star(s, a'))} = \mathbb{P}_\phi(\pi_l^\star(s) = a \mid \Gamma_l^\star(s)), \tag{1}$$

Figure 1: Pair of MDPs $\{\mathcal{M}^+, \mathcal{M}^-\}$ with uniform prior $\phi = (\frac{1}{2}, \frac{1}{2})$. $\mathcal{M}^+$ and $\mathcal{M}^-$ only differ through their reward at state s_L, resp. $+1$ and -1. Two actions are available at states s_1 to s_{L-1}: $\downarrow$ exits the chain and moves to an absorbing, zero-reward state, and $\rightarrow$ moves right with small negative reward $-\epsilon$.

| Policy | Agent starts at s_1
$\pi_1(s_1, a)$ for $a \in \{\downarrow, \rightarrow\}$ | Agent reaches $s_l, l > 1$
$\pi_l(s_l, a)$ for $a \in \{\downarrow, \rightarrow\}$ | Expected # episodes to reach s_L |
|---|---|---|---|
| Bayes-optimal | $(0, 1)$ | $(0, 1)$ | 1 |
| Approximation 1 (e.g., Soft Q-Learning) | $(0.5, 0.5)$ | $(0.5, 0.5)$ | $\Omega(2^L)$ |
| Marginal $\mathbb{P}_\phi(\pi^\star)$ | $(0.5, 0.5)$ | $(0.5, 0.5)$ | $\Omega(2^L)$ |
| Conditional $\mathbb{P}_\phi(\pi^\star \mid \Gamma^\star)$ | $(0.5, 0.5)$ | $(0, 1)$ | 2 |
| Thompson Sampling | $(0, 1)$ w.p. 0.5
$(1, 0)$ w.p. 0.5 | $(0, 1)$ | 2 |
| VAPOR | $(0, 1)$ | $(0, 1)$ | 1 |

Table 1: Comparison of algorithm performance on MDP in Figure 1. Unprincipled approaches like Soft Q-learning take time exponential in L to reach the uncertain reward state. Naively using the marginal posterior probability of *action optimality* as the policy at each state also requires exponential time, however the policy dervied from the posterior probability of *state-action optimality* $\mathbb{P}_{\Gamma^\star}$ takes *consistent* actions and is therefore efficient. Similar good performance is achieved by Thompson sampling (implicit approximation of $\mathbb{P}_{\Gamma^\star}$, Section 6) and VAPOR (explicit approximation of $\mathbb{P}_{\Gamma^\star}$, Section 4).

which is the probability under the posterior that action a is optimal at state s conditioned on state optimality (*i.e.*, conditioned on all actions taken before timestep l being optimal). It turns out that this policy explores efficiently, as measured by regret (see Corollary 1). Concretely, we have shown that the two facets of RL (inference and control) can be distilled into a single quantity: $\mathbb{P}_{\Gamma^\star}$. We use Bayesian inference to compute $\mathbb{P}_{\Gamma^\star}$ and then use that to derive a good control policy. This is a principled and consistent Bayesian 'RL as inference' approach. The remaining challenge thus lies in computing $\mathbb{P}_{\Gamma^\star}$. Unfortunately, doing so involves computing several complicated integrals with respect to the posterior and is intractable in most cases. In Section 4, we introduce the second contribution of this manuscript, which is a way to approximate $\mathbb{P}_{\Gamma^\star}$ using a computationally tractable variational approach.

3.1 Instructive Example

To gain intuition on the difference between *action optimality* (*i.e.*, $\mathbb{P}_\phi(\pi^\star)$) and *state-action optimality* (*i.e.*, $\mathbb{P}_{\Gamma^\star}$), we consider the simple decision problem of Figure 1. Each episode starts in the leftmost state and the agent can traverse a chain of states in order to reach the rightmost state, where the reward is *always* either $+1$ or -1 with equal probability. Once the agent reaches the rightmost state it will resolve its uncertainty. At each state the agent has the option to move $\rightarrow$, paying a cost of ϵ where $\epsilon L \ll 1$, or move $\downarrow$ with no cost. We see that there are only 2 consistent trajectories: either take action $\downarrow$ at state s_1 (optimal for $\mathcal{M}^-$), or repeat actions $\rightarrow$ to reach s_L (optimal for $\mathcal{M}^+$). We detail how a selection of algorithms perform on this problem in Table 1.

It is worth examining in detail what has gone wrong for the policy that samples according to $\mathbb{P}_\phi(\pi^\star)$. Even if the agent has traveled to the right a few times it will exit the chain with probability 0.5 at each new state, which leads to poor exploration. Taking action $\rightarrow$ a few times and then exiting the chain has zero probability of being optimal under the posterior, so this sequence of actions is *inconsistent* with the posterior. Conditioning on the event $\Gamma^\star(s)$ when at state s forces the policy to be consistent with the set of the beliefs that would get the agent to state s in the first place, which, as we prove later, yields deep exploration. In our chain example, the only belief that takes action $\rightarrow$ is the one in which the end state has reward $+1$, so the only consistent policy conditioned on having taken $\rightarrow$ once is to continue all the way to the end state. The same issue arises in Thompson sampling, where in order to achieve consistency the agent samples a policy from its posterior and keeps it fixed for the entire episode since resampling at every timestep leads to inefficient exploration [69]. As we shall show in Section 6, Thompson sampling is exactly equivalent to sampling from $\mathbb{P}_{\Gamma^\star}$.

4 A Variational Bayesian Approach

As we have seen, having access to $\mathbb{P}_{\Gamma^\star}$ is sufficient to enable deep exploration. In this section, we derive a *variational*, *i.e.*, optimization-based, approach to approximate $\mathbb{P}_{\Gamma^\star}$. In most variational Bayesian approaches, the optimization objective is to find a surrogate probability measure that minimizes some dissimilarity metric from the intractable probability measure of interest. In this case, however, we have a downstream *control* problem and the optimization problem we formulate will take the associated value function into account when searching for the surrogate probability measure. The optimal value function $V^\star$ is a random variable under the posterior ϕ. Our next lemma relates the expected value of $V^\star$ under ϕ to our state-action optimality event $\Gamma^\star$.

Lemma 2. *We have* $\mathbb{E}_{s\sim\rho}\mathbb{E}_\phi V_1^\star(s) = \sum_{l,s,a}\mathbb{P}_\phi(\Gamma_l^\star(s,a))\mathbb{E}_\phi\left[r_l(s,a)\mid\Gamma_l^\star(s,a)\right].$

4.1 Information Theoretic Upper Bound

Lemma 2 depends on $\mathbb{P}_{\Gamma^\star}$, but the conditional expectation is not easy to deal with. To handle this, we upper bound each $\mathbb{E}_\phi[r_l(s,a)\mid\Gamma_l^\star(s,a)]$ in Lemma 2 using tools from information theory. To simplify the exposition, we consider the following standard sub-Gaussian assumption ([68, 60, 46]) and we defer to Appendix C.3 the treatment of the general case. We say $X:\Omega\to\mathbb{R}$ is σ-sub-Gaussian if $\mathbb{E}\exp(c(X-\mathbb{E}X))\leq\exp(c^2\sigma^2/2)$, for all $c\in\mathbb{R}$.

Lemma 3. *If* $r_l(s,a)$ *is* $\sigma_l(s,a)$*-sub-Gaussian under* ϕ *for each* $l\in[L]$ *and* $(s,a)\in\mathcal{S}\times\mathcal{A}$*, then*

$$\begin{aligned}
\mathbb{E}_\phi\left[r_l(s,a)\mid\Gamma_l^\star(s,a)\right] &\leq \mathbb{E}_\phi r_l(s,a) + \min_{\tau_l(s,a)>0}\left(\frac{\sigma_l^2(s,a)}{2\tau_l(s,a)}-\tau_l(s,a)\log\mathbb{P}_\phi(\Gamma_l^\star(s,a))\right) \\
&= \mathbb{E}_\phi r_l(s,a) + \sigma_l(s,a)\sqrt{-2\log\mathbb{P}_\phi(\Gamma_l^\star(s,a))}.
\end{aligned} \tag{2}$$

4.2 Optimization Problem

Finally, we combine Lemmas 2 and 3 to reveal a concave function in $\mathbb{P}_{\Gamma^\star}$ that upper bounds the value function objective $\mathbb{E}_{s\sim\rho}\mathbb{E}_\phi V_1^\star(s)$. For any $\tau\in\mathbb{R}_+^{L,S,A}$ and occupancy measure $\lambda\in\Lambda(P)$, we define the τ-*weighted entropy* of λ (summed over steps l) as $\mathcal{H}_\tau(\lambda):=-\sum_{l,s,a}\tau_l(s,a)\lambda_l(s,a)\log\lambda_l(s,a)$. In the following definition we take division and the square-root to be applied elementwise, and $\circ$ denotes elementwise multiplication. With this we can define the following optimistic value functions:

$$\mathcal{V}_\phi(\lambda,\tau) := \lambda^\top\left(\mathbb{E}_\phi r + \frac{\sigma^2}{2\tau}\right) + \mathcal{H}_\tau(\lambda), \tag{3}$$

$$\mathcal{V}_\phi(\lambda) := \min_{\tau\in\mathbb{R}_+^{L,S,A}}\mathcal{V}_\phi(\lambda,\tau) = \lambda^\top\left(\mathbb{E}_\phi r + \sigma\circ\sqrt{-2\log\lambda}\right). \tag{4}$$

Lemma 4. *For known* P *and* σ*-sub-Gaussian* r*, we have*

$$\mathbb{E}_{s\sim\rho}\mathbb{E}_\phi V_1^\star(s) \leq \mathcal{V}_\phi(\mathbb{P}_{\Gamma^\star}) \leq \underbrace{\max_{\lambda\in\Lambda(P)}\mathcal{V}_\phi(\lambda)}_{\text{VAPOR}}, \tag{5}$$

where VAPOR *is a concave optimization problem.*

The above optimization problem constitutes our *variational* objective, the solution of which yields an occupancy measure that approximates $\mathbb{P}_{\Gamma^\star}$. We call the approach 'VAPOR', for variational approximation of the posterior probability of optimality in RL. We discuss various properties of VAPOR in Appendix B (its unconstrained dual problem and its message passing interpretation).

Since we are using variational inference a natural question to ask is how well our variational solution approximates $\mathbb{P}_{\Gamma^\star}$. Here we provide a bound quantifying the dissimilarity between $\mathbb{P}_{\Gamma^\star}$ and the VAPOR solution, according to a weighted KL-divergence, where for any $\tau\in\mathbb{R}_+^{L,S,A}$, $\lambda,\lambda'\in\Lambda(P)$ we define $\mathrm{KL}_\tau(\lambda\mid\mid\lambda'):=\sum_{l,s,a}\tau_l(s,a)\lambda_l(s,a)\log(\lambda_l(s,a)/\lambda_l'(s,a))$.

Lemma 5. *Denoting by* λ^* *the* VAPOR *solution* (5) *and by* $\tau^*\in\arg\min_\tau\mathcal{V}_\phi(\lambda^*,\tau)$*, it holds that*

$$\mathrm{KL}_{\tau^*}(\mathbb{P}_{\Gamma^\star}\mid\mid\lambda^*) \leq \mathcal{V}_\phi(\lambda^*) - \mathbb{E}_{s\sim\rho}\mathbb{E}_\phi V_1^\star(s).$$

In other words, the (weighted) KL-divergence between $\mathbb{P}_{\Gamma^\star}$ and λ^* is upper bounded by how loose our upper bound in (5) is. In practice however, we care less about a bound on the divergence metric than we do about performance in the control problem. Our next result shows that the variational policy also satisfies a strong sub-linear Bayesian regret bound, *i.e.*, the resulting policy performs well.

4.3 Bayesian Regret Analysis

Learning problem. We consider that the agent interacts with the MDP $\mathcal{M}$ over a (possibly unknown) number of N episodes. We denote by $\mathcal{F}_t$ the sigma-algebra generated by all the history (*i.e.*, sequences of states, actions and rewards) before episode t, with $\mathcal{F}_1 = \emptyset$. We let $\mathbb{E}^t[\cdot] = \mathbb{E}[\cdot \mid \mathcal{F}_t]$, $\mathbb{P}^t(\cdot) = \mathbb{P}(\cdot \mid \mathcal{F}_t)$. In the Bayesian approach where $\mathcal{M}$ is sampled from a known prior ϕ, we want to minimize the *Bayes regret* over $T := NL$ timesteps of an algorithm alg producing policy π^t at each episode t, which is defined as its expected regret under that prior distribution

$$\mathcal{R}_{\mathcal{M}}(\text{alg}, T) := \sum_{t=1}^{N} \mathbb{E}_{s \sim \rho} \left(V_1^\star(s) - V_1^{\pi^t}(s) \right), \qquad \mathcal{BR}_\phi(\text{alg}, T) := \mathbb{E}_{\mathcal{M} \sim \phi} \mathcal{R}_{\mathcal{M}}(\text{alg}, T). \quad (6)$$

We incorporate VAPOR into a learning algorithm by executing at each episode the policy induced by the VAPOR optimization problem solution. It enjoys the following sub-linear Bayesian regret bound.

Theorem 1. *For known P and σ-sub-Gaussian additive reward noise, it holds that* $\mathcal{BR}_\phi(\text{VAPOR}, T) \leq \widetilde{O}(\sigma\sqrt{SAT})$.

In the above $\widetilde{O}$ suppresses log factors. The same regret bound holds for the (intractable) algorithm that uses (1) as the policy each episode.

Corollary 1. *Denote by $\text{alg}_{\Gamma^\star}$ the algorithm that produces policies based on $\mathbb{P}_{\Gamma^\star}^t$ for each episode t using (1). Then, under the same conditions as Theorem 1, we have $\mathcal{BR}_\phi(\text{alg}_{\Gamma^\star}, T) \leq \widetilde{O}(\sigma\sqrt{SAT})$.*

4.4 Interpretation of VAPOR

Inspecting $\mathcal{V}_\phi$ (4) reveals that VAPOR is equivalent to solving a two-player zero-sum game between a 'policy' player $\lambda \in \Lambda(P)$ and a 'temperature' player $\tau \in \mathbb{R}_+^{L,S,A}$. The latter finds the tightest τ that best balances two exploration mechanisms on a per state-action basis: an *optimism* term σ^2/τ that augments the expected reward $\mathbb{E}_\phi r$, and a τ-weighted *entropy regularization* term. The policy player maximizes the entropy-regularized optimistic reward.

The fact that entropy regularization falls out naturally from VAPOR is interesting because the standard 'RL as inference' framework conveniently reveals policy entropy regularization (Section 2.1), which has been widely studied theoretically [44, 20] and empirically to favor exploration in deep RL [41, 26]. The specificity here is that it is with respect to the *occupancy measure* instead of the policy, and it is *adaptively weighted for each state-action pair*. This enables us to obtain an 'RL as inference' framework with entropy regularization that explores provably efficiently. Regularizing with the (weighted) entropy of the occupancy measure is harder to implement in practice, therefore in Appendix E we propose a principled, albeit looser, upper bound of VAPOR that regularizes the optimistic reward with only the (weighted) entropy of the *policy*, rather than the occupancy measure, making the resulting objective amenable to online optimization with policy-gradient techniques.

5 Extension to Unknown Transition Dynamics

So far we have focused on the special case of known transition dynamics P. In this section, we derive a reduction from the case of unknown P to known P. This result implies that *any* algorithm that enjoys a Bayesian regret bound in the known-P special case can be easily converted into one that enjoys a regret bound for the more challenging unknown-P case. Our analysis relies on the following set of commonly used assumptions [46, Asm. 1], [60, Lem. 3], [61, Asm. 2&3].

Assumption 1. (i) *The mean rewards are bounded in $[0, 1]$ almost surely, independent over steps l and σ-sub-Gaussian under ϕ.* (ii) *The state space can be decomposed layerwise as $\mathcal{S} = \mathcal{S}_1 \cup \mathcal{S}_2 \cup \ldots \cup \mathcal{S}_L$.* (iii) *The transition functions are independent Dirichlet under ϕ, with parameter $\alpha_l(s, a) \in \mathbb{R}_+^{S_{l+1}}$ for each (s, a) with $\sum_{s' \in \mathcal{S}_{l+1}} \alpha_l(s, a, s') \geq 1$.*

Algorithm 1 `VAPOR` learning algorithm

For episode $t = 1, 2, \ldots$ **do**

1. Compute expected rewards $\mathbb{E}^t r$, transitions $\mathbb{E}^t P$, uncertainty measure $\widehat{\sigma}^t$

2. Solve `VAPOR` optimization problem $\lambda^t \in \operatorname{argmax}_{\lambda \in \Lambda(\mathbb{E}^t P)} \mathcal{V}_{\widehat{\phi}^t}(\lambda)$ from Equation (4)

3. Execute policy $\pi_l^t(s, a) \propto \lambda_l^t(s, a)$, for $l = 1, \ldots, L$

At a high level, our reduction transfers the uncertainty on the transitions to additional uncertainty on the rewards in the form of carefully defined zero-mean Gaussian noise. It extends the reward perturbation idea of the RLSVI algorithm [61], by leveraging a property of Gaussian-Dirichlet optimism [59] and deriving a new property of Gaussian sub-Gaussian optimism (Appendix D) which allows to bypass the assumption of binary rewards in $\{0, 1\}$ from [61, Asm. 3]. Our reduction implies the following 'dominance' property of the expected $V^\star$ under the transformed and original beliefs.

Lemma 6. *Define the mapping* $\mathcal{T} : \phi \mapsto \widehat{\phi}$ *that transforms the posterior* ϕ *into a distribution* $\widehat{\phi}$ *on the same space, with transition dynamics equal to* $\mathbb{E}_\phi P$ *and rewards distributed as* $\mathcal{N}(\mathbb{E}_\phi r, \widehat{\sigma}^2)$ *with*

$$\widehat{\sigma}_l^2(s, a) := 3.6^2 \sigma_l^2(s, a) + \frac{(L - l)^2}{\sum_{s'} \alpha_l(s, a, s')}.$$

	Original posterior ϕ	Transformed posterior $\widehat{\phi}$
Mean reward r	σ-sub-Gaussian	$\mathcal{N}\left(\mathbb{E}_\phi r, \widehat{\sigma}^2\right)$
Transitions P	Dirichlet(α)	$\mathbb{E}_\phi P$

Then under Assumption 1, it holds that

$$\mathbb{E}_{s \sim \rho} \mathbb{E}_\phi V_1^\star(s) \leq \mathbb{E}_{s \sim \rho} \mathbb{E}_{\widehat{\phi}} V_1^\star(s).$$

Now, let us return to the episodic interaction case and denote by $\phi^t := \phi(\cdot \mid \mathcal{F}_t)$ the posterior at the beginning of episode t and assume that it satisfies Assumption 1. For instance, under additive σ-sub-Gaussian reward noise, we can explicitly set the uncertainty $\widehat{\sigma}^t$ of the transformed posteriors $\widehat{\phi}^t$ as $(\widehat{\sigma}_l^t)^2(s, a) = (3.6^2 \sigma^2 + (L - l)^2)/\max(n_l^t(s, a), 1)$, where $n_l^t(s, a)$ denotes the visitation count to (s, a) at step l before episode t. This brings us to a key result necessary for a general regret bound.

Lemma 7. *Let* alg *be any procedure that maps posterior beliefs to policies, and denote by* $\mathcal{BR}_{\mathcal{T}, \phi}(\mathrm{alg}, T)$ *the Bayesian regret of* alg *where at each episode* $t = 1, \ldots, T$, *the policy and regret are computed by replacing* ϕ^t *with* $\mathcal{T}(\phi^t)$ *(Lemma 6), then under Assumption 1,*

$$\mathcal{BR}_\phi(\mathrm{alg}, T) \leq \mathcal{BR}_{\mathcal{T}, \phi}(\mathrm{alg}, T).$$

Thus if we have an algorithm with a Bayesian regret bound for the case of known transitions P, then we can convert it directly into an algorithm that achieves a regret bound for the case of unknown P, simply by increasing the amount of uncertainty in the posterior of the unknown rewards and replacing the unknown P with its mean when executing the algorithm. Combining Lemma 7 and Theorem 1 yields the following regret bound for `VAPOR` in the more general case (Algorithm 1).

Theorem 2. *Under Assumption 1, it holds that* $\mathcal{BR}_\phi(\texttt{VAPOR}, T) \leq \widetilde{O}(L\sqrt{SAT})$.

The Bayes regret bound in Theorem 2 is within a factor of $\sqrt{L}$ of the known information theoretic lower bound [32, 13], up to constant and log terms. It matches the best known bound for K-learning [46] and Thompson sampling [60]. There exists a complementary line of work deriving minimax-optimal regret bounds in the *frequentist* setting, both in the model-based [3, 40] and model-free [84, 38] cases. We refer to *e.g.*, [21] for discussion on the advantages and disadvantages of the Bayesian and frequentist approaches. Without claiming superiority of either, it is worth highlighting that compared to frequentist algorithms that produce *deterministic* and *non-stationary* policies (*i.e.*, depends on the episode number explicitly), `VAPOR` naturally yields *stochastic* and *stationary* policies.

6   Connections

Thompson Sampling. Thompson sampling (TS) or posterior sampling for RL (PSRL) [76, 73, 58] first *samples* an environment (*i.e.*, rewards and transition dynamics) from the posterior and then computes the optimal policy for this sample to be executed during the episode. Our principled Bayesian inference approach to RL uncovers an alternative view of TS which deepens our understanding of this popular algorithm. The next lemma shows that TS *implicitly* approximates $\mathbb{P}_{\Gamma^\star}$ by sampling, thus tightly connecting it to `VAPOR`'s *explicit* approximation of $\mathbb{P}_{\Gamma^\star}$.

Lemma 8. *Let* λ^{TS} *be the occupancy measure of the* TS *policy, it holds that* $\mathbb{E}[\lambda^{\mathrm{TS}}] = \mathbb{P}_{\Gamma^\star}$.

Plugging this observation into Lemma 4 and
retracing the proof of Theorem 2 immediately
yields regret bounds for TS matching that of
VAPOR. The explicit variational approximation
of $\mathbb{P}_{\Gamma^\star}$ by VAPOR has several advantages over the
implicit sampling-based approximation of $\mathbb{P}_{\Gamma^\star}$
by TS. **(i)** Having direct (approximate) access to
this probability can be desirable in some prac-
tical applications, for example to ensure safety

	TS / PSRL	VAPOR
$\mathbb{P}_{\Gamma^\star}$ approx.	Sample MDP $\mathcal{M}$ and compute $\pi^\star_{\mathcal{M}}$ $\Leftrightarrow \lambda^{\text{TS}} \sim \mathbb{P}_{\Gamma^\star}$ $\Rightarrow \mathbb{E}[\lambda^{\text{TS}}] = \mathbb{P}_{\Gamma^\star}$	Variationally approximate $\lambda^* \approx \mathbb{P}_{\Gamma^\star}$ and compute π^{λ^*}
Exploration mechanism	Stochastic optimism	Explicit optimism + Entropy regularization

constraints or to allocate budgets. **(ii)** TS suffers linear regret in the multi-agent and constrained
cases [51], while we expect suitable modifications of VAPOR to be able to handle these cases, as
suggested in the multi-armed bandit setting [50]. **(iii)** The VAPOR optimization problem can naturally
extend to parametrizing the occupancy measure to be in a certain family (*e.g.*, linear in some basis).
(iv) The objective we use in VAPOR is *differentiable*, opening the door to differentiable computing
architectures such as deep neural network. In contrast, performing TS requires to maintain an explicit
model over MDP parameters [58], which becomes prohibitively expensive as the MDP becomes large.
To alleviate this computational challenge of TS, some works have focused on cheaply generating
approximate posterior samples [56, 54, 61, 53], but it is not yet clear if this approach is better than
the variational approximation we propose.

K-learning. K-learning [46] endows the agent with a risk-seeking exponential utility function
and enjoys the same regret bound as Theorem 2. Its update rule is similar to soft Q-learning
[19, 25, 43, 22], which emerges from inference under Approximation 1 [37]. Although soft Q-
learning ignores epistemic uncertainty and thus suffers linear regret [52], K-learning *learns* a *scalar*
temperature parameter which balances both an optimistic reward and a policy entropy regularization
term. In contrast, VAPOR naturally produces a *separate* risk-seeking parameter for *each state-action*.
This enables a fine-grained control of the exploration-exploitation trade-off depending on the region
of the state-action space, which can make a large difference in practice. In the multi-armed bandit case
it was shown that K-learning and VAPOR coincide when VAPOR is constrained to have all temperature
parameters (denoted τ) equal [50]. This relationship does not hold in the more general MDP case.
While K-learning can be conveniently re-derived as an approximate inference procedure over the
moment generating function of $Q^\star$ [52], VAPOR is motivated from an inference perspective and free
from any assumption on optimality.

Maximum Entropy Exploration. A recent line of work called *maximum entropy exploration*
suggests that in the absence of reward the agent should cover the state-action space as uniformly
as possible by solving a maximum-entropy problem over occupancy measures $\max_{\lambda \in \Lambda(P)} \mathcal{H}(\lambda)$
[29, 9, 83, 77], where $\mathcal{H}$ denotes the entropy summed over steps l. VAPOR can thus be interpreted as
regularizing a reward-driven objective with a maximum entropy exploration term, that is weighted
with vanishing temperatures. In other words, the principle of (weighted) maximum-entropy explo-
ration can be derived by considering a variational approximation to Bayesian state-action optimality.

7 Numerical Experiments

GridWorld. We first study empirically how well VAPOR approximates $\mathbb{P}_{\Gamma^\star}$. Since $\mathbb{E}[\lambda^{\text{TS}}] = \mathbb{P}_{\Gamma^\star}$,
we estimate the latter by averaging over 1000 samples of the (random) TS occupancy measure (we
denote it by $\overline{\lambda}^{\text{TS}}_{(1000)}$). We design simple 10×10 GridWorld MDPs with four cardinal actions, known
dynamics and randomly generated reward. Figure 2 suggests that VAPOR and the TS average output
similar approximations of $\mathbb{P}_{\Gamma^\star}$, thus showing the accuracy of our variational approximation in this
domain. Unlike TS which requires estimating it with many samples, VAPOR approximates $\mathbb{P}_{\Gamma^\star}$ by
only solving a single convex optimization problem.

DeepSea. We now study the learning performance of the VAPOR Algorithm 1 in the hard-exploration
environment of *DeepSea* [61]. In this $L \times L$ grid MDP, the agent starts at the top-left cell and must
reach the lower-right cell. It can move left or right, always descending to the row below. Going left
yields no reward, while going right incurs a small cost of $0.01/L$. The bottom-right cell yields a
reward of 1, so that the optimal policy is to always go right. Local dithering (*e.g.*, Soft Q-learning,
ϵ-greedy) takes time exponential in L, so the agent must perform deep exploration to reach the goal.
Figure 3 shows the time required to 'solve' the problem as a function of the depth L, averaged over
10 seeds. The 'time to solve' is defined as the first episode where the rewarding state has been found

Figure 2: For 3 seeds of randomly generated reward means and noises in a GridWorld, visualization of the timestep-averaged stationary state distribution (*i.e.*, $L^{-1} \sum_{l,a} \lambda_l(s,a)$) for $\lambda^{\texttt{VAPOR}}$ *(left)* and $\overline{\lambda}^{\text{TS}}_{(1000)}$ *(right)*.

Figure 3: Learning time on DeepSea

Figure 4: Median human normalized score across 57 Atari games (with standard errors across 5 seeds).

at least in 10% of the episodes so far [46]. We compare VAPOR to TS / PSRL [58], K-learning [46] and a variant of RLSVI [61] that runs PSRL under the transformed posteriors of Lemma 6. (Several optimistic methods like UCBVI [3] or Optimistic Q-learning [32] were additionally compared by [46] but they performed worse.) We see that VAPOR achieves the lowest learning time as L increases.

Atari. Since VAPOR requires solving a convex optimization problem, it is amenable to online optimization and representing the policy using a deep neural network. In Appendix E, we derive VAPOR-lite, a principled, albeit looser, upper-bound approximation of VAPOR which can be readily incorporated in a policy-gradient agent. Essentially, VAPOR-lite endows a policy-gradient agent with **(i)** an uncertainty reward bonus and **(ii)** an uncertainty-weighted policy entropy regularization (which is thus a *weaker* form of entropy regularization than in the space of occupancy measures). In our experiments, we use an ensemble of reward predictors as uncertainty signal. We investigate the performance of VAPOR-lite on the Atari benchmark [5]. We consider a replay-based actor-critic agent with V-trace off-policy corrections [15] and an actor-learner decomposition [30] (see Appendix F for the full experimental details). We compare this agent without and with added *fixed* policy entropy regularization as commonly used [81, 41], to the same agent with the VAPOR-lite objective. We stress that unlike simply adding entropy regularization, which leads to local dithering and suffers linear regret, VAPOR-lite relies on a principled approach of casting RL as Bayesian inference. Figure 4 shows the performance advantage of augmenting a policy-gradient agent with VAPOR-lite on Atari. It reaches the peak performance of the replay actor-critic agent (resp. with entropy regularization) in about $2\times$ (resp. $1.5\times$) fewer environment frames, for essentially the same computational cost. This advantage comes from the fact that VAPOR-lite leads to deep exploration, which results in finding higher rewarding states and in better cumulative performance. This suggest that further gains could come from deriving a more accurate practical approximation of VAPOR.

8 Conclusion

RL is a statistical inference problem wrapped in a control problem. In this paper, we demonstrated that a single quantity can be used to handle both aspects of the problem — the posterior probability of each state-action being visited under the optimal policy, $\mathbb{P}_{\Gamma^\star}$. We can perform Bayesian inference to compute this, and then use it to generate a control policy that performs efficient exploration. This is a coherent and principled approach to 'RL as inference', rather than the heuristic approaches in prior work which could not compute valid posteriors. Unfortunately, computing $\mathbb{P}_{\Gamma^\star}$ is intractable in practice so we derived a variational approximation that we showed also explores efficiently. We concluded with some numerical experiments showing improved performance in the challenging 'DeepSea' unit test, as well as on the Atari suite. We leave to future work the best way to approximate the variational optimization problem in the case where the policy is parameterized using a deep neural network that is updated using online stochastic gradients.

References

[1] A. Abdolmaleki, J. T. Springenberg, Y. Tassa, R. Munos, N. Heess, and M. Riedmiller. Maximum a posteriori policy optimisation. *arXiv preprint arXiv:1806.06920*, 2018.

[2] P. Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3(Nov):397–422, 2002.

[3] M. G. Azar, I. Osband, and R. Munos. Minimax regret bounds for reinforcement learning. In *International Conference on Machine Learning*, pages 263–272. PMLR, 2017.

[4] M. Bellemare, S. Srinivasan, G. Ostrovski, T. Schaul, D. Saxton, and R. Munos. Unifying count-based exploration and intrinsic motivation. *Advances in neural information processing systems*, 29, 2016.

[5] M. G. Bellemare, Y. Naddaf, J. Veness, and M. Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, 2013.

[6] S. P. Boyd and L. Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

[7] Y. Burda, H. Edwards, A. Storkey, and O. Klimov. Exploration by random network distillation. *arXiv preprint arXiv:1810.12894*, 2018.

[8] C. Bălcău. Weighted entropic perturbation for linear programming. *Analele Universităţii Bucureşti. Matematică-Informatică*, 55, 01 2006.

[9] W. C. Cheung. Exploration-exploitation trade-off in reinforcement learning on online markov decision processes with global concave rewards. *arXiv preprint arXiv:1905.06466*, 2019.

[10] T. M. Cover and J. A. Thomas. Information theory and statistics. *Elements of information theory*, 1(1):279–335, 1991.

[11] S. Diamond and S. Boyd. CVXPY: A Python-embedded modeling language for convex optimization. *Journal of Machine Learning Research*, 17(83):1–5, 2016.

[12] A. Domahidi, E. Chu, and S. Boyd. ECOS: An SOCP solver for embedded systems. In *European Control Conference (ECC)*, pages 3071–3076, 2013.

[13] O. D. Domingues, P. Ménard, E. Kaufmann, and M. Valko. Episodic reinforcement learning in finite mdps: Minimax lower bounds revisited. In *Algorithmic Learning Theory*, pages 578–598. PMLR, 2021.

[14] V. Dwaracherla, Z. Wen, I. Osband, X. Lu, S. M. Asghari, and B. Van Roy. Ensembles for uncertainty estimation: Benefits of prior functions and bootstrapping. *arXiv preprint arXiv:2206.03633*, 2022.

[15] L. Espeholt, H. Soyer, R. Munos, K. Simonyan, V. Mnih, T. Ward, Y. Doron, V. Firoiu, T. Harley, I. Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. In *International conference on machine learning*, pages 1407–1416. PMLR, 2018.

[16] S.-C. Fang and H.-S. J. Tsao. Linear programming with entropic perturbation. *Zeitschrift für Operations Research*, 37(2):171–186, 1993.

[17] M. Fellows, A. Mahajan, T. G. Rudner, and S. Whiteson. Virel: A variational inference framework for reinforcement learning. *Advances in neural information processing systems*, 32, 2019.

[18] C. W. Fox and S. J. Roberts. A tutorial on variational bayesian inference. *Artificial intelligence review*, 38:85–95, 2012.

[19] R. Fox, A. Pakman, and N. Tishby. Taming the noise in reinforcement learning via soft updates. *arXiv preprint arXiv:1512.08562*, 2015.

[20] M. Geist, B. Scherrer, and O. Pietquin. A theory of regularized markov decision processes. In *International Conference on Machine Learning*, pages 2160–2169. PMLR, 2019.

[21] M. Ghavamzadeh, S. Mannor, J. Pineau, A. Tamar, et al. Bayesian reinforcement learning: A survey. *Foundations and Trends® in Machine Learning*, 8(5-6):359–483, 2015.

[22] J. Grau-Moya, F. Leibfried, and P. Vrancx. Soft Q-learning with mutual-information regularization. In *International conference on learning representations*, 2019.

[23] R. M. Gray. *Entropy and information theory*. Springer Science & Business Media, 2011.

[24] D. Grytskyy, J. Ramírez-Ruiz, and R. Moreno-Bote. A general markov decision process formalism for action-state entropy-regularized reward maximization. *arXiv preprint arXiv:2302.01098*, 2023.

[25] T. Haarnoja, H. Tang, P. Abbeel, and S. Levine. Reinforcement learning with deep energy-based policies. In *International conference on machine learning*, pages 1352–1361. PMLR, 2017.

[26] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pages 1861–1870. PMLR, 2018.

[27] S. Han and Y. Sung. Diversity actor-critic: Sample-aware entropy regularization for sample-efficient exploration. In *International Conference on Machine Learning*, pages 4018–4029. PMLR, 2021.

[28] B. Hao and T. Lattimore. Regret bounds for information-directed reinforcement learning. *arXiv preprint arXiv:2206.04640*, 2022.

[29] E. Hazan, S. Kakade, K. Singh, and A. Van Soest. Provably efficient maximum entropy exploration. In *International Conference on Machine Learning*, pages 2681–2691. PMLR, 2019.

[30] M. Hessel, M. Kroiss, A. Clark, I. Kemaev, J. Quan, T. Keck, F. Viola, and H. van Hasselt. Podracer architectures for scalable reinforcement learning. *arXiv preprint arXiv:2104.06272*, 2021.

[31] M. Jaggi. Revisiting frank-wolfe: Projection-free sparse convex optimization. In *International conference on machine learning*, pages 427–435. PMLR, 2013.

[32] C. Jin, Z. Allen-Zhu, S. Bubeck, and M. I. Jordan. Is Q-learning provably efficient? *Advances in neural information processing systems*, 31, 2018.

[33] H. Juergensen and D. E. Matthews. Entropy and higher moments of information. *Journal of Universal Computer Science*, 16(5):749–794, 2010.

[34] H. J. Kappen, V. Gómez, and M. Opper. Optimal control as a graphical model inference problem. *Machine learning*, 87:159–182, 2012.

[35] M. Kearns and S. Singh. Near-optimal reinforcement learning in polynomial time. *Machine learning*, 49:209–232, 2002.

[36] L. Lee, B. Eysenbach, E. Parisotto, E. Xing, S. Levine, and R. Salakhutdinov. Efficient exploration via state marginal matching. *arXiv preprint arXiv:1906.05274*, 2019.

[37] S. Levine. Reinforcement learning and control as probabilistic inference: Tutorial and review. *arXiv preprint arXiv:1805.00909*, 2018.

[38] G. Li, L. Shi, Y. Chen, Y. Gu, and Y. Chi. Breaking the sample complexity barrier to regret-optimal model-free reinforcement learning. *Advances in Neural Information Processing Systems*, 34:17762–17776, 2021.

[39] C. E. Luis, A. G. Bottero, J. Vinogradska, F. Berkenkamp, and J. Peters. Model-based uncertainty in value functions. *arXiv preprint arXiv:2302.12526*, 2023.

[40] P. Ménard, O. D. Domingues, X. Shang, and M. Valko. UCB momentum Q-learning: Correcting the bias without forgetting. In *International Conference on Machine Learning*, pages 7609–7618. PMLR, 2021.

[41] V. Mnih, A. P. Badia, M. Mirza, A. Graves, T. Lillicrap, T. Harley, D. Silver, and K. Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pages 1928–1937. PMLR, 2016.

[42] M. Mutti, L. Pratissoli, and M. Restelli. Task-agnostic exploration via policy gradient of a non-parametric state entropy estimate. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 9028–9036, 2021.

[43] O. Nachum, M. Norouzi, K. Xu, and D. Schuurmans. Bridging the gap between value and policy based reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 2772–2782, 2017.

[44] G. Neu, A. Jonsson, and V. Gómez. A unified view of entropy-regularized markov decision processes. *arXiv preprint arXiv:1705.07798*, 2017.

[45] B. O'Donoghue. Operator splitting for a homogeneous embedding of the linear complementarity problem. *SIAM Journal on Optimization*, 31(3):1999–2023, 2021.

[46] B. O'Donoghue. Variational Bayesian reinforcement learning with regret bounds. *Advances in Neural Information Processing Systems*, 34:28208–28221, 2021.

[47] B. O'Donoghue. On the connection between Bregman divergence and value in regularized markov decision processes. *arXiv preprint arXiv:2210.12160*, 2022.

[48] B. O'Donoghue. Efficient exploration via epistemic-risk-seeking policy optimization. *arXiv preprint arXiv:2302.09339*, 2023.

[49] B. O'Donoghue, E. Chu, N. Parikh, and S. Boyd. Conic optimization via operator splitting and homogeneous self-dual embedding. *Journal of Optimization Theory and Applications*, 169(3):1042–1068, June 2016.

[50] B. O'Donoghue and T. Lattimore. Variational Bayesian optimistic sampling. *Advances in Neural Information Processing Systems*, 34:12507–12519, 2021.

[51] B. O'Donoghue, T. Lattimore, and I. Osband. Matrix games with bandit feedback. In *Uncertainty in Artificial Intelligence*, pages 279–289. PMLR, 2021.

[52] B. O'Donoghue, I. Osband, and C. Ionescu. Making sense of reinforcement learning and probabilistic inference. In *International Conference on Learning Representations*, 2020.

[53] B. O'Donoghue, I. Osband, R. Munos, and V. Mnih. The uncertainty Bellman equation and exploration. In *International Conference on Machine Learning*, pages 3836–3845, 2018.

[54] I. Osband. *Deep Exploration via Randomized Value Functions*. PhD thesis, Stanford University, 2016.

[55] I. Osband, J. Aslanides, and A. Cassirer. Randomized prior functions for deep reinforcement learning. *Advances in Neural Information Processing Systems*, 31, 2018.

[56] I. Osband, C. Blundell, A. Pritzel, and B. Van Roy. Deep exploration via bootstrapped DQN. In *Advances In Neural Information Processing Systems*, pages 4026–4034, 2016.

[57] I. Osband, Y. Doron, M. Hessel, J. Aslanides, E. Sezener, A. Saraiva, K. McKinney, T. Lattimore, C. Szepesvari, S. Singh, et al. Behaviour suite for reinforcement learning. *arXiv preprint arXiv:1908.03568*, 2019.

[58] I. Osband, D. Russo, and B. Van Roy. (more) efficient reinforcement learning via posterior sampling. *Advances in Neural Information Processing Systems*, 26, 2013.

[59] I. Osband and B. Van Roy. Gaussian-dirichlet posterior dominance in sequential learning. *arXiv preprint arXiv:1702.04126*, 2017.

[60] I. Osband and B. Van Roy. Why is posterior sampling better than optimism for reinforcement learning? In *International conference on machine learning*, pages 2701–2710. PMLR, 2017.

[61] I. Osband, B. Van Roy, D. J. Russo, and Z. Wen. Deep exploration via randomized value functions. *Journal of Machine Learning Research*, 20:1–62, 2019.

[62] G. Ostrovski, M. G. Bellemare, A. Oord, and R. Munos. Count-based exploration with neural density models. In *International conference on machine learning*, pages 2721–2730. PMLR, 2017.

[63] D. Pathak, P. Agrawal, A. A. Efros, and T. Darrell. Curiosity-driven exploration by self-supervised prediction. In *International conference on machine learning*, pages 2778–2787. PMLR, 2017.

[64] J. Peters, K. Mulling, and Y. Altun. Relative entropy policy search. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 24, pages 1607–1612, 2010.

[65] M. L. Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

[66] K. Rawlik, M. Toussaint, and S. Vijayakumar. On stochastic optimal control and reinforcement learning by approximate inference. *Proceedings of Robotics: Science and Systems VIII*, 2012.

[67] D. Russo and B. Van Roy. Learning to optimize via information-directed sampling. *Advances in Neural Information Processing Systems*, 27, 2014.

[68] D. Russo and B. Van Roy. An information-theoretic analysis of thompson sampling. *The Journal of Machine Learning Research*, 17(1):2442–2471, 2016.

[69] D. J. Russo, B. Van Roy, A. Kazerouni, I. Osband, Z. Wen, et al. A tutorial on thompson sampling. *Foundations and Trends® in Machine Learning*, 11(1):1–96, 2018.

[70] T. Schaul, J. Quan, I. Antonoglou, and D. Silver. Prioritized experience replay. *arXiv preprint arXiv:1511.05952*, 2015.

[71] M. J. Schervish. *Theory of statistics*. Springer Science & Business Media, 2012.

[72] S. A. Serrano. *Algorithms for unsymmetric cone optimization and an implementation for problems with the exponential cone*. PhD thesis, Stanford University, 2015.

[73] M. Strens. A bayesian framework for reinforcement learning. In *ICML*, volume 2000, pages 943–950, 2000.

[74] R. S. Sutton and A. G. Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[75] J. Tarbouriech and A. Lazaric. Active exploration in markov decision processes. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 974–982. PMLR, 2019.

[76] W. R. Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3-4):285–294, 1933.

[77] D. Tiapkin, D. Belomestny, D. Calandriello, E. Moulines, R. Munos, A. Naumov, P. Perrault, Y. Tang, M. Valko, and P. Menard. Fast rates for maximum entropy exploration. *arXiv preprint arXiv:2303.08059*, 2023.

[78] E. Todorov. Linearly-solvable markov decision problems. *Advances in neural information processing systems*, 19, 2006.

[79] E. Todorov. Efficient computation of optimal actions. *Proceedings of the national academy of sciences*, 106(28):11478–11483, 2009.

[80] M. J. Wainwright, M. I. Jordan, et al. Graphical models, exponential families, and variational inference. *Foundations and Trends® in Machine Learning*, 1(1–2):1–305, 2008.

[81] R. J. Williams and J. Peng. Function optimization using connectionist reinforcement learning algorithms. *Connection Science*, 3(3):241–268, 1991.

[82] H. Yu, H. Zhang, and W. Xu. Do you need the entropy reward (in practice)? *arXiv preprint arXiv:2201.12434*, 2022.

[83] T. Zahavy, B. O'Donoghue, G. Desjardins, and S. Singh. Reward is enough for convex mdps. *Advances in Neural Information Processing Systems*, 34:25746–25759, 2021.

[84] Z. Zhang, Y. Zhou, and X. Ji. Almost optimal model-free reinforcement learning via reference-advantage decomposition. *Advances in Neural Information Processing Systems*, 33:15198–15207, 2020.

[85] B. D. Ziebart. *Modeling purposeful adaptive behavior with the principle of maximum causal entropy*. Carnegie Mellon University, 2010.

Appendix

Table of Contents

 # A   Graphical Models

(a) graphical model of the standard
‘RL as inference’ framework [37]

(b) graphical model for principled
Bayesian ‘RL as inference’

Figure 5: **(a)** In the standard ‘RL as inference’ framework[1], the binary random variables of state-action optimality[2] $\boldsymbol{\Gamma}^\star$ are *independent* and *observed*, equal one with probability proportional to the exponentiated reward, i.e., $\mathbb{P}(\Gamma_l^\star = 1) \propto \exp(\mathbf{r}_l)$. This assumption is arbitrary and ignores the role of uncertainty and exploration. **(b)** In our model, only rewards $\mathbf{r}$ are observed, with *unobserved* binary optimality variables $\boldsymbol{\Gamma}^\star$ and unobserved optimal values $\mathbf{Q}^\star$. $\mathbf{Q}_l^\star$ depends on current reward $\mathbf{r}_l$ and future $\mathbf{Q}_{l+1}^\star$, and determines action optimality $\pi_l^\star$. $\Gamma_l^\star$ depends on prior state-action optimality $\boldsymbol{\Gamma}_{l-1}^\star$ and current action optimality $\pi_l^\star$. ‘Optimality’ thus propagates both in a *backward* way (via $\mathbf{Q}_l^\star$) and a *forward* way (via $\boldsymbol{\Gamma}_l^\star$). Refraining from any modeling assumption on $\boldsymbol{\Gamma}^\star$, we derive a variational approximation of the posterior probability of $\boldsymbol{\Gamma}^\star$ which yields an algorithm that explores efficiently.

---

[2]There exist other approaches to the ‘RL as inference’ perspective, such as the VIREL framework [17], that provide alternative benefits yet do not offer any principled guarantees either.

[2]In the main text, we use the terminology of *events* but note that events can be seen as *binary random variables* by taking the indicator function of the event.

B Properties of the `VAPOR` Optimization Problem

The `VAPOR` optimization problem is an exponential cone program that can be solved efficiently using modern optimization methods [49, 12, 72, 45]. In Appendix B.1, we show that its dual is a convex optimization problem that is *unconstrained* in a 'value' variable and a 'temperature' variable. In Appendix B.2, we relate `VAPOR` to *message passing*, a popular technique to perform inference in graphical models [80], by showing that `VAPOR` can be cast as passing some forward and backward messages back and forth.

B.1 Dual Problem of `VAPOR`

We derive the dual problem of the `VAPOR` optimization problem (5) and show that it is a convex optimization problem in a 'value' variable $V \in \mathbb{R}^{L,S} \coloneqq \{\mathbb{R}^S\}_{l=1}^L$ and a 'temperature' variable $\tau \in \mathbb{R}_+^{L,S,A}$. Even though the 'primal' admits flow constraints in λ, this dual is *unconstrained* in V (the only constraint is the non-negativity of τ). In the case of unknown P (Section 5), the dual is the same as in Lemma 9 except that P is replaced by $\mathbb{E}_\phi P$ and the uncertainty σ is replaced by $\hat{\sigma}$.

Lemma 9. *The $\lambda^* \in \Lambda(P)$ solving the `VAPOR` optimization problem (5) is unique and satisfies*

$$\lambda_l^*(s, a) = \exp\left(\frac{\delta_{V^*, \tau^*, l}(s, a)}{\tau_l(s, a)} - 1\right),$$

where we define the 'advantage' function

$$\delta_{V^*, \tau^*, l}(s, a) = \mathbb{E}_\phi r_l(s, a) + \frac{\sigma_l^2(s, a)}{2\tau_l^*(s, a)} + \sum_{s'} P_l(s' \mid s, a) V_{l+1}^*(s') - V_l^*(s),$$

and where V^*, τ^* minimize the (convex) dual function

$$\min_{V \in \mathbb{R}^{L,S}} \min_{\tau \in \mathbb{R}_+^{L,S,A}} \left\{ \sum_s \rho(s) V_1(s) + \sum_{l,s,a} \tau_l(s, a) \exp\left(\frac{\delta_{V, \tau, l}(s, a)}{\tau_l(s, a)} - 1\right) \right\}. \qquad (7)$$

The induced policy π^* is uniquely defined as

$$\pi_l^*(s, a) = \frac{\exp\left(\frac{\delta_{V^*, \tau^*, l}(s, a)}{\tau_l^*(s, a)} - 1\right)}{\sum_{a'} \exp\left(\frac{\delta_{V^*, \tau^*, l}(s, a')}{\tau_l^*(s, a')} - 1\right)}$$

if the denominator is positive, otherwise $\pi_l^*(s, \cdot)$ can be any distribution.

Proof. The proof follows from applying the method of Lagrange multipliers to the `VAPOR` optimization problem using the definition of $\mathcal{V}$ in (4). Derivations of dual problems of related optimization problems in the space of occupancy measures can be found in *e.g.*, [64, 24]. Note that for a fixed temperature function $\tau \in \mathbb{R}_+^{L,S,A}$, `VAPOR` is an instance of linear programming with weighted entropic perturbation, which is a class of optimization problems shown to admit an unconstrained convex dual [8, 16]. $\qquad \square$

B.2 Message Passing View of `VAPOR`

Message passing is a popular technique to perform inference in graphical models [80]. In fact, as shown in [37, Section 2.3], the standard 'RL as inference' framework (Section 2.1) can recover the optimal policy using standard sum-product message passing, relying on a single backward message pass. While `VAPOR` does not have such a simplified derivation, the next lemma shows that it can be cast as passing some forward and backward messages back and forth. In this view, a backward message amounts to computing the optimal policy for a given reward (via backward induction), and a forward message amounts to computing the associated stationary state distribution (via the flow equations). This view stems from iteratively solving `VAPOR` using the Frank-Wolfe (a.k.a. conditional gradient) algorithm, where an update is equivalent to solving an MDP [29, 75, 83].

Lemma 10. *For any accuracy $\varepsilon > 0$, there exist forward-backward messages such that after* $\text{poly}(S, A, L, \sigma_{\max}, \varepsilon^{-1})$ *passes they output a $\lambda^{MP} \in \Lambda(P)$ with $\max_{\lambda \in \Lambda(P)} \mathcal{V}_\phi(\lambda) - \mathcal{V}_\phi(\lambda^{MP}) \le \varepsilon$.*

Algorithm 2 Frank-Wolfe algorithm for the `VAPOR` optimization problem (Lemma 10)

Require: Accuracy level $\varepsilon > 0$

    Set the smoothing parameter $\delta = \varepsilon/(\sigma_{\max}LSA)$

    Define $\mathcal{V}_\delta(\lambda) \coloneqq \sum_{l,s,a} \lambda_l(s,a)\left[\mathbb{E}r_l(s,a) + \sigma_l(s,a)\sqrt{-2(\log(\lambda_l(s,a) + \delta) + \delta)}\right]$

    Set the number of iterations $K = (\sigma_{\max}L\varepsilon^{-1})^5(SA)^4$

    Initialize any $\lambda^{(0)} \in \Lambda$

    for iterations $k = 1, 2, \ldots, K$ **do**

        Backward message pass: Compute the optimal policy $\pi^{(k-1)}$ for the reward $\nabla\mathcal{V}_\delta(\lambda^{(k-1)})$

        Forward message pass: Compute $d^{(k-1)}$ the stationary state distribution induced by $\pi^{(k-1)}$, *i.e.*,

$$d_1^{(k-1)}(s) = \rho(s), \quad d_{l+1}^{(k-1)}(s') = \sum_{s,a} P_l(s' \mid s,a)\pi_l^{(k-1)}(s,a)d_l(s)$$

        Combine: Compute for step size $\gamma_k = \frac{2}{k+1}$ the occupancy measure

$$\lambda_l^{(k)}(s,a) = (1 - \gamma_k)\lambda_l^{(k-1)}(s,a) + \gamma_k d_l^{(k-1)}(s)\pi_l^{(k-1)}(s,a)$$

    end for

    return $\lambda^{(K)}$

Proof. We consider in Algorithm 2 the Frank-Wolfe algorithm applied to maximizing the smoothed proxy V_δ over $\lambda \in \Lambda$ (throughout the proof we write $\Lambda = \Lambda(P)$ and omit the dependence on the beliefs ϕ for ease of notation). Each iteration represents one forward-backward message pass: the backward message computes the optimal policy for the reward given by the gradient of the objective V_δ evaluated at the current iterate (via backward induction), while the forward message computes the associated stationary state distribution (via the flow equations). Note that the chosen number of iterations K is polynomial in the inverse of the accuracy level ε^{-1}, the maximum uncertainty $\sigma_{\max} \coloneqq \max_{l,s,a} \sigma_l(s,a)$ and the MDP parameters L, S, A. To prove the ε-convergence in the original objective $\mathcal{V}$, we decompose

$$\mathcal{V}(\lambda^*) - \mathcal{V}(\lambda^{(K)}) = \mathcal{V}(\lambda^*) - \max_{\lambda\in\Lambda} V_\delta(\lambda) + \max_{\lambda\in\Lambda} V_\delta(\lambda) - \mathcal{V}_\delta(\lambda^{(K)}) + \mathcal{V}_\delta(\lambda^{(K)}) - \mathcal{V}(\lambda^{(K)})$$

$$\leq \underbrace{\mathcal{V}(\lambda^*) - V_\delta(\lambda^*)}_{①} + \underbrace{\max_{\lambda\in\Lambda} V_\delta(\lambda) - \mathcal{V}_\delta(\lambda^{(K)})}_{②} + \underbrace{\mathcal{V}_\delta(\lambda^{(K)}) - \mathcal{V}(\lambda^{(K)})}_{③}.$$

① and ③ can be bounded using the fact that for any $\lambda \in \Lambda$, $|\,\mathcal{V}_\delta(\lambda) - \mathcal{V}(\lambda)\,| \leq \sigma_{\max}LSA\delta$. ② can be bounded from the Frank-Wolfe convergence rate for smooth objective functions [31], since the proxy $\mathcal{V}_\delta$ is C_δ-smooth by construction, with $C_\delta = O(\sigma_{\max}\delta^{-4})$. As a result, $② \leq M_\delta/(K+2)$, where M_δ is the curvature constant of $\mathcal{V}_\delta$ over Λ, with $M_\delta \leq C_\delta \operatorname{diam}^2(\Lambda)$, where $\operatorname{diam}^2(\Lambda) \leq 2L$. Therefore, choosing $\delta = \varepsilon/(\sigma_{\max}LSA)$ and $K = (\sigma_{\max}L\varepsilon^{-1})^5(SA)^4$ gives

$$\mathcal{V}(\lambda^*) - \mathcal{V}(\lambda^{(K)}) \leq O\left(\sigma_{\max}LSA\delta + \frac{\sigma_{\max}L}{\delta^4 K}\right) = O(\varepsilon).$$

$\square$

 ## C Proofs

 ### C.1 Proof of Lemma 1

 Lemma 1. *For known P, it holds that* $\mathbb{P}_{\Gamma^\star} := \{\mathbb{P}_\phi(\Gamma_l^\star)\}_{l=1}^L \in \Lambda(P)$.

 Proof. We omit the dependence on the beliefs ϕ for ease of notation. At the initial step,

$$\mathbb{P}(\Gamma_1^\star(s,a)) = \mathbb{P}(\{s_1 = s\} \cap \{\pi_1^\star(s) = a\}) = \rho(s)\mathbb{P}(\pi_1^\star(s) = a),$$

 and from Bayes' rule and the fact that P is assumed known, we have the recursive equation

$$
\begin{aligned}
\mathbb{P}\left(\Gamma_{l+1}^\star(s',a')\right) &= \mathbb{P}\left(\Gamma_{l+1}^\star(s') \cap \{\pi_{l+1}^\star(s') = a'\}\right)\\
&= \mathbb{P}\left(\pi_{l+1}^\star(s') = a' \mid \Gamma_{l+1}^\star(s')\right)\mathbb{P}\left(\Gamma_{l+1}^\star(s')\right)\\
&= \mathbb{P}\left(\pi_{l+1}^\star(s') = a' \mid \Gamma_{l+1}^\star(s')\right)\sum_{s,a}\mathbb{P}\left(\Gamma_l^\star(s,a) \cap \{s_{l+1} = s'\}\right)\\
&= \mathbb{P}\left(\pi_{l+1}^\star(s') = a' \mid \Gamma_{l+1}^\star(s')\right)\sum_{s,a}\mathbb{P}\left(\{s_{l+1} = s'\} \mid \Gamma_l^\star(s,a)\right)\mathbb{P}\left(\Gamma_l^\star(s,a)\right)\\
&= \mathbb{P}\left(\pi_{l+1}^\star(s') = a' \mid \Gamma_{l+1}^\star(s')\right)\sum_{s,a}P_l(s' \mid s,a)\mathbb{P}\left(\Gamma_l^\star(s,a)\right).
\end{aligned}
\tag{8}
$$

 Summing (8) over $a' \in \mathcal{A}$ implies the non-negativity and flow conservation properties of $\mathbb{P}_{\Gamma^\star}$.
 Moreover, when $\sum_{a' \in \mathcal{A}}\mathbb{P}(\Gamma_l^\star(s,a')) > 0$, it holds that

$$\mathbb{P}(\pi_l^\star(s) = a \mid \Gamma_l^\star(s)) = \frac{\mathbb{P}(\Gamma_l^\star(s,a))}{\sum_{a' \in \mathcal{A}}\mathbb{P}(\Gamma_l^\star(s,a'))},$$

 which corresponds to (1). $\qquad\square$

 ### C.2 Proof of Lemma 2

 Lemma 2. *We have* $\mathbb{E}_{s\sim\rho}\mathbb{E}_\phi V_1^\star(s) = \sum_{l,s,a}\mathbb{P}_\phi(\Gamma_l^\star(s,a))\mathbb{E}_\phi[r_l(s,a) \mid \Gamma_l^\star(s,a)]$.

 Proof. Denote by $Z^\star$ the random variable of the total reward accumulated along a single rollout of
 the optimal policy $\pi^\star$, and let $Z_l^\star(s)$ be the total reward accumulated by $\pi^\star$ from state s at layer l and
 $Z_l^\star(s,a)$ be the total reward accumulated by $\pi^\star$ from state s at layer l after taking action a. We can
 write the total reward accumulated as

$$Z^\star = \sum_s Z_1^\star(s)\mathbb{1}\{s_1 = s\} = \sum_s Z_1^\star(s)\mathbb{1}\{\Gamma_1^\star(s)\}.$$

 Now for arbitrary $l \in \{1,\dots,L-1\}$,

$$
\begin{aligned}
\sum_s Z_l^\star(s)\mathbb{1}\{\Gamma_l^\star(s)\} &= \sum_{s,a}Z_l^\star(s,a)\mathbb{1}\{\pi_l^\star(s) = a\}\mathbb{1}\{\Gamma_l^\star(s)\}\\
&= \sum_{s,a}Z_l^\star(s,a)\mathbb{1}\{\Gamma_l^\star(s,a)\}\\
&= \sum_{s,a}R_l(s,a)\mathbb{1}\{\Gamma_l^\star(s,a)\} + \sum_{s,a}\mathbb{1}\{\Gamma_l^\star(s,a)\}\sum_{s'}Z_{l+1}^\star(s')\mathbb{1}\{s_{l+1} = s'\}\\
&= \sum_{s,a}R_l(s,a)\mathbb{1}\{\Gamma_l^\star(s,a)\} + \sum_{s'}Z_{l+1}^\star(s')\mathbb{1}\{\Gamma_{l+1}^\star(s')\},
\end{aligned}
$$

 and unrolling we obtain

$$Z^\star = \sum_{l,s,a}R_l(s,a)\mathbb{1}\{\Gamma_l^\star(s,a)\}.$$

657 Denoting by $\mathcal{F}_r$ the sigma-algebra generated by r, it holds from the tower property of conditional
658 expectation that

$$
\begin{aligned}
\mathbb{E}_\phi[R_l(s,a)\mathbb{1}\{\Gamma_l^\star(s,a)\}] &= \mathbb{E}_\phi[\mathbb{E}_\phi[R_l(s,a)\mathbb{1}\{\Gamma_l^\star(s,a)\} \mid \mathcal{F}_r]] \\
&= \mathbb{E}_\phi[\mathbb{E}_\phi[R_l(s,a) \mid \mathcal{F}_r]\mathbb{E}_\phi[\mathbb{1}\{\Gamma_l^\star(s,a)\} \mid \mathcal{F}_r]] \\
&= \mathbb{E}_\phi[r_l(s,a)\mathbb{1}\{\Gamma_l^\star(s,a)\}].
\end{aligned}
$$

659 Therefore it holds that

$$
\mathbb{E}_{s\sim\rho}\mathbb{E}_\phi V^\star(s) = \sum_{l,s,a} \mathbb{E}_\phi\left[r_l(s,a)\mathbb{1}\{\Gamma_l^\star(s,a)\}\right].
$$

660 Now note that

$$
\begin{aligned}
\mathbb{E}_\phi\left[r_l(s,a)\mathbb{1}\{\Gamma_l^\star(s,a)\}\right] &= \int_\mathbb{R} r\mathbb{P}_\phi(r_l(s,a) = r, \Gamma_l^\star(s,a)) \\
&= \int_\mathbb{R} r\mathbb{P}_\phi(r_l(s,a) = r \mid \Gamma_l^\star(s,a))\mathbb{P}_\phi(\Gamma_l^\star(s,a)) \\
&= \mathbb{E}_\phi\left[r_l(s,a) \mid \Gamma_l^\star(s,a)\right]\mathbb{P}_\phi(\Gamma_l^\star(s,a)).
\end{aligned}
$$

661 Putting it all together,

$$
\mathbb{E}_{s\sim\rho}\mathbb{E}_\phi V^\star(s) = \sum_{l,s,a} \mathbb{P}_\phi(\Gamma_l^\star(s,a))\mathbb{E}_\phi\left[r_l(s,a) \mid \Gamma_l^\star(s,a)\right].
$$

662 $\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\quad\square$

C.3 Proof of Lemma 3

664 We prove in Lemma 11 a generalization of Lemma 3 that does not rely on the assumption of σ-
665 sub-Gaussian mean rewards. It builds on the Donsker-Varadhan representation [23, 68, 67, 28]
666 (Proposition 1), see also [50, Theorem 1]. We denote by $\mathrm{KL}(\cdot \,||\, \cdot)$ the Kullback–Leibler divergence,
667 by $\Psi_X : \mathbb{R} \to \mathbb{R}$ the cumulant generating function of random variable $X - \mathbb{E}X$ and by $f^\star : \mathbb{R} \to \mathbb{R}$
668 the convex conjugate of function $f : \mathbb{R} \to \mathbb{R}$, *i.e.*,

$$
\Psi_X(\beta) := \log\mathbb{E}\exp(\beta(X - \mathbb{E}X)), \qquad f^\star(y) := \sup_{x\in\mathbb{R}}\{xy - f(x)\}.
$$

669 **Lemma 11.** *Let $X : \Omega \to \mathbb{R}$ be a random variable on $(\Omega, \mathcal{F}, \mathbb{P})$ satisfying $X \in L_1$ such that the*
670 *interior of the domain of Ψ_X is non-empty, and let $B \in \mathcal{F}$ be an event with $\mathbb{P}(B) > 0$. Then,*[3]

$$
\begin{aligned}
\mathbb{E}\left[X \mid B\right] &\le \mathbb{E}X + (\Psi_X^*)^{-1}\left(\mathrm{KL}(\mathbb{P}(X \in \cdot \mid B) \,||\, \mathbb{P}(X \in \cdot))\right) \\
&\le \mathbb{E}X + (\Psi_X^*)^{-1}\left(-\log\mathbb{P}(B)\right).
\end{aligned}
$$

671 *Proof.* Applying Proposition 1 to $\lambda(X - \mathbb{E}X)$ for arbitrary $\lambda \in \mathbb{R}_+$ with the choices $Q := \mathbb{P}(X \in \cdot)$,
672 $P := \mathbb{P}(X \in \cdot \mid B)$ gives

$$
\begin{aligned}
\mathrm{KL}(\mathbb{P}(X \in \cdot \mid B) \,||\, \mathbb{P}(X \in \cdot)) &\ge \sup_{\lambda\in\mathbb{R}_+}\{\lambda\mathbb{E}[(X - \mathbb{E}X) \mid B] - \log\mathbb{E}[\exp\lambda(X - \mathbb{E}X)]\} \\
&= \sup_{\lambda\in\mathbb{R}_+}\{\lambda(\mathbb{E}[X \mid B] - \mathbb{E}X) - \Psi_X(\lambda)\} \\
&= \Psi_X^\star(\mathbb{E}[X \mid B] - \mathbb{E}X),
\end{aligned}
$$

673 by definition of Ψ_X the cumulant generating function of $X - \mathbb{E}X$ and by definition of the convex
674 conjugate of Ψ_X which satisfies $\Psi_X^\star(y) = \sup_{\lambda\ge0}\{\lambda y - \Psi_X(\lambda)\}$. Since $\Psi_X^\star$ is strictly increasing,
675 its inverse $(\Psi_X^*)^{-1}$ is also strictly increasing, so

$$
\mathbb{E}[X \mid B] - \mathbb{E}X \le (\Psi_X^*)^{-1}\left(\mathrm{KL}(\mathbb{P}(X \in \cdot \mid B) \,||\, \mathbb{P}(X \in \cdot))\right),
$$

676 which proves the first inequality. We now derive the second inequality. Note the definition of the KL
677 divergence

$$
\mathrm{KL}(P \,||\, Q) = \int \log\left(\frac{dP}{dQ}\right) dP,
$$

---

[3]If $\Psi_X = 0$, then we take $(\Psi_X^*)^{-1} = 0$.

678 where $\frac{dP}{dQ}$ is the Radon-Nikodym derivative of P with respect to Q. We can then write

$$
\begin{aligned}
\mathrm{KL}(\mathbb{P}(X \in \cdot \mid B) \,||\, \mathbb{P}(X \in \cdot)) &= \int \log \frac{d\mathbb{P}(X \in \cdot \mid B)}{d\mathbb{P}(X \in \cdot)} d\mathbb{P}(X \in \cdot \mid B) \\
&\stackrel{\text{(i)}}{=} \int \log \frac{\mathbb{P}(X \in \cdot \mid B)}{\mathbb{P}(X \in \cdot)} d\mathbb{P}(X \in \cdot \mid B) \\
&\stackrel{\text{(ii)}}{=} \int \log \frac{\mathbb{P}(B \mid X \in \cdot)}{\mathbb{P}(B)} d\mathbb{P}(X \in \cdot \mid B) \\
&= \int \underbrace{\log \mathbb{P}(B \mid X \in \cdot)}_{\leq 0} d\mathbb{P}(X \in \cdot \mid B) - \log \mathbb{P}(B) \\
&\leq -\log \mathbb{P}(B),
\end{aligned}
$$

679 where (i) is from the formulation of Bayes' theorem stated in [71, Theorem 1.31] and (ii) applies
680 Bayes' rule. □

681 **Proposition 1** (Variational form of the KL-Divergence given in Theorem 5.2.1 of [23])**.** *Fix two*
682 *probability distributions P and Q such that P is absolutely continuous with respect to Q. Then,*

$$
\mathrm{KL}(P \,||\, Q) = \sup_{X} \left\{ \mathbb{E}_P[X] - \log \mathbb{E}_Q[\exp X] \right\},
$$

683 *where $\mathbb{E}_P$ and $\mathbb{E}_Q$ denote the expectation operator under P and Q respectively, and the supremum is*
684 *taken over all real valued random variables X such that $\mathbb{E}_P[X]$ is well defined and $\mathbb{E}_Q[\exp X] < \infty$.*
685

686 *Proof of Lemma 3.* Under the $\sigma_l(s, a)$-sub-Gaussian noise assumption of $r_l(s, a)$, we can bound the
687 cumulant generating function of $r_l(s, a)$ as

$$
\Psi_{r_l(s,a)}(\beta) \leq \frac{\beta^2 \sigma_l(s,a)^2}{2}.
$$

688 We therefore have that for any $y \geq 0$,

$$
(\Psi_{r_l(s,a)}^*)^{-1}(y) = \inf_{\tau_l(s,a) > 0} \left\{ \tau_l(s,a) \Psi_{r_l(s,a)}(1/\tau_l(s,a)) + \tau_l(s,a) y \right\} \leq \sigma_l(s,a) \sqrt{2y}. \tag{9}
$$

689 Plugging this bound into Lemma 11 yields Lemma 3. □

C.4 Proof of Lemma 4

691 **Lemma 4.** *For known P and σ-sub-Gaussian r, we have*

$$
\mathbb{E}_{s \sim \rho} \mathbb{E}_\phi V_1^\star(s) \leq \mathcal{V}_\phi(\mathbb{P}_{\Gamma^\star}) \leq \underbrace{\max_{\lambda \in \Lambda(P)} \mathcal{V}_\phi(\lambda)}_{\text{VAPOR}}, \tag{5}
$$

693 *where* VAPOR *is a concave optimization problem.*

694 *Proof.* Combining Lemmas 2 and 3 implies that

$$
\mathbb{E}_{s \sim \rho} \mathbb{E}_\phi V_1^\star(s) \leq \mathcal{V}\left(\mathbb{P}_{\Gamma^\star}, \sigma\right) \leq \max_{\lambda \in \Lambda(P)} \mathcal{V}\left(\lambda, \sigma\right),
$$

695 where the last inequality uses that $\mathbb{P}_{\Gamma^\star} \in \Lambda(P)$ from Lemma 1. VAPOR is a concave optimization
696 problem since (i) the objective function $\mathcal{V}$ is concave in λ by concavity of the function $x \in (0, 1) \to$
697 $x\sqrt{-\log x}$, and (ii) the constraints are a convex set due to the fact that the state-action polytope $\Lambda(P)$
698 is closed, bounded and convex [65, Theorem 8.9.4]. Finally, note that the maximum exists and is
699 attained, since $\Lambda(P)$ is closed, bounded and nonempty due to the fact that $\mathbb{P}_{\Gamma^\star} \in \Lambda(P)$. □

C.5 VAPOR without the Sub-Gaussian Assumption

701 From (9), for *any* set of reward beliefs, the VAPOR optimization problem (Lemma 4) becomes

$$
\max_{\lambda \in \Lambda(P)} \lambda^\top \left(\mathbb{E}_\phi r + (\Psi_r^*)^{-1}(-\log \lambda) \right) = \sum_{l,s,a} \lambda_l(s,a) \left(\mathbb{E}_\phi r_l(s,a) + (\Psi_{r_l(s,a)}^*)^{-1}(-\log \lambda_l(s,a)) \right).
$$

702 This objective remains a concave optimization problem since the function $(\Psi_{r_l(s,a)}^*)^{-1}$ is always
703 concave (as the inverse of the strictly increasing convex function $\Psi_{r_l(s,a)}$).

C.6 Proof of Lemma 5

Lemma 5. *Denoting by λ^* the* VAPOR *solution* (5) *and by $\tau^* \in \mathrm{argmin}_\tau \mathcal{V}_\phi(\lambda^*, \tau)$, it holds that*

$$\mathrm{KL}_{\tau^*}(\mathbb{P}_{\Gamma^\star} \parallel \lambda^*) \leq \mathcal{V}_\phi(\lambda^*) - \mathbb{E}_{s \sim \rho}\mathbb{E}_\phi V_1^\star(s).$$

Proof. The proof extends the relationship between Bregman divergence and value in policy-regularized MDPs [47] to the setting of occupancy-measure-regularized MDPs. The Bregman divergence generated by Ω between two points $\lambda, \lambda' \in \Lambda(P)$ is defined as

$$D_\Omega(\lambda, \lambda') := \Omega(\lambda) - \Omega(\lambda') - \nabla\Omega(\lambda')^\top(\lambda - \lambda').$$

For ease of notation, we omit the dependence on the beliefs ϕ throughout the proof. We write

$$\mathcal{V}(\lambda) := \sum_{l=1}^{L}\sum_{s,a}\lambda_l(s,a)\mathbb{E}_\phi r_l(s,a) - \Omega(\lambda), \qquad \mathcal{V}^* := \max_{\lambda \in \Lambda(P)}\mathcal{V}(\lambda), \qquad \lambda^* \in \mathrm{argmax}_{\lambda \in \Lambda(P)}\mathcal{V}(\lambda),$$

where $\Omega : \Lambda(P) \to \mathbb{R}$ is a continuously differentiable strictly convex regularizer defined as

$$\Omega(\lambda) := -\sum_{l=1}^{L}\sum_{s,a}\sigma_l(s,a)\lambda_l(s,a)\sqrt{-2\log\lambda_l(s,a)}.$$

By definition, λ^* must satisfy the first-order optimality conditions for the maximum of $\mathcal{V}$, and since $\lambda^* \in \mathrm{relint}(\Lambda(P))$ the following holds

$$(\mathbb{E}_\phi r - \nabla\Omega(\lambda^*))^\top(\lambda - \lambda^*) = 0, \quad \forall\lambda \in \Lambda(P).$$

Then,

$$\begin{aligned}
D_\Omega(\mathbb{P}_{\Gamma^\star}, \lambda^*) &= \Omega(\mathbb{P}_{\Gamma^\star}) - \Omega(\lambda^*) - \nabla\Omega(\lambda^*)^\top(\mathbb{P}_{\Gamma^\star} - \lambda^*) \\
&= \Omega(\mathbb{P}_{\Gamma^\star}) - \Omega(\lambda^*) - \mathbb{E}_\phi r^\top(\mathbb{P}_{\Gamma^\star} - \lambda^*) \\
&= \mathcal{V}^* - \mathbb{E}_\phi r^\top\mathbb{P}_{\Gamma^\star} + \Omega(\mathbb{P}_{\Gamma^\star}) \\
&= \mathcal{V}^* - \mathcal{V}(\mathbb{P}_{\Gamma^\star}).
\end{aligned} \tag{10}$$

We now notice that

$$\Omega(\lambda) = -\sum_{l=1}^{L}\sum_{s,a}\min_{\tau_l(s,a)>0}\left\{\frac{\sigma_l^2(s,a)}{2\tau_l(s,a)} - \tau_l(s,a)\lambda_l(s,a)\log\lambda_l(s,a)\right\}.$$

For any positive $\tau \in \mathbb{R}_+^{L,S,A}$, we define

$$\Omega_\tau(\lambda) := \sum_{l=1}^{L}\sum_{s,a}-\frac{\sigma_l^2(s,a)}{2\tau_l(s,a)} + \tau_l(s,a)\lambda_l(s,a)\log\lambda_l(s,a)$$

$$\mathcal{V}_\tau(\lambda) := \sum_{l=1}^{L}\sum_{s,a}\lambda_l(s,a)\mathbb{E}_\phi r_l(s,a) - \Omega_\tau(\lambda),$$

$$\mathcal{V}_\tau^* := \max_{\lambda \in \Lambda(P)}\mathcal{V}_\tau(\lambda), \quad \lambda_\tau^* \in \mathrm{argmax}_{\lambda \in \Lambda(P)}\mathcal{V}_\tau(\lambda).$$

Using that the KL-divergence is the Bregman divergence generated by the negative-entropy function, (10) implies that

$$\mathrm{KL}_\tau(\mathbb{P}_{\Gamma^\star} \parallel \lambda_\tau^*) = \mathcal{V}_\tau^* - \mathcal{V}_\tau(\mathbb{P}_{\Gamma^\star}).$$

Moreover, from strong duality (which holds because $\Lambda(P)$ is convex),

$$\min_{\tau \in \mathbb{R}_+^{L,S,A}}\max_{\lambda \in \Lambda(P)}\mathcal{V}_\tau(\lambda) = \max_{\lambda \in \Lambda(P)}\min_{\tau \in \mathbb{R}_+^{L,S,A}}\mathcal{V}_\tau(\lambda).$$

Denote $\tau^* \in \mathrm{argmin}_\tau \mathcal{V}_\tau^*$, then it holds that

$$\mathrm{KL}_{\tau^*}(\mathbb{P}_{\Gamma^\star} \parallel \lambda^*) = \mathcal{V}^* - \mathcal{V}_{\tau^*}(\mathbb{P}_{\Gamma^\star}) \leq \mathcal{V}^* - \mathcal{V}(\mathbb{P}_{\Gamma^\star}),$$

which concludes the proof. $\qquad\square$

 C.7   Proof of Theorem 1 and Corollary 1

Below we prove a more general statement that will imply Theorem 1 and Corollary 1.

Lemma 12. *Let* alg *produce any sequence of $\mathcal{F}_t$-measurable policies $\pi^t, t = 1, \ldots, N$, whose induced occupancy measures λ^{π^t} satisfy*

$$\mathbb{E}_{s\sim\rho}\mathbb{E}_\phi V_1^\star(s) \leq \mathcal{V}_{\phi^t}(\mathbb{E}^t \lambda^{\pi^t}), \tag{11}$$

where the uncertainty measure σ^t of the $\mathcal{V}_{\phi^t}$ function (4) satisfies

$$\sigma_l^t(s, a) = \frac{c_l(s, a)}{\sqrt{(n_l^t(s, a) \vee 1)}}, \tag{12}$$

where $c \in \mathbb{R}_+^{L,S,A}$ and $n_l^t(s, a)$ denotes the visitation count to (s, a) at step l before episode t and $(\cdot \vee 1) := \max(\cdot, 1)$. Then, letting $c_{\max} := \max_{l,s,a} c_l(s, a)$, it holds that

$$\mathcal{BR}_\phi(\mathrm{alg}, T) \leq \sqrt{2c_{\max}^2 TSA \log(SA)(1 + \log T/L)}$$
$$= \widetilde{O}(c_{\max}\sqrt{SAT}).$$

Proof. Note that $\mathbb{E}^t \lambda^{\pi^t}$ corresponds to the occupancy measure of policy π^t on the expected transition dynamics $\mathbb{E}^t P$, *i.e.*, $\mathbb{E}^t \lambda^{\pi^t} \in \Lambda(\mathbb{E}^t P)$. We bound the Bayes regret of alg as

$$\mathcal{BR}_\phi(\mathrm{alg}, T) \stackrel{(i)}{=} \mathbb{E} \sum_{t=1}^N \mathbb{E}_{s\sim\rho} \mathbb{E}^t \left[V_1^\star(s) - V_1^{\pi^t}(s) \right]$$

$$\stackrel{(ii)}{=} \mathbb{E} \sum_{t=1}^N \left[\mathbb{E}_{s\sim\rho}\mathbb{E}^t V_1^\star(s) - \sum_{l=1}^L \sum_{s,a} \mathbb{E}^t \lambda_l^{\pi^t}(s, a) \mathbb{E}^t r_l(s, a) \right]$$

$$\stackrel{(iii)}{\leq} \mathbb{E} \sum_{t=1}^N \left[\mathcal{V}_{\phi^t}(\mathbb{E}^t \lambda^{\pi^t}) - \sum_{l=1}^L \sum_{s,a} \mathbb{E}^t \lambda_l^{\pi^t}(s, a) \mathbb{E}^t r_l(s, a) \right]$$

$$\stackrel{(iv)}{=} \mathbb{E} \sum_{t=1}^N \sum_{l=1}^L \sum_{s,a} \mathbb{E}^t \lambda_l^{\pi^t}(s, a) \sigma_l^t(s, a) \sqrt{-2\log \mathbb{E}^t \lambda_l^{\pi^t}(s, a)}$$

$$\stackrel{(v)}{\leq} \mathbb{E} \sqrt{\sum_{t=1}^N \sum_{l=1}^L \mathcal{H}(\mathbb{E}^t \lambda_l^{\pi^t})} \sqrt{\sum_{t=1}^N \sum_{l=1}^L \sum_{s,a} 2\mathbb{E}^t \lambda_l^{\pi^t}(s, a) \sigma_l^t(s, a)^2}$$

$$\stackrel{(vi)}{\leq} \sqrt{\mathbb{E} \sum_{t=1}^N \sum_{l=1}^L \mathcal{H}(\mathbb{E}^t \lambda_l^{\pi^t})} \sqrt{\mathbb{E} \sum_{t=1}^N \sum_{l=1}^L \sum_{s,a} 2\mathbb{E}^t \lambda_l^{\pi^t}(s, a) \sigma_l^t(s, a)^2},$$

where (i) follows from the tower property of conditional expectation where the outer expectation is with respect to $\mathcal{F}_1, \mathcal{F}_2, \ldots$, (ii) is from the dual formulation of the value function averaged with respect to the initial state distribution [65] and the fact that $\lambda_l^{\pi^t}(s, a)$ and $r_l(s, a)$ are conditionally independent given $\mathcal{F}_t$, (iii) is due to condition (11), (iv) is from the definition of $\mathcal{V}_{\phi^t}$, (v) and (vi) are by applying the Cauchy-Schwarz inequality, where $\mathcal{H}$ denotes the entropy function [10].

We bound the left term by using the fact that $\mathcal{H}(\mathbb{E}^t \lambda_l^{\pi^t}) \leq \log SA$. We bound the right term using condition (12) and by applying the pigeonhole principle (*e.g.*, [46, Lemma 6]) which gives

$$\mathbb{E} \sum_{t=1}^N \sum_{l=1}^L \sum_{s,a} \frac{\mathbb{E}^t \lambda_l^{\pi^t}(s, a)}{n_l^t(s, a) \vee 1} = \mathbb{E} \sum_{t=1}^N \sum_{l=1}^L \mathbb{E}^t \left(\sum_{s,a} \frac{\mathbb{E}^t \lambda_l^{\pi^t}(s, a)}{n_l^t(s, a) \vee 1} \right)$$

$$= \sum_{l=1}^L \mathbb{E} \left(\sum_{t=1}^N \sum_{s,a} \frac{\lambda_l^{\pi^t}(s, a)}{n_l^t(s, a) \vee 1} \right)$$

$$\leq \sum_{l=1}^L |\mathcal{S}_l| A(1 + \log N)$$

$$= SA(1 + \log N),$$

which follows from the tower property of conditional expectation and since the counts at time t are $\mathcal{F}_t$-measurable. Taking $T = NL$ finally yields

$$\mathcal{BR}_\phi(\text{alg}, T) \leq \sqrt{2c_{\max}^2 NLSA \log(SA)(1 + \log N)}$$
$$= \widetilde{O}(c_{\max}\sqrt{SAT}).$$

$\square$

Theorem 1. *For known P and σ-sub-Gaussian additive reward noise, it holds that* $\mathcal{BR}_\phi(\texttt{VAPOR}, T) \leq \widetilde{O}(\sigma\sqrt{SAT})$.

Proof. Lemma 4 implies that the occupancy measures that solve the $\texttt{VAPOR}$ optimization problem satisfy condition (11). Moreover, under additive σ-sub-Gaussian reward noise, we can simply instantiate the c vector in condition (12) as the sub-Gaussian reward noise parameter. The result thus follows from applying Lemma 12 with $c_{\max} = \sigma$. $\square$

Corollary 1. *Denote by $\text{alg}_{\Gamma^\star}$ the algorithm that produces policies based on $\mathbb{P}_{\Gamma^\star}^t$ for each episode t using (1). Then, under the same conditions as Theorem 1, we have $\mathcal{BR}_\phi(\text{alg}_{\Gamma^\star}, T) \leq \widetilde{O}(\sigma\sqrt{SAT})$.*

Proof. The result comes from combining Lemmas 4 and 12, as done in the proof of Theorem 1. $\square$

C.8 Proof of Lemma 6

Definition 2 (Transformed beliefs). *Given any beliefs ϕ satisfying Assumption 1, we define the transformed beliefs $\widehat{\phi}$ according to which the transition dynamics are known and equal to $\mathbb{E}_\phi P$ and the rewards are distributed as $\mathbb{E}_\phi r + \omega$, where $\omega_l(s, a)$ follows an independent zero-mean Gaussian distribution with variance $\widehat{\sigma}^2$ defined for each step $l \in [L]$ and state-action pair $(s, a) \in \mathcal{S}_l \times \mathcal{A}$ as*

$$\widehat{\sigma}_l(s, a)^2 := 3.6^2 \sigma_l^2(s, a) + \frac{(L - l)^2}{\sum_{s' \in \mathcal{S}_{l+1}} \alpha_l(s, a, s')}.$$

We prove in Appendix C.8.1 the following stronger result which implies Lemma 6.

Lemma 13. *For any step $l \in [L]$ and state $s \in \mathcal{S}_l$, it holds that*

$$\mathbb{E}_\phi V_l^\star(s) \leq \mathbb{E}_{\widehat{\phi}} V_l^\star(s).$$

C.8.1 Proof of Lemma 13

Overview. The proof relies on studying properties of two stochastic Bellman operators, drawing inspiration from [61, Section 6.5]. In particular we will make use of the notion of stochastic optimism (Definition 3). To deal with the unknown transitions, we will use the property of Gaussian-Dirichlet optimism [59]. To deal with unknown rewards, we will derive a property of Gaussian-sub-Gaussian optimism (Lemma 19) which holds when the variance of the Gaussian distribution is multiplied by a small universal constant.

Definition 3. *A random variable X is stochastically optimistic with respect to another random variable Y, written $X \geq_{SO} Y$, if $\mathbb{E}u(X) \geq \mathbb{E}u(Y)$ for all convex increasing functions $u : \mathbb{R} \to \mathbb{R}$.*

Likewise, we will say that X is stochastically optimistic with respect to Y under ϕ and write that $X \mid \phi \geq_{SO} Y \mid \phi$ if $\mathbb{E}_\phi u(X) \geq \mathbb{E}_\phi u(Y)$ for all convex increasing functions $u : \mathbb{R} \to \mathbb{R}$.

We define the first Bellman operator for any step $l \in [L]$ and any $Q_{l+1} \in \mathbb{R}^{S_{l+1} \times A}$ as

$$\mathcal{B}_l Q_{l+1}(s, a) := r_l(s, a) + P_l(\cdot \mid s, a)^\top \max_{a'} Q_{l+1}(\cdot, a'),$$

and the second 'transformed' Bellman operator as

$$\widehat{\mathcal{B}}_l Q_{l+1}(s, a) := \mathbb{E}_\phi r_l(s, a) + \omega_l(s, a) + \mathbb{E}_\phi P_l(\cdot \mid s, a)^\top \max_{a'} Q_{l+1}(\cdot, a'),$$

where we recall that $\omega_l(s, a) \sim \mathcal{N}\left(0, \widehat{\sigma}_l(s, a)^2\right)$ is distributed independently across the state-action pairs $(s, a) \in \mathcal{S}_l \times \mathcal{A}$ under ϕ. Note that $\mathcal{B}_l$ and $\widehat{\mathcal{B}}$ can be viewed as randomized Bellman operators due to the randomness in the MDP $\mathcal{M}$ and in the distribution ω, respectively. We rely on two key properties.

Lemma 14 (Property 1: monotonicity). *For any step $l \in [L]$, consider two random Q functions $Q_{l+1}, Q'_{l+1} \in \mathbb{R}^{\mathcal{S}_{l+1} \times \mathcal{A}}$ such that conditioned on ϕ the entries of Q_{l+1} (respectively Q'_{l+1}) are drawn independently across state-action pairs $(s, a) \in \mathcal{S}_{l+1} \times \mathcal{A}$ and drawn independently of the noise terms $\omega_l(s, a)$. Then*

$$Q_{l+1}(s, a) \mid \phi \geq_{SO} Q'_{l+1}(s, a) \mid \phi \quad \forall (s, a) \in \mathcal{S}_{l+1} \times \mathcal{A}$$

implies

$$\widehat{\mathcal{B}}_l Q_{l+1}(s, a) \mid \widehat{\phi} \geq_{SO} \widehat{\mathcal{B}}_l Q'_{l+1}(s, a) \mid \widehat{\phi} \quad \forall (s, a) \in \mathcal{S}_l \times \mathcal{A}, \ l \in [L].$$

Proof. The proof follows that of [61, Lemma 3]. It relies on the fact that conditioned on ϕ, $\widehat{\mathcal{B}}_l Q_{l+1}(s, a)$ is a convex increasing function of $(Q_{l+1}(s, a))_{s,a}$ convolved with the independent noise term $\omega_l(s, a)$. The result therefore follows from the fact that stochastic optimism is preserved under convex increasing operations [61, Lemma 2]. $\square$

Lemma 15 (Property 2: stochastic optimism). *For any $l \in [L]$ and $(s, a) \in \mathcal{S}_{l+1} \times \mathcal{A}$, it holds that*

$$\widehat{\mathcal{B}}_l Q_{l+1}(s, a) \mid \widehat{\phi} \geq_{SO} \mathcal{B}_l Q_{l+1}(s, a) \mid \phi$$

for any fixed $Q_{l+1} \in \mathbb{R}^{\mathcal{S}_{l+1} \times \mathcal{A}}$ such that $\mathrm{Span}(Q_{l+1}) \leq L - l$.

Proof. For any fixed Q_{l+1}, it holds that

$$\widehat{\mathcal{B}}_l Q_{l+1}(s, a) \mid \widehat{\phi} \sim \mathcal{N}\left(b_l(s, a), \widehat{\sigma}_l(s, a)^2\right) \mid \phi,$$

where we define

$$b_l(s, a) := \mathbb{E}_\phi r_l(s, a) + \mathbb{E}_\phi P_l(\cdot \mid s, a)^\top \max_{a'} Q_{l+1}(\cdot, a').$$

Lemma 16 ([59]). *Let $Y = \sum_{i=1}^n A_i b_i$ for fixed $b \in \mathbb{R}^n$ and random variable A, where A is Dirichlet with parameter $\alpha \in \mathbb{R}^n$, and let $X \sim \mathcal{N}(\mu_X, \sigma_X^2)$ with $\mu_X \geq \frac{\sum_i \alpha_i b_i}{\sum_i \alpha_i}$ and $\sigma_X^2 \geq (\sum_i \alpha_i)^{-1} \mathrm{Span}(b)^2$, where $\mathrm{Span}(b) = \max_i b_i - \min_j b_j$, then $X \geq_{SO} Y$.*

In our case, in the notation of Lemma 16, A will represent the transition function probabilities, and b will represent $V := \max_a Q(\cdot, a)$, *i.e.*, for a given $(s, a) \in \mathcal{S}_l \times \mathcal{A}$ let X be a random variable distributed $\mathcal{N}(\mu_X, \sigma_X^2)$ where

$$\mu_X = \sum_{s' \in \mathcal{S}_{l+1}} \left(\alpha_l(s, a, s') V_{l+1}(s') / \sum_x \alpha_l(s, a, x) \right) = \sum_{s' \in \mathcal{S}_{l+1}} \mathbb{E}_\phi[P_l(s' \mid s, a)] V_{l+1}(s')$$

due to Assumption 1. Moreover, the lemma assumes that $\mathrm{Span}(V_{l+1}) \leq L - l$, so we choose $\sigma_X^2 = (L - l)^2 / (\sum_{s'} \alpha_l(s, a, s'))$. As a result, it holds that

$$\mathcal{N}\left(\mathbb{E}_\phi P_l(\cdot \mid s, a)^\top \max_{a'} Q_{l+1}(\cdot, a'), \frac{(L - l)^2}{\sum_{s'} \alpha_l(s, a, s')} \right) \mid \phi \geq_{SO} P_l(\cdot \mid s, a)^\top \max_{a'} Q_{l+1}(\cdot, a') \mid \phi.$$

Moreover, from the assumption of $\sigma_l(s, a)$-sub-Gaussian $r_l(s, a)$ and from the Gaussian Sub-Gaussian stochastic optimism property of Lemma 19,

$$\mathcal{N}\left(0, 3.6^2 \sigma_l^2(s, a)\right) \geq_{SO} r_l(s, a) - \mathbb{E}_\phi r_l(s, a) \mid \phi,$$

which means that

$$\mathcal{N}\left(\mathbb{E}_\phi r_l(s, a), 3.6^2 \sigma_l^2(s, a)\right) \mid \phi \geq_{SO} r_l(s, a) \mid \phi.$$

As a result, since the random variables $r_l(s, a)$, $P_l(\cdot \mid s, a)^\top \max_{a'} Q_{l+1}(\cdot, a')$, $\mathcal{N}\left(\mathbb{E}_\phi r_l(s, a), 3.6^2 \sigma_l^2(s, a)\right)$ and $\mathcal{N}\left(\mathbb{E}_\phi P_l(\cdot \mid s, a)^\top \max_{a'} Q_{l+1}(\cdot, a'), \frac{(L-l)^2}{\sum_{s'} \alpha_l(s, a, s')}\right)$ are mutually conditionally independent, we have

$$\mathcal{N}\left(b_l(s, a), \widehat{\sigma}_l(s, a)^2\right) \mid \phi \sim \mathcal{N}\left(\mathbb{E}_\phi r_l(s, a), 3.6^2 \sigma_l^2(s, a)\right)$$

$$+ \mathcal{N}\left(\mathbb{E}_\phi P_l(\cdot \mid s, a)^\top \max_{a'} Q_{l+1}(\cdot, a'), \frac{(L - l)^2}{\sum_{s'} \alpha_l(s, a, s')} \right) \mid \phi$$

$$\geq_{SO} r_l(s, a) + P_l(\cdot \mid s, a)^\top \max_{a'} Q_{l+1}(\cdot, a') \mid \phi$$

$$\sim \mathcal{B}_l Q_{l+1}(s, a) \mid \phi,$$

which concludes the proof. $\square$

Lemma 17. *For any $l \in [L]$ and $(s, a) \in \mathcal{S}_l \times \mathcal{A}$,*

$$Q_l^\star(s, a) \mid \widehat{\phi} \geq_{SO} Q_l^\star(s, a) \mid \phi.$$

Proof. Note that under ϕ, $Q_l^\star = \mathcal{B}_1 \mathcal{B}_2 \dots \mathcal{B}_L 0$ and under $\widehat{\phi}$, $Q_l^\star = \widehat{\mathcal{B}}_1 \widehat{\mathcal{B}}_2 \dots \widehat{\mathcal{B}}_L 0$. By Lemma 15,

$$(\widehat{\mathcal{B}}_L 0)(s, a) \mid \widehat{\phi} \geq_{SO} (\mathcal{B}_L 0)(s, a) \mid \phi.$$

Proceeding by induction, suppose that for some $l \leq L$,

$$(\widehat{\mathcal{B}}_{l+1} \dots \widehat{\mathcal{B}}_L 0)(s, a) \mid \widehat{\phi} \geq_{SO} (\mathcal{B}_{l+1} \dots \mathcal{B}_L 0)(s, a) \mid \phi.$$

Combining this with Lemma 14 shows

$$\begin{aligned}
\widehat{\mathcal{B}}_l(\widehat{\mathcal{B}}_{l+1} \dots \widehat{\mathcal{B}}_L 0)(s, a) \mid \widehat{\phi} &\geq_{SO} \widehat{\mathcal{B}}_l(\mathcal{B}_{l+1} \dots \mathcal{B}_L 0)(s, a) \mid \widehat{\phi} \\
&\geq_{SO} \mathcal{B}_l(\mathcal{B}_{l+1} \dots \mathcal{B}_L 0)(s, a) \mid \phi,
\end{aligned}$$

where the final step uses Lemma 15 and the fact that $\text{Span}(\mathcal{B}_{l+1} \dots \mathcal{B}_L 0) \leq L - l$. □

We are now ready to prove Lemma 13. We apply the property of stochastic optimism derived in Lemma 17 to the convex increasing function $u_s(Q) := \max_{a \in \mathcal{A}} Q(s, a)$ for every step $l \in [L]$ and state $s \in \mathcal{S}_l$, which yields the desired inequality $\mathbb{E}_\phi V_l^\star(s) \leq \mathbb{E}_{\widehat{\phi}} V_l^\star(s)$.

C.9   Proof of Lemma 7

Lemma 7. *Let* alg *be any procedure that maps posterior beliefs to policies, and denote by $\mathcal{BR}_{\mathcal{T},\phi}(\text{alg}, T)$ the Bayesian regret of* alg *where at each episode $t = 1, \dots, T$, the policy and regret are computed by replacing ϕ^t with $\mathcal{T}(\phi^t)$ (Lemma 6), then under Assumption 1,*

$$\mathcal{BR}_\phi(\text{alg}, T) \leq \mathcal{BR}_{\mathcal{T},\phi}(\text{alg}, T).$$

Proof. We recall that we denote by ϕ the prior on the MDP, by $\phi^t := \phi(\cdot \mid \mathcal{F}_t)$ the posterior beliefs at the beginning of each episode t and by $\mathcal{T}$ the mapping that transforms the posteriors according to Lemma 6. Using the tower property of conditional expectation (where the outer expectation is with respect to $\mathcal{F}_1, \mathcal{F}_2, \dots$), we can define the Bayes regret over T timesteps of alg under the sequence of original and transformed posteriors respectively as

$$\mathcal{BR}_\phi(\text{alg}, T) := \mathbb{E} \sum_{t=1}^N \mathbb{E}_{s \sim \rho} \mathbb{E}_{\phi^t} \left[V_1^\star(s) - V_1^{\pi^t}(s) \right],$$

$$\mathcal{BR}_{\mathcal{T},\phi}(\text{alg}, T) := \mathbb{E} \sum_{t=1}^N \mathbb{E}_{s \sim \rho} \mathbb{E}_{\mathcal{T}(\phi^t)} \left[V_1^\star(s) - V_1^{\pi^t}(s) \right].$$

The result then immediately comes from combining Lemmas 13 and 18. □

Lemma 18. *For any fixed policy π, it holds that*

$$\mathbb{E}_\phi V_1^\pi(s) = \mathbb{E}_{\widehat{\phi}} V_1^\pi(s).$$

Proof. We prove by induction on the step l that $\mathbb{E}_\phi Q_l^\pi(s, a) = \mathbb{E}_{\widehat{\phi}} Q_l^\pi(s, a)$ for any $(s, a) \in \mathcal{S}_l \times \mathcal{A}$. This is true at step $L + 1$. Assuming that it is true at step $l + 1$, then

$$\begin{aligned}
&\mathbb{E}_\phi Q_l^\pi(s, a) - \mathbb{E}_{\widehat{\phi}} Q_{l+1}^\pi(s', a') \\
&= \mathbb{E}_\phi \left[r_l(s, a) + \sum_{s'} P_l(s' \mid s, a) \sum_{a'} \pi_{l+1}(s', a') Q_{l+1}^\pi(s', a') \right] \\
&\quad - \mathbb{E}_{\widehat{\phi}} \left[\mathbb{E}_\phi r_l(s, a) + \omega_l(s, a) + \sum_{s'} \mathbb{E}_\phi P_l(s' \mid s, a) \sum_{a'} \pi_{l+1}(s', a') Q_{l+1}^\pi(s', a') \right] \\
&= \sum_{s'} \mathbb{E}_\phi P_l(s' \mid s, a) \sum_{a'} \pi_{l+1}(s', a') \left[\mathbb{E}_\phi Q_{l+1}^\pi(s', a') - \mathbb{E}_{\widehat{\phi}} Q_{l+1}^\pi(s', a') \right] \\
&= 0,
\end{aligned}$$

because $\mathbb{E}_\phi Q_l^\pi(s', a') = \mathbb{E}_{\widehat\phi} Q_l^\pi(s', a')$ for every $(s', a') \in \mathcal{S}_{l+1} \times \mathcal{A}$ by induction hypothesis. As a result,

$$\mathbb{E}_\phi V_1^\pi(s) - \mathbb{E}_{\widehat\phi} V_1^\pi(s) = \sum_a \pi_1(s, a)\mathbb{E}_\phi Q_1^\pi(s, a) - \sum_a \pi_1(s, a)\mathbb{E}_{\widehat\phi} Q_1^\pi(s, a) = 0.$$

$\square$

C.10 Proof of Theorem 2

Theorem 2. *Under Assumption 1, it holds that* $\mathcal{BR}_\phi(\text{VAPOR}, T) \leq \widetilde{O}(L\sqrt{SAT})$.

Proof. We first explicitly write the uncertainty measure $\widehat\sigma^t$ given our assumptions. The prior over the transition function $P_l(\,\cdot\mid s, a)$ is assumed Dirichlet, and let us denote the parameter of the Dirichlet distribution $\alpha_l^0(s, a) \in \mathbb{R}_+^{S_{l+1}}$ for each (s, a), where $\sum_{s' \in \mathcal{S}_{l+1}} \alpha_l^0(s, a, s') \geq 1$, *i.e.*, we start with a total pseudo-count of at least one for every state-action (as done in [46]). Since the likelihood for the transition function is a Categorical distribution, conjugacy of the categorical and Dirichlet distributions implies that the posterior over $P_l(\,\cdot\mid s, a)$ at time t is Dirichlet with parameter $\alpha_l^t(s, a)$, where $\alpha_l^t(s, a, s') = \alpha_l^0(s, a, s') + n_l^t(s, a, s')$ for each $s' \in \mathcal{S}_{l+1}$, where $n_l^t(s, a, s') \in \mathbb{N}$ is the number of times the agent has been in state s, taken action a, and transitioned to state s' at timestep l, and note that $\sum_{s' \in \mathcal{S}_{l+1}} n_l^t(s, a, s') = n_l^t(s, a)$, the total visit count to (s, a). Meanwhile, the reward noise is assumed additive σ-sub-Gaussian (with σ a constant scalar), so we can write the uncertainty measure $\sigma^t \in \mathbb{R}_+^{L,S,A}$ as $\sigma_l^t(s, a) = \sigma/\sqrt{(n_l^t(s, a) \vee 1)}$. As a result, we can write that

$$\widehat\sigma_l^t(s, a)^2 = \frac{3.6^2\sigma^2 + (L - l)^2}{(n_l^t(s, a) \vee 1)}. \tag{13}$$

The result follows from

$$\mathcal{BR}_\phi(\text{VAPOR}, T) \leq \mathcal{BR}_{\mathcal{T},\phi}(\text{VAPOR}, T) \leq \sqrt{2(3.6^2\sigma^2 + L^2)TSA\log(SA)(1 + \log T/L)}$$
$$= \widetilde{O}(L\sqrt{SAT}),$$

where the first inequality stems from Lemma 7 and the second inequality applies Lemma 12 with $c_{\max} = 3.6^2\sigma^2 + L^2$. $\square$

C.11 Proof of Lemma 8

Lemma 8. *Let* λ^{TS} *be the occupancy measure of the* TS *policy, it holds that* $\mathbb{E}[\lambda^{\text{TS}}] = \mathbb{P}_{\Gamma^\star}$.

Proof. Given any environment $\mathcal{M}$ sampled from the posterior ϕ, the optimal policy $\pi_{\mathcal{M}}^\star$ induces the occupancy measure $\lambda_l^{\pi_{\mathcal{M}}^\star}(s, a) = \mathbb{P}_{\mathcal{M}}(\Gamma_l^\star(s, a))$. Marginalizing over the environment $\mathcal{M}$ yields $\mathbb{E}[\lambda_l^{\text{TS}}(s, a)] = \int_{\mathcal{M}} \lambda_l^{\pi_{\mathcal{M}}^\star}(s, a)d\mathbb{P}(\mathcal{M}) = \mathbb{P}_\phi(\Gamma_l^\star(s, a))$. $\square$

 # D   Gaussian Sub-Gaussian Stochastic Optimism

847 The following technical lemma, which may be of independent interest, establishes a relation of
848 stochastic optimism (Definition 3) between a sub-Gaussian and a Gaussian whose variance is inflated
849 by a small universal constant.

850 **Lemma 19.** *Let Y be σ-sub-Gaussian. Let $X \sim \mathcal{N}(0, \kappa^2 \sigma^2)$ with $\kappa \geq 3.6$. Then $X \geq_{SO} Y$.*

851 *Proof.* Let $u : \mathbb{R} \to \mathbb{R}$ be a convex (increasing) function. We aim to show that $\mathbb{E}[u(X)] \geq \mathbb{E}[u(Y)]$.
852 Let $s_0 \in \mathbb{R}$ be a subgradient of u at 0 (which exists since u is convex). Then by convexity of u, we
853 have for all $x \in \mathbb{R}$, $u(x) \geq u(0) + s_0 x$. Define the function $f : \mathbb{R} \to \mathbb{R}$ as $f(x) := u(x) - u(0) - s_0 x$.
854 We have that $f(x) \geq 0$ for all $x \in \mathbb{R}$ and $f(0) = 0$. Since $\mathbb{E}X = \mathbb{E}Y = 0$, it suffices to show
855 that $\mathbb{E}[f(X)] \geq \mathbb{E}[f(Y)]$. For any $\epsilon \geq 0$, define the ϵ-sublevel set of the convex function f as
856 $K_\epsilon := \{x \in \mathbb{R} : f(x) \leq \epsilon\}$. Since K_ϵ is convex and by property of f, there exists $a(\epsilon) \in \mathbb{R}_- \cup \{-\infty\}$
857 and $b(\epsilon) \in \mathbb{R}_+ \cup \{+\infty\}$ such that $K_\epsilon = [a(\epsilon), b(\epsilon)]$. Then, for any random variable Z,

$$\mathbb{E}f(Z) = \int_0^\infty \mathbb{P}(f(Z) \geq \epsilon) \, d\epsilon$$
$$= \int_0^\infty (\mathbb{P}(Z \geq b(\epsilon)) + \mathbb{P}(Z \leq a(\epsilon))) \, d\epsilon.$$

858 By the σ-sub-Gaussian property of Y,

$$\mathbb{E}f(Y) = \int_0^\infty (\mathbb{P}(Y \geq b(\epsilon)) + \mathbb{P}(Y \leq a(\epsilon))) \, d\epsilon$$
$$= \int_0^\infty \left(\exp\left(\frac{-b(\epsilon)^2}{2\sigma^2} \right) + \exp\left(\frac{-a(\epsilon)^2}{2\sigma^2} \right) \right) \, d\epsilon$$
$$= \int_0^\infty (G(b(\epsilon)) + G(a(\epsilon))) \, d\epsilon,$$

859 where we define

$$G(x) := \exp\left(-x^2 / (2\sigma^2) \right).$$

860 Let $d := 2.69$ and $c := \frac{\kappa}{d} \geq 1.338$. Let $Z \sim \mathcal{N}(0, c^2 \sigma^2)$ and $F(x) := \mathbb{P}(Z \geq x)$. Note that

$$F(x) = \frac{1}{2} \left(1 - \mathrm{erf}\left(\frac{x}{\sigma c \sqrt{2}} \right) \right),$$

861 where erf denotes the error function, *i.e.*, $\mathrm{erf}(y) = 2\pi^{-1/2} \int_0^y \exp(-t^2) \, dt$. From Lemma 20, by
862 choice of constants c, d, it holds that $G(x) \leq dF(x)$. Therefore,

$$\mathbb{E}[f(Y)] \leq d \int_0^\infty (F(b(\epsilon)) + F(a(\epsilon))) \, d\epsilon$$
$$= d \int_0^\infty (\mathbb{P}(Z \geq b(\epsilon)) + \mathbb{P}(Z \geq a(\epsilon))) \, d\epsilon$$
$$= d\mathbb{E}[f(Z)]$$
$$\leq \mathbb{E}[f(dZ)]$$
$$= \mathbb{E}[f(X)],$$

863 where the last inequality applies Lemma 21 to the convex function f that satisfies $f(0) = 0$, and the
864 last equality is because $\kappa = cd$ which means that X and dZ follow the same distribution. $\square$

865 **Lemma 20.** *Denote by $c_0 > 0$ the (unique) solution of the equation*

$$\frac{1}{2} \left(1 - \mathrm{erf}\left(\frac{1}{c_0 \sqrt{2}} \right) \right) = \frac{1}{c_0 \sqrt{2\pi}} \exp\left(-1/(2c_0^2) \right).$$

866 *and let $d_0 > 0$ be defined as*

$$d_0 := \frac{2 \exp(-1/2)}{1 - \mathrm{erf}(\frac{1}{c_0 \sqrt{2}})}.$$

867   *Note that $c_0 \approx 1.33016$ and $d_0 \approx 2.68271$.*

868   *Then for any $c \geq c_0, d \geq d_0$, the function $\phi : \mathbb{R} \to \mathbb{R}$ defined as*

$$\phi(x) := \frac{d}{2}\left(1 - \operatorname{erf}\left(\frac{x}{c\sqrt{2}}\right)\right) - \exp(-x^2/2)$$

869   *is non-negative everywhere.*

870   *Proof.* Define

$$\phi_0(x) := \frac{d_0}{2}\left(1 - \operatorname{erf}\left(\frac{x}{c_0\sqrt{2}}\right)\right) - \exp(-x^2/2).$$

871   It suffices to prove that $\phi_0(x) \geq 0$ for all $x \in \mathbb{R}$. By the choices of c_0, d_0, it holds that

$$\phi_0(1) = \frac{d_0}{2}\left(1 - \operatorname{erf}\left(\frac{1}{c_0\sqrt{2}}\right)\right) - \exp(-1/2) = 0,$$

$$\phi_0'(1) = \frac{-d_0}{c_0\sqrt{2\pi}}\exp\left(-1/(2c_0^2)\right) + \exp(-1/2) = 0.$$

872   Moreover, analyzing the variations of ϕ yields that there exists $x_0 > 1$ such that $\phi_0'(x) \geq 0$ for
873   $x \in [1, x_0]$, and $\phi_0'(x) \leq 0$ otherwise. Therefore ϕ_0 is non-decreasing on $[1, x_0]$ and non-increasing
874   elsewhere. Since $\lim_{x \to +\infty} \phi_0(x) = 0$ and $\phi_0(1) = 0$, we get that $\phi_0(x) \geq 0$ for all $x \in \mathbb{R}$. $\square$

875   **Lemma 21.** *For any convex function $g : \mathbb{R} \to \mathbb{R}$ such that $g(0) = 0$, for any $s \geq 1$ and $x \in \mathbb{R}$, it*
876   *holds that $sg(x) \leq g(sx)$.*

877   *Proof.* By convexity of g, for any $x' \in \mathbb{R}$, we have $g(s^{-1}x') \leq s^{-1}g(x') + (1 - s^{-1})g(0) =$
878   $s^{-1}g(x')$, so by setting $x' = sx$ it holds that $sg(x) = sg(s^{-1}x') \leq g(x') = g(sx)$. $\square$

E   A Policy-Gradient Approximation

Since `VAPOR` requires solving a convex optimization problem, it is amenable to online optimization and representing the policy using a deep neural network. In this section, we derive a principled, albeit looser, upper-bound approximation of `VAPOR` which can be readily incorporated in a policy-gradient agent.

Denoting by μ^π the stationary state distribution of a policy π, note the relation $\lambda_l^\pi(s,a) = \pi_l(s,a)\mu_l^\pi(s)$. The regularization term of `VAPOR` can thus be decomposed in a (weighted) policy entropy regularization term and a (weighted) stationary state distribution entropy term, the latter of which is challenging to optimize in high-dimensional spaces [29, 36, 42]. In light of this, we introduce the following alternative optimization problem, which we call `VAPOR-lite`

$$\max_{\pi \in \Pi} \quad \sum_{l,s} \mu_l^\pi(s) \left(\sum_a \pi_l(s,a) \left(r_l(s,a) + \widehat{\sigma}_l(s,a) + \mathcal{H}_{\widehat{\sigma}_l(s,\cdot)}(\pi_l(s,\cdot)) \right) \right), \qquad (14)$$

where we define the weighted policy entropy

$$\mathcal{H}_{\widehat{\sigma}_l(s,\cdot)}(\pi_l(s,\cdot)) := -\sum_a \widehat{\sigma}_l(s,a)\pi_l(s,a)\log\pi_l(s,a).$$

Akin to policy-gradient methods, `VAPOR-lite` now optimizes over the policies π which can be parametrized by a neural network. It depends on an uncertainty signal $\widehat{\sigma}$ which can also be parametrized by a neural network (*e.g.*, an ensemble of reward predictors, as we consider in our experiments in Section 7). Compared to `VAPOR`, `VAPOR-lite` accounts for a *weaker* notion of weighted entropy regularization (*i.e.*, in the policy space instead of the occupancy-measure space), which allows to solve the objective using policy-gradient techniques. Importantly, `VAPOR-lite` remains a *principled* approach — we indeed prove in Appendix E.1 that:

- Solving `VAPOR-lite` in the space of occupancy measures is still a concave optimization problem and thus computationally tractable,
- `VAPOR-lite` upper bounds the `VAPOR` objective (up to a multiplicative factor in the uncertainty measure and a negligible additive bias),
- `VAPOR-lite` yields the same $\widetilde{O}(L\sqrt{SAT})$ regret bound as `VAPOR` for a careful schedule of uncertainty measures $\widehat{\sigma}$ over episodes.

Essentially, `VAPOR-lite` endows a policy-gradient agent with **(i)** an uncertainty reward bonus and **(ii)** an uncertainty-weighted policy entropy regularization. The latter exploration mechanism is novel and has an appealing interpretation: Unlike standard policy entropy regularization, it adaptively accounts for epistemic uncertainty, by eliminating actions from the entropy term where the agent has low uncertainty for each given state. In the limit of $\widehat{\sigma} \to 0$ (*i.e.*, no uncertainty), the regularization of `VAPOR-lite` vanishes and we recover the original policy-gradient objective.

E.1   Analysis of `VAPOR-lite`

Denoting the uncertainty signal of the `VAPOR` optimization problem by $\widehat{\sigma}$, we define the `VAPOR-lite`(c) optimization problem for any multiplicative scalar $c > 0$ as follows

$$\max_{\lambda \in \Lambda(\mathbb{E}_\phi P)} \quad \mathcal{U}_{\widehat{\phi}}(\lambda, c)$$

$$:= \sum_{l,s,a} \lambda_l(s,a) \left(\mathbb{E}_\phi r_l(s,a) + c\widehat{\sigma}_l(s,a) - \sum_{a'} c\widehat{\sigma}_l(s,a') \frac{\lambda_l(s,a')}{\sum_b \lambda_l(s,b)} \log\left(\frac{\lambda_l(s,a')}{\sum_b \lambda_l(s,b)} \right) \right)$$

$$= \sum_{l,s,a} \lambda_l(s,a) \left(\mathbb{E}_\phi r_l(s,a) + c\widehat{\sigma}_l(s,a) + \mathcal{H}_{c\widehat{\sigma}_l(s,\cdot)}\left(\frac{\lambda_l(s,\cdot)}{\sum_b \lambda_l(s,b)} \right) \right).$$

$$(15)$$

Note that this corresponds to the same objective as (14) except that it is optimized over the occupancy measures instead of the policies.

Lemma 22. *The* `VAPOR-lite`(c) *optimization problem is concave in* λ.

Proof. The objective is concave due to the fact that the normalized entropy function h of $u \in \mathbb{R}_{>0}^n$ given by $h(u) = \sum_{i=1}^n u_i \log(\mathbf{1}^\top u/u_i)$ is concave (see [6, Example 3.19]) since the perspective operation preserves convexity. $\qquad\square$

Lemma 23. *For any $\eta > 0$ and $\lambda \in \Lambda(\mathbb{E}_\phi P)$, it holds that*

$$\mathcal{V}_{\widehat{\phi}}(\lambda) \leq \mathcal{U}_{\widehat{\phi}}(\lambda, c_\eta) + \sqrt{2}\widehat{\sigma}_{\max}LS\eta,$$

where $c_\eta := \sqrt{2}(1 + \log 1/\eta)$ and $\widehat{\sigma}_{\max} := \max_{l,s,a} \widehat{\sigma}_l(s,a)$.

Proof. Any occupancy measure $\lambda \in \Lambda(\mathbb{E}_\phi P)$ can be decomposed as $\lambda_l(s,a) = \mu_l^\pi(s)\pi_l(s,a)$, where μ^π denotes the stationary state distribution under π, *i.e.*, $\mu_l^\pi(s) := \sum_{a \in \mathcal{A}} \lambda_l(s,a)$, and π is the policy given by $\pi_l(s,a) := \lambda_l(s,a)/\mu_l^\pi(s)$. It holds that

$$
\begin{aligned}
\lambda_l(s,a)\sqrt{-\log \lambda_l(s,a)} &\overset{(i)}{\leq} \lambda_l(s,a) - \lambda_l(s,a)\log\lambda_l(s,a) \\
&= \lambda_l(s,a) - \mu_l^\pi(s)\pi_l(s,a)\log\pi_l(s,a) - \pi_l(s,a)\mu_l^\pi(s)\log\mu_l^\pi(s) \\
&\overset{(ii)}{\leq} \lambda_l(s,a) - \mu_l^\pi(s)\pi_l(s,a)\log\pi_l(s,a) + \pi_l(s,a)\mu_l^\pi(s)\log 1/\eta + \pi_l(s,a)\eta \\
&= \lambda_l(s,a)\left(1 + \log 1/\eta\right) - \mu_l^\pi(s)\pi_l(s,a)\log\pi_l(s,a) + \pi_l(s,a)\eta,
\end{aligned}
$$

where (i) uses that $\sqrt{-\log x} \leq 1 - \log(x)$ for any $0 < x \leq 1$, and (ii) uses that $-x\log x \leq x\log 1/\eta + \eta$ for any $0 \leq x \leq 1$ and $\eta > 0$. Hence, we have

$$
\begin{aligned}
\mathcal{V}_{\widehat{\phi}}(\lambda) &= \sum_{l,s,a} \lambda_l(s,a)\mathbb{E}_\phi r_l(s,a) + \sum_{l,s,a} \widehat{\sigma}_l(s,a)\lambda_l^\pi(s,a)\sqrt{-2\log\lambda_l^\pi(s,a)} \\
&\leq \sum_{l,s,a} \lambda_l(s,a)\left(\mathbb{E}_\phi r_l(s,a) + \sqrt{2}(1 + \log 1/\eta)\widehat{\sigma}_l(s,a)\right) \\
&\quad + \sum_{l,s} \mu_l^\pi(s)\left(-\sum_a \sqrt{2}\widehat{\sigma}_l(s,a)\pi_l(s,a)\log\pi_l(s,a)\right) + \sum_{l,s,a}\sqrt{2}\eta\widehat{\sigma}_l(s,a)\pi_l(s,a) \\
&\leq \mathcal{U}_{\widehat{\phi}}(\lambda, c_\eta) + \sqrt{2}\widehat{\sigma}_{\max}LS\eta.
\end{aligned}
$$

$\qquad\square$

Lemma 24. *Consider the algorithm* `VAPOR-lite` *that at each episode $t = 1, \dots, N$ solves the optimization problem* `VAPOR-lite`$(c = \sqrt{2}(1 + \log SLt))$. *Then under Assumption 1, it holds that*

$$\mathcal{BR}_\phi(\texttt{VAPOR-lite}, T) \leq \widetilde{O}(L\sqrt{SAT}).$$

Proof. Denote by π^t the policy executed by the algorithm at episode t, and by $\mathbb{E}^t\mathbb{P}_{\Gamma^\star}$ the posterior probability of state-action optimality in the expected model $\mathbb{E}^t P$. It holds that

$$
\begin{aligned}
\mathbb{E}_{s \sim \rho}\mathbb{E}^t V_1^\star(s) &\overset{(i)}{\leq} \mathcal{V}_{\widehat{\phi}^t}(\mathbb{E}^t\mathbb{P}_{\Gamma^\star}) \\
&\overset{(ii)}{\leq} \mathcal{U}_{\widehat{\phi}^t}\left(\mathbb{E}^t\mathbb{P}_{\Gamma^\star}, 1/(SLt)\right) + \sqrt{2}\widehat{\sigma}_{\max}/t \\
&\overset{(iii)}{\leq} \mathcal{U}_{\widehat{\phi}^t}\left(\mathbb{E}^t\lambda^{\pi^t}, 1/(SLt)\right) + \sqrt{2}\widehat{\sigma}_{\max}/t,
\end{aligned}
$$

where (i) combines Lemmas 4 and 6, (ii) applies Lemma 23 to $\mathbb{E}^t\mathbb{P}_{\Gamma^\star} \in \Lambda(\mathbb{E}^t P)$ with the choice $\eta = 1/(SLt)$, and (iii) comes from the fact that $\mathbb{E}^t\lambda^{\pi^t} \in \text{argmax}_{\lambda \in \Lambda(\mathbb{E}^t P)} \mathcal{U}_{\widehat{\phi}^t}\left(\lambda, 1/(SLt)\right)$. Hence, retracing the steps of the regret derivation of the proof of Lemma 12, we can bound the Bayes regret

of `VAPOR-lite` as

$$\mathcal{BR}_\phi(\text{VAPOR-lite}, T) \leq \mathbb{E} \sum_{t=1}^{N} \left[\mathcal{U}_{\widehat{\phi}^t}(\mathbb{E}^t \lambda^{\pi^t}, 1/(SLt)) - \sum_{l=1}^{L} \sum_{s,a} \mathbb{E}^t \lambda_l^{\pi^t}(s,a) \mathbb{E}^t r_l(s,a) \right] + \sqrt{2}\widehat{\sigma}_{\max} \sum_{t=1}^{N} \frac{1}{t}$$

$$\leq \underbrace{\mathbb{E} \sum_{t=1}^{N} \sum_{l=1}^{L} \sum_{s,a} \mathbb{E}^t \lambda_l^{\pi^t}(s,a) \sqrt{2}(1 + \log SLt)\widehat{\sigma}_l^t(s,a)}_{:=Z_1}$$

$$+ \underbrace{\mathbb{E} \sum_{t=1}^{N} \sum_{l=1}^{L} \sum_{s,a} \mathbb{E}^t \lambda_l^{\pi^t}(s,a) \sqrt{2}(1 + \log SLt) \sum_{a'} \left(-\widehat{\sigma}_l^t(s,a') \pi_l^t(s,a') \log \pi_l^t(s,a') \right)}_{:=Z_2}$$

$$+ \sqrt{2}\widehat{\sigma}_{\max} \sum_{t=1}^{N} \frac{1}{t}.$$

To bound Z_1 we apply the Cauchy-Schwarz inequality and the pigeonhole principle, as in the proof of Lemma 12, which gives that $Z_1 = \widetilde{O}(\widehat{\sigma}_{\max}\sqrt{SAT})$. To bound Z_2, we introduce the second moment of the information [33] of a discrete random variable X supported on finite set $\mathcal{X}$ as

$$\mathcal{H}^{(2)}(X) := \sum_{x \in \mathcal{X}} \mathbb{P}(X = x) \left(-\log \mathbb{P}(X = x) \right)^2,$$

and note that $\mathcal{H}^{(2)}(X) \leq \log^2(|\mathcal{X}|)$ for $|\mathcal{X}| \geq 3$ [33, Proposition 8]. We bound

$$Z_2 \overset{\text{(i)}}{\leq} \mathbb{E} \sum_{t=1}^{N} \sum_{l=1}^{L} \sum_{s,a} \mathbb{E}^t \lambda_l^{\pi^t}(s,a) \sqrt{2}(1 + \log SLt)\widehat{\sigma}_l^t(s,a) \left(-\log \mathbb{E}^t \lambda_l^{\pi^t}(s,a) \right)$$

$$\overset{\text{(ii)}}{\leq} \mathbb{E} \sqrt{\sum_{t=1}^{N} \sum_{l=1}^{L} \mathcal{H}^{(2)}(\mathbb{E}^t \lambda_l^{\pi^t})} \sqrt{\sum_{t=1}^{N} \sum_{l=1}^{L} \sum_{s,a} 2\mathbb{E}^t \lambda_l^{\pi^t}(s,a)(1 + \log SLt)^2 \widehat{\sigma}_l^t(s,a)^2}$$

$$\overset{\text{(iii)}}{\leq} \widetilde{O}(\widehat{\sigma}_{\max}\sqrt{SAT}),$$

where (i) uses that $\mathbb{E}^t \lambda_l^{\pi^t}(s,a) \leq \pi_l^t(s,a)$, (ii) applies the Cauchy-Schwarz inequality and (iii) uses the pigeonhole principle (as in the Z_1 bound) combined with the aforementioned logarithmic upper bound on $\mathcal{H}^{(2)}$. Finally, we bound the last term by using that $\sum_{t=1}^{N} \frac{1}{t} \leq 1 + \log N$. Putting everything together and using that $\widehat{\sigma}_{\max} = O(L)$ yields the desired bound $\mathcal{BR}_\phi(\text{VAPOR-lite}, T) \leq \widetilde{O}(L\sqrt{SAT})$. $\square$

F Experiments

F.1 Reward-Free GridWorld

We empirically complement our discussion in Section 6
on the connection of `VAPOR` to maximum entropy ex-
ploration.   We consider a simple 4-room GridWorld
domain with no rewards, known deterministic transi-
tions, four cardinal actions and varying state space size.
We measure the ability of the agent to cover the state-
action space as quickly as possible, *i.e.*, visit each state-
action at least once. We consider the state-of-the-art al-
gorithm of [77] for the original maximum entropy ex-
ploration objective $\max_{\lambda \in \Lambda(P)} \mathcal{H}(\lambda)$, and compare it
to the same algorithm that optimizes for weighted en-
tropy $\max_{\lambda \in \Lambda(P)} \mathcal{H}_\sigma(\lambda)$, where we define the uncertainty
as $\sigma(s, a) = \mathbb{1}\{n(s, a) = 0\}$, with $n(s, a)$ the visitation
count to state-action (s, a). We see in Figure 6 that opti-
mizing for this weighted entropy objective results in faster

Figure 6: Optimizing for a weighted maxi-
mum entropy objective results in faster cov-
erage time and thus more aggressive explo-
ration in a reward-free GridWorld.

coverage time. This illustrates the exploration benefits of the state-action weighted entropy regular-
ization of `VAPOR` (*e.g.*, weighted by the uncertainty).

F.2 DeepSea (tabular)

We provide details on the experiment of Figure 3. For the transition function we use a prior
Dirichlet$(1/\sqrt{S})$ and for rewards a standard normal $\mathcal{N}(0, 1)$, as done by [52]. Similar to [61, 46, 39],
we accelerate learning by imagining that each experienced transition (s, a, s', r) is repeated 100 times.
Effectively, this strategy forces the MDP posterior to shrink faster without favoring any algorithm,
making them all converge in fewer episodes. In our implementation of `VAPOR`, we use CVXPY [11] to
solve the `VAPOR` optimization problem. For a reader interested in implementing it, note that although
the expression $x\sqrt{-\log x}$ that appears in the $\mathcal{V}_\phi$ function (4) is not an atomic function in CVXPY, a
simple trick is to use the equivalence

$$
\begin{array}{llll}
\max_{x} & x\sqrt{-\log x} & \Longleftrightarrow & \max_{x,y} \quad y \\[2mm]
\text{s.t.} & x \geq 0 & & \text{s.t.} \quad x \geq 0, \quad y \geq 0, \quad -x\log x \geq y^2/x
\end{array}
$$

where $-x \log x$ (cvxpy.entr(x)) and y^2/x (cvxpy.quad_over_lin(y, x)) are atomic functions.

F.3 DeepSea (neural network)

We consider the DeepSea domain where instead of using
a tabular state representation, we feed a one-hot represen-
tation of the agent location into a neural network, using
bsuite [57]. As discussed in prior works [61, 52, 48],
agents that do not adequately perform deep exploration
are far from being able to solve depths of up to 100 within
10^5 episodes. This includes vanilla actor-critic or Soft
Q-learning (depth up to around 14, showcasing a learn-
ing time that suffers from an exponential dependence
on depth), but also agents with some exploration mecha-
nisms such as optimistic actor-critic or Bootstrapped DQN
(depth up to around 50). In contrast, Figure 7 shows that
`VAPOR-lite` is able to solve DeepSea instances out to size
100 within 4×10^4 episodes, without a clear performance
degradation. We chose the exact same algorithmic config-
uration and hyperparameter choices as our experiments on

Figure 7: Learning time of `VAPOR-lite` on
DeepSea (one-hot pixel representation into
neural net). Dashed line represents 2^L where
L denotes the depth.

Atari (Appendix F.4), except $\sigma_{\text{scale}} = 3.0$ and Replay fraction $= 0.995$. This experiment shows that
`VAPOR-lite` is capable of *deep exploration*, as suggested by the regret analysis in Appendix E.1.

Common Hyperparameter	Value			
Discount factor	0.995			
Replay buffer size	$1e5$			
Replay fraction	0.9			
Replay prioritization exponent	1.0			
Adam step size	$1e-4$			
λ of V-Trace(λ)	0.9			
Algorithm-specific Hyperparameter (Figure 9)	None	Fixed, scalar	Tuned, scalar	Tuned, state-action
Entropy regularization β	/	0.01	/	/
Uncertainty scale σ_{scale}	0.01	0.01	0.01	0.005
$\tau_{\min}$	/	/	0.005	/
$\tau_{\max}$	/	/	10	/
τ_{init}	/	/	0.02	/
τ step size	/	/	$1e-4$	/

Table 2: Hyperparameters used in the Atari experiments.

F.4 Atari

RL agent. Our setup involves actors generating experience and sending them back to a learner, which mixes online data and offline data from a replay buffer to to update the network weights [30]. Our underlying agent is an actor-critic algorithm with use of replay data, thus we call it 'Replay Actor-Critic (RAC)'. We also made use of V-trace clipped importance sampling to the off-policy trajectories [15]. Replay was prioritized by TD-error and when sampling the replay prioritization exponent was 1.0 [70]. We note that, as commonly done on Atari, we consider the discounted RL setting (rather than the finite-horizon setting used to derive our theoretical results). We refer to Table 2 for hyperparameter details.

Uncertainty measure in `VAPOR-lite`. For the uncertainty measure $\widehat{\sigma}$, we use an ensemble of reward predictors. Specifically, we set it to the standard deviation of $H = 10$ randomly initialized reward prediction heads $\widehat{r}^{(i)}$ with randomized prior functions [55], *i.e.*,

$$\widehat{\sigma}(s,a) = \min\left(\sigma_{\text{scale}}\,\text{std}_{1 \leq i \leq H}(\{\widehat{r}^{(i)}(s,a)\}), 1\right),$$

with $\sigma_{\text{scale}} > 0$ a scaling hyperparameter. We also added a small amount of noise to the rewards in the replay buffer for the targets for the reward prediction ensemble (specifically, 0.1 times an independent standard normal distribution) [14], to prevent the ensemble from potentially collapsing due to the use of replay data.

Baselines. In Figure 4, we compare `VAPOR-lite`, whose policy loss may be condensely expressed as

$$\max_{\pi \in \Pi} \quad (\mu^\pi \pi)^\top (r + \widehat{\sigma}) + (\mu^\pi)^\top (\mathcal{H}_{\widehat{\sigma}}(\pi)), \tag{16}$$

to a standard actor-critic objective

$$\max_{\pi \in \Pi} \quad (\mu^\pi \pi)^\top r, \tag{17}$$

as well as to an actor-critic with *fixed scalar* entropy regularization

$$\max_{\pi \in \Pi} \quad (\mu^\pi \pi)^\top r + (\mu^\pi)^\top (\beta \mathcal{H}(\pi)), \tag{18}$$

where $\beta > 0$ is a hyperparameter (*e.g.*, $\beta = 0.01$ in [41], which is also used in Figure 4 as it performed best). We later compare to additional baselines (Figure 9).

Figure 8: Per-game human normalized score (averaged over 5 seeds).

Figure 9: Median human normalized score across 57 Atari games (with standard errors across 5 seeds) of an *optimistic* replay actor-critic agent, for different choices of *entropy regularization*. `VAPOR-lite`'s 'tuned, state-action' performs best.

On entropy regularization for policy improvement/evaluation. We refer to [82] for in-depth discussion on the difference of using entropy for policy improvement and/or for policy evaluation in entropy-regularized RL. Theory prescribes both [85] and some algorithms such as Soft Actor-Critic [26] implement both, yet as remarked by [82], omitting entropy for policy evaluation (*i.e.*, not having entropy as an intrinsic reward) tends to result in more stable and efficient learning. We also observed the same and thus only use entropy for policy improvement.

Related works. We mention here a couple of related works to our proposed algorithm. First, [22] argue that standard policy entropy regularization can be harmful when the RL problem contains actions that are rarely useful, and propose a method that uses mutual-information regularization to optimize a prior action distribution. Second, [27] discuss the limitation of policy entropy regularization being 'sample-unaware', and propose to regularize with respect to the entropy of a weighted sum of the policy action distribution and the sample action distribution from the replay buffer.

Per-game results. Figure 8 reports the performance of the Replay Actor-Critic (RAC) baseline compared to RAC augmented with VAPOR-lite, on each Atari game. We see that VAPOR-lite yields improvements in many games, especially in hard-exploration games such as Montezuma's Revenge or Venture.

Ablation on entropy regularization. `VAPOR-lite` advocates for two ingredients: *optimism* and *weighted entropy regularization*. While the first has already been investigated in deep RL for various choices of uncertainty bonus [4], the second is novel so we focus our attention on it here. For a fair comparison, we augment all agents with the optimistic reward component, to isolate the effect of the adaptive state-action entropy regularization of `VAPOR-lite`. We consider the following policy losses for various choices of entropy regularization

none: $\qquad\max_{\pi\in\Pi}\quad (\mu^\pi\pi)^\top (r+\widehat{\sigma})\,,$

fixed, scalar: $\qquad\max_{\pi\in\Pi}\quad (\mu^\pi\pi)^\top (r+\widehat{\sigma}) + (\mu^\pi)^\top (\beta\mathcal{H}(\pi))\,,$

tuned, scalar [48]: $\qquad\max_{\pi\in\Pi}\min_{\tau>0}\quad (\mu^\pi\pi)^\top \left(r+\widehat{\sigma}^2/(2\tau)\right) + (\mu^\pi)^\top (\tau\mathcal{H}(\pi))\,,$

tuned, state-action (`VAPOR-lite`): $\qquad\max_{\pi\in\Pi}\quad (\mu^\pi\pi)^\top (r+\widehat{\sigma}) + (\mu^\pi)^\top (\mathcal{H}_{\widehat{\sigma}}(\pi))\,.$

In particular, we have further compared to an optimistic actor-critic objective with *tuned, scalar* entropy regularization, specifically the epistemic-risk-seeking objective of [48] which corresponds to solving a principled saddle-point problem between a policy player and a scalar temperature player τ

parameterized by a neural network. We refer to Table 2 for hyperparameter details. We observe in Figure 9 the isolated benefits of `VAPOR-lite`'s *tuned, state-action* entropy regularization.

Future directions. Below we list some relevant directions for future empirical investigation:

- Although our simple $\widehat{\sigma}$ uncertainty measure using an ensemble of reward predictors worked well, more sophisticated domain-specific uncertainty signals could be used [62, 63, 7].
- A first 'looseness' of `VAPOR-lite` with respect to `VAPOR` is that it sets the temperatures τ to the uncertainties $\widehat{\sigma}$ (which yields the same $\widetilde{O}$ regret bound). An interesting extension for `VAPOR-lite` could be to optimize directly the temperatures by minimizing `VAPOR`'s saddle-point problem with a state-action dependent temperature player τ parameterized by an independent neural network.
- A second 'looseness' of `VAPOR-lite` with respect to `VAPOR` is that it bypasses the challenging optimization of the entropy of the state visitation distribution, by only (weight-)regularizing with the entropy of the policy. Various attempts have turned to density models or non-parametric entropy estimation [29, 36, 42], and it could be relevant to incorporate such techniques to get closer to the `VAPOR` objective.
- Our agent is relatively simple compared to modern state-of-the-art Atari agents since it is missing components like model-based rollouts, distributional heads, auxiliary tasks, *etc.* An interesting extension would be to incorporate the techniques discussed in this paper into the most effective policy-based agents.