End-to-end reconstruction meets data-driven regularization for inverse problems

Abstract

We propose an unsupervised approach for learning end-to-end reconstruction operators for ill-posed inverse problems. The proposed method combines the classical variational framework with iterative unrolling, which essentially seeks to minimize a weighted combination of the expected distortion in the measurement space and the Wasserstein-1 distance between the distributions of the reconstruction and ground-truth. More specifically, the regularizer in the variational setting is parametrized by a deep neural network and learned simultaneously with the unrolled reconstruction operator. The variational problem is then initialized with the reconstruction of the unrolled operator and solved iteratively till convergence. Notably, it takes significantly fewer iterations to converge, thanks to the excellent initialization obtained via the unrolled operator. The resulting approach combines the computational efficiency of end-to-end unrolled reconstruction with the well-posedness and noise-stability guarantees of the variational setting. Moreover, we demonstrate with the example of X-ray computed tomography (CT) that our approach outperforms state-of-the-art unsupervised methods, and that it outperforms or is on par with state-of-the-art supervised learned reconstruction approaches.

1 Introduction

Inverse problems are ubiquitous in imaging applications, wherein one seeks to recover an unknown model parameter $\boldsymbol{x} \in \mathbb{X}$ from its incomplete and noisy measurement, given by

$$\boldsymbol{y}^{\delta} = \mathcal{A}(\boldsymbol{x}) + \boldsymbol{e} \in \mathbb{Y}.$$

Here, the forward operator $\mathcal{A} : \mathbb{X} \to \mathbb{Y}$ models the measurement process in the absence of noise, and $\boldsymbol{e}$, with $\|\boldsymbol{e}\|_2 \leq \delta$, denotes the measurement noise. For example, in computed tomography (CT), the forward operator computes line integrals of $\boldsymbol{x}$ over a predetermined set of lines in $\mathbb{R}^3$ and the goal is to reconstruct $\boldsymbol{x}$ from its projections along these lines. Without any further information about $\boldsymbol{x}$, inverse problems are typically ill-posed, meaning that there could be several reconstructions that are consistent with the measurement, even without any noise.

The variational framework circumvents ill-posedness by encoding prior knowledge about $\boldsymbol{x}$ via a regularization functional $\mathcal{R} : \mathbb{X} \to \mathbb{R}$. In the variational setting, one solves

$$\min_{\boldsymbol{x} \in \mathbb{X}} \mathcal{L}_{\mathbb{Y}}(\boldsymbol{y}^{\delta}, \mathcal{A}(\boldsymbol{x})) + \lambda \, \mathcal{R}(\boldsymbol{x}), \tag{1}$$

where $\mathcal{L}_{\mathbb{Y}} : \mathbb{Y} \times \mathbb{Y} \to \mathbb{R}^{+}$ measures data-fidelity and $\mathcal{R}$ penalizes undesirable or unlikely solutions. The penalty $\lambda > 0$ balances the regularization strength with the fidelity of the reconstruction. The variational problem (1) is said to be well-posed if it has a unique solution varying continuously in $\boldsymbol{y}^{\delta}$.

The success of deep learning in recent years has led to a surge of data-driven approaches for solving inverse problems [5], especially in imaging applications. These methods come broadly

in two flavors: (i) end-to-end trained models that aim to directly map the measurement to the corresponding parameter and (ii) learned regularization methods that seek to find a data-adaptive regularizer instead of handcrafting it. Techniques in both categories have their relative advantages and demerits. Specifically, end-to-end approaches offer fast reconstruction of astounding quality, but lack in terms of theoretical guarantees and need supervised data (i.e., pairs of input and target images) for training. On the contrary, learned regularization methods inherit the provable well-posedness properties of the variational setting and can be trained in an unsupervised manner, however the reconstruction entails solving a high-dimensional optimization problem, which is often slow and computationally demanding.

Our work derives ideas from learned optimization and adversarial machine learning, and makes an attempt to combine the best features of both aforementioned paradigms. In particular, the proposed method offers the flexibility of unsupervised training, produces fast reconstructions comparable to end-to-end supervised methods in quality, while enjoying the well-posedness and stability guarantees of the learned regularization framework. We first provide a brief overview of the literature on data-driven techniques for inverse problems before explaining our specific contributions in detail.

1.1 Related works

End-to-end fully learned methods for imaging inverse problems either map the measurement directly to the image [30, 19], or learn to eliminate the artifacts from a model-based technique [10]. Such approaches are data-intensive and may generalize poorly when trained on limited data. Iterative unrolling [17, 29, 2, 11, 16], with its origin in the seminal work by Gregor and LeCun on data-driven sparse coding [9], employs reconstruction networks that are inspired by optimization-based approaches and hence are interpretable. The unrolling paradigm enables one to encode the knowledge about the acquisition physics into the model architecture [3], thereby achieving data-efficiency. Nevertheless, end-to-end trained methods are supervised, and it is often challenging to obtain a large ensemble of paired data, especially in medical imaging applications.

Learned regularization methods, broadly speaking, aim to learn a data-driven regularizer in the variational setting. Some notable approaches in this paradigm include adversarial regularization (AR) [14] and its convex counterpart [18], network Tikhonov (NETT) [13], total deep variation (TDV) [12], etc., wherein one explicitly parametrizes the regularization functional using a neural network. The regularization by denoising (RED) approach aims to solve inverse problems by using a denoiser inside an algorithm for minimizing the variational objective [21, 22, 7]. The Plug-and-play (PnP) method [25] with a learned denoiser is also implicitly equivalent to data-driven regularization, subject to additional constraints on the denoiser [20]. The deep image prior technique [26] does not require training, but it seeks to regularize the solution by restricting it to be in the range of a deep generator and can thus be interpreted broadly as a deep learning-based regularization scheme. It is relatively easier to analyze learned regularization schemes using the machinery of classical functional analysis [24], but they fall short in terms of reconstruction quality. Moreover, these methods require one to solve a high-dimensional, potentially non-convex, variational problem, leading to slow reconstruction and lack of provable convergence.

1.2 Specific contributions

Our work seeks to combine iterative unrolling with data-adaptive regularization via an adversarial learning framework, and hence is referred to as unrolled adversarial regularization (UAR). The proposed approach learns a data-adaptive regularizer parametrized by a neural network, together with an iteratively unrolled reconstruction network that minimizes the corresponding expected variational loss in an adversarial setting. Unlike AR [14] where the undesirable images are taken as the pseudo-inverse reconstruction and kept fixed throughout the training, we update them with the output of the unrolled reconstruction network in each training step, and, in turn, use them to further improve the regularizer. Thanks to the Kantorovich-Rubinstein (KR) duality [4], the alternating learning strategy of the reconstruction and the regularizer networks is equivalent to minimizing the expected data-fidelity over the distribution of the measurements, penalized by the Wasserstein-1 distance between the distribution of the reconstruction and the ground-truth. Once trained, the reconstruction operator produces a fast, end-to-end reconstruction. We show that this efficient reconstruction can be improved further by a refinement step that involves running a few iterations of gradient-descent on the variational loss with the corresponding regularizer, starting from this initial estimate. The refinement

step not only produces reconstructions that outperform state-of-the-art unsupervised methods and are competitive with supervised methods, but also facilitates a well-posedness and stability analyses akin to classical variational approaches [24]. Our theoretical results on the learned unrolled operator and the regularizer are corroborated by strong experimental evidence for the CT inverse problem.

2   The proposed unrolled adversarial regularization (UAR) approach

In this section, we give a short mathematical background on optimal transport, followed by a detailed description of the UAR framework, including the training protocol and the network architectures.

2.1   Background on Optimal transport

Optimal transport theory [8, 27] has recently gained prominence in the context of measuring the distance between two probability distributions. In particular, given two probability distributions π_1 and π_2 on $\mathbb{R}^n$, the Wasserstein-1 distance between them is defined as

$$\mathbb{W}_1(\pi_1, \pi_2) := \inf_{\mu \in \Pi(\pi_1, \pi_2)} \int \|\boldsymbol{x}_1 - \boldsymbol{x}_2\|_2 \, \mathrm{d}\mu(\boldsymbol{x}_1, \boldsymbol{x}_2), \tag{2}$$

where $\Pi(\pi_1, \pi_2)$ denotes all transport plans having π_1 and π_2 as marginals. The Wasserstein distance has proven to be suitable for deep learning tasks, when the data is assumed to be concentrated on low-dimensional manifolds in $\mathbb{R}^n$. It has been shown that in such cases, the Wasserstein distance provides a usable gradient during training [4], as opposed to other popular divergence measures.

By the KR duality, the Wasserstein-1 distance can be computed equivalently by solving a maximization problem over the space of 1-Lipschitz functions (denoted by $\mathbb{L}_1$) as

$$\mathbb{W}_1(\pi_1, \pi_2) = \sup_{\mathcal{R} \in \mathbb{L}_1} \int \mathcal{R}(\boldsymbol{x}_1) \, \mathrm{d}\pi_1(\boldsymbol{x}_1) - \int \mathcal{R}(\boldsymbol{x}_2) \, \mathrm{d}\pi_2(\boldsymbol{x}_2), \tag{3}$$

provided that π_1 and π_2 have compact support [23]. Finally, we recall the definition of push-forward of probability measures, which is used extensively in our theoretical exposition. Given a probability measure π on $\mathscr{A}$ and a measurable map $T : \mathscr{A} \to \mathscr{B}$, we define the push-forward of π by T (denoted as $T_{\#}\pi$) as a probability measure on $\mathscr{B}$ such that $T_{\#}\pi(B) = \pi(T^{-1}(B))$, for all measurable $B \subset \mathscr{B}$.

2.2   Training strategy and model parametrization for UAR

The principal idea behind UAR is to learn an unrolled deep network $\mathcal{G}_\phi : \mathbb{Y} \to \mathbb{X}$ for reconstruction, together with a regularization functional $\mathcal{R}_\theta : \mathbb{X} \to \mathbb{R}$ parametrized by another convolutional neural network (CNN). The role of $\mathcal{R}_\theta$ is to discern ground-truth images from images produced by $\mathcal{G}_\phi$, while $\mathcal{G}_\phi$ learns to minimize the variational loss with $\mathcal{R}_\theta$ as the regularizer. As the images produced by $\mathcal{G}_\phi$ gets better, $\mathcal{R}_\theta$ faces a progressively harder task of telling them apart from the ground-truth images, thus leading to an improved regularizer. On the other hand, as the regularizer improves, the quality of reconstructions obtained using $\mathcal{G}_\phi$ improves simultaneously. Consequently, $\mathcal{G}_\phi$ and $\mathcal{R}_\theta$ helps each other improve as the training progresses via an alternating update scheme.

2.2.1   Adversarial training

Let us denote by π_x the ground-truth distribution and by π_{y^δ} the distribution of the noisy measurement. The UAR algorithm trains $\mathcal{G}_\phi$ and $\mathcal{R}_\theta$ simultaneously starting from an appropriate initialization. At the k^{th} iteration of training, the parameters ϕ of the reconstruction network are updated as

$$\phi_k \in \arg\min_{\phi} J_k^{(1)}(\phi), \text{ where } J_k^{(1)}(\phi) := \mathbb{E}_{\pi_{y^\delta}} \left[\left\| \mathcal{A}(\mathcal{G}_\phi(\boldsymbol{y}^\delta)) - \boldsymbol{y}^\delta \right\|_2^2 + \lambda \, \mathcal{R}_{\theta_k}(\mathcal{G}_\phi(\boldsymbol{y}^\delta)) \right], \tag{4}$$

for a fixed regularizer parameter θ_k. Subsequently, the regularizer parameters are updated as

$$\theta_{k+1} \in \arg\max_{\theta : \mathcal{R}_\theta \in \mathbb{L}_1} J_k^{(2)}(\theta), \text{ where } J_k^{(2)}(\theta) := \mathbb{E}_{\pi_{y^\delta}} \left[\mathcal{R}_\theta \left(\mathcal{G}_{\phi_k}(\boldsymbol{y}^\delta) \right) \right] - \mathbb{E}_{\pi_x} \left[\mathcal{R}_\theta \left(\boldsymbol{x} \right) \right]. \tag{5}$$

The learning protocol for UAR is unsupervised, since the loss functionals $J_k^{(1)}(\phi)$ and $J_k^{(2)}(\theta)$ can be computed based solely on the marginals π_x and π_{y^δ}. The alternating update algorithm in (4) and (5)

Algorithm 1 Learning unrolled adversarial regularization (UAR).

---

1. Input: Data-set $\{\boldsymbol{x}_i\}_{i=1}^{N} \sim \pi_x$ and $\{\boldsymbol{y}_j\}_{j=1}^{N} \sim \pi_{y^\delta}$, initial reconstruction network parameter ϕ and regularizer parameter θ, batch-size $n_b = 1$, penalty $\lambda = 0.1$, gradient penalty $\lambda_{\mathrm{gp}} = 10.0$, Adam optimizer parameters $(\beta_1, \beta_2) = (0.50, 0.99)$.

2. (Learn a baseline regularizer) for mini-batch $k = 1, 2, \cdots, 10\frac{N}{n_b}$**, do:**

- Sample $\boldsymbol{x}_j \sim \pi_x$, $\boldsymbol{y}_j \sim \pi_{y^\delta}$, and $\epsilon_j \sim \mathrm{uniform}\,[0,1]$; for $1 \le j \le n_b$. Compute $\boldsymbol{u}_j = \mathcal{A}^\dagger(\boldsymbol{y}_j)$ and $\boldsymbol{x}_j^{(\epsilon)} = \epsilon_j \boldsymbol{x}_j + (1 - \epsilon_j)\,\boldsymbol{u}_j$.

- $\theta \leftarrow \mathrm{Adam}_{\eta,\beta_1,\beta_2}(\theta, \nabla \tilde{J}_1(\theta))$, where $\eta = 10^{-4}$, and

$$\tilde{J}_1(\theta) = \frac{1}{n_b}\sum_{j=1}^{n_b}\left[\mathcal{R}_\theta\left(\boldsymbol{x}_j\right) - \mathcal{R}_\theta\left(\boldsymbol{u}_j\right) + \lambda_{\mathrm{gp}}\left(\left\|\nabla\mathcal{R}_\theta\left(\boldsymbol{x}_j^{(\epsilon)}\right)\right\|_2 - 1\right)^2\right].$$

3. (Learn a baseline reconstruction operator) for mini-batch $k = 1, 2, \cdots, 5\frac{N}{n_b}$**, do:**

- Sample $\boldsymbol{y}_j \sim \pi_{y^\delta}$, and compute $\tilde{J}_2(\phi) = \frac{1}{n_b}\sum_{j=1}^{n_b}\left\|\boldsymbol{y}_j - \mathcal{A}\left(\mathcal{G}_\phi(\boldsymbol{y}_j)\right)\right\|_2^2 + \lambda\,\mathcal{R}_\theta\left(\mathcal{G}_\phi(\boldsymbol{y}_j)\right)$.

- $\phi \leftarrow \mathrm{Adam}_{\eta,\beta_1,\beta_2}(\phi, \nabla\tilde{J}_2(\phi))$, with $\eta = 10^{-4}$.

4. (Jointly train $\mathcal{R}_\theta$ and $\mathcal{G}_\phi$ adversarially) for mini-batch $k = 1, 2, \cdots, 25\frac{N}{n_b}$**, do:**

- Sample $\boldsymbol{x}_j$, $\boldsymbol{y}_j$, and $\epsilon_j \sim \mathrm{uniform}\,[0,1]$; for $1 \le j \le n_b$. Compute $\boldsymbol{u}_j = \mathcal{G}_\phi(\boldsymbol{y}_j)$ and $\boldsymbol{x}_j^{(\epsilon)} = \epsilon_j \boldsymbol{x}_j + (1 - \epsilon_j)\,\boldsymbol{u}_j$.

- $\theta \leftarrow \mathrm{Adam}_{\eta,\beta_1,\beta_2}(\theta, \nabla\tilde{J}_1(\theta))$, where $\tilde{J}_1(\theta)$ is as in Step 2, with $\eta = 2 \times 10^{-5}$.

- Update $\phi \leftarrow \mathrm{Adam}_{\eta,\beta_1,\beta_2}(\phi, \nabla\tilde{J}_2(\phi))$ twice, with $\tilde{J}_2(\phi)$ as in Step 3, and $\eta = 2 \times 10^{-5}$.

5. Output: The trained networks $\mathcal{G}_\phi$ and $\mathcal{R}_\theta$.

---

essentially seeks to solve the min-max variational problem given by

$$\min_{\phi}\ \max_{\theta:\mathcal{R}_\theta\in\mathbb{L}_1}\ \mathbb{E}_{\pi_{y^\delta}}\left\|\mathcal{A}(\mathcal{G}_\phi(\boldsymbol{y}^\delta)) - \boldsymbol{y}^\delta\right\|_2^2 + \lambda\left(\mathbb{E}_{\pi_{y^\delta}}\left[\mathcal{R}_\theta\left(\mathcal{G}_\phi(\boldsymbol{y}^\delta)\right)\right] - \mathbb{E}_{\pi_x}\left[\mathcal{R}_\theta\left(\boldsymbol{x}\right)\right]\right). \quad (6)$$

Thanks to KR duality in (3) and the definition of push-forward, (6) can be reformulated as

$$\min_{\phi}\ \mathbb{E}_{\pi_{y^\delta}}\left\|\mathcal{A}(\mathcal{G}_\phi(\boldsymbol{y}^\delta)) - \boldsymbol{y}^\delta\right\|_2^2 + \lambda\mathbb{W}_1\left((\mathcal{G}_\phi)_\#\pi_{y^\delta}, \pi_x\right). \quad (7)$$

We refer the reader to Section 3 for a mathematically rigorous statement of this equivalence as well as for a well-posedness theory of the problem in (7). Note that the equivalence of the alternating minimization procedure and the variational problem in (7) holds only if the regularizer is fully optimized in every iteration. Nevertheless, in practice, the reconstruction and regularizer networks are not fully optimized in every iteration. Instead, one refines the parameters by performing one (or a few) Adam updates on the corresponding loss functionals. Notably, if $\mathbb{W}_1\left((\mathcal{G}_{\phi_k})_\#\pi_{y^\delta}, \pi_x\right) = 0$, i.e., the parameters of $\mathcal{G}$ are such that the reconstructed images match the ground-truth in distribution, the loss functional $J_k^{(2)}(\theta)$ and its gradient vanish, leading to no further update of θ. Thus, both networks stop updating when the outputs of $\mathcal{G}_\phi$ are indistinguishable from the ground-truth images. The concrete training steps are listed in Algorithm 1.

2.2.2 Iteratively unrolled reconstruction operator

The objective of $\mathcal{G}_\phi$ is to approximate the minimizer of the variational loss with $\mathcal{R}_\theta$ as the regularizer. Therefore, an iterative unrolling strategy akin to [3] is adopted for parameterizing $\mathcal{G}_\phi$. Iterative unrolling seeks to mimic the variational minimizer via a primal-dual-style algorithm [6], with the proximal operators in the image and measurement spaces replaced with trainable CNNs. Although the variational loss in our case is non-convex, this parametrization for $\mathcal{G}_\phi$ is chosen because of its expressive power over a generic network. Initialized with $\boldsymbol{x}^{(0)} = \mathcal{A}^\dagger\boldsymbol{y}^\delta$ and $\boldsymbol{h}^{(0)} = \boldsymbol{0}$, $\mathcal{G}_\phi$ produces a reconstruction $\boldsymbol{x}^{(L)}$ by iteratively applying the CNNs $\Lambda_{\phi_{\mathrm{p}}^{(\ell)}}$ and $\Lambda_{\phi_{\mathrm{d}}^{(\ell)}}$ in $\mathbb{X}$ and $\mathbb{Y}$, respectively:

$$\boldsymbol{h}^{(\ell+1)} = \Gamma_{\phi_{\mathrm{d}}^{(\ell)}}\left(\boldsymbol{h}^{(\ell)}, \sigma^{(\ell)}\mathcal{A}(\boldsymbol{x}^\ell), \boldsymbol{y}^\delta\right),\ \text{and}\ \boldsymbol{x}^{(\ell+1)} = \Lambda_{\phi_{\mathrm{p}}^{(\ell)}}\left(\boldsymbol{x}^{(\ell)}, \tau^{(\ell)}\mathcal{A}^*(\boldsymbol{h}^{\ell+1})\right), 0 \le \ell \le L-1.$$

144 The step-size parameters $\sigma^{(\ell)}$ and $\tau^{(\ell)}$ are also made learnable and initialized as $\sigma^{(\ell)} = \tau^{(\ell)} = 0.01$
145 for each layer ℓ. The number of layers L is typically much smaller (we take $L = 20$) than the number
146 of iterations needed by an iterative primal-dual scheme to converge, thus expediting the reconstruction
147 by two orders of magnitude once trained.

148 The regularizer $\mathcal{R}_\theta$ is taken as a deep CNN with six convolutional layers, followed by one average-
149 pooling and two dense layers in the end.

2.2.3 Variational regularization as a refinement step

151 The unrolled operator $\mathcal{G}_{\phi^*}$ trained by solving the min-max problem in (6) provides reasonably good
152 reconstruction when evaluated on X-ray CT, and already outperforms state-of-the-art unsupervised
153 methods (c.f. Section 4). We demonstrate that the regularizer $\mathcal{R}_{\theta^*}$ obtained together with $\mathcal{G}_{\phi^*}$ by
154 solving (6) can be used in the variational framework to further improve the quality of the end-to-end
155 reconstruction $\mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta)$ for a given $\boldsymbol{y}^\delta \in \mathbb{Y}$. Specifically, we solve the variational problem

$$\min_{\boldsymbol{x} \in \mathbb{X}} \| \mathcal{A}(\boldsymbol{x}) - \boldsymbol{y}^\delta \|_2 + \lambda' \left(\mathcal{R}_{\theta^*}(\boldsymbol{x}) + \sigma \| \boldsymbol{x} \|_2^2 \right), \tag{8}$$

156 where $\lambda', \sigma \geq 0$, by applying gradient descent, initialized with $\mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta)$. The additional Tikhonov
157 term in (8) ensures coercivity of the overall regularizer, making it amenable to the standard well-
158 posedness analysis [24]. Practically, it improves the stability of the gradient descent optimizer
159 for (8). In practice, one essentially gets the same reconstruction with $\sigma = 0$ subject to early
160 stopping (100 iterations). Notably, the fidelity term in (8) is the ℓ_2 distance, instead of the squared-ℓ_2
161 fidelity. We have empirically observed that this choice of the fidelity term improves the quality
162 of the reconstruction, possibly due to the higher gradient of the objective in the initial solution
163 $\mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta)$. Since the end-to-end reconstruction gives an excellent initial point, it takes significantly
164 fewer iterations for gradiet-descent to recover the optimal solution to (8), and therefore UAR retains
165 its edge in reconstruction time over fully variational approaches with learned regularizers (e.g., AR
166 [14] or its convex version [18]).

3 Theoretical results

168 The theoretical properties of UAR are stated in this section and their proofs are provided in the
169 supplementary document. Throughout this section, we assume that $\mathbb{X} = \mathbb{R}^n$ and $\mathbb{Y} = \mathbb{R}^k$, and

170 A1. π_x is compactly supported and π_{y^δ} is supported on a compact set $K \subset \mathbb{R}^k$ for every $\delta \geq 0$.

171 We then consider the following problem:

$$\inf_{\phi} \sup_{\mathcal{R} \in \mathbb{L}_1} J_1 \left(\mathcal{G}_\phi, \mathcal{R} | \lambda, \pi_{y^\delta} \right) := \mathbb{E}_{\pi_{y^\delta}} \left\| \boldsymbol{y}^\delta - \mathcal{A}\, \mathcal{G}_\phi(\boldsymbol{y}^\delta) \right\|_2^2 + \lambda \left(\mathbb{E}_{\pi_{y^\delta}} \left[\mathcal{R}(\mathcal{G}_\phi(\boldsymbol{y}^\delta)) \right] - \mathbb{E}_{\pi_x} \left[\mathcal{R}(\boldsymbol{x}) \right] \right). \tag{9}$$

172 Problem (9) is identical to the min-max variational problem defined in (6), with the only difference
173 that the maximization in $\mathcal{R}$ is performed over the space of all 1-Lipschitz functions. Basically,
174 we consider the theoretical limiting case where the neural networks $\mathcal{R}_\theta$ are expressive enough to
175 approximate all functions in $\mathbb{L}_1$ with arbitrary accuracy. We make the following assumptions on $\mathcal{G}_\phi$:

176 A2. $\mathcal{G}_\phi$ is parametrized over a finite dimensional compact set K, i.e. $\phi \in K$.

177 A3. $\mathcal{G}_{\phi_n} \to \mathcal{G}_\phi$ pointwise whenever $\phi_n \to \phi$.

178 A4. $\sup_{\phi \in K} \| \mathcal{G}_\phi \|_\infty < \infty$.

179 Assumptions A2-A4 are satisfied, for instance, when $\mathcal{G}_\phi$ is parametrized by a neural network whose
180 weights are kept bounded during training. These assumptions apply to all results in this section.

3.1 Well-posedness of the adversarial loss

182 Here, we prove well-posedness and stability to noise for the optimal reconstructions. As a conse-
183 quence of the KR duality, (9) can be equivalently expressed as

$$\inf_{\phi} J_2 \left(\mathcal{G}_\phi | \lambda, \pi_{y^\delta} \right) := \mathbb{E}_{\pi_{y^\delta}} \left\| \boldsymbol{y}^\delta - \mathcal{A}\, \mathcal{G}_\phi(\boldsymbol{y}^\delta) \right\|_2^2 + \lambda \, \mathbb{W}_1(\pi_x, (\mathcal{G}_\phi)_\# \pi_{y^\delta}). \tag{10}$$

184 In the next theorem, we prove this equivalence, showing the existence of an optimal $\mathcal{G}_\phi$ and $\mathcal{R}$ for (9).

Theorem 1. *Problems* (9) *and* (10) *admit an optimal solution and*

$$\inf_{\phi} \sup_{\mathcal{R} \in \mathbb{L}_1} J_1 \left(\mathcal{G}_\phi, \mathcal{R} | \lambda, \pi_{y^\delta} \right) = \inf_{\phi} J_2 \left(\mathcal{G}_\phi | \lambda, \pi_{y^\delta} \right). \tag{11}$$

Moreover, if $(\mathcal{G}_{\phi^*}, \mathcal{R}^*)$ *is optimal for* (9)*, then* $\mathcal{G}_{\phi^*}$ *is optimal for* (10)*. Conversely, if* $\mathcal{G}_{\phi^*}$ *is optimal for* (10)*, then* $(\mathcal{G}_{\phi^*}, \mathcal{R}^*)$ *is optimal for* (9)*, for all* $\mathcal{R}^* \in \arg\max_{\mathcal{R} \in \mathbb{L}_1} \mathbb{E}_{\pi_{y^\delta}} \left[\mathcal{R}(\mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta)) \right] - \mathbb{E}_{\pi_x} \left[\mathcal{R}(\boldsymbol{x}) \right].$

Next, we study the stability of the optimal reconstruction $\mathcal{G}_{\phi^*}$ to noise. We consider $\mathcal{G}_{\phi_n}$, where

$$\phi_n \in \arg\inf_{\phi} J_2 \left(\mathcal{G}_\phi | \lambda, \pi_{y^{\delta_n}} \right), \tag{12}$$

and show that $\mathcal{G}_{\phi_n} \to \mathcal{G}_{\phi^*}$ as $\delta_n \to \delta$, thus establishing noise-stability of the unrolled reconstruction.

Theorem 2 (Stability to noise). *Suppose, for given a sequence of noise levels* $\delta_n \to \delta \in [0, \infty)$*, it holds that* $\pi_{y^{\delta_n}} \to \pi_{y^\delta}$ *in total variation. Then, with* ϕ_n *as in* (12)*,* $\mathcal{G}_{\phi_n} \to \mathcal{G}_{\phi^*}$ *up to sub-sequences.*

3.2 Effect of λ on the end-to-end reconstruction

In order to analyze the effect of the parameter λ in (10) on the resulting reconstruction $\mathcal{G}_{\phi^*}$, it is convenient to introduce the following two sets:

$$\Phi_{\mathcal{L}} := \left\{ \phi : \mathbb{E}_{\pi_{y^\delta}} \left\| \boldsymbol{y}^\delta - \mathcal{A} \mathcal{G}_\phi(\boldsymbol{y}^\delta) \right\|_2^2 = 0 \right\} \text{ and } \Phi_{\mathbb{W}} := \left\{ \phi : (\mathcal{G}_\phi)_\# \pi_{y^\delta} = \pi_x \right\}.$$

We assume that both $\Phi_{\mathcal{L}}$ and $\Phi_{\mathbb{W}}$ are non-empty, which is tantamount to asking that the parametrization of the end-to-end reconstruction operator is expressive enough to approximate a right inverse of $\mathcal{A}$ ($\Phi_{\mathcal{L}} \neq \emptyset$) and a transport map from π_{y^δ} to π_x ($\Phi_{\mathbb{W}} \neq \emptyset$), and therefore is not very restrictive (keeping in view the enormous approximation power of unrolled deep architectures).

Proposition 1. *Let* $\mathcal{G}_{\phi^*}$ *be a minimizer for* (10)*. Then, it holds that*

- $\mathbb{E}_{\pi_y} \left\| \boldsymbol{y}^\delta - \mathcal{A} \mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta) \right\|_2^2 \leq \lambda \mathbb{W}_1(\pi_x, (\mathcal{G}_\phi)_\# \pi_{y^\delta}), \quad$ *for every* $\phi \in \Phi_{\mathcal{L}}$.

- $\mathbb{W}_1(\pi_x, (\mathcal{G}_{\phi^*})_\# \pi_{y^\delta}) \leq \dfrac{1}{\lambda} \mathbb{E}_{\pi_{y^\delta}} \left\| \boldsymbol{y}^\delta - \mathcal{A} \mathcal{G}_\phi(\boldsymbol{y}^\delta) \right\|_2^2, \quad$ *for every* $\phi \in \Phi_{\mathbb{W}}$.

The previous proposition shows in a quantitative way that for small λ, the optimal $\mathcal{G}_{\phi^*}$ has less expected distortion in the measurement space as the quantity $\mathbb{E}_{\pi_{y^\delta}} \left\| \boldsymbol{y}^\delta - \mathcal{A} \mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta) \right\|_2^2$ is small. On the other hand, if λ is large, then the optimal $\mathcal{G}_{\phi^*}$ maps π_{y^δ} is closer to π_x as the quantity $\mathbb{W}(\pi_x, (\mathcal{G}_{\phi^*})_\# \pi_{y^\delta})$ is small. Therefore, the regularization is stronger in this case.

We extend this analysis by studying the behavior of the unrolled reconstruction as λ converges to 0 and to $+\infty$. Consider a sequence of parameters $\lambda_n > 0$ and the minimizer of the objective in (10) with parameter λ_n:

$$\phi_n' \in \arg\inf_{\phi} J_2 \left(\mathcal{G}_\phi | \lambda_n, \pi_{y^\delta} \right). \tag{13}$$

Theorem 3. *Suppose that* $\lambda_n \to 0$ *and* $\phi_1^* \in \arg\min_{\phi \in \Phi_{\mathcal{L}}} \mathbb{W}_1(\pi_x, (\mathcal{G}_\phi)_\# \pi_{y^\delta})$. *Then,* $\mathcal{G}_{\phi_n'} \to \mathcal{G}_{\phi_1^*}$ *up to sub-sequences, and* $\lim_{n \to \infty} \inf_{\phi} J_2 \left(\mathcal{G}_\phi | \lambda_n, \pi_{y^\delta} \right) = \mathbb{W}_1(\pi_x, (\mathcal{G}_{\phi_1^*})_\# \pi_{y^\delta})$.

Theorem 4. *Let* $\lambda_n \to +\infty$ *and* $\phi_2^* \in \arg\min_{\phi \in \Phi_{\mathbb{W}}} \mathbb{E}_{\pi_{y^\delta}} \left\| \boldsymbol{y}^\delta - \mathcal{A} \mathcal{G}_\phi(\boldsymbol{y}^\delta) \right\|_2^2$. *Then,* $\mathcal{G}_{\phi_n'} \to \mathcal{G}_{\phi_2^*}$ *up to sub-sequences, and* $\lim_{n \to \infty} \inf_{\phi} J_2 \left(\mathcal{G}_\phi | \lambda_n, \pi_{y^\delta} \right) = \mathbb{E}_{\pi_{y^\delta}} \left\| \boldsymbol{y}^\delta - \mathcal{A} \mathcal{G}_{\phi_2^*}(\boldsymbol{y}^\delta) \right\|_2^2$.

Theorems 3 and 4 characterize the optimal end-to-end reconstruction $\mathcal{G}_{\phi^*}$ as $\lambda \to 0$ and $\lambda \to \infty$, respectively. Specifically, if $\lambda \to 0$, $\mathcal{G}_{\phi^*}$ minimizes the Wasserstein distance between reconstruction and ground-truth among all the reconstruction operators that achieve zero expected data-distortion. In particular, $\mathcal{G}_{\phi^*}$ is close to the right inverse of $\mathcal{A}$ that minimizes the Wasserstein distance. Therefore, when λ is very small, we expect to obtain a reconstruction that is close to the unregularized solution in quality. If $\lambda \to \infty$ on the other hand, the operator $\mathcal{G}_{\phi^*}$ is close to a transport map between π_x and π_{y^δ}, i.e., $(\mathcal{G}_{\phi^*})_\# \pi_{y^\delta} = \pi_x$, which minimizes the expected data-distortion. Therefore the reconstruction produces realistic images, but they are not consistent with the measurement. These theoretical observations are corroborated by the numerical results (c.f. Section 4, Fig. 2). One has to thus select a λ that optimally trades-off data-distortion with the Wasserstein distance to achieve the best reconstruction performance.

method		PSNR (dB)	SSIM	# param.	reconstruction time (ms)
FBP		21.28 ± 0.13	0.20 ± 0.02	1	37.0 ± 4.6
TV		30.31 ± 0.52	0.78 ± 0.01	1	28371.4 ± 1281.5
Supervised methods					
U-Net		34.50 ± 0.65	0.90 ± 0.01	7215233	44.4 ± 12.5
LPD		35.69 ± 0.60	0.91 ± 0.01	1138720	279.8 ± 12.8
Unsupervised methods					
AR		33.82 ± 0.61	0.86 ± 0.01	19338465	22567.1 ± 309.7
ACR		31.55 ± 0.54	0.85 ± 0.01	606610	109952.4 ± 497.8
UAR	$\lambda = 0.001$	21.59 ± 0.11	0.22 ± 0.02	20477186	252.7 ± 13.3
	$\lambda = 0.01$	25.25 ± 0.08	0.37 ± 0.01		
	$\lambda = 0.1$	34.11 ± 0.66	0.87 ± 0.01		
	$\lambda = 1.0$	33.27 ± 0.76	0.87 ± 0.01		
UAR with refinement	$\lambda = \lambda' = 0.1$	34.55 ± 0.67	0.89 ± 0.01	–	5863.3 ± 106.1

Table 1: Average PSNR and SSIM (with their standard deviations) for different reconstruction methods. The reconstruction times and the number of learnable parameters are also indicated. Without any refinement, UAR outperforms AR and ACR in reconstruction quality and reduces the reconstruction time by a couple of orders of magnitude. With the refinement, UAR becomes on par with supervised post-processing, but the reconstruction time is still four times smaller than AR.

3.3 End-to-end reconstruction vis-à-vis the variational solution

The goal of this section is two-fold. Firstly, we theoretically justify the fact that the end-to-end reconstruction performs well, despite minimizing the expected loss over the distribution π_{y^δ}. Secondly, we analyze the role of the regularizer in the variational setting in refining the end-to-end reconstruction.

It is important to remark that the the end-to-end reconstruction is trained in on the expected variational loss computed using samples from π_{y^δ} and π_x. Therefore, the end-to-end reconstruction cannot learn a point-wise correspondence between measurement and model parameter, but only a distributional correspondence. Despite that, the end-to-end reconstruction achieves excellent performance for a given measurement vector $\boldsymbol{y}$. A justification of such phenomena is given by the next proposition.

Proposition 2. *Let $(\mathcal{G}_{\phi^*}, \mathcal{R}^*)$ be an optimal pair for (9) such that $\mathcal{R}^* \geq 0$ almost everywhere under $(\mathcal{G}_\phi)_{\#} \, \pi_{y^\delta}$. Define $M_1 := \mathbb{E}_{\pi_{y^\delta}} \left\| \boldsymbol{y}^\delta - \mathcal{A} \, \mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta) \right\|_2^2$ and $M_2 := \mathbb{W}_1(\pi_x, (\mathcal{G}_{\phi^*})_{\#} \pi_{y^\delta})$. Then, the following two upper bounds hold for every $\eta > 0$:*

- $\mathbb{P}_{\pi_{y^\delta}} \left\{ \boldsymbol{y}^\delta : \left\| \boldsymbol{y}^\delta - \mathcal{A} \, \mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta) \right\|_2^2 \geq \eta \right\} \leq \frac{M_1}{\eta}.$

- *Suppose, $\mathcal{R}^*(\boldsymbol{x}) = 0$ for π_x-almost every $\boldsymbol{x}$. Then, $\mathbb{P}_{(\mathcal{G}_{\phi^*})_{\#} \pi_{y^\delta}} \left\{ \boldsymbol{x} : \mathcal{R}^*(\boldsymbol{x}) \geq \eta \right\} \leq \frac{M_2}{\eta}.$*

Proposition 2 provides an estimate in probability of the sets $\{ \boldsymbol{y}^\delta : \left\| \boldsymbol{y}^\delta - \mathcal{A} \, \mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta) \right\|_2^2 \geq \eta \}$ and $\{ \boldsymbol{x} : \mathcal{R}^*(\boldsymbol{x}) \geq \eta \}$. In particular, if M_1 is small, then $\left\| \boldsymbol{y}^\delta - \mathcal{A} \, \mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta) \right\|_2^2$ is small in probability. If instead M_2 is small, then $\mathcal{R}^*(\boldsymbol{x})$ is small in probability on the support of $(\mathcal{G}_{\phi^*})_{\#} \pi_{y^\delta}$, implying that samples $\mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta)$ are difficult to distinguish from the ground-truth. We remark that the assumption $\mathcal{R}^*(\boldsymbol{x}) = 0$ can be justified using a data manifold assumption as in Section 3.3. of [14]. We now analyze the role of the regularizer $\mathcal{R}^*$ in the optimization of the variational problem (8) that refines the end-to-end reconstruction $\mathcal{G}_{\phi^*}$. We rely on a similar distributional analysis as the one performed in [14]. For $\eta > 0$, consider the transformation by a gradient-descent step on $\mathcal{R}^*$ given by $g_\eta(\boldsymbol{x}) = \boldsymbol{x} - \eta \nabla \mathcal{R}^*(\boldsymbol{x})$. Using the shorthand $\pi_{\mathcal{G}^*} := (\mathcal{G}_{\phi^*})_{\#} \pi_{y^\delta}$, and by denoting the distribution of $g_\eta(\boldsymbol{x})$ as $\pi_\eta := (g_\eta)_{\#} \pi_{\mathcal{G}^*}$ for $\boldsymbol{x} \sim \pi_{\mathcal{G}^*}$, we have the following theorem.

Theorem 5 ([14]). *Suppose that $\eta \to \mathbb{W}_1(\pi_\eta, \pi_x)$ is differentiable at $\eta = 0$. Then, the derivative at $\eta = 0$ satisfies $\frac{\mathrm{d}}{\mathrm{d}\eta} \mathbb{W}_1(\pi_\eta, \pi_x) \Big|_{\eta=0} = -\mathbb{E}_{\pi_{\mathcal{G}^*}} \| \nabla \mathcal{R}^*(\boldsymbol{x}) \|_2^2.$*

(a) ground-truth   (b) FBP: 21.19 dB, 0.22   (c) TV: 29.85 dB, 0.79   (d) U-net: 34.42 dB, 0.90

(e) LPD: 35.76 dB, 0.92   (f) ACR: 31.24 dB, 0.86   (g) AR: 33.52 dB, 0.86   (h) UAR: 33.85 dB, 0.87

Figure 1: Reconstruction on Mayo clinic data. UAR achieves better reconstruction quality than AR and ACR, while significantly reducing the reconstruction time (c.f. Table 1). The reduction in reconstruction time comes at the expense of higher training complexity as compared to AR.

(a) $\lambda = 0.001$: 21.60, 0.21   (b) $\lambda = 0.01$: 25.33, 0.37   (c) $\lambda = 0.1$: 34.65, 0.88   (d) $\lambda = 1.0$: 33.96, 0.88

Figure 2: Reconstruction of UAR for different λ. For $\lambda \to 0$, the unrolled generator seeks to find the minimizer of the expected data-fidelity loss, hence the reconstruction looks similar to FBP.

This theorem states that a gradient-descent step performed on $\mathcal{R}^*$ at $\boldsymbol{x} = \mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta)$ decreases the Wasserstein distance with respect to the ground-truth distribution π_x. Therefore, if the gradient-descent step to solve the variational problem (8) is initialized with the reconstruction $\mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta)$, the next iterate gets pushed closer to the ground-truth distribution π_x. We stress that this property holds because of the chosen initialization point, due to the relation between $\mathcal{R}^*$ and $\mathcal{G}_{\phi^*}$. For a different initialization, this property may not hold.

4 Numerical results

On the application front, we consider the prototypical inverse problem of CT reconstruction from noisy sparse-view projections. The abdominal CT scans for 10 patients, made publicly available by the Mayo-Clinic for the low-dose CT grand challenge [15], were used in our numerical experiments. Specifically, 2250 2D slices of size 512×512 corresponding to 9 patients were used to train the models, while 128 slices from the remaining one patient were used for evaluation. The projections were simulated in ODL [1] using a parallel-beam geometry with 200 uniformly spaced angular positions of the source, with 400 lines per angle. Subsequently, Gaussian noise with standard deviation $\sigma_e = 2.0$ was added to the projection data to simulate noisy sinograms.

(a) ground-truth   (b) 34.94, 0.88   (c) 35.46, 0.90   (d) ground-truth   (e) 33.84, 0.87   (f) 34.24, 0.89

Figure 3: Effect of refinement: (b) and (e): end-to-end reconstruction $\mathcal{G}_{\phi^*}(\boldsymbol{y}^\delta)$; (c) and (f): the respective refined reconstructions. The PSNR (dB) and SSIM scores are indicated below.

The proposed UAR method is compared with two classical model-based approaches for CT, namely filtered back-projection (FBP) and total variation (TV). The LPD method [3] and U-net-based post-processing [10] of FBP are chosen as two supervised approaches for comparison. The AR approach [14] and its convex variant [18], referred to as adversarial convex regularizer (ACR) , are taken as the competing unsupervised approaches. For LPD and AR, we develop a PyTorch-based implementation based on their publicly available TensorFlow codes[1][2], while for ACR, we use the publicly available PyTorch implementation[3].

The unrolled network $\mathcal{G}_\phi$ has 20 layers, with 5×5 filters in both primal and dual spaces to increase the overall receptive field for sparse-view measurements. The hyper-parameters involved in training the UAR are specified in Algorithm 1. We found that first training a baseline regularizer and a corresponding baseline reconstruction operator helps stabilize the training process. Training the UAR model took approximately 30 hours on an NVIDIA Quadro RTX 6000 GPU (24 GB of memory).

The average performance on the test images in terms of PSNR and SSIM [28] indicates that UAR (with $\lambda = 0.1$) outperforms AR and ACR by 0.3 dB and 2.6 dB, approximately. We would like to emphasize that this gain was found to be consistent across all test images and not just realized on average. With the refinement step, UAR surpasses AR by almost 0.7 dB and becomes on par with U-net post-processing. The end-to-end UAR reconstruction is a couple of orders of magnitude faster than AR, while the reduction in reconstruction time is by a factor of 4 with the refinement. The reconstructions of a representative test image using the competing methods are shown in Fig. 1 for a visual comparison. The effect of λ on the reconstruction of UAR is demonstrated in Fig. 2, which confirms the theoretical results in Section 3.2. The refinement step also visibly improves the reconstruction quality of the end-to-end operator, as shown in Fig. 3.

5 Conclusions and limitations

To the best of our knowledge, this work makes the first attempt to blend end-to-end reconstruction with data-driven regularization via an adversarial learning framework. Our UAR approach retains the fast reconstruction of the former together with provable guarantees of the latter. We rigorously analyze the proposed framework in terms of well-posedness, noise-stability, and the effect of the regularization penalty, and establish a link between the trained reconstruction operator and the corresponding variational objective. We show strong numerical evidence of the efficacy of the UAR approach for CT reconstruction, wherein it achieves the same performance as supervised data-driven post-processing and outperforms competing unsupervised techniques. Our work paves the way to better understand the role of adversarially learned regularizers in solving ill-posed inverse problems, although several important aspects need further investigation. Since the learned regularizer is non-convex, the performance of gradient-descent on the variational objective greatly depends on initialization. This problem is partly addressed by the unrolled reconstruction operator that efficiently computes a better initial point for gradient descent. However, the precise relationship between the end-to-end reconstruction and the variational minimizer for a given measurement vector remains elusive. Moreover, the quality of the reconstruction relies on the expressive power of neural networks and thus suffers from the curse of dimensionality. We believe that addressing such limitations will be important to better understand adversarial regularization methods.

---

[1]LPD: `https://github.com/adler-j/learned_primal_dual`.

[2]AR: `https://github.com/lunz-s/DeepAdverserialRegulariser`.

[3]ACR: `https://github.com/Subhadip-1/data_driven_convex_regularization`.

References

[1] J. Adler, H. Kohr, and O. Öktem. Operator discretization library (odl). *Software available from https://github.com/odlgroup/odl*, 2017.

[2] Jonas Adler and Ozan Öktem. Solving ill-posed inverse problems using iterative deep neural networks. *Inverse Problems*, 33(12), 2009.

[3] Jonas Adler and Ozan Öktem. Learned primal-dual reconstruction. *IEEE transactions on medical imaging*, 37(6):1322–1332, 2018.

[4] Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *Proceedings of the 34th International Conference on Machine Learning*, pages 214–223, 2017.

[5] Simon Arridge, Peter Maass, Ozan Öktem, and Carola-Bibiane Schönlieb. Solving inverse problems using data-driven models. *Acta Numerica*, 28:1–174, 2019.

[6] A. Chambolle and T. Pock. A first-order primal-dual algorithm for convex problems with applications to imaging. *J. Math. Imaging and Vision*, 40(1):120–145, 2010.

[7] Stanley H Chan, Xiran Wang, and Omar A Elgendy. Plug-and-play admm for image restoration: Fixed-point convergence and applications. *IEEE Transactions on Computational Imaging*, 3(1): 84–98, 2016.

[8] M. Cuturi and G. Peyré. Computational Optimal Transport. Arxiv preprint arXiv:1803.00567, 2019. https://arxiv.org/pdf/1803.00567.pdf.

[9] K. Gregor and Y. LeCun. Learning fast approximations of sparse coding. In *Intl. Conf. on Machine Learning*, 2010.

[10] K. H. Jin, M. T. McCann, E. Froustey, and M. Unser. Deep convolutional neural network for inverse problems in imaging. *IEEE Transactions on Image Processing*, 26(9):4509–4522, 2017.

[11] Erich Kobler, Teresa Klatzer, Kerstin Hammernik, and Thomas Pock. Variational networks: connecting variational methods and deep learning. In *German conference on pattern recognition*, pages 281–293. Springer, 2017.

[12] Erich Kobler, Alexander Effland, Karl Kunisch, and Thomas Pock. Total deep variation for linear inverse problems. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 7549–7558, 2020.

[13] Housen Li, Johannes Schwab, Stephan Antholzer, and Markus Haltmeier. NETT: solving inverse problems with deep neural networks. *Inverse Problems*, 36(6), 2020.

[14] Sebastian Lunz, Ozan Öktem, and Carola-Bibiane Schönlieb. Adversarial regularizers in inverse problems. In *Advances in Neural Information Processing Systems*, pages 8507–8516, 2018.

[15] C. McCollough. Tfg-207a-04: Overview of the low dose ct grand challenge. *Medical Physics*, 43(6):3759–3760, 2014.

[16] Tim Meinhardt, Michael Moller, Caner Hazirbas, and Daniel Cremers. Learning proximal operators: Using denoising networks for regularizing inverse imaging problems. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1781–1790, 2017.

[17] V. Monga, Y. Li, and Y. Eldar. Algorithm unrolling: Interpretable, efficient deep learning for signal and image processing. *arXiv preprint arXiv:1912.10557v3*, 2019.

[18] S. Mukherjee, S. Dittmer, Z. Shumaylov, S. Lunz, O. Öktem, and C.-B. Schönlieb. Learned convex regularizers for inverse problems. *arXiv preprint arXiv:2008.02839v2*, 2021.

[19] Changheun Oh, Dongchan Kim, Jun-Young Chung, Yeji Han, and H. Park. Eter-net: End to end mr image reconstruction using recurrent neural network. In *MLMIR@MICCAI*, 2018.

[20] J.-C. Pesquet, A. Repetti, M. Terris, and Y. Wiaux. Learning maximally monotone operators for image recovery. *arXiv preprint arXiv:2012.13247v2*, Apr. 2021.

[21] E. T. Reehorst and P. Schniter. Regularization by denoising: clarifications and new interpretations. *IEEE Transactions on Computational Imaging*, 5(1):52–67, 2019.

[22] Yaniv Romano, Michael Elad, and Peyman Milanfar. The little engine that could: Regularization by denoising (red). *SIAM Journal on Imaging Sciences*, 10(4):1804–1844, 2017.

[23] F. Santambrogio. *Optimal Transport for Applied Mathematicians*. Birkhäuser Basel, 2015.

[24] Otmar Scherzer, Markus Grasmair, Harald Grossauer, Markus Haltmeier, and Frank Lenzen. *Variational methods in imaging*. Springer, 2009.

[25] Y. Sun, B. Wohlberg, and Kamilov U. S. An online plug-and-play algorithm for regularized image reconstruction. *IEEE Transactions on Computational Imaging*, 5(3):395–408, 2019.

[26] Dmitry Ulyanov, Andrea Vedaldi, and Victor Lempitsky. Deep image prior. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 9446–9454, 2018.

[27] C. Villani. *Optimal transport — Old and new*, volume 338 of *Grundlehren der mathematischen Wissenschaften*. Springer Berlin Heidelberg, 2009. doi: 10.1007/978-3-540-71050-9.

[28] Z. Wang, A. C. Bovik, H. R. Sheikh, and E. P. Simoncelli. Image quality assessment: From error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–612, 2004.

[29] Y. Yang, J. Sun, H. Li, and Z. Xu. Deep admm-net for compressive sensing mri. In *Advances in Neural Information Processing Systems*, 2016.

[30] B. Zhu, J. Z. Liu, S. F. Cauley, B. R. Rosen, and M. S. Rosen. Image reconstruction by domain-transform manifold learning. *Nature*, 555:487–492, 2018.